Postal Service Mail.XML 9.0X Technical Specification for Postage Payment and Reporting (eDoc) November 2011 Release

Version 1.0.0

Copyright © 2011 USPS®. All Rights Reserved.

Table of Contents

TABLE OF CONTENTS **2**

DOCUMENT CHANGE HISTORY **14**

1. POSTAL SERVICE MAIL.XML TECHNICAL SPECIFICATION **22**

1.1 PROGRAM OVERVIEW 22
1.1.1 Mail.XML 9.0C Change History *24*
1.1.1 Mail.XML 9.0B Change History *24*
1.2 ABOUT SCHEMA MODULARIZATION 25
1.3 WHAT SCHEMAS COVER ELECTRONIC DOCUMENTATION (EDOC) FUNCTIONALITY? 26
1.4 USPS LIMITATION RULE ON TRANSACTION REQUESTS 26
1.5 RECOMMENDED FILE SIZES FOR OPTIMUM MAIL.XML PERFORMANCE 26
1.6 ROADMAP OF MAIL.XML 27
1.7 PURPOSE 27
1.8 INTENDED AUDIENCE 27
1.9 ABOUT THIS DOCUMENT 27
1.10 HOW TO READ DATA STRUCTURE 28
1.11 ISSUE RESOLUTION 28
1.12 MAIL.XML MESSAGE HIERARCHY 28
1.1.1 FULL-SERVICE & MIXED SERVICE MAILINGS 29
1.1.2 FULL-SERVICE & MIXED SERVICE MAILINGS 32
1.13 WORKFLOWS 35
1.13.1 Non-Periodicals without Full-Service *35*
1.13.1 Periodicals without Full-Service *35*
1.13.1 Non-Periodicals with Full-Service *35*
1.13.1 Periodicals with Full-Service *36*
1.13.1 Combined/ Commingled Mailing - non-Periodicals *36*
1.13.1 Combined/ Commingled Mailing - Periodicals *36*
1.13.1 Copalletized Mailing for Trays on Pallets non-Periodicals *37*
1.13.1 Copalletized Mailing for Bundles on Pallets - Standard Mail *37*
1.13.1 Copalletized Mailing for Bundles on Pallets - Periodicals Mail *37*
1.14 EXCEPTIONS 38

2. *POSTALONE!* – EDOC MAIL.XML MESSAGES **39**

2.1 OVERVIEW 39
2.2 MESSAGE RESPONSE RETRIEVAL REQUEST PROCESSING 39
2.2.1 Fault and Fault Recovery Messages *39*
2.3 ADDITIONAL RULES/CONSTRAINTS 39
2.3.1 Container Status Messages *39*
2.3.1 ContainerStatusQueryResponse Error Codes / Return Values *40*
2.4 ERROR CODES/RETURN VALUES 40
2.5 ADDITIONAL CONSTRAINTS 103
2.6 *POSTALONE!* WSDL INFORMATION 103
2.7 PERMIT INFORMATION 104

3. MAIL.XML VERSION 9.0B EDOC AND MISCELLANEOUS MESSAGES **110**

3.1 BEGINCOMBINEDMAILINGREQUEST 112
3.1.1 BeginCombinedMailingRequest Data Structure *113*
3.2 BEGINCOMBINEDMAILINGRESPONSE 113
3.2.1 BeginCombinedMailingResponse Data Structure *114*

Copyright © 2011 USPS®. All Rights Reserved.

3.3 BUNDLEDETAILCANCELREQUEST 115
3.3.1 BundleDetailCancelRequest Data Structure 115
3.4 BUNDLEDETAILCANCELRESPONSE 117
3.4.1 BundleDetailCancelResponse Data Structure 117
3.5 BUNDLEDETAILCREATEREQUEST 118
3.5.1 BundleDetailCancelRequest Data Structure 118
3.6 BUNDLEDETAILCREATERESPONSE 119
3.6.1 BundleDetailCreateResponse Data Structure 120
3.7 CLOSEMAILINGGROUPREQUEST 122
3.7.1 CloseMailingGroupRequest 122
3.8 CLOSEMAILINGGROUPRESPONSE 123
3.8.1 CloseMailingGroupResponse Data Structure 123
3.9 CONSOLIDATEDPERIODICALSTATEMENTCREATEREQUEST 124
3.9.1 ConsolidatedPeriodicalStatementCreateRequest Data Structure 127
3.10 CONSOLIDATEDPERIODICALSTATEMENTCREATERESPONSE 129
3.10.1 ConsolidatedPeriodicalStatementCreateResponse 130
3.11 CONTAINERBUNDLEREPORTCANCELREQUEST 131
3.11.1 ContainerBundleReportCancelRequest Data Structure 131
3.12 CONTAINERBUNDLEREPORTCANCELRESPONSE 132
3.12.1 ContainerBundleReportCancelResponse 132
3.13 CONTAINERBUNDLEREPORTCREATEREQUEST 133
3.13.1 ContainerBundleReportCreateRequest 134
3.14 CONTAINERBUNDLEREPORTCREATERESPONSE 140
3.14.1 ContainerBundleReportCreateResponse 140
3.15 CONTAINERBUNDLEREPORTQUERYREQUEST 142
3.15.1 ContainerBundleReportQueryRequest 142
3.16 CONTAINERBUNDLEREPORTQUERYRESPONSE 143
3.16.1 ContainerBundleReportQueryResponse 143
3.17 CONTAINERSTATUSQUERYREQUEST 149
3.17.1 ContainerStatusQueryRequest 149
3.18 CONTAINERSTATUSQUERYRESPONSE 150
3.18.1 ContainerStatusQueryResponse 151
3.19 CUSTOMERMAILREPORTCREATEREQUEST 153
3.19.1 CustomerMailReportCreateRequest 154
3.20 CUSTOMERMAILREPORTCREATERESPONSE 155
3.20.1 CustomerMailReportCreateResponse 155
3.21 ENDCOMBINEDMAILINGREQUEST 155
3.21.1 EndCombinedMailingRequest Data Structure 157
3.22 ENDCOMBINEDMAILINGRESPONSE 157
3.22.1 EndCombinedMailingResponse Data Structure 158
3.23 CONTAINERUPDATEREQUEST 158
3.23.1 ContainerUpdateRequest 160
3.24 CONTAINERUPDATERESPONSE 170
3.24.1 ContainerUpdateResponse 171
3.25 MAILINGGROUPQUERYREQUEST 173
3.25.1 MailingGroupQueryRequest 173
3.26 MAILINGGROUPQUERYRESPONSE 173
3.26.1 MailingGroupQueryResponse Data Structure 173
3.27 MAILPIECECANCELREQUEST 175
3.27.1 MailPieceCancelRequest 175
3.28 MAILPIECECANCELRESPONSE 185
3.28.1 MailPieceCancelResponse 185
3.29 MAILPIECECREATEREQUEST 186
3.29.1 MailPieceCreateRequest 187

Copyright © 2011 USPS®. All Rights Reserved.

3.30 MAILPIECECREATERESPONSE 200
3.30.1 MailPieceCreateResponse 200
3.31 MAILPIECEUPDATEREQUEST 201
3.31.1 MailPieceUpdateRequest 201
3.32 MAILPIECEUPDATERESPONSE 213
3.32.1 MailPieceUpdateResponse 214
3.33 OPENMAILINGGROUPREQUEST 215
3.33.1 OpenMailingGroupRequest 215
3.34 OPENMAILINGGROUPRESPONSE 217
3.34.1 OpenMailingGroupResponse 217
3.35 ORIGINALCONTAINERLINKAGECANCELREQUEST 218
3.35.1 OriginalContainerLinkageCancelRequest 219
3.36 ORIGINALCONTAINERLINKAGECANCELRESPONSE 220
3.36.1 OriginalContainerLinkageCancelResponse 220
3.37 ORIGINALCONTAINERLINKAGECREATEREQUEST 222
3.37.1 OriginalContainerLinkageCreateRequest 223
3.38 ORIGINALCONTAINERLINKAGECREATERESPONSE 223
3.38.1 OriginalContainerLinkageCreateResponse 224
3.39 PAYMENTMESSAGEQUERYREQUEST 225
3.39.1 PaymentMessageQueryRequest Data Structure 225
3.40 PAYMENTMESSAGEQUERYRESPONSE 226
3.40.1 PaymentMessageQueryResponse Data Structure 226
3.41 PERIODICALSTATEMENTCREATEREQUEST 227
3.41.1 PeriodicalStatementCreateRequest 229
3.42 PERIODICALSTATEMENTCREATERESPONSE 241
3.42.1 PeriodicalStatementCreateResponse Data Structure 242
3.43 PERIODICALSTATEMENTQUERYREQUEST 243
3.43.1 PeriodicalStatementQueryRequest Data Structure 243
3.44 POSTAGESTATEMENTCREATEREQUEST 244
3.44.1 PostageStatementCreateRequest Data Structure 247
3.45 PERIODICALSTATEMENTQUERYRESPONSE 247
3.45.1 PeriodicalStatementQueryResponse Data Structure 248
3.46 POSTAGEADJUSTMENTCREATEREQUEST 257
3.46.1 PostageAdjustmentCreateRequest Data Structure 258
3.47 POSTAGEADJUSTMENTCREATERESPONSE 260
3.47.1 PostageAdjustmentCreateResponse Data Structure 260
3.48 POSTAGESTATEMENTCANCELREQUEST 263
3.48.1 PostageStatementCancelRequest Data Structure 263
3.49 POSTAGESTATEMENTCANCELRESPONSE 264
3.49.1 PostageStatementCancelResponse Data Structure 264
3.50 POSTAGESTATEMENTCREATERESPONSE 265
3.50.1 PostageStatementCreateResponse Data Structure 265
3.51 POSTAGESTATEMENTQUERYRESPONSE 267
3.51.1 PostageStatementQueryResponse Data Structure 267
3.52 POSTAGESTATEMENTQUERYRESPONSE 268
3.52.1 PostageStatementQueryResponse Data Structure 269
3.53 POSTAGESTATEMENTSTATUSQUERYREQUEST 281
3.53.1 PostageStatementStatusQueryRequest data Structure 282
3.54 POSTAGESTATEMENTSTATUSQUERYRESPONSE 282
3.54.1 PostageStatementStatusQueryResponse Data Structure 282
3.55 QUALIFICATIONREPORTCREATEREQUEST 284
3.55.1 QualificationReportCreateRequest Data Structure 285
3.56 QUALIFICATIONREPORTCREATERESPONSE 287
3.56.1 QualificationReportCreateResponse Data Structure 287

Copyright © 2011 USPS®. All Rights Reserved.

3.57 QUALIFICATIONREPORTQUERYREQUEST 289
3.57.1 QualificationReportQueryRequest Data Structure 289
3.58 QUALIFICATIONREPORTQUERYRESPONSE 291
3.58.1 QualificationReportQueryResponse Data Structure 291
3.59 RECONCILIATIONREPORTQUERYREQUEST 293
3.59.1 ReconciliationReportQueryRequest Data Structure 293
3.60 RECONCILIATIONREPORTQUERYRESPONSE 294
3.60.1 ReconciliationReportQueryResponse Data Structure 294
3.61 SIBLINGCONTAINERCANCELREQUEST 298
3.61.1 SiblingContainerCancelRequest Data Structure 298
3.62 SIBLINGCONTAINERCANCELRESPONSE 299
3.62.1 SiblingContainerCancelResponse Data Structure 299
3.63 SIBLINGCONTAINERCREATEREQUEST 300
3.63.1 SiblingContainerCreateRequest Data Structure 300
3.64 SIBLINGCONTAINERCREATERESPONSE 303
3.64.1 SiblingContainerCreateResponse Data Structure 303
3.65 SUMMARYZIPDESTINATIONREPORTCREATEREQUEST 304
3.65.1 SummaryZipDestinationReportCreateRequest Data Structure 304
3.66 SUMMARYZIPDESTINATIONREPORTCREATERESPONSE 306
3.66.1 SummaryZipDestinationReportCreateResponse Data Structure 306

4. MAIL.XML VERSION 9.0C EDOC AND MISCELLANEOUS MESSAGES 308

4.1.1 MobileBarcode 308
4.1.1 eInduction Indicator 308
4.1.1 Ready for SASP Indicator 308
4.1.1 ContainerLevelType 308
4.1.1 ContainerInfoData 309
4.2 BEGINCOMBINEDMAILINGREQUEST 310
4.2.1 BeginCombinedMailingResponse Data Structure 311
4.3 BUNDLEDETAILCANCELREQUEST 313
4.3.1 BundleDetailCancelRequest Data Structure 313
4.4 BUNDLEDETAILCANCELRESPONSE 315
4.4.1 BundleDetailCancelResponse Data Structure 315
4.5 BUNDLEDETAILCREATEREQUEST 316
4.5.1 BundleDetailCreateRequest Data Structure 316
4.6 BUNDLEDETAILCREATERESPONSE 318
4.6.1 BundleDetailCreateResponse Data Structure 318
4.7 CLOSEMAILINGGROUPREQUEST 320
4.7.1 CloseMailingGroupRequest Data Structure 321
4.8 CLOSEMAILINGGROUPRESPONSE 321
4.8.1 CloseMailingGroupResponse Data Structure 322
4.9 CONSOLIDATEDPERIODICALSTATEMENTCREATEREQUEST 323
4.9.1 ConsolidatedPeriodicalStatementCreateRequest Data Structure 325
4.10 CONSOLIDATEDPERIODICALSTATEMENTCREATERESPONSE 327
4.10.1 ConsolidatedPeriodicalStatementCreateResponse Data Structure 328
4.11 CONTAINERBUNDLEREPORTCANCELREQUEST 329
4.11.1 ContainerBundleReportCancelRequest Data Structure 329
4.12 CONTAINERBUNDLEREPORTCANCELRESPONSE 330
4.12.1 ContainerBundleReportCancelResponse Data Structure 330
4.13 CONTAINERBUNDLEREPORTCREATEREQUEST 332
4.13.1 ContainerBundleReportCreateRequest Data Structure 332
4.14 CONTAINERBUNDLEREPORTCREATERESPONSE 338
4.14.1 ContainerBundleReportCreateResponse Data Structure 338
4.15 CONTAINERBUNDLEREPORTQUERYREQUEST 340

Copyright © 2011 USPS®. All Rights Reserved.

4.15.1 ContainerBundleReportQueryRequest Data Structure ... 340
4.16 CONTAINERBUNDLEREPORTQUERYRESPONSE ... 341
4.16.1 ContainerBundleReportQueryResponse Data Structure ... 341
4.17 CONTAINERSTATUSQUERYREQUEST ... 347
4.17.1 ContainerStatusQueryRequest Data Structure ... 347
4.18 CONTAINERSTATUSQUERYRESPONSE ... 349
4.18.1 ContainerStatusQueryResponse Data Structure ... 349
4.19 CUSTOMERMAILREPORTCREATEREQUEST ... 351
4.19.1 CustomerMailReportCreateRequest Data Structure ... 352
4.20 CUSTOMERMAILREPORTCREATERESPONSE ... 353
4.20.1 CustomerMailReportCreateResponse Data Structure ... 353
4.21 ENDCOMBINEDMAILINGREQUEST ... 354
4.21.1 EndCombinedMailingRequest Data Structure ... 355
4.22 ENDCOMBINEDMAILINGRESPONSE ... 355
4.22.1 EndCombinedMailingResponse Data Structure ... 356
4.23 CONTAINERUPDATEREQUEST ... 356
4.23.1 ContainerUpdateRequest Data Structure ... 358
4.24 CONTAINERUPDATERESPONSE ... 368
4.24.1 ContainerUpdateResponse Data Structure ... 369
4.25 MAILINGGROUPQUERYREQUEST ... 371
4.25.1 MailingGroupQueryRequest Data Structure ... 371
4.26 MAILINGGROUPQUERYRESPONSE ... 371
4.26.1 MailingGroupQueryResponse Data Structure ... 371
4.27 MAILPIECECANCELREQUEST ... 373
4.27.1 MailPieceCancelRequest Data Structure ... 373
4.28 MAILPIECECANCELRESPONSE ... 383
4.28.1 MailPieceCancelResponse Data Structure ... 383
4.29 MAILPIECECREATEREQUEST ... 384
4.29.1 MailPieceCreateRequest Data Structure ... 385
4.30 MAILPIECECREATERESPONSE ... 397
4.30.1 MailPieceCreateResponse Data Structure ... 398
4.31 MAILPIECEUPDATEREQUEST ... 399
4.31.1 MailPieceUpdateRequest Data Structure ... 399
4.32 MAILPIECEUPDATERESPONSE ... 411
4.32.1 MailPieceUpdateResponse Data Structure ... 412
4.33 OPENMAILINGGROUPREQUEST ... 413
4.33.1 OpenMailingGroupRequest Data Structure ... 413
4.34 OPENMAILINGGROUPRESPONSE ... 414
4.34.1 OpenMailingGroupResponse Data Structure ... 415
4.35 ORIGINALCONTAINERLINKAGECANCELREQUEST ... 416
4.35.1 OriginalContainerLinkageCancelRequest Data Structure ... 417
4.36 ORIGINALCONTAINERLINKAGECANCELRESPONSE ... 417
4.36.1 OriginalContainerLinkageCancelResponse Data Structure ... 418
4.37 ORIGINALCONTAINERLINKAGECREATEREQUEST ... 419
4.37.1 OriginalContainerLinkageCreateRequest Data Structure ... 420
4.38 ORIGINALCONTAINERLINKAGECREATERESPONSE ... 421
4.38.1 OriginalContainerLinkageCreateResponse Data Structure ... 421
4.39 PAYMENTMESSAGEQUERYREQUEST ... 423
4.39.1 PaymentMessageQueryRequest Data Structure ... 423
4.40 PAYMENTMESSAGEQUERYRESPONSE ... 423
4.40.1 PaymentMessageQueryResponse Data Structure ... 424
4.41 PERIODICALSTATEMENTCREATEREQUEST ... 424
4.41.1 PeriodicalStatementCreateRequest Data Structure ... 427
4.42 PERIODICALSTATEMENTCREATERESPONSE ... 439

Copyright © 2011 USPS®. All Rights Reserved.

4.42.1 PeriodicalStatementCreateResponse Data Structure ... 439
4.43 PERIODICALSTATEMENTQUERYREQUEST ... 441
4.43.1 PeriodicalStatementQueryRequest Data Structure ... 441
4.44 POSTAGESTATEMENTCREATEREQUEST ... 442
4.44.1 PostageStatementCreateRequest Data Structure ... 444
4.45 PERIODICALSTATEMENTQUERYRESPONSE ... 445
4.45.1 PeriodicalStatementQueryResponse Data Structure ... 445
4.46 POSTAGEADJUSTMENTCREATEREQUEST ... 455
4.46.1 PostageAdjustmentCreateRequest Data Structure ... 455
4.47 POSTAGEADJUSTMENTCREATERESPONSE ... 458
4.47.1 PostageAdjustmentCreateResponse Data Structure ... 458
4.48 POSTAGESTATEMENTCANCELREQUEST ... 461
4.48.1 PostageStatementCancelRequest Data Structure ... 461
4.49 POSTAGESTATEMENTCANCELRESPONSE ... 461
4.49.1 PostageStatementCancelResponse Data Structure ... 462
4.50 POSTAGESTATEMENTCREATERESPONSE ... 463
4.50.1 PostageStatementCreateResponse Data Structure ... 463
4.51 POSTAGESTATEMENTQUERYRESPONSE ... 465
4.51.1 PostageStatementQueryResponse Data Structure ... 465
4.52 POSTAGESTATEMENTQUERYRESPONSE ... 466
4.52.1 PostageStatementQueryResponse Data Structure ... 467
4.53 POSTAGESTATEMENTSTATUSQUERYREQUEST ... 479
4.53.1 PostageStatementStatusQueryRequest Data Structure ... 479
4.54 POSTAGESTATEMENTSTATUSQUERYRESPONSE ... 480
4.54.1 PostageStatementStatusQueryResponse Data Structure ... 480
4.55 QUALIFICATIONREPORTCREATEREQUEST ... 482
4.55.1 QualificationReportCreateRequest Data Structure ... 483
4.56 QUALIFICATIONREPORTCREATERESPONSE ... 484
4.56.1 QualificationReportCreateResponse Data Structure ... 484
4.57 QUALIFICATIONREPORTQUERYREQUEST ... 486
4.57.1 QualificationReportQueryRequest Data Structure ... 487
4.58 QUALIFICATIONREPORTQUERYRESPONSE ... 488
4.58.1 QualificationReportQueryResponse Data Structure ... 488
4.59 RECONCILIATIONREPORTQUERYREQUEST ... 490
4.59.1 ReconciliationReportQueryRequest Data Structure ... 490
4.60 RECONCILIATIONREPORTQUERYRESPONSE ... 491
4.60.1 ReconciliationReportQueryResponse Data Structure ... 491
4.61 SIBLINGCONTAINERCANCELREQUEST ... 495
4.61.1 SiblingContainerCancelRequest Data Structure ... 495
4.62 SIBLINGCONTAINERCANCELRESPONSE ... 496
4.62.1 SiblingContainerCancelResponse Data Structure ... 496
4.63 SIBLINGCONTAINERCREATEREQUEST ... 497
4.63.1 SiblingContainerCreateRequest Data Structure ... 498
4.64 SIBLINGCONTAINERCREATERESPONSE ... 500
4.64.1 SiblingContainerCreateResponse Data Structure ... 500
4.65 SUMMARYZIPDESTINATIONREPORTCREATEREQUEST ... 501
4.65.1 SummaryZipDestinationReportCreateRequest Data Structure ... 501
4.66 SUMMARYZIPDESTINATIONREPORTCREATERESPONSE ... 503
4.66.1 SummaryZipDestinationReportCreateResponse Data Structure ... 504

5. ADDITIONAL RULES/CONSTRAINTS ... 505

5.1.1 Container Status Messages ... 505
5.1.1 ContainerStatusQueryResponse Error Codes / Return Values ... 505
1.2 ERROR CODES/RETURN VALUES ... 505

Copyright © 2011 USPS®. All Rights Reserved.

5.2 ADDITIONAL CONSTRAINTS 567
5.3 *POSTALONE!* WSDL INFORMATION 567
5.4 PERMIT INFORMATION 568

6. APPENDIX A – MAIL.XML 9.0B COMPLEX AND ATTRIBUTE DATA TYPES DATA STRUCTURE 573

6.1 COMPLEXTYPE: ADDRESSTYPE 573
6.2 COMPLEXTYPE: CERTIFICATIONDATATYPE 574
6.3 COMPLEXTYPE: COMMONCONTACTTYPE 574
6.4 COMPLEXTYPE: CONTACTIDTYPE 575
6.5 COMPLEXTYPE: CONTAINERCOUNTTYPE 575
6.6 COMPLEXTYPE: CONTAINERPOSTAGETYPE 576
6.7 COMPLEXTYPE: DOCUMENTVERSIONDATA 577
6.8 COMPLEXTYPE: FULLCONTAINERIDTYPE 577
6.9 COMPLEXTYPE: GPSCOORDINATES 578
6.10 COMPLEXTYPE: INTELLIGENTMAILBARCODETYPE 579
6.11 COMPLEXTYPE: LARGETRANSACTIONDIVIDERGROUPTYPE 580
6.12 COMPLEXTYPE: LINKAGETYPE 580
6.13 COMPLEXTYPE: LINKINGCONTAINERIDTYPE 581
6.14 COMPLEXTYPE: MAILDATCONTAINERIDTYPE 581
6.15 COMPLEXTYPE: MAILERDATAREQUESTTYPE 582
6.16 COMPLEXTYPE: MAILERDATATYPE 583
6.17 COMPLEXTYPE: MAILXMLCONTAINERIDTYPE 584
6.18 ATTRIBUTEGROUP: MAILXMLMSGRESPONSEHEADERINFO 584
6.19 ATTRIBUTEGROUP: MAILXMLPOSTAGESTATEMENTREQUESTHEADERINFO 585
6.20 COMPLEXTYPE: MIDTYPE 585
6.21 COMPLEXTYPE: PARTICIPANTIDTYPE 586
6.22 COMPLEXTYPE: PERMITPUBLICATIONDATATYPE 586
6.23 COMPLEXTYPE: RETURNINFO 587
6.24 COMPLEXTYPE: SUBMITTINGSOFTWARETYPE 588

7. APPENDIX B - MAIL.XML 9.0C COMPLEX AND ATTRIBUTE DATA TYPES DATA STRUCTURE 590

8. APPENDIX C – MAIL.XML 9.0B/9.0C SIMPLE TYPES DATA STRUCTURE 591

8.1 SIMPLETYPE: ACTIONCODETYPE 591
8.2 SIMPLETYPE: ADDRESSCORRECTIONMOVETYPE 591
8.3 SIMPLETYPE: ADDITIONALINHOMERANGETYPE 591
8.4 SIMPLETYPE: ADJUSTMENTSTATUSTYPE 592
8.5 SIMPLETYPE: ADJUSTMENTTYPE 592
8.6 SIMPLETYPE: AGENCYCOSTCODETYPE 592
8.7 SIMPLETYPE: APPTMETHODTYPE 592
8.8 SIMPLETYPE: APPTSTATETYPE 592
8.9 SIMPLETYPE: APPTSTATUSTYPE 593
8.10 SIMPLETYPE: APPTTYPETYPE 593
8.11 SIMPLETYPE: BARCODERATETYPE 593
8.12 SIMPLETYPE: BILLREASONCODETYPE 593
8.13 SIMPLETYPE: BUNDLEDETAILLEVELTYPE 593
8.14 SIMPLETYPE: BUNDLELEVELTYPE 594
8.15 SIMPLETYPE: BUNDLERECORDSTATUSTYPE 594
8.16 SIMPLETYPE: BUNDLESTATUSTYPE 594
8.17 SIMPLETYPE: CHARGEABLEBUNDLELEVELTYPE 594
8.18 SIMPLETYPE: CHARGEABLECONTAINERTYPE 595
8.19 SIMPLETYPE: CHARGEABLECONTAINERLEVELTYPE 595

Copyright © 2011 USPS®. All Rights Reserved.

8.20 SIMPLETYPE: CHARGEABLEENTRYLEVELTYPE 595
8.21 SIMPLETYPE: CLASSNOTIFICATIONTYPE 595
8.22 SIMPLETYPE: CLOSEOUTIRREGULARITIESTYPE 595
8.23 SIMPLETYPE: CLOSEOUTRESOLUTIONTYPE 596
8.24 SIMPLETYPE: COMMUNICATIONROLETYPE 596
8.25 SIMPLETYPE: COMPONENTIDTYPE 596
8.26 SIMPLETYPE: COMPONENTWEIGHTTYPE 596
8.27 SIMPLETYPE: COMPONENTWEIGHTSOURCETYPE 597
8.28 SIMPLETYPE: COMPONENTWEIGHTSTATUSTYPE 597
8.29 SIMPLETYPE: CONSIGNEECONTENTIDTYPE 597
8.30 SIMPLETYPE: CONTAINERBUNDLESTATUSTYPE 597
8.31 SIMPLETYPE: CONTAINER24CHARACTERBARCODETYPE 597
8.32 SIMPLETYPE: CONTAINERACCEPTANCEDATETYPE 597
8.33 SIMPLETYPE: CCCLEVELTYPE 598
8.34 SIMPLETYPE: CONTAINERGROUPINGDESCRIPTIONTYPE 598
8.35 SIMPLETYPE: CONTAINERGROSSWEIGHTTYPE 598
8.36 SIMPLETYPE: CONTAINERHEIGHTTYPE 598
8.37 SIMPLETYPE: CONTAINERLEVELTYPE 598
8.38 SIMPLETYPE: CONTAINERPICKUPDATETYPE 602
8.39 SIMPLETYPE: CONTAINERPICKUPTIMETYPE 602
8.40 SIMPLETYPE: CONTAINERSHIPDATETYPE 602
8.41 SIMPLETYPE: CONTAINERSHIPTIMETYPE 602
8.42 SIMPLETYPE: CONTACTTYPE 602
8.43 SIMPLETYPE: CONTAINERTYPE 603
8.44 SIMPLETYPE: CONTAINERSTATUSTYPE 603
8.45 SIMPLETYPE: CONTAINERHEIGHTSOURCETYPE 603
8.46 SIMPLETYPE: CPTPERIODICALADPERCENTAGETYPE 603
8.47 SIMPLETYPE: CPTPERIODICALADPERCENTAGEBASISTYPE 603
8.48 SIMPLETYPE: CPTPERIODICALADPERCENTAGESTATUSTYPE 604
8.49 SIMPLETYPE: CQTDATABASEIDTYPE 604
8.50 SIMPLETYPE: CREDITDEBITINDICATOR 604
8.51 SIMPLETYPE: CRIDTYPE 604
8.52 SIMPLETYPE: CRIDSTATUSTYPE 604
8.53 SIMPLETYPE: CSATEMPLATETYPE 604
8.54 SIMPLETYPE: CSASTATUSTYPE 605
8.55 SIMPLETYPE: DATABASECONTAINERIDTYPE 605
8.56 SIMPLETYPE: DAYFREQUENCYTYPE 605
8.57 SIMPLETYPE: DAYSOFWEEKTYPE 605
8.58 SIMPLETYPE: DAYSTYPE 606
8.59 SIMPLETYPE: DEC03-2 606
8.60 SIMPLETYPE: DEC04-3 606
8.61 SIMPLETYPE: DEC18-6 606
8.62 SIMPLETYPE: DEC10-4 606
8.63 SIMPLETYPE: DEC18-8 606
8.64 SIMPLETYPE: DELIVERABILITYCODETYPE 606
8.65 SIMPLETYPE: ELECTRONICFILETYPE 607
8.66 SIMPLETYPE: EMAILTYPE 607
8.67 SIMPLETYPE: EMD8125ASNBARCODETYPE 607
8.68 SIMPLETYPE: ENCLOSEDBYTYPE 607
8.69 SIMPLETYPE: ENTRYDISCOUNTTYPE 607
8.70 SIMPLETYPE: ENTRYFACILITYTYPE 608
8.71 SIMPLETYPE: ENTRYPOINTEDPOSTALCODETYPE 608
8.72 SIMPLETYPE: ENTRYPOINTEDFACILITYTYPETYPE 608
8.73 SIMPLETYPE: ENTRYPOINTADLOCALEKEYTYPE 608
8.74 SIMPLETYPE: ENTRYPOINTADPOSTALCODETYPE 608

Copyright © 2011 USPS®. All Rights Reserved.

8.75 SIMPLETYPE: ES2 608
8.76 SIMPLETYPE: ES3 609
8.77 SIMPLETYPE: ES4 609
8.78 SIMPLETYPE: ES5 609
8.79 SIMPLETYPE: ES31 609
8.80 SIMPLETYPE: EXEMPTIONCODETYPE 609
8.81 SIMPLETYPE: FASTCONTENTIDTYPE 609
8.82 SIMPLETYPE: FASTSCHEDULERIDTYPE 610
8.83 SIMPLETYPE: FEENOTIFICATIONTYPE 610
8.84 SIMPLETYPE: FLATRATEINDICATORTYPE 610
8.85 SIMPLETYPE: FORMTYPE 610
8.86 SIMPLETYPE: FULLSERVICECOMPLIANCEINDICATORTYPE 610
8.87 SIMPLETYPE: FSPITYPE 610
8.88 SIMPLETYPE: GPSSYSTEMTYPE 611
8.89 SIMPLETYPE: IDTYPE 611
8.90 SIMPLETYPE: IMBTYPE 611
8.91 SIMPLETYPE: IMCBTYPE 611
8.92 SIMPLETYPE: IMPBTYPE 611
8.93 SIMPLETYPE: IMBARCODEIDTYPE 611
8.94 SIMPLETYPE: IMBSERIALNUMBER6TYPE 612
8.95 SIMPLETYPE: IMBSERIALNUMBER9TYPE 612
8.96 SIMPLETYPE: IMBUPPERSERIALIZATIONTYPE 612
8.97 SIMPLETYPE: IMBLOWERSERIALIZATIONTYPE 612
8.98 SIMPLETYPE: IMTBTYPE 612
8.99 SIMPLETYPE: INCENTIVETYPETYPE 612
8.100 SIMPLETYPE: INCLUDEDINOTHERDOCTYPE 612
8.101 SIMPLETYPE: INOUTCOUNTYINDICATORTYPE 613
8.102 SIMPLETYPE: INCOUNTYOUTCOUNTYINDICATORTYPE 613
8.103 SIMPLETYPE: INT04 613
8.104 SIMPLETYPE: JOBIDTYPE 613
8.105 SIMPLETYPE: LOCALEKEYTYPE 613
8.106 SIMPLETYPE: INDUCTIONSTATUSTYPE 613
8.107 SIMPLETYPE: LOGICALPHYSICALBUNDLEINDICATORTYPE 614
8.108 SIMPLETYPE: LOGICALPHYSICALCONTAINERINDICATORTYPE 614
8.109 SIMPLETYPE: MAILAGREEMENTTYPETYPE 614
8.110 SIMPLETYPE: MAILCLASSTYPE 614
8.111 SIMPLETYPE: MAILDATCONTAINERSTATUSTYPE 614
8.112 SIMPLETYPE: MAILDATRECORDSTATUS 614
8.113 SIMPLETYPE: MAILERID6TYPE 615
8.114 SIMPLETYPE: MAILERID9TYPE 615
8.115 SIMPLETYPE: MAILISSUETYPE 615
8.116 SIMPLETYPE: MAILXMLCONTAINERTYPE 615
8.117 SIMPLETYPE: MAILXMLPRESENTATIONCATEGORYTYPE 616
8.118 SIMPLETYPE: MAILXMLSTATUSTYPE 616
8.119 SIMPLETYPE: MIDSTATUSTYPE 616
8.120 SIMPLETYPE: METEREDAFFIXEDMETHODTYPE 616
8.121 SIMPLETYPE: MONTHTYPE 616
8.122 SIMPLETYPE: MOVEUPDATEMETHODTYPE 617
8.123 SIMPLETYPE: MOVEUPDATETYPE 617
8.124 SIMPLETYPE: MPUIDTYPE 617
8.125 SIMPLETYPE: NS02 617
8.126 SIMPLETYPE: NS03 617
8.127 SIMPLETYPE: NS04 618
8.128 SIMPLETYPE: NS05 618
8.129 SIMPLETYPE: NS06 618

Copyright © 2011 USPS®. All Rights Reserved.

8.130 SIMPLETYPE: NS08 618
8.131 SIMPLETYPE: NS09 618
8.132 SIMPLETYPE: NS10 618
8.133 SIMPLETYPE: NS11 618
8.134 SIMPLETYPE: NS13 619
8.135 SIMPLETYPE: NS22 619
8.136 SIMPLETYPE: N01 619
8.137 SIMPLETYPE: N02 619
8.138 SIMPLETYPE: N03 619
8.139 SIMPLETYPE: N04 619
8.140 SIMPLETYPE: N05 619
8.141 SIMPLETYPE: N06 620
8.142 SIMPLETYPE: NEWADDRESSTYPE 620
8.143 SIMPLETYPE: ADDRESSTYPE 620
8.144 SIMPLETYPE: ONEPASSPLANNEDORACTUALFLAGTYPE 620
8.145 SIMPLETYPE: PACKAGEIDTYPE 620
8.146 SIMPLETYPE: PACKAGESERVICESTYPE 620
8.147 SIMPLETYPE: PACKAGINGMETHODTYPE 621
8.148 SIMPLETYPE: PALLETHANDLINGUNITTYPE 621
8.149 SIMPLETYPE: PALLETTYPE 621
8.150 SIMPLETYPE: PARENTCONTAINERREFIDTYPE 621
8.151 SIMPLETYPE: PERCENTAGETYPE 622
8.152 SIMPLETYPE: PERIODICALPRICETYPE 622
8.153 SIMPLETYPE: PERIODICALSTATEMENTTYPE 622
8.154 SIMPLETYPE: PERMITTYPETYPE 622
8.155 SIMPLETYPE: PHONENUMBERTYPE 623
8.156 SIMPLETYPE: PICKUPORDELIVERYTYPE 623
8.157 SIMPLETYPE: PLANETCODETYPE 623
8.158 SIMPLETYPE: POSTAGEGROUPINGIDTYPE 623
8.159 SIMPLETYPE: POSTAGEPAYMENTMETHODTYPE 623
8.160 SIMPLETYPE: POSTAGESTATEMENTLINENUMBER1TYPE 623
8.161 SIMPLETYPE: POSTAGESTATEMENTLINENUMBER2TYPE 624
8.162 SIMPLETYPE: POSTAGESTATEMENTLINENUMBER3TYPE 625
8.163 SIMPLETYPE: POSTAGESTATEMENTSTATETYPE 625
8.164 SIMPLETYPE: POSTAGESTATEMENTSTATUSTYPE 625
8.165 SIMPLETYPE: PRICETYPE 626
8.166 SIMPLETYPE: PRIMARYSECONDARYINDICATORTYPE 626
8.167 SIMPLETYPE: PROCESSINGCATEGORYTYPE 626
8.168 SIMPLETYPE: PROCESSINGCODETYPE 626
8.169 SIMPLETYPE: PVDSCONTAINERTYPE 627
8.170 SIMPLETYPE: PVDSCONTAINERSUBTYPE 627
8.171 SIMPLETYPE: QUALIFICATIONREPORTCLASSTYPE 627
8.172 SIMPLETYPE: RATECATEGORYTYPE 627
8.173 SIMPLETYPE: RATELEVELTYPE 629
8.174 SIMPLETYPE: RATELEVELINDICATORTYPE 629
8.175 SIMPLETYPE: RATETYPE 629
8.176 SIMPLETYPE: REASONCODETYPE 630
8.177 SIMPLETYPE: RECIPIENTTYPE 631
8.178 SIMPLETYPE: RECURRINGSTATUSTYPE 631
8.179 SIMPLETYPE: RESERVATIONNUMBERTYPE 631
8.180 SIMPLETYPE: ROLETYPE 631
8.181 SIMPLETYPE: RESPONSIBLETRANSPORTATIONPARTYTYPE 632
8.182 SIMPLETYPE: ROUTINGZIPCODETYPE 633
8.183 SIMPLETYPE: S01 633
8.184 SIMPLETYPE: S02 633

Copyright © 2011 USPS®. All Rights Reserved.

8.185 SIMPLETYPE: S03 633
8.186 SIMPLETYPE: S04 633
8.187 SIMPLETYPE: S05 633
8.188 SIMPLETYPE: S06 634
8.189 SIMPLETYPE: S07 634
8.190 SIMPLETYPE: S08 634
8.191 SIMPLETYPE: S09 634
8.192 SIMPLETYPE: S10 634
8.193 SIMPLETYPE: S11 635
8.194 SIMPLETYPE: S12 635
8.195 SIMPLETYPE: S15 635
8.196 SIMPLETYPE: S16 635
8.197 SIMPLETYPE: S18 635
8.198 SIMPLETYPE: S20 635
8.199 SIMPLETYPE: S22 636
8.200 SIMPLETYPE: S25 636
8.201 SIMPLETYPE: S28 636
8.202 SIMPLETYPE: S30 636
8.203 SIMPLETYPE: S31 636
8.204 SIMPLETYPE: S37 637
8.205 SIMPLETYPE: S40 637
8.206 SIMPLETYPE: S45 637
8.207 SIMPLETYPE: S50 637
8.208 SIMPLETYPE: S60 637
8.209 SIMPLETYPE: S64 637
8.210 SIMPLETYPE: S66 638
8.211 SIMPLETYPE: S72 638
8.212 SIMPLETYPE: S80 638
8.213 SIMPLETYPE: S255 638
8.214 SIMPLETYPE: S256 638
8.215 SIMPLETYPE: S260 639
8.216 SIMPLETYPE: SACKINGBASISTYPE 639
8.217 SIMPLETYPE: SCHEDULEDINDUCTIONDATETYPE 639
8.218 SIMPLETYPE: SCHEDULEDINDUCTIONTIMETYPE 639
8.219 SIMPLETYPE: SCHEDULEDINHOMEDATETYPE 639
8.220 SIMPLETYPE: SEGMENTIDTYPE 639
8.221 SIMPLETYPE: SERVICELEVELINDICATORTYPE 639
8.222 SIMPLETYPE: SERVICECODETYPE 640
8.223 SIMPLETYPE: SERVICETYPECODETYPE 640
8.224 SIMPLETYPE: SORTATIONLEVELTYPE 640
8.225 SIMPLETYPE: SERVICESUBCODETYPE 641
8.226 SIMPLETYPE: STANDARDFLATTYPETYPE 641
8.227 SIMPLETYPE: STATECODE 641
8.228 SIMPLETYPE: STATUSTYPE 643
8.229 SIMPLETYPE: STOPDESIGNATORTYPE 643
8.230 SIMPLETYPE: SURCHARGETYPE 643
8.231 SIMPLETYPE: TOTALWEIGHTTYPE 644
8.232 SIMPLETYPE: TRAILERLENGTHTYPE 644
8.233 SIMPLETYPE: TRANSPORTATIONMETHODTYPE 644
8.234 SIMPLETYPE: TRANSSHIPBOLNUMBERTYPE 644
8.235 SIMPLETYPE: TRAYTYPE 644
8.236 SIMPLETYPE: TRUCKDISPATCHNUMBERTYPE 644
8.237 SIMPLETYPE: UNITLOADTYPE 645
8.238 SIMPLETYPE: UNLOADSTATETYPE 645
8.239 SIMPLETYPE: UOMTYPE 645

Copyright © 2011 USPS®. All Rights Reserved.

8.240 SIMPLETYPE: UNIQUECONTAINERIDTYPE 647
8.241 SIMPLETYPE: USERINFORMATIONLINE1TYPE 647
8.242 SIMPLETYPE: USERINFORMATIONLINE2TYPE 648
8.243 SIMPLETYPE: USERLICENSECODETYPE 648
8.244 SIMPLETYPE: USPSPICKUPTYPE 648
8.245 SIMPLETYPE: VERIFICATIONLOCATIONTYPE 648
8.246 SIMPLETYPE: VERIFICATIONREPORTTYPE 648
8.247 SIMPLETYPE: WASTEDPIECEINDICATORTYPE 649
8.248 SIMPLETYPE: WEEKFREQUENCYTYPE 649
8.249 SIMPLETYPE: WEIGHTBREAKTYPE 649
8.250 SIMPLETYPE: YESNO 650
8.251 SIMPLETYPE: ZIPCODETHREEORFIVEDIGIT 650
8.252 SIMPLETYPE: ZONEICTYPE 650
8.253 SIMPLETYPE: ONEPASSORTWOPASSTYPE 650
8.254 SIMPLETYPE: USPSPACKAGEUNIQUECHARACTERISTICTYPE 650
8.255 SIMPLETYPE: STANDARDFLATTYPETYPE 650
8.256 SIMPLETYPE: MARKETINGORFULFILLMENTTYPE 650
8.257 SIMPLETYPE: MLOCRRATETYPE 650
8.258 SIMPLETYPE: USPSPRICEINCENTIVETYPE 651

APPENDIX D - EDOCUMENTATION FORM VALUES 652

8.259 CONTAINER STATUS TYPE 652
8.260 ENTRY FACILITY TYPE VALUES 652
8.261 ENTRY FACILITY TYPE 652
8.262 FORM TYPE 652
8.263 FULL-SERVICE INDICATOR 653
8.264 POSTAGE STATEMENT STATUS DEFINITIONS 653
8.265 RATE CATEGORY 654
8.266 FIRST CLASS MAIL – RATE CATEGORY AND CORRESPONDING RATE LEVEL 655
8.267 PERIODICALS IN-COUNTY – RATE CATEGORY AND CORRESPONDING RATE LEVEL 655
8.268 PERIODICALS OUTSIDE-COUNTY – RATE CATEGORY AND CORRESPONDING RATE LEVEL 656
8.269 STANDARD MAIL – RATE CATEGORY AND CORRESPONDING RATE LEVEL 658
8.270 ADD PRICING FOR OUTSIDE COUNTY PERIODICALS PREPARED AS FSS 660
8.271 ADD FSS PREPARATION 661
8.272 FAULT CODES 662

9. APPENDIX E – POSTAGE STATEMENT MAPPINGS 664

9.1 MAILING INFORMATION – NON PERIODICALS 664

10. APPENDIX F - WSDLS AND XSDS 675

INDEX 678

Copyright © 2011 USPS®. All Rights Reserved.

Document Change History

These are the changes from RIBBS Version 9.8.4 (Aug 9, 2011)

These changes are being implemented to contribute to the goal of breaking down and editing the Postal Service Mail.XML technical specifications by Mail.XML supported versions to facilitate editing and enhance readability and navigation throughout the document.
In addition, to easier navigation, some sections such as the appendixes have been reorganized.

Previously the technical specifications were just divided by function (eDoc, Data Distribution, FAST). In that scheme, all supported Mail.XML for each release were all combined in one technical specification per function release. i.e. For Release 28 (November 2011) the Mail.XML eDoc technical specification included the supported Mail.XML versions 9.0B, 9.0C and 10.0C, as while the FAST technical specification containing Mail.XML 8.0B and 10.0 versions.
This approach resulted sometimes in bulky document that became difficult to edit, manage or read as with documents mounting up to sometimes more than 1000 pages.

With the new editing process, the technical guides are edited focusing on the Mail.XML supported version per function.
For instance, the FAST guide supporting Mail.XML 8.0B and 10.0 versions will have two different sub-Technical specifications for Release 29 (January 2012).

Each technical specification will also group all Mail.XML version and their respective supported errata versions.
For instance, 9.0B and 9.0C supported in eDoc technical specification for Release 28 are combined in one document since they are errata for Mail.XML 9.0. However if Mail.XML 8.0B and 8.1 were supported, they would have been in two different documents since they are not of the same Mail.XML version.
By convention, Mail.XML version name containing a letter, such as 7.0C, 9.0B, 10.0A are considered errata. In contrast, Mail.XML 8.0 and 8.1 are considered two different versions.

Editor	Date	Section #	Title	Description
Stepahnie Hartzberg	9/22/2011	2.4	Error Codes/Return Values	Added Error Codes: 8428. 8516, 8605, 8621, 9023, 9236, 9251, 9252, 9254, 9255, 9256, 9257, 8004 Updated Error Codes: Error Code 8055 Previous Error Text: PermitZIP4 field within PermitPublicationDatra block in the DocumentVersionDataWithPermit block in the QualificationReport block is required when the FormType is: FC, SM, BP, ML, PM, or PP. Updated Error Text: PermitZIP4 field within PermitPublicationData block in the DocumentVersionDataWithPermit block in the QualificationReport block is required when the FormType is: PM, FC, SM, BP, PP, or ML.

Copyright © 2011 USPS®. All Rights Reserved.

Editor	Date	Section #	Title	Description
				Error Code 8161 Previous Error Text: PermitType field in the PermitPublicationData block in the PermitHolderData block must be populated with PI or OI. Updated Error Text: PermitType field in the PermitPublicationData block in the PermitHolderForAPData block must be populated with PI or OI. Error Code 8382 Previous Error Text; FormType in the QualifcationReport block must be populated with F or MC, SM, BP, or PE when the FullServiceParticipationIndicator in the MailingGroupData block of the OpenMailingGroupRequest message is populated with F or M. Updated Error Text: FormType in the QualifcationReport block must be populated with FC, SM, BP, or PE when the FullServiceParticipationIndicator in the MailingGroupData block of the OpenMailingGroupRequest message is populated with F or M. Error Code 8588 Previous Error Text: RateType must be E or T when FormType is PM and ProcessingCategory is FL. Updated Error Text: RateType must be C, E, L, or T when FormType is PM and ProcessingCategory is FL. Error Code 8589 Previous Error Text: RateCategory must be S or PR when FormType is PM and ProcessingCategory is FL. Updated Error Text: RateCategory must be S, PR, P10, P11, P12, P13, P14, P15, or P16 when FormType is PM and ProcessingCategory is FL. Error Code 8590 Previous Error Text: RateType must be T when FormType is PM and ProcessingCategory is LT.

Copyright © 2011 USPS®. All Rights Reserved.

Editor	Date	Section #	Title	Description
				Updated Error Text: RateType must be C or T when FormType is PM and ProcessingCategory is LT. Error Code 8592 Previous Error Text: RateType must be E, G, J, K, 'O', X, or T when FormType is PM and ProcessingCategory is PF. Updated Error Text: RateType must be E, G, J, K, L, X, or T when FormType is PM and ProcessingCategory is PF. Error Code 8593 Previous Error Text: RateCategory must be S when FormType is PM and ProcessingCategory is PF. Updated Error Text: RateCategory must be S, P10, P11, P12, P13, P14, P15, or P16 when FormType is PM and ProcessingCategory is PF. Error Code 8595 Previous Error Text: RateCategory must be populated with S or PR when FormType is PM. Updated Error Text: RateCategory must be populated with S, PR, P10, P11, P12, P13, P14, P15, or P16 when FormType is PM. Error Code 8598: Previous Error Text: FlatRateIndicator must be populated with B, E, L, M, or S when FormType is PM. Updated Error Text: FlatRateIndicator must be populated with B, C, E, F, L, M, O, P, or S when FormType is PM. Error Code 8602 Previous Error Text: RateType must be populated with R, T, E, G, J, K, 'O', X or S when FormType is PM. Updated Error Text: RateType must be populated with C, L, T, E, G, J, K, or X when FormType is PM. Error Code 8611 Previous Error Text: ProcessingCategory must be populated with MP

Copyright © 2011 USPS®. All Rights Reserved.

Editor	Date	Section #	Title	Description
				or IR when FormType is PP and RateType is P. Updated Error Text: ProcessingCategory must be populated with MP, NP or IR when FormType is PP and RateType is P. Error Code 8613 Previous Error Text: RateCategory must be populated with S, Z1, or Z2 when FormType is PP and RateType is P. Updated Error Text: RateCategory must be populated with S when FormType is PP and RateType is P. Error Code 8616 Previous Error Text: SurchargeType must be populated with 2 or N when FormType is PP. Updated Error Text: SurchargeType must be populated with 2, N, or P when FormType is PP. Error Code 8618 Previous Error Text: BarcodeRate must be populated with Y or N when FormType is PP. Updated Error Text: BarcodeRate must be populated with N when FormType is PP and RateType is P. Error Code 8620 Previous Error Text: PostagePaymentMethod must be populated with S, M, or P when FormType is PP. Updated Error Text: PostagePaymentMethod must be populated with M or P when FormType is PP. Error Code 8698 Previous Error Text: VersionID in the ContainerDetailData must be populated and referenced with a VersionID in the DocumentVersionDataWithPermit block. (Container ID: %%1) Updated Error Text: VersionID in the ContainerDetailData must be populated and referenced with a VersionID in at least one DocumentVersionDataWithPermit

Copyright © 2011 USPS®. All Rights Reserved.

Editor	Date	Section #	Title	Description
				block associated to a Qualification Report. (Container ID: %%1) Error Code 8737 Previous Error Text: A ContainerDetailID field submitted in the PeriodicalStatementCreateRequest message must match a ContainerDetailID field submitted in the associated QualificationReportCreateRequestMessage. (ContainerDetailID %%1 missing for ContainerID %%2) Updated Error Text: A ContainerDetailID field submitted in the Periodical- or ConsolidatedPeriodicalStatementCreateRequest must match a ContainerDetailID field submitted in the associated QualificationReportCreateRequest. (ContainerDetailID %%1 missing for ContainerID %%2) Error Code 8885 Previous Error Text: When populated, the FullServiceLevelIndicator field must be set to F. Updated Error Text: When populated, the FullServiceParticipationIndicator field must be set to F. Error Code 9019 Previous Error Text: The FormType field must be set to First Class or Standard Mail for a co-palletized mailing with Container Type field set to F, O, or T. Updated Error Text: The FormType field must be set to First-Class Mail or Standard Mail for a co-palletized mailing with the Container Type field set to F, O or T. Error Code 9023 Previous Error Text: The PermitType in the PermitHolderData block must be populated with PI or OI for First-Class Commercial Plus Parcels. Updated Error Text: PermitType field in the PermitPublicationData block in the PermitHolderForAPData block must

Copyright © 2011 USPS®. All Rights Reserved.

Editor	Date	Section #	Title	Description
				be populated with PI or OI. Error Code 9158 Previos Error Text: AgencyCostCode field in MailXMLPostageStatementRequestHeaderInfo block of the ConsolidatedPeriodicalStatementCreateRequest message must match AgencyCostCode field in MailXMLPostageStatementRequestHeaderInfo block of EndCombinedMailingRequest message. Updated Error Text: AgencyCostCode field in MailXMLPostageStatementRequestHeaderInfo block of the ConsolidatedPeriodicalStatementCreateRequest message must match AgencyCostCode field in MailXMLPostageStatementRequestHeaderInfo block of EndCombinedMailingRequest message. Error Code 9180 Previous Error Text: For eInduction processing, the EntryLocaleKey field in the ContainerInfoData block must be populated when the corresponding ContainerType in the ContainerInfoData block is P, H, A, G, D, R, C, Z, M, T, O, E, F, S, 1, 2, 3, or L and the container is not a sibling. Updated Error Text: For eInduction processing, the EntryLocaleKey field in the ContainerInfoData block must be populated when the corresponding ContainerType is P, H, A, G, D, R, C, Z, M, T, O, E, F, S, 1, 2, 3, or L and the container is not a sibling. Error Code 9183 Previous Error Text: For eInduction processing, the ContainerBarcode field in the ContainerInfoData block must be unique within the mailing group and amongst all containers associated to the SubmittingParty CRID that were finalized within the last 45 days. Updated Error Text: For eInduction processing, the ContainerBarcode field in the ContainerInfoData block for IMcb(s)/pallets must be unique within the mailing group and amongst all containers associated to the SubmittingParty CRID that

Copyright © 2011 USPS®. All Rights Reserved.

Editor	Date	Section #	Title	Description
				were finalized within the last 45 days. Error Code 9184 Previous Error Text: For eInduction processing, the ContainerBarcode field in the ContainerInfoData block must be unique within the mailing group and amongst all containers finalized within the last 45 days. Updated Error Text: For eInduction processing, the ContainerBarcode field in the ContainerInfoData block for IMcb(s)/pallets must be unique within the mailing group and amongst all containers finalized within the last 45 days. Error Code 9242 Previous Error Text: The fields within the DocumentVersionDataWithPermit block for each unique VersionID must match for all QualificationReportDetailCreateRequest messages associated to the same Qualification Report. Updated Error Text: The fields within the DocumentVersionDataWithPermit block for each unique VersionID must match for all QualificationReportDetailCreateRequest messages associated to the same Qualification Report. VersionID (%%1) Error Code 9243 Previous Error Text: The QualificationReportCreateRequest messager is not supported in Mail.XML 10.0C. Updated Error Text: The QualificationReportCreateRequest message is not supported in Mail.XML 10.0C. Error Code 9245 Previous Error Text: The maximum weight for a Priority Mail Regional Rate Box A mail piece is 20 lbs. Updated Error Text: The maximum weight for a Priority Mail Regional Rate Box B mail piece is 20 lbs.

Copyright © 2011 USPS®. All Rights Reserved.

Editor	Date	Section #	Title	Description
				Removed Error Codes: 8695, 8975, 8976, 8977, 8978, 8979, 8980, 8981, 8982, 8983, 9104, 9178, 9189, 9190, 9207, 9212, 9240
Mema Bamba	9/01/2011		Change History	Added a new column “Date” to the table of Change History to record the date and editor of implemented changes.
Mema Bamba	8/31/2011	7.0	Appendix B	Adeed new headers to the tables of Complex and Attribute Data Types Data Structure for Mail.XML 9.0B
Mema Bamba	8/31/2011	6.0	Appendix A	Adeed new headers to the tables of Complex and Attribute Data Types Data Structure for Mail.XML 9.0C
Mema Bamba	8/31/2011	4.0	Mail.XML Version 9.0C eDoc and Miscellaneous Messages	Added headers to the table of Mail.XMl 9.0C messages
Mema Bamba	8/31/2011	3.0	Mail.XML Version 9.0B eDoc and Miscellaneous Messages	Added headers to the table of Mail.XMl 9.0B messages
Mema Bamba	8/31/2011	6.0,7.0,8.0,9.0,10,11.0	Appendix A, B, C, D, E, F	Reoganized the appendixes order
Mema Bamba	8/24/2011		Footer	Updated the footer to: USPS® – Postal Service Mail.XML 9.0X Technical Specification Version 1.0 - 08/24/2011 – Page 21 Copyright © 2011 USPS®. All Rights Reserved.

Copyright © 2011 USPS®. All Rights Reserved.

1. Postal Service Mail.XML Technical Specification

1.1 Program Overview

The *PostalOne!*® system is an electronic suite of services being developed for business mailers by the United States Postal Service® to improve the mailing process. The system takes advantage of the advances in technology and leverages them to significantly improve and simplify the mailing experience.

Customers can electronically send detailed information to the *PostalOne!* system using the mailing industry's standardized Mail.XML™ format. Mail.XML is an XML-based IDEAlliance® specification for web services. Web services uses simple HTTP(s) protocol to communicate data over the Internet, bypassing technology-specific restrictions and avoiding network-related security rules. See the IDEAlliance Mail.XML specifications at http://www.idealliance.org

The *PostalOne!* system allows customers to submit electronic documentation through the use of Mail.XML messages. Many of these messages are used to interact with the mailing supply chain via web services for a number of important functions including FAST, Full Service™ data distribution, and electronic documentation. This document is dedicated to describing the use of Mail.XML for electronic documentation of qualification reports, piece detail and piece range data, container and bundle reports, and postage statements.

The *PostalOne!* system currently supports three Mail.XML version: Mail.XML 7.0, 8.0, and 9.0. Beginning in Release 28.0.0, the *PostalOne!* system will support two new Mail.XML versions: Mail.XML 9.0C, and 10.0C. In versions 9.0C, and 10.0, the messages are broken up into multiple XSDs by function so developers only have to deal with the messages that are relevant to their application.

Mail.XML is an extremely fast and efficient way to present documentation. In many mailing scenarios – for example, “just in time” mail production of mailings of all sizes – there is no need to present an original file followed by a series of updates. In addition, the ability to query the *PostalOne!* system for status information about containers, handling units and postage statements allows mailers to automate processes and add considerable value to their postage reporting and documentation processes.

With Mail.XML, mailers can also update certain information about their mailings more quickly and more efficiently than Mail.dat, though there are certain rules and restrictions that will be discussed later in this document.

Mail.XML supports Full-Service, Mixed Service and Co-Palletized mailings. For Full and Mixed Service mailings, mailers will be required to submit qualification reports, piece information and postage statements for periodicals and non-periodicals mailings. Mailers will be required to submit qualification reports, piece information, postage statements and linkage information for Co-Palletizated mailings.

All business functions supported by the USPS as part of the Mail.XML implementation are based upon SOA (Services Oriented Architecture). With this architecture, mailers’ software manages the data transactions for query, create, update, and cancel business functions as well as subscription models. Additionally, mailers’ software is able to receive synchronous and asynchronous transactions through Web Services protocol from the USPS in support of the just-in-time communication architecture.

The Postal Service implementation of Mail.XML is a complement to Mail.dat. Mailers using Mail.dat can continue to use it as a database, but can use Mail.XML for communication and automation of business to business processing. Mail.XML allows business function-specific communication and faster change management processes with little to no impact to other service providers. For example, you can add optional fields or new messages without requiring software in the mailing supply chain to change. This is a core improvement area for the Mail.dat® specification.

Copyright © 2011 USPS®. All Rights Reserved.

Mail.XML supports electronic documentation and end-to-end mailing supply chain, business process management for a multitude of business processes. Mail.XML includes qualification reports, container and bundle reports, spoilage, eDropShip, containerization nesting, postage statements, postage adjustments, postage status query information, piece detail, piece ranging, and many other business process related communications. Mail.XML also provides the ability to electronically access USPS full-service data and to perform business functions related to full-service. Mail.XML allows create, update, and cancel transactions for the Cast of Characters (brokering of information) messages. Mail.XML supports copalletization, mixed mailing, manifest mailing, and business processes specific to MLOCR and continuous mailing environments.

One fundamental difference in the Mail.dat file and in Mail.XML messages is information content. For example, for qualification reports and postage statements, Mail.dat calculates from the raw data in several Mail.dat files the copies and pieces at each price level in the qualification report and the postage statements. This sometimes leads to round-off differences compared to qualification reports and postage statements calculated by the mailer using the same Mail.dat file. In Mail.XML, the mailer provides the numbers of copies and pieces for each price level directly and there is less round-off error.

There are two main types of Mail.XML messages that are used to share data between the mailer and the *PostalOne!* system. They are request messages and response messages.

Request Messages

Mail.XML request messages are used to submit mailing information to the *PostalOne!* system. Mailers submit request messages to send container information, mailpiece and piece range information, and postage information.

Response Messages

Mailers will receive a response message from the *PostalOne!* system after they submitt a request message. The response message is used to notify the customer of the status of their message.

- Accept Messages - Mailers will receive an Accept response if the request message that was submitted validated and uploaded successfully. After an Accept response is received, the mailer may continue submitting the remaining messages within that mailing group.
- Reject Messages - Mailers will receive a Reject response if the request message that was submitted did not validate and upload successfully. A ReturnCode and corresponding ReturnDescription, which describes the errors in the data, are provided in the response. The mailer must then update the data based on the error messages that were provided and resubmit.

The *Postal Service Mail.XML Technical Specification* is separated based on subject matter into the following volumes:

- *Postal Service Mail.XML Technical Specification for Postage Payment & Reporting (eDoc)*
- *Postal Service Mail.XML Technical Specification for Appointment Scheduling (FAST)*
- *Postal Service Mail.XML Technical Specification for Profiles & Full-Service Feedback*

This document focuses solely on the eDoc message functionalities covering Mail.XML versions 8.1, 9.0B, 9.0C and 10.0C.

Copyright © 2011 USPS®. All Rights Reserved.

1.1.1 Mail.XML 9.0C Change History

This major release corrects technical errors and introduces the schema modularization in an effort to streamline and modernize the USPS automation for 2011 as previously done in Mail.XML 9.0B.

The eDoc functionality of Mail.XML 9.0C discontinues support in November 2011 for the previous structure where the XSDs and messages are tightly coupled to one main XSD and one base XSD; the two prior versions, Mail.XML 7.0C and Mail.XML 8.0B previously supported this prior to November 2011. The main XSD covers all of the message sets of the eDoc, FAST, and Data Distribution specifications, which forces the XSD users to validate the complete XSD. With the introduction of stand-alone modularization in the Mail.XML 9.0A version, customers can develop and validate one or more message sets without the hassle of addressing the entire Mail.XML specification.

The Mail.XML 9.0C version will continue to maintain all of the messages that are currently supported. New enhancements addressing new elements, business rules, technical error fixes, and modularized XSDs are added in Mail.XML 9.0C.

Some of the new feature enhancements implemented in Mail.XML 9.0C are:

- New container levels (Origin SCF, Origin Mixed ADC Surface, Mixed ADC Air).
- The support to accept misshipped container to allow the mailers to notify USPS to accept and charge for misshipped container. (This field is added for future business requirement where misshipped when containers will be processed for postage)
- An optional element, eInductionIndicator serving as a flag to whether an e8125/e8017 needs to be generated for induction.
- A new USPS Price Incentive type called MobileBarcode has been added, allowing mailers to select this incentive as necessary. This incentive will only be available for mailings done in July and August 2011.
- New rate categories for Standard Mail Letter (Non Automation Carrier Route-Barcode and Non Automation Carrier Route, Carrier Route-Barcode) are being added.

Updates and changes in the Mail.XML 9.0C specification are **not backward compatible** with previous versions of Mail.XML for eDoc.

1.1.1 Mail.XML 9.0B Change History

This major release corrects technical errors and introduces the schema modularization in an effort to streamline and modernize the USPS automation for 2011.

The eDoc functionality of Mail.XML will continue to support the previous two versions (i.e. Mail.XML 7.0C and Mail.XML 8.0B) where the XSDs and messages are tightly coupled to one main XSD and one base XSD. The main XSD covers all of the message sets of the eDoc, FAST, and Data Distribution specifications, which forces the XSD users to validate the complete XSD. With the introduction of stand-alone modularization in Mail.XML 9.0A version customers can develop and validate one or more message sets without the hassle of addressing the entire Mail.XML specification.

Mail.XML 9.0B specification is not **backward compatible** with previous versions of Mail.XML for eDoc.

See below for high-level change history of each of the prior version of Mail.XML:

Copyright © 2011 USPS®. All Rights Reserved.

1.2 About Schema Modularization

From Mail.XML 9.0B publication, Mail.XML messages are now grouped into 6 sets:

- Transportation Messages
- Mailing Messages
- Data Distribution Messages
- Identification Messages
- Supply Chain Messages
- System Messages

The underlying schemas have been modularized to reflect these distinct message sets. Additionally, three "shared" or "common" schemas have been developed and they are:

1. One stores simple Mail.XML Mailing Message Specification type definitions that can be shared across message sets.
2. A second common module is made up of common elements and complex types that are shared across two or more message sets.
3. The final common module is made up of system messages and the attributes, elements and complex types that are *unique* to these messages.

Mail.XML schema modules are designed to stand alone, separated by business functions, enabling those interested in one or more message sets to develop and validate just those message sets without the requirement to address the entire Mail.XML specification. Each module will validate by itself or in combination with all other message sets when the entire Mail.XML Specification is considered. In addition each module will be versioned separately.

Version numbers are contained within the namespace designation. Modules will be documented individually as well.

The following Mail.XML XSD modules/namespaces have been developed:

- **mailxml_tm.xsd**: This module contains all the transportation (or FAST) messages with their attributes, elements and complex types that are *unique* to these messages. ***Namespace=mailxml_tm***

- **mailxml_mm .xsd**: This module contains all the mailing messages (eDoc) with their attributes, elements and complex types that are *unique* to these messages. ***Namespace=mailxml_mm***

- **mailxml_dd.xsd**: This module contains all the data distribution messages with their attributes, elements and complex types that are *unique* to these messages. ***Namespace=mailxml_dd***

- **mailxml_id.xsd**: This module contains all the identification messages(CRID, MID etc) with their attributes, elements and complex types that are *unique* to these messages. ***Namespace=mailxml_id***

- **mailxml_sc.xsd**: This module contains all the supply chain messages (Cross functional container based and other Mail.dat/mail.XML update functions) with their attributes, elements and complex types that are *unique* to these messages. ***Namespace=mailxml_sc***

- **mailxml.xsd**: This module contains all the system messages with their attributes, elements and complex types that are *unique* to these messages. Note that in order for the MessageResponseRetrievalResponse to work, all the other message modules are included by the system.xsd. ***Namespace=mailxml***

Copyright © 2011 USPS®. All Rights Reserved.

- **mailxml_defs.xsd**: This module contains all the common definitions of attributes, elements and complex types that are used across one or more message types. **Namespace=mailxml_defs**

- **mailxml_base.xsd**: This module contains all the simple types that are used everywhere in the mailxml. These simple types are associated with every element of each message. ***Namespace=mailxml_base***

1.3 What Schemas Cover Electronic Documentation (eDoc) Functionality?

With the breakdown of the XSD into multiple schemas – eDoc functionality will be covered by 2 separate modules. These modules are mailxml_mm.xsd and mailxml_sc.xsd.

In addition to the above modules, mailxml_base.xsd and mailxml_defs are common/shared XSD that will be referred by each of these individual eDoc-specific modules.

The mailxml.xsd module will be the source XSD that connects all messages to their system-level attributes. For example – MessageResponseRetrievalReponse is a shared attribute/complex type associated to almost every single Mail.XML message, regardless of whether it is Data Distribution, FAST or eDoc functionality. Other examples of shared attributes/types are: DeliveryResponse, NotificationResponse, Fault, etc.

1.4 USPS Limitation Rule on Transaction Requests

USPS has recently encountered unusual high volume with specific Mail.XML transactions by FAST and Full Service Data Distribution users, resulting in serious performance impact on several USPS servers that deal with authorization of all Mail.XML transactions.

The Postal Service is requiring that USPS Mail.XML customers update their Mail.XML software to query the USPS *PostalOne!*/FAST systems no more than seven times per hour. Similarly, USPS customers are encouraged to avoid setting up their web services pull software to query the *PostalOne!* servers no more than 200 times in a given 24 hour period for their eDoc, FAST, or Full Service data queries. This is a required change for all customers, and will greatly assist in avoiding performance issues that can hinder quality of service; users still have many opportunities to query necessary data within these limitations. Likewise, to improve overall experience for all customers it is absolutely necessary that customers program their software to query the USPS systems for different transactions at different times; in other words, configure some queries to occur at odd times, such as FAST queries, and configure other queries, such as eDoc and Data distribution, to occur at even times.

1.5 Recommended File Sizes for Optimum Mail.XML Performance

USPS® recommends following eDoc file sizes for the optimum performance

eDoc Message	File Size	Job Characteristics
QualificationReportCreateRequest	25 MB	Roughly 18,000 Containers (ContainerInfoData blocks)
MailPieceCreateRequest – MailPieceBlock	25 MB	Roughly 40,000 – 45,000 Mail Pieces (MailPieceBlocks)
MailPieceXeareRequest – MailPieceRangeBlock	25 MB	Roughly 25,000 – 30,000 piece ranges (MailPieceRangeBlock)
PostageStatementCreateRequest	25 MB	Roughly 35,000 Postage Statement Lines (PostageStatementLineItemData blocks)

Copyright © 2011 USPS®. All Rights Reserved.

1.6 Roadmap of Mail.XML

The table below shows the roadmap of the Mail.XML versions, starting from currently supported versions to versions that will be supported in future.

November 2010 Release 25.0.0	January 2011 Release 26.0.0	Fall 2011 Release 28.0.0
Mail.XML 6.0D Mail.XML 7.0C Mail.XML 8.0B	Mail.XML 7.0C * Mail.XML 8.0B Mail.XML 9.0B **	Mail.XML 8.0B * Mail.XML 9.0B Mail.XML 10.0 **

The version(s) flagged with single asterisk (*) are planned for de-commissioning within 120 days of the release date.

The version(s) flagged with double asterisk (**) are new versions planned for implementation with the release date. The release date will be different for each functionality and the dates may move to later in 2011.

1.7 Purpose

The purpose of this Technical Specification is to supplement the IDEAlliance Mail.XML and to provide Mail.XML users with specific information regarding the USPS implementation. USPS will support Mail.XML versions for electronic documentation as outlined in the Section 1.6 above. The content in this document is subject to change as IDEAlliance updates Mail.XML Specification. This technical specification includes the return codes, error codes and their descriptions, as well the WSDLs links for all the supported version of Mail.XML.

The USPS supports a test and production environment.

- **TEM (Testing Environment for Mailers)**: This environment is used for software approval processes for all mailers prior to moving into the production environment. Mailers must work with the *PostalOne!* Help Desk to start the approval process for their software, and must be approved in the TEM environment, prior to sending data transactions in the Production environment. For more information regarding TEM, see the *Test Environment for Mailers: Checklist and Troubleshooting Guide*

- **Production Environment**: This environment will be used by all customers that have been approved in the TEM environment by the USPS to start sending the transaction/messages.

1.8 Intended Audience

The intended audience for this specification is technical programmers and technical managers. Prior knowledge of XML language and Mail.dat functionalities will greatly improve the understanding of this document.

1.9 About This Document

The data structure tables for all the eDoc messages in Section 3.0, and 4.0 reference complex types. The details of these complex types are included in appendix A and B . The USPS recommends that customers study the complex types provided in appendix A and B to fully understand the structure of the eDoc messages.

In the data structure tables for all eDoc messages in Section 3.0 and 4.0 under the acceptable values column, actual simple type names are used for some of the elements. Review all simple types listed in Appendix C to fully understand the acceptable values that are validated by *PostalOne!* system. Also, You

Copyright © 2011 USPS®. All Rights Reserved.

will notice that in the Appendix C, simple type uses codes have now been updated with Mail.dat descriptions for your convenience. The USPS® recommends that you also read the *Postal Service Mail.dat Technical Specification*.

Also, in the data structure tables, some field names may contain spaces for readability purposes (because the names of those fields are lengthy). In Mail.XML, spaces are not allowed in the element names. For example: "SubmittingParty" is the element name but in the data table it may have been written as Submitting Party.

If you are using this document to code your software then use the latest version of Mail.XML XSD located on RIBBS® to fully understand the name of the element, structure of every block and message and to minimize the impact of incorrect coding.

1.10 How to Read Data Structure

There are three possibilities for every element listed in the data structure table of each message. These possibilities are REQUIRED, OPTIONAL, and CONDITIONALLY REQUIRED. The Required option means that mailer/preparer or sender of the message must provide data for the element. The Optional option means the sender of the message has a choice to include the data or omit it from submission. The third option of Conditionally Required means that if certain condition is met then the sender of the message must provide data for that particular element; for example - EntryPointEDPostalCode is conditionally required if EntryPointEDFacilityType is populated in the ContainerUpdateRequest message.

In addition to the above options, there are instances where the main block is marked as REQUIRED, but the elements within the block are OPTIONAL or vice versa. This means that sender of the message must include the block when sending the message, but can omit all elements within the block. A good example is the 'SubmittingParty' block, which is a REQUIRED block, but all elements within this block are OPTIONAL.

1.11 Issue Resolution

All issues where the USPS software may not comply with the business rules, the work-arounds for such issues are listed in the critical issues list on the RIBBS Intelligent Mail site under Latest News. For example – In some cases the work around for Full-Service ACS data is to receive the data through OneCode ACS method instead of Full-Service methods. Additionally, for postage statements too large, the work around is to divide the statements in multiple statements. The current *PostalOne!* Critical Issues list is found at Intelligent Mail on the Latest News tab at:

http://ribbs.usps.gov/intelligentmail_latestnews/documents/tech_guides/PostalOneCriticalIssueExtCustomers.pdf

1.12 Mail.XML Message Hierarchy

The sections below provide list of required vs. optional messages based on different scenarios. Also, the sections provide the list of prerequisite message that must be sent prior to sending the actual required message.

It is strongly recommended that customer wait to receive the response acknowledgement from USPS before sending the next message to avoid network clogging. It may impact the response time from USPS if multiple requests arrive at USPS servers in a non-sequential order.

Copyright © 2011 USPS®. All Rights Reserved.

1.1.1 Full-Service & Mixed Service Mailings

For full-service and mixed service mailings, the following messages are required for First-Class Mail, Standard Mail, and Package Services mailings: OpenMailingGroupRequest, QualificationReportCreateRequest, MailPieceCreateRequest, and PostageStatementCreateRequest. The messages that need to be submitted prior to each required message for full-service and mixed service mailings are listed below:

Required Full-Service/Mixed Service Messages for First-Class Mail, Standard Mail, or Package Services

Message	Required Prerequisite Messages
OpenMailingGroupRequest	None
QualificationReportCreateRequest	OpenMailingGroupRequest
**MailPieceCreateRequest	OpenMailingGroupRequest, QualificationReportCreateRequest
PostageStatementCreateRequest	OpenMailingGroupRequest, QualificationReportCreateRequest, MailPieceCreateRequest (before or after)

**As of Release 28, the MailPieceCreateRequest message can be submitted before and after a postage statement is submitted, prior to finalization.

All other messages are optional for full-service and mixed service mailings. The messages that need to be submitted prior to each optional message are listed below:

Optional Full-Service/Mixed Service Messages for First-Class Mail, Standard Mail, or Package Services

Message	Required Prerequisite Messages
BundleDetailCreateRequest	OpenMailingGroupRequest
BeginCombinedMailingRequest	OpenMailingGroupRequest, QualificationReportCreateRequest, MailPieceCreateRequest
EndCombinedMailingRequest	OpenMailingGroupRequest, QualificationReportCreateRequest, MailPieceCreateRequest, BeginCombinedMailingRequest, PostageStatementCreateRequest
PostageAdjustmentCreateRequest	OpenMailingGroupRequest, QualificationReportCreateRequest, MailPieceCreateRequest, PostageStatementCreateRequest
OriginalContainerLinkageCreate	OpenMailingGroupRequest, QualificationReportCreateRequest
CloseMailingGroupRequest	OpenMailingGroupRequest
SiblingContainerCreateRequest	None
ContainerUpdateRequest	None
MailingGroupQueryRequest	OpenMailingGroupRequest
PostageStatementQueryRequest	OpenMailingGroupRequest, QualificationReportCreateRequest, MailPieceCreateRequest, PostageStatementCreateRequest
PostageStatementStatusQueryRequest	OpenMailingGroupRequest, QualificationReportCreateRequest,

Copyright © 2011 USPS®. All Rights Reserved.

	MailPieceCreateRequest, PostageStatementCreateRequest
ReconciliationReportQueryRequest	
PaymentMessageQueryRequest	
BundleDetailCancelRequest	OpenMailingGroupRequest, QualificationReportCreateRequest, BundleDetailCreateRequest
MailPieceCancelRequest	OpenMailingGroupRequest, QualificationReportCreateRequest, MailPieceCreateRequest
PostageStatementCancelRequest	OpenMailingGroupRequest, QualificationReportCreateRequest, MailPieceCreateRequest, PostageStatementCreateRequest
OriginalContainerLinkageCancelRequest	OpenMailingGroupRequest, QualificationReportCreateRequest, OriginalContainerLinkageCreate
SiblingContainerCancelRequest	SiblingContainerCreateRequest
CustomerMailReportCreateRequest	OpenMailingGroupRequest QualificationReportCreateRequest PostageStatementCreateRequest
SummaryZipDestinationReportCreateRequest	OpenMailingGroupRequest QualificationReportCreateRequest PostageStatementCreateRequest

**As of Release 28, the MailPieceCreateRequest message can be submitted before and after a postage statement is submitted, prior to finalization.

For full-service and mixed service mailings, the following messages are required for Periodicals mailings: OpenMailingGroupRequest, QualificationReportCreateRequest, ContainerBundleReportCreateRequest , MailPieceCreateRequest, and PostageStatementCreateRequest. The messages that need to be submitted prior to each required message for full-service and mixed service mailings are listed below:

Required Full-Service/Mixed Service Messages for Periodicals

Message	Required Prerequisite Messages
OpenMailingGroupRequest	None
QualificationReportCreateRequest	OpenMailingGroupRequest
ContainerBundleReportCreateRequest	OpenMailingGroupRequest, QualificationReportCreateRequest
MailPieceCreateRequest	OpenMailingGroupRequest, QualificationReportCreateRequest, ContainerBundleReportCreateRequest
PeriodicalStatementCreateRequest	OpenMailingGroupRequest, QualificationReportCreateRequest, ContainerBundleReportCreateRequest , **MailPieceCreateRequest

Copyright © 2011 USPS®. All Rights Reserved.

All other messages are optional for full-service and mixed service mailings. The messages that need to be submitted prior to each optional message are listed below:

Optional Full-Service/Mixed Service Messages for Periodicals

Message	Required Prerequisite Messages
BundleDetailCreateRequest	OpenMailingGroupRequest
BeginCombinedMailingRequest	OpenMailingGroupRequest, QualificationReportCreateRequest, **MailPieceCreateRequest
EndCombinedMailingRequest	OpenMailingGroupRequest, QualificationReportCreateRequest, **MailPieceCreateRequest, BeginCombinedMailingRequest, PeriodicalStatementCreateRequest
PostageAdjustmentCreateRequest	OpenMailingGroupRequest, QualificationReportCreateRequest, **MailPieceCreateRequest, PeriodicalStatementCreateRequest
OriginalContainerLinkageCreate	OpenMailingGroupRequest, QualificationReportCreateRequest
CloseMailingGroupRequest	OpenMailingGroupRequest
SiblingContainerCreateRequest	None
ContainerUpdateRequest	None
MailingGroupQueryRequest	OpenMailingGroupRequest
ContainerBundleReportQueryRequest	OpenMailingGroupRequest
PeriodicalStatementQueryRequest	OpenMailingGroupRequest, QualificationReportCreateRequest, ContainerBundleReportCreateRequest, **MailPieceCreateRequest, PeriodicalStatementCreateRequest
PostageStatementStatusQueryRequest	OpenMailingGroupRequest, QualificationReportCreateRequest, ContainerBundleReportCreateRequest, **MailPieceCreateRequest, PeriodicalStatementCreateRequest
ReconciliationReportQueryRequest	
PaymentMessageQueryRequest	
ContainerBundleReportCancelRequest	OpenMailingGroupRequest
BundleDetailCancelRequest	OpenMailingGroupRequest, QualificationReportCreateRequest, BundleDetailCreateRequest
MailPieceCancelRequest	OpenMailingGroupRequest, QualificationReportCreateRequest, **MailPieceCreateRequest
PostageStatementCancelRequest	OpenMailingGroupRequest, QualificationReportCreateRequest,

Copyright © 2011 USPS®. All Rights Reserved.

	ContainerBundleReportCreateRequest, **MailPieceCreateRequest, PeriodicalStatementCreateRequest
OriginalContainerLinkageCancelRequest	OpenMailingGroupRequest, QualificationReportCreateRequest, OriginalContainerLinkageCreate
SiblingContainerCancelRequest	SiblingContainerCreateRequest

**As of Release 28, the MailPieceCreateRequest message can be submitted before and after a postage statement is submitted, prior to finalization.

1.1.2 Full-Service & Mixed Service Mailings

For eDoc mailings, the following messages are required for First-Class Mail, Standard Mail, and Package Services mailings: OpenMailingGroupRequest, QualificationReportCreateRequest, and PostageStatementCreateRequest except when the mailing is less than 10,000 pieces. The messages that need to be submitted prior to each required message for eDoc mailings are listed below.

The following are the rules that determine Required versus Optional eDoc Messages:

1. When a mailing is less than 10,000 pieces and mailing is not a Full-Service then set of eDoc messages marked as required below are not applicable.
2. When a mailing is above 10,000 pieces then set of eDoc messages below are required as outlined.
3. When a mailing is Full-Service then set of eDoc messages below are required. The Full-Service mailing over-writes the 10,000 pieces threshold.

Required eDoc Messages for First-Class Mail, Standard Mail, or Package Services

Message	Required Prerequisite Messages
OpenMailingGroupRequest	None
QualificationReportCreateRequest	OpenMailingGroupRequest
PostageStatementCreateRequest	OpenMailingGroupRequest, QualificationReportCreateRequest

All other messages are optional for eDoc mailings. The messages that need to be submitted prior to each optional message are listed below:

Optional eDoc Messages for First-Class Mail, Standard Mail, or Package Services

Message	Required Prerequisite Messages
BundleDetailCreateRequest	OpenMailingGroupRequest
**MailPieceCreateRequest	OpenMailingGroupRequest, QualificationReportCreateRequest
BeginCombinedMailingRequest * This is a required message for combined or commingled mailings	OpenMailingGroupRequest, QualificationReportCreateRequest
EndCombinedMailingRequest * This is required message for combined or commingle mailings.	OpenMailingGroupRequest, QualificationReportCreateRequest, BeginCombinedMailingRequest, PostageStatementCreateRequest
PostageAdjustmentCreateRequest	OpenMailingGroupRequest,

Copyright © 2011 USPS®. All Rights Reserved.

	QualificationReportCreateRequest, PostageStatementCreateRequest
OriginalContainerLinkageCreate* * USPS strongly recommends sending this message when Copalletizing the mail, even when the mailing is a Non Full-service mailing.	OpenMailingGroupRequest, QualificationReportCreateRequest
CloseMailingGroupRequest	OpenMailingGroupRequest
SiblingContainerCreateRequest	None
ContainerUpdateRequest	None
MailingGroupQueryRequest	OpenMailingGroupRequest
PostageStatementQueryRequest	OpenMailingGroupRequest, QualificationReportCreateRequest, PostageStatementCreateRequest
PostageStatementStatusQueryRequest	OpenMailingGroupRequest, QualificationReportCreateRequest, PostageStatementCreateRequest
ReconciliationReportQueryRequest	
PaymentMessageQueryRequest	
BundleDetailCancelRequest	OpenMailingGroupRequest, QualificationReportCreateRequest, BundleDetailCreateRequest
MailPieceCancelRequest	OpenMailingGroupRequest, QualificationReportCreateRequest
PostageStatementCancelRequest	OpenMailingGroupRequest, QualificationReportCreateRequest, PostageStatementCreateRequest
OriginalContainerLinkageCancelRequest	OpenMailingGroupRequest, QualificationReportCreateRequest, OriginalContainerLinkageCreate
SiblingContainerCancelRequest	SiblingContainerCreateRequest
CustomerMailReportCreateRequest	OpenMailingGroupRequest QualificationReportCreateRequest PostageStatementCreateRequest
SummaryZipDestinationReportCreateRequest	OpenMailingGroupRequest QualificationReportCreateRequest PostageStatementCreateRequest

For eDoc mailings, the following messages are required for Periodicals mailings: OpenMailingGroupRequest, QualificationReportCreateRequest, and PostageStatementCreateRequest. The messages that need to be submitted prior to each required message for eDoc mailings are listed below:

Required eDoc Messages for Periodicals

Message	Required Prerequisite Messages
OpenMailingGroupRequest	None
QualificationReportCreateRequest	OpenMailingGroupRequest
ContainerBundleReportCreateRequest	OpenMailingGroupRequest, QualificationReportCreateRequest
PeriodicalStatementCreateRequest	OpenMailingGroupRequest,

Copyright © 2011 USPS®. All Rights Reserved.

	QualificationReportCreateRequest

All other messages are optional for full-service and mixed service mailings. The messages that need to be submitted prior to each optional message are listed below:

Optional eDoc Messages for Periodicals

Message	Required Prerequisite Messages
BundleDetailCreateRequest	OpenMailingGroupRequest
**MailPieceCreateRequest	OpenMailingGroupRequest, QualificationReportCreateRequest
BeginCombinedMailingRequest	OpenMailingGroupRequest, QualificationReportCreateRequest
EndCombinedMailingRequest	OpenMailingGroupRequest, QualificationReportCreateRequest, BeginCombinedMailingRequest, PeriodicalStatementCreateRequest
PostageAdjustmentCreateRequest	OpenMailingGroupRequest, QualificationReportCreateRequest, PeriodicalStatementCreateRequest
OriginalContainerLinkageCreate* * USPS strongly recommends sending this message when Copalletizing the mail, even when the mailing is a Non Full-service mailing.	OpenMailingGroupRequest, QualificationReportCreateRequest
CloseMailingGroupRequest	OpenMailingGroupRequest
SiblingContainerCreateRequest	None
ContainerUpdateRequest	None
MailingGroupQueryRequest	OpenMailingGroupRequest
ContainerBundleReportQueryRequest	OpenMailingGroupRequest
PeriodicalStatementQueryRequest	OpenMailingGroupRequest, QualificationReportCreateRequest, PeriodicalStatementCreateRequest
PostageStatementStatusQueryRequest	OpenMailingGroupRequest, QualificationReportCreateRequest, PeriodicalStatementCreateRequest
ReconciliationReportQueryRequest	
PaymentMessageQueryRequest	
ContainerBundleReportCancelRequest	OpenMailingGroupRequest
BundleDetailCancelRequest	OpenMailingGroupRequest, QualificationReportCreateRequest, BundleDetailCreateRequest
MailPieceCancelRequest	OpenMailingGroupRequest, QualificationReportCreateRequest, MailPieceCreateRequest
PostageStatementCancelRequest	OpenMailingGroupRequest, QualificationReportCreateRequest, PeriodicalStatementCreateRequest
OriginalContainerLinkageCancelRequest	OpenMailingGroupRequest, QualificationReportCreateRequest, OriginalContainerLinkageCreate
SiblingContainerCancelRequest	SiblingContainerCreateRequest

Copyright © 2011 USPS®. All Rights Reserved.

**As of Release 28, the MailPieceCreateRequest message can be submitted before and after a postage statement is submitted, prior to finalization.

1.13 Workflows

1.13.1 Non-Periodicals without Full-Service

1. Send OpenMailingGroupRequest
2. Receive accepted OpenMailingGroupResponse with assigned MailingGroupID.
3. Use CustomerGroupID and MailingGroup in Attributes for additional messages.
4. Send QualificationReportCreateRequest
5. Receive accepted QualificationReportCreateResponse
6. Send PostageStatementCreateRequest
7. Receive accepted PostageStatementCreateResponse

1.13.1 Periodicals without Full-Service

1. Send OpenMailingGroupRequest
2. Receive accepted OpenMailingGroupResponse with assigned MailingGroupID.
3. Use CustomerGroupID and MailingGroup in Attributes for additional messages.
4. Send QualificationReportCreateRequest
5. Receive accepted QualificationReportCreateResponse
6. Send ContainerBundleReportCreateRequest
7. Receive accepted ContainerBundleReportCreateResponse
8. Send PeriodicalStatementCreateRequest
9. Receive accepted PeriodicalStatementCreateResponse

1.13.1 Non-Periodicals with Full-Service

1. Send OpenMailingGroupRequest
2. Receive accepted OpenMailingGroupResponse with assigned MailingGroupID.
3. Use CustomerGroupID and MailingGroup in Attributes for additional messages.
4. Send QualificationReportCreateRequest
5. Receive accepted QualificationReportCreateResponse
6. Send MailPieceCreateRequest
7. Receive accepted MailPieceCreateResponse.
8. Send PostageStatementCreateRequest
9. Receive accepted PostageStatementCreateResponse

As of Release 28 the following will also be accepted:

1. Send OpenMailingGroupRequest
2. Receive accepted OpenMailingGroupResponse with assigned MailingGroupID.
3. Use CustomerGroupID and in Attributes for additional messages.
4. Send QualificationReportCreateRequest
5. Receive accepted QualificationReportCreateResponse
6. Send PostageStatementCreateRequest
7. Receive accepted PostageStatementCreateResponse
8. Send MailPieceCreateRequest (prior to finalization)
9. Receive accepted MailPieceCreateResponse.

Copyright © 2011 USPS®. All Rights Reserved.

1.13.1 Periodicals with Full-Service

1. Send OpenMailingGroupRequest
2. Receive accepted OpenMailingGroupResponse with assigned MailingGroupID.
3. Use CustomerGroupID and MailingGroup in Attributes for additional messages.
4. Send QualificationReportCreateRequest
5. Receive accepted QualificationReportCreateResponse
6. Send ContainerBundleReportCreateRequest
7. Receive accepted ContainerBundleReportCreateResponse
8. Send MailPieceCreateRequest
9. Receive accepted MailPieceCreateResponse.
10. Send PeriodicalStatementCreateRequest
11. Receive accepted PeriodicalStatementCreateResponse

As of Release 28 the following will also be accepted:

1. Send OpenMailingGroupRequest
2. Receive accepted OpenMailingGroupResponse with assigned MailingGroupID.
3. Use CustomerGroupID and MailingGroup in Attributes for additional messages.
4. Send QualificationReportCreateRequest
5. Receive accepted QualificationReportCreateResponse
6. Send ContainerBundleReportCreateRequest
7. Receive accepted ContainerBundleReportCreateResponse
8. Send PeriodicalStatementCreateRequest
9. Receive accepted PeriodicalStatementCreateResponse
10. Send MailPieceCreateRequest (prior to finalization)
11. Receive accepted MailPieceCreateResponse.

For full-service in remaining scenarios insert send MailPieceCreateRequest and receive accepted MailPieceCreateResponse after receive accepted QualificationReportCreateResponse and either before or ater the Postage/Periodical Statement Request and Response.

1.13.1 Combined/ Commingled Mailing - non-Periodicals

1. Send OpenMailingGroupRequest
2. Receive accepted OpenMailingGroupResponse with assigned MailingGroupID.
3. Use CustomerGroupID and MailingGroup in Attributes for additional messages.
4. Send QualificationReportCreateRequest
5. Receive accepted QualificationReportCreateResponse
6. Send BeginCombinedMailingRequest
7. Receive accepted BeginCombinedMailingResponse
8. Use the CombinedMailingID in all the postage statements.
9. Send each PostageStatementCreateRequest
10. Receive each PostageStatementCreateResponse
11. After last PostageStatementCreateResponse, send EndCombinedMailingRequest
12. Receive EndCombinedMailingResponse.

The only noted difference between Commingled and Combined mailings is that for a Commingled Mailing, the USPS requires a minimum of 150 pieces per Zip Code to achieve five-digit postal rates, whereas a Combined Mailing has no such requirement.

1.13.1 Combined/ Commingled Mailing - Periodicals

1. Send OpenMailingGroupRequest
2. Receive accepted OpenMailingGroupResponse with assigned MailingGroupID.

Copyright © 2011 USPS®. All Rights Reserved.

3. Use CustomerGroupID and MailingGroup in Attributes for additional messages.
4. Send QualificationReportCreateRequest
5. Receive accepted QualificationReportCreateResponse
6. Send ContainerBundleReportCreateRequest
7. Receive accepted ContainerBundleReportCreateResponse
8. Send BeginCombinedMailingRequest
9. Receive accepted BeginCombinedMailingResponse
10. Use the CombinedMailingID in all the postage statements.
11. Send each PeriodicalStatementCreateRequest
12. Receive each PeriodicalStatementCreateResponse
13. After last PeriodicalStatementCreateResponse, send EndCombinedMailingRequest
14. Receive EndCombinedMailingResponse.

The only noted difference between Commingled and Combined mailings is that for a Commingled Mailing, the USPS requires a minimum of 150 pieces per Zip Code to achieve five-digit postal rates, whereas a Combined Mailing has no such requirement.

1.13.1 Copalletized Mailing for Trays on Pallets non-Periodicals

At consolidator (original site sending regular mailing via Mail.XML or Mail.dat)

1. Send OpenMailingGroupRequest
2. Receive accepted OpenMailingGroupResponse with assigned MailingGroupID.
3. Use CustomerGroupID and MailingGroup in Attributes for additional messages.
4. Send QualificationReportCreateRequest
5. Receive accepted QualificationReportCreateResponse
6. Send OriginalContainerLinkageCreateRequest. (Required when mail contains Full-Service pieces and strongly recommended by the USPS when non Full-service mail is copalletized)
7. Receive accepted OriginalContainerLinkageCreateResponse

1.13.1 Copalletized Mailing for Bundles on Pallets - Standard Mail

At consolidator (original site sending regular mailing via Mail.XML or Mail.dat)

1. Send OpenMailingGroupRequest
2. Receive accepted OpenMailingGroupResponse with assigned MailingGroupID.
3. Use CustomerGroupID and MailingGroup in Attributes for additional messages.
4. Send QualificationReportCreateRequest
5. Receive accepted QualificationReportCreateResponse
6. Send OriginalContainerLinkageCreateRequest. (Required when mail contains Full-Service pieces and strongly recommended by the USPS when non Full-service mail is copalletized)
7. Receive accepted OriginalContainerLinkageCreateResponse
8. Send BeginCombinedMailingRequest
9. Receive accepted BeginCombinedMailingResponse
10. Use the CombinedMailingID in all the postage statements.
11. Send each PostageStatementCreateRequest
12. Receive each PostageStatementCreateResponse
13. After last PostageStatementCreateResponse, send EndCombinedMailingRequest
14. Receive EndCombinedMailingResponse.

1.13.1 Copalletized Mailing for Bundles on Pallets - Periodicals Mail

At consolidator (original site sends regular mailing via Mail.XML or Mail.dat)

15. Send OpenMailingGroupRequest
16. Receive accepted OpenMailingGroupResponse with assigned MailingGroupID.
17. Use CustomerGroupID and MailingGroup in Attributes for additional messages.
18. Send QualificationReportCreateRequest

Copyright © 2011 USPS®. All Rights Reserved.

19. Receive accepted QualificationReportCreateResponse
20. Send ContainerBundleReportCreateRequest
21. Receive accepted ContainerBundleReportCreateResponse
22. Send OriginalContainerLinkageCreateRequest. (Required when mail contains Full-Service pieces and strongly recommended by the USPS when non Full-service mail is copalletized)
23. Receive accepted OriginalContainerLinkageCreateResponse
24. Send BeginCombinedMailingRequest
25. Receive accepted BeginCombinedMailingResponse
26. Use the CombinedMailingID in all the postage statements.
27. Send each PeriodicalStatementCreateRequest
28. Receive each PeriodicalStatementCreateResponse
29. After last PostageStatementCreateResponse, send EndCombinedMailingRequest
30. Receive EndCombinedMailingResponse.

1.14 Exceptions

The following cases are not supported in the Mail.XML:

- Full-service logical mailers who do not have the physical tray information for a specific logical tray. Job ID, Container ID, and Sibling Container ID would be populated as normal. Container Type would be T and IM Container or Tray Barcode would be filled with 24 digits of digit ‘9’. Beginning in Release 24, the number of duplicate Tray Barcodes cannot exceed 1% for any Full-Service or Mixed Service mailing. This duplication will cause validation failures for Qualification Report.

- Mailings with multiple mail classes such as Periodicals and Standard mixed together. This includes the experiment for copalletization of Periodicals and Standard Mail is not supported.

- For Original Container Linkage – mother containers are not supported

- International mail is not supported.

- Periodicals Exception to Sacking (DMM section 707.23.4.2). Sacking is not required for bundles prepared for and entered at a DDU when the mailer unloads bundles under (DMM section) 707.28.4.6. Mail presented under this exception is not subject to the container charge (but is still subject to the bundle charges).

- Periodicals parcels that are not bundled. If Periodicals parcels are not bundled, even irregular parcels, validation rejects the Qualification report. To submit Periodicals parcels that are not bundled per DMM section 707.23.4, submit the mailing with the alternative standardized documentation and postage statements.

- For MLOCR mailings, postage statements cannot claim the “Single Piece” rate category until a later release.

- Non-incidental enclosures are eligible for the full-service discount when enclosed in host mail pieces that receive full-service discount and are letters or machinable flats. For Postage Statements submitted via Mail.XML, the full-service discount on the non-incidental enclosure when applicable is not supported at this time. Mailer must request a refund of the amount of this postage by the usual manual refund process.

Copyright © 2011 USPS®. All Rights Reserved.

2. *PostalOne!* – eDoc Mail.XML Messages

2.1 Overview

This section provides the technical information related to the *PostalOne!* - Mail.XML Web Services messages. These messages support all eDocumentation and miscellaneous functionality related to mailer interaction with the *PostalOne!* system in managing, updating and querying mail contents. Web Services messages also supplement the Mail.dat functionality, such as payment message queries and container status checking for eDropShip. The *PostalOne!* system will support the new and enhanced version of these eDoc messages in November 2011 as described in this eDoc section of the Postal Service Mail.XML Technical Specification.

Just like the existing FAST and Full-Service Data Distribution, eDoc messages use the same technology concept of Web Services near real time messaging architecture. For eDoc messages, customers are required to have Web Services capable software that can manage the data itself and be able to send and receive the Web Services Mail.XML based transactions from the USPS. For those customers and vendors who have developed the WWS (Wizard Web Services) software, they are required to modify their software to work with Mail.XML XSD and enhance their WWS message names and implementation. The near real time architecture will allow you to send your final documentation transactions to the USPS and get a response in near real time in most cases. For large transactions, the asynchronous web services architecture provided through tracking ids in Mail.XML is available, which allows the customer's software to query the USPS *PostalOne!* system again to find out if the piece data or qualification reports were processed with either accepted or rejected response.

2.2 Message Response Retrieval Request Processing

2.2.1 Fault and Fault Recovery Messages

This series of messages is primarily used to support the Asynchronous communication when the response from the USPS may not be within a 7 seconds period and the USPS gives out a tracking ID to the customer. The customer then uses the Tracking ID to get his message response back using the Message Response Retrieval Request/Response message. Please note all of the response messages now have a TrackingID though all messages are not specifically outlined above under Mail.XML 10.0C section.

Message Response Retrieval Request

Message Response Retrieval Response

Customers have the ability to provide Tracking ID in the MessageResponseRetrievalRequest message to retrieve data for the entire Response message that are being supported in 10.0C.

2.3 Additional Rules/Constraints

2.3.1 Container Status Messages

The *PostalOne!* system will support status checking through Container Status Query Request and Response messages in this release by the originator of the data and by the entity identified as the Scheduler or Carrier in the eDocumentation. Status checking allows mailers to view the status of any given container(s) and ensure that the container is validated during the pre-induction and post-induction process

Copyright © 2011 USPS®. All Rights Reserved.

The *PostalOne!* system upon receiving the container status message shall go to the container management system of eInduction to find out all validation status of the requested container(s) and respond to the customer with the status information.

If there are any issues or validation errors for one or more containers, then the *PostalOne!* system shall respond back to the customer with validation failures for one or more container(s).

2.3.1 ContainerStatusQueryResponse Error Codes / Return Values

Error Code	Error Message
4050	Unauthorized Access Error
4051	Invalid Barcode
4052	Duplicate Barcode
4053	Scheduling Error
4054	Entry Point Discount Error
4055	No records were found for the given search criteria
4056	Payment is not finalized for pallet containers. No induction validation information is available
4057	Payment is not finalized for tray containers. No induction validation information is available

2.4 Error Codes/Return Values

Faults, such as a message timeout or invalid XML are to be communicated using the <fault element and returned within the detail section of the SOAP fault. The fault consists of a tracking ID and one or more fault codes and optional fault descriptions.

Below is the list of the error codes that will be used by USPS when deploying the eDocumentation Messages in starting in November 2009.

Error Code	Error Message	Messages
8000	CustomerGroupID in the HeaderInfo block must be the same for all messages in a mailing group.	Multiple
8002	CRID field within the SubmittingParty block must be the same for all request messages in a mailing group.	Multiple
8003	All fields within the DocumentVersionData block must match the corresponding fields in DocumentVersionData blocks and DocumentVersionDataWithPermit blocks with the same VersionID, except Periodicals with Non-Incidental Enclosures.	Multiple
8006	MailingGroupData block must be populated with a combination of values that exist in the *PostalOne!* Mail.dat database within the OpenMailingGroupRequest message.	OpenMailingGroup Response
8007	PermitNumber field within the PermitPublicationData block must map to the SubmitterCRID within the MailingGroupData block for preparing electronic documentation.	OpenMailingGroup Response

Copyright © 2011 USPS®. All Rights Reserved.

Error Code	Error Message	Messages
8008	PermitNumber field within the PermitPublicationData block must map to the SubmitterCRID within the MailingGroupData block must be unique when combined with the PermitType and PostOfficeOfMailingZip fields of the OpenMailingGroupRequest message.	OpenMailingGroup Response
8009	The first 5 characters of the PermitZIP4 field within the PermitPublicationData block must match the PostOfficeOfMailingZip field within the MailingGroupData block.	OpenMailingGroup Response
8010	MailingFacility field within the MailingGroupData block must be populated with a value that is the same as the CRID of the SubmittingParty block.	OpenMailingGroup Response
8011	OnePassIndicator field must be populated if the MailXMLPresentationCategory field in the MailingGroupData block is populated with M.	OpenMailingGroup Response
8012	OpenMailingGroupRequest message must be accepted before submitting the CloseMailingGroupRequst message for the specified MailingGroupID.	OpenMailingGroup Response, CloseMailingGrou pResponse
8013	The fields within the SubmittingParty block in the CloseMailingGroupRequest message must be populated with the same values as the fields within the SubmittingParty block of an open mailing group.	CloseMailingGrou pResponse
8014	CustomerGroupID field in the CloseMailingGroupRequest must be populated with the same value as the CustomerGroupID in the OpenMailingGroupRequest.	CloseMailingGrou pResponse
8015	MailingGroupID field in the CloseMailingGroupRequest must be populated with the same value as the MailingGroupID in the OpenMailingGroupResponse.	CloseMailingGrou pResponse
8016	MailingGroupID and CustomerGroupID in the CloseMailingGroupRequest must be populated with the same value as the MailingGroupID and CustomerGroupID of an accepted OpenMailingGroupRequest.	CloseMailingGrou pResponse
8017	OpenMailingGroupRequest message must be accepted before submitting the QualificationReportSummaryCreateRequest/ QualificationReportDetailCreateRequest message for the specified MailingGroupID and CustomerGroupID.	QualificationRepor tCreateResponse
8018	ContainerInfoData block(s) is required for each container/handling unit for a qualification report.	QualificationRepor tCreateResponse
8020	Each ContainerInfoData block needs the ContainerDetailData block populated except when it is a Parent Container or it is a Sibling Container.(Container ID: %%1).	QualificationRepor tCreateResponse, QualificationRepor tDetailCreateResp onse (10.0)
8022	ActualContainerShipDate is required when USPSPickup field in the ContainerInfoData block in the QualificationReport block is Y. (Container ID: %%1)	QualificationRepor tCreateResponse, QualificationRepor tDetailCreateResp nose (10.0)

Copyright © 2011 USPS®. All Rights Reserved.

Error Code	Error Message	Messages
8023	ContainerBarcode field in the ContainerInfoData block in the QualificationReport block cannot be populated when the ContainerType field value is L, M, or V. (Container ID: %%1)	QualificationReportCreateResponse, QualificationReportDetailCreateResponse (10.0)
8026	ParentContainerID field in the ContainerInfoData block in the QualificationReport block cannot be populated if the SiblingContainerID field is populated. (Container ID: %%1)	QualificationReportCreateResponse, QualificationReportDetailCreateResponse (10.0)
8027	ParentContainerID in the ContainerInfoData block in the QualificationReport block must point to another existing ParentContainerID within the QualificationReportSummaryCreateRequest/ QualificationReportDetailCreateRequest message. (Container ID: %%1)	QualificationReportCreateResponse
8028	SiblingContainerID field in the ContainerInfoData block in the QualificationReport block must point to a different container also in the QualificationReportSummaryCreateRequest/ QualificationReportDetailCreateRequest message. (Container ID: %%1)	QualificationReportCreateResponse
8030	EntryLocaleKey must contain 6 characters. (Container ID: %%1)	QualificationReportCreateResponse, QualificationReportDetailCreateResponse (10.0)
8032	AdditionalTrayPostageAmount must contain less than or equal to 4 decimal characters. (Container ID: %%1)	QualificationReportCreateResponse, QualificationReportDetailCreateResponse (10.0)
8033	PermitNumber within the PermitPublicationData block in the MailingGroupData block must be populated with a value combined with the PostOfficeOfMailingZIP in the MailingGroupData block that maps to a single active Finance Number.	OpenMailingGroupResponse
8035	InOutCountyIndicator field in the ContainerDetailData block in the ContainerInfoData block in the QualificationReport block is required when FormType is PE. (Container ID: %%1)	QualificationReportCreateResponse
8037	Only one ContainerID field in the MailXMLPieceRange block can be populated.	MailPieceCreateResponse
8039	BundleDetailCreateRequest message must be accepted before submitting the MailPieceCreateRequest message when BundleID in the MailPieceBlockGroup is populated for the specified MailingGroupID and CustomerGroupID.. (BundleID: %%1, ContainerID: %%2)	MailPieceCreateResponse
8040	PublicationNumber field in the QualificationReportPreparer block in the QualificationReport block cannot be populated when the FormType is not populated with PE for Periodicals.	QualificationReportCreateResponse, QualificationReportSummaryCreateResponse (10.0)

Copyright © 2011 USPS®. All Rights Reserved.

Error Code	Error Message	Messages
8041	PermitNumber field in the QualificationReportPreparer block in the QualificationReport block is required when the FormType is not PE for Periodicals or Pending Periodicals.	QualificationReportCreateResponse, QualificationReportSummaryCreateResponse (10.0)
8042	PermitType field within the QualificationReportPreparer in the QualificationReport block is required when the FormType is not PE for Periodicals or Pending Periodicals.	QualificationReportCreateResponse, QualificationReportSummaryCreateResponse (10.0)
8043	PermitZIP4 field within the QualificationReportPreparer block in the QualificationReport block is required when the FormType is not PE for Periodicals or Pending Periodicals.	QualificationReportCreateResponse, QualificationReportSummaryCreateResponse (10.0)
8045	VersionID field value within the DocumentVersionDataWithPermit block in the QualificationReport block must be referenced in at least one VersionID in the ContainerDetailData block. (Version ID: %%1)	QualificationReportCreateResponse, QualificationReportDetailCreateResponse (10.0)
8046	PieceWeight field within the DocumentVersionDataWithPermit block in the QualificationReport block must contain less than or equal to 4 decimal characters. (Version ID: %%1)	QualificationReportCreateResponse, QualificationReportDetailCreateResponse (10.0)
8047	AdPercent field value within the DocumentVersionDataWithPermit block in the QualificationReport block cannot be more than 4 decimals. (Version ID: %%1)	QualificationReportCreateResponse, QualificationReportDetailCreateResponse (10.0)
8048	AdPercent field value within the DocumentVersionDataWithPermit block in the QualificationReport block cannot be more than 100.00. (Version ID: %%1)	QualificationReportCreateResponse, QualificationReportDetailCreateResponse (10.0)
8049	RateAffixed field within the DocumentVersionDataWithPermit block in the QualificationReport block cannot be more than 3 decimal characters. (Version ID: %%1)	QualificationReportCreateResponse, QualificationReportDetailCreateResponse (10.0)
8050	RateAffixed field within the DocumentVersionDataWithPermit block in the QualificationReport block is required when the PermitType field is set to MT, PC, or OM. (Version ID: %%1)	QualificationReportCreateResponse, QualificationReportDetailCreateResponse (10.0)
8051	PermitNumber field in the DocumentVersionDataWithPermit block in the QualificationReport block is required when the FormType is FC, SM, BP, ML, PM, or PP. The PermitNumber field cannot be populated when FormType is PE for Periodicals. Form type is: %%2	QualificationReportCreateResponse

Copyright © 2011 USPS®. All Rights Reserved.

Error Code	Error Message	Messages
8053	PermitType field within PermitPublicationData block in the DocumentVersionDataWithPermit block in the QualificationReport block cannot be populated when the PublicaitonNumber is populated. (Version ID: %%1)	QualificationReportCreateResponse, QualificationReportDetailCreateResponse (10.0)
8055	PermitZIP4 field within PermitPublicationData block in the DocumentVersionDataWithPermit block in the QualificationReport block is required when the FormType is: PM, FC, SM, BP, PP, or ML.	QualificationReportCreateResponse
8058	PublicationNumber field in the PermitPublicationData block in the DocumentVersionDataWithPermit block in the QualificationReport data block should not be populated when the FormType is not populated with PE for Periodicals or Pending Periodicals.	QualificationReportCreateResponse
8061	QualificationReportSummaryCreateRequest/ QualificationReportDetailCreateRequest message must be accepted before submitting the BundleDetailCreateRequest message for the specified CustomerGroupID and MailingGroupID.	BundleDetailCreateResponse
8062	CustomerBundleID is a required field.	BundleDetailCreateResponse
8063	BundleZIP must be populated with either 3 or 5 characters.	BundleDetailCreateResponse
8064	BundleCarrierRoute is required when the SortationLevel in the BundleDetail block of the BundleDetailCreateRequest message is populated with A, B, C, D, or U.	BundleDetailCreateResponse
8065	MailingGroupID and Customer GroupID in the BundleCreateRequestHeaderInfo block must be populated with the same values as the MailingGroupID and CustomerGroupID of an accepted OpenMailingGroupRequest message.	BundleDetailCreateResponse
8066	ContainerID must be populated with the same value as the ContainerID in the ContainerInfoData block of the QualificationReportSummaryCreateRequest/ QualificationReportDetailCreateRequest message for the specified MailingGroupID and CustomerGroupID. Found Missing ContainerID: %%1	BundleDetailCreateResponse
8067	VersionID must be populated with the same value as the VersionID in the ContainerDetailData block of the QualificationReportSummaryCreateRequest/ QualificationReportDetailCreateRequest message for the specified MailingGroupID and CustomerGroupID. Found Missing VersionID: %%1	BundleDetailCreateResponse
8068	BundleDetailCreateRequest message with the updated number of pieces for the specified combination of MailingGroupID, CustomerGroupID, and BundleID must be accepted before submitting the BundleDetailCancelRequest message. (BundleID '%%1')	BundleDetailCreateResponse, BundleDetailCancelRequest
8069	MailPieceCancelRequest message with the updated number of cancelled pieces for the specified combination of MailingGroupID, CustomerGroupID, and BundleID must be accepted before submitting the BundleDetailCancelRequest message.	BundleDetailCancelRequest

Copyright © 2011 USPS®. All Rights Reserved.

Error Code	Error Message	Messages
8070	BundleDetailCreateRequest message must be accepted before submitting the BundleDetailCancelRequest message.	BundleDetailCancelRequest
8071	BundleID is a required field.	BundleDetailCancelRequest
8073	ContainerID must match the ContainerID in the BundleDetail block of the BundleDetailCreateRequest message for the specified MailingGroupID and CustomerGroupID. ContainerID %%1 was not found.	BundleDetailCancelRequest
8074	BundleID must match the BundleID in the BundleDetail block of the BundleDetailCreateRequest message for the specified MailingGroupID and CustomerGroupID.	BundleDetailCancelRequest
8075	OriginalContainer block must contain fields that are populated with the values that exist for the specified CRID.	SiblingContainerCreateResponse
8076	NewSiblingContainer block must be populated with values that tie to the values populated in the OriginalContainer block.	SiblingContainerCreateResponse
8077	CRID in the SubmittingParty block must be populated with the same value as the Mailing Facility ID in the .seg file for the specified information in the OriginalContainer block.	SiblingContainerCreateResponse
8078	UserLicenseCode field in the OriginalContainer block must be populated with the same value as the value populated in the User License Code field from the .hdr file of the existing container.	SiblingContainerCreateResponse
8079	MaildatJobID field in the OriginalContainer block must be populated with the same value as the value populated in the Job ID field from the .csm file of the existing container.	SiblingContainerCreateResponse
8080	ContainerID field in the OriginalContainer block must be populated with the same value as the value populated in the Container ID field in the .csm file of the existing container.	SiblingContainerCreateResponse
8081	UniqueContainerBarcode field in the OriginalContainer block, if populated, is populated with the same value as the Label: IM Container or IM Tray Barcode field in the .csm file of the existing container.(UniqueContainerBarcode %%1)	SiblingContainerCreateResponse
8082	UserLicenseCode field in the NewSiblingContainer block must be populated with the same value as the value populated in the UserLicenseCode field in the OriginalContainer block.	SiblingContainerCreateResponse
8083	MaildatJobID field in the NewSiblingContainer block must be populated with the same value as the value populated in the MaildatJobID field in the OriginalContainer block.	SiblingContainerCreateResponse
8084	MaildatJobID field in the NewSiblingContainer block must be populated with the same value as the value populated in the MaildatJobID field in the OriginalContainer block.	SiblingContainerCreateResponse
8087	ContainerID in the NewSiblingContainer block must be unique within the MaildatJobID. (ContainerID: %%1)	SiblingContainerCreateResponse
8088	The SiblingContainerCreateRequest messsage for this combination of CRID, MaildatJobID, ContainerId and SiblingContainerID does not exist.(Original ContainerID: %%1, Sibling ContainerID: %%2, CRID: %%3)	SiblingContainerCancelResponse
8089	SiblingToDelete block must be tied to an existing sibling container in the *PostalOne!* Mail.dat database for the specified CRID. (Sibling ContainerID: %%1)	SiblingContainerCancelReseponse

Copyright © 2011 USPS®. All Rights Reserved.

Error Code	Error Message	Messages
8090	UserLicenseCode field in the OriginalContainer block must be populated with the same value as the value populated in the UserLicenseCode field in the OriginalContainer block of the SiblingContainerCreateRequest message.	SiblingContainerCreateResponse
8091	MaildatJobID field in the OriginalContainer block must be populated with the same value as the value populated in the MaildatJobID field in the OriginalContainer block of the SiblingContainerCreateRequest message.	SiblingContainerCancelReseponse
8092	ContainerID field in the OriginalContainer block must be populated with the same value as the value populated in the ContainerID field in the OriginalContainer block of the SiblingContainerCreateRequest message.	SiblingContainerCancelReseponse
8093	UniqueContainerBarcode field in the OriginalContainer block, if populated, is populated with the same value as the value populated in the UniqueContainerBarcode field in the OriginalContainer block of the SiblingContainerCreateRequest message.	SiblingContainerCancelReseponse
8094	UserLicenseCode field in the SiblingToDelete block must be populated with the same value as the value populated in the UserLicenseCode field in the NewSiblingContainer block of the SiblingContainerCreateRequest message for the specified CRID.	SiblingContainerCancelReseponse
8095	MaildatJobID field in the SiblingToDelete block must be populated with the same value as the value populated in the MaildatJobID field in the NewSiblingContainer block of the SiblingContainerCreateRequest message for the specified CRID.	SiblingContainerCancelReseponse
8096	ContainerID field in the SiblingToDelete block must be populated with the same value as the value populated in the ContainerID field in the NewSiblingContainer block of the SiblingContainerCreateRequest message for the specified CRID.	SiblingContainerCancelReseponse
8097	UniqueContainerBarcode field in the SiblingToDelete block must be populated with the same value as the value populated in the UniqueContainerBarcode field in the NewSiblingContainer block of the SiblingContainerCreateRequest message for a specified CRID.	SiblingContainerCancelReseponse
8098	The ContainerID field in the SibilingToDelete block cannot have ContainerType set to L, V, or M. (Sibling ContainerID: %%1)	SiblingContainerCancelRequest
8100	OpenMailingGroupRequest message must be accepted before submitting the PostageStatementCreateRequest message for the specified CustomerGroupID and MailingGroupID.	Postage Statement Messages
8101	BeginCombinedMailingRequest message must be accepted before submitting the PostageStatementCreateRequest message for the specified CustomerGroupID and MailingGroupID for a combined mailing.	Postage Statement Messages
8102	LineItemSummaryData block is required when the ExtendedForm in the CreatePostageStatement block is populated with False.	Postage Statement Messages
8103	PostageStatementLineItemData is required when the ExtendedForm in the CreatePostageStatement block is populated with True.	Postage Statement Messages
8104	PermitHolderForAPData is required when the PostagePaymentMethod in the CreatePostageStatement block is populated with M or S.	Postage Statement Messages

Copyright © 2011 USPS®. All Rights Reserved.

Error Code	Error Message	Messages
8105	MailingGroupID and Customer GroupID in the MailXMLPostageStatementRequestHeaderInfo block must be populated with the same values as the MailingGroupID and CustomerGroupID of an accepted OpenMailingGroupRequest message.	Multiple
8106	AgencyCostCode in the CreatePostageStatement block must contain less than or equal to 5 characters.	Postage Statement Messages
8107	AgencyCostCode in the CreatePostageStatement block is required when the PermitType in the PermitPublicationData block in the MailingGroupData block is populated with OI or OM.	Postage Statement Messages
8113	CarrierRouteSequencingDate is required when the RateCategory in the PostageStatementLineItemData block is populated with A, B, D, O, A1, B1, or D1.	Postage Statement Messages
8114	PiecePostage in the LineItemSummaryData block must contain less than or equal to 4 decimal characters.	Postage Statement Messages
8115	PieceRate in the LineItemSummaryData block must contain less than or equal to 3 decimal characters.	Postage Statement Messages
8116	PostageAmount in the LineItemSummaryData block must contain less than or equal to 4 decimal characters.	Postage Statement Messages
8117	PoundPostage in the LineItemSummaryData block must contain less than or equal to 4 decimal characters.	Postage Statement Messages
8118	PoundRate in the LineItemSummaryData block must contain less than or equal to 3 decimal characters.	Postage Statement Messages
8119	PreparedAsSM must be populated with Yes when the FormType in the CreatePostageStatement block is populated with SM.	Postage Statement Messages
8121	TotalWeight in the LineItemSummaryData block must contain less than or equal to 4 decimal characters.	Postage Statement Messages
8123	ContainerDisplayName is required when the RegisterOfMailing in the CreatePostageStatement block is populated with True.	Postage Statement Messages
8124	ContainerID is required when the RegisterOfMailing in the CreatePostageStatement block is populated with True.	Postage Statement Messages
8125	EntryFacilityType is required when the RegisterOfMailing in the CreatePostageStatement block is populated with True.	Postage Statement Messages
8126	EntryZIP is required when the RegisterOfMailing in the CreatePostageStatement block is populated with True.	Postage Statement Messages
8128	PieceRate in the PostageStatementLineItemData block must contain less than or equal to 3 decimal characters.	Postage Statement Messages

Copyright © 2011 USPS®. All Rights Reserved.

Error Code	Error Message	Messages
8129	PostageAmount in the PostageStatementLineItemData block must contain less than or equal to 4 decimal characters.	Postage Statement Messages
8130	PoundRate in the PostageStatementLineItemData block must contain less than or equal to 3 decimal characters.	Postage Statement Messages
8131	When PreparedAsSM is True and Form Type is FC, then ProcessingCategory must be FL, LT, or PF, and RateCategory must be S.	Postage Statement Messages
8133	SinglePieceWeight in the PostageStatementLineItemData block must contain less than or equal to 4 decimal characters.	Postage Statement Messages
8134	TotalWeight in the PostageStatementLineItemData block must contain less than or equal to 4 decimals characters.	Postage Statement Messages
8135	Zone can only be populated with N, 1, 3, 4, 5, 6, 7, 8, DDU, or SCF in the PostageStatementCreateRequest message.	Postage Statement Messages
8136	VersionID is required when the PostageAffixedAmount in the CreatePostageStatement block is not provided.	Postage Statement Messages
8137	ContainerType is required when the RegisterOfMailing in the CreatePostageStatement block is populated with True.	Postage Statement Messages
8138	SinglePieceDimensionalWeight in the PostageStatementLineItemData block must contain less than or equal to 4 decimal characters.	Postage Statement Messages
8139	SinglePieceDimensionalWeight in the PostageStatementLineItemData block must be populated with a value greater than zero when the SurchargeType in the *PostageStatementLineItemData* block is populated with D.	Postage Statement Messages
8140	PostageAffixedAmount is required when the PostagePaymentMethod in the CreatePostageStatement block is populated with M or S.	Postage Statement Messages
8141	When SinglePieceWeight in the CreatePostageStatement block is provided, it must match all SinglePieceWeight fields in the PostageStatementLineItemData block.	Postage Statement Messages
8142	ServiceRate in the ExtraServiceData block must contain less than or equal to 3 decimal characters.	Postage Statement Messages
8143	ServiceValue in the ExtraServiceDatamust block must contain less than or equal to 4 decimal characters.	Postage Statement Messages
8144	TotalAmount in the ExtraServiceData block must contain less than or equal to 4 decimal characters.	Postage Statement Messages
8145	TotalAmount in the ExtraServiceSummaryData block must contain less than or equal to 4 decimal characters.	Postage Statement Messages
8146	PieceWeight in the DocumentVersionData block must contain less than or equal to 4 decimal characters.	Postage Statement Messages

Copyright © 2011 USPS®. All Rights Reserved.

Error Code	Error Message	Messages
8147	RateAffixed is required when the PostagePaymentMethod in the CreatePostageStatement block is populated with M or S.	Postage Statement Messages
8148	RateAffixed in the DocumentVersionData block must contain less than or equal to 3 decimal characters.	Postage Statement Messages
8149	SinglePieceDimensionalWeight CreatePostageStatement must contain less than or equal to 4 decimal characters.	Postage Statement Messages
8153	MoveUpdateMethod is required when the FormType in the CreatePostageStatement block is populated with SM.	Postage Statement Messages
8155	The PermitNumber and PermitZIP4 or PublicationNumber in the PermitHolderData or PublisherData blocks and the MailingAgentData block must map to the same Finance Number and must be active.	Postage Statement Messages
8156	PermitType must be populated with MT or OM when the MeteredAffixedMethod in the CreatePostageStatement block is populated with M.	Postage Statement Messages
8157	PermitType must be populated with PC when the PostagePaymentMethod in the CreatePostageStatement block is populated with S.	Postage Statement Messages
8158	PublicationNumber cannot be populated in the PermitPublicationData block in the PermitHolderData block of the PostageStatementCreateRequest.	Postage Statement Messages
8159	PublicationNumber cannot be populated in the PermitPublicationData block in the MailingOwnerData block of the PostageStatementCreateRequest.	Postage Statement Messages
8160	PublicationNumber cannot be populated in the PermitPublicationData block in the MailingAgentData block of the PostageStatementCreateRequest.	Postage Statement Messages
8161	PermitType field in the PermitPublicationData block in the PermitHolderForAPData block must be populated with PI or OI.	Postage Statement Messages
8162	PublicationNumber cannot be populated in the PermitPublicationData block in the PermitHolderForAPData block of the PostageStatementCreateRequest.	Postage Statement Messages
8163	PostageStatementMailingDate in the CreatePostageStatement block must match the PostageStatementMailingDate in the QualificationReportSummaryCreateRequest/ QualificationReportDetailCreateRequest message when it is populated for the same ContainerID for the specified MailingGroupID and CustomerGroupID.	Postage Statement Messages
8164	CombinedMailingID in the CreatePostageStatement block must match the CombinedMailingID in the BeginCombinedMailingAccept block of the BeginCombinedMailingResponse message for the specified MailingGroupID and CustomerGroupID.	Postage Statement Messages
8165	ServiceSubCode must be populated with N when ServiceCode in the ExtraServiceData block is populated with CM. Extra Service Data block number %%1 contains an invalid Sub Service Code %%2 for Service Code %%3.	Postage Statement Messages

Copyright © 2011 USPS®. All Rights Reserved.

Error Code	Error Message	Messages
8166	ServiceSubCode must be populated with N or R when ServiceCode in the ExtraServiceData block is populated with COD. Extra Service Data block number %%1 contains an invalid Sub Service Code %%2 for Service Code %%3.	Postage Statement Messages
8167	ServiceSubCode must be populated with N when ServiceCode in the ExtraServiceData block is populated with COM. Extra Service Data block number %%1 contains an invalid Sub Service Code %%2 for Service Code %%3.	Postage Statement Messages
8168	ServiceSubCode must be populated with E or R when ServiceCode in the ExtraServiceData block is populated with DC. Extra Service Data block number %%1 contains an invalid Sub Service Code %%2 for Service Code %%3.	Postage Statement Messages
8169	ServiceSubCode must be populated with N when ServiceCode in the ExtraServiceData block is populated with IM. Extra Service Data block number %%1 contains an invalid Sub Service Code %%2 for Service Code %%3.	Postage Statement Messages
8170	ServiceSubCode must be populated with N when ServiceCode in the ExtraServiceData block is populated with PAL. Extra Service Data block number %%1 contains an invalid Sub Service Code %%2 for Service Code %%3.	Postage Statement Messages
8171	ServiceSubCode must be populated with N when ServiceCode in the ExtraServiceData block is populated with RD. Extra Service Data block number %%1 contains an invalid Sub Service Code %%2 for Service Code %%3.	Postage Statement Messages
8172	ServiceSubCode must be populated with N when ServiceCode in the ExtraServiceData block is populated with RM. Extra Service Data block number %%1 contains an invalid Sub Service Code %%2 for Service Code %%3.	Postage Statement Messages
8173	ServiceSubCode must be populated with T when ServiceCode in the ExtraServiceData block is populated with RR. Extra Service Data block number %%1 contains an invalid Sub Service Code %%2 for Service Code %%3.	Postage Statement Messages
8174	ServiceSubCode must be populated with E when ServiceCode in the ExtraServiceData block is populated with RRE. Extra Service Data block number %%1 contains an invalid Sub Service Code %%2 for Service Code %%3.	Postage Statement Messages
8175	ServiceSubCode must be populated with N when ServiceCode in the ExtraServiceData block is populated with RRM. Extra Service Data block number %%1 contains an invalid Sub Service Code %%2 for Service Code %%3.	Postage Statement Messages
8176	ServiceSubCode must be populated with E or R when ServiceCode in the ExtraServiceData block is populated with SC. Extra Service Data block number %%1 contains an invalid Sub Service Code %%2 for Service Code %%3.	Postage Statement Messages
8177	ServiceSubCode must be populated with N when ServiceCode in the ExtraServiceData block is populated with SH. Extra Service Data block number %%1 contains an invalid Sub Service Code %%2 for Service Code %%3.	Postage Statement Messages
8178	SinglePieceWeight in the CreatePostageStatement block must be populated with the same value as the SinglePieceWeight in the PostageStatementLineItemData block for the specified MailingGroupID and CustomerGroupID.	Postage Statement Messages

Copyright © 2011 USPS®. All Rights Reserved.

Error Code	Error Message	Messages
8179	SinglePieceWeight in the CreatePostageStatement block must be populated with the same value as the PieceWeight in the DocumentVersionData block of the CreatePostageStatement block when the DocumentVersionData block is populated.	Postage Statement Messages
8181	DalPieces must be populated with a value that is equal to the total number of pieces with ProcessingCategory FL, MP, IR, or NP and RateCategory A, B, D, or O for the specified MailingGroupID and CustomerGroupID when provided.	Postage Statement Messages
8182	Pieces greater than 3.3 ounces and less than 16 ounces and pieces less than or equal to 3.3 ounces cannot be submitted together within a mailing when DalPieces is populated.	Postage Statement Messages
8184	StatementID in the PostageStatementQueryRequest message must exist for the specified MailingGroupID and CustomerGroupID.	Postage Statement Messages
8185	PeriodicalStatementID can only be submitted in the PeriodicalStatementQueryRequest.	Postage Statement Messages
8186	PostageStatementCreateRequest message or PeriodicalStatementCreateRequest message must be accepted before submitting the PostageStatementStatusQueryRequest message for the specified MailingGroupID, CustomerGroupID and StatementID.	Postage Statement Messages
8191	StatementID in the PostageStatementCancelRequest message must exist for the specified MailingGroupID and CustomerGroupID.	Postage Statement Messages
8193	OpenMailingGroupRequest message must be accepted before submitting the BeginCombinedMailingRequest for the specified MailingGroupID and CustomerGroupID.	BeginCombinedMailingResponse
8194	MailingGroupID and CustomerGroupID of the BeginCombinedMailingRequest must be populated with the same values as the value populated in MailingGroupID and CustomerGroupID for an accepted OpenMailingGroupRequest message.	BeginCombinedMailingResponse
8195	All PostageStatementCreateRequest messages must be submitted for the specified MailingGroupID, CustomerGroupID,and CombinedMailingID before submitting the EndCombinedMailingRequest message.	EndCombinedMailingResponse
8196	BeginCombinedMailingRequest message must be accepted for the specified MailingGroupID, CustomerGroupID, and CombinedMailingID before submitting the EndCombinedMailingRequest message.	EndCombinedMailingResponse
8197	MailingGroupID and CustomerGroupID in the of the EndCombinedMailingRequest must be populated with the same values as the value populated in MailingGroupID and CustomerGroupID for an accepted OpenMailingGroupRequest message.	EndCombinedMailingResponse
8198	OpenMailingGroupRequest message must be accepted before submitting the PeriodicalStatementCreateRequest message for the specified CustomerGroupID and MailingGroupID. (User Postage Statement ID: %%1).	Postage Statement Messages

Copyright © 2011 USPS®. All Rights Reserved.

Error Code	Error Message	Messages
8199	DocumentVersionData block in the CreatePeriodicalStatementData block is required. (User Postage Statement ID: %%1).	Postage Statement Messages
8200	AdvertisingPercentage in the CreatePeriodicalStatementData block must contain less than or equal to 2 decimal characters. (User Postage Statement ID: %%1).	Postage Statement Messages
8204	CopyWeight in the CreatePeriodicalStatementData block must contain less than or equal to 4 decimal characters. (User Postage Statement ID: %%1).	Postage Statement Messages
8205	DiscountQty in the PeriodicalLineItemData block is required when the PeriodicalPrice in the PeriodicalLineItemData block is populated with 1. (User Postage Statement ID: %%1).	Postage Statement Messages
8206	DiscountQty in the PeriodicalLineItemData block cannot contain decimal characters. (User Postage Statement ID: %%1).	Postage Statement Messages
8207	PeriodicalPrice in the PeriodicalLineItemData block can only be populated with Blank, 1, 5, 9, C, D, E, R, or Z. (User Postage Statement ID: %%1).	Postage Statement Messages
8210	Pieces in the PeriodicalLineItemData block is required when RateCategory in the PeriodicalLineItemData block is populated. (User Postage Statement ID: %%1).	Postage Statement Messages
8213	RateCategory in the PeriodicalLineItemData block can only be populated with A, B, D, O, FB, E, G, H, K, L1, L2, L3, L4, L5, L6, L, N in the PeriodicalLineItemData block. (User Postage Statement ID: %%1).	Postage Statement Messages
8214	At least one of the SubReqCopies or the NonCopies field is required and must be populated with a non-zero integer when both bundles and containers are not populated (User Postage Statement ID: %%1).	Postage Statement Messages
8217	ChargeableContainerLevel is required when InOutCountyIndicator is populated with N and ChargeableEntryLevel and ChargeableContainerType and Containers in the PeriodicalLineItemData block are populated. (User Postage Statement ID: %%1).	Postage Statement Messages
8218	ChargeableBundleLevel in the PeriodicalLineItemData block is required when InOutCountyIndicator is populated with N and ChargeableContainerLevel and Bundles in the PeriodicalLineItemData block are populated. (User Postage Statement ID: %%1).	Postage Statement Messages
8219	Bundles in the PeriodicalLineItemData block must contain less than or equal to 4 decimal characters. (User Postage Statement ID: %%1).	Postage Statement Messages
8220	Bundles in the PeriodicalLineItemData block is required when InOutCountyIndicator is populated with N and ChargeableContainerLevel and ChargeableBundleLevel in the PeriodicalLineItemData block are populated. (User Postage Statement ID: %%1).	Postage Statement Messages
8221	ChargeableEntryLevel is required when InOutCountyIndicator is populated with N and ChargeableContainerLevel and ChargeableContainerType and Containers in the PeriodicalLineItemData block are populated. (User Postage Statement ID: %%1).	Postage Statement Messages

Copyright © 2011 USPS®. All Rights Reserved.

Error Code	Error Message	Messages
8222	Containers in the PeriodicalLineItemData block must contain less than or equal to 4 decimal characters. (User Postage Statement ID: %%1).	Postage Statement Messages
8223	Containers in the PeriodicalLineItemData block is required when is populated with N and ChargeableContainerLevel, ChargeableEntryLevel and ChargeableContainerType in the PeriodicalLineItemData block are populated. (User Postage Statement ID: %%1).	Postage Statement Messages
8224	MachinableFlag in the PeriodicalLineItemData block is required when the RateCategory in the PeriodicalLineItemData block is populated and the processing category is flats. (User Postage Statement ID: %%1).	Postage Statement Messages
8225	PostagePaymentMethod in the CreatePeriodicalStatementData block can only be populated with P. (User Postage Statement ID: %%1).	Postage Statement Messages
8226	ProcessingCategory in the CreatePeriodicalStatementData block can only be populated with LT, FL, IR, MP, or NP. (User Postage Statement ID: %%1).	Postage Statement Messages
8227	RateType in the CreatePeriodicalStatementData block can only be populated with R, N, S, C, W, or Y. (User Postage Statement ID: %%1).	Postage Statement Messages
8228	SingleRideAlongWeight is required when the PeriodicalPrice in the PeriodicalLineItemData block is populated with 9. (User Postage Statement ID: %%1).	Postage Statement Messages
8229	SingleRideAlongWeight must contain less than or equal to 4 decimal characters. (User Postage Statement ID: %%1).	Postage Statement Messages
8234	CombinedMailingID in the CreatePeriodicalStatementData block must be populated with the same value as the CombinedMailingID of the BeginCombinedMailingRequest message for a specified MailingGroupID and CustomerGroupID. (User Postage Statement ID: %%1).	Postage Statement Messages
8235	AdPercent in the DocumentVersionData block must contain less than or equal to 2 decimal characters. (User Postage Statement ID: %%1).	Postage Statement Messages
8236	AdPercent in the DocumentVersionData block must be populated with the same value as the AdvertisingPercentage in the CreatePeriodicalStatementData block. (User Postage Statement ID: %%1).	Postage Statement Messages
8237	RateAffixed in the DocumentVersionData block must contain less than or equal to 3 decimal characters. (User Postage Statement ID: %%1).	Postage Statement Messages
8238	RateAffixed in the DocumentVersionData block is not required when the PermitType in the PermitPublicationData block within the CreatePeriodicalStatementData block is populated with PI. (User Postage Statement ID: %%1).	Postage Statement Messages
8239	PermitType in the PermitPublicationData block in the PublisherData block in the CreatePeriodicalStatementData block must be populated with PP. (User Postage Statement ID: %%1).	Postage Statement Messages

Copyright © 2011 USPS®. All Rights Reserved.

Error Code	Error Message	Messages
8240	PendingPostageAmount in the CreatePeriodicalStatementData block is required when the PermitType in the PermitPublicationData block within the CreatePeriodicalStatementData block is populated with PP. (User Postage Statement ID: %%1).	Postage Statement Messages
8241	PendingPostageAmount in the CreatePeriodicalStatementData block must contain exactly 2 decimal characters. (User Postage Statement ID: %%1).	Postage Statement Messages
8242	MailingGroupID and CustomerGroupID in the PeriodicalStatementCreateRequest message must be the same values as the MailingGroupID and CustomerGroupID of an accepted OpenMailingGroupRequest message. (User Postage Statement ID: %%1).	Postage Statement Messages
8243	RateCategory in the PeriodicalLineItemData block and ChargeableContainerLevel in the PeriodicalLineItemData block cannot be populated in the same line. (User Postage Statement ID: %%1).	Postage Statement Messages
8244	RateCategory in the PeriodicalLineItemData block and Zone in the PeriodicalLineItemData block cannot be populated in the same line. (User Postage Statement ID: %%1).	Postage Statement Messages
8245	Containers in the PeriodicalLineItemData block and Bundles in the PeriodicalLineItemData block cannot be populated in the same line. (User Postage Statement ID: %%1).	Postage Statement Messages
8246	RateCategory in the PeriodicalLineItemData block and PeriodicalPrice in the PeriodicalLineItemData block cannot be populated in the same line. (User Postage Statement ID: %%1).	Postage Statement Messages
8247	ChargeableContainerLevel in the PeriodicalLineItemData block and PeriodicalPrice in the PeriodicalLineItemData block cannot be populated in the same line. (User Postage Statement ID: %%1).	Postage Statement Messages
8248	The Pending Periodical PermitZIP+4 or Periodical Publication number must map to the same finance number as the OpenMailingGroupRequest for a specified MailingGroupID and CustomerGroupID and must be active. (User Postage Statement ID: %%1).	Postage Statement Messages
8250	PeriodicalStatementCreateRequest must be accepted prior to submitting the PeriodicalStatementQueryRequest message for the specified MailingGroupID, CustomerGroupID, and StatementID.	Postage Statement Messages
8252	Postage StatementID in the PeriodicalStatementQueryRequest message must match the StatementID provided in the PeriodicalStatementCreateResponse message for the specified MailingGroupID and CustomerGroupID.	Postage Statement Messages
8255	AdvertisingPercentage in the PeriodicalStatement block must contain less than or equal to 2 decimal characters. (User Postage Statement ID: %%1).	Postage Statement Messages
8258	CarrierRouteAddressMatchingDate in the PeriodicalStatement block is required when the RateCategory in the LineItemSummaryData block is populated with A, B, or D. (User Postage Statement ID: %%1).	Postage Statement Messages
8259	CarrierRouteAddressMatchingDate in the PeriodicalStatement block is required when the RateCategory in the PeriodicalLineItemData block is populated with A, B, or D. (User Postage Statement ID: %%1).	Postage Statement Messages

Copyright © 2011 USPS®. All Rights Reserved.

Error Code	Error Message	Messages
8260	CarrierRouteSequencingDate in the PeriodicalStatement block is required when the RateCategory in the LineItemSummaryData block is populated with A, AF, B, BF, D, or DF. (User Postage Statement ID: %%1).	Postage Statement Messages
8261	CarrierRouteSequencingDate in the PeriodicalStatement block is required when the RateCategory in the PeriodicalLineItemData block is populated with A, B, or D. (User Postage Statement ID: %%1).	Postage Statement Messages
8262	CopyWeight in the PeriodicalStatement block must contain less than or equal to 4 decimal characters. (User Postage Statement ID: %%1).	Postage Statement Messages
8263	FormType in the PeriodicalStatement block must be populated with PE. (User Postage Statement ID: %%1).	Postage Statement Messages
8264	PostagePaymentMethod in the PeriodicalStatement block must be populated with P. (User Postage Statement ID: %%1).	Postage Statement Messages
8265	ProcessingCategory in the PeriodicalStatement block must be populated with LT, FL, IR, MP, or NP. (User Postage Statement ID: %%1).	Postage Statement Messages
8267	SingleRideAlongWeight in the PeriodicalStatement block is required when the PeriodicalPrice in the PeriodicalLineItemData block is populated with 9. (User Postage Statement ID: %%1).	Postage Statement Messages
8268	SingleRideAlongWeight in the PeriodicalStatement block must contains less than or equal to 4 decimal characters. (User Postage Statement ID: %%1).	Postage Statement Messages
8272	AgencyCostCode in the PeriodicalStatement block must contain 6 characters when mapped to USPS. (User Postage Statement ID: %%1).	Postage Statement Messages
8273	AdPercent in the DocumentVersionData block must be populated with the same value as the AdvertisingPercentage in the PeriodicalStatement block. (User Postage Statement ID: %%1).	Postage Statement Messages
8274	RateAffixed in the DocumentVersionData block is not required when the PermitType in the PermitPublicationData block within the PeriodicalStatement block is populated with PI. (User Postage Statement ID: %%1).	Postage Statement Messages
8275	PermitType in the PermitPublicationData block within the ConsolidatedPeriodicalStatementCreateRequest message must be populated with PP.	Postage Statement Messages
8276	PendingPostageAmount in the PeriodicalStatement block is required when the PermitType in the PermitPublicationData block within the PeriodicalStatement block is populated with PP. (User Postage Statement ID: %%1).	Postage Statement Messages
8277	PendingPostageAmount in the PeriodicalStatement block must contain exactly 2 decimal characters. (User Postage Statement ID: %%1).	Postage Statement Messages
8279	Bundles in the PeriodicalLineItemData block of the CreateConsolidatedPeriodicalStatementData block must contain less than or equal to 4 decimal characters. (User Postage Statement ID: %%1).	Postage Statement Messages

Copyright © 2011 USPS®. All Rights Reserved.

Error Code	Error Message	Messages
8281	MailingGroupID and CustomerGroupID in the ConsolidatedPeriodicalStatementCreateRequest message must be the same values as the MailingGroupID and CustomerGroupID of an accepted OpenMailingGroupRequest message. (User Postage Statement ID: %%1).	Postage Statement Messages
8282	QualificationReportSummaryCreateRequest/ QualificationReportDetailCreateRequest message must be accepted before submitting the ContainerBundleReportCreateRequest message for the specified MailingGroupID and CustomerGroupID.	ContainerBundleQueryResponse
8283	Either the SackTrayContainerVersionRecord block, the PalletContainerVersionRecord block, or the BundleVersionRecord block is required when the ContainerBundleVersionRecords block is sent.	ContainerBundleQueryResponse
8286	Either the SackTrayContainerRecord block, the PalletContainerRecord block, or the BundleRecord block is required when the ContainerBundleSummaryRecords block is sent.	ContainerBundleQueryResponse
8288	ContainerBundleReportCreateRequest message can only be provided when the FormType in the QualificationReportSummaryCreateRequest/ QualificationReportDetailCreateRequest message is PE.	ContainerBundleQueryResponse
8289	Containers field in the SackTrayContainerVersionRecord block in the ContainerBundleVersionRecords block must contain less than or equal to 4 decimal characters.	ContainerBundleQueryResponse
8290	Containers field in the PalletContainerVersionRecord block in the ContainerBundleVersionRecords block must contain less than or equal to 4 decimal characters.	ContainerBundleQueryResponse
8291	Bundles field in the BundleVersionRecord block in the ContainerBundleVersionRecords block must contain less than or equal to 4 decimal characters.	ContainerBundleQueryResponse
8292	Containers field in the SackTrayContainerRecord block in the ContainerBundleSummaryRecords block must contain less than or equal to 4 decimal characters.	ContainerBundleQueryResponse
8293	Containers field in the PalletContainerRecord block in the ContainerBundleSummaryRecords block must contain less than or equal to 4 decimal characters.	ContainerBundleQueryResponse
8294	Bundles field in the BundleRecord block in the ContainerBundleSummaryRecords block must contain less than or equal to 4 decimal characters.	ContainerBundleQueryResponse
8295	The specified combination of MailingGroupID and CustomerGroupID in the ContainerBundleReportHeaderInfo block must match the values as that of the open mailing group.	ContainerBundleQueryResponse
8296	ContainerBundleReportCreateRequest message must be accepted before submitting the ContainerBundleReportQueryRequest message for the specified MailingGroupID and CustomerGroupID.	ContainerBundleReportQueryResponse
8297	CustomerGroupID and MailingGroupID must exist for an accepted ContainerBundleReportCreateRequest message.	ContainerBundleReportQueryResponse
8298	ContainerBundleReportCreateRequest message must be accepted before submitting the ContainerBundleCancelRequest message for the specified MailingGroupID and CustomerGroupID.	ContainerBundleReportCancelResponse

Copyright © 2011 USPS®. All Rights Reserved.

Error Code	Error Message	Messages
8299	The specified combination of CustomerGroupID and MailingGroupID must be populated with the same combination of CustomerGroupID and MailingGroupID as an accepted ContainerBundleReportCreateRequest message.	ContainerBundleReportCancelResponse
8300	QualificationReportSummaryCreateRequest/ QualificationReportDetailCreateRequest message must be accepted before submitting the MailPieceCreateRequest message to create a mail piece for the specified MailingGroupID and CustomerGroupID. (PieceID not found: %%1)	MailPieceCreateResponse
8301	QualificationReportSummaryCreateRequest/ QualificationReportDetailCreateRequest message must be accepted before submitting the MailPieceCreateRequest message to create a piece range for the specified MailingGroupID and CustomerGroupID. (PieceRangeID not found: %%1)	MailPieceCreateResponse
8302	LOTSequenceDirectionCode in the MailPieceBlock must be populated when combined with the LOTSequenceNumber is populated and when Carrier Route LOT is used. (Piece ID: %%1).	Multiple
8304	LOTSequenceNumber in the MailPieceBlock must be populated when the LOTSequenceDirection is populated.	Multiple
8306	WalkSequenceNumber in the MailPieceBlock must be populated when Carrier Route LOT is used and the LOTSequenceDirection is not populated.	Multiple
8307	DeliveryPointZIP in the MailPieceBlock block must contain 0, 5, 9, or 11 characters.	MailPieceCreateResponse
8309	DeliveryPointZIP in the MailPieceBlock block must be populated when the IMB block is not used and combined with the PlanetCode field. (Piece ID: %%1)	MailPieceCreateResponse
8310	MailerID6 in the IMbarcodeUpperSerialization block in the MailXMLPieceRangeBlock must match the MailerID6 in the IMbarcodeLowerSerialization block in the MailXMLPieceRangeBlock.(Piece Range ID is %%1)	Multiple
8311	MailerID9 in the IMbarcodeUpperSerialization block in the MailXMLPieceRangeBlock must match the MailerID9 in the IMbarcodeLowerSerialization block in the MailXMLPieceRangeBlock.(Piece Range ID is %%1)	Multiple
8312	SerialNumber6 in the IMbarcodeUpperSerialization block must be populated with a value greater than or equal to the SerialNumber6 in the IMbarcodeLowerSerialization block. (Piece Range ID is %%1)	Multiple
8313	SerialNumber9 in the IMbarcodeUpperSerialization block must be populated with a value greater than or equal to the SerialNumber9 in the IMbarcodeLowerSerialization block. (Piece Range ID is %%1)	Multiple
8314	MailerID6 fields must be blank when the ServiceLevelIndicator is populated with P. (piece_range_id: %%1)	MailPieceCreateResponse
8315	MailerID9 must be blank when the ServiceLevelIndicator is populated with P. (Found: %%1)	MailPieceCreateResponse
8316	SerialNumber6 must be blank when the ServiceLevelIndicator is populated with P. (Found: %%1)	MailPieceCreateResponse
8317	SerialNumber9 must be blank when the ServiceLevelIndicator is populated with P. (Found: %%1)	MailPieceCreateResponse

Copyright © 2011 USPS®. All Rights Reserved.

Error Code	Error Message	Messages
8318	The specified combination of MailingGroupID and CustomerGroupID in the MailPieceCreateRequest message must match the values of the accepted OpenMailingGroupRequest message.	MailPieceCreateResponse
8319	MailPieceCreateRequest must be accepted to create a mail piece before submitting a MailPieceUpdateRequest message for the specified MailingGroupID and CustomerGroupID.	MailPieceUpdateResponse
8320	MailPieceCreateRequest must be accepted to create a piece range before submitting a MailPieceUpdateRequest message for the specified MailingGroupID and CustomerGroupID.	MailPieceUpdateResponse
8325	MailPieceCreateRequest must be accepted to create a mail piece before submitting a MailPieceCancelRequest message for the specified MailingGroupID and CustomerGroupID.	MailPieceCancelResponse
8326	MailPieceCreateRequest must be accepted to create a piece range before submitting a MailPieceCancelRequest message for the specified MailingGroupID and CustomerGroupID.	MailPieceCancelResponse
8329	MailPieceBlock in the MailPieceCancelRequest message must be populated with the same values as the fields within the MailPieceBlock of the MailPieceCreateRequest message for the specified combination of MailingGroupID and CustomerGroupID.	MailPieceCancelResponse
8330	MailXMLPieceRangeBlock in the MailPieceCancelRequest message must be populated with the same values as the fields within the MailXMLPieceRangeBlock of the MailPieceCreateRequest message for the specified combination of MailingGroupID and CustomerGroupID.	MailPieceCancelResponse
8332	PostageStatementCreateRequest or PeriodicalStatementCreateRequest message must be accepted before submitting the PostageAdjustmentCreateRequest for the specified MailingGroupID and CustomerGroupID.	Postage Statement Messages
8333	StatementID in the PostageAdjustment block must be populated with the same value as the StatementID in the PostageStatementCreateResponse or PeriodicalStatementCreateResponse for a specified MailingGroupID and CustomerGroupID. (Statment ID: %%1)	Postage Statement Messages
8334	AdjustmentAmount in the PostageAdjustment block must contain less than or equal to 2 decimal characters. (Statment ID: %%1)	Postage Statement Messages
8335	AdjustmentAmount field in the PostageAdjustment block must be less than the PostageAmount field in the PostageStatementCreateRequest message or PeriodicalStatementCreateRequest message. (Statment ID: %%1)	Postage Statement Messages
8336	TotalPiecesAffected field within the PostageAdjustment block must be less than the TotalPieces field in the PostageStatementCreateRequest message or PeriodicalStatementCreateRequest message. (Statment ID: %%1)	Postage Statement Messages
8337	UserPostageStatementID in the PostageAdjustment block must be populated with the same value as the UserPostageStatementID in the PostageStatementCreateResponse message or the PeriodicalStatementCreateResponse message. (Statment ID: %%1)	Postage Statement Messages

Copyright © 2011 USPS®. All Rights Reserved.

Error Code	Error Message	Messages
8338	AdjustmentDate in the PostageAdjustment block must be populated with a date later than the latest mailing date for the specified StatementID, MailingGroupID and CustomerGroupID. (Statment ID: %%1)	Postage Statement Messages
8339	PostageAdjustment block AdjustmentAmount must be less than the TotalPostage generated by the system on the PostageStatementCreateRequest or PeriodicalStatementCreateRequest for a specified MailingGroupID and CustomerGroupID. (Statment ID: %%1)	Postage Statement Messages
8342	Mail.dat Job ID: %%1 and User License Code: %%2 not found. Values must be populated with the same value in the .hdr file from the original Mail.dat submission.	ContainerUpdateResponse
8343	ContainerID %%1 must be populated with the same value as the Container ID in the .csm file from the original Mail.dat job submission for the specified CRID.	ContainerUpdateResponse
8344	UniqueContainerBarcode %%1 must be populated with same value as the Label: IM Container Or IM Tray Barcode field in the .csm file from the original Mail.dat job submission for the specified CRID.	ContainerUpdateResponse
8345	EntryPointEDPostalCode must contain exactly 5 characters (Container ID: %%1).	ContainerUpdateResponse
8346	EntryPointEDPostalCode is required when the EntryPointEDFacilityType is populated. (Container ID: %%1)	ContainerUpdateResponse
8347	EntryPointEDFacilityType is required when the EntryPointEDPostalCode is populated. (Container ID: %%1)	ContainerUpdateResponse
8348	EntryPointADLocaleKey must contain exactly 6 characters. (Container ID: %%1)	ContainerUpdateResponse
8349	EntryPointADLocaleKey is required when the EntryPointADPostalCode is populated. (Container ID: %%1)	ContainerUpdateResponse
8350	EntryPointADPostalCode is required when the EntryPointADLocaleKey is populated. (Container ID: %%1)	ContainerUpdateResponse
8351	ParentContainerReferenceID is required when a Parent Container exists. (Container ID: %%1)	ContainerUpdateResponse
8352	ContainerStatus previously populated with C can only be updated to R or D for the specified CRID. (Container ID: %%1)	ContainerUpdateResponse
8353	ContainerStatus previously populated with D cannot be updated for the specified CRID. (Container ID: %%1)	ContainerUpdateResponse
8354	ContainerStatus previously populated with R can only be updated to D, X, T, or C for the specified CRID. (Container ID: %%1)	ContainerUpdateResponse
8355	ContainerStatus previously populated with T can only be updated to D, X, or C for the specified CRID. (Container ID: %%1)	ContainerUpdateResponse
8356	ContainerStatus previously populated with X can only be updated to T for the specified CRID. (Container ID: %%1)	ContainerUpdateResponse
8358	IMBarcode field must be populated with either 21 or 24 characters. (Container ID: %%1)	ContainerUpdateResponse
8360	ContainerStatus cannot be updated to R when the Container Status of the original Mail.dat submission is populated with R. (Container ID: %%1)	ContainerUpdateResponse
8361	StopDesignator field cannot be updated when updating an original Mail.XML job. (Container ID: %%1)	ContainerUpdateResponse

Copyright © 2011 USPS®. All Rights Reserved.

Error Code	Error Message	Messages
8362	The StopDesignator field can only be updated when the ContainerStatus in the SummaryRecordUpdate block of the ContainerUpdateRequest message is populated with T. (Container ID: %%1, ContainerStatus: %%2)	ContainerUpdateResponse
8363	The TruckDispatchNumber field can only be updated when the ContainerStatus in the SummaryRecordUpdate block of the ContainerUpdateRequest message is populated with T. (Container ID: %%1, ContainerStatus: %%2)	ContainerUpdateResponse
8378	ServiceLevelIndicator in at least one ContainerDetailData block must be populated with F when the FullServiceParticipationIndicator in the MailingGroupData block of the OpenMailingGroupRequest message is populated with M.	QualificationReportCreateResponse, QualificationReportDetailCreateResponse (10.0)
8379	ServiceLevelIndicator in the ContainerDetailData block must be populated with F when the FullServiceParticipationIndicator in the MailingGroupData block of the OpenMailingGroupRequest message is populated with F.	QualificationReportCreateResponse, QualificationReportDetailCreateResponse (10.0)
8380	At least one QualificationReportSummaryCreateRequest/ QualificationReportDetailCreateRequest ContainerInfoData block must have a ContainerType of L or M if the LogicalPhysicalIndicator in the OpenMailingGroupRequest is L, MailXMLPresentationCategory is P, FullServiceParticipationIndicator is F or M.	QualificationReportCreateResponse
8381	ContainerType must be populated with S, 1, 2, 3, 4, 5, E, F, O, T, B, U, Z, P, H, A, G, D, R, or C if the LogicalPhysicalContainerIndicator in the OpenMailingGroupRequest message is populated with P and FullServiceParticipationIndicator is F or M.	QualificationReportCreateResponse, QualificationReportDetailCreateResponse (10.0)
8382	FormType in the QualifcationReport block must be populated with FC, SM, BP, or PE when the FullServiceParticipationIndicator in the MailingGroupData block of the OpenMailingGroupRequest message is populated with F or M.	QualificationReportCreateResponse, QualificationReportSummaryCreateResponse (10.0)
8383	ContainerInfoData block ProcessingCategory must be LT, FL, or CD when the QualificationReport block FormType is FC and FullServiceParticipationIndicator in the MailingGroupData block is F or M for the specified MailingGroupID and CustomerGroupID.	QualificationReportCreateResponse, QualificationReportDetailCreateRespone (10.0)
8384	ContainerInfoData block ProcessingCategory must be populated with LT or FL when the QualificationReport block FormType is SM and FullServiceParticipationIndicator in the MailingGroupData block is F or M for a specified MailingGroupID and CustomerGroupID.	QualificationReportCreateResponse, QualificationReportDetailCreateRespone (10.0)
8385	ContainerInfoData block ProcessingCategory must be populated with LT or FL when the QualificationReport block FormType is PE and FullServiceParticipationIndicator in the MailingGroupData block is F or M for a specified MailingGroupID and CustomerGroupID.	QualificationReportCreateResponse, QualificationReportDetailCreateRespone (10.0)

Copyright © 2011 USPS®. All Rights Reserved.

Error Code	Error Message	Messages
8386	ContainerInfoData block ProcessingCategory must be populated with FL when the QualificationReport block FormType is BP and FullServiceParticipationIndicator in the MailingGroupData block is F or M for the specified MailingGroupID and CustomerGroupID.	QualificationReportCreateResponse, QualificationReportDetailCreateResponse (10.0)
8387	CSAID is required when mail is DMU verified, mail is origin-entered, and FullServiceParticipationIndicator in the MailingGroupData block is F or M.	QualificationReportCreateResponse, QualificationReportDetailCreateResponse (10.0)
8388	CSAID is required when the mailer is a large volume mailer, mail is entered at a BMEU at an agreed upon time prior to CET, and FullServiceParticipationIndicator in the MailingGroupData block is F or M. (Container ID %%1)	QualificationReportCreateResponse, QualificationReportDetailCreateResponse (10.0)
8390	CSAID is required when the EntryPointFacilityType in the ContainerInfoData block is populated with O and the ConsigneeApptID in the ContainerInfoData block is populated and FullServiceParticipationIndicator in the MailingGroupData block is F or M.	QualificationReportCreateResponse, QualificationReportDetailCreateResponse (10.0)
8392	ScheduledInductionDateTime is required when the ConsigneeApptID in the ContainerInfoData block is populated and FullServiceParticipationIndicator in the MailingGroupData block is F or M. (Container ID: %%1).	QualificationReportCreateResponse, QualificationReportDetailCreateResponse (10.0)
~~8394~~	~~ScheduledInductionDateTime is required when the CSAID in the ContainerInfoData block is populated and the USPSPickup field in the ContainerInfoData block is populated with N and FullServiceParticipationIndicator in the MailingGroupData block is F or M.~~	~~QualificationReportCreateResponse~~
8396	ScheduledShipDateTime is required when the EntryPointFacilityType is O, USPSPickup is populated with Y, and FullServiceParticipationIndicator in the MailingGroupData block is F or M.	QualificationReportCreateResponse, QualificationReportDetailCreateResponse (10.0)
8399	ContainerDetailData block TotalPieces must be 0 when the ContainerDetailData block is provided, ContainerInfoData block SiblingContainerID is populated, and MailingGroupData block FullServiceParticipationIndicator is F or M. (Container ID: %%1)	QualificationReportCreateResponse, QualificationReportDetailCreateResponse (10.0)
8400	ContainerBarcode must be populated with 21 characters when the ContainerType in the ContainerInfoData block is populated with B, U, P, H, A, G, D, R, or C and FullServiceParticipationIndicator in the MailingGroupData block is F or M.	QualificationReportCreateResponse, QualificationReportDetailCreateResponse (10.0)
8401	ContainerBarcode must be populated with 24 characters when the ContainerType in the ContainerInfoData block is populated with S, 1, 2, 3, 4, 5, E, F, O, or T and FullServiceParticipationIndicator in the MailingGroupData block is F or M.	QualificationReportCreateResponse, QualificationReportDetailCreateResponse (10.0)

Copyright © 2011 USPS®. All Rights Reserved.

Error Code	Error Message	Messages
8402	UniqueContainerBarcode is required when the SiblingContainerCreateRequest ContainerType is B, U, P, H, A, G, D, R, C, S, 1, 2, 3, 4, 5, E, F, O, or T and the Full-Service Participation Indicator in the .seg file is F or M. (ContainerID: %%1)	SiblingContainerCreateResponse
8405	BarcodeID in the IMB block is required when the MailPieceBlock is provided.	MailPieceCreateResponse
8406	ServiceTypeCode field is required when the MailPieceBlock is provided and the MailClass in the IMB block is not populated.	MailPieceCreateResponse
8407	MailClass field is required when the MailPieceBlock is provided and the ServiceTypeCode in the IMB block is not populated.	MailPieceCreateResponse
8412	DeliveryPointZIP in the IMB block is required when the IMB block is provided. (Piece_id: %%1)	MailPieceCreateResponse
8413	At least one of CRID, MailerID6, MailerID9, PermitNumber or PublicationNumber in the QualificationReportPreparer block must be populated when the FullServiceParticipationIndicator in the OpenMailingCreateRequest is F or M	QualificationReportCreateResponse, QualificationReportSummaryCreateResponse (10.0)
8414	At least one of CRID, MailOwnerMID6, MailOwnerMID9, PermitNumber, or PublicationNumber in the MailOwner block of the MailPieceCreateRequest message must be populated when the MailPieceBlock is populated and the MailPieceBlock ServiceLevelIndicator is F.	MailPieceCreateResponse
8416	At least one of CRID, MailerID6, or MailerID9 in the MailOwner block of the MailPieceCreateRequest message must be populated when the MailXMLRangeBlock is populated	MailPieceCreateResponse
8417	MailerID9 must be populated with the same value as the MailerID9 in the IMbarcodeLowerSerialization block when submitted instead of the MailerID6. (ContainerID: %%1)	MailPieceCreateResponse
8418	MailerID6 must be populated with the same value as the MailerID6 in the IMbarcodeLowerSerialization block when submitted instead of the MailerID9. (ContainerID: %%1)	MailPieceCreateResponse
8419	For all Full-Service MailXMLPieceRangeBlocks, the sum of the IMbarcodeUpperSerialization minus the IMbarcodeLowerSerialization plus one must be between the smaller of the sum of Pieces or Copies and 20% more than the larger of the sum of Pieces or Copies.	MailPieceCreateResponse
8420	IMbarcodeUpperSerialization subtracted by the IMbarcodeLowerSerialization must equal the piece count and copy count when the PieceRange block is provided.	MailPieceUpdateResponse
8421	The number of MailPieceBlocks associated to a ContainerID must equal the sum or between TotalPieces and TotalCopies in the ContainerDetailData block in the Qual Report for the ContainerID, MailingGroupID, and CustomerGroupID. (Container ID: %%1)	MailPiececreateResponse
8422	The number of pieces in PieceRangeBlocks associated to a ContainerID cannot exceed the value in the ContainerDetailData block TotalPieces when the PieceRange Block is populated for a specified MailingGroupID and CustomerGroupID. (Container ID: %%1)	MailPieceCreateResponse
8423	PostageStatementLineItemData block is required when the FullServiceParticipationIndicator in the MailingGroupData block is populated with F or M.	Postage Statement Messages

Copyright © 2011 USPS®. All Rights Reserved.

Error Code	Error Message	Messages
~~8425~~	~~When the FullServiceParticipationIndicator in the MailingGroupData block is populated with F or M, the MailPieceCreateRequest message must be accepted before submitting the PostageStatementCreateRequest message.~~	~~MailPieceCreateResponse~~
8427	The pieces associated to a ContainerID in the Postage-, Periodical-, or ConsolidatedPeriodicalStatementCreateRequest message cannot exceed the sum of TotalPieces for that ContainerID in the Qualification Report (ContainerID %%1).	Postage Statement Messages
8428	MailXMLPieceBlock ServiceLevelIndicator must be F when the ContainerDetailData block ServiceLevelIndicator fields are all populated with F for the specified ContainerID within a specified MailingGroupID and CustomerGroupID. (ContainerID: %%1)	Multiple Messages
8429	MailXMLPieceRangeBlock ServiceLevelIndicator must be F when the ContainerDetailData block ServiceLevelIndicator fields are all populated with F for the specified ContainerID within a specified MailingGroupID and CustomerGroupID. (ContainerID: %%1)	MailPieceCreateResponse
8432	QualificationReportSummaryCreateRequest/ QualificationReportDetailCreateRequest message must be accepted before submitting the PostageStatementCreateRequest message as for the specified MailingGroupID and CustomerGroupID when the FullServiceParticipationIndicator is F.	Postage Statement Messages
8434	ServiceLevelIndicator in the PieceRangeBlock must be populated with F, B, P, or O when the FullServiceParticipationIndicator field within the MailingGroupData block is M.	MailPieceCreateResponse
8435	At least one PieceRangeBlock must have the ServiceLevelIndicator field populated with F when the FullServiceParticipationIndicator field within the MailingGroupData block is populated with M.	MailPieceCreateResponse
8436	ServiceLevelIndicator in the ContainerDetailData block must be populated with F, B, P, or O when the FullServiceParticipationIndicator field within the MailingGroupData block is M.	QualificationReportCreateResponse, QualificationReportDetailCreateResponse (10.0)
8438	ContainerType must be populated with L when the PresentationCategory is populated with M and LogicalPhysicalContainerIndicator is populated with L in the MailingGroupData block.	QualificationReportCreateResponse, QualificationReportDetailCreateResponse (10.0)
8439	ContainerType must be populated with E, F, O, M, P, T, H, A, G, D, R or C in the ContainerInfoData block when another ContainerType field in the ContainerInfoData block is populated with L for the specified MailingGroupID and CustomerGroupID.	QualificationReportCreateResponse, QualificationReportDetailCreateResponse (10.0)
8440	At least one ContainerDetailData block must exist for each ContainerInfoData block in the Qual Reportwhen the ContainerType is L and the OpenMailingGroupRequest MailXMLPresentationCategory is M for the specified MailingGroupID and CustomerGroupID.	QualificationReportCreateResponse, QualificationReportDetailCreateResponse (10.0)
8441	CustomerQualificationReportID field in the QualificationReport block is required when the MailXMLPresentationCategory field within the MailingGroupData block of the OpenMailingGroupRequest message is M.	QualificationReportCreateResponse

Copyright © 2011 USPS®. All Rights Reserved.

Error Code	Error Message	Messages
8443	CustomerQualificationReportID field in the QualificationReport block is required for a MLOCR One-Pass mailing.	QualificationReportCreateResponse
8444	The OnePassPlannedOrActualFlag in the QualificationReportSummaryCreateRequest/ QualificationReportDetailCreateRequest message is required when the OnePassIndicator field in the OpenMailingGroupRequest message is Yes for the specified MailingGroupID and CustomerGroupID.	QualificationReportCreateResponse
8445	PostageStatementLineItemData Containers for an MLOCR mailing must be in the QualificationReportSummaryCreateRequest/ QualificationReportDetailCreateRequest message when the OnePassPlannedOrActualFlag is A for the specified MailingGroupID and CustomerGroupID. (ContainerID %%1 was not found)	Postage Statement Messages
8446	Mailing must be a One Pass MLOCR when OnePassPlannedOrActualFlag in the QualificationReportSummaryCreateRequest/ QualificationReportDetailCreateRequest message is populated with A in the second submission for the specified MailingGroupID and CustomerGroupID.	QualificationReportCreateResponse
8449	FormType in the QualificationReport bock must be FC for First-Class or SM for Standard Mail.	QualificationReportCreateResponse
8451	No more than one LineItemSummaryData block in the CreatePostageStatement block can have the RateCategory populated with S for the specified MailingGroupID and CustomerGroupID.	Postage Statement Messages
8452	PostageAdjustmentCreateRequest message cannot be submitted for MLOCR mailings.	Postage Statement Messages
8453	ProcessingCategory must be LT, FL, or CD when the FormType in the QualificationReport block is FC and MailXMLPresentationCategory in the MailingGroupData block is M for the specified MailingGroupID and CustomerGroupID.	QualificationReportCreateResponse
8454	DocumentVersionData or -DataWithPermit PieceWeight cannot exceed 13oz when the QualificationReportSummaryCreateRequest/ QualificationReportDetailCreateRequest FormType is FC and the ProcessingCategory is FL.	QualificationReportCreateResponse
8456	PostagePaymentMethod in the PostageStatementCreateRequest must be P or M when the FormType is FC and ProcessingCategory is FL for the specified MailingGroupID and CustomerGroupID.	Postage Statement Messages
8460	ProcessingCategory in the ContainerInfoData block must be populated with LT when the FormType QualificationReport block is populated with SM for an MLOCR mailing.	QualificationReportCreateResponse
8461	PieceWeight in the DocumentVersionData block or the DocumentVersionDataWithPermit block must be less than or equal to 3.3 ounces when the ProcessingCategory is LT and FormType is SM in the QualificationReportSummaryCreateRequest/ QualificationReportDetailCreateRequest message.	QualificationReportCreateResponse
8467	PostageAffixedAmount must be populated with a value greater than 0 when the PostagePaymentMethod in the CreatePostageStatement block is populated with M or S.	Postage Statement Messages

Copyright © 2011 USPS®. All Rights Reserved.

Error Code	Error Message	Messages
8469	MeteredAffixedMethod is required when the PostagePaymentMethod in the CreatePostageStatement block is populated with M.	Postage Statement Messages
8470	PermitHolderData block in the CreatePostageStatement block is required when the PostagePaymentMethod in the CreatePostageStatement block is populated with M or S.	Postage Statement Messages
8475	StatementID in the PostageAdjustment block must be populated with a value that references a postage statement where the Stage is not populated with FIN. (Statment ID: %%1)	Postage Statement Messages
8480	StatementID in the PostageAdjustment block must be populated with a value that references a postage statement that has not already been adjusted. (Statment ID: %%1)	Postage Statement Messages
8481	A PeriodicalStatementCreateRequest must be accepted before sumbitting a PostageStatementCreateRequest message with the EnclosedBy field set to PE for the same MailingGroupID and CustomerGroupID.	Postage Statement Messages
8482	OpenMailingGroupRequest message must be accepted before submitting the PeriodicalStatementCreateRequest for the specified MailingGroupID and CustomerGroupID.	Periodical Postage Statement Messages
8485	ProcessingCategory must be populated with FL, NP, MP, or IR when the FormType is BP.	Multiple
8486	Zone must be populated with N, 1, 3, 4, 5, 6, 7, 8, DDU or SCF when FormType is BP and Processing Category is FL, MP, IR, or NP.	Multiple
8490	EntryDiscount must be populated with N, B, S or D when FormType is BP.	Multiple
8491	RateCategory must be populated with D, N, or S when the FormType is BP.	Postage Statement Messages
8492	SurchargeType must be populated with N when the FormType is BP.	Postage Statement Messages
8493	WeightBreakType must be populated with N when the FormType is BP.	Postage Statement Messages
8494	BarcodeRate must be populated with Y or N when the FormType is BP.	Postage Statement Messages
8497	PostagePaymentMethod must be populated with P when the FormType is BP.	Postage Statement Messages
8498	RateType must be populated with B when FormType is BP.	Postage Statement Messages
8500	SinglePieceWeight must be populated with a value less than or equal to 15 pounds when the FormType is BP.	Postage Statement Messages
8501	TotalPieces and TotalCopies must be populated with the same values when FormType is BP.	Multiple
8502	ServiceCode must be populated with COD, COM, DC, IM, PAL, RD, RR, RRE, RRM, SC, or SH when FormType is BP.	Postage Statement Messages

Copyright © 2011 USPS®. All Rights Reserved.

Error Code	Error Message	Messages
8503	ProcessingCategory must be populated with LT, FL, CD, or PF when FormType is FC.	Multiple
8504	Zone must be populated with N when FormType is FC and ProcessingCategory is LT, FL, CD, or PF.	Multiple
8505	RateType must be populated with R or M when FormType is FC and ProcessingCategory is LT.	Postage Statement Messages
8506	RateCategory must be populated with E, H, L1, L2, N, PR, or S when FormType is FC and ProcessingCategory is LT.	Postage Statement Messages
8507	RateType must be populated with R or M when FormType is FC and ProcessingCategory is FL.	Postage Statement Messages
8508	RateCategory must be populated with E, H, L3, L4, N, PR, or S when FormType is FC and ProcessingCategory is FL.	Postage Statement Messages
8509	RateType must be populated with R or M when FormType is FC and ProcessingCategory is CD.	Postage Statement Messages
8510	RateCategory must be populated with E, H, L1, L2, N, or S when FormType is FC and ProcessingCategory is CD.	Postage Statement Messages
8511	RateType must be populated with R when FormType is FC and ProcessingCategory is PF.	Postage Statement Messages
8512	RateCategory must be populated with E, G, H, K, L3, L4, L5, L6, S, or N when FormType is FC and ProcessingCategory is PF.	Postage Statement Messages
8513	EntryDiscount must be populated with N when FormType is FC.	Postage Statement Messages
8515	SurchargeType must be populated with A, E, N, R or L when FormType is FC.	Postage Statement Messages
8516	WeightBreakType must be populated with A, B, or N when provided and when the FormType is FC.	Postage Statement Messages
8517	SinglePieceWeight must be populated with a value greater than 0.0625 pounds when FormType is FC and SurchargeType is E and WeightBreakType is A.	Postage Statement Messages
8518	SinglePieceWeight must be populated with a value less than or equal to 0.0625 pounds when FormType is FC and SurchargeType is E and WeightBreakType is B.	Postage Statement Messages
8519	BarcodeRate must be populated with N or O when FormType is FC.	Postage Statement Messages
8520	EntryFacilityType must be populated with O, B, S, or D when FormType is FC.	Postage Statement Messages
8521	PackagingMethod must be populated with 0, 1, or Blank when FormType is FC.	Postage Statement Messages

Copyright © 2011 USPS®. All Rights Reserved.

Error Code	Error Message	Messages
8522	PostagePaymentMethod must be populated with S, M, or P when FormType is FC.	Postage Statement Messages
8524	MoveUpdateMethod must be populated with ASE, ACS, ALT, FAST, MULT, or NCOA when FormType is SM.	Postage Statement Messages
8525	EnclosedBy must be populated with SM, BP, PE, or ML when FormType is FC.	Postage Statement Messages
8526	ServiceCode must be populated with SH, COM, COD, RR, RM, SC, DC, RRE, CM, IM, or RD when FormType is FC.	Postage Statement Messages
8527	ProcessingCategory must be populated with PF when FormType is FC and ServiceCode is SC.	Postage Statement Messages
8528	ProcessingCategory must be populated with FL, MP, NP, or IR when FormType is ML.	Multiple
8529	Zone must be populated with N when FormType is ML and ProcessingCategory is MP or IR.	Multiple
8530	ProcessingCategory must be populated with FL, MP, or IR when FormType is ML and RateType is F.	Postage Statement Messages
8531	Zone must be populated with N when FormType is ML and RateType is F.	Postage Statement Messages
8533	ProcessingCategory must be populated with FL, MP, or IR when FormType is ML and RateType is L.	Postage Statement Messages
8536	EntryDiscount must be populated with N when FormType is ML.	Multiple
8537	RateCategory must be populated with G, N, S, or E when FormType is ML.	Postage Statement Messages
8538	SurchargeType must be populated with N when FormType is ML.	Postage Statement Messages
8539	WeightBreakType must be populated with N when FormType is ML.	Postage Statement Messages
8540	BarcodeRate must be populated with Y or N when FormType is ML.	Postage Statement Messages
8541	EntryFacilityType must be populated with A, O, B, S, or D when FormType is ML.	Postage Statement Messages
8542	PackagingMethod must be populated with 0, 1, 2, or Blank when FormType is ML.	Postage Statement Messages
8543	PostagePaymentMethod must be populated with M or P when FormType is ML.	Postage Statement Messages

Copyright © 2011 USPS®. All Rights Reserved.

Error Code	Error Message	Messages
8544	RateType must be populated with L or F when FormType is ML.	Postage Statement Messages
8545	SackingBasis must be populated with 0 or 1 when FormType is ML.	Postage Statement Messages
8546	SinglePieceWeight must be less than or equal to 35 pounds when FormType is ML and BarcodeRate is Yes.	Postage Statement Messages
8547	SinglePieceWeight must be less than or equal to 70 pounds when FormType is ML and BarcodeRate is No.	Postage Statement Messages
8548	TotalPieces and TotalCopies must be populated with the same values when the FormType is ML.	Multiple
8549	ServiceCode must be populated with COD, COM, DC, IM, PAL, RD, RR, RRE, RRM, SC, or SH when FormType is ML.	Postage Statement Messages
8550	ProcessingCategory must be populated with LT, FL, MP, IR, or NP when FormType is PE.	QualificationReportCreateResponse
8551	Zone must be populated with N, 1, 3, 4, 5, 6, 7, 8, ICD, ADC, DDU, or SCF when FormType is PE and Zone is provided.	Multiple
8554	EntryFacilityType must be populated with O, B, D, A, or S when FormType is PE. (User Postage Statement ID: %%1).	Periodical Postage Statement Messages
8557	LimitedCirculationDiscountClaimed must be populated with Yes when the FormType is PE and RateType is W or Y. (User Postage Statement ID: %%1).	Periodical Postage Statement Messages
8558	ContainerChargeContainerLevel must be populated with 3, 5, A, or M when FormType is PE.	QualificationReportCreateResponse
8559	InOutCountyIndicator must be populated with N or I when FormType is PE.	Multiple
8560	AdPercent is required when FormType is PE. (User Postage Statement ID: %%1).	Periodical Postage Statement Messages
8562	EntryFacilityType must be populated with O, B, S, D, or A when FormType is PE or Pending Periodicals. (User Postage Statement ID: %%1).	Periodical Postage Statement Messages
8563	RateCategory must be populated with A, B, D, E, G, H, K, L, L1, L2, L3, L4, L5, L6, L7, L8, FB, N, or O when mailing is identified as Periodicals. (User Postage Statement ID: %%1).	Periodical Postage Statement Messages
8564	When populated, Zone must be populated with DDU, 1, 3, 4, 5, 6, 7, 8, SCF, ADC, or N when FormType is PE and InOutCountyIndicator is I. (User Postage Statement ID: %%1).	Periodical Postage Statement Messages
8567	ProcessingCategory can only be populated with FL, MP, or LT when FormType is PE and InOutCountyIndicator is I and RateCategory is L, H, or E. (User Postage Statement ID: %%1).	Periodical Postage Statement Messages
8571	RateCategory must be populated with A, B, D, FB, E, G, H, K, L3, L4, L5, or L6 when FormType is PE, and InOutCountyIndicator is N, and MachinableFlag is N, and ProcessingCategory is FL. (User Postage Statement ID: %%1).	Periodical Postage Statement Messages

Copyright © 2011 USPS®. All Rights Reserved.

Error Code	Error Message	Messages
8572	RateCategory must be populated with A, B, D, FB, E, G, H, K, L3, L4, L5, or L6 when FormType is PE and InOutCountyIndicator is N and MachinableFlag is Blank and ProcessingCategory is IR, MP, or NP. (User Postage Statement ID: %%1).	Periodical Postage Statement Messages
8573	RateCategory must be populated with A, B, D, FB, E, G, H, K, L1, L2, L3, L4, L5, or L6 when FormType is PE and InOutCountyIndicator is N and MachinableFlag is Blank and ProcessingCategory is LT. (User Postage Statement ID: %%1).	Periodical Postage Statement Messages
8574	ChargeableContainerLevel must be populated with M when FormType is PE and InOutCountyIndicator is N and ChargeableBundleLevel is M. (User Postage Statement ID: %%1).	Periodical Postage Statement Messages
8575	ChargeableContainerLevel must be populated with M or A when FormType is PE and InOutCountyIndicator is N and ChargeableBundleLevel is A. (User Postage Statement ID: %%1).	Periodical Postage Statement Messages
8576	ChargeableContainerLevel must be populated with M, A, or 3 when FormType is PE and InOutCountyIndicator is N and ChargeableBundleLevel is 3. (User Postage Statement ID: %%1).	Periodical Postage Statement Messages
8577	ChargeableContainerLevel must be populated with M, A, 3, or 5 when FormType is PE and InOutCountyIndicator is N and ChargeableBundleLevel is 5. (User Postage Statement ID: %%1).	Periodical Postage Statement Messages
8578	ContainerType must be populated with Pallets-Sacks-Trays when FormType is PE and Containers is populated. (User Postage Statement ID: %%1).	Periodical Postage Statement Messages
8579	ChargeableEntryLevel must be populated with C, J, or O when FormType is PE and ChargeableContainerLevel is M. (User Postage Statement ID: %%1).	Periodical Postage Statement Messages
8581	ChargeableEntryLevel must be populated with B, C, J, K, O, or R when FormType is PE and ChargeableContainerLevel is A. (User Postage Statement ID: %%1).	Periodical Postage Statement Messages
8583	ChargeableEntryLevel must be populated with B, C, J, K, O, R, or S when FormType is PE and ChargeableContainerLevel is 3. (User Postage Statement ID: %%1).	Periodical Postage Statement Messages
8585	ChargeableEntryLevel must be populated with B, C, D, J, K, O, R, or S when FormType is PE and ChargeableContainerLevel is 5. (User Postage Statement ID: %%1).	Periodical Postage Statement Messages
8586	ProcessingCategory must be populated with LT, FL or PF when FormType is PM.	Postage Statement Messages
8587	Zone must be populated with N, 1, 3, 4, 5, 6, 7, or 8 when FormType is PM and ProcessingCategory is LT, FL, or PF.	Postage Statement Messages
8588	RateType must be C, E, L, or T when FormType is PM and ProcessingCategory is FL	Postage Statement Messages
8589	RateCategory must be S, PR, P10, P11, P12, P13, P14, P15, or P16 when FormType is PM and ProcessingCategory is FL..	Postage Statement Messages
8590	RateType must be C or T when FormType is PM and ProcessingCategory is LT	Postage Statement Messages

Copyright © 2011 USPS®. All Rights Reserved.

Error Code	Error Message	Messages
8591	RateCategory must be S when FormType is PM and ProcessingCategory is LT.	Postage Statement Messages
8592	RateType must be E, G, J, K, L, X, or T when FormType is PM and ProcessingCategory is PF.	Postage Statement Messages
8593	RateCategory must be S, P10, P11, P12, P13, P14, P15, or P16 when FormType is PM and ProcessingCategory is PF.	Postage Statement Messages
8594	EntryDiscount must be populated with N when FormType is PM.	Postage Statement Messages
8595	RateCategory must be populated with S, PR, P10, P11, P12, P13, P14, P15, or P16 when FormType is PM.	Postage Statement Messages
8596	SurchargeType must be populated with D, E, N, or P when FormType is PM.	Postage Statement Messages
8597	WeightBreakType must be populated with N when FormType is PM.	Postage Statement Messages
8598	FlatRateIndicator must be populated with B, C, E, F, L, M, O, P, or S when FormType is PM.	Postage Statement Messages
8599	BarcodeRate must be populated with N or O when FormType is PM.	Postage Statement Messages
8600	EntryFacilityType must be populated with O, B, S, or D when FormType is PM.	Postage Statement Messages
8601	PostagePaymentMethod must be populated with P when FormType is PM.	Postage Statement Messages
8602	RateType must be populated with C, L, T, E, G, J, K, or X when FormType is PM.	Postage Statement Messages
8603	PriceType must be populated with Commercial, Commercial Plus, or Retail when FormType is PM.	Postage Statement Messages
8605	ServiceCode must be populated with AS, RAS, CM, COD, COM, DC, IM, RD, RM, RR, RRE, RRM, SC, or SH when FormType is PM.	Postage Statement Messages
8606	ProcessingCategory must be populated with MP, IR, or NP when FormType is PP.	Postage Statement Messages
8607	Zone must be populated with N, 1, 3, 4, 5, 6, 7, 8, DDU or SCF when FormType is PP.	Postage Statement Messages
8611	ProcessingCategory must be populated with MP, NP or IR when FormType is PP and RateType is P.	Postage Statement Messages

Copyright © 2011 USPS®. All Rights Reserved.

Error Code	Error Message	Messages
8612	Zone must be populated with 1, 3, 4, 5, 6, 7, or 8 when FormType is PP and RateType is P.	Postage Statement Messages
8613	RateCategory must be populated with S when FormType is PP and RateType is P.	Postage Statement Messages
8616	SurchargeType must be populated with 2 or N when FormType is PP.	Postage Statement Messages
8617	WeightBreakType must be populated with N when FormType is PP.	Postage Statement Messages
8618	BarcodeRate must be populated with N when FormType is PP and RateType is P.	Postage Statement Messages
8620	PostagePaymentMethod must be populated with M or P when FormType is PP.	Postage Statement Messages
8621	RateType must be populated with P when FormType is PP.	Postage Statement Messages
8626	SinglePieceWeight must be populated with a value less than or equal to 70 pounds when FormType is PP, RateType is P, SurchargeType is N, RateCategory is S, and BarcodeRate is Y.	Postage Statement Messages
8627	SinglePieceWeight must be populated with a value less than or equal to 70 pounds when FormType is PP, RateType is P, SurchargeType is N, RateCategory is S, and BarcodeRate is N.	Postage Statement Messages
8628	SinglePieceWeight must be populated with a value less than or equal to 70 pounds when FormType is PP, RateType is P, SurchargeType is P, and RateCategory is S.	Postage Statement Messages
8629	SinglePieceWeight must be populated with a value less than or equal to 70 pounds when FormType is PP RateType is P, SurchargeType is 2, and RateCategory is S.	Postage Statement Messages
8630	SinglePieceWeight must be populated with a value less than or equal to 70 pounds when FormType is PP, RateType is P, SurchargeType is N or 2, and RateCategory is Z1 or Z2.	Postage Statement Messages
8631	SinglePieceWeight must be populated with a value less than or equal to 70 pounds when FormType is PP and RateType is P and SurchargeType is P or 2 and RateCategory is Z1 or Z2.	Postage Statement Messages
8632	TotalPieces and TotalCopies must be populated with the same values when FormType is PP.	Multiple
8633	If populated, ServiceCode must be populated with COD, COM, DC, IM, PAL, RD, RR, RRE, RRM, SC, or SH when FormType is PP.	Postage Statement Messages
8634	ProcessingCategory must be populated with LT, FL, MP, IR, NP, CM, NA, or NB when FormType is SM. (User Postage Statement ID: %%1).	Multiple
8635	Zone must be populated with N when FormType is SM and ProcessingCategory is LT, FL, MP, IR, or CM. (User Postage Statement ID: %%1).	Multiple

Copyright © 2011 USPS®. All Rights Reserved.

Error Code	Error Message	Messages
8637	RateCategory must be populated with N when FormType is SM and ProcessingCategory is CM. (User Postage Statement ID: %%1).	Postage Statement Messages
8638	EntryDiscount must be populated with N when FormType is SM and ProcessingCategory is CM. (User Postage Statement ID: %%1).	Postage Statement Messages
8640	RateCategory must be populated with A, B, D, O, E, G, H, K, L3, L4, L5, or L6 when FormType is SM and ProcessingCategory is FL. (User Postage Statement ID: %%1).	Postage Statement Messages
8642	RateCategory must be populated with A, B, D, O, P5, P6, P7, P8, PG, PI, PK, or PM when FormType is SM and ProcessingCategory is IR. (User Postage Statement ID: %%1).	Postage Statement Messages
8644	RateCategory must be populated with A, A1, B, B1, D, D1, O, E, G, H, K, L1, L2, L5, L6, L7, L8, NG, NK, N5, or N6 when FormType is SM and ProcessingCategory is LT. (User Postage Statement ID: %%1).	Postage Statement Messages
8646	RateCategory must be populated with A, B, D, PE, PQ, or PR when FormType is SM and ProcessingCategory is MP. (User Postage Statement ID: %%1).	Postage Statement Messages
8648	RateCategory must be populated with N5, N6, NG, or NK when FormType is SM and ProcessingCategory is NA or NB. (User Postage Statement ID: %%1).	Postage Statement Messages
8649	EntryDiscount must be populated with N, B, S, or D when FormType is SM. (User Postage Statement ID: %%1).	QualificationReportCreateResponse
8650	RateCategory must be populated with A, B, D, O, E, G, H, K, N, L1, L2, L3, L4, L5, L6, L7, L8, PE, PG, PI, PK, PM, PQ, PR, P5, P6, P7, or P8 when FormType is SM. (User Postage Statement ID: %%1).	Postage Statement Messages
8651	SurchargeType must be populated with L or N when FormType is SM. (User Postage Statement ID: %%1).	Postage Statement Messages
8652	WeightBreakType must be populated with A, B, or H when FormType is SM. (User Postage Statement ID: %%1).	Postage Statement Messages
8653	PieceWeight must be populated with a value greater than 0.2063 pounds when FormType is SM and WeightBreakType is A. (User Postage Statement ID: %%1).	Postage Statement Messages
8654	PieceWeight must be populated with a value less than or equal to 0.2063 pounds when FormType is SM and WeightBreakType is B. (User Postage Statement ID: %%1).	Postage Statement Messages
8655	PieceWeight must be populated with a value greater than 0.2063 pounds when FormType is SM and WeightBreakType is H and ProcessingCategory is LT. (User Postage Statement ID: %%1).	Postage Statement Messages
8656	BarcodeRate must be populated with Y, N, or O when FormType is SM. (User Postage Statement ID: %%1).	Postage Statement Messages
8657	EntryFacilityType must be populated with O, B, S, or D when FormType is SM. (User Postage Statement ID: %%1).	Postage Statement Messages
8658	PackagingMethod must be populated with 0, 1, 2, or Blank when FormType is SM. (User Postage Statement ID: %%1).	Postage Statement Messages

Copyright © 2011 USPS®. All Rights Reserved.

Error Code	Error Message	Messages
8659	PostagePaymentMethod must be populated with S, M, or P when FormType is SM. (User Postage Statement ID: %%1).	Postage Statement Messages
8660	RateType must be populated with R or N when FormType is SM. (User Postage Statement ID: %%1).	Postage Statement Messages
8661	SackingBasis must be populated with 0, 1, 2, 3, 4, or Blank when FormType is SM. (User Postage Statement ID: %%1).	Postage Statement Messages
8662	EnclosedBy must be populated with SM, BP, PE, PP, or ML when FormType is SM. (User Postage Statement ID: %%1).	Postage Statement Messages
8663	ServiceCode must be populated with DC, IM, RRM, or RD when FormType is SM. (User Postage Statement ID: %%1).	Postage Statement Messages
8665	The MailingGroupID in the OriginalContainerLinkageCancelRequest must be populated with the Consolidator MailingGroupID.	OriginalContainerLinkageCancelResponse
8666	OpenMailingGroupRequest message must be accepted before submitting the OriginalContainerLinkageCreateRequest message for the specified CRID when a Mail.dat container is being linked.	OriginalContainerLinkageCreateResponse
8667	QualificationReportSummaryCreateRequest/ QualificationReportDetailCreateRequest must be accepted before submitting the OriginalContainerLinkageCreateRequest for the specified CRID when a Mail.XML container is being linked. (Linked Mailing Group: %%1, Linked Container ID: %%2).	OriginalContainerLinkageCreateResponse
8668	Values populated in the MailDatContainer block must exist when the original container was submitted through Mail.dat. (Original Mail.dat Job ID: %%1, Original Mail.dat Container ID: %%2).	OriginalContainerLinkageCreateResponse
8669	Values populated in the MailXMLContainer block must exist when the original container was submitted through Mail.XML. (Original Mailing Group: %%1, Original Container ID: %%2).	OriginalContainerLinkageCreateResponse
8670	Either the MailDatContainer block or the MailXMLContainer block of the OriginalContainer block is required.	OriginalContainerLinkageCreateResponse
8672	Populated fields in the MailXMLContainer block in the LinkedContainer block must link to fields in a MailXMLContainer block in the OriginalContainer block. (Linked Mailing Group: %%1, Linked Container ID: %%2).	OriginalContainerLinkageCreateResponse
8673	CustomerGroupID in the OriginalContainerLinkageCreateHeaderInfo block is required.	OriginalContainerLinkageCreateResponse
8674	MailingGroupID in the OriginalContainerLinkageCreateHeaderInfo block is required.	OriginalContainerLinkageCreateResponse
8675	OriginalContainerLinkageCreateRequest message must be accepted before the OriginalContainerLinkageCancelRequest message for the specified CRID when the linked container is created through Mail.XML. (Reason: %%1)	OriginalContainerLinkageCancelResponse

Copyright © 2011 USPS®. All Rights Reserved.

Error Code	Error Message	Messages
8676	OpenMailingGroupRequest message must be accepted before submitting the OriginalContainerCancelLinkageRequest message for the specified CRID when the linked container is created through Mail.dat.	OriginalContainerLinkageCancelResponse
8677	OpenMailingGroupRequest message must be accepted before submitting the OriginalContainerCreateLinkageRequest message for the specified CRID when the linked container is created through Mail.dat.	OriginalContainerLinkageCreateResponse
8678	PublicationNumber within the PermitPublicationData block in the MailingGroupData block must be populated with a value combined with the PostOfficeOfMailingZIP in the MailingGroupData block that maps to a single active Finance Number.	OpenMailingGroupResponse
8679	PermitNumber field within the PermitPublicationData block in the DocumentVersionDataWithPermit block must exist and map back to a Finance Number. (Version ID: %%1)	QualificationReportCreateResponse, QualificationReportDetailCreateResponse (10.0)
8680	MailPieceBlock or MailXMLPieceRangeBlock is required when the FullServiceParticipationIndicator is populated with M.	MailPieceCreateResponse
8689	BundleID must be a unique value within a ContainerID in the BundleDetail block across the mailing group. (ContainerID: %%1, BundleID: %%2).	BundleDetailCreateResponse
8692	OriginalContainer block must contain fields that are populated with the values that exist in the *PostalOne!* Mail.dat database for the specified CRID.	SiblingContainerCancelResponse
8693	ContainerID value that has been deleted within the SiblingContainerCancelRequest message cannot be reused within a mailing group. (Sibling Container ID: %%1 was previously cancelled.)	SiblingContainerCreateaResponse
8694	UserPostageStatementID must be unique within the MailingGroupID. (User Postage Statement ID: %%1).	Periodical Postage Statement Messages
8695	ServiceCode must be populated with CM, COD, DC, IM, RD, RM, RR, RRE, RRM, SC, or SH when FormType is PM.	Postage Statement Messages
8696	CustomerQualificationReportID in the QualificationReport must be a unique value within the MailingGroupID.	QualificationReportCreateResponse
8697	ContainerID in the QualificationReport must be a unique value within the MailingGroupID. (Container ID: %%1)	QualificationReportCreateResponse, QualificationReportDetailCreateResponse (10.0)
8698	VersionID in the ContainerDetailData must be populated and referenced with a VersionID in at least one DocumentVersionDataWithPermit block associated to a Qualification Report. (Container ID: %%1)	QualificationReportCreateResponse, QualificationReportDetailCreateResponse (10.0)
8702	ContainerPostage is required when the FullServiceParticipationIndicator is F or M except when the ContainerID is populated for all PeriodicalStatementLineItemData blocks for the specified StatementSequenceNumber. (User Postage Statement ID: %%1).	Periodical Postage Statement Messages

Copyright © 2011 USPS®. All Rights Reserved.

Error Code	Error Message	Messages
8715	SiblingContainerCancelRequest message cannot be submitted when the original container and sibling container have the ContainerStatus of Ready to Pay. (Orig ContainerID: %%1, Sibling ContainerID: %%2)	SiblingContainerCancelResponse
8717	When the USPSPriceIncentiveType in the DocumentVersionData, LineItemSummaryData, or PostageStatementLineItemData block is provided, it must be set to Saturation-HDSCF, Saturation-HDTotal, PostageAffixedReplyRidesFree, MobileBarcode, or SummerSale.	Postage Statement Messages
8718	The maximum weight for First-Class Mail Automation Letters and Cards is 3.5 ounces.	Postage Statement Messages
8719	The maximum weight for First-Class Mail Non-Automation Letters is 13 ounces.	Postage Statement Messages
8720	The maximum weight for First-Class Mail Automation Flats is 13 ounces.	Postage Statement Messages
8721	The maximum weight for First-Class Mail Non-Automation Flats is 13 ounces.	Postage Statement Messages
8724	The StandardFlatType field in the LineItemSummary or PostageStatementLineItemData blocks must be populated when FormType is SM and ProcessingCategory is FL.	Postage Statement Messages
8725	The StandardFlatType field in the DocumentVersionDataWithPermit block must be populated when FormType is SM and ProcessingCategory is FL.	QualificationReportCreateResponse
8726	The RateCategory must be E, H, L3, L4, A, B, D, or O for Standard Mail Flat Catalogs.	Postage Statement Messages
8728	The Maximum weight for Standard Mail Letters is 16 ounces.	Postage Statement Messages
8729	The Maximum weight for Standard Mail Flats is 16 ounces.	Postage Statement Messages
8731	The maximum weight for Package Services Bound Printed Matter is 20 ounces.	Postage Statement Messages
8732	The version weight for Periodical and Pending Periodical Letters cannot be greater than 16 ounces (Postg Stmt. %%1).	Postage Statement Messages
8733	The version weight for Periodical and Pending Periodical machinable Flats cannot be greater than 22 ounces (Postg Stmt. %%1).	Postage Statement Messages
8734	Rate Categories AF, BF, DF, GF, and KF are not supported for First-Class Mail, Standard Mail, or Periodicals.	Multiple
8735	A ContainerDetailID field submitted in the MailPieceCreateRequest message must match a ContainerDetailID field submitted in the associated QualificationReportSummaryCreateRequest/ QualificationReportDetailCreateRequest Message. (ContainerDetailID %%1 missing for ContainerID %%2)	MailPieceCreateResponse

Copyright © 2011 USPS®. All Rights Reserved.

Error Code	Error Message	Messages
8736	A ContainerDetailID field submitted in the PostageStatementCreateRequest message must match a ContainerDetailID field submitted in the associated QualificationReportSummaryCreateRequest/ QualificationReportDetailCreateRequest Message. (ContainerDetailID %%1 missing for ContainerID %%2)	Postage Statement Messages
8737	A ContainerDetailID field submitted in the Periodical- or ConsolidatedPeriodicalStatementCreateRequest must match a ContainerDetailID field submitted in the associated QualificationReportSummaryCreateRequest/ QualificationReportDetailCreateRequest . (ContainerDetailID %%1 missing for ContainerID %%2)QualificationReportSummaryCreateRequest/ QualificationReportDetailCreateRequest	Postage Statement Messages
8738	The number of pieces for a ContainerDetailID submitted in the MailPieceCreateRequest cannot exceed the number of pieces associated to that ContainerDetailID field in the QualificationReportSummaryCreateRequest/ QualificationReportDetailCreateRequest . (ContainerDetailID %%1 within ContainerID %%2)	MailPieceCreateResponse
~~8739~~	~~The number of pieces for the ContainerDetailID field submitted in the PostageStatementCreateRequest cannot exceed the pieces for that ContainerDetailID in the MailPieceCreateRequest. (ContainerDetailID %%1 missing for ContainerID %%2)~~	~~Postage Statement Messages~~
~~8740~~	~~The ContainerDetailID number of pieces in the Periodical- or ConsolidatedPeriodicalStatementCreateRequest cannot exceed the number of pieces associated to the MailPieceCreateRequest ContainerDetailID. (ContainerDetailID %%1 missing for ContainerID %%2)~~	~~Postage Statement Messages~~
8765	ParentContainerID field in the QualificationReportSummaryCreateRequest/ QualificationReportDetailCreateRequest message is required when the IncludedinOtherDoc field is L and the SiblingContainerID is null. (ContainerDetailID %%1 missing for ContainerID %%2)	QualificationReportCreateResponse
8767	SiblingContainerID is an optional field and cannot be populated if the ParentContainerID field is populated. When populated its length should be between 1 and 6 characters. (Found SiblingContainerID %% for ContainerID %%2)	QualificationReportCreateResponse, QualificationReportDetailCreateRespose (10.0)
8768	The system only supports Transportation Update with Container Status T in the ContainerUpdateRequest message.	ContainerUpdateResponse
8769	The system supports Transportation Update with Container Status T and Submission Date is within 30 days of the Postage Statement Mailing Date.	ContainerUpdateResponse
8809	A postage statement line did not map to a valid rate.	Postage Statement Messages
8810	The Permit Number, Type and Zip4 Option of the Permit Holder block must be populated in a PostageStatementCreateRequest message.	Postage Statement Messages

Copyright © 2011 USPS®. All Rights Reserved.

Error Code	Error Message	Messages
8811	Verify that at least one Permit block was submitted.	Postage Statement Messages
8812	FullServiceParticipationIndicator in the MailingGroupData block of the OpenMailingGroupRequest message must be populated with F or M for mail piece or piece range creation.	MailPieceCreateResponse
8813	OriginalContainerCancelRequest message cannot cancel linked containers when the PostageStatementStatus in the PostageStatementSummary block is UPD and the ContainerType is V. (Linked Mailing Group: %%1, Linked Container ID: %%2).	OriginalContainerLinkageCancelResponse
8814	OriginalContainerCancelRequest message cannot cancel linked containers when the ContainerType of the original and linked container is O, T, E, or L. (Linked Mailing Group: %%1, Linked Container ID: %%2).	OriginalContainerLinkageCancelResponse
8815	At least one Extra Service Summary Data Block does not match the expected Rates.	Postage Statement Messages
8817	EnclosedBy in the CreatePostageStatement block must be populated with PE for Enclosures.	Postage Statement Messages
8818	EnclosingIssueDate is required when EnclosedBy in CreatePostageStatement block is populated with PE for Enclosures.	Postage Statement Messages
8819	FormType in the CreatePostageStatement block must be populated with FC or SM when EnclosedBy in CreatePostageStatement block is populated with PE.	Postage Statement Messages
8820	EntryLocaleKey field in the ContainerInfoData block must be populated for drop shipped mail. (Container ID: %%1)	QualificationReportCreateResponse, QualificationReportDetailCreateRespose (10.0)
8821	PostageStatementLineData does not match the Extended form setting in the header.	Postage Statement Messages
8822	More than %%1 failures for error code: %%2	All Request Messages
8823	Version ID must be unique within the submitted message. (Version ID: %%1).	Multiple
8824	An error occurred when parsing the message.	Multiple
8826	SiblingContainerCreateRequest message must be sent before the original container has ContainerStatus populated with R.	ContainerUpdateResponse
8827	The MaildatJobID and UserLicenseCode provided did not map to a valid job.	ContainerUpdateResponse
8828	The new linked ctr id is already assigned to a different original ctr. (Linked ctr: %%1)	OriginalContainerLinkageCreateResponse
8831	When provided, RateCategory must be A, B, D, E, H, O, L1, L2, L3, or L4 when the FormType is PE, the InOutCountyIndicator is I, and the ServiceLevelIndicator for the associated ContainerID is F.	Postage Statement Messages
8832	When provided, RateCategory must be A, B, D, E, H, O, L1, L2, L3, L4, or FB when the FormType is PE, the InOutCountyIndicator is N, and the ServiceLevelIndicator for the associated ContainerID is F.	Postage Statement Messages

Copyright © 2011 USPS®. All Rights Reserved.

Error Code	Error Message	Messages
8833	RateCategory can only be E, H, L1, or L2 when FormType is FC, ProcessingCategory is CD, and the ServiceLevelIndicator for the associated ContainerID is F.	Postage Statement Messages
8834	RateCategory can only be E, H, L1, or L2 when FormType is FC, ProcessingCategory is LT, and the ServiceLevelIndicator for the associated ContainerID is F.	Postage Statement Messages
8835	RateCategory can only be E, H, L3, or L4 when FormType is FC, ProcessingCategory is FL, and the ServiceLevelIndicator for the associated ContainerID is F.	Postage Statement Messages
8836	RateCategory can only be A, B, D, O, E, H, L1 or L2 when FormType is SM, ProcessingCategory is LT, and the ServiceLevelIndicator for the associated ContainerID is F.	Postage Statement Messages
8837	The RateCategory field can only be populated with A,B, D, O, E, H, L3 or L4 when the FormType is SM, ProcessingCategory is FL, and the ServiceLevelIndicator for the associated ContainerID is F.	Postage Statement Messages
8838	RateCategory can only be A, B, D, O, E, H, L3 or L4 when FormType is BP, ProcessingCategory is FL, and the ServiceLevelIndicator for the associated ContainerID is F.	Postage Statement Messages
8839	A Header record for Periodical Statement %%1 failed to generate.	Postage Statement Messages
8840	Only one Pieces field in the MailXMLPieceRange block can be populated.	MailPieceCreateResponse
8841	Only one Copies field in the MailXMLPieceRange block can be populated.	MailPieceCreateResponse
8842	The Origin Container Barcode specified in the Original Container Linkage message does not match the submitted Origin Container Barcode: %%1	OriginalContainerLinkageCreateResponse
8843	The Linked Container Barcode specified in the Original Container Linkage message does not match the submitted Linked Container Barcode: %%1	OriginalContainerLinkageCreateResponse
8844	The ProcessingCategory of child containers must match the ProcessingCategory of their respective parent container.	QualificationReportCreateResponse, QualificationReportDetailCreateRespose (10.0)
8845	The CinCode field in in the ContainerInfoData can only contain numeric characters.	QualificationReportCreateResponse, QualificationReportDetailCreateRespose (10.0)
8846	The FormType must be PE for a Periodical Statement.	Postage Statement Messages
8847	The mail class must be the same across a co-palletized mailing.	OriginalContainerLinkageCreateResponse
8849	The Permit with Number %%1, and Type %%2 does not map to the same Finance Number as the permit for the Mailing Group.	QualificationReportCreateResponse

Copyright © 2011 USPS®. All Rights Reserved.

Error Code	Error Message	Messages
8850	An OriginalContainerID and OriginalMailingGroup or a OriginalJobID in the OriginalContainerLinkageCreateRequest can not have been previously linked to a consolidator MailingGroup. Container Id %%1	OriginalContainerLinkageCreateResponse
8851	The ContainerID field in the OriginalContainer block does not have a finalized postage statement associated to it, which is needed for Tray-Based Co-Palletization. Container Id: %%1	OriginalContainerLinkageCreateResponse
8856	The Total Postage for line block %%1 must be between the Postage calculated at the minimum and maximum rates for Section %%2, Line Number %%3	Postage Statement Messages
8857	The number of pieces in the InCountyAddressedSupplementPieces field cannot exceed the sum of all pieces in PeriodicalLineItemData blocks where InOutCountyIndicator is set to I. (User Postage Statement ID: %%1)	Postage Statement Messages
8858	The service level of the Linked Container may not be higher than that of the Original Container. Original Container Service Level: %%1, Linked Container Service Level: %%2	OriginalContainerLinkageCreateResponse
8859	When populated, the ContainerType field in SiblingContainerCreateRequest message must be populated with 1, 2, 3, 4, 5, E, F, O, P, S, T, B, U, Z, H, A, G, D, R, or C.	SiblingContainerCreateaResponse
8860	The number of pieces in the OutsideCountyAddressedSupplementPieces field cannot exceed the sum of all pieces in PeriodicalLineItemData blocks where InOutCountyIndicator is set to N. (User Postage Statement ID: %%1)	Postage Statement Messages
8861	For Copalletization, the linked container must have an Included In Other Documentation value of L. Container ID: %%1	OriginalContainerLinkageCreateResponse
8862	For Copalletization, the original container must have an Included In Other Documentation value of O. Container ID: %%1	OriginalContainerLinkageCreateResponse
8864	Each Periodical Statement submitted in a PeriodicalStatementCreateRequest or a ConsolidatedStatementCreateRequest must contain at least one PeriodicalLineItemData block.	Postage Statement Messages
8865	Each Postage Statement submitted in a PostageStatementCreateRequest must contain at least one PostageStatementLineItemData block or one LineItemSummaryData block.	Postage Statement Messages
8866	Invalid permit information was entered to claim the Science and Agriculture rate.	Postage Statement Messages
8867	Invalid permit information was entered to claim the Non-Profit rate.	QualificationReportCreateResponse
8868	Invalid permit information was entered to claim the Classroom rate.	QualificationReportCreateResponse
8869	An Internal Error occured during the %%1 step while processing your message.	Postage Statement Messages

Copyright © 2011 USPS®. All Rights Reserved.

Error Code	Error Message	Messages
8870	A QualificationReportSummaryCreateRequest/ QualificationReportDetailCreateRequest with the OnePassPlannedOrActualFlag with A must be preceded by a QualificationReportSummaryCreateRequest/ QualificationReportDetailCreateRequest with the OnePassPlannedOrActualFlag set to P .	QualificationReportCreateResponse
8871	All Postage Statements in a Combined Mailing must have the same Form Type. The Form Type for this Combined Mailing is %%1.	Postage Statement Messages
8873	Invalid permit information was entered to claim the Science of Agriculture Limited Circulation rate.	QualificationReportCreateResponse
8874	Invalid permit information was entered to claim the Regular Limited Circulation rate.	QualificationReportCreateResponse
8875	All Periodical Statements in a ConsolidatedPeriodicalStatementCreateRequest must have the same Combined Mailing ID.	Multiple
8876	The QualificationReportSummaryCreateRequest/ QualificationReportDetailCreateRequest message cannot have the records with the IncludedInOtherDoc field values set to O and L.	QualificationReportCreateResponse
8877	The LineItemSummaryData block must have the PiecePostage field populated when the single piece weight is not provided.	Postage Statement Messages
8878	The PostageAmount in the LineItemSummaryData block must equal the PiecePostage plus the PoundPostage when the single piece weight is not provided.	Postage Statement Messages
8879	The PostageAmount in the LineItemSummaryData block cannot be greater than the PiecePostage amount when the single piece weight is not provided.	Postage Statement Messages
8880	The Piece Postage for line block %%1 must be between the Postage calculated at the minimum and maximum rates for Section %%2, Line Number %%3	Postage Statement Messages
8881	The Pound Postage for line block %%1 must be between the Postage calculated at the minimum and maximum rates for Section %%2, Line Number %%3	Postage Statement Messages
8882	Tray based copal container linkages cannot be cancelled. (ContainerID: %%1)	OriginalContainerLinkageCancelResponse
8883	Bundle based copal container linkages cannot be cancelled after the associated postage statements have been finalized. (ContainerID: %%1	OriginalContainerLinkageCancelResponse
8884	The Original Container and Linked Container must have the same Container Barcodes required for Fullservice and Mixed Service containers. %%1	OriginalContainerLinkageCreateResponse
8885	When populated, the FullServiceParticipationIndicator field must be set to F.	Postage Statement Messages
8886	The Permit Holder Permit Type cannot equal PE or PP in a PostageStatementCreateRequest message.	Postage Statement Messages
8887	The finance number %%1 associated with .mpa permit number %%2 and permit type %%3 does not have a non-profit status.	Postage Statement Messages

Copyright © 2011 USPS®. All Rights Reserved.

Error Code	Error Message	Messages
8888	Container updates to origin containers in a co-pal tray job are not allowed after the consolidator job has been submitted. (Container ID: %%1)	ContainerUpdateResponse
8889	The number of pieces must equal the number of copies when the mailing does not include Firm Bundles or Addressed Supplements and InOutCountyIndicator is N.	Postage Statement Messages
8890	The number of pieces must be less than or equal to the number of copies when the mailing includes Firm Bundles but does not have any Addressed Supplements and InOutCountyIndicator is N.	Postage Statement Messages
8891	The number of pieces must be greater than or equal to the number of copies when the mailing includes Addressed Supplements but does not have Firm Bundles and InOutCountyIndicator is N.	Postage Statement Messages
8900	The CRID in the SubmittingParty block of the SiblingContainerCreateRequest message must match the CRID of the mailer that created the MailingGroup. (CRID: %%1)	SiblingContainerCreateResponse
8901	The CustomerGroupID field within the OriginalContainer block of the SiblingContainerCreateRequest message must be a string between 1 and 25 characters and match the CustomerGroupID of the existing container. (Container GroupID: %%1)	SiblingContainerCreateResponse
8902	The MailingGroupID field within the OriginalContainer block of the SiblingContainerCreateRequest message must be a non-negative integer and match the MailingGroupID of the existing container. (Mailing Group ID: %%1)	SiblingContainerCreateResponse
8903	The ContainerID fields in the OriginalContainer block of the SiblingContainerCreateRequest message must match the ContainerID fields in the QualificationReportSummaryCreateRequest/ QualificationReportDetailCreateRequest message for the existing container. (Container ID: %%1)	SiblingContainerCreateResponse
8906	The ProcessingCategory field in the SummaryZipDestinationReport block of the SummaryZipDestinationReportCreateRequest message must be populated with LT, FL, CD, MP, IR, PF, CM, NP, NA, or NB.	SummaryZipDestinationReportCreateResponse
8907	The PostagePaymentMethod field in the SummaryZipDestinationReport block of the SummaryZipDestinationReportCreateRequest message must be populated with S, M or P.	SummaryZipDestinationReportCreateResponse
8908	The combination of MailingGroupID and CustomerGroupID in the SummaryZipDestinationReportCreateRequest message must be populated with the same values as that of the open mailing group.	SummaryZipDestinationReportCreateResponse
8909	The QualificationReportSummaryCreateRequest/ QualificationReportDetailCreateRequest message must be accepted before submitting the SummaryZipDestinationReportCreateRequest message for that specified MailingGroupID.	SummaryZipDestinationReportCreateResponse
8910	The PostageStatementCreateRequest message must be accepted before submitting the SummaryZipDestinationReportCreateRequest message for that specified MailingGroupID.	SummaryZipDestinationReportCreateResponse

Copyright © 2011 USPS®. All Rights Reserved.

Error Code	Error Message	Messages
8911	The CustomerGroupID field within the NewSiblingContainer block of the SiblingContainerCreateRequest message is the same value as the CustomerGroupID in the OriginalContainer block. (Container ID: %%1 , Customer Group ID: %%2)	SiblingContainerCreateaResponse, SiblingContainerCancelResponse
8912	The MailingGroupID field within the NewSiblingContainer block of the SiblingContainerCreateRequest message is the same value as the MailingGroupID in the OriginalContainer block. (Container ID: %%1 , Mailing Group ID: %%2)	SiblingContainerCreateResponse
8915	The UniqueContainerBarcode field in the NewSiblingContainer block of the SiblingContainerCreateRequest message is a required field when the FullServiceParticipationIndicator in the OpenMailingGroupRequest message was F. (Container ID: %%1)	SiblingContainerCreateResponse
8916	The UniqueContainerBarcode field in the NewSiblingContainer block of the SiblingContainerCreateRequest message is a required field when the FullServiceParticipationIndicator in the OpenMailingGroupRequest message was M. (Container ID: %%1)	SiblingContainerCreateResponse
8930	The combination of MailingGroupID and CustomerGroupID in the CustomerMailReportCreateRequest message must be populated with the same values as that of the OpenMailing Group.	CustomerMailReportCreateResponse
8931	The QualificationReportSummaryCreateRequest/ QualificationReportDetailCreateRequest message must be accepted before submitting the CustomerMailReportCreateRequest message for that specified MailingGroupID.	CustomerMailReportCreateResponse
8932	The PostageStatementCreateRequest message must be accepted before submitting the CustomerMailReportCreateRequest message for that specified MailingGroupID.	CustomerMailReportCreateResponse
8935	The PermitType field in the PermitInfo block in the CustomerMailReportInfo block of the CustomerMailReportCreateRequest message must be PI, MT, PC, BR, GH, OI or OM when the PermitNumber field is populated.	CustomerMailReportCreateResponse
8936	The PermitType field in the AdditionalPermitInfo block in the CustomerMailReportInfo block of the CustomerMailReportCreateRequest message must be PI, MT, PC, BR, GH, OI or OM when the PermitNumber field is populated.	CustomerMailReportCreateResponse
8937	The SiblingContainerCreateRequest message cannot be processed after the PostageStatementCreateRequest has been submitted for this Mailing Group. (Orig Container ID: %%1)	SiblingContainerCreateaResponse
8938	The CRID in the SubmittingParty block of the SiblingContainerCancelRequest message must match the CRID of the mailer that created the MailingGroup. (CRID: %%1)	SiblingContainerCancelResponse
8939	The CustomerGroupID field within the OriginalContainer block of the SiblingContainerCancelRequest message is a string between 1 and 25 characters and must match the CustomerGroupID of the existing container. (Container GroupID: %%1)	SiblingContainerCancelResponse
8940	The MailingGroupID field within the OriginalContainer block of the SiblingContainerCancelRequest message is a non-negative integer and must match the MailingGroupID of the existing container. (Mailing Group ID: %%1)	SiblingContainerCancelResponse

Copyright © 2011 USPS®. All Rights Reserved.

Error Code	Error Message	Messages
8941	The ContainerID fields in the OriginalContainer block of the SiblingContainerCancelRequest message must match the ContainerID fields in the QualificationReportSummaryCreateRequest/ QualificationReportDetailCreateRequest message for the existing container. (Container ID: %%1)	SiblingContainerCancelResponse
8942	The CustomerGroupID field within the SiblingToDelete block of the SiblingContainerCancelRequest message must match the CustomerGroupID in the OriginalContainer block. (Container ID: %%1 , Customer Group ID: %%2)	SiblingContainerCancelResponse
8943	The MailingGroupID field within the SiblingToDelete block of the SiblingContainerCancelRequest message must be populated with the same value as the MailingGroupID in the OriginalContainer block. (Container ID: %%1 , Mailing Group ID: %%2)	SiblingContainerCancelResponse
8944	The SiblingContainerCancel message must be submitted and processed before finalization of the postage statement associated to the oldest sibling for Full-Service and Mixed mailings. (Orig Container ID: %%1)	SiblingContainerCancelRequest
8945	The CustomerGroupID in the FullContainerID Block of the ContainerUpdateRequest message must match the CustomerGroupID of the existing container. (Container ID: %%1 , Customer Group ID: %%2)	ContainerUpdateResponse
8946	The MailingGroupID in the FullContainerID Block of the ContainerUpdateRequest message must match the MailingGroupID of the existing container. (MailingGroup ID: %%1)	ContainerUpdateResponse
8947	The ContainerID in the FullContainerID Block of the ContainerUpdateRequest message must match the ContainerID in the QualificationReportSummaryCreateRequest/ QualificationReportDetailCreateRequest Message for the specified MailingGroupID. (Container ID: %%1)	ContainerUpdateResponse
8948	The UniqueContainerBarcode in the ContainerUpdateRequest FullContainerID block must match the existing container in the Qual Report message for the MailingGroupID and ContainerID. (Container ID: %%1, UniqueContainerBarcode: %%2)	ContainerUpdateResponse
8949	The Reservaton field can only be updated when the ContainerStatus in the SummaryRecordUpdate block of the ContainerUpdateRequest message is populated with T. (Container ID: %%1)	ContainerUpdateResponse
8950	The IMBarcode field can only be updated when the ContainerStatus in the SummaryRecordUpdate block of the ContainerUpdateRequest message is populated with T. (Container ID: %%1)	ContainerUpdateResponse
8951	The ScheduledInductionDateTIme field can only be updated when the ContainerStatus in the SummaryRecordUpdate block of the ContainerUpdateRequest message is populated with T. (Container ID: %%1)	ContainerUpdateResponse
8952	The CSATripID field can only be updated when the ContainerStatus in the SummaryRecordUpdate block of the ContainerUpdateRequest message is populated with T. (Container ID: %%1)	ContainerUpdateResponse

Copyright © 2011 USPS®. All Rights Reserved.

Error Code	Error Message	Messages
8953	The USPSPickUp field can only be updated when the ContainerStatus in the SummaryRecordUpdate block of the ContainerUpdateRequest message is populated with T. (Container ID: %%1)	ContainerUpdateResponse
8954	The ConsigneeContentID field can only be updated when the ContainerStatus in the SummaryRecordUpdate block of the ContainerUpdateRequest message is populated with T. (Container ID: %%1)	ContainerUpdateResponse
8955	The EntryPointADLocaleKey field can only be updated when the ContainerStatus in the SummaryRecordUpdate block of the ContainerUpdateRequest message is populated with T. (Container ID: %%1)	ContainerUpdateResponse
8956	The EntryPointADPostalCode field can only be updated when the ContainerStatus in the SummaryRecordUpdate block of the ContainerUpdateRequest message is populated with T. (Container ID: %%1)	ContainerUpdateResponse
8957	The ScheduledShipDateTIme field can only be updated when the ContainerStatus in the SummaryRecordUpdate block of the ContainerUpdateRequest message is populated with T. (Container ID: %%1)	ContainerUpdateResponse
8958	The ContainerStatus field in the SummaryRecordUpdate block of the ContainerUpdateRequest message must be populated with T when updating a Mail.XML job. (Container ID: %%1, ContainerStatus: %%2)	ContainerUpdateResponse
8959	The PostageStatementMailingDate in the ContainerInfoData block cannot be more than %%1 days in the future of the submission date and cannot be backdated prior to %%2.	QualificationReportCreateResponse, QualificationReportDetailCreateResponse (10.0)
8960	The ScheduledInductionDateTime field in the ContainerInfoData block must be within 30 days of the past or present of the PostageStatementMailingDate.	QualificationReportCreateResponse, QualificationReportDetailCreateResponse (10.0)
8961	The ScheduledShipDateTime field in the ContainerInfoData block must be within 30 days of the past or present of the PostageStatementMailingDate.	QualificationReportCreateResponse, QualificationReportDetailCreateResponse (10.0)
8962	The EntryLocaleKey field in the ContainerInfoData block is required unless the EntryFacilityType field in the ContainerInfoData block is populated with O and no appointment is provided.	QualificationReportCreateResponse, QualificationReportDetailCreateResponse (10.0)
8963	The ScheduledInductionDate field in the SummaryRecordUpdate block of the ContainerUpdateRequest message must be within 30 days of PostageStatementMailingDate field in the QualificationReportSummaryCreateRequest/ QualificationReportDetailCreateRequest message for a Full-Service mailing.	ContainerUpdateResponse

Copyright © 2011 USPS®. All Rights Reserved.

Error Code	Error Message	Messages
8964	The ScheduledShipDate field in the SummaryRecordUpdate block of the ContainerUpdateRequest message must be within 30 days of the PostageStatementMailingDate field in the QualificationReportSummaryCreateRequest/ QualificationReportDetailCreateRequest message for a Full-Service mailing.	ContainerUpdateResponse
8965	The PublicationNumber in the PermitInfo block or the AdditionalPermitInfo block in the CustomerMailReportInfo block of the CustomerMailReportCreateRequest message cannot be populated.	CustomerMailReportCreateResponse
8967	The ContainerID field of the NewSiblingContainer must be unique within the mailing group. (Container ID: %%1).	SiblingContainerCreateResponse
8968	The ContainerID field in the PostageStatementLineItemData block in the PostageStatementCreateRequest message referenced as a sibling container with a ContainerType of M must be linked to an existing physical container. (Container ID: %%1).	PostageStatement CreateResponse
8969	The ContainerID field in the PostageStatementLineItemData block in the PostageStatementCreateRequest message referenced as a sibling container with a ContainerType of L must be linked to an existing physical handling unit. (Container ID: %%1).	Postage Statement Messages
8970	The MailXMLPresentationCategory in the OpenMailingGroupRequest must be populated with M for the SummaryZIPDestinationReportCreateRequest message to be processed.	SummaryZipDestinationReportCreateResponse
8971	The MailXMLPresentationCategory in the OpenMailingGroupRequest must be populated with M for the CustomerMailReportCreateRequest message to be processed.	CustomerMailReportCreateResponse
8972	If the OriginalContainer block UniqueContainerBarcode field is populated in the SiblingContainerCreateRequest or -CancelRequest, it must match the Qual Report ContainerBarcode field. (Container ID: %%1, UniqueContainerBarcode: %%2).	SiblingContainerCreateaResponse, SiblingContainerCancelRequest
8973	Transportation updates cannot be performed on linked containers created at the Consolidator level for all Mail.XML Tray-Based Co-Palletized Full or Mixed-Service mailings. (Container ID: %%1).	OriginalContainerLinkageCreateResponse
8974	A linked container cannot be updated after the associated Postage Statement has been finalized for all Mail. XML Bundle-Based Co-Palletized Full or Mixed-Service mailings. (Container ID: %%1).	OriginalContainerLinkageCreateResponse
8975	Each container in the PostageStatementCreateRequest message must have been submitted in a QualificationReportSummaryCreateRequest/ QualificationReportDetailCreateRequest message.	Postage Statement Messages
8984	Average piece range count error	MailPieceCreateResponse
8985	Duplicate Tray barcode error	QualificationReportCreateResponse, QualificationReportDetailCreateResponse (10.0)

Copyright © 2011 USPS®. All Rights Reserved.

Error Code	Error Message	Messages
8986	The PermitHolderData block PermitType in the PostageStatementCreateRequest message must be PI, PC, or MT when the PostageStatementCreateRequest RateCategory is S and the OpenMailingGroupRequest MailXMLPresentationCategory is M.	Postage Statement Messages
8987	The SortationLevel must be AJ when the RateLevel is SP in the QualificationReportSummaryCreateRequest/ QualificationReportDetailCreateRequest message and FormType is FC in the QualificationReportSummaryCreateRequest/ QualificationReportDetailCreateRequest message and the MailXMLPresentationCategory is M in the OpenMailingGroupRequest.	QualificationReportCreateResponse
8988	At least one SortationLevel in the QualificationReportSummaryCreateRequest/ QualificationReportDetailCreateRequest message must be set to AJ when the RateCategory is S and the FormType is FC in the PostageStatementCreateRequest and the PresentationCategory is M in the OpenMailingGroupRequest.	Postage Statement Messages
8989	The BarcodeID, ServiceTypeCode, MailerID6 or -9, and SerialNumber9 or -6 fields in the MailPieceCreateRequest IMB block must be populated when the OpenMailingGroupRequest MailXMLPresentationCategory is M and FullServiceParticipationIndicator is F or M.	MailPieceCreateResponse
8990	The MailPieceCreateRequest message IMbarcodeLowerSerialization and IMbarcodeUpperSerialization block fields must be populated when the OpenMailingGroupRequest message MailXMLPresentationCategory is M and the FullServiceParticipationIndicator is F or M.	MailPieceCreateResponse
8991	The AutomationAddressMatchDate cannot be more than 90 calendar days before the PostageStatementMailingDate when RateCategory is A, B, D, or O for carrier route mail.	Postage Statement Messages
8992	The AutomationAddressMatchDate cannot be more than 180 calendar days before the PostageStatementMailingDate when RateCategory is E, H, L, L1, L2, L3, or L4 for non-carrier route automation mail.	Postage Statement Messages
8993	When the PeriodicalPrice field within the PeriodicalLineItemData block is set to 1, the sum of DiscountQty must be greater than 0 and less than or equal to the sum of Pieces for In-County Piece Prices.	Postage Statement Messages
8994	The InOutCountyIndicator field must be set to I when the PeriodicalPrice field is set to 1 within the PeriodicalLineItemData block of the PeriodicalStatementCreateRequest message.	Postage Statement Messages
8995	The Zone field must be set to DDU when the PeriodicalPrice field is set to 1 within the PeriodicalLineItemData block of the PeriodicalStatementCreateRequest message.	Postage Statement Messages
8996	The InOutCountyIndicator field must be set to I when the PeriodicalPrice field is set to 1 within the PeriodicalLineItemData block within the PeriodicalStatement block of the ConsolidatedPeriodicalStatementCreateRequest message.	Postage Statement Messages

Copyright © 2011 USPS®. All Rights Reserved.

Error Code	Error Message	Messages
8997	The Zone field must be set to DDU when the PeriodicalPrice field is set to 1 within the PeriodicalLineItemData block within the PeriodicalStatement block of the ConsolidatedPeriodicalStatementCreateRequest message.	Postage Statement Messages
8998	When the PeriodicalPrice field is set to 1 and the mailing does not contain In-County Addressed Supplements, the sum of DiscountQty must be greater than 0 and less than or equal to the number of Copies for In-County Pound Prices.	Postage Statement Messages
8999	The postage statement with statement ID: %%1, has been frozen and cannot be cancelled.	Postage Statement Messages
9000	PendingPostageAmount cannot be provided when the PublicationNumber is provided in the PermitPublicationData block within the CreatePeriodicalStatementData block of the PeriodicalStatementCreateRequest message. (User Postage Statement ID: %%1)	Postage Statement Messages
9001	PendingPostageAmount cannot be provided when the PublicationNumber is provided in the PermitPublicationData block within the PeriodicalStatement block of the ConsolidatedPeriodicalStatementCreateRequest message. (User Postage Statement ID: %%1)	Postage Statement Messages
9002	There can be no more than 999 unique CustomerReferenceIDs submitted in the PostageStatementCreateRequest, PeriodicalStatementCreateRequest, or ConsolidatedPeriodicalStatementCreateRequest messages submitted to a single Mail.XML MailingGroupID.	Postage Statement Messages
9003	The PostageStatementMailingDate field in the ContainerInfoData block in the QualificationReportSummaryCreateRequest/ QualificationReportDetailCreateRequest message cannot span the price change date; within a job these dates must either be all before or all after %%1.	QualificationReportCreateResponse
9004	The PostageStatementMailingDate field cannot be more than %%1 days in the future of the submission date and cannot be backdated prior to %%2.	QualificationReportCreateResponse, QualificationRaeportDetailCreateResponse (10.0)
9005	The PostageStatementMailingDate fields within a Mailing Group cannot span a price change date; they must be populated with all dates either before or after %%1.	Multiple
9006	The Zone field in the ContainerDetailData block must be populated when the FormType is PE for Periodicals.	QualificationReportCreateResponse
9008	A Transportaion Update when ContainerStatus is T cannot be submitted more than 30 calendar days after the PostageStatementMailingDate.	ContainerUpdateResponse
9012	StandardFlatType must be the same for all DocumentVersionData, PostageStatementLineItemData, and LineItemSummaryData blocks within a PostageStatementCreateRequest message.	Postage Statement Messages
9013	The ContainerType field in the ContainerInfoData block contains an invalid value; ContainerType AB is not supported.	QualificationReportCreateResponse, QualificationReportDetailCreateResponse (10.0)

Copyright © 2011 USPS®. All Rights Reserved.

Error Code	Error Message	Messages
9014	The maximum weight for Standard Mail Automation Carrier Route Letters is 3.5 ounces.	Postage Statement Messages
9015	The ProcessingCategory in the PeriodicalStatement or CreatePeriodicalStatement blocks must be set to FL when the SortationLevel in the QualificationReportSummaryCreateRequest/ QualificationReportDetailCreateRequest or BundleDetailCreateRequest is set to E or F.	Postage Statement Messages
9016	The ProcessingCategory in the PeriodicalStatement or CreatePeriodicalStatement blocks must be set to FL when the BundleLevel in the BundleDetail block in the BundleDetailCreateRequest is set to X.	Postage Statement Messages
9017	The BundleLevel in the BundleDetailCreateRequest must be set to X when the associated SortationLevel in the QualificationReportSummaryCreateRequest/ QualificationReportDetailCreateRequest or BundleDetailCreateRequest is set to E or F for Periodicals.	BundleDetailCreateResponse
9018	The ContainerType in the QualificationReportSummaryCreateRequest/ QualificationReportDetailCreateRequest must be set to P, Z, H, A, G, D, R, or C when the associated SortationLevel in the QualificationReportSummaryCreateRequest/ QualificationReportDetailCreateRequest is set to E or F for Periodicals.	QualificationReportCreateResponse
9019	The FormType field must be set to First-Class Mail or Standard Mail for a co-palletized mailing with the Container Type field set to F, O or T	QualificationReportCreateResponse
9023	The EntryPointFacilityType in the ContainerInfoData block cannot be populated with N when the FullServiceParticipationIndicator in the OpenMailingGroupRequest message is F or M.	QualificationReportCreateResponse
9024	The CSAID in the ContainerInfoData block must be populated with a 10 digit numeric between 1000000000 and 9999999999 when the FullServiceParticipationIndicator in the OpenMailingGroupRequest message is F or M.	QualificationReportCreateResponse, QualificationReportDetailCreateResponse (10.0)
9026	When the mailing is Full-Service or Mixed Service, the ConsigneeApptID in the ContainerInfoData block must be populated with one of the formats specified in the Mail.XML Tech Spec.	QualificationReportCreateResponse, QualificationReportDetailCreateResponse (10.0)
9027	The EntryPointADLocaleKey in the SummaryRecordUpdate block must be populated with 6 alphanumeric characters and cannot be populated with ORIGIN when the EntryPointFacilityType is O, the ContainerStatus is T and the mailing is Mixed or Full -Service.	ContainerUpdateResponse
9029	When the mailing is Full-Service or Mixed Service and the ContainerStatus in the SummaryRecordUpdate block is T, the ReservationNumber in the SummaryRecordUpdate block must be populated with one of the formats specified in the Mail.XML Tech Spec.	ContainerUpdateResponse
9031	The piece weight for First-Class Commercial Plus Parcels must be greater than or equal to 3.5oz and less than 16oz.	Postage Statement Messages

Copyright © 2011 USPS®. All Rights Reserved.

Error Code	Error Message	Messages
9032	The SurchargeType in the PostageStatementLineItemData or LineItemSummaryData block must be populated with N for First-Class Commercial Plus Parcels.	Postage Statement Messages
9033	PermitType field in the PermitPublicationData block in the PermitHolderForAPData block must be populated with PI or OI.	Postage Statement Messages
9034	The maximum weight for Package Services Bound Printed Matter non-barcoded Flats is 15 pounds.	Postage Statement Messages
9035	The maximum weight for Package Services Media/ Library Mail non-barcoded Flats is 70 pounds.	Postage Statement Messages
9036	The version weight for Periodical and Pending Periodical non-machinable Flats cannot be greater than 4.4 pounds (Postg Stmt. %%1).	Postage Statement Messages
9037	When submitting multiple MailPieceCreateRequest messages, the messages may only contain MailPieceBlockGroups or MailXMLPieceRangeBlockGroups, but not both within the same Mailing Group.	MailPieceCreateResponse
9038	The ContainerBarcode in the ContainerInfoData block must be unique below the configurable threshold (%%1) when the mailing is Full-Service or Mixed Service. (Container Barcode: %%2).	QualificationReportCreateResponse, QualificationReportDetailCreateResponse (10.0)
9040	The FormType field contains an invalid value; it must contain FC or SM when the USPSPriceIncentiveType field is populated with MobileBarcode.	Multiple
9041	The PermitType field contains an invalid value; it must contain PI when the USPSPriceIncentiveType field is populated with MobileBarcode.	Multiple
9042	The ProcessingCategory field contains an invalid value; it must contain FL,LT, or CD when the USPSPriceIncentiveType field is populated with MobileBarcode.	Multiple
9043	The PostageStatementMailingDateTime field must be populated with a date between %%1 and %%2.	Multiple
9045	The PostageStatementMailingDateTime field must be populated with a date between %%1 and %%2 for an update submission when the USPSPriceIncentiveType field is populated with MobileBarcode.	ContainerUpdateResponse
9046	The PostageStatementMailingDateTime field must be populated between %%1 and %%2 for an update submission when the .cpt Postal Price Incentive Type of the Mail.dat original submission is populated with MB.	ContainerUpdateResponse
9061	ScheduledInductionDateTime field in the ContainerInfoData block is required when USPSPickUp field in the ContainerInfoData block is No and the FullServiceParticipationIndicator in the OpenMailingGroupRequest message is F or M.	QualificationReportCreateResponse (9.0)
9061	ScheduledInductionDateTime field in the ContainerInfoData block is required when USPSPickUp field in the ContainerInfoData block is No and the FullServiceParticipationIndicator field in the OpenMailingGroupRequest message is F or M.	QualificationReportDetailCreateResponse (10.0)

Copyright © 2011 USPS®. All Rights Reserved.

Error Code	Error Message	Messages
9062	The EntryPointFacilityType field in the ContainerInfoData block cannot be populated with B, D, or S when the FormType field in the QualificationReport block of the QualificationReportSummaryCreateRequest/ QualificationReportDetailCreateRequest message is populated with FC.	OpenMailingGroupRequest, QualificationReportCreateResponse
9063	The EntryPointFacilityType field in the ContainerInfoData block cannot be populated with B, D, or S when the FormType field in the QualificationReport block of the QualificationReportSummaryCreateRequest message is populated with FC.	QualificationReportDetailCreateResponse (10.0)
9064	The CSAID field in the ContainerInfoData block is required when the FormType field in the QualificationReport block is FC and the SortationLevel in the ContainerInfoData block is AK, AL, AM, AN, AO, AP, or AQ.	QualificationReportDetailCreateResponse (9.0C)
9065	The CSAID field in the ContainerInfoData block is required when the FormType in the QualificationReport block of the QualificationReportSummaryCreateRequest message is FC and SortationLevel in the ContainerInfoData block is AK, AL, AM, AN, AO, AP or AQ.	QualificationReportDetailCreateResponse (10.0)
9067	OpenMailingGroupRequest message must be accepted before submitting the QualificationReportSummaryCreateRequest message for the specified MailingGroupID and CustomerGroupID.	QualificationReportDetailCreateResponse (10.0)
9068	The CustomerQualificationReportID field in the QualificationReportSummary block of the QualificationReportSummaryCreateRequest message must be populated with a unique value within a MailingGroupID.	QualificationReportSummaryCreateResponse (10.0)
9070	The FormType field in the QualificationReportSummary block contains an invalid value; it must contain FC, PE, PP, SM, BP, ML, or PM.	QualificationReportSummaryCreateResponse (10.0)
9072	OpenMailingGroupRequest message must be accepted before submitting the QualificationReportDetailCreateRequest message for the specified MailingGroupID and CustomerGroupID.	QualificationReportDetailCreateResponse (10.0)
9073	The CustomerQualificationReportID field in the QualificationReportDetailCreateRequest message must match an existing CustomerQualificationReportID from an accepted QualificationReportSummaryCreateRequest message within a MailingGroupID.	QualificationReportDetailCreateResponse (10.0)
9074	InOutCountyIndicator field in the ContainerDetailData block in the ContainerInfoData block in the QualificationReport block is required when FormType in the QualificationReportSummaryRequest message is PE. (Container ID: %%1)	QualificationReportDetailCreateResponse (10.0)
9075	PermitNumber field in the DocumentVersionDataWithPermit block in the QualificationReport block is required when the FormType in the QualificationReportSummaryCreateRequest message is PM, FC, SM, BP, PP, or ML. Form type is: %%2	QualificationReportDetailCreateResponse (10.0)
9076	PermitZIP4 field within PermitPublicationData block in the DocumentVersionDataWithPermit block in the QualificationReport block is required when the FormType in the QualificationReportSummaryCreateRequest message is PM, FC, SM, BP, PP, or ML.	QualificationReportDetailCreateResponse (10.0)

Copyright © 2011 USPS®. All Rights Reserved.

Error Code	Error Message	Messages
9077	PublicationNumber field in the PermitPublicationData block in the DocumentVersionDataWithPermit block should not be populated when the FormType in the QualificationReportSummaryRequest message is not populated with PE for Periodicals or Pending Periodicals.	QualificationReportDetailCreateResponse (10.0)
9078	All QualificationReportDetailCreateRequest messages must be accepted before submitting the associated BundleDetailCreateRequest message for the specified MailingGroupID and CustomerGroupID.	BundleDetailCreateResponse
9079	All QualificationReportDetailCreateRequest messages must be accepted before submitting the associated ContainerBundleReportCreateRequest message for the specified MailingGroupID and CustomerGroupID.	ContainerBundleReportCreateResponse
9080	ContainerBundleReportCreateRequest message can only be provided when the FormType in the QualificationReportSummaryCreateRequest message is PE.	ContainerBundleReportCreateResponse
9081	All QualificationReportDetailCreateRequest messages must be accepted before submitting the associated MailPieceCreateRequest message to create a piece range for the specified MailingGroupID and CustomerGroupID.	MailPieceCreateResponse
9082	All QualificationReportDetailCreateRequest messages must be accepted before submitting the associated MailPieceCreateRequest message to create a mail piece for the specified MailingGroupID and CustomerGroupID.	MailPieceCreateResponse
9083	At least one QualificationReportDetailCreateRequest ContainerInfoData block must have a ContainerType of L or M if the LogicalPhysicalIndicator in the OpenMailingGroupRequest is L, MailXMLPresentationCategory is P, FullServiceParticipationIndicator is F or M.	QualificationReportDetailCreateRequest (10.0)
9084	All QualificationReportDetailCreateRequest messages must be accepted before submitting the associated PostageStatementCreateRequest message for the specified MailingGroupID and CustomerGroupID.	Postage Statement Messages
9085	PieceWeight field in the DocumentVersionDataWithPermit block must be less than or equal to 13 oz when the ProcessingCategory field is populated with FL and the FormType field in the QualificationReportSummaryCreateRequest message is populated with FC.	QualificationReportDetailCreateRequest (10.0)
9088	ProcessingCategory field in the ContainerInfoData block must be populated with LT when the FormType field in the QualificationReportSummaryCreateRequest message is populated with ‘SM’ for MLOCR mailings.	QualificationReportDetailCreateRequest (10.0)
9089	PieceWeight field in the DocumentVersionDataWithPermit block cannot exceed 3.3 ounces when the ProcessingCategory field in the ContainerInfoData block is LT and the FormType field in the QualificationReportSummaryCreateRequest message is SM.	QualificationReportDetailCreateRequest (10.0)
9090	All QualificationReportDetailCreateRequest messages must be accepted before submitting the associated OriginalContainerLinkageCreateRequest message for the specified MailingGroupID and CustomerGroupID.	OriginalContainerLinkageCreateResponse

Copyright © 2011 USPS®. All Rights Reserved.

Error Code	Error Message	Messages
9091	A ContainerDetailID field submitted in the MailPieceCreateRequest message must match a ContainerDetailID field submitted in the associated QualificationReportDetailCreateRequest message. (ContainerDetailID %%1 missing for ContainerID %%2)	MailPieceCreateResponse
9092	A ContainerDetailID field submitted in the PostageStatementCreateRequest message must match a ContainerDetailID field submitted in the associated QualificationReportDetailCreateRequest message. (ContainerDetailID %%1 missing for ContainerID %%2)	Postage Statement Messages
9093	A ContainerDetailID field submitted in the PeriodicalStatementCreateRequest message must match a ContainerDetailID field submitted in the associated QualificationReportDetailCreateRequest message. (ContainerDetailID %%1 missing for ContainerID %%2)	Postage Statement Messages
9094	A ContainerDetailID field submitted in the ConsolidatedPeriodicalStatementCreateRequest message must match a ContainerDetailID field in the associated QualificationReportDetailCreateRequest message. (ContainerDetailID %%1 missing for ContainerID %%2)	Postage Statement Messages
9095	The number of pieces for a ContainerDetailID submitted in the MailPieceCreateRequest cannot exceed number of pieces associated to that ContainerDetailID field in the QualificationReportDetailCreateRequest. (ContainerDetailID %%1 within ContainerID %%2)	MailPieceCreateResponse
9096	ParentContainerID field in the QualificationReportDetailCreateRequest message is required when the IncludedInOtherDoc field is L and the SiblingContainerID is null. (ContainerDetailID %%1 missing for ContainerID %%2)	QualificationReportDetailCreateResponse (10.0)
9098	The ContainerID fields in the OriginalContainer block of the SiblingContainerCreateRequest message must match the ContainerID fields in the QualificationReportDetailCreateRequest message for the existing container. (Container ID: %%1)	SiblingContainerCreateResponse
9099	All QualificationReportDetailCreateRequest messages must be accepted before submitting the associated SummaryZipDestinationReportCreateRequest message for the specified MailingGroupID and CustomerGroupID.	SummaryZipDetaintationReportCreateResponse
9100	All QualificationReportDetailCreateRequest messages must be accepted before submitting the associated CustomerMailReportCreateRequest message for the specified MailingGroupID and CustomerGroupID.	CustomerMailReportCreateResponse
9101	The ContainerID fields in the FullContainer block of the ContainerUpdateRequest message must match the ContainerID fields in the Qualification Report for the existing container. (Container ID: %%1)	ContainerUpdateResponse
9102	The ScheduledInductionDate field in the SummaryRecordUpdate block of the ContainerUpdateRequest message must be within 30 days of PostageStatementMailingDate field in the QualificationReportDetailCreateRequest message for a Full-Service mailing.	ContainerUpdateResponse

Copyright © 2011 USPS®. All Rights Reserved.

Error Code	Error Message	Messages
9103	The ScheduledShipDate field in the SummaryRecordUpdate block of the ContainerUpdateRequest message must be within 30 days of PostageStatementMailingDate field in the QualificationReportDetailCreateRequest message for a Full-Service mailing.	ContainerUpdateResponse
9105	The SortationLevel must be AJ when the RateLevel is SP in the QualificationReportDetailCreateRequest message and FormType is FC in the QualificationReportSummaryCreateRequest message and the MailXMLPresentationCategory is M in the OpenMailingGroupRequest.	QualificationReportDetailCreateResponse (10.0)
9106	At least one SortationLevel in the Qualification Report message must be AJ when the RateCategory is S and the FormType is FC in the PostageStatementCreateRequest and the MailXMLPresentationCategory is M in the OpenMailingGroupRequest.	QualificationReportDetailCreateResponse (10.0)
9107	The ProcessingCategory in the PeriodicalStatement or CreatePeriodicalStatement blocks must be set to FL when the SortationLevel in the Qualification Report or BundleDetailCreateRequest is set to E or F.	Postage Statement Messages
9109	The ContainerType in the QualificationReportDetailCreateRequest must be set to P, Z, H, A, G, D, R, or C when the associated SortationLevel in the QualificationReportDetailCreateRequest is set to E or F for Periodicals.	QualificationReportDetailCreateResponse (10.0)
9111	PostageStatementMailingDate in the CreatePostageStatement block must match the PostageStatementMailingDate in QualificationReportDetailCreateRequest message when it's populated for the same ContainerID for the specified MailingGroupID and CustomerGroupID.	Postage Statement Messages
9112	The ContainerID fields in the OriginalContainer block of the SiblingContainerCancelRequest message must match the ContainerID fields in the QualificationReportDetailCreateRequest message for the existing container. (Container ID: %%1)	SiblingContainerCancelResponse
9113	ContainerID must be populated with the same value as the ContainerID in the ContainerInfoData block of the QualificationReportDetailCreateRequest message for the specified MailingGroupID and CustomerGroupID. Found Missing ContainerID: %%1	BundleDetailCreateResponse
9114	VersionID must be populated with the same value as the VersionID in the ContainerDetailData block of the QualificationReportDetailCreateRequest message for the specified MailingGroupID and CustomerGroupID. Found Missing VersionID: %%1	BundleDetailCreateResponse
9115	The count of the Copies field in the PeriodicalLineItemData block must be equal to the sum of NonCopies and SubreqCopies in the PeriodicalStatementCreateRequest message.	Postage Statement Messages
9116	The count of the Copies field in the PeriodicalLineItemData block must be equal to the sum of NonCopies and SubreqCopies in the ConsolidatedPeriodicalStatementCreateRequest message.	Postage Statement Messages

Copyright © 2011 USPS®. All Rights Reserved.

Error Code	Error Message	Messages
9130	The FormType field in the CreatePostageStatement block must be populated with PM when the ContainerType field in the PostageStatementLineItemData block is 6, 7, 8, 9, 10, or 11.	Postage Statement Messages
9132	The FormType field in the QualificationReport block of the QualificationReportSummaryCreateRequest message must be populated with PM when the ContainerType field in the ContainerInfoData block is 6, 7, 8, 9, 10, or 11.	Postage Statement Messages
9133	The FormType field in the CreatePostageStatement block must be populated with PM when the RateCategory field in the associated postage statement is P10, P11, P12, P13, P14, P15, or P16.	Postage Statement Messages
9136	The maximum weight for a Priority Mail cubic mail piece is 20lbs.	Postage Statement Messages
9137	The CRID field within the QualificationReportPreparer block in the QualificationReport block is required.	QualificationReportSummaryCreateResponse (10.0)
9138	The FormType in the qualification report must be set to FC when the SortationLevel in the is set to AK, AL, AM, AN, AO, AP, or AQ.	QualificationReportCreateResponse, QualificationReportDetailCreateResponse (10.0)
9139	The PMODIndicator field in the DocumentVersionData block must be populated with Yes when the ContainerType is populated with 6, 7, 8, 9, 10, or 11.	Postage Statement Messages
9140	The PMODIndicator field in the DocumentVersionData block must be populated with Yes when the RateCategory is populated with P12, P13, P14, P15, or P16.	Postage Statement Messages
9141	The FormType field in the CreatePostageStatement block must be populated with PM when the FlatRateIndicator is populated with O, C, P, or F.	Postage Statement Messages
9142	The IssueDate field in the MailXMLPostageStatementRequestHeaderInfo block of the ConsolidatedPeriodicalStatementCreateRequest message must match IssueDate field in the MailXMLPostageStatementRequestHeaderInfo block of BeginCombinedMailingRequest message.	Postage Statement Messages
9143	IssueNumber field in the MailXMLPostageStatementRequestHeaderInfo block of the ConsolidatedPeriodicalStatementCreateRequest message must match IssueNumber field in the MailXMLPostageStatementRequestHeaderInfo block of BeginCombinedMailingRequest message.	Postage Statement Messages
9144	VolumeNumber field in MailXMLPostageStatementRequestHeaderInfo block of the ConsolidatedPeriodicalStatementCreateRequest message must match VolumeNumber field in the MailXMLPostageStatementRequestHeaderInfo block of BeginCombinedMailingRequest message.	Postage Statement Messages

Copyright © 2011 USPS®. All Rights Reserved.

Error Code	Error Message	Messages
9145	CustomerReferenceID field in MailXMLPostageStatementRequestHeaderInfo block of ConsolidatedPeriodicalStatementCreateRequest message must match CustomerReferenceID in MailXMLPostageStatementRequestHeaderInfo block of BeginCombinedMailingRequest message.	Postage Statement Messages
9146	AgencyCostCode field in MailXMLPostageStatementRequestHeaderInfo block of the ConsolidatedPeriodicalStatementCreateRequest message must match AgencyCostCode field in MailXMLPostageStatementRequestHeaderInfo block of BeginCombinedMailingRequest message.	Postage Statement Messages
9147	PermitNumber field in MailXMLPostageStatementRequestHeaderInfo block of the ConsolidatedPeriodicalStatementCreateRequest message must match PermitNumber field in MailXMLPostageStatementRequestHeaderInfo block of BeginCombinedMailingRequest message.	Postage Statement Messages
9148	PermitType field in the MailXMLPostageStatementRequestHeaderInfo block of the ConsolidatedPeriodicalStatementCreateRequest message must match PermitType field in the MailXMLPostageStatementRequestHeaderInfo block of BeginCombinedMailingRequest message.	Postage Statement Messages
9149	PermitZip4 field in MailXMLPostageStatementRequestHeaderInfo block of the ConsolidatedPeriodicalStatementCreateRequest message must match PermitZip4 field in MailXMLPostageStatementRequestHeaderInfo block of BeginCombinedMailingRequest message.	Postage Statement Messages
9150	PublicationNumber field in MailXMLPostageStatementRequestHeaderInfo block of the ConsolidatedPeriodicalStatementCreateRequest message must match PublicationNumber in MailXMLPostageStatementRequestHeaderInfo block of BeginCombinedMailingRequest message.	Postage Statement Messages
9151	PostageStatementMethod in MailXMLPostageStatementRequestHeaderInfo block of ConsolidatedPeriodicalStatementCreateRequest message must match PostageStatementMethod in MailXMLPostageStatementRequestHeaderInfo block of BeginCombinedMailingRequest message.	Postage Statement Messages
9152	RateType field in the MailXMLPostageStatementRequestHeaderInfo block of the ConsolidatedPeriodicalStatementCreateRequest message must match RateType field in the MailXMLPostageStatementRequestHeaderInfo block of BeginCombinedMailingRequest message.	Postage Statement Messages
9153	ProcessingCategory field in MailXMLPostageStatementRequestHeaderInfo block of the ConsolidatedPeriodicalStatementCreateRequest message must match ProcessingCategory MailXMLPostageStatementRequestHeaderInfo block of BeginCombinedMailingRequest message.	Postage Statement Messages

Copyright © 2011 USPS®. All Rights Reserved.

Error Code	Error Message	Messages
9154	IssueDate field in the MailXMLPostageStatementRequestHeaderInfo block of the ConsolidatedPeriodicalStatementCreateRequest message must match IssueDate field in the MailXMLPostageStatementRequestHeaderInfo block of EndCombinedMailingRequest message.	Postage Statement Messages
9155	IssueNumber field in the MailXMLPostageStatementRequestHeaderInfo block of the ConsolidatedPeriodicalStatementCreateRequest message must match IssueNumber field in the MailXMLPostageStatementRequestHeaderInfo block of EndCombinedMailingRequest message.	Postage Statement Messages
9156	VolumeNumber field in MailXMLPostageStatementRequestHeaderInfo block of the ConsolidatedPeriodicalStatementCreateRequest message must match VolumeNumber field in the MailXMLPostageStatementRequestHeaderInfo block of EndCombinedMailingRequest message.	Postage Statement Messages
9157	CustomerReferenceID field in MailXMLPostageStatementRequestHeaderInfo block of ConsolidatedPeriodicalStatementCreateRequest message must match CustomerReferenceID in MailXMLPostageStatementRequestHeaderInfo block of EndCombinedMailingRequest message.	Postage Statement Messages
9158	AgencyCostCode field in MailXMLPostageStatementRequestHeaderInfo block of the ConsolidatedPeriodicalStatementCreateRequest message must match AgencyCostCode field in MailXMLPostageStatementRequestHeaderInfo block of EndCombinedMailingRequest message	Postage Statement Messages
9159	PermitNumber field in MailXMLPostageStatementRequestHeaderInfo block of the ConsolidatedPeriodicalStatementCreateRequest message must match PermitNumber field in MailXMLPostageStatementRequestHeaderInfo block of EndCombinedMailingRequest message.	Postage Statement Messages
9160	PermitType field in the MailXMLPostageStatementRequestHeaderInfo block of the ConsolidatedPeriodicalStatementCreateRequest message must match PermitType field in the MailXMLPostageStatementRequestHeaderInfo block of EndCombinedMailingRequest message.	Postage Statement Messages
9161	The PermitZip4field in MailXMLPostageStatementRequestHeaderInfo block of the ConsolidatedPeriodicalStatementCreateRequest message must match PermitZip4field in MailXMLPostageStatementRequestHeaderInfo block of EndCombinedMailingRequest message.	Postage Statement Messages

Copyright © 2011 USPS®. All Rights Reserved.

Error Code	Error Message	Messages
9162	PublicationNumber field in MailXMLPostageStatementRequestHeaderInfo block of the ConsolidatedPeriodicalStatementCreateRequest message must match PublicationNumber in MailXMLPostageStatementRequestHeaderInfo block of EndCombinedMailingRequest message.	Postage Statement Messages
9163	PostageStatementMethod in MailXMLPostageStatementRequestHeaderInfo block of ConsolidatedPeriodicalStatementCreateRequest message must match PostageStatementMethod in MailXMLPostageStatementRequestHeaderInfo block of EndCombinedMailingRequest message.	Postage Statement Messages
9164	RateType field in the MailXMLPostageStatementRequestHeaderInfo block of the ConsolidatedPeriodicalStatementCreateRequest message must match RateType field in the MailXMLPostageStatementRequestHeaderInfo block of EndCombinedMailingRequest message.	Postage Statement Messages
9165	ProcessingCategory field in MailXMLPostageStatementRequestHeaderInfo block of the ConsolidatedPeriodicalStatementCreateRequest message must match ProcessingCategory MailXMLPostageStatementRequestHeaderInfo block of EndCombinedMailingRequest message.	Postage Statement Messages
9167	The FormType field in the QualificationReport block of the QualificationReportSummaryCreateRequest message must be populated with FC when the ContentOfMail field in the DocumentVersionWithPermit block is populated with F.	QualificationReportSummaryCreateResponse (10.0)
9168	The FormType field in the CreatePostageStatement block must be populated with FC when the ContentOfMailType field in the DocumentVersionData block is populated with F.	Postage Statement Messages
9170	The ProcessingCategory field in the ContainerInfoData block must be populated with LT or FL when the ContentOfMail field in the DocumentVersionDataWithPermit block is populated with F.	QualificationReportDetailCreateResponse (10.0)
9171	The ProcessingCategory field must be populated with LT or FL when the ContentOfMailType field in the DocumentVersionData block is populated with F.	QualificationReportDetailCreateResponse (10.0)
9173	When ContentOfMail in the DocumentVersionDataWithPermit block or ContentOfMailType in the DocumentVersionData block is set to F, then all instances of those fields in the Mailing Group must also be set to F.	QualificationReportDetailCreateResponse (10.0)
9175	A postage statement may not be resubmitted with the EstimateIndicator field in the CreatePostageStatement block populated with Yes after the postage statement was previously submitted with an EstimateIndicator value of No.	Postage Statement Messages
9179	For eInduction processing, the ContainerBarcode field in the ContainerInfoData block must be populated when the corresponding ContainerType in the ContainerInfoData block is P, H, A, G, D, R, C, or Z.	QualificationReportCreateResponse (9.0C) QualificationReportDetailCreateResponse (10.0C)

Copyright © 2011 USPS®. All Rights Reserved.

Error Code	Error Message	Messages
9180	For eInduction processing, the EntryLocaleKey field in the ContainerInfoData block must be populated when the corresponding ContainerType is P, H, A, G, D, R, C, Z, M, T, O, E, F, S, 1, 2, 3, or L and the container is not a sibling. Note: This validation will be configurable in that it can be turned on or off as necessary.	QualificationReportCreateResponse (9.0C) QualificationReportDetailCreateResponse (10.0C)
9181	For eInduction processing, the ContainerBarcode field in the ContainerInfoData block must contain exactly 21 characters when the corresponding ContainerType in the ContainerInfoData block is P, H, A, G, D, R, C, or Z.	QualificationReportCreateResponse (9.0C) QualificationReportDetailCreateResponse (10.0C)
9182	For eInduction processing, the ContainerBarcode field in the ContainerInfoData block must begin with '99M' when the corresponding ContainerType in the ContainerInfoData block is P, H, A, G, D, R, C, or Z.	QualificationReportCreateResponse (9.0C) QualificationReportDetailCreateResponse (10.0C)
9183	For eInduction processing, the ContainerBarcode field in the ContainerInfoData block for IMcb(s)/pallets must be unique within the mailing group and amongst all containers associated to the SubmittingParty CRID that were finalized within the last 45 days.	QualificationReportCreateResponse (9.0C) QualificationReportDetailCreateResponse (10.0C)
9184	For eInduction processing, the ContainerBarcode field in the ContainerInfoData block for IMcb(s)/pallets must be unique within the mailing group and amongst all containers finalized within the last 45 days. Note: This validation will be a warning. In addition, this validation will be configurable in that it can be turned on or off as necessary.	QualificationReportCreateResponse (9.0C) QualificationReportDetailCreateResponse (10.0C)
9185	The CustomerReferenceID field in the PeriodicalStatement block must contain one value in the ConsolidatedPeriodicalStatementCreateRequest message.	Postage Statement Messages
9188	The MixedMailFlag field in the MailXMLQualReportRequestHeaderInfo block of the QualificationReportDetailCreateRequest must match the MixedMailFlag field in MailXMLQualReportRequestHeaderInfo block of QualificationReportSummaryCreateRequest message.	QualificationReportCreateResponse (9.0C) QualificationReportDetailCreateResponse (10.0C)
9191	The MailerID6 field in the SubmittingParty block of the QualificationReportDetailCreateRequest message must match the MailerID6 field in the SubmittingParty block of the QualificationReportSummaryCreateRequest message.	QualificationReportDetailCreateResponse (10.0C)
9192	The MailerID9 field in the SubmittingParty block of the QualificationReportDetailCreateRequest message must match the MailerID9 field in the SubmittingParty block of the QualificationReportSummaryCreateRequest message.	QualificationReportDetailCreateResponse (10.0C)

Copyright © 2011 USPS®. All Rights Reserved.

Error Code	Error Message	Messages
9194	The ShippingAgent field in the SubmittingParty block of the QualificationReportDetailCreateRequest message must match the ShippingAgent field in the SubmittingParty block of the QualificationReportSummaryCreateRequest message.	QualificationReportDetailCreateResponse (10.0C)
9195	The ReceivingAgent field in the SubmittingParty block of the QualificationReportDetailCreateRequest message must match the ReceivingAgent field in the SubmittingParty block of the QualificationReportSummaryCreateRequest message.	QualificationReportDetailCreateResponse (10.0C)
9196	The SoftwareName field in the SubmittingSoftware block of the QualificationReportDetailCreateRequest message must match the SoftwareName field in the SubmittingSoftware block of the QualificationReportSummaryCreateRequest message.	QualificationReportDetailCreateResponse (10.0C)
9197	The Vendor field in the SubmittingSoftware block of the QualificationReportDetailCreateRequest message must match the Vendor field in the SubmittingSoftware block of the QualificationReportSummaryCreateRequest message.	QualificationReportDetailCreateResponse (10.0C)
9198	The Version field in the SubmittingSoftware block of the QualificationReportDetailCreateRequest message must match the Version field in the SubmittingSoftware block of the QualificationReportSummaryCreateRequest message.	QualificationReportDetailCreateResponse (10.0C)
9199	The ApprovalDate field in the SubmittingSoftware block of the QualificationReportDetailCreateRequest message must match the ApprovalDate field in the SubmittingSoftware block of the QualificationReportSummaryCreateRequest message.	QualificationReportDetailCreateResponse (10.0C)
9200	The ApprovalKey field in the SubmittingSoftware block of the QualificationReportDetailCreateRequest message must match the ApprovalKey field in the SubmittingSoftware block of the QualificationReportSummaryCreateRequest message.	QualificationReportDetailCreateResponse (10.0C)
9204	A PMOD package cannot be placed inside a PMOD container for Priority Mail.	Postage Statement Messages
9205	ParentContainerID in the ContainerInfoData block in the QualificationReport block must point to another existing ParentContainerID within the Qualification Report. (Container ID: %%1)	QualificationReportDetailCreateResponse (10.0)
9206	SiblingContainerID field in the ContainerInfoData block in the QualificationReport block must point to a different container within the Qualification Report. (Container ID: %%1)	QualificationReportDetailCreateResponse (10.0)
9208	The PMODIndicator must be populated with the same value for all postage statements in a mailing group.	Postage Statement Messages
9209	The submitted StatementID does not exist.	ContainerManifestCreateResponse (10.0)
9210	At least one ContainerID submitted in the ContainerManifestCreateRequest must be associated to an IM Container Barcode provided in the IMcb field.	ContainerManifestCreateResponse (10.0)
9211	The combination of ContainerID and StatementID must be unique within the submitted ContainerManifestCreateRequest message.	ContainerManifestCreateResponse (10.0)

Copyright © 2011 USPS®. All Rights Reserved.

Error Code	Error Message	Messages
9213	The TotalDocVersionWithPermitBlocksCount must match number of DocumentVersionDataWithPermit blocks submitted in the QualificationReportDetailCreateRequest message.	QualificationReportDetailCreateResponse (10.0)
9215	ProcessingCategory must be populated with FL, NP, MP, or IR when the FormType in the QualificationReportSummaryCreateRequest message is BP.	QualificationReportDetailCreateResponse (10.0)
9216	Zone must be populated with N, 1, 3, 4, 5, 6, 7, 8, DDU or SCF when FormType field in the QualificationReportSummaryCreateRequest message is BP and Processing Category is FL, MP, IR, or NP.	QualificationReportDetailCreateResponse (10.0)
9217	EntryDiscount must be populated with N, B, S or D when FormType field in the QualificationReportSummaryCreateRequest message is BP.	QualificationReportDetailCreateResponse (10.0)
9218	TotalPieces and TotalCopies must be populated with the same values when FormType field in the QualificationReportSummaryCreateRequest message is BP.	QualificationReportDetailCreateResponse (10.0)
9219	ProcessingCategory must be populated with LT, FL, CD, or PF when FormType field in the QualificationReportSummaryCreateRequest message is FC.	QualificationReportDetailCreateResponse (10.0)
9220	Zone must be populated with N when FormType field in the QualificationReportSummaryCreateRequest message is FC and ProcessingCategory is LT, FL, CD, or PF.	QualificationReportDetailCreateResponse (10.0)
9221	EntryDiscount must be populated with N when FormType field in the QualificationReportSummaryCreateRequest message is FC.	QualificationReportDetailCreateResponse (10.0)
9222	ProcessingCategory must be populated with FL, MP, NP, or IR when FormType field in the QualificationReportSummaryCreateRequest message is ML.	QualificationReportDetailCreateResponse (10.0)
9223	Zone must be populated with N when FormType field in the QualificationReportSummaryCreateRequest message is ML and ProcessingCategory is MP or IR.	QualificationReportDetailCreateResponse (10.0)
9224	EntryDiscount must be populated with N when FormType field in the QualificationReportSummaryCreateRequest message is ML.	QualificationReportDetailCreateResponse (10.0)
9225	TotalPieces and TotalCopies must be populated with the same values when the FormType field in the QualificationReportSummaryCreateRequest message is ML.	QualificationReportDetailCreateResponse (10.0)
9226	ProcessingCategory must be populated with LT, FL, MP, IR, or NP when FormType field in the QualificationReportSummaryCreateRequest message is PE.	QualificationReportDetailCreateResponse (10.0)
9227	Zone must be populated with N, 1, 3, 4, 5, 6, 7, 8, ICD, ADC, DDU, or SCF when FormType field in the QualificationReportSummaryCreateRequest message is PE and Zone is provided.	QualificationReportDetailCreateResponse (10.0)

Copyright © 2011 USPS®. All Rights Reserved.

Error Code	Error Message	Messages
9228	ContainerChargeContainerLevel must be populated with 3, 5, A, or M when FormType field in the QualificationReportSummaryCreateRequest message is PE.	QualificationReportDetailCreateResponse (10.0)
9229	InOutCountyIndicator must be populated with N or I when FormType field in the QualificationReportSummaryCreateRequest message is PE.	QualificationReportDetailCreateResponse (10.0)
9230	ProcessingCategory must be populated with LT, FL, MP, IR, NP, CM, NA, or NB when FormType field in the QualificationReportSummaryCreateRequest message is SM. (User Postage Statement ID: %%1).	QualificationReportDetailCreateResponse (10.0)
9231	Zone must be populated with N when FormType FormType field in the QualificationReportSummaryCreateRequest message is SM and ProcessingCategory is LT, FL, MP, IR, or CM. (User Postage Statement ID: %%1).	QualificationReportDetailCreateResponse (10.0)
9232	EntryDiscount must be populated with N, B, S, or D when FormType FormType field in the QualificationReportSummaryCreateRequest message is SM. (User Postage Statement ID: %%1).	QualificationReportDetailCreateResponse (10.0)
9233	The Zone field in the ContainerDetailData block must be populated when the FormType field in the QualificationReportSummaryCreateRequest message is PE for Periodicals.	QualificationReportDetailCreateResponse (10.0)
9235	The StandardFlatType field in the DocumentVersionDataWithPermit block must be populated when FormType field in the QualificationReportSummaryCreateRequest message is SM and ProcessingCategory is FL.	QualificationReportDetailCreateResponse (10.0)
9236	A Qualification Report cannot have records with the IncludedInOtherDoc field values set to both O and L.	QualificationReportDetailCreateResponse
9237	QualificationReportDetailCreateRequest for a co-palletized mailing with the ContainerType set to F, O, or T can only be submitted when the FormType in the associated QualificationReportSummaryCreateRequest is FC or SM.	QualificationReportDetailCreateResponse (10.0)
9238	PostageStatementMailingDate in the CreatePeriodicalStatement block must match the PostageStatementMailingDate in QualificationReportDetailCreateRequest message when it's populated for the same ContainerID for the specified MailingGroupID and CustomerGroupID.	Postage Statement Messages
9239	PostageStatementMailingDate in the PeriodicalStatement block must match the PostageStatementMailingDate in QualificationReportDetailCreateRequest message when it's populated for the same ContainerID for the specified MailingGroupID and CustomerGroupID.	Postage Statement Messages
9241	ProcessingCategory field in the ContainerInfoData block must be LT, FL, or CD when the FormType field in the QualificationReportSummaryCreateRequest message is FC and the MailXMLPresentationCategory field in the OpenMailingGroupRequest message is 'M'.	QualificationReportDetailCreateResponse (10.0)

Copyright © 2011 USPS®. All Rights Reserved.

Error Code	Error Message	Messages
9242	The fields within the DocumentVersionDataWithPermit block for each unique VersionID must match for all QualificationReportDetailCreateRequest messages associated to the same Qualification Report. VersionID (%%1)	QualificationReportDetailCreateResponse (10.0)
9243	The QualificationReportSummaryCreateRequest/ QualificationReportDetailCreateRequest message is not supported in Mail.XML 10.0C.QualificationReportSummaryCreateRequest/ QualificationReportDetailCreateRequest	QualificationReportCreateResponse
9244	The maximum weight for a Priority Mail Regional Rate Box A mail piece is 15 lbs.	Postage Statement Messages
9245	The maximum weight for a Priority Mail Regional Rate Box B mail piece is 20 lbs.	Postage Statement Messages
9246	The PostageStatementMailingDate field in the ContainerInfoData block in the QualificationReportDetailCreateRequest message cannot span the price change date; within a job these dates must either be all before or all after %%1.	QualificationReportDetailCreateResponse (10.0)
9247	The pieces associated to a ContainerDetailID in the Postage-, Periodical-, or ConsolidatedPeriodicalStatementCreateRequest cannot exceed the sum of TotalPieces for that ContainerDetailID in the Qualification Report (ContainerID %%1 ContainerDetailID %%2).	Postage Statement Messages
9248	A ContainerID in the MailPieceCreateRequest must exist in an accepted Qualification Report (Container ID %%1).	MailPieceCreateResponse
9249	A ContainerID in the Postage-, Periodical-, or ConsolidatedPeriodicalStatementCreateRequest must exist in an accepted Qualification Report (Container ID %%1).	Postage Statement Messages
9250	FormType field in the QualificationReportSummaryCreateRequest message must be FC or SM when the MailXMLPresentationCategory field in the OpenMailingGroupRequest message is populated with M.	QualificationReportSummaryCreateResponse (10.0)
9251	The number of QualificationReportDetailCreateRequest messages associated to a QualificationReportSummaryCreateRequest message cannot exceed the value populated in the TotalMessageCount field in the QualificationReportSummaryCreateRequest.	QualificationReportDetailCreateResponse
9252	The PostageStatementMailingDate cannot be set to a date on or after the upcoming price change date - %%1	Postage Statement Messages
9254	When PreparedAsSM is True and FormType is PM, then ProcessingCategory must be FL, LT, or PF, and RateCategory must be S.	Postage Statement Messages
9255	For MLOCR mailings, the rate category must be one of E, H, L3, L4, N, or S for Flats or one of E, H, L1, L2, L3, L4, N, or S for Letters.	Postage Statement Messages
9256	The container status cannot be updated to C or D when the container is paid for on a Finalized Postage Statement (CTR ID %%1).	ContainerUpdateCreateResponse
9257	The IMB block must be populated in the MailPieceBlock of the MailPieceCreateRequest message.	MailPieceCreateResponse

Copyright © 2011 USPS®. All Rights Reserved.

Error Code	Error Message	Messages
9308	The OpenMailingGroupCreateRequest message is no longer accepted for Mail.XML version 7.0C or 8.0B after %SubmitDateCutoff%.	OpenMailingGroup Response
8004	More than %%1 failures for Warning code: %%2	Multiple Messages

Code	Warning Message	Messages
8357	When ContainerStatus is T, the ContainerUpdate message can only update the the Transportation Update fields listed in the Mail.XML Technical Specification. (Container ID: %%1)	ContainerUpdateR esponse
8359	Postage cancellation will occur when the ContainerStatus is C or D and the Container Status from the original Mail.dat job is R and the postage statement status from the original Mail.dat job is UPD. (Container ID: %%1)	ContainerUpdateR esposne
8852	The number of In County Copies does not match between the Piece and Pound charge lines for User Postage Stmt %%1. Piece: %%2, Pound: %%3.	Postage Statement Messages
8853	The number of Out County Copies does not match between the Piece and Pound charge lines for User Postage Stmt %%1. Piece: %%2, Pound: %%3	Postage Statement Messages
8872	The PDRMailPieceBlock block and the PDRRangePieceBlock block are not supported.	Multiple
9022	The EntryPointLocaleKey in the ContainerInfoData block must be populated with alphanumeric characters and cannot be populated with ORIGIN when the EntryPointFacilityType in the ContainerInfoData block is O and the mailing is Full-Service or Mixed Service.	QualificationRepor tCreateResponse
9049	The AdPercent field in the DocumentVersionData block does not match the previously stored advertising percentage for VersionID (%%1)	Postage Statement Messages
9057	The PieceWeight field in the DocumentVersionData block does not match the previously stored edition weight for VersionID (%%1)	Postage Statement Messages

2.5 Additional Constraints

N/A

2.6 *PostalOne!* WSDL Information

All web services transactions that are made with the USPS should comply with the WSDL specification that are posted on RIBBS® and can be downloaded from the following location:
http://ribbs.usps.gov/intelligentmail_guides/documents/tech_guides/xmlspec/wsdls/wsdls.htm

A web services request must include a valid and active USPS User ID and Password as defined in the UserAuthenticationInfo.xsd file that is provided as part of the WSDL downloable files. A typical web service message construct defined is as follows:

Copyright © 2011 USPS®. All Rights Reserved.

```
<wsdl:message name="DeliveryApptContentUpdateRequest">
        <wsdl:part name="authInfo" element="auth:AuthenticationInfo"/>
        <wsdl:part name="apptContentUpdate" element="tns:apptContentUpdate"/>
</wsdl:message>
```

With the following

String-typed WSDL:

```
        <wsdl:message name="StartTheClockQueryRequest">
                <wsdl:part element="auth:AuthenticationInfo" name="authInfo"/>
                <wsdl:part element="tns:startTheClockQuery" name="startTheClockQuery"/>
        </wsdl:message>
```

XSD-typed WSDL:

```
        <wsdl:message name="FullServiceStartTheClockQueryRequest">
                <wsdl:part element="uspsmxml:FullServiceStartTheClockQueryRequest"
                name="FullServiceStartTheClockQueryRequest"/>
        </wsdl:message>
```

USPS will validate and authenticate the user information before processing the request. An error message will be returned in response to the web service request for invalid user information.

Types of WSDLS

There are two types of WSDLs, the String-Type WSDL and Message-Type WSDL. The following is basic information on each of the WSDL types to help customers understand the advantages and disadvantages of consuming the string versus message type WSDL.

- **Consuming String-Type WSDLs:**

  The string-type is a more generalized method, in which a customer needs to manually register each message type and register all services in their environment to later use for invoking the remote service. This is a manual process and cannot be automated easily. This is the major disadvantage of using this method. The advantage is that one string type WSDL can be used for any version of Mail.XML but they need to be manually registered in the code. As of the Mail.XML 9.0X implementation, the USPS only supports Message-Type WSDLs.

- **<u>Consuming Message-Type WSDLs:</u>**

  The message-type eliminates the need to manually registering each service and message type. With this method, a customer can use an automated tool that can setup their environment without the manually registering each service. However, this approach requires updates to WSDLs every time a new Mail.XML version is released. In other words, it is tightly coupled with the Mail.XML Specification Version. The USPS is transitioning to this type of Message WSDLs to remove manual editing and registering of messages. As of the Mail.XML 9.0 release, USPS no longer supports String-Type WSDLs.

The customer must use either string-type or message-type to consume the services. The URLs to download all WSDLs are provided in Appendix D.

2.7 Permit Information

Copyright © 2011 USPS®. All Rights Reserved.

Permit Holder – This is the permit charged for the postage statement. The *PostalOne!* system uses the PermitHolderData block to reference the PermitNumber or PublicationNumber for a Periodicals postage statement. The 'PermitType' and 'PermitZip4' fields are also available in the PermitHolderData block and is associated to the 'Permit Number'. This information is displayed in the 'Permit Holder' section of a postage statement.

PermitHolderData

- MID – Optional block
- CRID – Optional field
- ContactName – Required field
- PermitPublicationData
    - PermitNumber – Required field
    - PermitType – Required field
    - PermitZip4 – Required field
    - PublicationNumber – Required for Periodicals

Mailing Agent - This identifies the organization that prepared the mailing and/or delivered it to the postal service for mailing. This information is linked to the user's login account. The *PostalOne!* system looks up the Company Name, Address Line 1, Address Line2, City, State, Zip Code, Zip Code4, Contact Phone, and Contact Email using the PermitNumber and PermitZip4 fields within th MailingAgentData block. This information is displayed in the Mailing Agent section of a postage statement.

MailingAgentData

- MID – Optional block
- CRID – Optional field
- ContactName – Required field
- PermitPublicationData
    - PermitNumber – Required field
    - PermitType – Required field
    - PermitZip4 – Required field
    - PublicaitonNumber – Required for Periodicals

Mail Owner - This identifies the organization who owns the mail being sent. The *PostalOne!* system looks up the Company_Name, Address_Line1, Address_Line2, City, State, Zip_Code, Zip_Code4, Contact_Phone, and Contact_Email in the P_Finance, P_Permit, and P_Company tables using the PermitNumber and PermitZip4 fields within the PermitPublicationData block within the MailingOwnerData block within the CreatePostageStatement block in the PostageStatementCreateRequest message. The State is determined from the Zip_Code. The *PostalOne!* system will populate the Mail Owner (Organization for Mailing is Prepared is Prepared) information with Permit Holder information. This information is displayed in the Org. For Mailing is Prepared section of a postage statement.

MailingOwnerData

- MID – Optional block
- CRID – Optional field
- ContactName – Required field
- PermitPublicationData
    - PermitNumber – Required field
    - PermitType – Required field
    - PermitZip4 – Required field
    - PublicationNumber – Required for Periodicals

Publisher Data - The *PostalOne!* system looks up the Company_Name, Address_Line1, Address_Line2, City, State, Zip_Code, Zip_Code4, Contact_Phone, and Contact_Email in the P_Finance, P_Permit, and P_Company tables using the PublicationNumber or PermitNumber field within the PermitPublicationData

Copyright © 2011 USPS®. All Rights Reserved.

block within PublisherData block within the CreatePeriodicalStatement block. This information is displayed in the Publication Title and Owner or News Agent's Name section of a periodicals postage statement.

PublisherData

- MID – Optional block
- CRID – Optional field
- ContactName – Required field
- PermitPublicationData
    - PermitNumber – Required for Pending Periodicals
    - PermitType – Required for Pending Periodicals
    - PermitZip4 – Required for Pending Periodicals
    - PublicationNumber – Required for Periodicals

SubmittingParty Block (All Messages):

- MailerID6 – Optional field
- MailerID9 – Optional field
- CRID – Optional field
- SchedulerID – field is ignored
- MaildatUserLicenseCode – field is ignored

The information in the SubmittingParty block is not displayed on postage statements or reports on the *PostalOne!* Dashboard.

SubmittingSoftware Block (All Messages):

- SoftwareName – Required field
- Vendor – Required field
- Version – Required field
- ApprovalDate – Optional field
- ApprovalKey – Optional field

The information in the SubmittingSoftware block is not displayed on postage statements or reports on the *PostalOne!* Dashboard.

OpenMailingGroupRequest

PermitPublicationData – fields should be populated with Mailing Agent permit information:

- PermitNumber – Required field
- PermitType – Required field
- PermitZip4 – Required field
- PublicationNumber – Required for Periodicals

QualificationReportCreateRequest

MailOwner Block – fields should be populated with Mail Owner permit information:

- PermitNumber – Required field
- PermitType – Required field
- PermitZip4 – Required field
- PublicationNumber – Required for Periodicals

QualificationReportPreparer Block – fields should be populated with Mailing Agent permit information:

- PermitNumber – Required field

Copyright © 2011 USPS®. All Rights Reserved.

- PermitType – Required field
- PermitZip4 – Required field
- PublicationNumber – Required for Periodicals
- MailerID6 – Optional field
- MailderID9 – Optional field
- CRID – Optional field

PermitPublicationData Block – fields should be populated with Permit Holder permit information:

- PermitNumber – Required field
- PermitType – Required field
- PermitZip4 – Required field
- PublicationNumber – Required for Periodicals

QualificationReportSummaryCreateRequest

QualificationReportPreparer Block – fields should be populated with Mailing Agent permit information:

- PermitNumber – Required field
- PermitType – Required field
- PermitZip4 – Required field
- PublicationNumber – Required for Periodicals
- MailerID6 – Optional field
- MailderID9 – Optional field
- CRID – Optional field

QualificationReportDetailCreateRequest

MailOwner Block – fields should be populated with Mail Owner permit information:

- PermitNumber – Required field
- PermitType – Required field
- PermitZip4 – Required field
- PublicationNumber – Required for Periodicals

PermitPublicationData Block – fields should be populated with Permit Holder permit information:

- PermitNumber – Required field
- PermitType – Required field
- PermitZip4 – Required field
- PublicationNumber – Required for Periodicals

PostageStatementCreateRequest

PermitHolderData Block – fields should be populated with Permit Holder permit information:

- MID – Optional block
- CRID – Optional field
- ContactName – Required field
- PermitPublicationData
    - PermitNumber – Required field
    - PermitType – Required field
    - PermitZip4 – Required field
    - PublicationNumber – Required for Periodicals

MailingOwnerData Block – fields should be populated Mail Owner permit information:

Copyright © 2011 USPS®. All Rights Reserved.

- MID – Optional block
- CRID – Optional field
- ContactName – Required field
- PermitPublicationData
    - PermitNumber – Required field
    - PermitType – Required field
    - PermitZip4 – Required field
    - PublicationNumber – Required for Periodicals

MailingAgentData block – fields should be populated with Mailing Agent permit information:

- MID – Optional block
- CRID – Optional field
- ContactName – Required field
- PermitPublicationData
    - PermitNumber – Required field
    - PermitType – Required field
    - PermitZip4 – Required field
    - PublicationNumber – Required for Periodicals

PermitHolderForAPData block – fields should be populated with Permit Holder permit information:

- MID – Optional block
- CRID – Optional field
- ContactName – Required field
- PermitPublicationData
    - PermitNumber – Required field
    - PermitType – Required field
    - PermitZip4 – Required field
    - PublicationNumber – Required for Periodicals

PeriodicalStatementCreateRequest

MailingAgentData block – fields should be populated with Mailing Agent permit information:

- MID – Optional block
- CRID – Optional field
- ContactName – Required field
- PermitPublicationData
    - PermitNumber – Required field
    - PermitType – Required field
    - PermitZip4 – Required field
    - PublicationNumber – Required for Periodicals

PublisherData block – fields should be populated with Permit Holder permit information:

- MID – Optional block
- CRID – Optional field
- ContactName – Required field
- PermitPublicationData
    - PermitNumber – Required for Pending Periodicals
    - PermitType – Required for Pending Periodicals
    - PermitZip4 – Required for Pending Periodicals
    - PublicationNumber – Required for Periodicals

Copyright © 2011 USPS®. All Rights Reserved.

ConsolidatedPeriodicalStatementCreateRequest

MailingAgentData block – fields should be populated with Mailing Agent permit information:

- MID – Optional block
- CRID – Optional field
- ContactName – Required field
- PermitPublicationData
    - PermitNumber – Required field
    - PermitType – Required field
    - PermitZip4 – Required field
    - PublicationNumber – Required for Periodicals

PublisherData block – fields should be populated with Permit Holder permit information:

- MID – Optional block
- CRID – Optional field
- ContactName – Required field
- PermitPublicationData
    - PermitNumber – Required for Pending Periodicals
    - PermitType – Required for Pending Periodicals
    - PermitZip4 – Required for Pending Periodicals
    - PublicationNumber – Required for Periodicals

Copyright © 2011 USPS®. All Rights Reserved.

3. Mail.XML Version 9.0B eDoc and Miscellaneous Messages

Below are the messages where a new element or structure of the message is changed from the Mail.XML 8.1 version. It is recommended that customer refers to the above sections for the structure of other messages; however it critical that the customer implement those messages using the new modularized structure.

QualificationReportCreateRequest
QualificationReportQueryRequest
QualificationReportQueryResponse
BundleDetailCreateRequest
PostageStatementCreateRequest
PostageStatementQueryResponse
PeriodicalStatementCreateRequest
PeriodicalStatementQueryResponse
ConsolidatedPeriodicalStatementCreateRequest
SummaryZipDestinationReportCreateRequest
ContainerBundleReportCreateRequest
ContainerBundleReportQueryResponse
ContainerUpdateRequest
MailPieceCreateRequest
MailPieceUpdateRequest

The Mail.XML 8.0B will continue to support all of the Mail.XML 8.0B and Mail.XML 7.0C specification messages All of the business rules and the structure of the messages are same as defined above in Section 2.2. However, in addition to the messages listed above – following new eDoc messages have been implemented in Mail.XML 8.0B version:

- SummaryZipDestinationReportCreateRequest
- SummaryZipDestinationReportCreateResponse
- CustomerMailReportCreateRequest
- CustomerMailReportCreateResponse

The Mail.XML version 7.0C is an overall umbrella specification containing all WWS functionality, existing Transportation and appointment management, and extra eDoc messages. The extra eDoc messages will support full-service pieces, periodicals reports and postage statements, and combined mailing web services messaging. Mail.XML eDOC Web Service Messages will allow customers to submit and receive postal documents electronically via Web Services. Two additional technical specifications are provided to describe the entire scope of the Mail.XML implementation, the Postal Service Mail.XML Technical Specification for Appointment Scheduling (FAST) and the Postal Service Mail.XML Technical Specification for Full-Service Feedback and Profile Management available at http://ribbs.usps.gov/index.cfm?page=intellmailguides.

The table below lists all Mail.XML 9.0B messages for postage payment and reporting that *PostalOne!* started supporting from November 2009.

Message
BeginCombinedMailingRequest
BeginCombinedMailingResponse
BundleDetailCancelRequest
BundleDetailCancelResponse

Copyright © 2011 USPS®. All Rights Reserved.

Message
BundleDetailCreateRequest
BundleDetailCreateResponse
CloseMailingGroupRequest
CloseMailingGroupResponse
ConsolidatedPeriodicalStatementCreateRequest
ConsolidatedPeriodicalStatementCreateResponse
ContainerBundleReportCancelRequest
ContainerBundleReportCancelResponse
ContainerBundleReportCreateRequest
ContainerBundleReportCreateResponse
ContainerBundleReportQueryRequest
ContainerBundleReportQueryResponse
ContainerStatusQueryRequest
ContainerStatusQueryResponse
CustomerMailReportCreateRequest
CustomerMailReportCreateResponse
EndCombinedMailingRequest
EndCombinedMailingResponse
ContainerUpdateRequest
ContainerUpdateResponse
MailingGroupQueryRequest
MailingGroupQueryResponse
MailPieceCancelRequest
MailPieceCancelResponse
MailPieceCreateRequest
MailPieceCreateResponse
MailPieceUpdateRequest
MailPieceUpdateResponse
OpenMailingGroupRequest
OpenMailingGroupResponse
OriginalContainerLinkageCancelRequest
OriginalContainerLinkageCancelResponse
OriginalContainerLinkageCreateRequest
OriginalContainerLinkageCreateResponse
PaymentMessageQueryRequest
PaymentMessageQueryResponse
PeriodicalStatementCreateRequest
PeriodicalStatementCreateResponse
PeriodicalStatementQueryRequest
PeriodicalStatementQueryResponse
PostageAdjustmentCreateRequest
PostageAdjustmentCreateResponse
PostageStatementCancelRequest
PostageStatementCancelResponse

Copyright © 2011 USPS®. All Rights Reserved.

Message
PostageStatementCreateRequest
PostageStatementCreateResponse
PostageStatementQueryRequest
PostageStatementQueryResponse
PostageStatementStatusQueryRequest
PostageStatementStatusQueryResponse
QualificationReportCreateRequest
QualificationReportCreateResponse
ReconciliationReportQueryRequest
ReconciliationReportQueryResponse
SiblingContainerCancelRequest
SiblingContainerCancelResponse
SiblingContainerCreateRequest
SiblingContainerCreateResponse
SummaryZipDestinationReportCreateRequest
SummaryZipDestinationReportCreateResponse

3.1 BeginCombinedMailingRequest

Purpose
The beginCombinedMailing method sends the combined mailing ID information and starts a combined mailing.
Business Rules

- Will accept if a combined mailing is NOT already open for a mailing group
- Will reject if a combined mailing is already open for a mailing group
- This message is used to combine statements from the PostageStatementCreateRequest.
- This message is used to combine statements from the PeriodicalStatementCreateRequest and/or the ConsolidatedPeriodicalStatementCreateRequest
- All postage statement in a combined mailing must be the same form type
- Beginning in Release 26.1, First-Class Commerical Plus Parcels will be accepted when the following conditions are met:
    - FormType in the CreatePostageStatement block is FC (First-Class)
    - PresentationCategory in the CreatePostageStatement block is PF (Parcel, First-Class)
    - PriceType in the CreatePostageStatement block is commercialplus

Note - Important information on combined and consolidated postage statements:

Part A – Currently, the Mail.XML specs allows the user to provide different data for the fields listed in Part C below for each postage statement request. During a Combined Mailing Request or during a Consolidated Periodical Postage Statement Request, the values of these fields (listed in Part C) have to be same from a business and processing stand-point. The current implementation of Mail.XML does not provide a feature where the user could supply this data for all of the postage statements that are consolidated or combined. A future release of Mail.XML and *PostalOne!* will cater to this requirement where the user will be required to provide with only one set of data (listed in Part C) for the whole message set of combined or consolidated postage statements. However, in the current implementation, USPS recommends all users to follow the set of instructions provided in section.

Copyright © 2011 USPS®. All Rights Reserved.

Part B – For the following set of postage statement message requests, follow the instructions documented in Part C below.

- BeginCombinedMailingRequest
- EndCombinedMailingRequest
- ConsolidatedPeriodicalStatementCreateRequest
- PeriodicalStatementCreateRequest
- PostageStatementCreateRequest

Part C – For all of the postage statement create requests (items 3, 4, and 5 from above), during a Combined Mailing request (meaning postage statements enclosed in between items 1 and 2 from above) and for ConsolidatedPeriodicalStatementCreateRequest user must provide the same values inside all of the postage statements for the following fields.

- IssueDate
- IssueNumber
- VolumeNumber
- CustomerReferenceID
- AgencyCostCode
- PermitPublicationData *(block of PermitHolderData block)*
- PostagePaymentMethod
- RateType
- ProcessingCategory

3.1.1 BeginCombinedMailingRequest Data Structure

Field Description

Mail.XML 9.0B - BeginCombinedMailingRequest				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
MailXMLPostageStatement RequestHeaderInfo block	MailXMLPostage StatementRequestHeaderInfo		Attributes block	See Appendix A for Details
SubmittingParty Block	participantIDType		Required block; Identifies the customer submitting the message	See Appendix A for Details
SubmittingSoftware Block	participantIDType		Required block; Identifies the software submitting the message	See Appendix A for Details

3.2 BeginCombinedMailingResponse

Purpose

The BeginCombinedMailingResponse will be used by USPS to notify the customer if their request to create a combined mailing has been accepted or rejected.

Error/Return Codes

Refer Section 2.6 to refer shared error/return codes and also a list of error/return codes tied this message.

Copyright © 2011 USPS®. All Rights Reserved.

Business Rules

- Will accept if a combined mailing is NOT already open for a mailing group
- Will reject if a combined mailing is already open for a mailing group
- This message is used to combine statements from the PostageStatementCreateRequest.
- This message is used to combine statements from the PeriodicalStatementCreateRequest and/or the ConsolidatedPeriodicalStatementCreateRequest
- The ReturnInfo block will have a description for rejection

3.2.1 BeginCombinedMailingResponse Data Structure

Field Description

Mail.XML 9.0B - BeginCombinedMailingResponse				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
BeginCombinedMailingAccept Block begins			Block received upon accepting request	
MailXMLMsgResponseHeaderInfo Block begins	MailXMLMsgResponseHeaderInfo		Attributes block	See Appendix A for Details
CombinedMailingID	Non-negative Integer		Optional	
ReturnInfo Block	ReturnInfo		Optional Provides reason for return Not required Multiple pairings of ReturnCode and ReturnDescription can be provided in the block	See Appendix A for Details
BeginCombinedMailingAccept Block ends				
BeginCombinedMailingReject Block begins			Block received upon rejecting request	
MailXMLMsgResponseHeaderInfo Block	Attributes		Attributes block	See Appendix A for Details
ReturnInfo Block	ReturnInfo		Required Provides reason for return Required Multiple pairings of ReturnCode	See Appendix A for Details

Copyright © 2011 USPS®. All Rights Reserved.

Mail.XML 9.0B - BeginCombinedMailingResponse				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
			and ReturnDescription can be provided in the block	
BeginCombinedMailingReject Block ends				

3.3 BundleDetailCancelRequest

Purpose
Message cancels the bundle detail data submitted related to a qualification report
Business Rules

- Message cannot be sent until the BundleDetailCreateRequest message has been filed in the *PostalOne!* system and accepted through the BundleDetailCreateResponse message
- Updated number of pieces must be received for the specified MailingGroupID, CustomerGroupID, and BundleID
- A MailPieceCancelRequest message must be accepted with the updated number of cancelled pieces in the specified bundle
- BundleID can be reused after it has been cancelled

3.3.1 BundleDetailCancelRequest Data Structure

Field Description

Mail.XML 9.0B - BundleDetailCancelRequest				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
MailXMLHeaderInfo block begins			Attributes block	
CustomerGroupID	String, 25 characters		Required field; must be populated with the same value as the value populated in the CustomerGroupID field of the BundleDetailCreateResponse	
MailingGroupID	Non-Negative Integer		Required field; must be populated with the same value as the value populated in the MailingGroupID	

Copyright © 2011 USPS®. All Rights Reserved.

Mail.XML 9.0B - BundleDetailCancelRequest				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
			field of the BundleDetailCreateResponse	
MaildatJobID			Optional	
UserLicenseCode			Optional	
MailXMLHeaderInfo block ends				
SubmittingParty Block	ParticipantIDType		Required block; Identifies the customer submitting the message	Refer 'ParticipantIDType' complex type in Appendix A.
SubmittingSoftware Block	SubmittingSoftwareType		Required block; Identifies the software submitting the message	Refer 'SubmittingSoftware' complex type in Appendix A.
UserLicenseCode	String, 4 characters		Field not supported	
MaildatJobID	String, 8 characters		Field not supported	
CustomerGroupID	String, 25 characters		Field not supported; redundant	
MailingGroupID	Non-Negative Integer		Field not supported; redundant	
Sequence Block BEGIN			Required 1 to many allowed	Placed ContainerID and BundleID in a sequence block to create a link to establish relationship between BundleIDs and ContainerIDs
ContainerID	String, 6 characters		Required	
BundleID	String, 6 characters		XSD Stand-point: Optional 0 to many allowed Implementation Stand-point: REQUIRED field	
Sequence Block END				

Copyright © 2011 USPS®. All Rights Reserved.

3.4 BundleDetailCancelResponse

Purpose
Accept or reject a request to cancel bundle detail data

Error/Return Codes
Refer Section 2.6 to view shared error/return codes and also a list of error/return codes tied this message.

Business Rules
- Will accept if the bundle detail data exists in the *PostalOne!* system
- Will reject if the bundle detail data does not exist in the *PostalOne!* system
- Will reject if any pieces in the BundleDetail block have finalized postage

3.4.1 BundleDetailCancelResponse Data Structure

Field Description

Mail.XML 9.0B - BundleDetailCancelResponse				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
BundleDetailCancelAccept block begins			Response from USPS indicating that the BundleDetailCancelRequest message was accepted	
MailXMLMsgResponseHeaderInfo Block	MailXMLMsgResponseHeaderInfo			See Appendix A for Details
ReturnInfo block	ReturnInfo		Optional block; 0 to many pairings of ReturnCode and ReturnDescription	See Appendix A for Details
BundleDetailCancelAccept block ends				
BundleDetailCancelReject block begins			Response from USPS indicating that the BundleDetailCancelRequest message was rejected	
MailXMLMsgResponseHeaderInfo Block	MailXMLMsgResponseHeaderInfo			See Appendix A for Details
ReturnInfo Block	ReturnInfo			See Appendix A for Details
BundleDetailCancelReject				

Copyright © 2011 USPS®. All Rights Reserved.

Mail.XML 9.0B - BundleDetailCancelResponse				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
block ends				

3.5 BundleDetailCreateRequest

Purpose
Message sends bundle detail information associated to a qualification report to the *PostalOne!* system
Business Rules

- Message cannot be sent until a QualificationReportCreateRequest message has been accepted and the customer receives an acceptance message through the QualificationReportCreateResponse
- Bundle detail data from this message must be tied to that of the QualificationReportCreateRequest message (ContainerID)
- MailingGroupID and CustomerGroupID must exist for an open mailing
- VersionID must be the same for the BundleDetail and ContainerDetailData blocks
- BundleID in the BundleDetail block must be unique within each container

3.5.1 BundleDetailCancelRequest Data Structure

Field Description

Mail.XML 9.0B - BundleDetailCreateRequest				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
BundleDetailCreate Request Message BEGINS				
MailXMLHeaderInfo block begins				
CustomerGroupID	String, 25 characters		Optional	
MailingGroupID	Non-Negative Integer		Optional	
MaildatJobID	Mailxml_base:job IDType	Simple type	Optional	Refer this simple type in Appendix C
UserLicenseCode	Mailxml_base:us erLicenseCodeTy pe	Simple type	Optional	Refer this simple type in Appendix C
MailXMLHeaderInfo block ends				
SubmittingParty Block	ParticipantIDType		Required block; Identifies the customer submitting the	Refer 'ParticipantIDTyp e' complex type in Appendix .

Copyright © 2011 USPS®. All Rights Reserved.

Mail.XML 9.0B - BundleDetailCreateRequest				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
			message	
SubmittingSoftware Block	SubmittingSoftwareType		Required block; Identifies the software submitting the message	Refer 'SubmittingSoftware' complex type in Appendix C.
Choice Block BEGINS			Required	
Sequence Block BEGINS				
UserLicenseCode	Mailxml_base:userLicenseCodeType		Field not supported	Refer this simple type in Appendix C
MaildatJobID	Mailxml_base:jobIDType		Field not supported	Refer this simple type in Appendix C
Sequence Block ENDS				
Sequence Block BEGINS				
CustomerGroupID	String, 25 characters		Field not supported (redundant)	
MailingGroupID	Non-Negative Integer		Field not supported (redundant)	
Sequence Block ENDS				
Choice Block ENDS				
BundleDetail Block			Required block; 1 to many pairings (Required block for any mailing that includes bundled mail)	Refer "BundleDetailType" complex in Appendix C
BundleDetailCreate Request Message ENDS				

3.6 BundleDetailCreateResponse

Purpose
Accept or reject a request to create bundle detail data

Error/Return Codes

Copyright © 2011 USPS®. All Rights Reserved.

Refer Section 2.6 to view shared error/return codes and also a list of error/return codes tied this message.

Business Rules

- Will accept if all required fields are populated and values are valid
- Will reject if all required fields are not populated
- Will reject if invalid values are provided

3.6.1 BundleDetailCreateResponse Data Structure

Field Description

Mail.XML 9.0B - BundleDetailCreateResponse				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
BundleDetailCreateAccept block begins			Response from USPS indicating that the BundleDetailCreateRequest message was accepted if the bundle detail matches the existing data in the *PostalOne!* system	
MailXMLHeaderInfo block begins			Attributes block	
CustomerGroupID	String, 25 characters		Required field; must be populated with the same value as the value populated in the CustomerGroupID field of the BundleDetailCreateRequest	
MailingGroupID	Non-Negative Integer		Required field; must be populated with the same value as the value populated in the MailingGroupID field of the BundleDetailCreateRequest	
MaildatJobID			Optional	

Copyright © 2011 USPS®. All Rights Reserved.

Mail.XML 9.0B - BundleDetailCreateResponse				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
UserLicenseCode			Optional	
MailXMLHeaderInfo block ends				
ReturnInfo block	ReturnInfo		Optional block; 0 to many pairings of ReturnCode and ReturnDescription	See Appendix A for Details
BundleDetailCreateAccept block ends				
BundleDetailCreateReject block begins			Response from USPS indicating that the BundleDetailCreateRequest message was rejected since the bundle detail does not match the existing data in the *PostalOne!* system	
MailXMLHeaderInfo block begins			Attributes block	
CustomerGroupID	String, 25 characters		Required field; must be populated with the same value as the value populated in the CustomerGroupID field of the BundleDetailCreateRequest	
MailingGroupID	Non-Negative Integer		Required field; must be populated with the same value as the value populated in the MailingGroupID field of the BundleDetailCreateRequest	

Copyright © 2011 USPS®. All Rights Reserved.

Mail.XML 9.0B - BundleDetailCreateResponse				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
MaildatJobID			Optional	
UserLicenseCode			Optional	
MailXMLHeaderInfo block ends			Attributes block	
ReturnInfo Block	ReturnInfo			See Appendix A for Details

3.7 CloseMailingGroupRequest

Purpose
If a mailing group was opened in error, the group can be closed through the CloseMailingGroupRequest by passing in the USPS mailing group ID. This prevents additional mailing documents from being added to the mailing group and mailing documents attached to the group from being processed further. This message can also be used if a Qualification Report message is submitted in error or needs to be updated, since there is currently no ability to update the Qualification Report in Mail.XML. After the CloseMailingGroupRequest is submitted, the job is no longer displayed on the *PostalOne!* dashboard.

Business Rules
- Request to close a mailing group must occur before any eDoc finalization within the mailing group
- Request to close a mailing group must be submitted against a currently open mailing group
- CustomerGroupID, MailingGroupID and SubmittingParty information must exactly match an existing mailing group
- MailingGroupIDs will not be reassigned and data from the closed mailing will be stored

3.7.1 CloseMailingGroupRequest

Field Description

Mail.XML 9.0B - CloseMailingGroupRequest				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
MailXMLMailGroupRequest HeaderInfo Block begins			Attributes block	
CustomerGroupID	String, 25 characters		Required (attribute)	
MailingGroupID	Non-negative Integer		Required (attribute)	
MailXMLMailGroupRequest HeaderInfo Block ends				
SubmittingParty Block	ParticipantIDType		Required block; Identifies the customer submitting the message	Refer 'ParticipantID Type' complex type in Appendix A.
SubmittingSoftware Block	SubmittingSoftwareType		Required block; Identifies the software submitting the message	Refer 'SubmittingSoftware' complex type

Copyright © 2011 USPS®. All Rights Reserved.

Mail.XML 9.0B - CloseMailingGroupRequest				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
				in Appendix A.

3.8 CloseMailingGroupResponse

Purpose
The CloseMailingGroupResponse will be used by USPS to notify the customer if their request to close a mailing group has been accepted or rejected.

Error/Return Codes

Refer Section 2.6 to view shared error/return codes and also a list of error/return codes tied this message.

Business Rules

- Will accept if the CustomerGroupID, MailingGroupID and SubmittingParty information matches an existing mailing group
- Will reject if the CustomerGroupID, MailingGroupID and SubmittingParty information does NOT match an existing mailing group
- Will reject if invalid values are provided in the request
- Will reject if PostageStatementStatus is FPP or FIM
- Will reject if PostageStatementStatus is UPD while mailing is undergoing finalization
- Will reject if mail is being inducted
- All postage statements must have PostageStatementStatus of REV
- The ReturnInfo block will have a description for rejection

3.8.1 CloseMailingGroupResponse Data Structure

Field Description

Mail.XML 9.0B - CloseMailingGroupResponse				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
CloseMailingGroupAccept Block begins			Block received upon accepting request	
MailXMLOpenMailGroupResponseHeaderInfo Block begins			Attributes block	
CustomerGroupID	String, 25 characters		Required (attribute)	
MailingGroupID	Non-negative Integer		Required (attribute)	
Status	mailxml_base:statusType	Refer 'statusType' simple type	Not required (attribute)	Refer Appendix B
MailXMLOpenMailGroupResponseHeaderInfo Block ends				

Copyright © 2011 USPS®. All Rights Reserved.

Mail.XML 9.0B - CloseMailingGroupResponse				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
ReturnInfo Block	ReturnInfo			See Appendix A for Details
CloseMailingGroupAccept Block ends				
CloseMailingGroupReject Block begins			Block received upon rejecting request	
MailXMLOpenMailGroupResponseHeaderInfo Block begins			Attributes block	
CustomerGroupID	String, 25 characters		Required (attribute)	
Status	mailxml_base:statusType	Refer 'statusType' simple type	Not required (attribute)	Refer Appendix B
MailXMLOpenMailGroupResponseHeaderInfo Block ends				
ReturnInfo Block	ReturnInfo			See Appendix A for Details
CloseMailingGroupReject Block ends				

3.9 ConsolidatedPeriodicalStatementCreateRequest

Purpose
Allows the USPS customer to create a consolidated statement by combining previously submitted Periodicals statements

Business Rules

- Must send a successful OpenMailingGroupRequest message before sending the ConsolidatedPeriodicalStatementCreateRequest message
- Must send a successful QualificationReportCreateRequest message before sending the ConsolidatedPeriodicalStatementCreateRequest message
- Must send a successful ContainerBundleReportCreateRequest message before sending the ConsolidatedPeriodicalStatementCreateRequest message
- Must send a successful PeriodicalStatementCreateRequest message before sending the ConsolidatedPeriodicalStatementCreateRequest message
- Consolidated Statement must consolidate all child statements with Statement Sequence Numbers between FirstStatementSequenceNumber and LastStatementSequenceNumber are required.
- For full-service or mixed service mailings, there are two options for how to populate the required container information:
    - PeriodicalLineItemData block
        - Include one PeriodicalLineItemData block for each container represented on each line of the postage statement. The container IDs must match an ID of a container from a previously submitted qualification report.
        - Do not include ContainerPostage block. If provided, it will be ignored.

Copyright © 2011 USPS®. All Rights Reserved.

- ContainerPostage block
  - All containers are represented in the ContainerPostage blocks with the number of pieces and copies for each container. The container IDs must match an ID of a container from a previously submitted qualification report.
  - Do not provide Container IDs in the LineItemData blocks. Lines could potentially then be collapsed together as they would not need to be broken out by container. (If any Container ID is provided, the Container Postage block will be disregarded).
- Notes:
  - Parent and sibling containers do not need to be represented in either option.
  - Any full-service or mixed service container that is not represented via one of the two above methods will not be sent to SASP and will not receive full-service feedback.

- For full-service and mixed service mailings, each container ID in the postage statement message (either in the PeriodicalLineItemData block or in the ContainerPostage block) must exist in a previously submitted QualificationReportCreateRequest message.
- For full-service and mixed service mailings, each container ID in the postage statement message (either in the PeriodicalLineItemData block or in the ContainerPostage block) must exist in a previously submitted MailPieceCreateRequest message, if the MailPieceCreateRequest message was submitted prior to the ConsolidatedPeriodicalStatementCreateRequest. If the MailPieceCreateRequest message is submitted after the ConsolidatedPeriodicalStatementCreateRequest and each container ID is not accounted for, the statement will not be able to be finalized.
- For full-service and mixed service mailings, the total number of pieces per container ID in the postage statement message must not exceed the total number of pieces per container ID in the QualificationReportCreateRequest message.
- For full-service and mixed service mailings, the total number of pieces in the QualificationReportCreateRequest message exactly match the total number of pieces in the MailPieceCreateRequest message for each container ID included in the postage statement message.
- Beginning in Release 25.0.0, the system will support government Inside-County Consolidated Periodical and Consolidated Pending Periodical mailings.
- Beginning in Release 26.0.0, Rate Categories AF, BF, DF, GF, and KF are not supported for First-Class Mail, Standard Mail, or Periodicals submitted after the January 2, 2011 price changed.
- Beginning in Release 26.0.0, the number of pieces must equal the number of copies when the mailing does not include Firm Bundles or Addressed Supplements and InOutCountyIndicator is N when the Postage Statement Mailing date is after the January 2, 2011 price change date.
- Beginning in Release 26.0.0, the number of pieces must be less than or equal to the number of copies when the mailing includes Firm Bundles but does not have any Addressed Supplements and InOutCountyIndicator is N when the Postage Statement Mailing date is after the January 2, 2011 price change date.
- Beginning in Release 26.0.0, the number of pieces must be greater than or equal to the number of copies when the mailing includes Addressed Supplements but does not have Firm Bundles and InOutCountyIndicator is N when the Postage Statement Mailing date is after the January 2, 2011 price change date.
- For the Combined/Commingled Mailing – user must first send the BeginCombinedMailingRequest message prior to sending the PostageStatement messages.
- Beginning in Release 28.0.0, the *PostalOne!* system will not store an update made to the AdPercent field that was submitted in the DocumentVersionData block in the ConsolidatedPeriodicalStatementCreateRequest message submitted after the first

Copyright © 2011 USPS®. All Rights Reserved.

ConsolidatedPeriodicalCreateRequest message has been submitted to a mailing group for each unique version in that mailing group.

- Beginning in Release 28.0.0, the *PostalOne!* system will store the AdPercent submitted in the first ConsolidatedPeriodicalStatementCreateRequest when it does not match the value submitted in the last accepted qualification report message.
- Begininng in Release 28.0.0, the *PostalOne!* system will not store an update made to the PieceWeight field that was submitted in the DocumentVersionData block in the ConsolidatedPeriodicalStatementCreateRequest message submitted after the first ConsolidatedPeriodicalStatementCreateRequest message has been submitted to a mailing group for each unique version in that mailing group.
- Beginning in Release 28.0.0, the *PostalOne!* system will store the PieceWeight submitted in the first ConsolidatedPeriodicalStatementCreateRequest when it does not match the value submitted in the last accepted qualification report message.

Note - Important information on combined and consolidated postage statements:

(This note comprised of the following three parts, please review)

Part A – Currently, the Mail.XML specs allows the user to provide different data for the fields listed in Part C below for each postage statement request. During a Combined Mailing Request or during a Consolidated Periodical Postage Statement Request, the values of these fields (listed in Part C) have to be same from a business and processing stand-point. The current implementation of Mail.XML does not provide a feature where the user could supply this data for all of the postage statements that are consolidated or combined. A future release of Mail.XML and *PostalOne!* will cater to this requirement where the user will be required to provide with only one set of data (listed in Part C) for the whole message set of combined or consolidated postage statements. However, in the current implementation, USPS recommends all users to follow the set of instructions provided in section.

Part B – For the following set of postage statement message requests, follow the instructions documented in Part C below.

- BeginCombinedMailingRequest
- EndCombinedMailingRequest
- ConsolidatedPeriodicalStatementCreateRequest
- PeriodicalStatementCreateRequest
- PostageStatementCreateRequest

Part C – For all of the postage statement create requests (items 3, 4, and 5 from above), during a Combined Mailing request (meaning postage statements enclosed in between items 1 and 2 from above) and for ConsolidatedPeriodicalStatementCreateRequest user must provide the same values inside all of the postage statements for the following fields.

- IssueDate
- IssueNumber
- VolumeNumber
- CustomerReferenceID
- AgencyCostCode
- PermitPublicationData *(block of PermitHolderData block)*
- PostagePaymentMethod
- RateType
- ProcessingCategory

Copyright © 2011 USPS®. All Rights Reserved.

3.9.1 ConsolidatedPeriodicalStatementCreateRequest Data Structure

Field Description

Mail.XML 9.0B - ConsolidatedPeriodicalStatementCreateRequest				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
ConsolidatedPeriodicalStatementCreateRequest Message BEGINS				
MailXMLPostageStatementRequestHeaderInfo block	MailXMLPostageStatementRequestHeaderInfo		Attributes block	See Appendix C for Details
SubmittingParty Block	ParticipantIDType		Required block; Identifies the customer submitting the message	See Appendix C for Details
SubmittingSoftware Block	SubmittingSoftwareType		Required block; Identifies the software submitting the message	See Appendix C for Details
CreateConsolidatedPeriodicalStatementData block begins			Required block; contains data for consolidated periodical statements	

Copyright © 2011 USPS®. All Rights Reserved.

Mail.XML 9.0B - ConsolidatedPeriodicalStatementCreateRequest				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
PeriodicalStatement block	createPeriodicalStatementType	Required block; contains data critical to postage statement calculation (one to many pairings can be submitted within the CreateConsolidatedPeriodicalStatementData block)	One too many child Periodicals postage statements for a consolidated periodicals postage statement. Child statements must be at the entry level and version level to produce a Periodicals postage statement register. For a single consolidated statement, the publisher data and the mailing agent data must be the same for all of the child statements.	See PeriodicalStatement block in PeriodicalStatementCreateRequest message for blocks and elements that are required by the USPS. The PeriodicalStatement block used in this message is exactly same as in the PeriodicalStatementCreateRequest message
FirstStatementSequenceNumber	String, 30 characters		Required field	
LastStatementSequenceNumber	String, 30 characters		Required field	
LimitedCirculationDiscountClaimed	Mailxml_base:yesNo	Yes No	Required field	
PublisherData	mailerDataRequestType		Required field, there must be only one publication number for a Periodical or permit number with type PP for a pending Periodical in a consolidated statement.	See 'mailerDataResuestType' complex in Appendix C
MailingAgentData	mailerDataRequestType		Required field, there must be only one mailing agent in a consolidated statement.	See 'mailerDataResuestType' complex in Appendix C for Details
ContainerCount block	ContainerCountT		Required block; at	See

Copyright © 2011 USPS®. All Rights Reserved.

Mail.XML 9.0B - ConsolidatedPeriodicalStatementCreateRequest				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
	ype		least one of the fields in this block must be populated with a nonzero value	Appendix C for Details
PeriodicalLineItemData block			Optional block; data used to generate container and bundle charges at the parent statement level for a consolidated periodicals statement. (one to many pairings) Alternatively, there may be no container and bundle charges or container and bundle charges may be provided at the child statement level.	See PeriodicalLIneItem in PeriodicalStatement block in PeriodicalStatementCreateRequest message.
CreateConsolidatedPeriodicalStatementData block ends				
ConsolidatedPeriodicalStatementCreateRequest Message ENDS				

3.10 ConsolidatedPeriodicalStatementCreateResponse

Purpose
Response on whether the consolidated periodical postage statement was accepted or rejected

Error/Return Codes
Refer Section 2.6 to view shared error/return codes and also a list of error/return codes tied this message.

Business Rules
- Will reject the request if the mailing group does not exist
- Will reject the request if there are no child statements to consolidate
- Will reject the request if one of the child statements with StatementSequenceNumber in between the First and Last Statement Sequence Number has For Consolidated field set to False

Copyright © 2011 USPS®. All Rights Reserved.

- Will accept the request if the TotalPostage field is populated with the same value as the sum of all values in the TotalPostage field for all child statements

3.10.1 ConsolidatedPeriodicalStatementCreateResponse

Field Description

Mail.XML 9.0B - ConsolidatedPeriodicalStatementCreateResponse				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
ConsolidatedPeriodicalStatementCreateAccept block begins			Required block if the ConsolidatedPeriodicalStatementRequest has valid fields and the mailing group exists	
MailXMLPostageStatementRequestHeaderInfo block begins	MailXMLPostageStatementRequestHeaderInfo		Attributes block	See Appendix A for Details
StatementID	Non-negative integer		Required field; paired with TotalPostage and ReturnInfo block	
TotalPostage	Double		Required field; paired with StatementID and ReturnInfo block, two decimal places.	
PostageStatementStatus	Mailxml_base:postageStatementStatusType	• Refer 'postage StatementStatusType' simple type	See Postage Statement Status Definitions	See Appendix E for Details And Refer Appendix B
ReturnInfo block	ReturnInfo		Optional block; paired with StatementID and TotalPostage	See Appendix A for Details
ConsolidatedPeriodicalStatementCreateAccept block ends				
ConsolidatedPeriodicalStatementCreateReject block begins			Required block if the fields in the request message are not valid or if the mailing group does not exist	
MailXMLPostageStatementRequestHeaderInfo block	MailXMLPostageStatementRequestHeaderInfo		Attributes block	See Appendix E for Details

Copyright © 2011 USPS®. All Rights Reserved.

Mail.XML 9.0B - ConsolidatedPeriodicalStatementCreateResponse				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
ReturnInfo block	ReturnInfo		Required block; zero to many pairings can be submitted between ReturnCode and ReturnDescription	See Appendix E for Details
ConsolidatedPeriodicalStatementCreateReject block ends				

3.11 ContainerBundleReportCancelRequest

Purpose
Request to cancel the container and bundle report information within a mailing group

Business Rules

- ContainerBundleReportCreateRequest message must be submitted successfully by the customer
- MailingGroupID and CustomerGroupID must exist for an open mailing group
- ContainerBundleReportCreateRequest must be accepted before submitting the ContainerBundleCancelRequest message for the specified MailingGroupID and CustomerGroupID
- The specified ContainerBundleReportID will cancel all Container Bundle Reports for the specific MailingGroupID and CustomerGroupID when the ContainerBundleReportCancelRequest message has been accepted

3.11.1 ContainerBundleReportCancelRequest Data Structure

Field Description

Mail.XML 9.0B - ContainerBundleReportCancelRequest				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
ContainerBundleReportHeaderInfo block begins			Attributes block	
CustomerGroupID	String, 25 characters		Optional (attribute)	
MailingGroupID	Non-Negative integer		Optional (attribute)	
MaildatJobID	String, 8 characters		Optional (attribute)	
UserLicenseCode	String, 4 characters		Optional (attribute)	
ContainerBundleReportHeaderInfo block ends				
SubmittingParty Block	ParticipantIDType		Required block; Identifies the customer	Refer 'ParticipantID Type'

Copyright © 2011 USPS®. All Rights Reserved.

Mail.XML 9.0B - ContainerBundleReportCancelRequest				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
			submitting the message	complex type in Appendix E.
SubmittingSoftware Block	SubmittingSoftwareType		Required block; Identifies the software submitting the message	Refer 'SubmittingSoftware' complex type in Appendix E.

2.2.1 - ContainerBundleReportCancelRequest

3.12 ContainerBundleReportCancelResponse

Purpose
Response message to inform the customer of whether the container bundle report information has been cancelled or the reason why it was not

Error/Return Codes
Refer Section 2.6 to view shared error/return codes and also list a of error/return codes tied this message.

Business Rules
- Will accept if the container bundle report information exists within the mailing group
- Will reject if the container bundle report information does not exist within the mailing group
- Postage statement associated with the Container Bundle Report must have PostageStatementStatus populated with UPD for USPS Processing Due and not undergoing finalization within the specified MailingGroupID

3.12.1 ContainerBundleReportCancelResponse

Field Description

Mail.XML 9.0B - ContainerBundleReportCancelResponse				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
ContainerBundleReportCancelAccept block begins			Required block if the container bundle report data exists in the mailing group	
ContainerBundleReportHeaderInfo block begins			Attributes block	
CustomerGroupID	String, 25 characters		Optional (attribute)	
MailingGroupID	Non-Negative integer		Optional (attribute)	
MaildatJobID	String, 8		Optional (attribute)	

Copyright © 2011 USPS®. All Rights Reserved.

Mail.XML 9.0B - ContainerBundleReportCancelResponse				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
	characters			
UserLicenseCode	String, 4 characters		Optional (attribute)	
ContainerBundleReportHeaderInfo block ends				
ContainerBundleReportID	String, 12 characters		Required field; must be populated with the same value as the CustomerBundleReportID field of the ContainerBundleReportCreateResponse message – a one to many ratio	
ReturnInfo Block	ReturnInfo			See Appendix A for Details
ContainerBundleReportCancelAccept block ends				
ContainerBundleReportCancelReject block begins			Required block if the container bundle report data does not exists in the mailing group	
ContainerBundleReportHeaderInfo block begins			Attributes block	
CustomerGroupID	String, 25 characters		Optional (attribute)	
MailingGroupID	Non-Negative integer		Optional (attribute)	
MaildatJobID	String, 8 characters		Optional (attribute)	
UserLicenseCode	String, 4 characters		Optional (attribute)	
ContainerBundleReportHeaderInfo block ends				
ReturnInfo Block	ReturnInfo			See Appendix A for Details
ContainerBundleReportCancelReject block ends				

2.2.2 - ContainerBundleReportCancelResponse

3.13 ContainerBundleReportCreateRequest

Purpose
Message is used to deliver the Container and Bundle Report information to the *PostalOne!* system

Copyright © 2011 USPS®. All Rights Reserved.

Business Rules

- ContainerBundleReportCreateRequest message can only be provided when the FormType in at least one QualificationReportCreateRequest message is populated with PE for the specified MailingGroupID and CustomerGroupID.
- MailingGroupID and CustomerGroupID must exist for an open mailing group
- Multiple ContainerBundleReportCreateRequest messages can be submitted within the same MailingGroupID
- A ContainerBundleSummary can be submitted for all chargeable containers and bundles or a ContainerBundleVersionReport for the chargeable containers and bundles apportioned to each Version

3.13.1 ContainerBundleReportCreateRequest

Field Description

Mail.XML 9.0B - ContainerBundleReportCreateRequest				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
ContainerBundleReportCreateRequest Message BEGINS				
MailXMLHeaderInfo block begins			Attributes block	
CustomerGroupID	String, 25 characters		Optional	
MailingGroupID	Non-Negative integer		Optional	
MaildatJobID	Mailxml_base:jobIDType		Optional	Refer Appendix B
UserLicenseCode	Mailxml_base:uderLicenseCode		Optional	Refer Appendix B
MailXMLHeaderInfo block ends				
SubmittingParty Block	ParticipantIDType		Required block; Identifies the customer submitting the message	Refer 'ParticipantIDType' complex type in Appendix C.
SubmittingSoftware Block	SubmittingSoftwareType		Required block; Identifies the software submitting the message	Refer 'SubmittingSoftware' complex type in Appendix C.

Copyright © 2011 USPS®. All Rights Reserved.

Mail.XML 9.0B - ContainerBundleReportCreateRequest				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
Choice Block BEGINS			Choice between ContainerBundleVersionRecords Block OR ContainerBundleSummaryRecord Block	
ContainerBundleVersionRecords block begins			Only 1 occurrence is allowed	
SackTrayContainerVersion Records block begins			Optional block; 0 to many pairings can be submitted depending upon the number of SackTrayContainer MPURecords (used for Sack or Tray charges)	
DocumentVersionData	DocumentVersionDataType		Required	See Appendix C for Details
PublicationInfo	permitPublication DataType		Required	See Appendix C for Details
PublicationTitle	String, 60 characters		Optional	
PostageStatementLineNumber	mailxml_base:postageStatementLineNumber2Type	Refer 'postageStatementLineNumber2Type' simple type	Optional field; uses the Container Level and Entry level to find the lines	Refer Appendix B
ChargeableContainerLevel	mailxml_base:chargeableContainerLevelType	Refer 'chargeableContainerLevelType' simple type	Required field; <BLANK> = NULL is not supported	Refer Appendix B
ChargeableEntryLevel	mailxml_base:chargeableEntryLevelType	Refer 'chargeableEntry LevelType' simple type	Required field; <BLANK> = NULL is not supported	Refer Appendix B
Containers	Double		Required field	
IssueDate	Date	YYYY-MM-DD	Required field	
IssueNumber	String, 6 characters		Optional field	

Copyright © 2011 USPS®. All Rights Reserved.

Mail.XML 9.0B - ContainerBundleReportCreateRequest				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
VolumeNumber	String, 5 characters		Optional field	
SackTrayContainerVersion Records block ends				
PalletContainerVersionRec ords block begins			Optional block; 0 to many pairings can be submitted depending upon the number of PalletMPURecords (used for Pallet charges)	
DocumentVersionData	DocumentVersio nData Type			See Appendix C for Details
PublicationInfo	permitPublication DataType			See Appendix C for Details
PublicationTitle	String, 60 characters		Optional	
PostageStatementLineNum ber	mailxml_base:po stageStatementLi neNumber1Type	Refer 'postageStateme ntLineNumber1Ty pe' simple type	Optional field; uses the Container Level and Entry level to find the lines	Refer Appendix B
ChargeableContainerLevel	mailxml_base:ch argeableContaine rLevelType	Refer 'chargeableConta inerLevelType' simple type	Required field; <BLANK> = NULL is not supported	Refer Appendix B
ChargeableEntryLevel	mailxml_base:ch argeableEntryLev elType	Refer 'chargeableEntry LevelType' simple type	Required field; <BLANK> = NULL is not supported	Refer Appendix B
Containers	Double		Required field	
IssueDate	Date	YYYY-MM-DD	Required field	
IssueNumber	String, 6 characters		Optional field	
VolumeNumber	String, 5 characters		Optional field	
PalletContainerVersionRec ords block ends				
BundleVersionRecord block begins			Optional block; 0 to many pairings can be submitted	

Copyright © 2011 USPS®. All Rights Reserved.

Mail.XML 9.0B - ContainerBundleReportCreateRequest				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
			depending upon the number of BundleMPURecords (used for Bundle charges)	
DocumentVersionData	DocumentVersionDataType			See Appendix C for Details
PublicationInfo	permitPublicationDataType			See Appendix C for Details
PublicationTitle	String, 60 characters		Optional	
PostageStatementLineNumber	mailxml_base:postageStatementLineNumber3Type	Refer 'postageStatementLineNumber3Type' simple type	Optional field; uses the Container Level and Entry level to find the lines	Refer Appendix B
ChargeableContainerLevel	mailxml_base:chargeableContainerLevelType	Refer 'chargeableContainerLevelType' simple type	Required field; <BLANK> = NULL is not supported	Refer Appendix B
ChargeableBundleLevel	mailxml_base:chargeableBundleLevelType	Refer 'chargeableBundleLevelType' simple type	Required field; <BLANK> = NULL is not supported	Refer Appendix B
Bundles	Double		Required field	
IssueDate	Date	YYYY-MM-DD	Required field	
IssueNumber	String, 6 characters		Optional field	
VolumeNumber	String, 5 characters		Optional field	
BundleVersionRecord block ends				
ContainerBundleVersionRecords block ends				
ContainerBundleSummaryRecords block begins			Required block for each ContainerBundleMPURecord block	
SackTrayContainerRecord block begins			Optional block; 0 to many pairings can be submitted depending upon the number of	

Copyright © 2011 USPS®. All Rights Reserved.

Mail.XML 9.0B - ContainerBundleReportCreateRequest				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
			SackTrayContainerMPURecords (used for Sack or Tray charges)	
PublicationInfo	permitPublicationDataType			See Appendix C for Details
PublicationTitle	String, 60 characters		Optional	
PostageStatementLineNumber	mailxml_base:postageStatementLineNumber2Type	Refer 'postageStatementLineNumber2Type' simple type	Optional field; uses the Container Level and Entry level to find the lines	Refer Appendix B
ChargeableContainerLevel	mailxml_base:chargeableContainerLevelType	Refer 'chargeableContainerLevelType' simple type	Required field; <BLANK> = NULL is not supported	Refer Appendix B
ChargeableEntryLevel	mailxml_base:chargeableEntryLevelType	Refer 'chargeableEntryLevelType' simple type	Required field; <BLANK> = NULL is not supported	Refer Appendix B
Containers	Double		Required field	
IssueDate	Date	YYYY-MM-DD	Required field	
IssueNumber	String, 6 characters		Optional field	
VolumeNumber	String, 5 characters		Optional field	
SackTrayContainerRecord block ends				
PalletContainerRecord block begins			Optional block; 0 to many pairings can be submitted depending upon the number of PalletMPURecords (used for Pallet charges)	
PublicationInfo	permitPublicationDataType			See Appendix C for Details
PublicationTitle	String, 60 characters		Optional	
PostageStatementLineNumber	mailxml_base:postageStatementLi	Refer 'postageStateme	Optional field; uses the Container Level	Refer Appendix B

Copyright © 2011 USPS®. All Rights Reserved.

Mail.XML 9.0B - ContainerBundleReportCreateRequest				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
	neNumber1Type	ntLineNumber1Type' simple type	and Entry level to find the lines	
ChargeableContainerLevel	mailxml_base:chargeableContainerLevelType	Refer 'chargeableContainerLevelType' simple type	Required field; <BLANK> = NULL is not supported	Refer Appendix B
ChargeableEntryLevel	mailxml_base:chargeableEntryLevelType	Refer 'chargeableEntryLevelType' simple type	Required field; <BLANK> = NULL is not supported	Refer Appendix B
Containers	Double		Required field	
IssueDate	Date	YYYY-MM-DD	Required field	
IssueNumber	String, 6 characters		Optional field	
VolumeNumber	String, 5 characters		Optional field	
PalletContainerRecord block ends				
BundleRecord block begins			Optional block; 0 to many pairings can be submitted depending upon the number of BundleMPURecords (used for Bundle charges)	
PublicationInfo	permitPublicationDataType			See Appendix C for Details
PublicationTitle	String, 60 characters		Optional	
PostageStatementLineNumber	mailxml_base:postageStatementLineNumber3Type	Refer 'postageStatementLineNumber3Type' simple type	Optional field; uses the Container Level and Entry level to find the lines	Refer Appendix B
ChargeableContainerLevel	mailxml_base:chargeableContainerLevelTYpe	Refer 'chargeableCOntainerLevelType' simple type	Required field; <BLANK> = NULL is not supported	Refer Appendix B
ChargeableBundleLevel	mailxml_base:chargeableBundleLevelType	Refer 'chargeableBundleLevelType'	Required field; <BLANK> = NULL is not supported	Refer Appendix B

Copyright © 2011 USPS®. All Rights Reserved.

Mail.XML 9.0B - ContainerBundleReportCreateRequest				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
		simple type		
Bundles	Double		Required field	
IssueDate	Date	YYYY-MM-DD	Required field	
IssueNumber	String, 6 characters		Optional field	
VolumeNumber	String, 5 characters		Optional field	
BundleRecord block ends				
ContainerBundleSummaryRecords block ends				
Choice Block ENDS				
ContainerBundleReportCreateRequest Message ENDS				

2.2.3 - ContainerBundleReportCreateRequest

3.14 ContainerBundleReportCreateResponse

Purpose
ResponseResponse message to inform the customer whether the ContainerBundleReportCreateRequest was accepted or rejected

Error/Return Codes
Refer Section 2.6 to view shared error/return codes and also a list of error/return codes tied this message.

Business Rules
- QualificationReportCreateRequest message must be accepted before submitting the ContainerBundleReportCreateRequest message for the specified MailingGroupID and CustomerGroupID

3.14.1 ContainerBundleReportCreateResponse

Field Description

Mail.XML 9.0B - ContainerBundleReportCreateResponse				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
ContainerBundleReportCreateAccept block begins			Required block if the ContainerBundleRe	

Copyright © 2011 USPS®. All Rights Reserved.

Mail.XML 9.0B - ContainerBundleReportCreateResponse				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
			portCreateRequest message has an existing MailingGroupID and the fields are valid	
ContainerBundleReportHeaderInfo block begins			Attributes block	
CustomerGroupID	String, 25 characters		Optional (attribute)	
MailingGroupID	Non-Negative integer		Optional (attribute)	
MaildatJobID	String, 8 characters		Optional (attribute)	
UserLicenseCode	String, 4 characters		Optional (attribute)	
ContainerBundleReportHeaderInfo block ends				
ContainerBundleReportID	String, 12 characters		Required field; Respond with either the ContainerBundleReportID and ContainerBundleStatus or just the Tracking ID	
ContainerBundleStatus	mailxml_base:containerBundleStatusTYpe	Refer 'containerBundleStatusType' simple type	Required field; Respond with either the ContainerBundleReportID and ContainerBundleStatus or just the Tracking ID	Refer Appendix B
ReturnInfo Block	ReturnInfo			See Appendix A for Details
ContainerBundleReportCreateAccept block ends				
ContainerBundleReportCreateReject block begins			Required block if the ContainerBundleReportCreateRequest message does not have an existing MailingGroupID or the fields are not valid	
ContainerBundleReportHeaderInfo block begins			Attributes block	

Copyright © 2011 USPS®. All Rights Reserved.

Mail.XML 9.0B - ContainerBundleReportCreateResponse				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
CustomerGroupID	String, 25 characters		Optional (attribute)	
MailingGroupID	Non-Negative integer		Optional (attribute)	
MaildatJobID	String, 8 characters		Optional (attribute)	
UserLicenseCode	String, 4 characters		Optional (attribute)	
ContainerBundleReportHeaderInfo block ends				
ReturnInfo Block	ReturnInfo			See Appendix A for Details
ContainerBundleReportHeaderInfo block ends				

2.2.4 - ContainerBundleReportCreateResponse

3.15 ContainerBundleReportQueryRequest

Purpose
Request to retrieve all the Container and Bundle information for a Periodicals Outside County Container or Bundle report

Business Rules

- Submitted after a successful ContainerBundleReportCreateResponse message is returned to the customer
- MailingGroupID and CustomerGroupID must exist for an open mailing group
- QueryRequest message can only query the database for electronic documentation submitted through Mail.XML

3.15.1 ContainerBundleReportQueryRequest

Field Description

Mail.XML 9.0B - ContainerBundleReportQueryRequest				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
ContainerBundleReportHeaderInfo block begins			Attributes block	
CustomerGroupID	String, 25 characters		Optional (attribute)	
MailingGroupID	Non-Negative integer		Optional (attribute)	
MaildatJobID	String, 8 characters		Optional (attribute)	
UserLicenseCode	String, 4 characters		Optional (attribute)	
ContainerBundleReportHeaderInfo block ends				

Copyright © 2011 USPS®. All Rights Reserved.

Mail.XML 9.0B - ContainerBundleReportQueryRequest				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
SubmittingParty Block	ParticipantIDType		Required block; Identifies the customer submitting the message	Refer 'ParticipantID Type' complex type in Appendix E.
SubmittingSoftware Block	SubmittingSoftwareType		Required block; Identifies the software submitting the message	Refer 'SubmittingSoftware' complex type in Appendix E.

2.2.5 - ContainerBundleReportQueryRequest

3.16 ContainerBundleReportQueryResponse

Purpose
Response to the customer displaying the container and bundle data query results or the reason why there was a query error

Error/Return Codes
Refer Section 2.6 to view shared error/return codes and also a list of error/return codes tied this message.

Business Rules
- Submitted after a successful ContainerBundleReportCreateResponse message is returned to the customer
- ContainerBundleReportCreateRequest must be accepted before submitting the ContainerBundleQueryRequest message for the specified MailingGroupID and CustomerGroupID
- Optional blocks and fields will only be generated in the QueryResults block when the value has been populated in the database
- Required blocks and fields will always be generated in the QueryResults block
- Data will be generated post-processing with converted values in the QueryResults block
- QueryResults block will generate one to many ContainerBundleReportIDs in the QueryResults block of the ContainerBundleReportQueryResponse message

3.16.1 ContainerBundleReportQueryResponse

Field Description

Mail.XML 9.0B - ContainerBundleReportQueryResponse				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
MailXMLHeaderInfo block begins				
CustomerGroupID	String, 25		Optional (attribute)	

Copyright © 2011 USPS®. All Rights Reserved.

Mail.XML 9.0B - ContainerBundleReportQueryResponse				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
	characters			
MailingGroupID	Non-Negative integer		Optional (attribute)	
MaildatJobID	Mailxml_base:jobIDType		Optional (attribute)	
UserLicenseCode	Mailxml_base:userLicenseCode		Optional (attribute)	
MailXMLHeaderInfo block ends				
Sequence BEGINS				
TrackingID	String 12	-	Optional. Returned when transaction fails	-
Choice Block BEGINS				
QueryResults block begins			Required block; either the QueryResults or QueryError block must be populated in the response	
ContainerBundleReportID	String, 12 characters		Optional field	
ContainerBundleVersionRecords block begins				
SackTrayContainerVersionRecords block begins			Optional block; 0 to many pairings can be submitted depending upon the number of SackTrayContainerMPURecords (used for Sack or Tray charges)	
DocumentVersionData	DocumentVersionData Type			See Appendix C for Details
PublicationInfo	permitPublicationDataType			See Appendix C for Details
PublicationTitle	String, 60 characters		Optional	
PostageStatementLineNumber	mailxml_base:postageStatementLineNumber2Type	Refer 'postageStatementLineNumber2Type' simple type	Optional field; uses the Container Level and Entry level to find the lines	Refer Appendix B
ChargeableContainerLevel	mailxml_base:chargeableContaine	Refer 'chargeableConta	Required field; <BLANK> = NULL	Refer Appendix B

Copyright © 2011 USPS®. All Rights Reserved.

Mail.XML 9.0B - ContainerBundleReportQueryResponse				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
	rLevelType	inerLevelTYpe' simple type	is not supported	
ChargeableEntryLevel	mailxml_base:chargeableEntryLevelTYpe	Refer 'chargeableEntryLevelType' simple type	Required field; <BLANK> = NULL is not supported	Refer Appendix B
Containers	Double		Required field	
IssueDate	Date	YYYY-MM-DD	Required field	
IssueNumber	String, 6 characters		Optional field	
VolumeNumber	String, 5 characters		Optional field	
SackTrayContainerVersion Records block ends				
PalletContainerVersionRec ords block begins			Optional block; 0 to many pairings can be submitted depending upon the number of PalletMPURecords (used for Pallet charges)	
DocumentVersionData	DocumentVersionData Type			See Appendix C for Details
PublicationInfo	permitPublicationDataType			See Appendix C for Details
PublicationTitle	String, 60 characters		Optional	
PostageStatementLineNumber	mailxml_base:postageStatementLineNumber1Type	Refer 'postageStatementLineNumber1Type' simple type	Optional field; uses the Container Level and Entry level to find the lines	Refer Appendix B
ChargeableContainerLevel	mailxml_base:chargeableContainerLevelType	Refer 'chargeableContainerLevelType' simple type	Required field; <BLANK> = NULL is not supported	Refer Appendix B
ChargeableEntryLevel	mailxml_base:chargeableEntryLevelTYpe	Refer 'chargeableEntryLevelTYpe' simple type	Required field; <BLANK> = NULL is not supported	Refer Appendix B
Containers	Double		Required field	
IssueDate	Date	YYYY-MM-DD	Required field	
IssueNumber	String, 6 characters		Optional field	
VolumeNumber	String, 5 characters		Optional field	
PalletContainerVersionRec				

Copyright © 2011 USPS®. All Rights Reserved.

Mail.XML 9.0B - ContainerBundleReportQueryResponse				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
ords block ends				
BundleVersionRecord block begins			Optional block; 0 to many pairings can be submitted depending upon the number of BundleMPURecord s (used for Bundle charges)	
DocumentVersionData	DocumentVersio nData Type			See Appendix C for Details
PublicationInfo	permitPublication DataType			See Appendix C for Details
PublicationTitle	String, 60 characters		Optional	
PostageStatementLineNum ber	mailxml_base:po stageStatementLi neNumber3Type	Refer 'postageStateme ntLineNumber3Ty pe' simple type	Optional field; uses the Container Level and Entry level to find the lines	Refer Appendix B
ChargeableContainerLevel	mailxml_base:ch argeableContaine rLevelType	Refer 'chargeableConta inerLevelType' simple type	Required field; <BLANK> = NULL is not supported	Refer Appendix B
ChargeableBundleLevel	mailxml_base:ch argeableBundleL evelType	Refer 'chargeableBundl eLevelType' simple type	Required field; <BLANK> = NULL is not supported	Refer Appendix B
Bundles	Double		Required field	
IssueDate	Date	YYYY-MM-DD	Required field	
IssueNumber	String, 6 characters		Optional field	
VolumeNumber	String, 5 characters		Optional field	
BundleVersionRecord block ends				
ContainerBundleVersionRe cords block ends				
ContainerBundleSummaryR ecords block begins			Required block for each ContainerBundleM PURecord block	
SackTrayContainerRecord block begins			Optional block; 0 to many pairings can be submitted depending upon the number of SackTrayContainer	

Copyright © 2011 USPS®. All Rights Reserved.

Mail.XML 9.0B - ContainerBundleReportQueryResponse				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
			MPURecords (used for Sack or Tray charges)	
PublicationInfo	permitPublicationDataType			See Appendix C for Details
PublicationTitle	String, 60 characters		Optional	
PostageStatementLineNumber	mailxml_base:postageStatementLineNumber2Type	Refer 'postageStatementLineNumber2Type' simple type	Optional field; uses the Container Level and Entry level to find the lines	Refer Appendix B
ChargeableContainerLevel	mailxml_base:chargeableContainerLevelTYpe	Refer 'chargeableContainerLevelTYpe' simple type	Required field; <BLANK> = NULL is not supported	Refer Appendix B
ChargeableEntryLevel	mailxml_base:chargeableEntryLevelType	Refer 'chargeableEntryLevelTYpe' simple type	Required field; <BLANK> = NULL is not supported	Refer Appendix B
Containers	Double		Required field	
IssueDate	Date	YYYY-MM-DD	Required field	
IssueNumber	String, 6 characters		Optional field	
VolumeNumber	String, 5 characters		Optional field	
SackTrayContainerRecord block ends				
PalletContainerRecord block begins			Optional block; 0 to many pairings can be submitted depending upon the number of PalletMPURecords (used for Pallet charges)	
PublicationInfo	permitPublicationDataType			See Appendix C for Details
PublicationTitle	String, 60 characters		Optional	
PostageStatementLineNumber	mailxml_base:postageStatementLineNumber1Type	Refer 'postageStatementLineNUmber1Type' simple type	Optional field; uses the Container Level and Entry level to find the lines	Refer Appendix B
ChargeableContainerLevel	mailxml_base:chargeableCOntainerLevelType	Refer 'chargeableContainerLevelType' simple type	Required field; <BLANK> = NULL is not supported	Refer Appendix B

Copyright © 2011 USPS®. All Rights Reserved.

Mail.XML 9.0B - ContainerBundleReportQueryResponse				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
ChargeableEntryLevel	mailxml_base:chargeableEntryLevelType	Refer 'chargeableEntryLevelType' simple type	Required field; <BLANK> = NULL is not supported	Refer Appendix B
Containers	Double		Required field	
IssueDate	Date	YYYY-MM-DD	Required field	
IssueNumber	String, 6 characters		Optional field	
VolumeNumber	String, 5 characters		Optional field	
PalletContainerRecord block ends				
BundleRecord block begins			Optional block; 0 to many pairings can be submitted depending upon the number of BundleMPURecords (used for Bundle charges)	
PublicationInfo	permitPublicationDataType			See Appendix C for Details
PublicationTitle	String, 60 characters		Optional	
PostageStatementLineNumber	mailxml_base:postageStatementLineNumber3Type	Refer 'postageStatementLineNumber3Type' simple type	Optional field; uses the Container Level and Entry level to find the lines	Refer Appendix B
ChargeableContainerLevel	mailxml_base:chargeableContainerLevelTYpe	Refer 'chargeableContainerLevelType' simple type	Required field; <BLANK> = NULL is not supported	Refer Appendix B
ChargeableBundleLevel	mailxml_base:chargeableBundleLevelType	Refer 'chargeableBundleLevelType' simple type	Required field; <BLANK> = NULL is not supported	Refer Appendix B
Bundles	Double		Required field	
IssueDate	Date	YYYY-MM-DD	Required field	
IssueNumber	String, 6 characters		Optional field	
VolumeNumber	String, 5 characters		Optional field	
BundleRecord block ends				
ContainerBundleSummaryRecords block ends				
ReturnInfo Block	ReturnInfo			See Appendix C for Details

Copyright © 2011 USPS®. All Rights Reserved.

Mail.XML 9.0B - ContainerBundleReportQueryResponse				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
QueryResults block begins				
QueryError block begins			Required when the query data cannot be provided; provides a reason for the error	
ReturnInfo Block	ReturnInfo			See Appendix C for Details
QueryError block ends				
Choice Block ENDS				
Sequence Block ENDS				
ContainerBundleReportQueryResponse Message ENDS				

2.2.6 - ContainerBundleReportQueryResponse

3.17 ContainerStatusQueryRequest

The container status message set for PS Form 8017 and PS form 8125 containers allows a mailer, mail owner, or consolidator to provide container key information and find out if the container has any eDropShip-related or any other issues prior to shipping the container to the USPS.

3.17.1 ContainerStatusQueryRequest

Field Description

Mail.XML 9.0B - ContainerStatusQueryRequest				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
StatusQueryMsgHeaderInfo block Opens				
CreatorSchedulerCorpID	String, 12 characters		Required (attribute)	
CreatorSchedulerID	String, 12 characters		Non required (attribute)	
StatusQueryMsgHeaderInfo block Closes				
SubmittingParty	ParticipantIDType		Identifies the customer submitting the	Refer 'ParticipantID Type'

Copyright © 2011 USPS®. All Rights Reserved.

Mail.XML 9.0B - ContainerStatusQueryRequest				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
			message	complex type in Appendix D.
SubmittingSoftware	SubmittingSoftwareType		Identifies the software submitting the message	Refer 'SubmittingSoftware' complex type in Appendix D.
ContainerID Block Opens				
MaildatContainer Block Opens				
UserLicenceCode	String, 4 characters		Required (attribute)	
MaildatJobID	String, 8 characters		Required (attribute)	
DatabaseContainerID	Non Negative Integer, 6 digits		Required (attribute)	
UniqueContainerBarcode	String, 24 characters		Optional (attribute)	
MaildatContainer Block Closes				
MailXMLContainer Block Opens				
MailingGroupID	Non Negative Integer		Required	
CustomerGroupID	String, 25 characters		Required	
ContainerBarcode	Container24CharacterBarcodeType		Optional	
ContainerID	String, 6 characters		Required	
MailXMLContainer Block Closes				
ContainerID Block Closes				
ConsigneeApptID	String, 12 characters		Required. 1 to many allowed	
ContentID Block Opens			Required. 1 to many block allowed	
ConsigneeContentID	String, 12 characters		Required (attribute)	
SchedulerContentID	String, 12 characters		Optional (attribute)	
ContentID Block Closes				

3.18 ContainerStatusQueryResponse

The following eDropShip issues can stop the creation of an electronic 8125 (e8125) are:

Copyright © 2011 USPS®. All Rights Reserved.

invalid barcode – the barcode data format is not valid

payment not finalized – the clerk has not yet finalized payment

payment not yet processed – the electronic data has not been updated by the mailer to make the container in a ready to pay status

entry point payment discount error – the entry point discount filed vs. the physical facility where mail is scheduled through FAST for delivery does not support the discount type

In all of these cases, unless the issues are resolved electronically through an update of data or through the clerk finalizing the postage, the containers' e8125 or e8017 will not be generated and sent to the Surface Visibility (SV) devices for induction. When that container shows up without an e8125 at the plant, the container can be stopped and its processing can be delayed or it can be returned to the shipper.

3.18.1 ContainerStatusQueryResponse

Field Description

Mail.XML 9.0B - ContainerStatusQueryResponse				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
StatusQueryMsgHeaderInfo block Opens				
CreatorSchedulerCorpID	String, 12 characters		Required (attribute)	
CreatorSchedulerID	String, 12 characters		Optional (attribute)	
StatusQueryMsgHeaderInfo block Closes				
QueryResults Block Opens				
UniqueContainerBarcode	String, 24characters		Optional	
ConsigneeFacility Block Opens				
CompanyName	String, 40 characters		Optional	
FacilityNumber	String, 15 characters		Optional	
FacilityAddress Block Opens				
CommunicationRole	mailxml_base:communicationRoleType	Refer 'communicationRoleType' simple type	Required (attribute)	Refer Appendix B
Address1	String, 64 characters		Optional	
Address2	String, 64 characters		Optional	

Copyright © 2011 USPS®. All Rights Reserved.

Mail.XML 9.0B - ContainerStatusQueryResponse				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
Address3	String, 40 characters		Optional	
Address4	String, 40 characters		Optional	
City	String, 45 characters		Optional	
County	String, 45 characters		Optional	
State	mailxml_base:stateCode	Refer 'stateCode' simple type	Optional	Refer Appendix B
ZipCode	Number, 9 digits		Optional	
GPSCoordinates	gPSCoordinates			Refer 'GPSCoordinates' complex type in Appendix D.
FacilityAddress Block Closes				
FacilityName	String, 40 characters		Optional	
FacilityType	String, 15 characters		Optional	
URL	url		Optional	
CommonContact Block Opens				
ContactType	Mailxml_base:contactType	Refer 'contactType' simple type	Required (attribute)	Refer Appendix B
ContactName	String, 60 characters		Optional	
Telephone	String, 25 characters		Optional	
MobilePhone	String, 25 characters		Optional	
Email	String		Optional	
Fax	String, 25 characters		Optional	
GPSCoordinates	gPSCoordinates			Refer 'GPSCoordinates' complex type in Appendix D.
ContactID Block Opens				
IDValue	String, 30 characters		Optional	
IDValueTypes	mailxml_base:ID	Refer 'IDType'	Optional	Refer

Copyright © 2011 USPS®. All Rights Reserved.

Mail.XML 9.0B - ContainerStatusQueryResponse				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
	Type	simple type		Appendix B
ContactID Block Closes				
CommonContact Block Closes				
ConsigneeFacility Block Closes				
ContainerStatus	mailxml_base:containerStatusType	Refer 'containerStatusType' simple type	Optional	Refer Appendix B
ReturnInfo	ReturnInfo		Required	Refer 'ReturnInfo' complex type in Appendix D.
QueryResults Block Closes				
QueryError Block Opens				
ReturnInfo	ReturnInfo		Required	Refer 'ReturnInfo' complex type in Appendix D.
QueryError Block Closes				

3.19 CustomerMailReportCreateRequest

Purpose
This report is used mainly for Permit/Customer Identification. This report allows the specific customer identification and permit identification who may need to be charged for paying the shortage of postage.

Business Rules

- This report is required for MLOCR mailing
- Message cannot be sent until a QualificationReportCreateRequest message has been accepted and the customer receives an acceptance message through the QualificationReport CreateResponse message
- Message cannot be sent until a PostageSatementCreateRequest message has been accepted and the customer receives an acceptance message through the PostageStatementCreate Response message
- Will accept if the CustomerGroupID, MailingGroupID, and SubmittingParty information matches an existing mailing group.
- Will validate that the OnePassPlannedOrActual element within the CustomerMailReportCreateRequest matches the OnePassPlannedOrActualFlag element within the QualificationReportCreateRequest message
- Will reject if invalid values are provided

Copyright © 2011 USPS®. All Rights Reserved.

3.19.1 CustomerMailReportCreateRequest

Field Description

Mail.XML 9.0B - CustomerMailReportCreateRequest				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
SubmittingParty	Mailxml:participantIDType		Required Block but all attributes within this block are optional	Refer 'ParticipantIDType' complex type in Appendix E
SubmittingSoftware	Mailxml:submittingSoftwareType		Required	Refer 'SubmittingParty' complex type in Appendix E
CustomerGroupID	String 25		Required	
MailingGroupID	nonnegative Integer		Required	
OnePassPlannedOrActual	Boolean	Yes/No	Optional	
OnePassOrTwoPass	Mailxml_base:onePassOrTwoPassType	Refer 'onePassOrTwoPassType' simple type		Refer Appendix B
CustomerMailReportInfo Block BEGIN			Required 1 to many allowed	
CustomerName	String 50		Optional	
PermitInfo	Complex Type		Optional	Refer 'permitPublicationDataType' complex in Appendix E
Weight	Double		Optional The value of Weight must be in Pounds.	
RateAffixed	Double		Optional	
AdditionalPermitInfo	Complex Type		Optional Cannot populate PublicationNumber.	Refer 'permitPublicationDataType' complex in Appendix E
NumberOfPieces	nonnegative Integer		Optional	
PostageAffixed	Double		Optional	
TotalPostage	Double		Optional	
RunningTotalNumberOfPieces	nonnegative Integer		Optional	

Copyright © 2011 USPS®. All Rights Reserved.

Mail.XML 9.0B - CustomerMailReportCreateRequest				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
CustomerMailReportInfo Block END				

3.20 CustomerMailReportCreateResponse

Purpose
This is a response message to CustomerMailReportCreateRequest

Business Rules

- This report is required for MLOCR mailing

3.20.1 CustomerMailReportCreateResponse

Field Description

Mail.XML 9.0B - CustomerMailReportCreateResponse				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
CustomerMailReportCreate Accept Block BEGIN			Either Accept or Reject Block is returned	
ReturnInfo	Complex Type		Optional	Refer 'ReturnInfo' complex in Appendix E
CustomerMailReportCreate Accept Block END				
CustomerMailReportCreate Reject Block BEGIN			Either Accept or Reject Block is returned	
ReturnInfo	Complex Type		Optional	Refer 'ReturnInfo' complex in Appendix E
CustomerMailReportCreate Reject Block END				

3.21 EndCombinedMailingRequest

Purpose
The endCombinedMailing method is used to mark when postage statements for a combined mailing have all been submitted.

Copyright © 2011 USPS®. All Rights Reserved.

Business Rules

- BeginCombinedMailingRequest must be accepted before submitting the EndCombinedMailingRequest message for the specified MailingGroupID and CustomerGroupID
- All postage statements to be combined must be submitted before sending the end request
- This message is used to combine statements from the PostageStatementCreateRequest.
- This message is used to combine statements from the PeriodicalStatementCreateRequest and/or the ConsolidatedPeriodicalStatementCreateRequest
- All postage statements within the combined mailing must have the same FormType
- All periodical statements within a Combined Periodical mailing must have the same CombinedMailingID
- All postage statements within the combined mailing must be accepted before the submission of the EndCombinedMailingRequest message. The postage statement will not be included in the combined mailing if it is submitted after the EndCombinedMailingRequest message is submitted or if it was rejected.
- Beginning in Release 26.1, First-Class Commerical Plus Parcels will be accepted when the following conditions are met:
    - FormType in the CreatePostageStatement block is FC (First-Class)
    - PresentationCategory in the CreatePostageStatement block is PF (Parcel, First-Class)
    - PriceType in the CreatePostageStatement block is commercialplus

Note - Important information on combined and consolidated postage statements:

Part A – Currently, the Mail.XML specs allows the user to provide different data for the fields listed in Part C below for each postage statement request. During a Combined Mailing Request or during a Consolidated Periodical Postage Statement Request, the values of these fields (listed in Part C) have to be same from a business and processing stand-point. The current implementation of Mail.XML does not provide a feature where the user could supply this data for all of the postage statements that are consolidated or combined. A future release of Mail.XML and *PostalOne!* will cater to this requirement where the user will be required to provide with only one set of data (listed in Part C) for the whole message set of combined or consolidated postage statements. However, in the current implementation, USPS recommends all users to follow the set of instructions provided in section.

Part B – For the following set of postage statement message requests, follow the instructions documented in Part C below.

- BeginCombinedMailingRequest
- EndCombinedMailingRequest
- ConsolidatedPeriodicalStatementCreateRequest
- PeriodicalStatementCreateRequest
- PostageStatementCreateRequest

Part C – For all of the postage statement create requests (items 3, 4, and 5 from above), during a Combined Mailing request (meaning postage statements enclosed in between items 1 and 2 from above) and for ConsolidatedPeriodicalStatementCreateRequest user must provide the same values inside all of the postage statements for the following fields.

- IssueDate
- IssueNumber
- VolumeNumber
- CustomerReferenceID
- AgencyCostCode

Copyright © 2011 USPS®. All Rights Reserved.

- PermitPublicationData *(block of PermitHolderData block)*
- PostagePaymentMethod
- RateType
- ProcessingCategory

3.21.1 EndCombinedMailingRequest Data Structure

Field Description

Mail.XML 9.0B - EndCombinedMailingRequest				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
MailXMLPostageStatement RequestHeaderInfo block	MailXMLPostage StatementReque stHeaderInfo		Attributes block	See Appendix E for Details
SubmittingParty Block	ParticipantIDType		Required block; Identifies the customer submitting the message	See Appendix E for Details
SubmittingSoftware Block	SubmittingSoftwa reType		Required block; Identifies the software submitting the message	See Appendix E for Details
CombinedMailingID	Non-negative Integer		Required	

3.22 EndCombinedMailingResponse

Purpose
The EndCombinedMailingResponse will be used by USPS to notify the customer if their request to end a combined mailing has been accepted or rejected.

Error/Return Codes

Refer Section 2.6 to learn shared error/return codes and also list of error/return codes tied this message.

Business Rules

- Will accept if a combined mailing is open for the mailing group and more than one postage statement has been submitted
- Will reject if a combined mailing is NOT already open for the mailing group
- Will reject if a more than one postage statement has NOT been submitted for the mailing group
- Upon accepting, the *PostalOne!* system will be able to display the combined postage statements
- The ReturnInfo block will have a description for rejection
- This message is used to combine statements from the PostageStatementCreateRequest.
- This message is used to combine statements from the PeriodicalStatementCreateRequest and/or the ConsolidatedPeriodicalStatementCreateRequest
- Beginning in Release 25.0.0, the Periodical Verification statement will be generated immediately after receiving an EndCombinedMailingResponse accept message.

Copyright © 2011 USPS®. All Rights Reserved.

3.22.1 EndCombinedMailingResponse Data Structure

Field Description

Mail.XML 9.0B - EndCombinedMailingResponse				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
EndCombinedMailingAccept Block begins			Block received upon accepting request	
MailXMLMsgResponseHeaderInfo Block	MailXMLMsgResponseHeaderInfo		Attributes block	See Appendix E for Details
CombinedMailingID	Non-negative integer		Required	
ReturnInfo Block	ReturnInfo		Optional Provides reason for return Required Multiple pairings of ReturnCode and ReturnDescription can be provided in the block	See Appendix E for Details
EndCombinedMailingAccept Block ends				
EndCombinedMailingReject Block begins			Block received upon accepting request	
MailXMLMsgResponseHeaderInfo Block	MailXMLMsgResponseHeaderInfo		Attributes block	See Appendix E for Details
ReturnInfo Block	ReturnInfo		Required Provides reason for return Required Multiple pairings of ReturnCode and ReturnDescription can be provided in the block	See Appendix E for Details
EndCombinedMailingAccept Block ends				

2.2.7 - EndCombinedMailingResponse

3.23 ContainerUpdateRequest

Purpose
Allows USPS customers to update a container originally submitted through Mail.dat or Mail.XML.

Business Rules
Mail.dat Business Rules:

- Must be submitted after a Mail.dat file submission has occurred

Copyright © 2011 USPS®. All Rights Reserved.

- The container must already exist in the *PostalOne!* system
- The container must not have any finalized postage
- All additional business rules that apply to Mail.dat file based container updates apply to the Mail.XML container update message set
    - All fields for Full and Mixed Service processing must be provided prior to submission
    - A matching ID in the ContainerID field in the FullContainerID block must exist.
- The CRID must match the Mailing Facility ID in the .seg file
- The following elements can be submitted in the ContainerUpdateRequest to update the value originally submitted in the .csm file (indicated in parenthesis):
    - ReservationNumber (Reservation Number)
    - IMBarcode (Label: IM™ Container Or IM™ Tray Barcode)
    - ScheduledInductionDate (Scheduled Induction Date)
    - ScheduledInductionTime (Scheduled Induction Time)
    - CSATripID (CSA Trip ID)
    - USPSPickUp (USPS Pick UP)
    - ConsigneeContentID (FAST Content ID)
    - FASTScheduerID (FAST Scheduler ID)
    - EntryPointADLocaleKey (Entry Point - Actual / Delivery - Locale Key)
    - EntryPointADPostalCode (Entry Point - Actual / Delivery - Postal Code)
    - ScheduledShipDate (Scheduled Ship Date)
    - ScheduledShipTime (Scheduled Ship Time)
    - TruckDispatchNumber (Truck or Dispatch Number)
    - StopDesignator (Stop Designator)
- Beginning in Release 26.0.0, a Transportation Update will not be accepted when a container is identified as having a parent container through the Parent Container Reference ID originally submitted in the in the .csm file.
- Beginning in Release 26.0.0, a Transportation Update will not be accepted when a container is identified as having a sibling logical container through the Sibling Container Reference ID and Sibling Container Indicator originally submitted in the .csm file.

Mail.XML Business Rules:

- Must be submitted after the QualificationReportCreateRequest message has been accepted
- The container must already exist in the *PostalOne!*
- All of the data element within the SummaryRecordUpdate block should be treated as Optional except for the ContainerStatus element.
- The system shall track every container data updated through Mail.XML by user/company that has sent the update. It will also flag the transaction that are being updated with Mail.XML instead of Mail.dat
- The following elements can be submitted in the ContainerUpdateRequest to update the value originally submitted in the QualificationReportCreateRequest (indicated in parenthesis):
    - IMBarcode (ContainerBarcode)
    - EntryPointADLocaleKey (EntryLocaleKey)
    - EntryPointADPostalCode (PhysicalPostalCodeEntryPoint)
    - ScheduledInductionDate (ScheduleInductionDateTime)
    - ScheduledInductionTime (ScheduleInductionDateTime)
    - CSADispatchNumber (CSADispatchNumber)
    - USPSPickUp (USPSPickUp)
    - ConsigneeContentID (ConsigneeContentID)
    - ScheduledShipDate (ScheduledShipDateTime)
    - ScheduledShipTime (ScheduledShipDateTime)
    - TruckDispatchNumber (TruckAndDispatchNumber)

Copyright © 2011 USPS®. All Rights Reserved.

- Beginning in Release 25.0.0, for Transportation Updates, all fields provided in the ContainerUpdateRequest message will be validated, but only the valid Transportation Update fields will be updated in the database. Any additional fields provided will be ignored.
- Beginning in Release 26.0.0, a Transportation Update when ContainerStatus is T cannot be submitted more than 30 calendar days after the PostageStatementMaililngDate.
- Beginning in Release 26.0.0, the *PostalOne!* system will only support Transportation Updates submitted within 30 days of the Postage Statement Mailing Date. If the Submission Date for the Mail.dat file or Mail.XML ContainerUpdateRequest message is more than 30 days after the Postage Statement Mailing Date, the file and/or message will be rejected.
- Beginning in Release 26.0.0, a Transportation Update will not be accepted when a container is identified as having a parent container through the ParentContainerRefID originally submitted in the original QualificationReportCreateRequest.
- Beginning in Release 26.0.0, a Transportation Update will not be accepted when a container is identified as having a sibling container through the SiblingContainerID submitted in the original QualificationReportCreateRequest.
- Beginning in Release 28.0.0, the CSATripID field in the SummaryRecordUpdate block will be ignored when the ContainerStatus field is populated with 'T' for a Transportation Update.

3.23.1 ContainerUpdateRequest

Field Description

Mail.XML 9.0B - ContainerUpdateRequest				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
SubmittingParty Block	ParticipantIDType		Required block; Identifies the customer submitting the message	Refer 'ParticipantID Type' complex type in Appendix C.
SubmittingSoftware Block	SubmittingSoftwareType		Required block; Identifies the software submitting the message	Refer 'SubmittingSoftware' complex type in Appendix C.
SummaryRecordUpate Block begins			Contains all information to be updated 1 to many can be submitted	
FullContainerID block begins				
UserLicenseCode	userLicenseCode Type		Required for Mail.dat updates	Refer appendix B
MaildatJobID	jobIDType		Required for Mail.dat updates	Refer Appendix B
CustomerGroupID	String 25		Required for Mail.XML updates	

Copyright © 2011 USPS®. All Rights Reserved.

Mail.XML 9.0B - ContainerUpdateRequest				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
MailingGroupID	nonNegative Integer		Required for Mail.XML updates	
ContainerID	String 6	1, 2, 3, 4, 5, E, F, L, O, P, S, T, V, B, U, Z, X, H, A, G, D, R, C, M	Required 1 to many allowed	
UniqueContainerBarcode	Mailxml_base:IMCBType	-	Optional	Refer appendix B
FullContainerID block ends				
Choice Block BEGIN			Optional Block 0 to 2 allowed. Either provide ENtryPointEDPostalCode and EntryPointEDFacilityTYpe OR EntryPointADLocaleKey and EntryPointADPostalCode	
EntryPointEDPostalCode	Mailxml_base:entryPointEDPostalCodeType		Conditionally required if EntryPointEDFacilityType is populated Ignored for Mail.XML transportation updates	Refer Appendix B
EntryPointEDFacilityType	mailxml_base:entryPointEDPostalCodeType	Refer 'entryPointEDPOstalCodeType' simple type	Conditionally required if EntryPointEDPostalCode is populated Ignored for Mail.XML transportation updates	Refer Appendix B
EntryPointADLocaleKey	entryPointADLocaleKeyType		Conditionally required if EntryPointADPostalCode is populated Original data will be	Refer Appendix B

Copyright © 2011 USPS®. All Rights Reserved.

Mail.XML 9.0B - ContainerUpdateRequest				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
			updated for Mail.XML transportation updates (this updates the PhysicalPostalCode EntryPoint from the Qualification Report message)	
EntryPointADPostalCode	entryPointADPostalCodeType		Conditionally required if EntryPointADLocaleKey is populated Original data will be updated for Mail.XML transportation updates	Refer Appendix B
Choice Block END				
ContainerGroupingDescription	String, 9 characters		Not required Ignored for Mail.XML transportation updates	
ParentContainerRefID	String, 6 characters		Not required Ignored for Mail.XML transportation updates	
TruckDispatchNumber	truckDispatchNumberType		Not required Ignored for Mail.XML transportation updates	Refer Appendix B
StopDesignator	stopDesignatorType		Not required Ignored for Mail.XML transportation updates	Refer Appendix B
ReservationNumber	ReservationNUmberType		Not required Original data will be updated for Mail.XML transportation	Refer Appendix B

Copyright © 2011 USPS®. All Rights Reserved.

Mail.XML 9.0B - ContainerUpdateRequest				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
			updates	
Sequence Block # 1 BEGIN			Optional	
ContainerShipDate	Date	YYYY-MM-DD	Conditionally required if ContainerShipTime is populated Ignored for Mail.XML transportation updates	
ContainerShipTime	Time	HH:MM:SS	Conditionally required if ContainerShipDate is populated Ignored for Mail.XML transportation updates	
Sequence Block # 1 END				
Sequence Block # 2 BEGIN			Optional	
ScheduledShipDate	Date	YYYY-MM-DD	Conditionally required if ScheduledShipTim e is populated Original data will be updated for Mail.XML transportation updates	
ScheduledShipTime	Time	HH:MM:SS	Conditionally required if ScheduledShipDate is populated Original data will be updated for Mail.XML transportation updates	
Sequence Block # 2 END				

Copyright © 2011 USPS®. All Rights Reserved.

Mail.XML 9.0B - ContainerUpdateRequest				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
Sequence Block # 3 BEGIN			Optional	
ActualContainerShipDate	Date	YYYY-MM-DD	Conditionally required if ActualContainerShipTime is populated Ignored for Mail.XML transportation updates	
ActualContainerShipTime	Time	HH:MM:SS	Conditionally required if ActualContainerShipDate is populated Ignored for Mail.XML transportation updates	
Sequence Block # 4 END				
Sequence Block # 5 BEGIN			Optional	
ScheduledContainerPickupDate	Date	YYYY-MM-DD	Conditionally required if ScheduledContainerPickupTime is populated Ignored for Mail.XML transportation updates	
ScheduledContainerPickupTime	Time	HH:MM:SS	Conditionally required if ScheduledContainerPickupDate is populated Ignored for Mail.XML transportation updates	
Sequence Block # 5 END				
Sequence Block # 6 BEGIN			Optional	

Copyright © 2011 USPS®. All Rights Reserved.

Mail.XML 9.0B - ContainerUpdateRequest				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
ActualContainerPickupDate	Date	YYYY-MM-DD	Conditionally required if ActualContainerPickupTime is populated Ignored for Mail.XML transportation updates	
ActualContainerPickupTime	Time	HH:MM:SS	Conditionally required if ActualContainerPickupDate is populated Ignored for Mail.XML transportation updates	
Sequence Block # 6 END				
ContainerAcceptanceDate	Date	YYYY-MM-DD	Not required Ignored for Mail.XML transportation updates	
ScheduledInHomeDate	Date	YYYY-MM-DD	Not required Ignored for Mail.XML transportation updates	
AdditionalInHomeRange	String, 1 character		Not required Ignored for Mail.XML transportation updates	
Sequence Block # 7 BEGIN			Optional	
ScheduledInductionDate	Date	YYYY-MM-DD	Conditionally required if ScheduledInductionTime is populated Original data will be updated for Mail.XML	

Copyright © 2011 USPS®. All Rights Reserved.

Mail.XML 9.0B - ContainerUpdateRequest				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
			transportation updates	
ScheduledInductionTime	Time	HH:MM:SS	Conditionally required if ScheduledInduction Date is populated Original data will be updated for Mail.XML transportation updates	
Sequence Block # 7 END				
Sequence Block # 8 BEGIN			Optional	
ActualInductionDate	Date	YYYY-MM-DD	Conditionally required if ActualInductionTim e is populated Ignored for Mail.XML transportation updates	
ActualInuctionTime	Time	HH:MM:SS	Conditionally required if ActualInductionDat e is populated Ignored for Mail.XML transportation updates	
Sequence Block # 8 END				
Sequence Block # 9 BEGIN			Optional	
PostageStatementMailingD ate	Date	YYYY-MM-DD	Conditionally required if PostageStatement MailingTime is populated Ignored for Mail.XML transportation updates	

Copyright © 2011 USPS®. All Rights Reserved.

Mail.XML 9.0B - ContainerUpdateRequest				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
PostageStatementMailingTime	Time	HH:MM:SS	Conditionally required if PostageStatement MailingDate is populated Ignored for Mail.XML transportation updates	
Sequence Block # 9 END				
ContainerReadyToPayTransactionID	Number, 6 characters		Not required Ignored for Mail.XML transportation updates	
TransportationCarrierID	String, 15 characters		Not required Ignored for Mail.XML transportation updates	
CSATripID	String, 10 characters		Not required Original data will be updated for Mail.XML transportation updates	
InternalDate	Date	YYYY-MM-DD	Not required Ignored for Mail.XML transportation updates	
TotalWeight	Number, 5 characters		Not required Ignored for Mail.XML transportation updates. The value of TotalWeight must be in Pounds.	
UniqueContainerID	String, 12 characters		Not required	

Copyright © 2011 USPS®. All Rights Reserved.

Mail.XML 9.0B - ContainerUpdateRequest				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
ContainerStatus	mailxml_base:maildatContainerStatusType	Refer 'maildatContainerStatusTYpe' simple type	Required Must be 'T' for Mail.XML updates	Refer Appendix B
TransShipBoLNumber	String, 5 characters		Not required Ignored for Mail.XML transportation updates	
PostageGroupingID	String, 8 characters		Not required Ignored for Mail.XML transportation updates	
ContainerGrossWeight	String, 5 characters		Not required Ignored for Mail.XML transportation updates. The value of ContainerGrossWeight must be in Pounds.	
ContainerHeight	Number, 3 characters		Not required Ignored for Mail.XML transportation updates	
ContainerHeightSource	mailxml_base:containerHeightSourceType	Refer 'containerHeightSourceType' simple type	Not required Ignored for Mail.XML transportation updates	Refer Appendix B
TransportDUNSNumber	String, 15 characters		Not required Ignored for Mail.XML transportation updates	
IMBarcode	IMCBType		Not required Original data will be updated for Mail.XML	Refer Appendix B

Copyright © 2011 USPS®. All Rights Reserved.

Mail.XML 9.0B - ContainerUpdateRequest				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
			transportation updates	
UserInformationLine1	String, 40 characters		Not required Ignored for Mail.XML transportation updates	
UserInformationLine2	String, 40 characters		Not required Ignored for Mail.XML transportation updates	
ConsigneeContentID	String, 9 characters		Not required Original data will be updated for Mail.XML transportation updates	
FASTSchedulerID	String, 12 characters		Not required Original data will be updated for Mail.XML transportation updates.	
USPSPickUp	String, 1 character	Y = Yes N = No	Not required Original data will be updated for Mail.XML transportation updates	
CarrierRouteNumber	String exactly 4		Optional Ignored for Mail.XML transportation updates	
CinCode	String 3		Optional Ignored for Mail.XML transportation updates	
ContainerDisplayName	String 50		Optional Ignored for Mail.XML	

Copyright © 2011 USPS®. All Rights Reserved.

Mail.XML 9.0B - ContainerUpdateRequest				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
			transportation updates	
ContainerType	Mailxml_base:mailXMLContainerType		Optional Ignored for Mail.XML transportation updates	Refer Appendix B
IncludedInOtherDoc	includedinotherdocType		Optional Ignored for Mail.XML transportation updates	Refer Appendix B
SiblingContainerID	String 6		Optional Ignored for Mail.XML transportation updates	
SortationLevel	Mailxml_base:ContainerLevelType		Optional Ignored for Mail.XML transportation updates	Refer Appendix B
OverflowIndicator	Mailxml_base:yesNo	Yes No	Optional Ignored for Mail.XML transportation updates	Refer Appendix B
SummaryRecordUpate Block ends				

2.2.8 – ContainerUpdateRequest

3.24 ContainerUpdateResponse

Purpose
The MailDatContainerUpdateResonse will be used by USPS to notify the customer if their request to update a container originally submitted via Mail.dat has been accepted or rejected.

Error/Return Codes

Refer Section 2.6 to view shared error/return codes and also a list of error/return codes tied this message.

Business Rules

Copyright © 2011 USPS®. All Rights Reserved.

Mail.dat Business Rules:

- Will accept if original container exists and valid values are passed in updated fields
- Will reject if original container does not exist or invalid values are passed in updated fields
- If accepted, container information returned will reflect updated values in *PostalOne!*
- If rejected, container information returned will reflect attempted updated values from the request
- Will reject if attempting to update the logical facility after payment has been received on a container
- Will only allow T status after an R or X
- Will reject if deleted containers are attempted to be re-used
- The ReturnInfo block will have a description for rejection

- Postage statement will be cancelled if ContainerStatus is updated to C or D and PostageStatementStatus is UPD and ContainerStatus is R
- EntryPointEDPostalCode and EntryPointEDFacility fields cannot be updated when the original container has a ContainerStatus of R
- Only the Full Container Block will be returned to a mailer to confirm requested updates if the message is accepted
- Postage statement will be cancelled and the associated Reconciliation Report will be updated for the specified CRID if PosatageStatementStatus is UPD and all SummaryRecordUpdate block are updated to D
- The ContainerStatus field in the SummaryRecordUpdate block can only be populated with R if it is updating a container that has the ContainerStatus populated with C for Cancel in the prior update
- Transportation update information is not sent to the Full-Service system for Full-Service appointment or CSA compliance checking

3.24.1 ContainerUpdateResponse

Field Description

Mail.XML 9.0B - ContainerUpdateResponse				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
ContainerUpdateAccept Block begins			Block received upon accepting request	
FullContainerID block begins				
Choice Block BEGIN				
UserLicenseCode			Required	
MaildatJobID			Required	
CustomerGroupID	String 25		Required	
MailingGroupID	171nonnegative Integer		Required	

Copyright © 2011 USPS®. All Rights Reserved.

Mail.XML 9.0B - ContainerUpdateResponse				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
Choice Block END				
ContainerID	String	1, 2, 3, 4, 5, E, F, L, O, P, S, T, V, B, U, Z, X, H, A, G, D, R, C, M	Required 1 to many allowed	
UniqueContainerBarcode	24 Character Barcode		Optional	
FullContainerID block ends				
ReturnInfo block	ReturnInfo		Optional	See Appendix E for Details
MaildatContainerUpdateAccept block ends				
MaildatContainerUpdateReject block begins				
ReturnInfo block	ReturnInfo		Required	See Appendix E for Details
FullContainerID Block BEGIN				
Choice Block BEGIN				
UserLicenseCode			Required	
MaildatJobID			Required	
CustomerGroupID	String 25		Required	
MailingGroupID	nonnegative Integer		Required	
Choice Block END				
ContainerID	String	1, 2, 3, 4, 5, E, F, L, O, P, S, T, V, B, U, Z, X, H, A, G, D, R, C, M	Required 1 to many allowed	
UniqueContainerBarcode	24 Character Barcode		Optional	
FullContainerID block ends				
ContainerUpdateReject block ends				

2.2.9 - ContainerUpdateResponse

Copyright © 2011 USPS®. All Rights Reserved.

3.25 MailingGroupQueryRequest

The MailingGroupQueryRequest message will allow the customer to provide a Customer Group ID (Customer Job ID) to request the information on a mailing group in the *PostalOne!* system.
For more details on required vs. optional fields and blocks as well as the data types, please review the *Mail.XML Transaction Message Protocol Messaging Specification*.

3.25.1 MailingGroupQueryRequest

Field Description

Mail.XML 9.0B - MailingGroupQueryRequest				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
SubmittingParty	ParticipantIDType		Identifies the customer submitting the message	Refer 'ParticipantID Type' complex type in Appendix D.
SubmittingSoftware	SubmittingSoftwareType		Identifies the software submitting the message	Refer 'SubmittingSoftware' complex type in Appendix D.
MailXMLMailGroupRequest HeaderInfo Block Opens				
CustomerGroupID	String, 25 characters		Required (attribute)	
MailingGroupID	Non Negative Integer		Required (attribute)	
MailXMLMailGroupRequest HeaderInfo Block Close				

2.2.10 - MailingGroupQueryRequest

3.26 MailingGroupQueryResponse

The MailingGroupQueryResponse message will allow the USPS *PostalOne!* system to sends back basic information about the mailer, including Permit or Publication Number information, mailing acceptance office ZIP Code, and the type of presort used in the mailing while assigning a MailingGroupID.
For more details on required vs. optional fields and blocks as well as the data types, please review the *Mail.XML Transaction Message Protocol Messaging Specification*.

3.26.1 MailingGroupQueryResponse Data Structure

Field Description

Mail.XML 9.0B - MailingGroupQueryResponse

Copyright © 2011 USPS®. All Rights Reserved.

Field	Format	Acceptable Values	Business Rules	Comments
MailXMLMailGroupRequest HeaderInfo block Opens				
CustomerGroupID	String, 25 characters		Required (attribute)	
MailingGroupID	Non Negative Integer		Required (attribute)	
MailXMLMailGroupRequest HeaderInfo block Opens				
Status	mailxml_base:statusType	Refer 'statusType' simple type	Optional (attribute)	Refer Appendix B
QueryResults Block Opens				
MailingGroup Block Opens				
CustomerDescription	String, 50 characters		Optional	
SubmitterCRID	String, 10 characters		Optional	
PermitPublicationData	PermitPublication Data			Refer 'PermitPublicationData' complex type in Appendix D.
PostOfficeOfMailingZip	String, 5 characters		Must be exactly 5 characters	
MailingFacility	String, 10 characters		Optional	
MailXmlPresentationCategory	mailxml_base:mailXMLPresentationCategoryType	Refer 'mailXMLPresentationCategoryType' simple type	Optional	Refer Appendix B
MailerID	String		Optional	
FullServiceParticitpationIndicator	mailxml_base:fspiTYpe	Refer 'fspiType' simple type	Optional	Refer Appendix B
MailAgreementType	mailxml_base:mailAgreementTypeType	Refer 'mailAgreementTypeTYpe' simple type	Optional	Refer Appendix B
ContractNumber	String, 20 characters		Optional	
OnePassIndicator	String	Yes, No	Optional	
LogicalPhysicalContainerIndicator	mailxml_base:logicalPhysicalContainerIndicatorType	Refer 'logicalPhysicalContainerIndicatorType' simple type	Optional	Refer Appendix B
MailingGroup Block Closes			Optional	
ReturnInfo	ReturnInfo		Required	Refer 'ReturnInfo'

Copyright © 2011 USPS®. All Rights Reserved.

Mail.XML 9.0B - MailingGroupQueryResponse				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
				complex type in Appendix D.
QueryResults Block Closes				
QueryError Block Opens				
ReturnInfo	ReturnInfo		Required	Refer 'ReturnInfo' complex type in Appendix D.
QueryError Block Closes				

2.2.11 - MailingGroupQueryResponse

3.27 MailPieceCancelRequest

Purpose
Used to cancel a previously created mailpiece or piece range

Business Rules

- Must be submitted to a currently existing mailpiece or piece range
- MailingGroupID and CustomerGroupID must exist for an open mailing
- Cannot cancel a mailpiece if the 'W' or 'S' indicators for WastedPieceIndicator have resulted in adjusting an already finalized postage statement
- Cannot cancel a mailpiece or piece range if postage has been finalized on its corresponding container

3.27.1 MailPieceCancelRequest

Field Description

Mail.XML 9.0B - MailPieceCancelRequest				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
CustomerGroupID	String 25		Optional	
MailingGroupID	nonNegative Integer		Optional	
MaildatJobID			Optional	
UserLicenseCode			Optional	
SubmittingParty Block	ParticipantIDType		Required block; Identifies the customer submitting the message	Refer 'ParticipantID Type' complex type in Appendix E.

Copyright © 2011 USPS®. All Rights Reserved.

Mail.XML 9.0B - MailPieceCancelRequest				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
SubmittingSoftware Block	SubmittingSoftwareType		Required block; Identifies the software submitting the message	Refer 'SubmittingSoftware' complex type in Appendix E.
UserLicenseCode			Field not being supported	
MaildatJobID			Field not being supported	
TransmittedCount	nonNegative Integer		Optional	
PDRMailPieceBlock			Block not being supported	
PackageID				
CQTDatabaseID				
MailPiece block begins			Required	
ServiceLevelIndicator			Required	
Choice Block BEGIN			Optional Choice Block. If used then either provide LOTSequenceDirectionCode and LOTSequenceNumber OR WalkSequenceNumber	
LOTSequenceDirectionCode	String 1		Required	
LOTSequenceNumber	Ns04		Required	
WalkSequenceNumber	Ns05		Required	
Choice Block END				
Choice Block BEGIN			Optional Choice block. If used, provide either IMB Block data OR PlanetCode (Optional) with DeliveryPointZip data OR DeliveryContainerId with DeliveryPointZip data.	
IMB block	IntelligentMailBarcodeType		Required	See Appendix E for Details

Copyright © 2011 USPS®. All Rights Reserved.

Mail.XML 9.0B - MailPieceCancelRequest				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
PlanetCode			Optional	
DeliveryPointZip	Mailxml_base:RoutingZipCodeType	Refer 'RoutingZipCode Type' simple type	Required	Appendix B
DeliveryContainerID	Numeric String 22		Required	
DeliveryPointZip	Mailxml_base:RoutingZipCodeType	Refer 'RoutingZipCode Type' simple type	Required	Appendix B
Choice Block END				
PieceID	String 22		Required	
WastedPieceIndicator			Optional	
MLOCRrateANDpostageMarking	String 7		Optional	
MoveComplianceUpdateMethod			Optional	
MailOwner block	ParticipantIDType		Optional	See Appendix E for Details
BarCodeApplicator block	ParticipantIDType		Optional	See Appendix E for Details
MachineID	String 4		Optional	
ACSKeyline	String 16		Optional	
MailPiece block ends				
PDRMailPieceBlock block ends				
PDRRangePieceBlock block begins			Block not being supported	
DatabaseContainerID				
PieceRangeBlock block begins			Required	
IMbarcodeLowerSerialization block begins				
MailerID6			Required	
SerialNumber9			Required	
MailerID9			Required	
SerialNumber6			Required	
IMbarcodeLowerSerialization block ends				
IMBarcodeUpperSerialization block begins				
MailerID6			Required	
SerialNumber9			Required	
MailerID9			Required	
SerialNumber6			Required	

Copyright © 2011 USPS®. All Rights Reserved.

Mail.XML 9.0B - MailPieceCancelRequest				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
IMBarcodeUpperSerialization block ends				
MailPreparer block	ParticipantIDType			See Appendix E for Details
MailOwner block	ParticipantIDType			See Appendix E for Details
ServiceTypeCode			Required	
MailClass			Required	
ServiceLevelIndicator			Required	
Pieces	nonNegative Integer		Required	
Copies	nonNegative Integer		Required	
PieceRangeBlock block ends				
PDRRangePieceBlock block Ends				
MailPieceID Block begins				
IMB block begins	IntelligentMailBarcodeType			See Appendix E for Details
PlanetCode			Optional	
DeliveryPointZip	Mailxml_base:RoutingZipCodeType	Refer 'RoutingZipCode Type' simple type	Conditionally required for Full-Service / Mixed Service mailings.	Appendix B
DeliveryContainerID	Ns22		Required	
DeliveryPointZip	Mailxml_base:RoutingZipCodeType	Refer 'RoutingZipCode Type' simple type	Conditionally required for Full-Service / Mixed Service mailings.	Appendix B
MailPieceID Block ends				
PieceRangeID	String 22		Required	
CustomerGroupID	String, 25 characters		Required field; must be populated with the same value as the CustomerGroupID in the MailPieceCreateResponse message	
MailingGroupID	Non-negative Integer		Required field; must be populated with the same value as the MailingGroupID in	

Copyright © 2011 USPS®. All Rights Reserved.

Mail.XML 9.0B - MailPieceCancelRequest				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
			the MailPieceCreateResponse message	
TransmittedCount	Non-negative Integer		Not required Count of records transmitted in message	
MailPieceBlockGroup Block begins			1 to many can be submitted Either MailPieceBlock or MailXMLPieceRangeBlock submitted	
ContainerID	String 6		Required	
BundleID	String 12		Optional	
MailPieceBlock block begins				
ServiceLevelIndicator	mailxml_base:serviceLevelIndicatorType	Refer 'serviceLevelIndicatorType' simple type	Required	Refer Appendix B
LOTSequenceDirectionCode	String, 1 character		Not required Either WalkSequenceNumber or pair of LOTSequenceDirectionCode and LOTSequenceNumber	
LOTSequenceNumber	Number, 4 characters		Not required Either WalkSequenceNumber or pair of LOTSequenceDirectionCode and LOTSequenceNumber	
WalkSequenceNumber	Number, 5 characters		Not required Either WalkSequenceNumber or pair of LOTSequenceDirectionCode and LOTSequenceNumber	
IntelligentMailBarcodeType Block	IntelligentMailBarcodeType			See Appendix E for Details
PlanetCode	Number, 13 characters		Not required	

Copyright © 2011 USPS®. All Rights Reserved.

Mail.XML 9.0B - MailPieceCancelRequest				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
DeliveryPointZIP	Number, 11 characters		Conditionally required if PlanetCode is submitted	
DeliveryContainerID			Field not being supported	
DeliveryPointZIP			Field not being supported in conjunction with DeliveryContainerID	
PieceID	String, 22 characters		Required	
WastedPieceIndicator	mailxml_base:wastedPieceIndicatorTYpe	Refer 'wastedPieceIndicatorType' simple type	Not required	Refer Appendix B
MLOCRrateANDpostageMarking	String, 7 characters	Letters/Flats P1/F1 = Barcoded 1-ounce Permit Imprint P2/F2 = Barcoded 2-ounce Permit Imprint P3/F3 = Barcoded 3-ounce Permit Imprint P4/F4 = Barcoded 4-ounce Permit Imprint /F5 = Barcoded 5-ounce Permit Imprint /F6 = Barcoded 6-ounce Permit Imprint /F7 = Barcoded 7-ounce Permit Imprint /F8 = Barcoded 8-ounce Permit Imprint /F9 = Barcoded 9-ounce Permit Imprint /F0 = Barcoded	Not required	

Copyright © 2011 USPS®. All Rights Reserved.

Mail.XML 9.0B - MailPieceCancelRequest				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
		10-ounce Permit Imprint /FA = Barcoded 11-ounce Permit Imprint /FB = Barcoded 12-ounce Permit Imprint /FC = Barcoded 13-ounce Permit Imprint 51/MF = Barcoded 5-Digit Meter Postage Affixed - 1 ounce 52/ = Barcoded 5-Digit Meter Postage Affixed - 2 ounces 53/ = Barcoded 5-Digit Meter Postage Affixed - 3 ounces 54/ = Barcoded 5-Digit Meter Postage Affixed - 4 ounces 31/MT = Barcoded 3-Digit Meter Postage Affixed - 1 ounce 32/ = Barcoded 3-Digit Meter Postage Affixed - 2 ounces 33/ = Barcoded 3-Digit Meter Postage Affixed - 3 ounces 34/ = Barcoded 3-Digit Meter Postage Affixed - 4 ounces A1/MD = Barcoded AADC Meter Postage Affixed - 1 ounce A2/ = Barcoded AADC Meter Postage Affixed - 2 ounces		

Copyright © 2011 USPS®. All Rights Reserved.

Mail.XML 9.0B - MailPieceCancelRequest				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
		A3/ = Barcoded AADC Meter Postage Affixed - 3 ounces A4/ = Barcoded AADC Meter Postage Affixed - 4 ounces M1/MX = Barcoded Mixed AADC Meter Postage Affixed - 1 ounce M2/ = Barcoded Mixed AADC Meter Postage Affixed - 2 ounces M3/ = Barcoded Mixed AADC Meter Postage Affixed - 3 ounces M4/ = Barcoded Mixed AADC Meter Postage Affixed - 4 ounces 11/ = Presorted Meter Postage Affixed - 1 ounce 12/ = Presorted Meter Postage Affixed - 2 ounces 13/ = Presorted Meter Postage Affixed - 3 ounces 14/ = Presorted Meter Postage Affixed - 4 ounces S1/ = Precanceled $0.15 Stamp Affixed (card) S2/ = S2 Precanceled $0.25 Stamp Affixed		

Copyright © 2011 USPS®. All Rights Reserved.

Mail.XML 9.0B - MailPieceCancelRequest				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
MoveComplianceUpdateMethod	mailxml_base:moveUpdateMethodType	Refer 'moveUpdateMethodType' simple type	Not required	Refer Appendix B
MailOwner Block	ParticipantIDType			See Appendix E for Details
BarCodeApplicator Block	ParticipantIDType			See Appendix E for Details
MachineID	String, 4 characters		Not required	
CustomerBundleID	String, 12 characters		Not required	
ACSKeyline	String, 16 characters		Not required	
MailPieceBlock Block ends				
MailPieceBlockGroup Block ends				
MailXMLPieceRangeBlock Block begins			0 to 1 can be submitted Either MailPieceBlock or MailXMLPieceRangeBlock submitted	
PieceRangeID	String 22			
ContainerID	Char 24			
IMBarcodeLowerSerialization Block begins			Required Only one can be submitted	
MailerID6	Number, 6 characters		Required Only one pairing of MailerID and SerialNumber is required	
SerialNumber9	Number, 9 characters		Required Only one pairing of MailerID and SerialNumber is required	
MailerID9	Number, 9 characters		Required Only one pairing of MailerID and SerialNumber is required	
SerialNumber6	Number, 6 characters		Required Only one pairing of MailerID and SerialNumber is	

Copyright © 2011 USPS®. All Rights Reserved.

Mail.XML 9.0B - MailPieceCancelRequest				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
			required	
IMBarcodeLowerSerialization Block ends				
IMBarcodeUpperSerialization Block begins			Required Only one can be submitted	
MailerID6	Number, 6 characters		Required Only one pairing of MailerID and SerialNumber is required	
SerialNumber9	Number, 9 characters		Required Only one pairing of MailerID and SerialNumber is required	
MailerID9	Number, 9 characters		Required Only one pairing of MailerID and SerialNumber is required	
SerialNumber6	Number, 6 characters		Required Only one pairing of MailerID and SerialNumber is required	
IMBarcodeUpperSerialization Block ends				
MailPreparer Block	ParticipantIDType			See Appendix E for Details
MailOwner Block	ParticipantIDType			See Appendix E for Details
ServiceTypeCode	Number, 3 characters		Conditionally required if Mail Class is not provided	
MailClass	Number, 1 character		Conditionally required if Service Type Code is not provided	
ServiceLevelIndicator	mailxml_base:serviceLevelIndicatorType	Refer 'serviceLevelIndicatorType' simple type	Required	Refer Appendix B
Pieces	nonNegative Integer		Required	
Copies	nonNegative		Required	

Copyright © 2011 USPS®. All Rights Reserved.

Mail.XML 9.0B - MailPieceCancelRequest				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
	Integer			
PieceRangeBlock Block ends				
MailXMLPieceRangeBlock Block ends				

2.2.12 - MailPieceCancelRequest

3.28 MailPieceCancelResponse

Purpose
Accept or reject a request to cancel a mailpiece or piece range

Error/Return Codes
Refer Section 2.6 to view shared error/return codes and also a list of error/return codes tied this message.

Business Rules
- Will accept if the mailpiece or piece range exists
- Will accept if Postage StatementStatus is UPD for USPS Processing Due
- Will reject if the mailpiece or piece range does not exist
- Will reject if a mailpiece 'W' or 'S' indicators for WastedPieceIndicator have resulted in adjusting an already finalized postage statement
- Will reject if Postage StatementStatus is FIN for finalized or FPP for finalized pending payment
- For mail piece and piece range cancellation QualificationReportCreateRequest and BundleDetailCreateRequest messages have not been accepted
- The MailPieceBlock for the MailPieceCancelRequest and MailPieceCreateRequest must be the same for the specified MailingGroupID and CustomerGroupID
- The MailXMLPieceRangeBlock for the MailPieceCancelRequest and MailPieceCreateRequest must be the same for the specified MailingGroupID and CustomerGroupID
- The ReturnInfo block will have a description for rejection

3.28.1 MailPieceCancelResponse

Field Description

Mail.XML 9.0B - MailPieceCancelResponse				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
MailPieceCreateAccept Block begins			Block received upon accepting request 1 to many can be submitted	
MailXMLHeaderInfo block begins				
CustomerGroupID	String 25		Optional	
MailingGroupId	nonNegative Integer		Optional	

Copyright © 2011 USPS®. All Rights Reserved.

Mail.XML 9.0B - MailPieceCancelResponse				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
MaildatJobID			Optional	
UserLicenseCode			Optional	
MailXMLHeaderInfo block ends				
CancelConfirmID	String, 12 characters		Required	
ReturnInfo Block	ReturnInfo		Optional	See Appendix A for Details
MailPieceCreateAccept Block ends				
MailPieceCreateReject Block begins			Block received upon rejecting request 1 to many can be submitted	
MailXMLHeaderInfo block begins				
CustomerGroupID	String 25		Optional	
MailingGroupId	nonNegative Integer		Optional	
MaildatJobID			Optional	
UserLicenseCode			Optional	
MailXMLHeaderInfo block ends				
ReturnInfo Block	ReturnInfo		Required	See Appendix A for Details
MailPieceCreateReject Block ends				

2.2.13 - MailPieceCancelResponse

3.29 MailPieceCreateRequest

Purpose
Used to create mailpieces or piece ranges for a mailing group. Piece Range records should represent the maximum number of pieces for a handling unit/container for a particular service level. To ensure efficient Full-Service processing, single pieces should be represented by Mail Pieces instead of the same Upper and Lower Piece Ranges.

Business Rules

- The MailPieceCreateRequest message can only be submitted when the FullServiceParticipationIndicator in the OpenMailingGroupRequest message is set to F (Full-Service) or M (Mixed Service).
- Must be submitted after all QualificationReportCreateRequest messages have been accepted
- MailingGroupID and CustomerGroupID must exist for an open mailing

Copyright © 2011 USPS®. All Rights Reserved.

- In November – for the WastedPieceIndicator field; only 'X' and 'T' are recommended at this time. If 'W' or 'S' is provided then system will ignore those values and those will be treated as blank by the system.
- Beginning in Release 25.0.0, the system will support shortage and spoilage that do not trigger postage adjustment with WastedPieceIndicator field set to X and T. The system will validate that the number of MailPieceBlock blocks without WastedPieceIndicator set to X and T equals the sum of the TotalPieces fields, the TotalCopies fields, or a value in between the sum of these fields in the ContainerDetailData blocks in the QualificationReportCreateRequest message.
- For full-service and mixed service mailings, each container ID in the MailPieceCreateRequest message must exist in a previously submitted QualificationReportCreateRequest message.
- For full-service and mixed service mailings, the total number of pieces per container ID in the MailPieceCreateRequest message cannot exceed the total number of pieces per container in the previously submitted QualificationReportCreateRequest message (for mail piece or piece range).
- Beginning in Release 25.0.0, for Full-Service and Mixed Service mailings, at least one of CRID, MailOwnerMID6, MailOwnerMID9, PermitNumber, or PublicationNumber must be provided,
- Beginning in Release 25.0.0, for MLOCR mailings, either the BarcodeID, ServiceTypeCode, MailerID6, and SerialNumber9 fields or the BarcodeID, ServiceTypeCode, MailerID9, and SerialNumber6 fields must be populated.
- Beginning in Release 25.0.0, for MLOCR mailings, the IMBUpperSerialization block and IMBLowerSerialization block must be populated.
- Beginning in Release 26.0.0, the MailPieceCreateRequest messages will be rejected when the sum of the MailXMLPieceRangeBlock IMbarcodeUpperSerialization minus the MailXMLPieceRangeBlocks IMbarcodeLowerSerialization plus 1 (one) for all Full-Service blocks within the mailing group is either:
    - 20% or more greater than the larger of either (1) the sum of the Pieces field for all full-service PieceRangeBlocks or (2) the sum of Copies field for all full-service PieceRangeBlocks, or
    - Less than the smaller of either (1) the sum of the Pieces field for all full-service PieceRangeBlocks or (2) the sum of Copies field for all full-service PieceRangeBlocks.
- Beginning in Release 28.0.0, MailPieceCreateRequest messages can be submitted before or after the Postage/Periodical/Consolidated Statements. If they are submitted after, it must be before finalization. Full-service or mixed service mailings cannot be finalized until all pieces are submitted via the MailPieceCreateRequest messages. All piece counts must match between the MailPieceCreateRequest, Postage/Periodical/Consolidated Statements and QualificationReportCreateRequest messages.
- Beginning in Release 28.0.0, the mailing data will not be sent to the SASP system when a postage statement is submitted as without piece data.
- Beginning in Release 28.0.0, the ContainerDetailID field in the MailXMLPieceRange block will not be accepted.

3.29.1 MailPieceCreateRequest

Field Description

Mail.XML 9.0B - MailPieceCreateRequest				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
MailPieceCreateRequest Message BEGINS				

Copyright © 2011 USPS®. All Rights Reserved.

Mail.XML 9.0B - MailPieceCreateRequest				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
SubmittingParty Block	ParticipantIDType		Required block; Identifies the customer submitting the message	Refer 'ParticipantID Type' complex type in Appendix C.
SubmittingSoftware Block	SubmittingSoftwareType		Required block; Identifies the software submitting the message	Refer 'SubmittingSoftware' complex type in Appendix C.
UserLicenseCode	Mailxml_base:userLicenseCodeType		Field not being supported	Refer Appendix B
MaildatJobID	Mailxml_base:jobIDType		Field not being supported	Refer Appendix B
TransmittedCount	nonNegative Integer		Optional	
Choice Block BEGINS			Either PDRMailPIeceBlock or PDRRangePieceBlock	Currently this block is not supported.
PDRMailPieceBlock			Block not being supported	
PDRRangePieceBlock			Block not being supported	
Choice Block ENDS				
CustomerGroupID	String, 25 characters		Required field; must be populated with the same value as the CustomerGroupID in the QualificationReport CreateResponse message	
MailingGroupID	Non-negative Integer		Required field; must be populated with the same value as the MailingGroupID in the QualificationReport CreateResponse	

Copyright © 2011 USPS®. All Rights Reserved.

Mail.XML 9.0B - MailPieceCreateRequest				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
			message	
TransmittedCount	Non-negative Integer		Optional Count of records transmitted in message	
Choice Block BEGINS			Either MailPieceBlockGroup or MailXMLPieceRangeBlock	
MailPieceBlockGroup block BEGINS				
ContainerID	String 6		Required	
ContainerDetailID	String 9		Optional. Links QUal, Postage, and Mailpiece data	-
BundleID	String 12		Optional	
MailPieceBlock Block begins			1 to many can be submitted Either MailPieceBlock or MailXMLPieceRangeBlock submitted	
ServiceLevelIndicator	mailxml_base:serviceLevelIndicatorType	Refer 'serviceLevelIndicatorType' simple type	Required For Full-Service / Mixed Service mailings, the ServiceLevelIndicator field must be populated with 'F' when its associated ContainerID has the ServiceLevelIndicator field in the QualificationReportCreateRequest message populated with 'F'.	Refer Appendix B
Choice Block BEGINS			OPTIONAL. If provided then either LOTSequence	-

Copyright © 2011 USPS®. All Rights Reserved.

Mail.XML 9.0B - MailPieceCreateRequest				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
			Data or WalkSequence data should be provided.	
Sequence Block BEGINS				
LOTSequenceDirectionCode	String, 1 character		Either WalkSequenceNumber or combination of LOTSequenceDirectionCode and LOTSequenceNumber should be provided.	
LOTSequenceNumber	Number, 4 characters		Either WalkSequenceNumber or combination of LOTSequenceDirectionCode and LOTSequenceNumber should be provided	
Sequence Block ENDS				
WalkSequenceNumber	Number, 5 characters		Either WalkSequenceNumber or combination of LOTSequenceDirectionCode and LOTSequenceNumber	
Choice Block ENDS				
Choice Block BEGINS			Optional Either IMB or PlantCode with DeliveryPointZip OR DeliveryCOntainerID with DeliveryPointZip is required, if this choice block is used.	

Copyright © 2011 USPS®. All Rights Reserved.

Mail.XML 9.0B - MailPieceCreateRequest				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
IMB Block	IntelligentMailBarcodeType	This is a complex type	Required Block. Only one occurrence is allowed	See Appendix C for Details
Sequence Block BEGINS				
PlanetCode	mailxml_base:planetCodeType	Refer 'planetCodeType' simple type	Not required	Refer appendix B
DeliveryPointZIP	Mailxml_base:routingZipCodeType	Refer 'routingZipCodeType' simple type	Conditionally required if PlanetCode is submitted	See Appendix B
Sequence Block ENDS				
Sequence Block BEGINS				
DeliveryContainerID	Numeric string, 22 characters		Field not being supported	
DeliveryPointZIP	Mailxml_base:routingZipCodeType	Refer 'routingZipCodeType' simple type	Field not being supported in conjunction with DeliveryContainerID	See Appendix B
Sequence Block ENDS				
Choice Block ENDS				
PieceID	String, 22 characters		Required	
WastedPieceIndicator	mailxml_base:wastedPieceIndicatorType	Refer 'wastedPieceIndicatorType' simple type	Not required	Refer Appendix B
MLOCRrateANDpostageMarking	String, 7 characters	Letters/Flats P1/F1 = Barcoded 1-ounce Permit Imprint P2/F2 = Barcoded 2-ounce Permit Imprint P3/F3 = Barcoded 3-ounce Permit Imprint P4/F4 = Barcoded 4-ounce Permit	Not required	

Copyright © 2011 USPS®. All Rights Reserved.

Mail.XML 9.0B - MailPieceCreateRequest				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
		Imprint /F5 = Barcoded 5-ounce Permit Imprint /F6 = Barcoded 6-ounce Permit Imprint /F7 = Barcoded 7-ounce Permit Imprint /F8 = Barcoded 8-ounce Permit Imprint /F9 = Barcoded 9-ounce Permit Imprint /F0 = Barcoded 10-ounce Permit Imprint /FA = Barcoded 11-ounce Permit Imprint /FB = Barcoded 12-ounce Permit Imprint /FC = Barcoded 13-ounce Permit Imprint 51/MF = Barcoded 5-Digit Meter Postage Affixed – 1 ounce 52/ = Barcoded 5-Digit Meter Postage Affixed – 2 ounces 53/ = Barcoded 5-Digit Meter Postage Affixed – 3 ounces 54/ = Barcoded 5-Digit Meter Postage Affixed – 4 ounces 31/MT = Barcoded 3-Digit Meter Postage Affixed – 1 ounce 32/ = Barcoded 3-Digit Meter Postage Affixed –		

Copyright © 2011 USPS®. All Rights Reserved.

Mail.XML 9.0B - MailPieceCreateRequest				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
		2 ounces 33/ = Barcoded 3-Digit Meter Postage Affixed – 3 ounces 34/ = Barcoded 3-Digit Meter Postage Affixed – 4 ounces A1/MD = Barcoded AADC Meter Postage Affixed – 1 ounce A2/ = Barcoded AADC Meter Postage Affixed – 2 ounces A3/ = Barcoded AADC Meter Postage Affixed – 3 ounces A4/ = Barcoded AADC Meter Postage Affixed – 4 ounces M1/MX = Barcoded Mixed AADC Meter Postage Affixed – 1 ounce M2/ = Barcoded Mixed AADC Meter Postage Affixed – 2 ounces M3/ = Barcoded Mixed AADC Meter Postage Affixed – 3 ounces M4/ = Barcoded Mixed AADC Meter Postage Affixed – 4 ounces 11/ = Presorted Meter Postage Affixed – 1 ounce 12/ = Presorted Meter Postage Affixed – 2		

Copyright © 2011 USPS®. All Rights Reserved.

Mail.XML 9.0B - MailPieceCreateRequest				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
		ounces 13/ = Presorted Meter Postage Affixed – 3 ounces 14/ = Presorted Meter Postage Affixed – 4 ounces S1/ = Precanceled $0.15 Stamp Affixed (card) S2/ = S2 Precanceled $0.25 Stamp Affixed		
MoveComplianceUpdateMethod	mailxml_base:moveUpdateMethodType	Refer 'moveUpdateMethodType' simple type	Not required	Refer Appendix B
MailOwner Block	mailOwnerBlockType	Refer complex type in Appendix C	Optional Block	See Appendix C for Details
BarCodeApplicator Block	ParticipantIDType			See Appendix C for Details
MachineID	String, 4 characters		Optional	
ACSKeyline	String, 16 characters		Optional	
MailPieceBlock Block ends				
MailPieceBlockGroup block ends				
MailXMLPieceRangeBlock Block begins			1 to many can be submitted Either MailPieceBlock or MailXMLPieceRangeBlock submitted	
ContainerID	Char 24		Required 1 to many allowed	
ContainerDetailID	String 9	-	Optional 0 to many allowed	

Copyright © 2011 USPS®. All Rights Reserved.

Mail.XML 9.0B - MailPieceCreateRequest				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
PieceRangeBlock Block begins			Required 1 to many can be submitted	
PieceRangeID	String 22		Required	
IMBarcodeLowerSerialization Block begins			Required Only one can be submitted	
Choice Block BEGINS				
Sequence Block # 1 BEGINS				
MailerID6	mailerID6Type		Required Only one pairing of MailerID and SerialNumber is required If provided, MailerID6 fields must be the same in the IMbarcodeUpperSerialization and IMbarcodeLowerSerialization blocks	Refer Appendix B
SerialNumber9	iMBSerialNumber9Type		Required Only one pairing of MailerID and SerialNumber is required	Refer Appendix B
Sequence Block # 1 ENDS				
Sequence Block # 2 BEGINS				
MailerID9	mailerID9Type		Required Only one pairing of MailerID and SerialNumber is required If provided, MailerID9 fields must be the same in the IMbarcodeUpperSerialization and IMbarcodeLowerSerialization blocks	Refer Appendix B

Copyright © 2011 USPS®. All Rights Reserved.

Mail.XML 9.0B - MailPieceCreateRequest				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
SerialNumber6	iMBSerialNumber6Type		Required Only one pairing of MailerID and SerialNumber is required	Refer Appendix B
Sequence Block # 2 ENDS				
Choice Block ENDS				
IMBarcodeLowerSerialization Block ends				
IMBarcodeUpperSerialization Block begins			Required Only one can be submitted	
Choice Block BEGINS				
Sequence Block BEGINS				
MailerID6	mailerID6Type		Required Only one pairing of MailerID and SerialNumber is required If provided, MailerID6 fields must be the same in the IMbarcodeUpperSerialization and IMbarcodeLowerSerialization blocks	Refer Appendix B
SerialNumber9	iMBSerialNumber9Type		Required Only one pairing of MailerID and SerialNumber is required	
Sequence Block ENDS				
Sequence Block BEGINS				
MailerID9	mailerID9Type		Required Only one pairing of MailerID and SerialNumber is required If provided, MailerID9 fields must be the same in the IMbarcodeUpperSerialization and	Refer Appendix B

Copyright © 2011 USPS®. All Rights Reserved.

Mail.XML 9.0B - MailPieceCreateRequest				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
			IMbarcodeLowerSerialization blocks	
SerialNumber6	iMBSerialNumber6Type		Required Only one pairing of MailerID and SerialNumber is required	
Sequence Block ENDS				
Choice Block ENDS				
IMBarcodeUpperSerialization Block ends				
MailPreparer Block	ParticipantIDType		Conditionally required for Full-Service mailings. If not provided then user will get Full-Service compliance error and no Full-Service data feedback will be available to the mailer.	See Appendix C for Details
MailOwner Block	ParticipantIDType		Conditionally required for Full-Service mailings. If not provided then user will get Full-Service compliance error and no Full-Service data feedback will be available to the mailer.	See Appendix C for Details
Choice Block BEGINS			Required ServiceCode or MailClass	
ServiceTypeCode	serviceTypeCodeType		Conditionally required for Full-Service / Mixed Service mailings if Mail Class is not provided.	Refer Appendix B
MailClass	mailClassType		Conditionally required for Full-	Refer Appendix B

Copyright © 2011 USPS®. All Rights Reserved.

Mail.XML 9.0B - MailPieceCreateRequest				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
			Service / Mixed Service mailings if Service Type Code is not provided.	
Choice Block ENDS				
ServiceLevelIndicator	mailxml_base:serviceLevelIndicatorType	Refer 'serviceLevelIndicatorType' simple type	Required For Full-Service / Mixed Service mailings, the ServiceLevelIndicator field must be populated with 'F' when its associated ContainerID has the ServiceLevelIndicator field in the QualificationReportCreateRequest message populated with 'F'.	Refer Appendix B
Pieces	Non-Negative Integer		Required 1 to many allowed If the FullServiceParticipationIndicator field is populated with a 'F', then the IMbarcodeUpperSerialization block minus the IMbarcodeLowerSerialization block is equal to the piece count and the copy count.	
Copies	Non-Negative Integer		Required 1 to many allowed If the FullServiceParticipationIndicator field is populated with a 'F', then the	

Copyright © 2011 USPS®. All Rights Reserved.

Mail.XML 9.0B - MailPieceCreateRequest				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
			IMbarcodeUpperSerialization block minus the IMbarcodeLowerSerialization block is equal to the piece count and the copy count.	
PieceRangeBlock Block ends				
MailXMLPieceRangeBlock Block ends				
MailXMLLargeTransactionDividerGroupOptionalType block begins			Not currently supported	
MessageGroupID	String 20		Not currently supported	
TotalMessageCount	Positive Integer		Not currently supported	
MessageSerialNumber	Positive Integer		Not currently supported	
TransmittedRecordCount	Positive Integer		Not currently supported	
TotalRecordsAcrossMessages	Positive Integer		Not currently supported	
LastMessage	Yes/No	Yes No	Not currently supported	
MailXMLLargeTransactionDividerGroupOptionalType block ends			Not currently supported	
MailXMLHeaderInfo block begins				
CustomerGroupID	String 25		Optional	
MailingGroupID	nonNegativeInteger		Optional	
MaildatJobID			Optional	
UserLicenceCode			Optional	
MailXMLHeaderInfo block ends				
MailPieceCreateRequest Message ENDS				

2.2.14 - MailPieceCreateRequest

Copyright © 2011 USPS®. All Rights Reserved.

3.30 MailPieceCreateResponse

Purpose
Accept or reject a request to create a mailpiece or piece range

Error/Return Codes
Refer Section 2.6 to view shared error/return codes and also a list of error/return codes tied this message.

Business Rules
- Will accept if all required fields are populated and values are valid
- Will reject if all required fields are not populated
- Will reject if invalid values are provided
- Will reject if FullServiceParticipationIndicator is NOT F for Full-Service or M for Mixed Service
- Mail Pieces and piece ranges for a specified MailingGroupID and CustomerGroupID must have an accepted QualificationReportCreateRequest and BundleDetailCreatRequest
- The ReturnInfo block will have a description for rejection

3.30.1 MailPieceCreateResponse

Field Description

Mail.XML 9.0B - MailPieceCreateResponse				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
MailPieceCreateAccept Block begins			Block received upon accepting request 1 to many can be submitted	
MailXMLHeaderInfo block begins				
CustomerGroupID	String 25		Optional	
MailingGroupId	nonNegative Integer		Optional	
MaildatJobID			Optional	
UserLicenseCode			Optional	
MailXMLHeaderInfo block ends				
ReturnInfo Block	ReturnInfo		Optional	See Appendix A for Details
MailPieceCreateAccept Block ends				
MailPieceCreateReject Block begins			Block received upon rejecting request Only one can be submitted	
MailXMLHeaderInfo block begins				

Copyright © 2011 USPS®. All Rights Reserved.

Mail.XML 9.0B - MailPieceCreateResponse				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
CustomerGroupID	String 25		Optional	
MailingGroupId	nonNegative Integer		Optional	
MaildatJobID			Optional	
UserLicenseCode			Optional	
MailXMLHeaderInfo block ends				
ReturnInfo Block	ReturnInfo		Required	See Appendix A for Details
MailPieceCreateReject Block ends				

2.2.15 - MailPieceCreateResponse

3.31 MailPieceUpdateRequest

Purpose
Used to update a previously created mailpiece or piece range

Business Rules

- Must be submitted to a currently existing mailpiece or piece range
- MailingGroupID and CustomerGroupID must exist for an open mailing
- The MailPieceBlock for the MailPieceUpdateRequest and MailPieceCreateRequest must be the same for the specified MailingGroupID and CustomerGroupID
- The MailXMLPieceRangeBlock for the MailPieceUpdateRequest and MailPieceCreateRequest must be the same for the specified MailingGroupID and CustomerGroupID
- Cannot update a mailpiece if the 'W' or 'S' indicators for WastedPieceIndicator have resulted in adjusting an already finalized postage statement
- Cannot update a mailpiece or piece range if postage has been finalized on its corresponding container
- Beginning in Release 26.0.0, the MailPieceUpdateRequest messages will be rejected where the sum of the MailXMLPieceRangeBlock IMbarcodeUpperSerialization minus the MailXMLPieceRangeBlocks IMbarcodeLowerSerialization plus 1 (one) for all Full-Service blocks within the mailing group is either:
    - 20% or more greater than the larger of either (1) the sum of the Pieces field for all full-service PieceRangeBlocks or (2) the sum of Copies field for all full-service PieceRangeBlocks, or
    - Less than the smaller of either (1) the sum of the Pieces field for all full-service PieceRangeBlocks or (2) the sum of Copies field for all full-service PieceRangeBlocks
- Beginning in Release 28.0.0, the ContainerDetailID field in the MailXMLPieceRange block will not be accepted.

3.31.1 MailPieceUpdateRequest

Field Description

Mail.XML 9.0B - MailPieceUpdateRequest

Copyright © 2011 USPS®. All Rights Reserved.

Field	Format	Acceptable Values	Business Rules	Comments
MailPieceUpdateRequest Message BEGINS				
SubmittingParty Block	ParticipantIDType		Required block; Identifies the customer submitting the message	Refer 'ParticipantID Type' complex type in Appendix C.
SubmittingSoftware Block	SubmittingSoftwareType		Required block; Identifies the software submitting the message	Refer 'SubmittingSoftware' complex type in Appendix C.
UserLicenseCode	Mailxml_base:userLicenseCodeType		Field not being supported	Refer Appendix B
MaildatJobID	Mailxml_base:jobIDType		Field not being supported	Refer Appendix B
TransmittedCount	nonNegative Integer		Optional	
Choice Block BEGINS			Either PDRMailPIeceBlock or PDRRangePieceBlock	Currently this block is not supported.
PDRMailPieceBlock			Block not being supported	
PDRRangePieceBlock			Block not being supported	
Choice Block ENDS				
CustomerGroupID	String, 25 characters		Required field; must be populated with the same value as the CustomerGroupID in the QualificationReport CreateResponse message	
MailingGroupID	Non-negative Integer		Required field; must be populated with the same value as the MailingGroupID in the	

Copyright © 2011 USPS®. All Rights Reserved.

Mail.XML 9.0B - MailPieceUpdateRequest				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
			QualificationReport CreateResponse message	
TransmittedCount	Non-negative Integer		Optional Count of records transmitted in message	
Choice Block BEGINS			Either MailPieceBlockGroup or MailXMLPieceRangeBlock	
MailPieceBlockGroup block BEGINS				
ContainerID	String 6		Required	
ContainerDetailID	String 9		Optional. Links Qual, Postage, and Mailpiece data	-
BundleID	String 12		Optional	
MailPieceBlock Block begins			1 to many can be submitted Either MailPieceBlock or MailXMLPieceRangeBlock submitted	
ServiceLevelIndicator	mailxml_base:serviceLevelIndicatorType	Refer 'serviceLevelIndicatorType' simple type	Required For Full-Service / Mixed Service mailings, the ServiceLevelIndicator field must be populated with 'F' when its associated ContainerID has the ServiceLevelIndicator field in the QualificationReport CreateRequest message populated with 'F'.	Refer Appendix B
Choice Block BEGINS			OPTIONAL.	-

Copyright © 2011 USPS®. All Rights Reserved.

Mail.XML 9.0B - MailPieceUpdateRequest				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
			If provided then e ither LOTSequence Data or WalkSequence data should be provided.	
Sequence Block BEGINS				
LOTSequenceDirectionCod e	String, 1 character		Either WalkSequenceNu mber or combination of LOTSequenceDirec tionCode and LOTSequenceNum ber should be provided.	
LOTSequenceNumber	Number, 4 characters		Either WalkSequenceNu mber or combination of LOTSequenceDirec tionCode and LOTSequenceNum ber should be provided	
Sequence Block ENDS				
WalkSequenceNumber	Number, 5 characters		Either WalkSequenceNu mber or combination of LOTSequenceDirec tionCode and LOTSequenceNum ber	
Choice Block ENDS				
Choice Block BEGINS			Optional Either IMB or PlantCode with DeliveryPointZip OR DeliveryCOntainerI D with DeliveryPointZip is required, if this	

Copyright © 2011 USPS®. All Rights Reserved.

Mail.XML 9.0B - MailPieceUpdateRequest				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
			choice block is used.	
IMB Block	IntelligentMailBarcodeType	This is a complex type	Required Block. Only one occurrence is allowed	See Appendix C for Details
Sequence Block BEGINS				
PlanetCode	mailxml_base:planetCodeType	Refer 'planetCodeType' simple type	Not required	Refer appendix B
DeliveryPointZIP	Mailxml_base:routingZipCodeType	Refer 'routingZipCodeType' simple type	Conditionally required if PlanetCode is submitted	See Appendix B
Sequence Block ENDS				
Sequence Block BEGINS				
DeliveryContainerID	Numeric string, 22 characters		Field not being supported	
DeliveryPointZIP	Mailxml_base:routingZipCodeType	Refer 'routingZipCodeType' simple type	Field not being supported in conjunction with DeliveryContainerID	See Appendix B
Seuqnce Block ENDS				
Choice Block ENDS				
PieceID	String, 22 characters		Required	
WastedPieceIndicator	mailxml_base:wastedPieceIndicatorType	Refer 'wastedPieceIndicatorType' simple type	Not required	Refer Appendix B
MLOCRrateANDpostageMarking	String, 7 characters	Letters/Flats P1/F1 = Barcoded 1-ounce Permit Imprint P2/F2 = Barcoded 2-ounce Permit Imprint P3/F3 = Barcoded 3-ounce Permit Imprint P4/F4 =	Not required	

Copyright © 2011 USPS®. All Rights Reserved.

Mail.XML 9.0B - MailPieceUpdateRequest				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
		Barcoded 4-ounce Permit Imprint /F5 = Barcoded 5-ounce Permit Imprint /F6 = Barcoded 6-ounce Permit Imprint /F7 = Barcoded 7-ounce Permit Imprint /F8 = Barcoded 8-ounce Permit Imprint /F9 = Barcoded 9-ounce Permit Imprint /F0 = Barcoded 10-ounce Permit Imprint /FA = Barcoded 11-ounce Permit Imprint /FB = Barcoded 12-ounce Permit Imprint /FC = Barcoded 13-ounce Permit Imprint 51/MF = Barcoded 5-Digit Meter Postage Affixed – 1 ounce 52/ = Barcoded 5-Digit Meter Postage Affixed – 2 ounces 53/ = Barcoded 5-Digit Meter Postage Affixed – 3 ounces 54/ = Barcoded 5-Digit Meter Postage Affixed – 4 ounces 31/MT = Barcoded 3-Digit Meter Postage Affixed – 1 ounce 32/ = Barcoded		

Copyright © 2011 USPS®. All Rights Reserved.

Mail.XML 9.0B - MailPieceUpdateRequest				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
		3-Digit Meter Postage Affixed – 2 ounces 33/ = Barcoded 3-Digit Meter Postage Affixed – 3 ounces 34/ = Barcoded 3-Digit Meter Postage Affixed – 4 ounces A1/MD = Barcoded AADC Meter Postage Affixed – 1 ounce A2/ = Barcoded AADC Meter Postage Affixed – 2 ounces A3/ = Barcoded AADC Meter Postage Affixed – 3 ounces A4/ = Barcoded AADC Meter Postage Affixed – 4 ounces M1/MX = Barcoded Mixed AADC Meter Postage Affixed – 1 ounce M2/ = Barcoded Mixed AADC Meter Postage Affixed – 2 ounces M3/ = Barcoded Mixed AADC Meter Postage Affixed – 3 ounces M4/ = Barcoded Mixed AADC Meter Postage Affixed – 4 ounces 11/ = Presorted Meter Postage Affixed – 1 ounce 12/ = Presorted		

Copyright © 2011 USPS®. All Rights Reserved.

Mail.XML 9.0B - MailPieceUpdateRequest				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
		Meter Postage Affixed – 2 ounces 13/ = Presorted Meter Postage Affixed – 3 ounces 14/ = Presorted Meter Postage Affixed – 4 ounces S1/ = Precanceled $0.15 Stamp Affixed (card) S2/ = S2 Precanceled $0.25 Stamp Affixed		
MoveComplianceUpdateMethod	mailxml_base:moveUpdateMethodType	Refer 'moveUpdateMethodType' simple type	Not required	Refer Appendix B
MailOwner Block	mailOwnerBlockType	Refer complex type in Appendix C	Optional Block	See Appendix C for Details
BarCodeApplicator Block	ParticipantIDType			See Appendix C for Details
MachineID	String, 4 characters		Optional	
ACSKeyline	String, 16 characters		Optional	
MailPieceBlock Block ends				
MailPieceBlockGroup block ends				
MailXMLPieceRangeBlock Block begins			1 to many can be submitted Either MailPieceBlock or MailXMLPieceRangeBlock submitted	
ContainerID	Char 24		Required 1 to many allowed	

Copyright © 2011 USPS®. All Rights Reserved.

Mail.XML 9.0B - MailPieceUpdateRequest				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
ContainerDetailID	String 9	-	Optional 0 to many allowed	
PieceRangeBlock Block begins			Required 1 to many can be submitted	
PieceRangeID	String 22		Required	
IMBarcodeLowerSerialization Block begins			Required Only one can be submitted	
Choice Block BEGINS				
Sequence Block # 1 BEGINS				
MailerID6	mailerID6Type		Required Only one pairing of MailerID and SerialNumber is required If provided, MailerID6 fields must be the same in the IMbarcodeUpperSerialization and IMbarcodeLowerSerialization blocks	Refer Appendix B
SerialNumber9	iMBSerialNumber9Type		Required Only one pairing of MailerID and SerialNumber is required	Refer Appendix B
Sequence Block # 1 ENDS				
Sequence Block # 2 BEGINS				
MailerID9	mailerID9Type		Required Only one pairing of MailerID and SerialNumber is required If provided, MailerID9 fields must be the same in the IMbarcodeUpperSerialization and	Refer Appendix B

Copyright © 2011 USPS®. All Rights Reserved.

Mail.XML 9.0B - MailPieceUpdateRequest				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
			IMbarcodeLowerSerialization blocks	
SerialNumber6	iMBSerialNumber6Type		Required Only one pairing of MailerID and SerialNumber is required	Refer Appendix B
Sequence Block # 2 ENDS				
Choice Block ENDS				
IMBarcodeLowerSerialization Block ends				
IMBarcodeUpperSerialization Block begins			Required Only one can be submitted	
Choice Block BEGINS				
Sequence Block BEGINS				
MailerID6	mailerID6Type		Required Only one pairing of MailerID and SerialNumber is required If provided, MailerID6 fields must be the same in the IMbarcodeUpperSerialization and IMbarcodeLowerSerialization blocks	Refer Appendix B
SerialNumber9	iMBSerialNumber9Type		Required Only one pairing of MailerID and SerialNumber is required	
Sequence Block ENDS				
Sequence Block BEGINS				
MailerID9	mailerID9Type		Required Only one pairing of MailerID and SerialNumber is required If provided, MailerID9 fields must be the same in the	Refer Appendix B

Copyright © 2011 USPS®. All Rights Reserved.

Mail.XML 9.0B - MailPieceUpdateRequest				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
			IMbarcodeUpperSerialization and IMbarcodeLowerSerialization blocks	
SerialNumber6	iMBSerialNumber6Type		Required Only one pairing of MailerID and SerialNumber is required	
Sequence Block ENDS				
Choice Block ENDS				
IMBarcodeUpperSerialization Block ends				
MailPreparer Block	ParticipantIDType		Conditionally required for Full-Service mailings. If not provided then user will get Full-Service compliance error and no Full-Service data feedback will be available to the mailer.	See Appendix C for Details
MailOwner Block	ParticipantIDType		Conditionally required for Full-Service mailings. If not provided then user will get Full-Service compliance error and no Full-Service data feedback will be available to the mailer.	See Appendix C for Details
Choice Block BEGINS			Required ServiceCode or MailClass	
ServiceTypeCode	serviceTypeCodeType		Conditionally required for Full-Service / Mixed Service mailings if Mail Class is not provided.	Refer Appendix B

Copyright © 2011 USPS®. All Rights Reserved.

Mail.XML 9.0B - MailPieceUpdateRequest				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
MailClass	mailClassType		Conditionally required for Full-Service / Mixed Service mailings if Service Type Code is not provided.	Refer Appendix B
Choice Block ENDS				
ServiceLevelIndicator	mailxml_base:serviceLevelIndicatorType	Refer 'serviceLevelIndicatorType' simple type	Required For Full-Service / Mixed Service mailings, the ServiceLevelIndicator field must be populated with 'F' when its associated ContainerID has the ServiceLevelIndicator field in the QualificationReportCreateRequest message populated with 'F'.	Refer Appendix B
Pieces	Non-Negative Integer		Required 1 to many allowed If the FullServiceParticipationIndicator field is populated with a 'F', then the IMbarcodeUpperSerialization block minus the IMbarcodeLowerSerialization block is equal to the piece count and the copy count.	
Copies	Non-Negative Integer		Required 1 to many allowed If the FullServiceParticipationIndicator field is	

Copyright © 2011 USPS®. All Rights Reserved.

Mail.XML 9.0B - MailPieceUpdateRequest				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
			populated with a 'F', then the IMbarcodeUpperSerialization block minus the IMbarcodeLowerSerialization block is equal to the piece count and the copy count.	
PieceRangeBlock Block ends				
MailXMLPieceRangeBlock Block ends				
MailXMLHeaderInfo block begins				
CustomerGroupID	String 25		Optional	
MailingGroupID	nonNegativeInteger		Optional	
MaildatJobID	Mailxml_base:jobIDType		Optional	Refer Appendix B
UserLicenceCode	Mailxml_base:userLicenseCodeType		Optional	Refer Appendix B
MailXMLHeaderInfo block ends				

2.2.16 - MailPieceUpdateRequest

3.32 MailPieceUpdateResponse

Purpose
Accept or reject a request to update a mailpiece or piece range

Error/Return Codes
Refer Section 2.6 to view shared error/return codes and also a list of error/return codes tied this message.

Business Rules
- Will accept if the mailpiece or piece range exists
- Will accept if postage statement is USPS Processing Due
- Will reject if the mailpiece or piece range does not exist

Copyright © 2011 USPS®. All Rights Reserved.

- Will reject if a mailpiece 'W' or 'S' indicators for WastedPieceIndicator have resulted in adjusting an already finalized postage statement
- Will reject if postage statement is finalized or finalized pending payment on the mailpiece or piece range's corresponding container
- The ReturnInfo block will have a description for rejection

3.32.1 MailPieceUpdateResponse

Field Description

Mail.XML 9.0B - MailPieceUpdateResponse				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
MailPieceCreateAccept Block begins			Block received upon accepting request 1 to many can be submitted	
MailXMLHeaderInfo block begins				
CustomerGroupID	String 25		Optional	
MailingGroupID	nonNegative Integer		Optional	
MaildatJobID			Optional	
UserLicenseCode			Optional	
MailXMLHeaderInfo block ends				
ReturnInfo Block	ReturnInfo		Optional	See Appendix A for Details
MailPieceCreateAccept Block ends				
MailPieceCreateReject Block begins			Block received upon rejecting request 1 to many can be submitted	
MailXMLHeaderInfo block begins				
CustomerGroupID	String 25		Optional	
MailingGroupID	nonNegative Integer		Optional	
MaildatJobID			Optional	
UserLicenseCode			Optional	
MailXMLHeaderInfo block begins				
ReturnInfo Block	ReturnInfo		Required	See Appendix A for Details

Copyright © 2011 USPS®. All Rights Reserved.

Mail.XML 9.0B - MailPieceUpdateResponse				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
MailPieceCreateReject Block ends				

2.2.17 - MailPieceUpdateResponse

3.33 OpenMailingGroupRequest

Purpose
Allows USPS customers to create mailing groups to submit qualification report, mailpiece, and postage statement information.

Business Rules

- Must be submitted before all other messages for eDoc with the exception of SiblingContainerCreate or ContainerUpdate message
- Multiple mailing groups can be opened for a distinct SubmitterCRID, Permit Number or Publication Number, PostOfficeOfMailingZip, MailingFacility, and MailXMLPresentationCategory
- The dashboard will not display empty mailing groups
- Letters and Flats can both be part of the same mailing group but both require separate postage statements by shape.

3.33.1 OpenMailingGroupRequest

Field Description

Mail.XML 9.0B - OpenMailingGroupRequest				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
MailXMLOpenMailGroupRequestHeaderInfo Block begins			Attributes block	
CustomerGroupID	String, 25 characters		Required (attribute)	This is a user/customer identified sequence number that should be tracked internally by customer software.
MailXMLOpenMailGroupRequestHeaderInfo Block ends				
SubmittingParty Block	ParticipantIDType		Required block; Identifies the customer submitting the message	Refer 'ParticipantID Type' complex type in Appendix E.

Copyright © 2011 USPS®. All Rights Reserved.

Mail.XML 9.0B - OpenMailingGroupRequest				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
SubmittingSoftware Block	SubmittingSoftwareType		Required block; Identifies the software submitting the message	Refer 'SubmittingSoftware' complex type in Appendix E.
MailingGroupData Block begins			Provides the basic information for the mailing group Only one must be submitted with OpenMailingGroup Request message	
CustomerDescription	String, 50 characters		Not required	
SubmitterCRID	String, 10 characters		Required	
PermitPublicationData Block	PermitPublicationDataType			See Appendix A for Details
PostOfficeOfMailingZip	String, 5 characters		Required	
MailingFacility	String, 10 characters		Conditionally required for a Full-Service/Mixed Service mailing	
MailXmlPresentationCategory	mailxml_base:mailXMLPresentationCategoryType	Refer 'mailXMLPresentationCategoryType' simple type	Required	Refer Appendix B
MailerID	String, 9 characters		Not required	
FullServiceParticipationIndicator	mailxml_base:fspiType	Refer 'fspiType' simple type	Conditionally required for Full-Service/Mixed Service mailing; <BLANK> field is invalid	Refer Appendix B
MailAgreementType	mailxml_base:mailAgreementTypeType	Refer 'mailAgreementTypeType' simple type	Not required	Refer Appendix B
ContractNumber	String, 20 characters		Not required	
OnePassIndicator	Boolean	Yes/No	Conditionally required when MailXMLPresentationCategory is 'M'	
LogicalPhysicalContainerIndicator	mailxml_base:logicalPhysicalConta	Refer 'logicalPhysicalC	Conditionally required for a Full-	Refer Appendix B

Copyright © 2011 USPS®. All Rights Reserved.

Mail.XML 9.0B - OpenMailingGroupRequest				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
	inerIndicatorType	ontainerIndicator Type' simple type	Service/Mixed Service mailing	
MailingGroupData Block ends				

2.2.18 - OpenMailingGroupRequest

3.34 OpenMailingGroupResponse

Purpose
The OpenMailingGroupResponse will be used by USPS to notify the customer if their request to open a mailing group has been accepted or rejected.

Error/Return Codes

Refer Section 2.6 to view shared error/return codes, Cross message validations, and a list of error/return codes tied this message.

Business Rules

- Will reject if invalid values are provided in the request
- Will reject if MailingGroupData required data does not exist in database
- The ReturnInfo block will have a description for rejection

3.34.1 OpenMailingGroupResponse

Field Description

Mail.XML 9.0B - OpenMailingGroupResponse				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
OpenMailingGroupAccept Block begins			Block received upon accepting request	
MailXMLOpenMailGroupRe sponseHeaderInfo Block begins			Attributes block	
CustomerGroupID	String, 25 characters		Required (attribute)	
MailingGroupID	Non-negative Integer		Required (attribute)	
Status	mailxml_base:sta tusType	Refer 'statusType' simple type	Not required (attribute)	Refer Appendix B

Copyright © 2011 USPS®. All Rights Reserved.

Mail.XML 9.0B - OpenMailingGroupResponse				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
MailXMLOpenMailGroupResponseHeaderInfo Block ends				
ReturnInfo Block	ReturnInfo			See Appendix A for Details
OpenMailingGroupAccept Block ends				
OpenMailingGroupReject Block begins			Block received upon rejecting request	
MailXMLOpenMailGroupResponseHeaderInfo Block ends				
CustomerGroupID	String, 25 characters		Required (attribute)	
MailingGroupID	Non-negative Integer		Not required (attribute)	
Status	mailxml_base:statusType	Refer 'statusType' simple type	Not required (attribute)	Refer Appendix B
PostOfficeMailingZip	String Exactly 5		Required	
ReturnInfo Block	ReturnInfo			See Appendix A for Details
MailXMLOpenMailGroupResponseHeaderInfo Block ends				
OpenMailingGroupReject Block ends				

2.2.19 - OpenMailingGroupResponse

3.35 OriginalContainerLinkageCancelRequest

Purpose
Used to cancel an existing Container Linkage

Copyright © 2011 USPS®. All Rights Reserved.

Business Rules

- MailingGroupID and CustomerGroupID must exist for an open mailing group
- OriginalContainerLinkageCreateRequest message must be accepted before submitting the OriginalContainerLinkageCancelRequest for the specified MailingGroupID and CustomerGroupID
- Original container and linked container must be on a postage statement with PostageStatementStatus populated with UPD and not undergoing finalization
- Original container submitted through Mail.dat before Ready to Pay status
- Original container submitted through Mail.XML before Ready to Pay status
- Linked container submitted through Mail.dat before Ready to Pay status
- Linked container created through Mail.XML must be on a postage statement with PostageStatementStatus populated with UPD for USPS Processing Due for the specified MailingGroupID
- Cannot cancel linked containers for Bundle-Based Co-Palletization after postage statement finalization
- Cannot cancel linked containers for Tray-Based Co-Palletization after OriginalContainerLinkageCreateRequest has been accepted

3.35.1 OriginalContainerLinkageCancelRequest

Field Description

Mail.XML 9.0B - OriginalContainerLinkageCancelRequest				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
OriginalContainerLinkageCreateHeaderInfo block begins			Attributes block	
CustomerGroupID	String, 25 characters		Required field	
MailingGroupID	Non-Negative integer		Required field	
OriginalContainerLinkageCreateHeaderInfo block ends				
SubmittingParty Block	ParticipantIDType		Required block; Identifies the customer submitting the message	Refer 'ParticipantID Type' complex type in Appendix E.
SubmittingSoftware Block	SubmittingSoftwareType		Required block; Identifies the software submitting the message	Refer 'SubmittingSoftware' complex type in Appendix E.
CancelLinkage Block	LinkageType		Required field;	See Appendix E for Details

Copyright © 2011 USPS®. All Rights Reserved.

2.2.20 - OriginalContainerLinkageCancelRequest

3.36 OriginalContainerLinkageCancelResponse

Purpose
Accept or reject a request to cancel a Container Linkage

Error/Return Codes
Refer Section 2.6 to view shared error/return codes and also a list of error/return codes tied this message.

Business Rules

- The ReturnInfo block will have a description for rejection
- Original container created through Mail.dat must exist within the database for the specified UserLicenseCode, MaildatJobID, ContainerID, and UniqueContainerBarcode
- Original Container created through Mail.XML must exist within the database for the specified MailingGroupID and CustomerGroupID
- Linkage created through Mail.XML must exist within the database for the specified MailingGroupID and CustomerGroupID

3.36.1 OriginalContainerLinkageCancelResponse

Field Description

Mail.XML 9.0B - OriginalContainerLinkageCancelResponse				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
OriginalContainerLinkageCancelAccept block begins			Response from USPS indicating that the OriginalContainerLinkageCancelRequest message was accepted	
OriginalContainerLinkageHeaderInfo block begins			Attributes block	
CustomerGroupID	String, 25 characters		Required field; must be populated with the same value as the CustomerGroupID in the OriginalContainerLinkageCreateRequest message	
MailingGroupID	Non-Negative integer		Required field; must be populated with the same value as the MailingGroupID in the OriginalContainerLinkageCreateReque	

Copyright © 2011 USPS®. All Rights Reserved.

Mail.XML 9.0B - OriginalContainerLinkageCancelResponse				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
			st message	
OriginalContainerLinkageHeaderInfo block ends				
CancelLinkage Block	LinkageType		Required field;	See Appendix A for Details
OriginalContainerLinkageCancelAccept block ends				
OriginalContainerLinkageCancelReject block begins			Response from USPS indicating that the OriginalContainerLinkageCancelRequest message was rejected	
OriginalContainerLinkageHeaderInfo block begins			Attributes block	
CustomerGroupID	String, 25 characters		Required field; must be populated with the same value as the CustomerGroupID in the OriginalContainerLinkageCreateRequest message	
MailingGroupID	Non-Negative integer		Required field; must be populated with the same value as the MailingGroupID in the OriginalContainerLinkageCreateRequest message	
OriginalContainerLinkageHeaderInfo block ends				
CancelLinkage Block	LinkageType		Required field;	See Appendix A for Details
ReturnInfo Block	ReturnInfo		Required field;	See Appendix A for Details
OriginalContainerLinkageCancelReject block ends				

2.2.21 - OriginalContainerLinkageCancelResponse

Copyright © 2011 USPS®. All Rights Reserved.

3.37 OriginalContainerLinkageCreateRequest

Purpose
Used to create a co-palletized container relationship

Business Rules

- Only one OriginalContainer block can be linked to only one LinkedContainer block
- MailingGroupID and CustomerGroupID must exist for an open mailing group
- QualificationReportCreateRequest message must be accepted before submitting the OriginalContainerLinkageCreateRequest message for the specified MailingGroupID and CustomerGroupID
- FormType in the ContainerInfoData block within the QualificationReport block in the QualificationReportCreateRequest message must be populated with FC for First Class, SM for Standard Mail, and PE for Periodicals and Pending Periodicals to link a Mail.XML container through the OriginalContainerLinkageCreateRequest message
- Class from the .mpu file must be populated with 1 for First Class, 2 for Periodicals, 3 for Standard Mail, 5 for Pending Periodicals to link a Mail.dat container through OriginalContainerLinkageCreateRequest message
- Mail Class must be same across a Co-Palletized mailing.
- IncludedInOtherDoc field within the ContainerInfoData block in the QualificationReport block in the QualificationReportCreateRequest message must be populated with O for Original or L for Linked to link a Mail.XML container through the OriginalContainerLinkageCreateRequest message
- Included In Other Documentation field in the .csm file must be populated with O for Original or L for Linked to link a Mail.dat container through the OriginalContainerLinkageCreateRequest message
- Original Container submitted through Mail.XML can be linked to a MailXMLContainer through the OriginalContainerLinkageCreateRequest message
- Original Container submitted through Mail.dat can be linked to a MailXMLContainer through the OriginalContainerLinkageCreateRequest message
    - Users are allowed to submit origin files through either form of eDocumentation (Mail.dat and Mail.XML) for a single consolidated mailing to be submitted with consolidator's Mail.XML file. One option is all origin files are submitted via Mail.dat and the consolidator submits a Mail.XML file for the consolidated job. Another option is some origin files submitted via Mail.dat and other origin files submitted via Mail.XML and the consolidator submits a Mail.XML file for the consolidated job. A consolidator can combine Mail.dat origin containers with Mail.XML origin containers onto the same pallet. In this case, the Consolidator's OriginalContainerLinkageCreateRequest message shall contain both OriginalContainer, MaildatContainer blocks and OriginalContainer, MailXMLContainer blocks which will reference the origin mailings that were previously submitted.

- OriginalContainerLinkageCreateRequest message cannot link Mail.dat container to an original container submitted through Mail.dat or Mail.XML container
- It is strongly recommended to use OriginalContainerLinkageCreateRequest message whenever Copalletizing the mail even when the mailing is a non full-service mailing.
- When Copalletizing Full-Service mailings then this message is required.
- OriginalContainerID, OriginalMailingGroup, and OriginalJobID cannot have been previously linked to a consolidator MailingGroupID
- ContainerID in the OriginalContainer block must be associated to a finalized postage statement for Tray-Based Co-Palletization
- Presentation Category must be the same between the original and linked containers
- Service Level for the linked container cannot be higher than the original container

Copyright © 2011 USPS®. All Rights Reserved.

3.37.1 OriginalContainerLinkageCreateRequest

Field Description

Mail.XML 9.0B - OriginalContainerLinkageCreateRequest				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
OriginalContainerLinkageCreateHeaderInfo block begins			Attributes block	
CustomerGroupID	String, 25 characters		Required field	
MailingGroupID	Non-Negative integer		Required field	
OriginalContainerLinkageCreateHeaderInfo block ends				
SubmittingParty Block	ParticipantIDType		Required block; Identifies the customer submitting the message	Refer 'ParticipantID Type' complex type in Appendix E.
SubmittingSoftware Block	SubmittingSoftwareType		Required block; Identifies the software submitting the message	Refer 'SubmittingSoftware' complex type in Appendix E.
CreateLinkage Block	LinkageType		Required field;	See Appendix E for Details

2.2.22 - OriginalContainerLinkageCreateRequest

3.38 OriginalContainerLinkageCreateResponse

Purpose
Accept or reject a request Container Linkage request

Error/Return Codes

Refer Section 2.6 to view shared error/return codes and also a list of error/return codes tied this message.

Business Rules

- The ReturnInfo block will have a description for rejection
- Response – Original Container for the specified UserLicenseCode, MaildatJobID, ContainerID, and UniqueContainerBarcode must exist in the database if submitted through Mail.dat
- Response – Original Container for the specified MailingGroupID and CustomerGroupID must exist in the database if submitted through Mail.XML

Copyright © 2011 USPS®. All Rights Reserved.

3.38.1 OriginalContainerLinkageCreateResponse

Field Description

Mail.XML 9.0B - OriginalContainerLinkageCreateResponse				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
LinkedContainerCreateAccept Block begins			Response from USPS indicating that the OriginalConatinerLinkageCreateRequest message was accepted	
OriginalContainerLinkageHeaderInfo block begins			Attributes block	
CustomerGroupID	String, 25 characters		Required field; must be populated with the same value as the CustomerGroupID in the OriginalContainerLinkageCreateRequest message	
MailingGroupID	Non-Negative integer		Required field; must be populated with the same value as the MailingGroupID in the OriginalContainerLinkageCreateRequest message	
OriginalContainerLinkageHeaderInfo block ends				
LinkageCreated Block	LinkageType		Required field;	See Appendix E for Details
ReturnInfo Block	ReturnInfo		Required field;	See Appendix A for Details
LinkedContainerCreateAccept block ends				
LinkedContainerCreateReject			Response from USPS indicating that the OriginalConatinerLinkageCreateRequest message was rejected	
OriginalContainerLinkageCreateHeaderInfo			Attributes block	
CustomerGroupID	String, 25		Required field	

Copyright © 2011 USPS®. All Rights Reserved.

Mail.XML 9.0B - OriginalContainerLinkageCreateResponse				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
	characters			
MailingGroupID	Non-Negative integer		Required field	
OriginalContainerLinkageCreateHeaderInfo				
LinkageRejected Block	LinkageType		Required field	See Appendix E for Details
ReturnInfo Block	ReturnInfo		Required field	See Appendix A for Details
LinkedContainerCreateReject block ends				

2.2.23 - OriginalContainerLinkageCreateResponse

3.39 PaymentMessageQueryRequest

After paying for postage, send the PaymentMessageQueryRequest. The request requires the Statement ID, tracking ID, mailing and Customer group ID besides the submitting party and submitting software.

3.39.1 PaymentMessageQueryRequest Data Structure

Field Description

Mail.XML 9.0B - PaymentMessageQueryRequest				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
SubmittingParty	ParticipantIDType		Identifies the customer submitting the message	Refer 'ParticipantID Type' complex type in Appendix D.
SubmittingSoftware	SubmittingSoftwareType		Identifies the software submitting the message	Refer 'SubmittingSoftware' complex type in Appendix D.
PostageMessageHeaderInfo block Opens				
CustomerGroupID	String, 25 characters		Required (attribute)	
MailingGroupID	Non Negative Integer		Required (attribute)	
PostageMessageHeaderInfo block Closes				

Copyright © 2011 USPS®. All Rights Reserved.

2.2.24 - PaymentMessageQueryRequest

3.40 PaymentMessageQueryResponse

PaymentMessageQueryResponse includes a QueryResponseResponse and a QueryError block. The QueryResponse includes Postage statement data blocks for postage statement(s). Each Postage statement data block includes PostageStatementTransactionNumber, CustomerReferenceTransactionNumber, MailingFacility, PostageAmountPaid, DateOfTransaction, and TimeOfTransaction. Both messages include ReturnInfo.

3.40.1 PaymentMessageQueryResponse Data Structure

Field Description

Mail.XML 9.0B - PaymentMessageQueryResponse				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
PostageMessageHeaderInfo block Opens				
CustomerGroupID	String, 25 characters		Required (attribute)	
MailingGroupID	Non Negative Integer		Required (attribute)	
PostageMessageHeaderInfo block Closes				
QueryResults Block Opens				
PaymentMessage Block Opens				
PostageStatementTransactionNumber	String		Optional	
CustomerReferenceTransactionNumber	String		Optional	
MailingFacility	String		Optional	
PostageAmountPaid	Double		Optional	
DateOfTransaction	Date	YYYY-MM-DD	Optional	
TimeOfTransaction	Time	HH:MM:SS	Optional	
PaymentMessage Block Closes				
ReturnInfo	ReturnInfo		Required	Refer 'ReturnInfo' complex type in Appendix D.
QueryResults Block Closes				
QueryError Block Opens				
ReturnInfo	ReturnInfo		Required	Refer 'ReturnInfo' complex type in Appendix D.

Copyright © 2011 USPS®. All Rights Reserved.

Mail.XML 9.0B - PaymentMessageQueryResponse				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
QueryError Block Closes				

2.2.25 - PaymentMessageQueryResponse

3.41 PeriodicalStatementCreateRequest

Purpose
Allows the USPS customer to submit a Periodicals postage statement to a mailing group

Business Rules

- Mail owner or preparer must send the OpenMailingGroupRequest message and open a mailing group successfully (receive a MailingGroupID) in an acceptance message before sending this message
- Mail owner or preparer must send the QualificationReportCreateRequest message and receive an accepted response that the mailing is qualified before sending this message
- Mail owner or preparer must send the ContainerBundleReportCreateRequest message and receive an accept response before sending this message
- Mail owner or preparer must send this message before sending the ConsolidatedPeriodicalStatementRequest message
- For full-service or mixed service mailings, there are two options for how to populate the required container information:
    - PeriodicalLineItemData block
        - Include one PeriodicalLineItemData block for each container represented on each line of the postage statement. The container IDs must match an ID of a container from a previously submitted qualification report.
        - Do not include ContainerPostage block. If provided, it will be ignored.
    - ContainerPostage block
        - All containers are represented in the ContainerPostage blocks with the number of pieces and copies for each container. The container IDs must match an ID of a container from a previously submitted qualification report.
        - Do not provide Container IDs in the PeriodicalLineItemData blocks. Lines could potentially then be collapsed together as they would not need to be broken out by container. (If any Container ID is provided, the Container Postage block will be disregarded).
    - Notes:
        - Parent and sibling containers do not need to be represented in either option.
        - Any full-service or mixed service container that is not represented via one of the two above methods will not be sent to SASP and will not receive full-service feedback.
- For full-service and mixed service mailings, each container ID in the postage statement message (either in the PeriodicalLineItemData block or in the ContainerPostage block) must exist in a previously submitted QualificationReportCreateRequest message.
- For full-service and mixed service mailings, each container ID in the postage statement message (either in the PeriodicalLineItemData block or in the ContainerPostage block) must exist in a previously submitted MailPieceCreateRequest message.
- For full-service and mixed service mailings, the total number of pieces per container ID in the postage statement message must not exceed the total number of pieces per container ID in the QualificationReportCreateRequest message.

Copyright © 2011 USPS®. All Rights Reserved.

- For full-service and mixed service mailings, the total number of pieces in the QualificationReportCreateRequest message exactly match the total number of pieces in the MailPieceCreateRequest message for each container ID included in the postage statement message.
- Firm Bundles and Addressed Supplements;
    - For a mailing that includes neither Addressed Supplements nor Firm Bundles, the number of copies must equal the number of pieces
    - For a mailing including Firm Bundles and no Addressed Supplements, the number of pieces cannot exceed the number of copies
    - For a mailing including Addressed Supplements and no Firm Bundles, the number of copies cannot exceed the number of pieces
    - The number of In-County Copies and Outside-County Copies must match between Piece and Pound postage lines.
    - The sum of InCountyAddressedSupplementPieces, OutsideCountyAddressedSupplementPieces, and PiecesExcludingAddressedSupplmentPieces must equal the total pieces submitted
    - The number of InCountyAddressedSupplementPieces and OutsideCountyAddressedSupplementPieces cannot exceed the number of In-County and Outside-County pieces, respectively
- Beginning in Release 25.0.0, the system will support government Inside-County Periodical and Pending Periodical mailings.
- Beginning in Release 26.0.0, Rate Categories AF, BF, DF, GF, and KF are not supported for First-Class Mail, Standard Mail, or Periodicals submitted after the January 2, 2011 price changed.
- Beginning in Release 26.0.0, the number of pieces must equal the number of copies when the mailing does not include Firm Bundles or Addressed Supplements and InOutCountyIndicator is N when the Postage Statement Mailing date is after the January 2, 2011 price change date
- Beginning in Release 26.0.0, the number of pieces must be less than or equal to the number of copies when the mailing includes Firm Bundles but does not have any Addressed Supplements and InOutCountyIndicator is N.
- Beginning in Release 26.0.0, the number of pieces must be greater than or equal to the number of copies when the mailing includes Addressed Supplements but does not have Firm Bundles and InOutCountyIndicator is N.
- For the Combined/Commingled Mailing – user must first send the BeginCombinedMailingRequest message prior to sending the PostageStatement messages.
- Beginning in Release 28.0.0, the *PostalOne!* system will not store an update made to the AdPercent field that was submitted in the DocumentVersionData block in the PeriodicalStatementCreateRequest message submitted after the first PeriodicalStatementCreateRequest message has been submitted to a mailing group for each unique version in that mailing group.
- The *PostalOne!* system will store the AdPercent submitted in the first PeriodicalStatementCreateRequest when it does not match the value submitted in the last accepted qualification report message.
- Beginning in Release 28.0.0, the *PostalOne!* system will not store an update made to the PieceWeight field that was submitted in the DocumentVersionData block in the PeriodicalStatementCreateRequest message submitted after the first PeriodicalStatementCreateRequest message has been submitted to a mailing group for each unique version in that mailing group.
- Beginning in Release 28.0.0, the *PostalOne!* system will store the PieceWeight submitted in the first PeriodicalStatementCreateRequest when it does not match the value submitted in the last accepted qualification report message.

Note - Important information on combined and consolidated postage statements:

Copyright © 2011 USPS®. All Rights Reserved.

(This note comprised of the following three parts, please review)

Part A – Currently, the Mail.XML specs allows the user to provide different data for the fields listed in Part C below for each postage statement request. During a Combined Mailing Request or during a Consolidated Periodical Postage Statement Request, the values of these fields (listed in Part C) have to be same from a business and processing stand-point. The current implementation of Mail.XML does not provide a feature where the user could supply this data for all of the postage statements that are consolidated or combined. A future release of Mail.XML and *PostalOne!* will cater to this requirement where the user will be required to provide with only one set of data (listed in Part C) for the whole message set of combined or consolidated postage statements. However, in the current implementation, USPS recommends all users to follow the set of instructions provided in section.

Part B – For the following set of postage statement message requests, follow the instructions documented in Part C below.

- BeginCombinedMailingRequest
- EndCombinedMailingRequest
- ConsolidatedPeriodicalStatementCreateRequest
- PeriodicalStatementCreateRequest
- PostageStatementCreateRequest

Part C – For all of the postage statement create requests (items 3, 4, and 5 from above), during a Combined Mailing request (meaning postage statements enclosed in between items 1 and 2 from above) and for ConsolidatedPeriodicalStatementCreateRequest user must provide the same values inside all of the postage statements for the following fields.

- IssueDate
- IssueNumber
- VolumeNumber
- CustomerReferenceID
- AgencyCostCode
- PermitPublicationData *(block of PermitHolderData block)*
- PostagePaymentMethod
- RateType
- ProcessingCategory

3.41.1 PeriodicalStatementCreateRequest

Field Description

Mail.XML 9.0B - PeriodicalStatementCreateRequest				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
PeriodicalStatementCreate Request Message BEGINS				
MailXMLPostageStatement RequestHeaderInfo block	Attributes		Attributes block	See Appendix C for Details

Copyright © 2011 USPS®. All Rights Reserved.

Mail.XML 9.0B - PeriodicalStatementCreateRequest				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
SubmittingParty Block	ParticipantIDType		Required block; Identifies the customer submitting the message	See Appendix C for Details
SubmittingSoftware Block	SubmittingSoftwareType		Required block; Identifies the software submitting the message	See Appendix C for Details
CreatePeriodicalStatement block begins			Required block; contains data critical to postage statement calculation	
AdvertisingPercentage	Mailxml_base:PercentageType		Required field; 5 total digits with a max value of 100.00	Refer simple type 'Percentage Type' in Appendix B
DeliveryStatisticsFileDate	Date	-	Optional To allow USPS to validate the correct file for simplified addresses.	-
AutomationAddressMatchDate	Date	YYYY-MM-DD	Optional field; Required for Automation mailings. The system will validate that this field cannot be more than 90 calendar days before the PostageStatement MailingDate for Carrier Route mail (RateCategory A, B, D, AF, BF, or DF). The field cannot be more than 180 calendar days before the PostageStatement MailingDate for	

Copyright © 2011 USPS®. All Rights Reserved.

Mail.XML 9.0B - PeriodicalStatementCreateRequest				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
			non-Carrier Route Mail (RateCategory E, H, L, L1, L2, L3, or L4).	
CustomerReferenceID	String, 40 characters		Optional field; Used to populate Customer Reference ID. Mailers may submit up to 999 unique CustomerReferenceIDs.	CustomerReferenceID represents CAPS Account Number
UserPostageStatementID	String, 10 characters		Optional field; Used to populate User Postage Statement ID to uniquely identify postage statement	
CarrierRouteAddressMatchDate	Date	YYYY-MM-DD	Optional field; Required for Carrier Route Automation pieces	
CarrierRouteSequencingDate	Date	YYYY-MM-DD	Optional field; Required for Carrier Route Sequencing pieces	
CertificationData block	CertificationDataType		Required block; data used in the certification statement section of the postage statement	See Appendix C for Details
ContainerCount block	mailxml:containerCountType		Required block; at least one of the fields in this block must be populated with a nonzero value	Refer Appendix C
CopyWeight	Double		Required field; used for *PostalOne!* postage calculation, accepts up to four decimal places. The value of CopyWeight must be in Pounds.	
EditionCode	String, 20 characters		Optional field; printed on postage	

Copyright © 2011 USPS®. All Rights Reserved.

Mail.XML 9.0B - PeriodicalStatementCreateRequest				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
			statement if provided	
FirstIssueDate	Date	YYYY-MM-DD	Optional field; not used by *PostalOne!*	
FormType	mailxml_base:formType	Refer 'formType' simple type	Required field	Refer Appendix B
IssueDate	Date	YYYY-MM-DD	Required field	
IssueFrequency	String, 20 characters		Optional field; populated with the frequency the postage statement comes from Publication data	
LastIssueDate	Date	YYYY-MM-DD	Optional field; not used by *PostalOne!*	
PostageStatementMailingDate	Date	YYYY-MM-DD	Required field; Used to determine prices and display on postage statement It may be up to one year in future or back dated to the most recent price change	
Over10	Mailxml_base:yesNo	Yes = Subscribers or Requesters over the 10% rule No = No subscribers or requesters over the 10% rule	Required field	
LimitedCirculationDiscountClaimed	yesNo	Yes = discount claimed No = no discount claimed	Required field	
PeriodicalLineItemData block begins			Required block; data used to generate specific line items of postage statement (0 to many pairings)	
Copies	Non-negative Integer		Optional field; total copies for pound postage lines	
ContainerDetailID	String, 9	-	Optional to link qualification report	-

Copyright © 2011 USPS®. All Rights Reserved.

Mail.XML 9.0B - PeriodicalStatementCreateRequest				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
			to periodical statement	
DiscountQty	Double		Optional field; Required when PeriodicalPrice is 1 to indicate In County number of addressed DDU pieces; must be a Non-negative integer.	
PeriodicalPrice	mailxml_base:periodicalPriceType	Refer 'periodicalPriceType' simple type	Optional field *PostalOne!* allows only the value 1 in the request message to indicate the Addressed DDU Pieces discount. The system will validate that Zone is DDU, InOutCountyIndicator is I, and DiscountQuantity is populated.	Refer Appendix B
InOutCountyIndicator	Mailxml_base:inCountyOutCountyIndicatorType	Refer 'inCountyOutCountyIndicatorType' simple type	Required field	Refer Appendix B
LineLabel	String, 80 characters		Optional field; this field may be overwritten during postage statement calculation	

Copyright © 2011 USPS®. All Rights Reserved.

LineNumber	String, 3 characters		Optional field; this field may be overwritten during postage statement calculation This field will be ignored if populated; LineNumber will only be taken into account for Full-Service discount lines	
NonCopies	Non-negative Integer		Optional field; Required for NonSubscriber copies or NonRequester copies for piece and pound postage lines. At least one of SubReqCopies and NonCopies must be populated with a non-negative integer.	
PieceRate	Double		Optional field; not used by *PostalOne!* If populated up to three decimal places are accepted.	
Pieces	Non-negative Integer		Optional field; Required for piece postage lines (i.e. when RateCategory is populated)	
PostageAmount	Double		Optional field; not used by *PostalOne!* Accepts up to four decimals when populated.	
PoundRate	Double		Optional field; not used by *PostalOne!* If populated up to three decimal places are accepted.	

Copyright © 2011 USPS®. All Rights Reserved.

RateCategory	Mailxml_base:rateCategoryType	Refer 'rateCategoryType' simple type	Optional field required for piece postage lines. It cannot be populated when Zone, PeriodicalPrice, or ChargeableContainerLevel are populated.	Refer Appendix B
Section	String, 1 character		Optional field; not used by *PostalOne!* This field will be ignored if populated; Section will only be taken into account for Full-Service discount lines	
SubReqCopies	Non-negative Integer		Optional field; Required for Subscriber copies or Requester copies for piece and pound postage lines. At least one of SubReqCopies and NonCopies must be populated with a non-negative integer.	
Zone	mailxml_base:zoneICType	Refer 'zoneICType' simple type	Optional field; Required for pound postage lines. It cannot be populated when RateCategory is populated.	Refer Appendix B
ChargeableContainerType	mailxml_base:chargeableContainerType	Refer 'chargeableContainerType' simple type	Optional field; Required for Outside County Container charge lines. Must also populate ChargeableContain	Refer Appendix B

Copyright © 2011 USPS®. All Rights Reserved.

			erLevel, ChargeableEntryLevel, and Containers.	
ChargeableContainerLevel	mailxml_base:chargeableContainerLevelType	Refer 'chargeableContainerLevelTYpe' simple type	Optional field; Required for Outside County container and bundle charge lines. Must also populate containers or Bundles. Cannot be populated if RateCategory or PeriodicalPrice are populated. (<BLANK> is not a value being supported)	Refer Appendix B
ContainerID	String 6 characters		Optional field	
ChargeableBundleLevel	mailxml_base:chargeableBundleLevelType	refer 'chargeableBundleLevelType' simple type	Optional field; Required for Outside County container and bundle charge lines. Must also populate bundles and ChargeableCOntainerLevel. (<BLANK> is not a value being supported)	Refer Appendix B
Bundles	Double		Optional field; Required for Outside County bundle charge lines. Must also populate ChargeableBundleLevel and ChargeableContainerLevel. Cannot be populated if Containers is populated. (*PostalOne!* accepts up to four decimal places on	

Copyright © 2011 USPS®. All Rights Reserved.

			each line)	
ChargeableEntryLevel	mailxml_base:chargeableEntryLevelType	Refer 'chargeableEntryLevelType' simple type	Optional field; Required for Outside County container charge lines. Must also populate ChargeableContainerLevel, ChargeableContainerType, and Containers.	Refer Appendix B
Containers	Double		Optional field; Required for Outside County container charge lines . Must also populate ChargeableContainerLevel, ChargeableContainerType, and ChargeableEntryLevel. Cannot be populated if Bundles is populated (*PostalOne!* accepts up to four decimal places on each line)	
MachinableFlag	Mailxml_base:yesNo	Yes No	Optional field; Required for piece postage lines with processing category flats.	
FullServiceParticipationIndicator	Mailxml_base:fspiType	Refer 'fspiType' simple type	Optional field, used for a piece postage line to indicate Full-Service pieces.	Refer Appendix B
USPSPackageUniqueCharacteristic	Mailxml_base:uspsPackageUniqueCharacteristicType	Simple type	Optional	Refer Appendix B
USPSPriceIncentiveType	Mailxml_base:USPSPriceIncentiveType	Simple Type	Optional The *PostalOne!* system does not perform any validation on PermitNumber when this field data	Refer Appendix B

Copyright © 2011 USPS®. All Rights Reserved.

			is provided. The Mailer can use "PostageAffixedReplyRidesFree" only for First Class Mail Letters and must be Full-Service IMb mail pieces weighing between 1 to 1.2 Oz but will be processed at 2Oz price rate. Reply Rides Free is not supported for metered mailings with mail piece weights reported as 1 oz.	

○

USPSPriceIncentiveID	Mailxml_base:USPSPriceIncentiveIDType	Simple Type	Optional This field is ignored.	Refer Appendix B
PeriodicalLineItemData block ends				
PostagePaymentMethod	Mailxml_base:postagePaymentMethodType	Refer 'postagePaymentMethodType' simple type	Required field	Refer Appendix B
ProcessingCategory	Mailxml_base:processingCategoryType	Refer 'processingCategoryType' simple type	Required field	Refer Appendix B
PublicationTitle	String, 60 characters		Optional field, *PostalOne!* uses this to get the Title	
CombinedMailingID	Non-negative Integer		Optional, required for combined mailing. See BeginCombinedMailingRequest for business rules.	
RateType	Mailxml_base:rateType	Refer 'rateType' simple type	Required field	Refer Appendix B
SingleRideAlongWeight	Double		Optional, required for a Ride Along weight in pounds. *PostalOne!* accepts up to four decimal places.	

Copyright © 2011 USPS®. All Rights Reserved.

			* Populating this field indicates ride-along in mailing. The value of SingleRideAlongWeight must be in Pounds.	
StatementSequenceNumber	String, 20 characters		Optional field; displayed on postage statement if provided	
EntryFacilityType	Mailxml_base:entryFacilityType	Refer 'entryFacilityType' simple type	Optional field; Required for discounts on dropping to entry facility type	Refer Appendix B
EntryZIP	Numeric, exactly 5 characters		Optional field; displayed on the postage statement register info if provided	
AgencyCostCode	Mailxml_base:agencyCostCodeType	Numeric, 5 or 6 characters	Optional field; Required if a government publication (can start with leading zeros)	Refer Appendix B
RepositionableNotesIndicator	Mailxml_base:yesNo	No = no repositionable notes Yes = repositionable notes	Required field	
DocumentVersionData block BEGIN	DocumentVersionData Type		Optional Block	See Appendix A for Details
VersionID	String, 10 characters		Required;	
VersionName	String, 12 characters		Required;	
VersionDescription	String, 30 characters		Optional	
PieceWeight	Decimal		Required PieceWeight must be provided must be in Pounds.	
AdPercent	Mailxml_base:percentageType		Optional field. Must match AdvertisingPercentage when provided.	Refer 'percentageType' simple type in Appendix B

Copyright © 2011 USPS®. All Rights Reserved.

RateAffixed	Decimal	-	Optional field. Required when PermitType is MT or PC. Accepts up to three decimals when populated.	-
ContentOfMailType	Mailxml_base:contentofmailtype	Refer this simple type in Appendix C	Optional	Refer Appendix B
StandardFlatType	Mailxml_base:standardFlatTypeType	Refer this simple type in Appendix C	Optional	Refer Appendix B
USPSPriceIncentiveType	Mailxml_base:USPSPriceIncentiveType	Simple Type	Optional The *PostalOne!* system does not perform any validation on PermitNumber when this field data is provided. The Mailer can use "PostageAffixedReplyRidesFree" only for First Class Mail Letters and must be Full-Service IMb mail pieces weighing between 1 to 1.2 oz but will be processed at 2Oz price rate.	Refer Appendix B
USPSPriceIncentiveID	Mailxml_base:USPSPriceIncentiveIDType	Simple Type	Optional This field is ignored.	Refer Appendix B
DocumentVersionData Block END				
MoveUpdateMethod	Mailxml_base:moveUpdateMethodType	Refer 'moveUpdateMethodType'	Optional field; does not apply for Periodicals	Refer Appendix B
VolumeNumber	String, 5 characters		Optional field	
IssueNumber	String, 6 numbers		Optional field	
InCountyAddressedSupplementPieces	Non-negative Integer		Optional field	
OutsideCountyAddressedSupplementPieces	Non-negative Integer		Optional field	
PiecesExcludingAddressed	Non-negative		Required field,	

Copyright © 2011 USPS®. All Rights Reserved.

SupplementPieces	Integer		replaces total pieces in postage statement	
ContainerPostage Block	Mailxml:container PostageType		Required by the *PostalOne! for Full-Service or Mixed mailings (Full-Service plus another type)*	Refer 'containerPostageType' complex in Appendix C
MailingAgentData block	mailerDataRequestType		Required field; Required if there is a mailing agent for the mail owner	See Appendix C for Details
PublisherData block	MailerDataRequestType		Required block; *PostalOne!* uses this data to bill the postage statement. must contain the Publication Number of the Periodical or the combination of PermitNumber, PermitType with value PP, and PermitZIP4 representing pending Periodical.	See Appendix C for Details
PendingPostageAmount	Double	-	Optional, required for pending Periodical permit type PP, up to two decimal places accepted.	
CreatePeriodicalStatement Data block ends				
PeriodicalStatementCreate Request Message ENDS				

2.2.26 - PeriodicalStatementCreateRequest

3.42 PeriodicalStatementCreateResponse

Purpose
Response to the customer's request to create a Periodical Postage Statement

Error/Return Codes
Refer Section 2.6 to view shared error/return codes and also a list of error/return codes tied this message.

Copyright © 2011 USPS®. All Rights Reserved.

Business Rules

- Message will be sent in response to and must follow the PeriodicalStatementCreateRequest

3.42.1 PeriodicalStatementCreateResponse Data Structure

Field Description

Mail.XML 9.0B - PeriodicalStatementCreateResponse				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
PeriodicalStatementCreateAccept block begins			Response from USPS indicating that the PeriodicalStatementCreateRequest message was accepted and a Periodical Postage Statement was created (choice between StatementID, UserPostageStatementID, TotalPostage, TotalPostageDue, and ReturnInfo block or TrackingID and ReturnInfo block)	
MailXMLPostageStatementResponseHeaderInfo block	MailXMLPostageStatementResponseHeaderInfo		Attributes block	See Appendix E for Details
StatementID	Non-negative integer		Required field	
UserPostageStatementID	String, 10 characters		Optional field	
TotalPostage	Double		Required field, two decimal points provided. If not generated for Statement ID there will be a reject block.	
TotalPostageDue	Double		Required field, may be zero, two decimal points provided. If not generated for Statement ID there will be a reject	

Copyright © 2011 USPS®. All Rights Reserved.

Mail.XML 9.0B - PeriodicalStatementCreateResponse				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
			block.	
ReturnInfo block	ReturnInfo		Optional block; paired with StatementID, UserPostageStatementID, TotalPostage, and TotalPostageDue	See Appendix E for Details
PeriodicalStatementCreateAccept block ends				
PeriodicalStatementCreateReject block begins			Response from USPS indicating that the PeriodicalStatementCreateRequest message was rejected and a Periodical Postage Statement was not created and the reason why	
MailXMLPostageStatementResponseHeaderInfo block	MailXMLPostageStatementResponseHeaderInfo			See Appendix E for Details
ReturnInfo block	ReturnInfo		Required block	See Appendix E for Details
PeriodicalStatementCreateReject block ends				

2.2.27 - PeriodicalStatementCreateResponse

3.43 PeriodicalStatementQueryRequest

Purpose
Allows the USPS customer to retrieve a Periodicals postage statement

Business Rules

- Must be submitted after a periodical postage statement has been created (after the PeriodicalStatementCreateRequest message has been accepted)

3.43.1 PeriodicalStatementQueryRequest Data Structure

Field Description

Mail.XML 9.0B - PeriodicalStatementQueryRequest				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
MailXMLPostageStatementRequestHeaderInfo block	MailXMLPostageStatementReque		Attributes block	See Appendix E

Copyright © 2011 USPS®. All Rights Reserved.

Mail.XML 9.0B - PeriodicalStatementQueryRequest				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
	stHeaderInfo			for Details
SubmittingParty Block	ParticipantIDType		Required block; Identifies the customer submitting the message	See Appendix E for Details
SubmittingSoftware Block	SubmittingSoftwareType		Required block; Identifies the software submitting the message	See Appendix E for Details
StatementID	Non-negative integer		Required field	
IncludeChildStatement	yesNo	Yes/No	Required field, if No only the requested Statement ID is returned. If Yes, the statement ID requested and its child statements are returned.	

2.2.28 - PeriodicalStatementQueryRequest

3.44 PostageStatementCreateRequest

Purpose
Allows the USPS customer to submit a 3600-series postage statement to a mailing group. This message allows the customer to submit either the basic-form or extended-form of the 3600-series postage statement, in order to accommodate either singular or multiple entries for each line item, which allows the customer to submit non-identical piece weight mailings.

Business Rules

- Must be submitted after all mail pieces or piece ranges are submitted for a mailing group
- Postage adjustments will be expected for postage statements with wasted or spoiled pieces
- The 'Section' and 'Line Number' elements will be corrected if an error is made in submitting
- The only instance where ‘Section’ and ‘Line Number’ will be taken as submitted (and not corrected/changed) is for the Full-Service discount lines. Otherwise, the full-service discount lines will be generated based on a FullServiceParticipationIndicator of ‘F’ in the PostageStatementLineItemData block.
- The PermitHolderforAPData block will be required for Postage Payment Method of 'S' or 'M' and cannot be a meter. It must be either an OI or PI permit.

The FormType field cannot be 'PE' = Periodicals Class for a PostageStatementCreateRequest. In this case use the PeriodicalStatementCreateRequest message.

- For full-service or mixed service mailings, there are two options for how to populate the required container information:
    - LineItemData block
        - Include one PostageStatementLineItemData block for each container represented on each line of the postage statement. The container IDs must match an ID of a container from a previously submitted qualification report.
        - Do not include ContainerPostage block. If provided, it will be ignored.

Copyright © 2011 USPS®. All Rights Reserved.

- ContainerPostage block
  - All containers are represented in the ContainerPostage blocks with the number of pieces and copies for each container. The container IDs must match an ID of a container from a previously submitted qualification report.
  - Do not provide Container IDs in the LineItemData blocks. Lines could potentially then be collapsed together as they would not need to be broken out by container. (If any Container ID is provided, the Container Postage block will be disregarded).
- Notes:
  - Parent and sibling containers do not need to be represented in either option.
  - Any full-service or mixed service container that is not represented via one of the two above methods will not be sent to SASP and will not receive full-service feedback.

- For full-service and mixed service mailings, each container ID in the postage statement message (either in the LineItemData block or in the ContainerPostage block) must exist in a previously submitted QualificationReportCreateRequest message.
- For full-service and mixed service mailings, each container ID in the postage statement message (either in the LineItemData block or in the ContainerPostage block) must exist in a previously submitted MailPieceCreateRequest message.
  - Beginning in Release 28.0.0, MailPieceCreateRequest messages can be submitted before or after the Postage/Periodical/Consolidated Statements. If they are submitted after, it must be before finalization. Full-service or mixed service mailings cannot be finalized until all pieces are submitted via the MailPieceCreateRequest messages. All piece counts must match between the MailPieceCreateRequest, Postage/Periodical/Consolidated Statements and QualificationReportCreateRequest messages.
  -
- For full-service and mixed service mailings, the total number of pieces per container ID in the postage statement message must not exceed the total number of pieces per container ID in the QualificationReportCreateRequest message.
- For full-service and mixed service mailings, the total number of pieces in the QualificationReportCreateRequest message exactly match the total number of pieces in the MailPieceCreateRequest message for each container ID included in the postage statement message.
- PublicationNumber cannot be populated in a PostageStatementCreateRequest message
- Beginning in Release 25.0.0, for MLOCR First-Class mailings claiming Single Piece prices, the PermitType in the PermitHolderData block in the PostageStatementCreateRequest message must be set to Permit Imprint (PI), Metered (MT), or PC (Precanceled Stamps). At least one SortationLevel in QualificationReportCreateRequest message must be set to “AN.” NOTE:Wherever SortationLevel is used, it is defined as Type=ContainerLevelType.

- Beginning in Release 26.0.0, FormType PM for Priority Mail is not supported after the January 2, 2011 price change date.
- Beginning in Release 26.0.0, FormType PP for Package Services Parcel Post is not supported after the January 2, 2011 price change date.
- Beginning in Release 26.0.0, Standard Mail Parcels are not supported for 7.0 and 8.0 version files that are submitted after the January 2, 2011 price change date.
- Beginning in Release 26.0.0, Rate Categories AF, BF, DF, GF, and KF are not supported for First-Class Mail, Standard Mail, or Periodicals submitted after the January 2, 2011 price change date.
- Beginning in Release 26.0.0, the ProcessingCategory field cannot be populated with IR for Bound Printed Matter Package Service mailings submitted after the January 2, 2011 price change date.

Copyright © 2011 USPS®. All Rights Reserved.

- For the Combined/Commingled Mailing – user must first send the BeginCombinedMailingRequest message prior to sending the PostageStatement messages
- Beginning in Release 26.1, First-Class Commercial Plus Parcels will be accepted after the April 2011 price change date when the following conditions are met:
    - FormType in the CreatePostageStatement block is FC (First-Class)
    - PresentationCategory in the CreatePostageStatement block is PF (Parcel, First-Class)
    - PriceType in the CreatePostageStatement block is commercialplus
- Beginning in Release 26.1, the following ServiceCode values will be supported for First-Class Commercial Plus Parcels:
    - CM – Certified Mail
    - COD – Collect on Delivery
    - COM – Certificate of Mailing
    - DC – Delivery Confirmation
    - IM – Insured Mail
    - RD – Restricted Delivery
    - RR – Return Receipt
    - RRE – Return Receipt Electronic
    - SC – Signature Confirmation
    - SH – Special Handling
-

Note - Important information on combined and consolidated postage statements:

(This note comprised of the following three parts, please review)

Part A – Currently, the Mail.XML specs allows the user to provide different data for the fields listed in Part C below for each postage statement request. During a Combined Mailing Request or during a Consolidated Periodical Postage Statement Request, the values of these fields (listed in Part C) have to be same from a business and processing stand-point. The current implementation of Mail.XML does not provide a feature where the user could supply this data for all of the postage statements that are consolidated or combined. A future release of Mail.XML and *PostalOne!* will cater to this requirement where the user will be required to provide with only one set of data (listed in Part C) for the whole message set of combined or consolidated postage statements. However, in the current implementation, USPS recommends all users to follow the set of instructions provided in section.

Part B – For the following set of postage statement message requests, follow the instructions documented in Part C below.

- BeginCombinedMailingRequest
- EndCombinedMailingRequest
- ConsolidatedPeriodicalStatementCreateRequest
- PeriodicalStatementCreateRequest
- PostageStatementCreateRequest

Part C – For all of the postage statement create requests (items 3, 4, and 5 from above), during a Combined Mailing request (meaning postage statements enclosed in between items 1 and 2 from above) and for ConsolidatedPeriodicalStatementCreateRequest user must provide the same values inside all of the postage statements for the following fields.

- IssueDate
- IssueNumber
- VolumeNumber
- CustomerReferenceID
- AgencyCostCode
- PermitPublicationData *(block of PermitHolderData block)*

Copyright © 2011 USPS®. All Rights Reserved.

- PostagePaymentMethod
- RateType
- ProcessingCategory

3.44.1 PostageStatementCreateRequest Data Structure

Field Description

Mail.XML 9.0B - PostageStatementCreateRequest				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
PostageStatementCreateRequest Message BEGINS				
MailXMLPostageStatementRequestHeaderInfo	MailXMLPostageStatementRequestHeaderInfo		Attributes block	See Appendix C for Details
SubmittingParty	ParticipantIDType		Required block; Identifies the customer submitting the message	See Appendix C for Details
SubmittingSoftware	SubmittingSoftwareType		Required block; Identifies the software submitting the message	See Appendix C for Details
CreatePostageStatmentBlock	createPostageStatementType	Complex Type	Required Only one can be submitted	Refer "CreatePostageStatementType" complex in Appendix C
PostageStatementCreateRequest Message ENDS				

2.2.29 - PostageStatementCreateRequest

3.45 PeriodicalStatementQueryResponse

Purpose
Return either the postage statement query results data or the reason why there was a query error

Copyright © 2011 USPS®. All Rights Reserved.

Error/Return Codes

Refer Section 2.6 to view shared error/return codes and also a list of error/return codes tied this message.

Business Rules

- Will accept if StatementID or TrackingID exists
- Will reject if StatementID or TrackingID does not exist
- The ReturnInfo block will have a description for a QueryError

3.45.1 PeriodicalStatementQueryResponse Data Structure

Field Description

Mail.XML 9.0B - PeriodicalStatementQueryResponse				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
PeriodicalStatementQueryResponse Message BEGINS				
MailXMLPostageStatementResponseHeaderInfo block	MailXMLPostageStatementResponseHeaderInfo		Attributes block	See Appendix C for Details
Sequence Block BEGINS				
TrackingID	String, 12	-	Optional. Provides the tracking ID when message fails to get delivered	-
Choice Block BEGINS				
QueryResults block begins			Required block; accepting the query request message and returning the query for a successful PeriodicalStatementQueryRequest message	
PeriodicalStatementDataType Block BEGINS				
AdvertisingPercentage	Mailxml_base:PercentageType		Required field; 5 total digits with a max value of	*Refer this simple type in Appendix C*

Copyright © 2011 USPS®. All Rights Reserved.

Mail.XML 9.0B - PeriodicalStatementQueryResponse				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
			100.00	
DeliveryStatisticsFileDate	Date	-	Optional. Allows USPS to validate the correct file date for simplified addresses.	-
AutomationAddressMatchDate	Date	YYYY-MM-DD	Optional field; Required for Automation mailings The system will validate that this field cannot be more than 90 calendar days before the PostageStatement MailingDate for Carrier Route mail (RateCategory A, B, D, AF, BF, or DF). The field cannot be more than 180 calendar days before the PostageStatement MailingDate for non-Carrier Route Mail (RateCategory is E, H, L, L1, L2, L3, or L4).	
CustomerReferenceID	String, 40 characters		Optional field; Used to populate Customer Reference ID	CustomerReferenceID represents CAPS Account Number
UserPostageStatementID	String, 10 characters		Optional field; Used to populate User Postage Statement ID to uniquely identify postage statement	
CarrierRouteAddressMatchDate	Date	YYYY-MM-DD	Optional field; Required for Carrier	

Copyright © 2011 USPS®. All Rights Reserved.

Mail.XML 9.0B - PeriodicalStatementQueryResponse				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
			Route Automation pieces	
CarrierRouteSequencingDate	Date	YYYY-MM-DD	Optional field; Required for Carrier Route Sequencing pieces	
CertificationData block	CertificationData Type		Required block; data used in the certification statement section of the postage statement	See Appendix C for Details
ContainerCount block	ContainerCountType		Required block; at least one of the fields in this block must be populated with a nonzero value	See Appendix C for Details
CopyWeight	Double		Required field; used for *PostalOne!* postage calculation, *PostalOne!* accepts up to four decimals. The value of CopyWeight must be in Pounds.	
EditionCode	String, 20 characters		Optional field; printed on postage statement if provided	
FirstIssueDate	Date	YYYY-MM-DD	Optional field; not used by *PostalOne!*	
FormType	Mailxml_base:formType	Refer 'formType' simple type	Required field	Refer Appendix B
IssueDate	Date	YYYY-MM-DD	Required field	
IssueFrequency	String, 20 characters		Optional field; populated with the frequency the postage statement comes from Publication data	
LastIssueDate	Date	YYYY-MM-DD	Optional field; not used by *PostalOne!*	
PostageStatementMailingDate	Date	YYYY-MM-DD	Required field; Used to determine prices and display on postage statement	

Copyright © 2011 USPS®. All Rights Reserved.

Mail.XML 9.0B - PeriodicalStatementQueryResponse				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
			It may be up to one year in future or back dated to most recent price change	
Over10	Mailxml_base:yes No	Yes = Subscribers or Requesters over the 10% rule No = No subscribers or requesters over the 10% rule	Required field	
LimitedCirculationDiscount Claimed	Mailxml_base:yes No	Yes No	Required field	
PeriodicalLineItemData block begins			Required block; data used to generate specific line items of postage statement (one to many pairings)	
Copies	Non-negative Integer		Optional field; total copies for pound postage lines	
ContainerDetailID	String 9	-	Optional to link qual report to periodical statement	-
DiscountQty	Double		Optional field; Required for corresponding PeriodicalPrice	
PeriodicalPrice	Mailxml_base:periodicalPriceType	Refer 'periodicalPriceType' simple type	Optional field, used if the Periodical Postage Statement line in acceptable values is present.	Refer Appendix B
InOutCountyIndicator	mailxml_base:inCountyOutCountyIndicatorType	Refer 'inCountyOutCountyIndicatorType' simple type	Required field	Refer Appendix B
LineLabel	String, 80 characters		Optional field; this field will be overwritten during postage statement calculation	
LineNumber	String, 3		Optional field; this	

Copyright © 2011 USPS®. All Rights Reserved.

Mail.XML 9.0B - PeriodicalStatementQueryResponse				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
	characters		field will be overwritten during postage statement calculation This field will be ignored if populated; LineNumber will only be taken into account for Full-Service discount lines	
NonCopies	Non-negative Integer		Optional field; Required for NonSubscriber copies or NonRequester copies for pound postage lines	
PieceRate	Decimal		Optional field	
Pieces	Non-negative Integer		Optional field; Required for Piece Postage lines	
PostageAmount	Decimal		Optional field	
PoundRate	Decimal		Optional field	
RateCategory	mailxml_base:rateCategory	Refer 'rateCategory' simple type	Optional field, required for piece postage lines	Refer Appendix B

Copyright © 2011 USPS®. All Rights Reserved.

Section	String, 1 character		Optional field; not used by *PostalOne!* This field will be ignored if populated; Section will only be taken into account for Full-Service discount lines	
SubReqCopies	Non-negative Integer		Optional field; Required for pound postage lines	
Zone	mailxml_base:zoneICType	Refer 'zoneICType' simple type	Optional field; Required for pound postage lines	Refer Appendix B
ChargeableContainerType	mailxml_base:chargeableContainerType	Refer 'chargeableContainerType' simple type	Optional field; Required for Outside County Container charge lines.	Refer Appendix B
ChargeableContainerLevel	mailxml_base:chargeableContainerLevelType	Refer 'chargeableContainerLevelType' simple type	Optional field; Required for Outside County container and bundle charge lines	Refer Appendix B
ContainerID	String, 6		Optional	
ChargeableBundleLevel	mailxml_base:chargeableBundleLevelType	Refer 'chargeableBundleLevelType' simple type	Optional field; Required for Outside County container and bundle charge lines	Refer Appendix B
Bundles	Decimal		Optional field; Required for Outside County bundle charge lines (*PostalOne!* provides four decimal places on each line)	
ChargeableEntryLevel	mailxml_base:chargeableEntryLevelType	Refer 'chargeableEntryLevelType' simple type	Optional field; Required for Outside County container charge lines	Refer Appendix B

Copyright © 2011 USPS®. All Rights Reserved.

Containers	Decimal		Optional field; Required for Outside County container charge lines (*PostalOne!* provides four decimal places on each line)	
MachinableFlag	Mailxml_base:yes No	Yes No	Optional field; Required for piece postage lines where processing category is flats.	
FullServiceParticipationIndicator	mailxml_base:fspiType	Refer 'fspiType' simple type	Optional	Refer Appendix B
USPSPackageUniqueCharacteristic	Mailxml_base:uspsPackageUniqueCharacteristicType	Refer this simple type in Appendix C	Optional	Refer Appendix B
USPSPriceIncentiveType	Mailxml_base:USPSPriceIncentiveType	Simple Type	Optional The *PostalOne!* system does not perform any validation on PermitNumber when this field data is provided. The Mailer can use "PostageAffixedReplyRidesFree" only for First Class Mail Letters and must be Full-Service IMb mail pieces weighing between 1 to 1.2 oz but will be processed at 2Oz price rate.	Refer Appendix B
USPSPriceIncentiveID	Mailxml_base:USPSPriceIncentiveIDType	Simple Type	Optional This field is ignored.	Refer Appendix B
PeriodicalLineItemData block ends				
PostagePaymentMethod	Mailxml_base:postagePaymentMethodType	Refer 'postagePaymentMethodType'	Required field	

Copyright © 2011 USPS®. All Rights Reserved.

		simple type		
ProcessingCategory	Mailxml_base:processingCategoryType	Refer 'processingCategoryType' simple type	Required field	Refer Appendix B
PublicationTitle	String, 60 characters		Optional field, *PostalOne!* uses this to get the Title	
CombinedMailingID	Non-negative Integer		Optional field, required if a combined mailing	
RateType	Mailxml_base:rateType	Refer 'rateType' simple type	Required field	Refer Appendix B
SingleRideAlongWeight	Decimal		Optional The value of SingleRideAlongWeight must be in Pounds.	
StatementSequenceNumber	String, 20 characters		Optional field; displayed on postage statement if provided	
EntryFacilityType	mailxml_base:entryFacilityType	Refer 'entryFacilityType' simple type	Optional field; Required for discounts on dropping to entry facility type	Refer Appendix B
EntryZip	Numeric, exactly 5 characters		Optional field; displayed on the postage statement register info if provided	
AgencyCostCode	Mailxml_base:agencyCostCodeType		Optional field; Required if a government publication (can start with leading zeros)	Refer this simple type in Appendix C
RepositionableNotesIndicator	Mailxml_ase:yesNo	NO = no repositionable notes Yes = repositionable notes	Required field	
DocumentVersionData block	DocumentVersionData Type		Optional block; Required for Version Summary	See Appendix C for Details

Copyright © 2011 USPS®. All Rights Reserved.

			Report	
MoveUpdateMethod	Mailxml_base:moveUpdateMethodType	Refer 'moveUpdateMethodType' simple type	Optional field; does not apply for Periodicals	Refer Appendix B
VolumeNumber	String, 5	-	Optional	-
IssueNumber	String, 6	-	Optional	-
InCountyAddressedSupplementPieces	Non-negative Integer		Optional	
OutsideCountyAddressedSupplementPieces	Non-negative Integer		Optional	
PiecesExcludingAddressedSupplementPIeces	Non-negative Integer		Required	
ContainerPostage Block	containerPostageType	-	Optional. Allow 0 to many	Refer "containerPostageType" in the Appendix C
StatementID	Non-negative integer		Optional field	
MailClass	mailxml_base:mailClassType	Refer 'mailClassType' simple type	Optional field	Refer Appendix B
Origin	String, 6 characters		Optional field	
PostageStatementStatus	Mailxml_base:postageStatementStatusType		Optional field	Refer Appendix B
TotalCopies	Non-negative Integer		Required field	
TotalPieces	Non-negative Integer		Required field	
TotalPostageAmount	Double		Required field, two decimal places	
TotalWeight	Double		Required field, no decimal places. The value of TotalWeight must be in Pounds.	
MailingAgentData block	mailerDataType		Required field; Required if there is a mailing agent for the mail owner	Refer this complex type in Appendix C
PublisherData block	mailerDataType		Required block; *PostalOne!* uses this data to bill the postage statement	Refer this complex type in Appendix C
PendingPostageAmount	Double	-	Optional, required	

Copyright © 2011 USPS®. All Rights Reserved.

			for pending Periodicals, two decimal places provided.	
PeriodicalStatementData block ends				
ReturnInfo block	basicReturnInfoType		Optional block	See Appendix C for Details
QueryResults block ends				
QueryError block begins			Required block if there are any failed validations in the PeriodicalStatementQueryRequest message or when the query data cannot be provided	
ReturnInfo block	basicReturnInfoType		Required block	See Appendix C for Details
QueryError block ends				
PeriodicalStatementQueryResponse Message ENDS				

2.2.30 - PeriodicalStatementQueryResponse

3.46 PostageAdjustmentCreateRequest

Purpose
Customer provides PostageAdjustmentCreateRequest message to document spoilage and shortage pieces

Business Rules

- Postage adjustment can only occur for the latest mailing date associated with the StatementID in the PostageAdjustment block
- Mail.dat fields cannot be accepted in the PostageAdjustmentCreateRequest message
- PostageAdjustmentCreateRequest will support postage adjustments for both postage statements and periodical postage adjustments
- Beginning in Release 26.1, First-Class Commerical Plus Parcels will be accepted when the following conditions are met:
    - FormType in the CreatePostageStatement block is FC (First-Class)
    - PresentationCategory in the CreatePostageStatement block is PF (Parcel, First-Class)
    - PriceType in the CreatePostageStatement block is commercialplus

Copyright © 2011 USPS®. All Rights Reserved.

3.46.1 PostageAdjustmentCreateRequest Data Structure

Field Description

Mail.XML 9.0B - PostageAdjustmentCreateRequest				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
SubmittingParty Block	ParticipantIDType		Required block; Identifies the customer submitting the message	Refer 'ParticipantID Type' complex type in Appendix E.
SubmittingSoftware Block	SubmittingSoftwareType		Required block; Identifies the software submitting the message	Refer 'SubmittingSoftware' complex type in Appendix E.
UserLicenseCode	String, 4 characters		Field not being supported; using the CustomerGroupID and MailingGroupID	
MaildatJobID	String, 8 characters		Field not being supported; using the CustomerGroupID and MailingGroupID	
CustomerGroupID	String, 25 characters		Required field; must be populated with the same value as the value populated in the CustomerGroupID field in the PostagestatementCreateResponse message	
MailingGroupID	Non-negative Integer		Required field; must be populated with the same value as the value populated in the MailingGroupID field in the PostagestatementCreateResponse message	
PostageAdjustment Block begins			Required field; 1 to many pairings can be submitted	

Copyright © 2011 USPS®. All Rights Reserved.

Mail.XML 9.0B - PostageAdjustmentCreateRequest				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
PostageAdjustmentUserID	String, 12 characters		Required field	
StatementID	Non-negative Integer		Required field; must be populated with the same value as the value populated in the StatementID field in the PostageStatement CreateAccept block of the PostageStatement CreateResponse	
RateType	mailxml_base:rateType	Refer 'rateType' simple type	Optional field	Refer Appendix B
AdjustmentDate	Date	YYYY-MM-DD	Required field Must be populated with a date later than the latest mailing date for the specified MailingGroup, StatementID, and CustomerGroupID	
AdjustmentType	mailxml_base:adjustmentType	Refer 'adjustmentType' simple type	Required field.	Refer Appendix B
AdjustmentAmount	Number		Required field. Accepts up to two decimals. Cannot exceed the total postage on the postage statement.	
CreditDebitIndicator	mailxml_base:creditDebitIndicator	Refer 'creditDebitIndicator' simple type	Required field	Refer Appendix B
TotalPiecesAffected	Non-negative Integer		Required field Cannot exceed the total pieces on the postage statement.	
UserComments	String, 20 characters		Optional field	
UserPostageStatementID	String, 10 characters		Optional field	
AdjustmentStatus	mailxml_base:adj	refer	Optional field	Refer

Copyright © 2011 USPS®. All Rights Reserved.

Mail.XML 9.0B - PostageAdjustmentCreateRequest				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
	ustmentStatusType	'adjustmentStatusTYpe' simple type		Appendix B
PostageAdjustment Block ends				

2.2.31 - PostageAdjustmentCreateRequest

3.47 PostageAdjustmentCreateResponse

Purpose
Response from the *PostalOne!* system informing the customer of whether the postage adjustment data sent in the PostageAdjustmentCreateRequest message has been accepted

Error/Return Codes
Refer Section 2.6 to view shared error/return codes and also a list of error/return codes tied this message.

Business Rules
- Must be returned to the customer after the PostageAdjustementCreateRequest message is sent by the customer to *PostalOne!*
- PostageStatementCreateRequest or PeriodicalStatementCreateRequest must be accepted before submitting the PostageAdjustmentCreateRequest for the specified MailingGroupID and CustomerGroupID
- StatementID or UserPostageStatementID specified must exist for a postage statement or periodical postage statement
- Mailing date given must be the latest mailing date for the StatementID specified
- MLOCR mailings cannot have postage adjusted
- PostageStatementStatus must be UPD for USPS Processing Due for the specified StatementID

3.47.1 PostageAdjustmentCreateResponse Data Structure

Field Description

Mail.XML 9.0B - PostageAdjustmentCreateResponse				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
PostageAdjustmentCreateAccept Block begins			Response from USPS indicating that the data in the PostageAdjustment CreateRequest message was accepted	
UserLicenseCode			Field not being supported; using the CustomerGroupID and MailingGroupID	

Copyright © 2011 USPS®. All Rights Reserved.

Mail.XML 9.0B - PostageAdjustmentCreateResponse				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
MaildatJobID			Field not being supported; using the CustomerGroupID and MailingGroupID	
CustomerGroupID	String, 25 characters		Required field; must be populated with the same value as the value populated in the CustomerGroupID field in the PostageStatement CreateAccept block of the PostageStatement CreateResponse	
MailingGroupID	Non-negative Integer		Required field; must be populated with the same value as the value populated in the MailingGroupID field in the PostageStatement CreateAccept block of the PostageStatement CreateResponse	
PostageAdjustmentUserID	String, 12 characters		Required field; 1 to many pairings of PostageAdjustment UserID, PostageAdjustment ConfirmID and ReturnInfo Block can be submitted	
	Non-negative Integer		Required field; must be populated with the same value as the value populated in the StatementID field in the PostageStatement CreateAccept block of the PostageStatement CreateResponse	

Copyright © 2011 USPS®. All Rights Reserved.

Mail.XML 9.0B - PostageAdjustmentCreateResponse				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
ReturnInfo Block	ReturnInfo			See Appendix A for Details
PostageAdjustmentCreateAccept Block ends				
PostageAdjustmentCreateReject Block begins			Response from USPS indicating that the PostageAdjustment CreateRequest message was rejected	
UserLicenseCode			Field not being supported	
MaildatJobID			Field not being supported	
CustomerGroupID	String, 25 characters		Required field; must be populated with the same value as the value populated in the CustomerGroupID field in the PostageStatement CreateAccept block of the PostageStatement CreateResponse	
MailingGroupID	Non-negative Integer		Required field; must be populated with the same value as the value populated in the CustomerGroupID field in the PostageStatement CreateAccept block of the PostageStatement CreateResponse	
PostageAdjustmentUserID	String, 12 characters		Required field; 1 to many pairings of PostageAdjustment UserID and ReturnInfo Block can be submitted	
ReturnInfo Block	ReturnInfo		Required field;	See Appendix A for Details
PostageAdjustmentCreateR				

Copyright © 2011 USPS®. All Rights Reserved.

Mail.XML 9.0B - PostageAdjustmentCreateResponse				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
eject Block ends				

2.2.32 - PostageAdjustmentCreateResponse

3.48 PostageStatementCancelRequest

Purpose
Allows the USPS customer to cancel a submitted postage statement (including a Periodicals statement) that has not already been reversed or finalized

Business Rules

- Must be submitted after a postage statement has been created (PeriodicalStatementCreateResponse or PostageStatementCreateResponse indicates accepted)
- Will not be accepted after a postage statement has been finalized (PostageStatementStatus is FIN or FPP.)
- All postage statements in a mailing group is cancelled if a StatementID is not submitted
- Beginning in Release 26.1, First-Class Commerical Plus Parcels will be accepted after the April 2011 price change date when the following conditions are met:
    - FormType in the CreatePostageStatement block is FC (First-Class)
    - PresentationCategory in the CreatePostageStatement block is PF (Parcel, First-Class)
    - PriceType in the CreatePostageStatement block is commercialplus

3.48.1 PostageStatementCancelRequest Data Structure

Field Description

Mail.XML 9.0B - PostageStatementCancelRequest				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
MailXMLPostageStatement RequestHeaderInfo Block			Attributes block	See Appendix E for Details
SubmittingParty Block	ParticipantIDType		Required block; Identifies the customer submitting the message	See Appendix E for Details
SubmittingSoftware Block	SubmittingSoftwa reType		Required block; Identifies the software submitting the message	See Appendix E for Details
StatementID	Non-negative Integer		*PostalOne!* assigned postage statement ID Optional	

2.2.33 - PostageStatementCancelRequest

Copyright © 2011 USPS®. All Rights Reserved.

3.49 PostageStatementCancelResponse

Purpose
Accept or reject a request to cancel postage statement (including a periodical statement)

Error/Return Codes
Refer Section 2.6 to view shared error/return codes and also a list of error/return codes tied this message.

Business Rules
- Will accept if postage statements exist in the mailing group and postage is not finalized
- Will reject if postage statements do not exist in the mailing group or the StatementID requested does not exist.
- Will reject if postage is finalized (PostageStatementStatus is FIN or FPP.)
- The ReturnInfo block will have a description for rejection

3.49.1 PostageStatementCancelResponse Data Structure

Field Description

Mail.XML 9.0B - PostageStatementCancelResponse				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
PostageStatementCancelAccept Block begins			Block received upon accepting request	
MailXMLMsgResponseHeaderInfo Block	MailXMLMsgResponseHeaderInfo		Attributes block	See Appendix E for Details
UserPostageStatementID	String, 10 characters		User created postage statement ID Optional	
StatementID	Non-negative Integer		*PostalOne!* assigned postage statement ID Required	
PostageStatementCancelAccept Block ends				
PostageStatementCancelReject Block begins				
MailXMLMsgResponseHeaderInfo Block	MailXMLMsgResponseHeaderInfo		Attributes block	See Appendix E for Details
ReturnInfo Block	basicReturnInfoType		Provides reason for return Required Multiple pairings of ReturnCode and ReturnDescription can be provided in	See Appendix

Copyright © 2011 USPS®. All Rights Reserved.

Mail.XML 9.0B - PostageStatementCancelResponse				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
			the block	
PostageStatementCancelReject Block ends				

2.2.34 - PostageStatementCancelResponse

3.50 PostageStatementCreateResponse

Purpose
The PostageStatementCreateResponse will be used by USPS to notify the customer if their request to submit a 3600-series postage statement to a mailing group has been accepted or rejected.

Error/Return Codes
Refer Section 2.6 to view shared error/return codes and also a list of error/return codes tied this message.

Business Rules
- Will accept if all required fields are provided and values are valid
- Will reject if a required field is not provided
- Will reject if a value provided is invalid
- Will reject if not all pieces are accounted for from submitted mailpieces or piece ranges
- Will reject if FormType is 'PE' for Periodicals
- Will reject if PostagePaymentMethod is 'S' or 'M' and PermitHolderForAPData Block is not provided
- The ReturnInfo block will have a description for rejection

3.50.1 PostageStatementCreateResponse Data Structure

Field Description

Mail.XML 9.0B - PostageStatementCreateResponse				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
PostageStatementCreateAccept Block begins			Either StatementID, UserPostageStatementID, TotalPostage, TotalPostageDue and ReturnInfo Block group or TrackingID and ReturnInfo Block group is submitted in the PostageStatement CreateAccept Block	
MailXMLPostageStatement ResponseHeaderInfo block	Attributes		Attributes block	See Appendix E for Details

Copyright © 2011 USPS®. All Rights Reserved.

Mail.XML 9.0B - PostageStatementCreateResponse				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
StatementID	Non-negative Integer		Required field; paired with UserPostageStatementID, TotalPostage, TotalPostageDue, and ReturnInfo block	
UserPostageStatementID	String, 10 characters		Optional field; paired with StatementID, TotalPostage, TotalPostageDue, and ReturnInfo block	
TotalPostage	Double		Two decimals Required field; paired with StatementID, UserPostageStatementID, TotalPostageDue, and ReturnInfo block	
TotalPostageDue	Double		Required field; paired with StatementID, UserPostageStatementID, TotalPostage and ReturnInfo block	
ReturnInfo Block	basicReturnInfoType		Optional block; paired with StatementID, UserPostageStatementID, TotalPostage, and TotalPostageDue	See Appendix E for Details
PostageStatementCreateAccept Block ends				
PostageStatementCreateReject Block begins			Response from USPS indicating that the PostageStatementCreateRequest message was rejected and a Postage Statement was not created and the reason why	

Copyright © 2011 USPS®. All Rights Reserved.

Mail.XML 9.0B - PostageStatementCreateResponse				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
CustomerGroupID	String, 25 characters		Required field; must be populated with the same value as the CustomerGroupID in the MailXMLPostageStatementRequestHeaderInfo block of the PostageStatement CreateRequest message	
MailXMLPostageStatement ResponseHeaderInfo block	MailXMLPostage StatementRespo nseHeaderInfo		Attributes block	See Appendix E for Details
ReturnInfo Block	basicReturnInfoT ype		Provides reason for return Required Multiple pairings of ReturnCode and ReturnDescription can be provided in the block	See Appendix E for Details
PostageStatementCreateR eject Block ends				

2.2.35 - PostageStatementCreateResponse

3.51 PostageStatementQueryResponse

Purpose
Accept or reject a request to create a combined mailing

Error/Return Codes
Refer Section 2.6 to view shared error/return codes and also a list of error/return codes tied this message.

Business Rules
- Will accept if PostageStatementID or TrackingID exists
- Will reject if PostageStatementID or TrackingID does not exist
- The ReturnInfo block will have a description for a Query Error

3.51.1 PostageStatementQueryResponse Data Structure

Field Description

Mail.XML 9.0B - PostageStatementQueryResponse				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**

Copyright © 2011 USPS®. All Rights Reserved.

Mail.XML 9.0B - PostageStatementQueryResponse				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
PostageStateQueryResponse Message BEGINS				
MailXMLPostageStatementResponseHeaderInfo Block	MailXMLPostageStatementResponseHeaderInfo		Attributes block	Refer this attribute in Appendix C
Sequence Block BEGINS				
TrackingID	String,12	-	Optional.	-
Choice Block BEGINS				
QueryResults Block begins				
PostageStatementData Block	postageStatementDataType		Required. Only 1 occurrence	Refer 'postageStatementDataType' complex in Appendix C
ReturnInfo Block	basicReturnInfoType		Optional	See Appendix C for Details
QueryResults Block ends				
QueryError Block begins				
ReturnInfo Block	basicReturnInfoType		Provides reason for return Required Multiple pairings of ReturnCode and ReturnDescription can be provided in the block	See Appendix C for Details
QueryError Block ends				
Choice Block ENDS				
Sequence Block ENDS				
PostageStatementQueryResponse Message ENDS				

2.2.36 - PostageStatementQueryResponse

3.52 PostageStatementQueryResponse

Purpose

Copyright © 2011 USPS®. All Rights Reserved.

Accept or reject a request to create a combined mailing

Error/Return Codes

Refer Section 2.6 to view shared error/return codes and also a list of error/return codes tied this message.

Business Rules

- Will accept if PostageStatementID or TrackingID exists
- Will reject if PostageStatementID or TrackingID does not exist
- The ReturnInfo block will have a description for a Query Error

3.52.1 PostageStatementQueryResponse Data Structure

Field Description

Mail.XML 9.0B - PostageStatementQueryResponse				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
MailXMLPostageStatement ResponseHeaderInfo Block begins	MailXMLPostage StatementRespo nseHeaderInfo		Attributes block	
QueryResults Block begins				
PostageStatementData Block begins	postageStatemen tDataType			
AgencyCostCode	agencyCostCode Type	Number 5 or 6 digits	Optional field, required for OI or OM government permit types	
AutomationAddressMatchD ate	Date	YYYY-MM-DD	Optional field; required for automation rate pieces The mailer must specify the date when the address list was generated.	
CustomerReferenceID	String, 40 characters		Optional	CustomerRe ferenceID represents CAPS Account Number
UserPostageStatementID	String, 10 characters		Optional	
CarrierRouteAddressMatch Date	Date	YYYY-MM-DD	Optional field; required for Carrier Route rate pieces	
CarrierRouteSequencingDa te	Date	YYYY-MM-DD	Optional field; required for Carrier Route rate pieces	
CertificationData Block	certificationData		Required	See

Copyright © 2011 USPS®. All Rights Reserved.

Mail.XML 9.0B - PostageStatementQueryResponse				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
begins	Type			Appendix A for Details
ContainerCount Block begins	containerCountType		Required block; at least one of the fields in this block must be populated with a nonzero value	
Trays2mm	Non-negative Integer		Optional field; Required if no other fields are populated with a nonzero value	
EnclosedBy	mailxml_base:enclosedByType	Refer 'enclosedByType' simple type	Optional Generated field	Refer Appendix B
DalPieces	Non-negative Integer		Optional Generated if Detached Address Labels	
ExtendedForm	Boolean	True, False	Required Generated according to PostageStatement CreateRequest data input	
FormType	Mailxml_base:formType	Refer 'formType' simple type	Required Generated according to PostageStatement CreateRequest data input	Refer Appendix B
LineItemSummaryData Block begins			Optional 1 to many can be generated for Extended form = False according to PostageStatement CreateRequest data input	
ProcessingCategory	Mailxml_base:processingCategoryType	Refer 'processingCategoryType' simple type	Required field Generated according to PostageStatement CreateRequest data input If FormType = BP, then the following values are valid: FL, NP, MP, IR	Refer Appendix B

Copyright © 2011 USPS®. All Rights Reserved.

Mail.XML 9.0B - PostageStatementQueryResponse				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
			If FormType = FC, then the following values are valid: LT, FL, CD, PF If FormType = ML, then the following values are valid: FL, NP, MP, IR If FormType = PM, then the following values are valid: LT, FL, PF If FormType = PP, then the following values are valid: MP, IR, NP If FormType = SM, then the following values are valid: LT, FL, MP, IR, NP, CM, NA, NB	
BarcodeRate	Mailxml_base:barcodeRateType	Refer 'barcodeRateType' simple type	Required Generated according to PostageStatementCreateRequest data input	
EntryDiscount	Mailxml_base:entryDiscountType	Refer 'entryDiscountType' simple type	Required Generated according to PostageStatementCreateRequest data input	Refer Appendix B
LineLabel	String, 80 characters		Optional	
LineNumber	String, 3 characters		Optional This field will be ignored if populated; LineNumber will only be taken into account for Full-Service discount lines	
PiecePostage	Double		Optional, up to four decimals	
PieceRate	Double		Optional, up to three decimals	
PostageAmount	Double		Required, up to four	

Copyright © 2011 USPS®. All Rights Reserved.

Mail.XML 9.0B - PostageStatementQueryResponse				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
			decimals	
PoundPostage	Double		Optional, up to four decimals	
PoundRate	Double		Optional, up to three decimals	
PreparedAsSM	Boolean	True, False	Required Generated according to PostageStatement CreateRequest data input The “True” indicates that mail is actually prepared as Standard when the RateCategory=S The “False” indicates that mail is actually prepared as First Class when the RateCategory=S	
RateCategory	Mailxml_base:rateCategoryType	Refer ‘rateCategoryType’ simple type	Required field If FormType = BP, then this field must be D, N, or S If FormType = FC, then this field must be E, H, L1, L2, L3, L4, N, or S If FormType = ML, then this field must be G, N, S If FormType = PM, then this field must be S If FormType = PP, then this field must be G, K, S, Z1, or Z2 If FormType = SM, then this field must be A, B, E, H, N, AF, BF, DF, L1, L2, L5, L6, L7, L8, NG,	Refer Appendix B

Copyright © 2011 USPS®. All Rights Reserved.

Mail.XML 9.0B - PostageStatementQueryResponse				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
			NK, N5, N6, PI, PM, P7, P8, PE, PQ, PR, PG, PK, P5, or P6	
Section	String, 1 character		Optional This field will be ignored if populated; Section will only be taken into account for Full-Service discount lines	
SurchargeType	Mailxml_base:surchargeType	Refer 'surchargeType' simple type	Required If FormType = BP, this field must be N If FormType = FC, this field must be A, E, N, or R If FormType = ML, this field must be N If FormType = PM, this field must be D, E, N, or P If FormType = PP, this field must be 2 or N If FormType = SM, this field must be L or N Generated according to PostageStatement CreateRequest data input	Refer Appendix B
TotalPieces	Non-negative Integer		Required Generated according to PostageStatement CreateRequest data input	
TotalWeight	Double		Optional The value of TotalWeight must be in Pounds.	
WeightBreakType	Mailxml_base:weightBreakType	Refer 'weightBreakTYp	Optional field If FormType is BP	Refer Appendix B

Copyright © 2011 USPS®. All Rights Reserved.

Mail.XML 9.0B - PostageStatementQueryResponse				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
		e' simple type	this field must be N. If FormType is FC this field must be A, B or N. If FormType is ML this field must be N. If FormType is PM this field must be N. If FormType is PP this field must be N. If FormType is SM this field must be A, B or H. Generated according to PostageStatement CreateRequest data input	
Zone	Mailxml_base:zoneICType	Refer 'zoneICType' simple type	Optional Generated according to PostageStatement CreateRequest data input	Refer Appendix B
FlatRateIndicator	Mailxml_base:flatRateIndicatorType	Refer 'flatRateIndicator Type' simple type	Optional Generated according to PostageStatement CreateRequest data input	Refer Appendix B
FullServiceParticipationIndicator	Mailxml_base:fspiType	Refer 'fspiType' simple type	Optional field, Generated according to PostageStatement CreateRequest data input	Refer Appendix B
SinglePieceDimensionalWeight	Double		Optional, required for balloon or oversize prices up to four decimals. The value of SinglePieceDimensionWeight must be in Pounds.	
LineItemSummaryData Block ends				
PostageStatementLineItem Data Block begins			Optional 1 to many can be generated for	

Copyright © 2011 USPS®. All Rights Reserved.

Mail.XML 9.0B - PostageStatementQueryResponse				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
			Extended form =True according to PostageStatement CreateRequest data input	
ProcessingCategory	Mailxml_base:processingCategoryType	Refer 'processingCategoryType' simple type	Optional Generated according to PostageStatement CreateRequest data input	Refer Appendix B
BarcodeRate	Mailxml_base:barcodeRateType	Refer 'barcodeRateType' simple type	Required Generated according to PostageStatement CreateRequest data input	Refer Appendix B
ContainerDisplayName	String, 50 characters		Optional	
ContainerID	String, 6 characters		Optional	
EntryDiscount	Mailxml_base:entryDiscountType	Refer 'entryDiscountType' simple type	Required	Refer Appendix B
EntryFacilityType	Mailxml_base:entryFacilityType	Refer 'entryFacilityType' simple type	Optional	Refer Appendix B
EntryZip	Mailxml_base:zipCodeThreeOrFiveDigit	Refer 'zipCodeThreeDigitOrFiveDigit' simple type	Optional	Refer Appendix B
Heavy Letter	Boolean	True, False	Required	
LineLabel	String, 80 characters		Optional	
LineNumber	String, 3 characters		Optional This field will be ignored if populated; LineNumber will only be taken into account for Full-Service discount lines	
PieceRate	Double		Optional, up to three decimals	
PostageAmount	Decimal		Optional up to four decimals	

Copyright © 2011 USPS®. All Rights Reserved.

Mail.XML 9.0B - PostageStatementQueryResponse				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
PoundRate	Decimal		Optional up to three decimals	
PreparedAsSM	Boolean	True, False	Required The “True” indicates that mail is actually prepared as Standard when the RateCategory=S The “False” indicates that mail is actually prepared as First Class when the RateCategory=S	
RateCategory	Mailxml_base:rateCategoryType	Refer ‘rateCategoryType’ simple type	Required field If FormType = BP, then this field must be D, N, or S If FormType = FC, then this field must be E, H, L1, L2, L3, L4, N, or S If FormType = ML, then this field must be G, N, S If FormType = PM, then this field must be S If FormType = PP, then this field must be G, K, S, Z1, or Z2 If FormType = SM, then this field must be A, B, E, H, N, AF, BF, DF, L1, L2, L5, L6, L7, L8, NG, NK, N5, N6, PI, PM, P7, P8, PE, PQ, PR, PG, PK, P5, or P6	Refer Appendix B
Section	String, 1 character		Optional This field will be ignored if	

Copyright © 2011 USPS®. All Rights Reserved.

Mail.XML 9.0B - PostageStatementQueryResponse				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
			populated; Section will only be taken into account for Full-Service discount lines	
SinglePieceWeight	Double		Required up to four decimals The value of SinglePieceWeight must be in Pounds.	
SurchargeType	Mailxml_base:surchargeType	Refer 'surchargeType' simple type	Required If FormType = BP, this field must be N If FormType = FC, this field must be A, E, N, or R If FormType = ML, this field must be N If FormType = PM, this field must be D, E, N, or P If FormType = PP, this field must be 2 or N If FormType = SM, this field must be L or N	Refer Appendix B
TotalPieces	Non-negative Integer		Required	
TotalWeight	Double		Optional The value of TotalWeight must be in Pounds.	
Zone	Mailxml_base:zoneICType	Refer 'zoneICType' simple type	Optional	Refer Appendix B
VersionID	String, 10 characters		Optional	
ContainerType	Mailxml_base:mailXMLContainerType	Refer 'mailXMLContainerType' simple type	Optional field	Refer Appendix B
FlatRateIndicator	Mailxml_base:flatRateIndicatorType	Refer 'flatRateIndicatorType' simple type	Optional	Refer Appendix B

Copyright © 2011 USPS®. All Rights Reserved.

Mail.XML 9.0B - PostageStatementQueryResponse				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
FullServiceParticipationIndicator	Mailxml_base:fspiType	Refer 'fspiType' simple type	Optional Generated according to postage statement input.	Refer Appendix B
SinglePieceDimensionalWeight	Double		Optional, required for balloon or oversize prices up to four decimals. The value of SinglePieceDimensionWeight must be in Pounds.	
PostageStatementLineItem Data Block ends				
PostageStatementMailingDate	Date	YYYY-MM-DD	Required It may be up to one year in future or back dated to most recent price change	
PackagingMethod	packagingMethodType	0 = Piece Count 1 = Weight 2 = Both	Optional	
PostageAffixedAmount	Double		Optional up to three decimals	
PostagePaymentMethod	Mailxml_base:postagePaymentMethodType	Refer 'packagingPaymentMethodType' simple type	Required	Refer Appendix B
ProcessingCategory	Mailxml_base:processingCategoryType	Refer 'processingCategoryType' simple type	Required	Refer Appendix B
RateType	Mailxml_base:rateType	Refer 'rateType' simple type	Required	Refer Appendix B
RegisterOfMailing	Boolean	True, False	Required	
SackingBasis	Mailxml_base:sackingBasisType	Refer 'sackingBasisType' simple type	Optional	Refer Appendix B
SinglePieceWeight	Double		Required up to four decimal places The value of SinglePieceWeight must be in Pounds.	
ExtraServiceData Block begins			Optional 0 to many can be generated	

Copyright © 2011 USPS®. All Rights Reserved.

Mail.XML 9.0B - PostageStatementQueryResponse				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
			according to postage statement input	
ServiceCode	Mailxml_base:serviceCodeType	Refer 'serviceCodeType' simple type	Required	Refer Appendix B
ServiceRate	Double		Optional up to three decimals	
ServiceSubCode	Mailxml_base:serviceSubCodeType	Refer 'serviceSubCodeType' simple type	Required	Refer Appendix B
ServiceValue	Double		Required up to three decimals	
TotalAmount	Double		Optional up to three decimals	
TotalPieces	Non-negative Integer		Required	
ExtraServiceData Block ends				
ExtraServiceSummaryData Block begins			Optional 0 to many can be submitted	
LineLabel	String, 80 characters		Optional	
LineNumber	String, 3 characters		Optional This field will be ignored if populated; LineNumber will only be taken into account for Full-Service discount lines	
Section	String, 1 character		Optional This field will be ignored if populated; Section will only be taken into account for Full-Service discount lines	
ServiceCode	Mailxml_base:serviceCodeType	Refer 'serviceCodeType' simple type	Required	Refer Appendix B
TotalAmount	Double		Required up to three decimal	

Copyright © 2011 USPS®. All Rights Reserved.

Mail.XML 9.0B - PostageStatementQueryResponse				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
			places	
TotalPieces	Non-negative Integer		Required	
ExtraServiceSummaryDataends				
StatementSequenceNumber	String, 20 characters		Optional	
RepositionableNotesIndicator	Boolean		Required	
DocumentVersionDataBlock	DocumentVersionData		Optional 0 to many can be submitted	See Appendix E
MeteredAffixedMethod	Mailxm_base:meteredAffixedMethodType	–Refer 'meteredAffixedMethodType' simple type	Optional	Refer Appendix B
CombinedMailingID	Non-negative Integer		Optional field; required for combined mailings	
SinglePieceDimensionalWeight	Double		Optional up to four decimal places. The value of SinglePieceDimensionWeight must be in Pounds.	
EnclosingVolumeNo	String, 5 characters		Optional	
EnclosingIssueNo	String, 6 characters		Optional	
EnclosingIssueDate	Date	YYYY-MM-DD	Optional	
PriceType	priceType	commercial,commercialplus	Optional	
MoveUpdateMethod	Mailxml_base:moveUpdateMethodType	Refer 'moveUpdateMethodType' simple type	Optional	Refer Appendix B
StatementID	Non-negative integer		Optional	
MailClass	mailClassType		Required	
Origin	String		Optional	
SpecialFeesAmount	Double		Required	
PostageStatementStatus	postageStatementStatusType	See Appendix A for Details for values	Optional	See Appendix A for Details for values
TotalPieces	Non-negative integer		Required	

Copyright © 2011 USPS®. All Rights Reserved.

Mail.XML 9.0B - PostageStatementQueryResponse				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
TotalPostageAmount	Double		Required up to two decimal places	
TotalPostageAmountDue	Double		Required up to two decimal places, may be 0.00.	
TotalWeight	Double		Required The value of TotalWeight must be in Pounds.	
PermitHolderData Block	mailerDataType		Required	See Appendix E for Details
MailingOwnerData Block	mailerDataType		Optional	See Appendix E for Details
MailingAgentData Block	mailerDataType		Required	See Appendix
PermitHolderForAPData Block begins	mailerDataType		Optional	See Appendix
ReturnInfo Block	basicReturnInfoType			See Appendix E for Details
QueryResults Block ends				
QueryError Block begins				
ReturnInfo Block	basicReturnInfoType		Provides reason for return Required Multiple pairings of ReturnCode and ReturnDescription can be provided in the block	See Appendix E for Details
QueryError Block ends				

2.2.37 - PostageStatementQueryResponse

3.53 PostageStatementStatusQueryRequest

Purpose
Used to query the status of a postage statement

Business Rules

- Must be submitted after a postage statement has been created
- Beginning in Release 26.1, First-Class Commerical Plus Parcels will be accepted after the April 2011 price change date when the following conditions are met:
    - FormType in the CreatePostageStatement block is FC (First-Class)
    - PresentationCategory in the CreatePostageStatement block is PF (Parcel, First-Class)
    - PriceType in the CreatePostageStatement block is commercialplus

Copyright © 2011 USPS®. All Rights Reserved.

3.53.1 PostageStatementStatusQueryRequest data Structure

Field Description

Mail.XML 9.0B - PostageStatementStatusQueryRequest				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
MailXMLDashboardHeaderInfo Block	Complex		Attributes block	
SubmittingParty			Required block; Identifies the customer submitting the message	
SubmittingSoftware			Required block; Identifies the software submitting the message	
StatementID	Non-negative Integer		Required if the TrackingID is not provided	
IncludeChildStatement	yesNo	Yes, No	Optional, only used for Periodicals Consolidated postage statements. If yes, the child statements will be returned in the response, else child statements will not be returned.	

2.2.38 - PostageStatementStatusQueryRequest

3.54 PostageStatementStatusQueryResponse

Purpose
Accept or reject a query for postage statement status

Error/Return Codes
Refer Section 2.6 to view shared error/return codes and also a list of error/return codes tied this message.

Business Rules
- Will accept if postage statement exists in the mailing group
- Will reject if postage statement does not exist in the mailing group
- The ReturnInfo block will have a description for a QueryError

3.54.1 PostageStatementStatusQueryResponse Data Structure

Field Description

Copyright © 2011 USPS®. All Rights Reserved.

Mail.XML 9.0B - PostageStatementStatusQueryResponse				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
MailXMLDashboardHeaderInfo Block	Attributes		Attributes block	See Appendix E for Details
QueryResults Block begins				
MailingGroup Block begins			Optional 0 to many can be submitted	
MailingGroup Block begins			Optional, only one may be submitted	
CustomerDescription	String, 50 characters		Optional	
SubmitterCRID	CRIDType		Required	
PermitPublicationData Block begins	permitPublicationDataType		Required	See Appendix E for Details
PostOfficeOfMailingZip	String, 5 characters		Required	
MailingFacility	CRIDType		Optional	
MailXMLPresentationCategory	Mailxml_base:mailXMLPresentationCategoryType	Refer 'mailXMLPresentationCategoryType' simple type	Required	Refer Appendix B
MailerID	String, 9 characters		Optional	
FullServiceParticipationIndicator	Mailxml_base:fspiType	Refer 'fspiType' simple type	Optional	Refer Appendix B
MailAgreementType	Mailxml_base:mailAgreementTypeType	Refer 'mailAgreementTypeType' simple type	Optional	Refer Appendix B
ContractNumber	String, 20 characters		Optional	
OnePassIndicator	String, 3 characters	Yes, No	Optional	
LogicalPhysicalContainerIndicator	Mailxml_base:logicalPhysicalContainerIndicatorType	Refer 'logicalPhysicalContainerIndicatorType' simple type	Optional	Refer Appendix B
MailingGroup Block ends				
~~UserPostageStatementID~~	~~String, 10 characters~~	-	~~Optional~~	
PostageStatementSummary Block begins			Required 1 to many can be submitted	
StatementID	Non-negative Integer		Optional	
UserPostageStatementID	String, 10 characters		Optional	

Copyright © 2011 USPS®. All Rights Reserved.

Mail.XML 9.0B - PostageStatementStatusQueryResponse				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
UserPostageStatementSequenceID	Numeric String 10		Optional	
USPSPostageStatementSequenceNumber	Numeric String, 10 characters		Optional	
PostageStatementStatus	String, 15 characters	See Appendix A for Details for values	Required	
PostageStatementSummary Block ends				
ReturnInfo Block	basicReturnInfoType		Provides reason for return Optional Multiple pairings of ReturnCode and ReturnDescription can be provided in the block	See Appendix E for Details
QueryResults Block ends				
QueryError Block begins				
ReturnInfo Block	ReturnInfo		Provides reason for return Required Multiple pairings of ReturnCode and ReturnDescription can be provided in the block	See Appendix E for Details
QueryError Block ends				

2.2.39 - PostageStatementStatusQueryResponse

3.55 QualificationReportCreateRequest

Purpose
The Qualification Report is used to submit standardized documentation compliant with the DMM 708.1. A mailing group may have multiple qualification reports.

Business Rules

- Cannot be sent until an OpenMailingGroupRequest message has been sent and accepted
- No updates can be made to the QualificationReportCreateRequest message. Beginning with Release 24, transportation updates can be submitted via the Mail.XML ContainerUpdateRequest message for certain business scenarios that require container update, such as logical mailings.
- Changes to a Qualification Report can be made when the customer closes a mailing group through the CloseMailingGroupRequest message and opens a new mailing group with the OpenMailingGroupRequest message
- QualificationReportCreateRequest message must be accepted before the BundleDetailCreateRequest message can be sent.
- Qualification report data cannot be used to send transportation data to the FAST system

Copyright © 2011 USPS®. All Rights Reserved.

- Beginning in Release 26.0.0, FormType PM for Priority Mail is not supported after the January 2, 2011 price change date.
- Beginning in Release 26.0.0, FormType PP for Package Services Parcel Post is not supported after the January 2, 2011 price change date.
- Beginning in Release 26.0.0, Standard Mail Parcels are not supported for 7.0 and 8.0 version files that are submitted after the January 2, 2011 price change date.
- Beginning in Release 26.0.0, Rate Categories AF, BF, DF, GF, and KF are not supported for First-Class Mail, Standard Mail, or Periodicals submitted after the January 2, 2011 price changed.
- Beginning in Release 26.0.0, the ProcessingCategory cannot be populated with NA or NB for Standard Mail submitted after the January 2, 1011 price change date.
- Beginning in Release 26.0.0, the ProcessingCategory field cannot be populated with IR for Bound Printed Matter Package Service mailings submitted after the January 2, 2011 price change date
  - Beginning in Release 26.1, First-Class Commercial Plus Parcels will be accepted after the April 2011 price change date when the following conditions are met:
    - FormType in the CreatePostageStatement block is FC (First-Class)
    - PresentationCategory in the CreatePostageStatement block is PF (Parcel, First-Class)
    - PriceType in the CreatePostageStatement block is commercialplus
- Beginning in Release 27.0, the ContainerType F (Flat Tubs) will be accepted for tray based copalletization of for First-Class Mail or Standard Mail.
  - Beginning in Release 27.0, the new MobileBarcode USPSPriceIncentiveType will be accepted for First-Class Mail and Standard Mail. The MobileBarcode USPSPriceIncentiveType will be accepted for Regular and Non-Profit Standard Mail
  - The PermitType field must be set to PI (PermitImprint) for the MoibileBarcode USPSPriceIncentiveType
  - The ProcessingCategory must be set to LT (Letters), CD (Cards), or FL (Flats) for the MobileBarcode USPSPriceIncentiveType
- The PostageStatementMailingData must be set to a date in between July 1, 2011 and August 31, 2011 for the MobileBarcode USPSPriceIncentiveType
- Beginning in Release 28.0.0, the CSADispatchNumber field in the ContainerInfoData block will be ignored
- Beginning in Release 28.0.0, the *PostalOne!* system will ignore the QualificationReportCreateRequest message if it is submitted after the PeriodicalStatementCreateRequest or ConsolidatedPeriodicalStatementCreateRequest and the AdPercent field in the DocumentVersionDataWithPermit block does not match the AdPercent of the previously submitted PeriodicalStatementCreateRequest or ConsolidatedPeriodicalStatementCreateRequest.
- Beginning in Release 28.0.0, the *PostalOne!* system will ignore the QualificationReportCreateRequest message if it is submitted after the PeriodicalStatementCreateRequest or ConsolidatedPeriodicalStatementCreateRequest and the PieceWeight field in the DocumentVersionDataWithPermit block does not match the PieceWeight of the previously submitted PeriodicalStatementCreateRequest or ConsolidatedPeriodicalStatementCreateRequest.

3.55.1 QualificationReportCreateRequest Data Structure

Field Description

Mail.XML 9.0B - QualificationReportCreateRequest				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
QualificationReportCreateR				

Copyright © 2011 USPS®. All Rights Reserved.

Mail.XML 9.0B - QualificationReportCreateRequest				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
equest Message BEGINS				
MailXMLQualReportRequestHeaderInfo block begins			Attributes block; 0 to 1	
CustomerGroupID	String, 25 characters		Required field; must be populated with the same value as the CustomerGroupID in the OpenMailingGroup Request message	
MailingGroupID	Non-Negative Integer		Required field; must be populated with the same value as the MailingGroupID in the OpenMailingGroup Request message	
Replace	Mailxml_base:yes No	Yes No	Optional field	
MixedMailFlag	Mailxml_base:yes No	Yes or No	Required to identify the mixed mailing.	-
MailXMLQualReportRequestHeaderInfo block ends				
SubmittingParty Block	ParticipantIDType		Required block; Identifies the customer submitting the message	Refer 'ParticipantID Type' complex type in Appendix C.
SubmittingSoftware Block	SubmittingSoftwareType		Required block; Identifies the software submitting the message	Refer 'SubmittingSoftware' complex type in Appendix C.
OnePassPlannedOrActualFlag	Mailxml_base:onePassPlannedOrActualFlagType	A = Actual P = Planned	Optional field. Must submit a Qualification Report with this field set to P before submitting one with this field set to A.	Refer Appendix B for the complete list of accepted values
QualificationReport block	qualificationRepo	Complex Type	Required block;	Refer

Copyright © 2011 USPS®. All Rights Reserved.

Mail.XML 9.0B - QualificationReportCreateRequest				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
	rtDataType		contains the values necessary to populate a Qualification Report	"qualification ReportData Type" complex in Appendix C
QualificationReportCreateRequest Message ENDS				

2.2.40 - QualificationReportCreateRequest

3.56 QualificationReportCreateResponse

Purpose
The QualificationReportCreateResponse will be used by USPS to notify the customer if their request to create a qualification report has been accepted or rejected.

Error/Return Codes
Refer Section 2.6 to view shared error/return codes and also a list of error/return codes tied this message.

Business Rules
- Must be returned to the customer after the QualificationReportCreateRequest message is sent by the customer to *PostalOne!*
- OpenMailingGroupResponse must respond with an accept block
- PermitNumber must map back to FinanceNumber
- TotalCopies can be greater that the TotalPieces in the same messages for periodical using Firm Bundles
- Version ID must exist in DocumentVersionDataWithPermit

3.56.1 QualificationReportCreateResponse Data Structure

Field Description

Mail.XML 9.0B - QualificationReportCreateResponse				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
QualificationReportCreateAccept block begins			Response from USPS indicating that the QualificationReport CreateRequest message was accepted and a Qualification Report	

Copyright © 2011 USPS®. All Rights Reserved.

Mail.XML 9.0B - QualificationReportCreateResponse				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
			was created	
MailXMLQualReportResponseHeaderInfo block begins			Attributes block	
CustomerGroupID	String, 25 characters		Required field; must be populated with the same value as the CustomerGroupID in the MailXMLQualReportRequestHeaderInfo block of the QualificationReportCreateRequest message	
MailingGroupID	Non-negative integer		Required field; must be populated with the same value as the MailingGroupID in the MailXMLQualReportRequestHeaderInfo block of the QualificationReportCreateRequest message	
MailXMLQualReportResponseHeaderInfo block ends			End of block	
CustomerQualificationReportID	String, 66 characters		Optional field	
ReturnInfo block	ReturnInfo		Optional block	See Appendix E for Details
QualificationReportCreateAccept block ends			End of block	
QualificationReportCreateReject block begins			Response from USPS indicating that the QualificationReportCreateRequest message was rejected and a Qualification Report was not created and the reason why	
MailXMLQualReportResponseHeaderInfo block begins			Attributes block	
CustomerGroupID	String, 25 characters		Required field; must be populated	

Copyright © 2011 USPS®. All Rights Reserved.

Mail.XML 9.0B - QualificationReportCreateResponse				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
			with the same value as the CustomerGroupID in the MailXMLQualReportRequestHeaderInfo block of the QualificationReportCreateRequest message	
MailingGroupID	Non-negative integer		Required field; must be populated with the same value as the MailingGroupID in the MailXMLQualReportRequestHeaderInfo block of the QualificationReportCreateRequest message	
MailXMLQualReportResponseHeaderInfo block ends			End of block	
ReturnInfo block	ReturnInfo		Required block	See Appendix E for Details
QualificationReportCreateReject block ends			End of block	

2.2.41 - QualificationReportCreateResponse

3.57 QualificationReportQueryRequest

Purpose
This message should be sent when customer would like to request the qualification Report.

Business Rules
- Cannot be sent until the QualificationReportCreateRequest has been successful.

3.57.1 QualificationReportQueryRequest Data Structure

Field Description

Mail.XML 9.0B - QualificationReportQueryRequest				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
QualificationReportQueryRequest				

Copyright © 2011 USPS®. All Rights Reserved.

Mail.XML 9.0B - QualificationReportQueryRequest				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
Message BEGINS				
MailXMLMessageHeaderInfo block begins			Attributes block	
CustomerGroupID	String, 25 characters		Required field	
MailingGroupID	Non-Negative Integer		Required field	
MailXMLMessageHeaderInfo block ends				
Sequence Block BEGINS				
SubmittingParty	participantIDType	-	Required	Refer Appendix C
SubmittingSoftware	submittingSoftwareType	-	Required	Refer Appendix C
MailingFacility	Mailxml_base:CRIDType	Simple type	Required	Refer “CRIDType” simple type in Appendix B
PostageStatementStatus	Mailxml_base:postageStatementStatusType	Simple Type	Optional	Refer this simple type in Appendix C
QualificationReportClass	Mailxml_base:qualificationReportClassType	Simple Type	Optional	Refer this simple type in Appendix C
CustomerQualificationReportID	String, 66	-	Optional	
BeginDate	Date/Time	-	Optional	-
EndDate	Date/Time	-	Optional	-
Preparer Block	permitPublicationDataType	Complex Type	Optional	Refer this complex type in Appendix C
PermitHolder Block	permitPublicationDataType	Complex Type	Optional	Refer this complex type in Appendix C
IssueBeginDate	Date/Time	-	Optional	-
IssueEndDate	Date/Time	-	Optional	-
IssueNumber	String, 6	-	Optional	-
VolumeNumber	String, 5	-	Optional	-

Copyright © 2011 USPS®. All Rights Reserved.

Mail.XML 9.0B - QualificationReportQueryRequest				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
DestinationFacilityZip	String, 9	Up to nine digit zip code of the destination facility	Required	
Sequence Block ENDS				
QualificationReportQueryRequest Message ENDS				

2.2.42 - QualificationReportQueryRequest

3.58 QualificationReportQueryResponse

Purpose
This is a response message returned from USPS to the requester who sends the QualificationReportQueryRequest message.

Business Rules
- Cannot be sent until QualificationReportQueryRequest message is received
- USPS collects the data based on the QueryRequest and return all data in this message.

3.58.1 QualificationReportQueryResponse Data Structure

Field Description

Mail.XML 9.0B - QualificationReportQueryResponse				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
QualificationReportQueryResponse Message BEGINS				
MailXMLMessageHeaderInfo block begins			Attributes block	
CustomerGroupID	String, 25 characters		Required field	
MailingGroupID	Non-Negative Integer		Required field	
MailXMLMessageHeaderInfo block ends				
Sequence Block BEGINS				
TrackingID	String, 12	-	Optional. Returns the	

Copyright © 2011 USPS®. All Rights Reserved.

Mail.XML 9.0B - QualificationReportQueryResponse				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
			tracking ID when an error is occurred or when message is too large and request cannot be completed	
Choice Block BEGINS				
QueryResult Block BEGINS	-	-	Required Block	
Sequence Block BEGINS				
QualificationReport block	qualificationReportDataType	Complex Type	Required block; contains the values necessary to populate a Qualification Report	Refer "qualification ReportData Type" complex in Appendix C
ReturnInfo	basicReturnInfoType	-	Optional Block Allow 0 to many occurrence	Refer "ReturnInfo" or "basicReturnInfoData" block in Appendix C
Sequence Block ENDS				
QueryResults block ENDS				
QueryError Block BEGINS			Required Block	
ReturnInfo	basicReturnInfoType		Required block when error occurs	Refer "ReturnInfo" or "basicReturnInfoData" block in Appendix C
Choice Block ENDS				
Sequence Block ENDS				
QualificationReportQueryResponse Message ENDS				

2.2.43 - QualificationReportQueryResponse

Copyright © 2011 USPS®. All Rights Reserved.

3.59 ReconciliationReportQueryRequest

The customer cannot update the Qualification report once filed. After the customer goes through the process of printing and delivering the mail to the USPS, the Reconciliation report is created that shows how much mail was planned and how much was mailed. In the ReconciliationReportQueryRequest, the customer is required to provide the mailing group ID and Customer group ID besides the mandatory elements of Submitting party and Submitting software.

3.59.1 ReconciliationReportQueryRequest Data Structure

Field Description

Mail.XML 9.0B - ReconciliationReportQueryRequest				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
MailXMLDashboardtHeaderInfo block Opens				
CustomerGroupID	String, 25 characters		Required (attribute)	
MailingGroupID	Non Negative Integer		Required (attribute)	
MailXMLDashboardtHeaderInfo block Closes				
SubmittingParty	ParticipantIDType		Identifies the customer submitting the message	Refer 'ParticipantID Type' complex type in Appendix D.
SubmittingSoftware	SubmittingSoftwareType		Identifies the software submitting the message	Refer 'SubmittingSoftware' complex type in Appendix D.
QualificationReportClass	mailxml_base:qualificationReportClassType	Refer 'qualificationReportClassType' simple type	Optional	Refer Appendix B
BeginDate	DateTime	YYYY-MM-DDTHH:MM:SS	Optional	
EndDate	DateTime	YYYY-MM-DDTHH:MM:SS	Optional	
Preparer Block Opens				
PermitNumber	String, 8 characters		Optional	
PermitType	mailxml_base:permitTypeType	Refer 'permitTypeType' simple type	Optional	Refer Appendix B
PermitZip4	Number, 9 digits		Optional	
PublicationNumber	Number, 9 digits		Optional	

Copyright © 2011 USPS®. All Rights Reserved.

Mail.XML 9.0B - ReconciliationReportQueryRequest				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
Preparer Block Closes				
PermitHolder Block Opens				
PermitNumber	String, 8 characters		Optional	
PermitType	mailxml_base:permitTypeType	Refer 'permitTypeTYpe' simple type	Optional	Refer Appendix B
PermitZip4	Number, 9 digits		Optional	
PublicationNumber	Number, 9 digits		Optional	
PermitHolder Block Closes				
IssueBeginDate	DateTime	YYYY-MM-DDTHH:MM:SS	Optional	
IssueEndDate	DateTime	YYYY-MM-DDTHH:MM:SS	Optional	
IssueNumber	String, 6		Optional	
VolumeNumber	String, 5		Optional	

2.2.44 - ReconciliationReportQueryRequest

3.60 ReconciliationReportQueryResponse

In the ReconciliationReportQueryResponse message the *PostalOne!* system responds back with a reconciliation report for every qualification report within the Job/mailing group. The USPS responds back with one Mailing Group Summary and one or more Reconciliation Summary reports. The message also includes an optional Return Code and description. If there are issues, the USPS responds back with the Query Error block and provides one or more Return codes and descriptions to explain the errors.

3.60.1 ReconciliationReportQueryResponse Data Structure

Field Description

Mail.XML 9.0B - ReconciliationReportQueryResponse				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
MailXMLDashboardtHeader Info block Opens				
CustomerGroupID	String, 25 characters		Required (attribute)	
MailingGroupID	Non Negative Integer		Required (attribute)	
MailXMLDashboardtHeader Info block Closes				
QueryResults Block Opens				
MailingGroupSummary block Opens				

Copyright © 2011 USPS®. All Rights Reserved.

Mail.XML 9.0B - ReconciliationReportQueryResponse				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
MailerJobID	String, 12 characters		Optional	
BeginDate	DateTime	YYYY-MM-DDTHH:MM:SS	Optional	
EndDate	DateTime	YYYY-MM-DDTHH:MM:SS	Optional	
OpenDate	DateTime	YYYY-MM-DDTHH:MM:SS	Optional	
CloseDate	DateTime	YYYY-MM-DDTHH:MM:SS	Optional	
PreparerName	String		Optional	
PreparerCRID	String, 15 characters		Optional	
Origin	String		Optional	
Description	String		Optional	
MailingGroupSummary block Closes				
QualificationSummaryReport block Opens				
RateCategory	mailxml_base:rateCategoryType	Refer 'rateCategoryType' simple type	Optional	Refer Appendix B
Pieces	Non Negative Integer		Optional	
ClosedPieces	Non Negative Integer		Optional	
FormType	mailxml_base:formType	Refer 'formTYpe' simple type	Optional	Refer Appendix B
TotalPieces	Non Negative Integer		Optional	
TotalClosedPieces	Non Negative Integer		Optional	
PostageStatements block Opens				
Line	String, 2 characters		Optional	
USPSProcessingDue block Opens				
Pieces	Non Negative Integer		Optional	
Postage	Decimal		Optional	
TotalPieces	Non Negative Integer		Optional	
TotalPostage	Decimal		Optional	

Copyright © 2011 USPS®. All Rights Reserved.

Mail.XML 9.0B - ReconciliationReportQueryResponse				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
USPSProcessingDue block Closes				
Finalize block Opens				
Pieces	Non Negative Integer		Optional	
Postage	Decimal		Optional	
TotalPieces	Non Negative Integer		Optional	
TotalPostage	Decimal		Optional	
Finalize block Closes				
PostageStatements block Closes				
QualificationSummaryReport block Closes				
ReconciliationReport block Opens				
OriginalPieces	Non Negative Integer		Optional	
ActualPieces	Non Negative Integer		Optional	
Postage	Decimal		Optional	
ClosedContainer block Opens				
OriginalPieces	Non Negative Integer		Optional	
ActualPieces	Non Negative Integer		Optional	
Postage	Decimal		Optional	
ClosedContainer block Closes				
PostageStatementCanceled block Opens				
OriginalPieces	Non Negative Integer		Optional	
ActualPieces	Non Negative Integer		Optional	
Postage	Decimal		Optional	
PostageStatementCanceled Closes				
PostageStatementUSPSProcessingDue block Opens				
OriginalPieces	Non Negative Integer		Optional	
ActualPieces	Non Negative Integer		Optional	
Postage	Decimal		Optional	
PostageStatementUSPSPr				

Copyright © 2011 USPS®. All Rights Reserved.

Mail.XML 9.0B - ReconciliationReportQueryResponse				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
ocessingDue block Closes				
PostageStatementReworked block Opens				
OriginalPieces	Non Negative Integer		Optional	
ActualPieces	Non Negative Integer		Optional	
Postage	Decimal		Optional	
PostageStatementReworked block Closes				
PostageStatementFinalized block Opens				
OriginalPieces	Non Negative Integer		Optional	
ActualPieces	Non Negative Integer		Optional	
Postage	Decimal		Optional	
PostageStatementFinalized block Closes				
PostageStatementReversed block Opens				
OriginalPieces	Non Negative Integer		Optional	
ActualPieces	Non Negative Integer		Optional	
Postage	Decimal		Optional	
PostageStatementReversed block Closes				
PostageStatementNotAvailable block Opens				
OriginalPieces	Non Negative Integer		Optional	
ActualPieces	Non Negative Integer		Optional	
Postage	Decimal		Optional	
PostageStatementNotAvailable block Closes				
TotalPieces	Non Negative Integer		Optional	
TotalActualPieces	Non Negative Integer		Optional	
TotalPostage	Decimal		Optional	
ReconciliationReport block Closes				
ReturnInfo	ReturnInfo			Refer 'ReturnInfo' complex type in Appendix

Copyright © 2011 USPS®. All Rights Reserved.

Mail.XML 9.0B - ReconciliationReportQueryResponse				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
				D.
QueryResults Block Closes				
QueryError Block Opens				
ReturnInfo	ReturnInfo			Refer 'ReturnInfo' complex type in Appendix D.
QueryError Block Closes				

2.2.45 - ReconciliationReportQueryResponse

3.61 SiblingContainerCancelRequest

Purpose
Cancel sibling containers that are tied to the original container and are not necessary

Business Rules

- Must have previously provided the original container information and the sibling container information to the *PostalOne!* system
- ContainerIDs deleted may NOT be reused within a mailing group
- Customer will be allowed to remove one or more sibling containers from a single original container through a single SiblingContainerCancelRequest message
- The system validates that one or more sibling containers are sent with unique barcodes for cancellation/deletion if the original container is a Full-Service, Mixed Full-Service, or Basic container and that it does not belong to an MLOCR category
- Sibling containers submitted through Mail.dat or Mail.XML can be cancelled through the SiblingContainerCancelRequest message
- Cannot remove a sibling container that is in Ready to Pay status
- Cannot remove logical containers with ContainerType L, V, or M

3.61.1 SiblingContainerCancelRequest Data Structure

Field Description

Mail.XML 9.0B - SiblingContainerCancelRequest				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
SubmittingParty Block	ParticipantIDType		Required block; Identifies the customer submitting the message	Refer 'ParticipantID Type' complex type in Appendix E.
SubmittingSoftware Block	SubmittingSoftwareType		Required block; Identifies the software submitting	Refer 'SubmittingSoftware'

Copyright © 2011 USPS®. All Rights Reserved.

Mail.XML 9.0B - SiblingContainerCancelRequest				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
			the message	complex type in Appendix E.
OriginalContainer Block	FullContainerIDType		Required field;	See Appendix E for Details
SiblingToDelete Block	FullContainerIDType		Required field;	See Appendix E for Details

2.2.46 - SiblingContainerCancelRequest

3.62 SiblingContainerCancelResponse

Purpose
Responds to the customer's request to determine if the sibling containers can be cancelled

Error/Return Codes
Refer Section 2.6 to view shared error/return codes and also a list of error/return codes tied this message.

Business Rules

- Must be returned to the customer after the SiblingContainerCancelRequest message is sent by the customer to *PostalOne!*
- Will reject if any of the containers have been finalized
- Will reject if original container information does not exist in *PostalOne!* system
- SiblingContainerCreateRequest must be accepted for the specific CRID if the sibling container is created through Mail.XML
- Sibling to be deleted must tie to an existing sibling container in the *PostalOne!* database
- Original container must be tied to an existing original container in the *PostalOne!* database
- Sibling to be deleted and the original container must be on a postage statement with UPD status for USPS Processing Due
- Sibling to be deleted and the original container cannot be on a postage statement with FIN status for Finalized or FPP status for Finalized Pending Payment

3.62.1 SiblingContainerCancelResponse Data Structure

Field Description

Mail.XML 9.0B - SiblingContainerCancelResponse				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
SIblingContainerCancelAccept Block begins			Response from USPS indicating that the SiblingContainerCancelRequest message was accepted	

Copyright © 2011 USPS®. All Rights Reserved.

Mail.XML 9.0B - SiblingContainerCancelResponse				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
CancelledSiblingContainer Block	FullContainerIDT ype		Required field;	See Appendix E for Details
ReturnInfo Block	ReturnInfo		Required field;	See Appendix A for Details
SIblingContainerCancelAcc ept block ends			End of block	
SiblingContainerCancelReje ct block begins			Response from USPS indicating that the SiblingContainerCa ncelRequest message was rejected	
CancelledSiblingContainer block	FullContainerIDT ype			See Appendix E for Details
SiblingToDelete Block	FullContainerIDT ype		Required field;	See Appendix A for Details
ReturnInfo Block	ReturnInfo		Required field;	See Appendix A for Details
SiblingContainerCancelReje ct block ends			End of block	

2.2.47 - SiblingContainerCancelResponse

3.63 SiblingContainerCreateRequest

Purpose
Message allows customers to add sibling containers to original containers when a container in the mailing cannot support all mail pieces/handling units. The same message is used for Mail.XML Qualification data update when adding physical containers and handling units for Logical containers and handling units

Business Rules

- Must previously provide the original container information to the *PostalOne!* system for the specified CRIDthe postage statement is finalized
- Only logical containers can have siblings for MLOCR mailings
- Customer will be allowed to add one or more sibling containers to a single container through one SiblingContainerCreateRequest message

3.63.1 SiblingContainerCreateRequest Data Structure

Field Description

Mail.XML 9.0B - SiblingContainerCreateRequest

Copyright © 2011 USPS®. All Rights Reserved.

Field	Format	Acceptable Values	Business Rules	Comments
SubmittingParty Block	ParticipantIDType		Required block; Identifies the customer submitting the message	Refer 'ParticipantID Type' complex type in Appendix E.
SubmittingSoftware Block	SubmittingSoftwareType		Required block; Identifies the software submitting the message	Refer 'SubmittingSoftware' complex type in Appendix E.
OriginalContainer Block	LinkingContainerIDType		Required field;	See Appendix E for Details
UserLicenseCode	UserLicenseCode Type		Either the UserLicenseCode and MaildatJobID or the CustomerGroupID and MailingGroupID are required.	
MaildatJobID	JobIDType		Either the UserLicenseCode and MaildatJobID or the CustomerGroupID and MailingGroupID are required.	
CustomerGroupID	Alphanumeric, 25 characters		Either the UserLicenseCode and MaildatJobID or the CustomerGroupID and MailingGroupID are required.	
MailingGroupID	Non-negative integer		Either the UserLicenseCode and MaildatJobID or the CustomerGroupID and MailingGroupID are required.	
ContainerID	Alphanumeric, 6 characters		Required	
UniqueContainerBarcode	Container24CharacterBarcodeTyp		Optional	

Copyright © 2011 USPS®. All Rights Reserved.

Mail.XML 9.0B - SiblingContainerCreateRequest				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
	e			
NewSiblingContainer Block	FullContainerIDType		Required field;	See Appendix E for Details
UserLicenseCode	UserLicenseCodeType		Either the UserLicenseCode and MaildatJobID or the CustomerGroupID and MailingGroupID are required.	
MaildatJobID	JobIDType		Either the UserLicenseCode and MaildatJobID or the CustomerGroupID and MailingGroupID are required.	
CustomerGroupID	Alphanumeric, 25 characters		Either the UserLicenseCode and MaildatJobID or the CustomerGroupID and MailingGroupID are required.	
MailingGroupID	Non-negative integer		Either the UserLicenseCode and MaildatJobID or the CustomerGroupID and MailingGroupID are required.	
ContainerID	Alphanumeric, 6 characters		Required	
UniqueContainerBarcode	Container24CharacterBarcodeType		Conditionally required for Full-Service physical sibling containers	
ContainerType	mailxml_base:mailXMLContainerType	Refer 'mailXMLContainerType' simple type	Required field;	Refer Appendix B
End Sequence Block				

2.2.48 - SiblingContainerCreateRequest

Copyright © 2011 USPS®. All Rights Reserved.

3.64 SiblingContainerCreateResponse

Purpose
Responds to the customer's request to determine if the sibling containers are valid

Error/Return Codes
Refer Section 2.6 to view shared error/return codes and also a list of error/return codes tied this message.

Business Rules
- Must be returned to the customer after the SiblingContainerCreateRequest message is sent by the customer to *PostalOne!*
- Sibling Container must not be finalized
- Will reject if ContainerID in NewSiblingContainer block exist in the *PostalOne!* system
- Will reject if original container information does not exist in *PostalOne!* system

3.64.1 SiblingContainerCreateResponse Data Structure

Field Description

Mail.XML 9.0B - SiblingContainerCreateResponse				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
SiblingContainerCreateAccept Block begins			Response from USPS indicating that the SiblingContainerCreateRequest message was accepted	
NewSiblingContainer Block	FullContainerIDType		Required field;	See Appendix E for Details
AcceptedSiblingContainer Block	FullContainerIDType		Required field;	See Appendix E for Details
ReturnInfo Block	ReturnInfo			See Appendix A for Details
SiblingContainerCreateAccept Block ends				
SiblingContainerCreateReject Block begins			Response from USPS indicating that the SiblingContainerCreateRequest message was rejected	
RejectedSiblingContainer block	FullContainerIDType		Required field;	See Appendix E for Details.
ReturnInfo Block	ReturnInfo		Required field;	See Appendix A for Details

Copyright © 2011 USPS®. All Rights Reserved.

Mail.XML 9.0B - SiblingContainerCreateResponse				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
SiblingContainerCreateReject block ends			End of block	

2.2.49 - SiblingContainerCreateResponse

3.65 SummaryZipDestinationReportCreateRequest

Purpose
This report is used by the USPS to identify all pieces of the postage statements are correctly calculated and can be verified through this report against all postage statements.

Business Rules

- This report is required for MLOCR mailings.
- A QualificationReportCreateRequest and PostageStatementCreateRequest message must be submitted prior to submitting the SummaryZipDestinationReportCreateRequest.
- The *PostalOne!* system will validate the fields in the SummaryZipDestinationReportCreateRequest message.
- The *PostalOne!* system will generate the SummaryZipDestinationReportCreateAccept block in the SummaryZipDestinationCreateResponse message if the SummaryZipDestinationReportCreateRequest message is accepted.
- The *PostalOne!* system will generate the SummaryZipDestinationReportCreateReject block in the SummaryZipDestinationCreateResponse message if the SummaryZipDestinationReportCreateRequest message is rejected.
- Beginning in Release 26.0.0, the *PostalOne!* system will continue to support NFM Processing Category (i.e. NA or NB).

3.65.1 SummaryZipDestinationReportCreateRequest Data Structure

Field Description

Mail.XML 9.0B - SummaryZipDestinationReportCreateRequest				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
SummaryZipDestinationReportCreateRequest Message BEGINS				
SubmittingParty	Mailxml:participantIDType		Required Block but all attributes within this block are optional	Refer 'ParticipantIDType' complex type in Appendix C
SubmittingSoftware	Mailxml:submittin		Required	Refer

Copyright © 2011 USPS®. All Rights Reserved.

Mail.XML 9.0B - SummaryZipDestinationReportCreateRequest				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
	gSoftwareType			'SubmittingParty' complex type in Appendix C
CustomerGroupID	String 25		Required	
MailingGroupID	nonnegative Integer		Required	
OnePassPlannedOrActual	Mailxml_base:yesNo	Yes/No	Optional	
OnePassOrTwoPass	Mailxml_base:onePassOrTwoPassType	Refer 'onePassOrTwoPassType' simple type	Optional	Refer Appendix B
Sequence Block BEGIN			1 to many allowed	
EntryPointZip	Mailxml_base:zipCodeThreeOrFiveDigit	Refer 'zipCodeThreeOrFiveDigit' simple type		Refer Appendix B
EntryFacilityType	Mailxml_base:EntryFacilityType	Refer 'entryFacilityType' simple type	Optional	Refer Appendix B
SummaryZipDestinationReport Block BEGIN			Required 1 to many allowed	
DestinationZip	Mailxml_base:zipCodeThreeOrFiveDigit	Refer 'zipCodeThreeOrFiveDigit' simple type	Required	Refer Appendix B
ProcessingCategory	Mailxml_base:processingCategoryType	Refer 'processingCategoryType' simple type	Optional	Refer Appendix B
PostagePaymentMethod	Mailxml_base:postagePaymentMethodType	Refer 'postagePaymentMethodTYpe' simple type	Required	Refer Appendix B
MLOCRRateType	Mailxml_base:mlocrRateType	Refer simple type definition in appendix B	Optional	Refer Appendix B
Weight	Double		Optional The value of Weight must be in Pounds.	

Copyright © 2011 USPS®. All Rights Reserved.

Mail.XML 9.0B - SummaryZipDestinationReportCreateRequest				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
RateAffixed	Double		Optional	
NumberOfPieces	nonnegative Integer		Optional	
NumberOfPiecesDifference	nonnegative Integer		Optional	
PostageAffixed	Double		Optional	
CumulativePostageAffixed	Double		Optional	
TotalPostage	Double		Optional	
NetPostageDue	Double		Optional	
CumulativePostageDue	Double		Optional	
RunningTotalPieces	nonnegative Integer		Optional	
SortationLevel	Mailxml_base:containerLevelType		Required	Refer simple type containerLevelType in Appendix B
SummaryZipDestinationReport Block END				
Sequence Block END				
SummaryZipDestinationReportCreateRequest Message ENDS				

2.2.50 - SummaryZipDestionationReportCreateRequest

3.66 SummaryZipDestinationReportCreateResponse

Purpose
This is the response message to SummaryZipDestinationReportCreateRequest message

Business Rules

- This message is required for MLOCR mailing.
- The *PostalOne!* System will generate the SummaryZipDestinationReportCreateAccept block in the SummaryZipDestinationCreateResponse message if the SummaryZipDestinationReportCreateRequest message is accepted
- The *PostalOne!* System will generate the SummaryZipDestinationReportCreateReject block in the SummaryZipDestinationCreateResponse message if the SummaryZipDestinationReportCreateRequest message is rejected
-

3.66.1 SummaryZipDestinationReportCreateResponse Data Structure

Field Description

Copyright © 2011 USPS®. All Rights Reserved.

Mail.XML 9.0B - SummaryZipDestinationReportCreateResponse				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
SummaryZipDestinationReportCreateAccept Block BEGIN			Either Accept or Reject Block is returned	
ReturnInfo	Complex Type		Optional	Refer 'ReturnInfo' complex in Appendix E
SummaryZipDestinationReportCreateAccept Block END				
SummaryZipDestinationReportCreateReject Block BEGIN			Either Accept or Reject Block is returned	
ReturnInfo	Complex Type		Optional	Refer 'ReturnInfo' complex in Appendix E
SummaryZipDestinationReportCreateReject Block END				

2.2.51 - SummaryZipDestionationReportCreateResponse

Copyright © 2011 USPS®. All Rights Reserved.

4. Mail.XML Version 9.0C eDoc and Miscellaneous Messages

The following updates are the new enhancements implemented in Mail.XML 9.0 Errata C from the previous version Mail.XML 9.0B. These changes are mainly related to novel fields added to ContainerInfoData and ContainerLevelType.

4.1.1 MobileBarcode

MobileBarcode is being introduced as a new USPSPriceIncentiveType incentive to allow mailers to select this option as necessary in the PostageStatementCreateRequest message set.The MobileBarcode incentive will be supported from July 2011 to August 2011.

The Mobile Barcode incentive will be available through Postal Wizard and BMEU entry for Regular prices and Nonprofit prices.

Validation error messages for Rate Type N = Nonprofit together with Postal Incentive Type MB = Mobile Barcode shall be removed.

Apply 3% discount for postage statements of the form type 3602 N when Rate Type N= Nonprofit together with Postal Incentive Type MB = Mobile Barcode together with USPSPriceIncentiveType of “Mobile Barcode”.

4.1.1 eInduction Indicator

The element eInductionIndicator is being added as a yesNo type optional type in ContainerInfoData in the QualificationReportCreateRequest message set and in the QualificationReportDetailCreateRequest for Mail.XMl 10.0C. This shall serve as a flag as to whether an e8125/e8017 needs to be generated for eInduction pallets or not; a flag of yes will trigger eInduction validations and e8125 creation.

4.1.1 Ready for SASP Indicator

The ReadyforSASP element is in ContainerInfoData as a yesNo optional type, and serves as a flag verifying whether all Full Service eDoc data has been provided to the *PostalOne!* system for the SASP system. This element is supported in the QualificationReportCreateRequest message set and in the QualificationReportDetailCreateRequest for Mail.XMl 10.0C.

4.1.1 ContainerLevelType

ContainerLevelType is being updated with new enumerations to the container levels. This will allow a direct correlation to the optional First-Class container labels defined in DMM 705.8.10.1 that do not already exist in the specification:

- AR = Origin SCF
- AS = Origin Mixed ADC Surface
- AT = Mixed ADC Air

All other container separations, as outlined in 705.10, for other mail classes have a specific entry in the container levels codes. These three separations share a code value with other container levels prepared under the DMM or a CSA.

Copyright © 2011 USPS®. All Rights Reserved.

4.1.1 ContainerInfoData

ContainerInfoData in the QualificationReportCreateRequest message set and in the QualificationReportDetailCreateReqquest for Mail.XMl 10.0C is updated with “AcceptMisshipped” as a new optional field. This new field “Accept Misshipped” will allow mailers to notify USPS that, USPS should accept and charge for this Misshipped container. In case No is selected, this field will notify USPS not to accept the container. The Qualification Report Create and Query messages will be enhanced by this change.

the new element and structures changes from the previous version Mail.XML are implemented in the Mail.XML 9.0C PostageStatementCreateRequest and QualificationReportCreateRequest messages . It is recommended that customers refer to the above sections for the structure of other messages; however, it critical is that the customer implement those messages using the new modularized structure.

The table below lists all Mail.XML 9.0C messages for postage payment and reporting that *PostalOne!*

Message
BeginCombinedMailingRequest
BeginCombinedMailingResponse
BundleDetailCancelRequest
BundleDetailCancelResponse
BundleDetailCreateRequest
BundleDetailCreateResponse
CloseMailingGroupRequest
CloseMailingGroupResponse
ConsolidatedPeriodicalStatementCreateRequest
ConsolidatedPeriodicalStatementCreateResponse
ContainerBundleReportCancelRequest
ContainerBundleReportCancelResponse
ContainerBundleReportCreateRequest
ContainerBundleReportCreateResponse
ContainerBundleReportQueryRequest
ContainerBundleReportQueryResponse
ContainerStatusQueryRequest
ContainerStatusQueryResponse
CustomerMailReportCreateRequest
CustomerMailReportCreateResponse
EndCombinedMailingRequest
EndCombinedMailingResponse
ContainerUpdateRequest
ContainerUpdateResponse
MailingGroupQueryRequest
MailingGroupQueryResponse
MailPieceCancelRequest
MailPieceCancelResponse
MailPieceCreateRequest

Copyright © 2011 USPS®. All Rights Reserved.

Message
MailPieceCreateResponse
MailPieceUpdateRequest
MailPieceUpdateResponse
OpenMailingGroupRequest
OpenMailingGroupResponse
OriginalContainerLinkageCancelRequest
OriginalContainerLinkageCancelResponse
OriginalContainerLinkageCreateRequest
OriginalContainerLinkageCreateResponse
PaymentMessageQueryRequest
PaymentMessageQueryResponse
PeriodicalStatementCreateRequest
PeriodicalStatementCreateResponse
PeriodicalStatementQueryRequest
PeriodicalStatementQueryResponse
PostageAdjustmentCreateRequest
PostageAdjustmentCreateResponse
PostageStatementCancelRequest
PostageStatementCancelResponse
PostageStatementCreateRequest
PostageStatementCreateResponse
PostageStatementQueryRequest
PostageStatementQueryResponse
PostageStatementStatusQueryRequest
PostageStatementStatusQueryResponse
QualificationReportCreateRequest
QualificationReportCreateResponse
ReconciliationReportQueryRequest
ReconciliationReportQueryResponse
SiblingContainerCancelRequest
SiblingContainerCancelResponse
SiblingContainerCreateRequest
SiblingContainerCreateResponse
SummaryZipDestinationReportCreateRequest
SummaryZipDestinationReportCreateResponse

4.2 BeginCombinedMailingRequest

Purpose
The beginCombinedMailing method sends the combined mailing ID information and starts a combined mailing.
Business Rules

- Will accept if a combined mailing is NOT already open for a mailing group
- Will reject if a combined mailing is already open for a mailing group
- This message is used to combine statements from the PostageStatementCreateRequest.

Copyright © 2011 USPS®. All Rights Reserved.

- This message is used to combine statements from the PeriodicalStatementCreateRequest and/or the ConsolidatedPeriodicalStatementCreateRequest
- All postage statement in a combined mailing must be the same form type
- Beginning in Release 26.1, First-Class Commerical Plus Parcels will be accepted when the following conditions are met:
    - FormType in the CreatePostageStatement block is FC (First-Class)
    - PresentationCategory in the CreatePostageStatement block is PF (Parcel, First-Class)
    - PriceType in the CreatePostageStatement block is commercialplus

Note - Important information on combined and consolidated postage statements:

Part A – Currently, the Mail.XML specs allows the user to provide different data for the fields listed in Part C below for each postage statement request. During a Combined Mailing Request or during a Consolidated Periodical Postage Statement Request, the values of these fields (listed in Part C) have to be same from a business and processing stand-point. The current implementation of Mail.XML does not provide a feature where the user could supply this data for all of the postage statements that are consolidated or combined. A future release of Mail.XML and *PostalOne!* will cater to this requirement where the user will be required to provide with only one set of data (listed in Part C) for the whole message set of combined or consolidated postage statements. However, in the current implementation, USPS recommends all users to follow the set of instructions provided in section.

Part B – For the following set of postage statement message requests, follow the instructions documented in Part C below.

- BeginCombinedMailingRequest
- EndCombinedMailingRequest
- ConsolidatedPeriodicalStatementCreateRequest
- PeriodicalStatementCreateRequest
- PostageStatementCreateRequest

Part C – For all of the postage statement create requests (items 3, 4, and 5 from above), during a Combined Mailing request (meaning postage statements enclosed in between items 1 and 2 from above) and for ConsolidatedPeriodicalStatementCreateRequest user must provide the same values inside all of the postage statements for the following fields.

- IssueDate
- IssueNumber
- VolumeNumber
- CustomerReferenceID
- AgencyCostCode
- PermitPublicationData *(block of PermitHolderData block)*
- PostagePaymentMethod
- RateType
- ProcessingCategory

4.2.1 BeginCombinedMailingResponse Data Structure

Field Description

Mail.XML 9.0C - BeginCombinedMailingRequest				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**

Copyright © 2011 USPS®. All Rights Reserved.

Mail.XML 9.0C - BeginCombinedMailingRequest				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
MailXMLPostageStatement RequestHeaderInfo block	MailXMLPostage StatementReque stHeaderInfo		Attributes block	See Appendix E for Details
SubmittingParty Block	participantIDTyp e		Required block; Identifies the customer submitting the message	See Appendix E for Details
SubmittingSoftware Block	participantIDTyp e		Required block; Identifies the software submitting the message	See Appendix E for Details

Purpose
The BeginCombinedMailingResponse will be used by USPS to notify the customer if their request to create a combined mailing has been accepted or rejected.

Error/Return Codes
Refer Section 2.6 to refer shared error/return codes and also a list of error/return codes tied this message.

Business Rules
- Will accept if a combined mailing is NOT already open for a mailing group
- Will reject if a combined mailing is already open for a mailing group
- This message is used to combine statements from the PostageStatementCreateRequest.
- This message is used to combine statements from the PeriodicalStatementCreateRequest and/or the ConsolidatedPeriodicalStatementCreateRequest
- The ReturnInfo block will have a description for rejection

Field Description

Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
BeginCombinedMailingAcc ept Block begins			Block received upon accepting request	
MailXMLMsgResponseHea derInfo Block begins	MailXMLMsgRes ponseHeaderInfo		Attributes block	See Appendix E for Details
CombinedMailingID	Non-negative Integer		Optional	
ReturnInfo Block	ReturnInfo		Optional Provides reason for return Not required Multiple pairings of	See Appendix E for Details

Copyright © 2011 USPS®. All Rights Reserved.

Field	Format	Acceptable Values	Business Rules	Comments
			ReturnCode and ReturnDescription can be provided in the block	
BeginCombinedMailingAccept Block ends				
BeginCombinedMailingReject Block begins			Block received upon rejecting request	
MailXMLMsgResponseHeaderInfo Block	Attributes		Attributes block	See Appendix E for Details
ReturnInfo Block	ReturnInfo		Required Provides reason for return Required Multiple pairings of ReturnCode and ReturnDescription can be provided in the block	See Appendix E for Details
BeginCombinedMailingReject Block ends				

2.3.052 - BeginCombinedMailingResponse

4.3 BundleDetailCancelRequest

Purpose
Message cancels the bundle detail data submitted related to a qualification report
Business Rules

- Message cannot be sent until the BundleDetailCreateRequest message has been filed in the *PostalOne!* system and accepted through the BundleDetailCreateResponse message
- Updated number of pieces must be received for the specified MailingGroupID, CustomerGroupID, and BundleID
- A MailPieceCancelRequest message must be accepted with the updated number of cancelled pieces in the specified bundle
- BundleID can be reused after it has been cancelled

4.3.1 BundleDetailCancelRequest Data Structure

Field Description

Mail.XML 9.0C - BundleDetailCancelRequest

Copyright © 2011 USPS®. All Rights Reserved.

Field	Format	Acceptable Values	Business Rules	Comments
MailXMLHeaderInfo block begins			Attributes block	
CustomerGroupID	String, 25 characters		Required field; must be populated with the same value as the value populated in the CustomerGroupID field of the BundleDetailCreateResponse	
MailingGroupID	Non-Negative Integer		Required field; must be populated with the same value as the value populated in the MailingGroupID field of the BundleDetailCreateResponse	
MaildatJobID			Optional	
UserLicenseCode			Optional	
MailXMLHeaderInfo block ends				
SubmittingParty Block	ParticipantIDType		Required block; Identifies the customer submitting the message	Refer 'ParticipantIDType' complex type in Appendix E.
SubmittingSoftware Block	SubmittingSoftwareType		Required block; Identifies the software submitting the message	Refer 'SubmittingSoftware' complex type in Appendix E.
UserLicenseCode	String, 4 characters		Field not supported	
MaildatJobID	String, 8 characters		Field not supported	
CustomerGroupID	String, 25 characters		Field not supported; redundant	
MailingGroupID	Non-Negative Integer		Field not supported; redundant	
Sequence Block BEGIN			Required 1 to many allowed	Placed ContainerID and BundleID in a

Copyright © 2011 USPS®. All Rights Reserved.

Mail.XML 9.0C - BundleDetailCancelRequest				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
				sequence block to create a link to establish relationship between BundleIDs and ContainerIDs
ContainerID	String, 6 characters		Required	
BundleID	String, 6 characters		XSD Stand-point: Optional 0 to many allowed Implementation Stand-point: REQUIRED field	
Sequence Block END				

2.3.053 - BundleDetailCancelRequest

4.4 BundleDetailCancelResponse

Purpose
Accept or reject a request to cancel bundle detail data

Error/Return Codes
Refer Section 2.6 to view shared error/return codes and also a list of error/return codes tied this message.

Business Rules
- Will accept if the bundle detail data exists in the *PostalOne!* system
- Will reject if the bundle detail data does not exist in the *PostalOne!* system
- Will reject if any pieces in the BundleDetail block have finalized postage

4.4.1 BundleDetailCancelResponse Data Structure

Field Description

Mail.XML 9.0C - BundleDetailCancelResponse				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
BundleDetailCancelAccept block begins			Response from USPS indicating that the BundleDetailCancelRequest	

Copyright © 2011 USPS®. All Rights Reserved.

Mail.XML 9.0C - BundleDetailCancelResponse				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
			message was accepted	
MailXMLMsgResponseHeaderInfo Block	MailXMLMsgResponseHeaderInfo			See Appendix B for Details
ReturnInfo block	ReturnInfo		Optional block; 0 to many pairings of ReturnCode and ReturnDescription	See Appendix E for Details
BundleDetailCancelAccept block ends				
BundleDetailCancelReject block begins			Response from USPS indicating that the BundleDetailCancelRequest message was rejected	
MailXMLMsgResponseHeaderInfo Block	MailXMLMsgResponseHeaderInfo			See Appendix B for Details
ReturnInfo Block	ReturnInfo			See Appendix B for Details
BundleDetailCancelReject block ends				

2.3.054 - BundleDetailCancelResponse

4.5 BundleDetailCreateRequest

Purpose
Message sends bundle detail information associated to a qualification report to the *PostalOne!* system
Business Rules

- Message cannot be sent until a QualificationReportCreateRequest message has been accepted and the customer receives an acceptance message through the QualificationReportCreateResponse
- Bundle detail data from this message must be tied to that of the QualificationReportCreateRequest message (ContainerID)
- MailingGroupID and CustomerGroupID must exist for an open mailing
- VersionID must be the same for the BundleDetail and ContainerDetailData blocks
- BundleID in the BundleDetail block must be unique within each container

4.5.1 BundleDetailCreateRequest Data Structure

Field Description

Mail.XML 9.0C - BundleDetailCreateRequest

Copyright © 2011 USPS®. All Rights Reserved.

Field	Format	Acceptable Values	Business Rules	Comments
BundleDetailCreate Request Message BEGINS				
MailXMLHeaderInfo block begins				
CustomerGroupID	String, 25 characters		Optional	
MailingGroupID	Non-Negative Integer		Optional	
MaildatJobID	Mailxml_base:jobIDType	Simple type	Optional	Refer this simple type in Appendix C
UserLicenseCode	Mailxml_base:userLicenseCodeType	Simple type	Optional	Refer this simple type in Appendix C
MailXMLHeaderInfo block ends				
SubmittingParty Block	ParticipantIDType		Required block; Identifies the customer submitting the message	Refer 'ParticipantIDType' complex type in Appendix C.
SubmittingSoftware Block	SubmittingSoftwareType		Required block; Identifies the software submitting the message	Refer 'SubmittingSoftware' complex type in Appendix C.
Choice Block BEGINS			Required	
Sequence Block BEGINS				
UserLicenseCode	Mailxml_base:userLicenseCodeType		Field not supported	Refer this simple type in Appendix C
MaildatJobID	Mailxml_base:jobIDType		Field not supported	Refer this simple type in Appendix C
Sequence Block ENDS				
Sequence Block BEGINS				
CustomerGroupID	String, 25 characters		Field not supported (redundant)	
MailingGroupID	Non-Negative Integer		Field not supported (redundant)	

Copyright © 2011 USPS®. All Rights Reserved.

Mail.XML 9.0C - BundleDetailCreateRequest				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
Sequence Block ENDS				
Choice Block ENDS				
BundleDetail Block			Required block; 1 to many pairings (Required block for any mailing that includes bundled mail)	Refer "BundleDetailType" complex in Appendix C
BundleDetailCreate Request Message ENDS				

2.4.04 – BundleDetailCreateRequest

4.6 BundleDetailCreateResponse

Purpose
Accept or reject a request to create bundle detail data

Error/Return Codes
Refer Section 2.6 to view shared error/return codes and also a list of error/return codes tied this message.

Business Rules
- Will accept if all required fields are populated and values are valid
- Will reject if all required fields are not populated
- Will reject if invalid values are provided

4.6.1 BundleDetailCreateResponse Data Structure

Field Description

Mail.XML 9.0C - BundleDetailCreateResponse				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
BundleDetailCreateAccept block begins			Response from USPS indicating that the BundleDetailCreateRequest message was accepted if the bundle detail	

Copyright © 2011 USPS®. All Rights Reserved.

Mail.XML 9.0C - BundleDetailCreateResponse				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
			matches the existing data in the *PostalOne!* system	
MailXMLHeaderInfo block begins			Attributes block	
CustomerGroupID	String, 25 characters		Required field; must be populated with the same value as the value populated in the CustomerGroupID field of the BundleDetailCreateRequest	
MailingGroupID	Non-Negative Integer		Required field; must be populated with the same value as the value populated in the MailingGroupID field of the BundleDetailCreateRequest	
MaildatJobID			Optional	
UserLicenseCode			Optional	
MailXMLHeaderInfo block ends				
ReturnInfo block	ReturnInfo		Optional block; 0 to many pairings of ReturnCode and ReturnDescription	See Appendix E for Details
BundleDetailCreateAccept block ends				
BundleDetailCreateReject block begins			Response from USPS indicating that the BundleDetailCreateRequest message was rejected since the bundle	

Copyright © 2011 USPS®. All Rights Reserved.

Mail.XML 9.0C - BundleDetailCreateResponse				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
			detail does not match the existing data in the *PostalOne!* system	
MailXMLHeaderInfo block begins			Attributes block	
CustomerGroupID	String, 25 characters		Required field; must be populated with the same value as the value populated in the CustomerGroupID field of the BundleDetailCreateRequest	
MailingGroupID	Non-Negative Integer		Required field; must be populated with the same value as the value populated in the MailingGroupID field of the BundleDetailCreateRequest	
MaildatJobID			Optional	
UserLicenseCode			Optional	
MailXMLHeaderInfo block ends			Attributes block	
ReturnInfo Block	ReturnInfo			See Appendix B for Details

2.3.055 - BundleDetailCreateResponse

4.7 CloseMailingGroupRequest

Purpose
If a mailing group was opened in error, the group can be closed through the CloseMailingGroupRequest by passing in the USPS mailing group ID. This prevents additional mailing documents from being added to the mailing group and mailing documents attached to the group from being processed further. This message can also be used if a Qualification Report message is submitted in error or needs to be updated, since there is currently no ability to update the Qualification Report in Mail.XML. After the CloseMailingGroupRequest is submitted, the job is no longer displayed on the *PostalOne!* dashboard.

Business Rules

- Request to close a mailing group must occur before any eDoc finalization within the mailing group

Copyright © 2011 USPS®. All Rights Reserved.

- Request to close a mailing group must be submitted against a currently open mailing group
- CustomerGroupID, MailingGroupID and SubmittingParty information must exactly match an existing mailing group
- MailingGroupIDs will not be reassigned and data from the closed mailing will be stored

4.7.1 CloseMailingGroupRequest Data Structure

Field Description

Mail.XML 9.0C - CloseMailingGroupRequest				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
MailXMLMailGroupRequest HeaderInfo Block begins			Attributes block	
CustomerGroupID	String, 25 characters		Required (attribute)	
MailingGroupID	Non-negative Integer		Required (attribute)	
MailXMLMailGroupRequest HeaderInfo Block ends				
SubmittingParty Block	ParticipantIDType		Required block; Identifies the customer submitting the message	Refer 'ParticipantID Type' complex type in Appendix E.
SubmittingSoftware Block	SubmittingSoftwa reType		Required block; Identifies the software submitting the message	Refer 'SubmittingS oftware' complex type in Appendix E.

2.3.056 - CloseMailingGroupRequest

4.8 CloseMailingGroupResponse

Purpose
The CloseMailingGroupResponse will be used by USPS to notify the customer if their request to close a mailing group has been accepted or rejected.

Error/Return Codes
Refer Section 2.6 to view shared error/return codes and also a list of error/return codes tied this message.

Business Rules
- Will accept if the CustomerGroupID, MailingGroupID and SubmittingParty information matches an existing mailing group
- Will reject if the CustomerGroupID, MailingGroupID and SubmittingParty information does NOT match an existing mailing group
- Will reject if invalid values are provided in the request
- Will reject if PostageStatementStatus is FPP or FIM
- Will reject if PostageStatementStatus is UPD while mailing is undergoing finalization

Copyright © 2011 USPS®. All Rights Reserved.

- Will reject if mail is being inducted
- All postage statements must have PostageStatementStatus of REV
- The ReturnInfo block will have a description for rejection

4.8.1 CloseMailingGroupResponse Data Structure

Field Description

Mail.XML 9.0C - CloseMailingGroupResponse				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
CloseMailingGroupAccept Block begins			Block received upon accepting request	
MailXMLOpenMailGroupResponseHeaderInfo Block begins			Attributes block	
CustomerGroupID	String, 25 characters		Required (attribute)	
MailingGroupID	Non-negative Integer		Required (attribute)	
Status	mailxml_base:statusType	Refer 'statusType' simple type	Not required (attribute)	Refer Appendix B
MailXMLOpenMailGroupResponseHeaderInfo Block ends				
ReturnInfo Block	ReturnInfo			See Appendix B for Details
CloseMailingGroupAccept Block ends				
CloseMailingGroupReject Block begins			Block received upon rejecting request	
MailXMLOpenMailGroupResponseHeaderInfo Block begins			Attributes block	
CustomerGroupID	String, 25 characters		Required (attribute)	
Status	mailxml_base:statusType	Refer 'statusType' simple type	Not required (attribute)	Refer Appendix B
MailXMLOpenMailGroupResponseHeaderInfo Block ends				
ReturnInfo Block	ReturnInfo			See Appendix B for Details
CloseMailingGroupReject Block ends				

2.3.057 - CloseMailingGroupResponse

Copyright © 2011 USPS®. All Rights Reserved.

4.9 ConsolidatedPeriodicalStatementCreateRequest

Purpose
Allows the USPS customer to create a consolidated statement by combining previously submitted Periodicals statements

Business Rules

- Must send a successful OpenMailingGroupRequest message before sending the ConsolidatedPeriodicalStatementCreateRequest message
- Must send a successful QualificationReportCreateRequest message before sending the ConsolidatedPeriodicalStatementCreateRequest message
- Must send a successful ContainerBundleReportCreateRequest message before sending the ConsolidatedPeriodicalStatementCreateRequest message
- Must send a successful PeriodicalStatementCreateRequest message before sending the ConsolidatedPeriodicalStatementCreateRequest message
- Consolidated Statement must consolidate all child statements with Statement Sequence Numbers between FirstStatementSequenceNumber and LastStatementSequenceNumber are required.
- For full-service or mixed service mailings, there are two options for how to populate the required container information:
    - PeriodicalLineItemData block
        - Include one PeriodicalLineItemData block for each container represented on each line of the postage statement. The container IDs must match an ID of a container from a previously submitted qualification report.
        - Do not include ContainerPostage block. If provided, it will be ignored.
    - ContainerPostage block
        - All containers are represented in the ContainerPostage blocks with the number of pieces and copies for each container. The container IDs must match an ID of a container from a previously submitted qualification report.
        - Do not provide Container IDs in the LineItemData blocks. Lines could potentially then be collapsed together as they would not need to be broken out by container. (If any Container ID is provided, the Container Postage block will be disregarded).
    - Notes:
        - Parent and sibling containers do not need to be represented in either option.
        - Any full-service or mixed service container that is not represented via one of the two above methods will not be sent to SASP and will not receive full-service feedback.
- For full-service and mixed service mailings, each container ID in the postage statement message (either in the PeriodicalLineItemData block or in the ContainerPostage block) must exist in a previously submitted QualificationReportCreateRequest message.
- For full-service and mixed service mailings, each container ID in the postage statement message (either in the PeriodicalLineItemData block or in the ContainerPostage block) must exist in a previously submitted MailPieceCreateRequest message.
    - Beginning in Release 28.0.0, MailPieceCreateRequest messages can be submitted before or after the Postage/Periodical/Consolidated Statements. If they are submitted after, it must be before finalization. Full-service or mixed service mailings cannot be finalized until all pieces are submitted via the MailPieceCreateRequest messages. All piece counts must match between the MailPieceCreateRequest, Postage/Periodical/Consolidated Statements and QualificationReportCreateRequest messages.
    -

Copyright © 2011 USPS®. All Rights Reserved.

- For full-service and mixed service mailings, the total number of pieces per container ID in the postage statement message must not exceed the total number of pieces per container ID in the QualificationReportCreateRequest message.
- For full-service and mixed service mailings, the total number of pieces in the QualificationReportCreateRequest message exactly match the total number of pieces in the MailPieceCreateRequest message for each container ID included in the postage statement message.
- Beginning in Release 25.0.0, the system will support government Inside-County Consolidated Periodical and Consolidated Pending Periodical mailings.
- Beginning in Release 26.0.0, Rate Categories AF, BF, DF, GF, and KF are not supported for First-Class Mail, Standard Mail, or Periodicals submitted after the January 2, 2011 price changed.
- Beginning in Release 26.0.0, the number of pieces must equal the number of copies when the mailing does not include Firm Bundles or Addressed Supplements and InOutCountyIndicator is N when the Postage Statement Mailing date is after the January 2, 2011 price change date.
- Beginning in Release 26.0.0, the number of pieces must be less than or equal to the number of copies when the mailing includes Firm Bundles but does not have any Addressed Supplements and InOutCountyIndicator is N when the Postage Statement Mailing date is after the January 2, 2011 price change date.
- Beginning in Release 26.0.0, the number of pieces must be greater than or equal to the number of copies when the mailing includes Addressed Supplements but does not have Firm Bundles and InOutCountyIndicator is N when the Postage Statement Mailing date is after the January 2, 2011 price change date.
- For the Combined/Commingled Mailing – user must first send the BeginCombinedMailingRequest message prior to sending the PostageStatement messages.
- Beginning in Release 28.0.0, the *PostalOne!* system will not store an update made to the AdPercent field that was submitted in the DocumentVersionData block in the ConsolidatedPeriodicalStatementCreateRequest message submitted after the first ConsolidatedPeriodicalCreateRequest message has been submitted to a mailing group for each unique version in that mailing group.
- Beginning in Release 28.0.0, the *PostalOne!* system will store the AdPercent submitted in the first ConsolidatedPeriodicalStatementCreateRequest when it does not match the value submitted in the last accepted qualification report message.
- Begininng in Release 28.0.0, the *PostalOne!* system will not store an update made to the PieceWeight field that was submitted in the DocumentVersionData block in the ConsolidatedPeriodicalStatementCreateRequest message submitted after the first ConsolidatedPeriodicalStatementCreateRequest message has been submitted to a mailing group for each unique version in that mailing group.
- Beginning in Release 28.0.0, the *PostalOne!* system will store the PieceWeight submitted in the first ConsolidatedPeriodicalStatementCreateRequest when it does not match the value submitted in the last accepted qualification report message.

Note - Important information on combined and consolidated postage statements:

(This note comprised of the following three parts, please review)

Part A – Currently, the Mail.XML specs allows the user to provide different data for the fields listed in Part C below for each postage statement request. During a Combined Mailing Request or during a Consolidated Periodical Postage Statement Request, the values of these fields (listed in Part C) have to be same from a business and processing stand-point. The current implementation of Mail.XML does not provide a feature where the user could supply this data for all of the postage statements that are consolidated or combined. A future release of Mail.XML and *PostalOne!* will cater to this requirement

Copyright © 2011 USPS®. All Rights Reserved.

where the user will be required to provide with only one set of data (listed in Part C) for the whole message set of combined or consolidated postage statements. However, in the current implementation, USPS recommends all users to follow the set of instructions provided in section.

Part B – For the following set of postage statement message requests, follow the instructions documented in Part C below.

- BeginCombinedMailingRequest
- EndCombinedMailingRequest
- ConsolidatedPeriodicalStatementCreateRequest
- PeriodicalStatementCreateRequest
- PostageStatementCreateRequest

Part C – For all of the postage statement create requests (items 3, 4, and 5 from above), during a Combined Mailing request (meaning postage statements enclosed in between items 1 and 2 from above) and for ConsolidatedPeriodicalStatementCreateRequest user must provide the same values inside all of the postage statements for the following fields.

- IssueDate
- IssueNumber
- VolumeNumber
- CustomerReferenceID
- AgencyCostCode
- PermitPublicationData *(block of PermitHolderData block)*
- PostagePaymentMethod
- RateType
- ProcessingCategory

4.9.1 ConsolidatedPeriodicalStatementCreateRequest Data Structure

Field Description

Mail.XML 9.0C - ConsolidatedPeriodicalStatementCreateRequest				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
ConsolidatedPeriodicalStatementCreateRequest Message BEGINS				
MailXMLPostageStatement RequestHeaderInfo block	MailXMLPostage StatementRequestHeaderInfo		Attributes block	See Appendix C for Details
SubmittingParty Block	ParticipantIDType		Required block; Identifies the customer submitting the message	See Appendix C for Details
SubmittingSoftware Block	SubmittingSoftwareType		Required block; Identifies the software submitting the message	See Appendix C for Details
CreateConsolidatedPeriodic			Required block;	

Copyright © 2011 USPS®. All Rights Reserved.

Mail.XML 9.0C - ConsolidatedPeriodicalStatementCreateRequest				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
alStatementData block begins			contains data for consolidated periodical statements	
PeriodicalStatement block	createPeriodicalStatementType	Required block; contains data critical to postage statement calculation (one to many pairings can be submitted within the CreateConsolidatedPeriodicalStatementData block)	One too many child Periodicals postage statements for a consolidated periodicals postage statement. Child statements must be at the entry level and version level to produce a Periodicals postage statement register. For a single consolidated statement, the publisher data and the mailing agent data must be the same for all of the child statements.	See PeriodicalStatement block in PeriodicalStatementCreateRequest message for blocks and elements that are required by the USPS. The PeriodicalStatement block used in this message is exactly same as in the PeriodicalStatementCreateRequest message
FirstStatementSequenceNumber	String, 30 characters		Required field	
LastStatementSequenceNumber	String, 30 characters		Required field	
LimitedCirculationDiscountClaimed	Mailxml_base:yesNo	Yes No	Required field	
PublisherData	mailerDataRequestType		Required field, there must be only one publication number for a Periodical or permit number with type PP for a pending Periodical in a consolidated statement.	See 'mailerDataResuestType' complex in Appendix C
MailingAgentData	mailerDataRequestType		Required field, there must be only one mailing agent	See 'mailerDataResuestType'

Copyright © 2011 USPS®. All Rights Reserved.

Mail.XML 9.0C - ConsolidatedPeriodicalStatementCreateRequest				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
			in a consolidated statement.	complex in Appendix C for Details
ContainerCount block	ContainerCountType		Required block; at least one of the fields in this block must be populated with a nonzero value	See Appendix C for Details
PeriodicalLineItemData block			Optional block; data used to generate container and bundle charges at the parent statement level for a consolidated periodicals statement. (one to many pairings) Alternatively, there may be no container and bundle charges or container and bundle charges may be provided at the child statement level.	See PeriodicalLIneItem in PeriodicalStatement block in PeriodicalStatementCreateRequest message.
CreateConsolidatedPeriodicalStatementData block ends				
ConsolidatedPeriodicalStatementCreateRequest Message ENDS				

2.4.09 – ConsolidatedPeriodicalStatementCreateRequest

4.10 ConsolidatedPeriodicalStatementCreateResponse

Purpose
Response on whether the consolidated periodical postage statement was accepted or rejected

Error/Return Codes
Refer Section 2.6 to view shared error/return codes and also a list of error/return codes tied this message.

Business Rules
- Will reject the request if the mailing group does not exist

Copyright © 2011 USPS®. All Rights Reserved.

- Will reject the request if there are no child statements to consolidate
- Will reject the request if one of the child statements with StatementSequenceNumber in between the First and Last Statement Sequence Number has For Consolidated field set to False
- Will accept the request if the TotalPostage field is populated with the same value as the sum of all values in the TotalPostage field for all child statements

4.10.1 ConsolidatedPeriodicalStatementCreateResponse Data Structure

Field Description

Mail.XML 9.0C - ConsolidatedPeriodicalStatementCreateResponse				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
ConsolidatedPeriodicalStatementCreateAccept block begins			Required block if the ConsolidatedPeriodicalStatementRequest has valid fields and the mailing group exists	
MailXMLPostageStatementRequestHeaderInfo block begins	MailXMLPostageStatementRequestHeaderInfo		Attributes block	See Appendix E for Details
StatementID	Non-negative integer		Required field; paired with TotalPostage and ReturnInfo block	
TotalPostage	Double		Required field; paired with StatementID and ReturnInfo block, two decimal places.	
PostageStatementStatus	Mailxml_base:postageStatementStatusType	• Refer 'postageStatementStatusType' simple type	See Postage Statement Status Definitions	See Appendix E for Details And Refer Appendix B
ReturnInfo block	ReturnInfo		Optional block; paired with StatementID and TotalPostage	See Appendix B for Details
ConsolidatedPeriodicalStatementCreateAccept block ends				
ConsolidatedPeriodicalStatementCreateReject block begins			Required block if the fields in the request message are not valid or if the mailing group	

Copyright © 2011 USPS®. All Rights Reserved.

Mail.XML 9.0C - ConsolidatedPeriodicalStatementCreateResponse				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
			does not exist	
MailXMLPostageStatement RequestHeaderInfo block	MailXMLPostage StatementReque stHeaderInfo		Attributes block	See Appendix E for Details
ReturnInfo block	ReturnInfo		Required block; zero to many pairings can be submitted between ReturnCode and ReturnDescription	See Appendix E for Details
ConsolidatedPeriodicalStat ementCreateReject block ends				

2.3.58 - ConsolidatedPeriodicalStatementCreateResponse

4.11 ContainerBundleReportCancelRequest

Purpose
Request to cancel the container and bundle report information within a mailing group

Business Rules

- ContainerBundleReportCreateRequest message must be submitted successfully by the customer
- MailingGroupID and CustomerGroupID must exist for an open mailing group
- ContainerBundleReportCreateRequest must be accepted before submitting the ContainerBundleCancelRequest message for the specified MailingGroupID and CustomerGroupID
- The specified ContainerBundleReportID will cancel all Container Bundle Reports for the specific MailingGroupID and CustomerGroupID when the ContainerBundleReportCancelRequest message has been accepted

4.11.1 ContainerBundleReportCancelRequest Data Structure

Field Description

Mail.XML 9.0C - ContainerBundleReportCancelRequest				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
ContainerBundleReportHea derInfo block begins			Attributes block	
CustomerGroupID	String, 25 characters		Optional (attribute)	
MailingGroupID	Non-Negative integer		Optional (attribute)	
MaildatJobID	String, 8 characters		Optional (attribute)	
UserLicenseCode	String, 4 characters		Optional (attribute)	
ContainerBundleReportHea				

Copyright © 2011 USPS®. All Rights Reserved.

Mail.XML 9.0C - ContainerBundleReportCancelRequest				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
derInfo block ends				
SubmittingParty Block	ParticipantIDType		Required block; Identifies the customer submitting the message	Refer 'ParticipantID Type' complex type in Appendix E.
SubmittingSoftware Block	SubmittingSoftwareType		Required block; Identifies the software submitting the message	Refer 'SubmittingSoftware' complex type in Appendix E.

2.3.59 - ContainerBundleReportCancelRequest

4.12 ContainerBundleReportCancelResponse

Purpose
Response message to inform the customer of whether the container bundle report information has been cancelled or the reason why it was not

Error/Return Codes
Refer Section 2.6 to view shared error/return codes and also list a of error/return codes tied this message.

Business Rules
- Will accept if the container bundle report information exists within the mailing group
- Will reject if the container bundle report information does not exist within the mailing group
- Postage statement associated with the Container Bundle Report must have PostageStatementStatus populated with UPD for USPS Processing Due and not undergoing finalization within the specified MailingGroupID

4.12.1 ContainerBundleReportCancelResponse Data Structure

Field Description

Mail.XML 9.0C - ContainerBundleReportCancelResponse				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
ContainerBundleReportCancelAccept block begins			Required block if the container bundle report data exists in the mailing group	
ContainerBundleReportHeaderInfo block begins			Attributes block	
CustomerGroupID	String, 25 characters		Optional (attribute)	
MailingGroupID	Non-Negative		Optional (attribute)	

Copyright © 2011 USPS®. All Rights Reserved.

Mail.XML 9.0C - ContainerBundleReportCancelResponse				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
	integer			
MaildatJobID	String, 8 characters		Optional (attribute)	
UserLicenseCode	String, 4 characters		Optional (attribute)	
ContainerBundleReportHeaderInfo block ends				
ContainerBundleReportID	String, 12 characters		Required field; must be populated with the same value as the CustomerBundleReportID field of the ContainerBundleReportCreateResponse message – a one to many ratio	
ReturnInfo Block	ReturnInfo			See Appendix B for Details
ContainerBundleReportCancelAccept block ends				
ContainerBundleReportCancelReject block begins			Required block if the container bundle report data does not exists in the mailing group	
ContainerBundleReportHeaderInfo block begins			Attributes block	
CustomerGroupID	String, 25 characters		Optional (attribute)	
MailingGroupID	Non-Negative integer		Optional (attribute)	
MaildatJobID	String, 8 characters		Optional (attribute)	
UserLicenseCode	String, 4 characters		Optional (attribute)	
ContainerBundleReportHeaderInfo block ends				
ReturnInfo Block	ReturnInfo			See Appendix B for Details
ContainerBundleReportCancelReject block ends				

2.3.60 - ContainerBundleReportCancelResponse

Copyright © 2011 USPS®. All Rights Reserved.

4.13 ContainerBundleReportCreateRequest

Purpose
Message is used to deliver the Container and Bundle Report information to the *PostalOne!* system

Business Rules

- ContainerBundleReportCreateRequest message can only be provided when the FormType in at least one QualificationReportCreateRequest message is populated with PE for the specified MailingGroupID and CustomerGroupID.
- MailingGroupID and CustomerGroupID must exist for an open mailing group
- Multiple ContainerBundleReportCreateRequest messages can be submitted within the same MailingGroupID
- A ContainerBundleSummary can be submitted for all chargeable containers and bundles or a ContainerBundleVersionReport for the chargeable containers and bundles apportioned to each Version

4.13.1 ContainerBundleReportCreateRequest Data Structure

Field Description

Mail.XML 9.0C - ContainerBundleReportCreateRequest				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
ContainerBundleReportCreateRequest Message BEGINS				
MailXMLHeaderInfo block begins			Attributes block	
CustomerGroupID	String, 25 characters		Optional	
MailingGroupID	Non-Negative integer		Optional	
MaildatJobID	Mailxml_base:jobIDType		Optional	Refer Appendix B
UserLicenseCode	Mailxml_base:uderLicenseCode		Optional	Refer Appendix B
MailXMLHeaderInfo block ends				
SubmittingParty Block	ParticipantIDType		Required block; Identifies the customer submitting the message	Refer 'ParticipantIDType' complex type in Appendix C.
SubmittingSoftware Block	SubmittingSoftwareType		Required block; Identifies the software submitting the message	Refer 'SubmittingSoftware' complex type

Copyright © 2011 USPS®. All Rights Reserved.

Mail.XML 9.0C - ContainerBundleReportCreateRequest				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
				in Appendix C.
Choice Block BEGINS			Choice between ContainerBundleVersionRecords Block OR ContainerBundleSummaryRecord Block	
ContainerBundleVersionRecords block begins			Only 1 occurrence is allowed	
SackTrayContainerVersion Records block begins			Optional block; 0 to many pairings can be submitted depending upon the number of SackTrayContainer MPURecords (used for Sack or Tray charges)	
DocumentVersionData	DocumentVersionDataType		Required	See Appendix C for Details
PublicationInfo	permitPublicationDataType		Required	See Appendix C for Details
PublicationTitle	String, 60 characters		Optional	
PostageStatementLineNumber	mailxml_base:postageStatementLineNumber2Type	Refer 'postageStatementLineNumber2Type' simple type	Optional field; uses the Container Level and Entry level to find the lines	Refer Appendix B
ChargeableContainerLevel	mailxml_base:chargeableContainerLevelType	Refer 'chargeableContainerLevelType' simple type	Required field; <BLANK> = NULL is not supported	Refer Appendix B
ChargeableEntryLevel	mailxml_base:chargeableEntryLevelType	Refer 'chargeableEntryLevelType' simple type	Required field; <BLANK> = NULL is not supported	Refer Appendix B
Containers	Double		Required field	

Copyright © 2011 USPS®. All Rights Reserved.

Mail.XML 9.0C - ContainerBundleReportCreateRequest				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
IssueDate	Date	YYYY-MM-DD	Required field	
IssueNumber	String, 6 characters		Optional field	
VolumeNumber	String, 5 characters		Optional field	
SackTrayContainerVersion Records block ends				
PalletContainerVersionRec ords block begins			Optional block; 0 to many pairings can be submitted depending upon the number of PalletMPURecords (used for Pallet charges)	
DocumentVersionData	DocumentVersio nData Type			See Appendix C for Details
PublicationInfo	permitPublication DataType			See Appendix C for Details
PublicationTitle	String, 60 characters		Optional	
PostageStatementLineNum ber	mailxml_base:po stageStatementLi neNumber1Type	Refer 'postageStateme ntLineNumber1Ty pe' simple type	Optional field; uses the Container Level and Entry level to find the lines	Refer Appendix B
ChargeableContainerLevel	mailxml_base:ch argeableContaine rLevelType	Refer 'chargeableConta inerLevelType' simple type	Required field; <BLANK> = NULL is not supported	Refer Appendix B
ChargeableEntryLevel	mailxml_base:ch argeableEntryLev elType	Refer 'chargeableEntry LevelType' simple type	Required field; <BLANK> = NULL is not supported	Refer Appendix B
Containers	Double		Required field	
IssueDate	Date	YYYY-MM-DD	Required field	
IssueNumber	String, 6 characters		Optional field	
VolumeNumber	String, 5 characters		Optional field	
PalletContainerVersionRec ords block ends				

Copyright © 2011 USPS®. All Rights Reserved.

Mail.XML 9.0C - ContainerBundleReportCreateRequest				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
BundleVersionRecord block begins			Optional block; 0 to many pairings can be submitted depending upon the number of BundleMPURecords (used for Bundle charges)	
DocumentVersionData	DocumentVersionDataType			See Appendix C for Details
PublicationInfo	permitPublicationDataType			See Appendix C for Details
PublicationTitle	String, 60 characters		Optional	
PostageStatementLineNumber	mailxml_base:postageStatementLineNumber3Type	Refer 'postageStatementLineNumber3Type' simple type	Optional field; uses the Container Level and Entry level to find the lines	Refer Appendix B
ChargeableContainerLevel	mailxml_base:chargeableContainerLevelType	Refer 'chargeableContainerLevelType' simple type	Required field; <BLANK> = NULL is not supported	Refer Appendix B
ChargeableBundleLevel	mailxml_base:chargeableBundleLevelType	Refer 'chargeableBundleLevelType' simple type	Required field; <BLANK> = NULL is not supported	Refer Appendix B
Bundles	Double		Required field	
IssueDate	Date	YYYY-MM-DD	Required field	
IssueNumber	String, 6 characters		Optional field	
VolumeNumber	String, 5 characters		Optional field	
BundleVersionRecord block ends				
ContainerBundleVersionRecords block ends				
ContainerBundleSummaryRecords block begins			Required block for each ContainerBundleMPURecord block	
SackTrayContainerRecord block begins			Optional block; 0 to many pairings can	

Copyright © 2011 USPS®. All Rights Reserved.

Mail.XML 9.0C - ContainerBundleReportCreateRequest				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
			be submitted depending upon the number of SackTrayContainer MPURecords (used for Sack or Tray charges)	
PublicationInfo	permitPublication DataType			See Appendix C for Details
PublicationTitle	String, 60 characters		Optional	
PostageStatementLineNum ber	mailxml_base:po stageStatementLi neNumber2Type	Refer 'postageStateme ntLineNumber2Ty pe' simple type	Optional field; uses the Container Level and Entry level to find the lines	Refer Appendix B
ChargeableContainerLevel	mailxml_base:ch argeableContaine rLevelType	Refer 'chargeableConta inerLevelType' simple type	Required field; <BLANK> = NULL is not supported	Refer Appendix B
ChargeableEntryLevel	mailxml_base:ch argeableEntryLev elType	Refer 'chargeableEntry LevelType' simple type	Required field; <BLANK> = NULL is not supported	Refer Appendix B
Containers	Double		Required field	
IssueDate	Date	YYYY-MM-DD	Required field	
IssueNumber	String, 6 characters		Optional field	
VolumeNumber	String, 5 characters		Optional field	
SackTrayContainerRecord block ends				
PalletContainerRecord block begins			Optional block; 0 to many pairings can be submitted depending upon the number of PalletMPURecords (used for Pallet charges)	
PublicationInfo	permitPublication DataType			See Appendix C for Details
PublicationTitle	String, 60		Optional	

Copyright © 2011 USPS®. All Rights Reserved.

Mail.XML 9.0C - ContainerBundleReportCreateRequest				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
	characters			
PostageStatementLineNumber	mailxml_base:postageStatementLineNumber1Type	Refer 'postageStatementLineNumber1Type' simple type	Optional field; uses the Container Level and Entry level to find the lines	Refer Appendix B
ChargeableContainerLevel	mailxml_base:chargeableContainerLevelType	Refer 'chargeableContainerLevelType' simple type	Required field; <BLANK> = NULL is not supported	Refer Appendix B
ChargeableEntryLevel	mailxml_base:chargeableEntryLevelType	Refer 'chargeableEntryLevelType' simple type	Required field; <BLANK> = NULL is not supported	Refer Appendix B
Containers	Double		Required field	
IssueDate	Date	YYYY-MM-DD	Required field	
IssueNumber	String, 6 characters		Optional field	
VolumeNumber	String, 5 characters		Optional field	
PalletContainerRecord block ends				
BundleRecord block begins			Optional block; 0 to many pairings can be submitted depending upon the number of BundleMPURecords (used for Bundle charges)	
PublicationInfo	permitPublicationDataType			See Appendix C for Details
PublicationTitle	String, 60 characters		Optional	
PostageStatementLineNumber	mailxml_base:postageStatementLineNumber3Type	Refer 'postageStatementLineNumber3Type' simple type	Optional field; uses the Container Level and Entry level to find the lines	Refer Appendix B
ChargeableContainerLevel	mailxml_base:chargeableContainerLevelTYpe	Refer 'chargeableCOntainerLevelType' simple type	Required field; <BLANK> = NULL is not supported	Refer Appendix B

Copyright © 2011 USPS®. All Rights Reserved.

Mail.XML 9.0C - ContainerBundleReportCreateRequest				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
ChargeableBundleLevel	mailxml_base:chargeableBundleLevelType	Refer 'chargeableBundleLevelType' simple type	Required field; <BLANK> = NULL is not supported	Refer Appendix B
Bundles	Double		Required field	
IssueDate	Date	YYYY-MM-DD	Required field	
IssueNumber	String, 6 characters		Optional field	
VolumeNumber	String, 5 characters		Optional field	
BundleRecord block ends				
ContainerBundleSummaryRecords block ends				
Choice Block ENDS				
ContainerBundleReportCreateRequest Message ENDS				

2.4.11 – ContainerBundleReportCreateRequest

4.14 ContainerBundleReportCreateResponse

Purpose
ResponseResponse message to inform the customer whether the ContainerBundleReportCreateRequest was accepted or rejected

Error/Return Codes
Refer Section 2.6 to view shared error/return codes and also a list of error/return codes tied this message.

Business Rules
- QualificationReportCreateRequest message must be accepted before submitting the ContainerBundleReportCreateRequest message for the specified MailingGroupID and CustomerGroupID

4.14.1 ContainerBundleReportCreateResponse Data Structure

Field Description

Mail.XML 9.0C - ContainerBundleReportCreateResponse				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
ContainerBundleReportCreateAccept block begins			Required block if the	

Copyright © 2011 USPS®. All Rights Reserved.

Mail.XML 9.0C - ContainerBundleReportCreateResponse				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
			ContainerBundleReportCreateRequest message has an existing MailingGroupID and the fields are valid	
ContainerBundleReportHeaderInfo block begins			Attributes block	
CustomerGroupID	String, 25 characters		Optional (attribute)	
MailingGroupID	Non-Negative integer		Optional (attribute)	
MaildatJobID	String, 8 characters		Optional (attribute)	
UserLicenseCode	String, 4 characters		Optional (attribute)	
ContainerBundleReportHeaderInfo block ends				
ContainerBundleReportID	String, 12 characters		Required field; Respond with either the ContainerBundleReportID and ContainerBundleStatus or just the Tracking ID	
ContainerBundleStatus	mailxml_base:containerBundleStatusTYpe	Refer 'containerBundleStatusType' simple type	Required field; Respond with either the ContainerBundleReportID and ContainerBundleStatus or just the Tracking ID	Refer Appendix B
ReturnInfo Block	ReturnInfo			See Appendix B for Details
ContainerBundleReportCreateAccept block ends				
ContainerBundleReportCreateReject block begins			Required block if the ContainerBundleReportCreateRequest message does not have an existing MailingGroupID or the fields are not valid	
ContainerBundleReportHea			Attributes block	

Copyright © 2011 USPS®. All Rights Reserved.

Mail.XML 9.0C - ContainerBundleReportCreateResponse				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
derInfo block begins				
CustomerGroupID	String, 25 characters		Optional (attribute)	
MailingGroupID	Non-Negative integer		Optional (attribute)	
MaildatJobID	String, 8 characters		Optional (attribute)	
UserLicenseCode	String, 4 characters		Optional (attribute)	
ContainerBundleReportHeaderInfo block ends				
ReturnInfo Block	ReturnInfo			See Appendix B for Details
ContainerBundleReportHeaderInfo block ends				

2.3.61 - ContainerBundleReportCreateResponse

4.15 ContainerBundleReportQueryRequest

Purpose
Request to retrieve all the Container and Bundle information for a Periodicals Outside County Container or Bundle report

Business Rules

- Submitted after a successful ContainerBundleReportCreateResponse message is returned to the customer
- MailingGroupID and CustomerGroupID must exist for an open mailing group
- QueryRequest message can only query the database for electronic documentation submitted through Mail.XML

4.15.1 ContainerBundleReportQueryRequest Data Structure

Field Description

Mail.XML 9.0C - ContainerBundleReportQueryRequest				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
ContainerBundleReportHeaderInfo block begins			Attributes block	
CustomerGroupID	String, 25 characters		Optional (attribute)	
MailingGroupID	Non-Negative integer		Optional (attribute)	
MaildatJobID	String, 8 characters		Optional (attribute)	
UserLicenseCode	String, 4 characters		Optional (attribute)	
ContainerBundleReportHea				

Copyright © 2011 USPS®. All Rights Reserved.

Mail.XML 9.0C - ContainerBundleReportQueryRequest				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
derInfo block ends				
SubmittingParty Block	ParticipantIDType		Required block; Identifies the customer submitting the message	Refer 'ParticipantID Type' complex type in Appendix E.
SubmittingSoftware Block	SubmittingSoftwareType		Required block; Identifies the software submitting the message	Refer 'SubmittingSoftware' complex type in Appendix E.

2.3.62 - ContainerBundleReportQueryRequest

4.16 ContainerBundleReportQueryResponse

Purpose
Response to the customer displaying the container and bundle data query results or the reason why there was a query error

Error/Return Codes
Refer Section 2.6 to view shared error/return codes and also a list of error/return codes tied this message.

Business Rules
- Submitted after a successful ContainerBundleReportCreateResponse message is returned to the customer
- ContainerBundleReportCreateRequest must be accepted before submitting the ContainerBundleQueryRequest message for the specified MailingGroupID and CustomerGroupID
- Optional blocks and fields will only be generated in the QueryResults block when the value has been populated in the database
- Required blocks and fields will always be generated in the QueryResults block
- Data will be generated post-processing with converted values in the QueryResults block
- QueryResults block will generate one to many ContainerBundleReportIDs in the QueryResults block of the ContainerBundleReportQueryResponse message

4.16.1 ContainerBundleReportQueryResponse Data Structure

Field Description

Mail.XML 9.0C - ContainerBundleReportQueryResponse				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
MailXMLHeaderInfo block begins				
CustomerGroupID	String, 25 characters		Optional (attribute)	

Copyright © 2011 USPS®. All Rights Reserved.

Mail.XML 9.0C - ContainerBundleReportQueryResponse				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
MailingGroupID	Non-Negative integer		Optional (attribute)	
MaildatJobID	Mailxml_base:jobIDType		Optional (attribute)	
UserLicenseCode	Mailxml_base:userLicenseCode		Optional (attribute)	
MailXMLHeaderInfo block ends				
Sequence BEGINS				
TrackingID	String 12	-	Optional. Returned when transaction fails	-
Choice Block BEGINS				
QueryResults block begins			Required block; either the QueryResults or QueryError block must be populated in the response	
ContainerBundleReportID	String, 12 characters		Optional field	
ContainerBundleVersionRecords block begins				
SackTrayContainerVersionRecords block begins			Optional block; 0 to many pairings can be submitted depending upon the number of SackTrayContainerMPURecords (used for Sack or Tray charges)	
DocumentVersionData	DocumentVersionData Type			See Appendix C for Details
PublicationInfo	permitPublicationDataType			See Appendix C for Details
PublicationTitle	String, 60 characters		Optional	
PostageStatementLineNumber	mailxml_base:postageStatementLineNumber2Type	Refer 'postageStatementLineNumber2Type' simple type	Optional field; uses the Container Level and Entry level to find the lines	Refer Appendix B
ChargeableContainerLevel	mailxml_base:chargeableContainerLevelType	Refer 'chargeableContainerLevelTYpe'	Required field; <BLANK> = NULL is not supported	Refer Appendix B

Copyright © 2011 USPS®. All Rights Reserved.

Mail.XML 9.0C - ContainerBundleReportQueryResponse				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
		simple type		
ChargeableEntryLevel	mailxml_base:chargeableEntryLevelTYpe	Refer 'chargeableEntryLevelType' simple type	Required field; <BLANK> = NULL is not supported	Refer Appendix B
Containers	Double		Required field	
IssueDate	Date	YYYY-MM-DD	Required field	
IssueNumber	String, 6 characters		Optional field	
VolumeNumber	String, 5 characters		Optional field	
SackTrayContainerVersionRecords block ends				
PalletContainerVersionRecords block begins			Optional block; 0 to many pairings can be submitted depending upon the number of PalletMPURecords (used for Pallet charges)	
DocumentVersionData	DocumentVersionData Type			See Appendix C for Details
PublicationInfo	permitPublicationDataType			See Appendix C for Details
PublicationTitle	String, 60 characters		Optional	
PostageStatementLineNumber	mailxml_base:postageStatementLineNumber1Type	Refer 'postageStatementLineNumber1Type' simple type	Optional field; uses the Container Level and Entry level to find the lines	Refer Appendix B
ChargeableContainerLevel	mailxml_base:chargeableContainerLevelType	Refer 'chargeableContainerLevelType' simple type	Required field; <BLANK> = NULL is not supported	Refer Appendix B
ChargeableEntryLevel	mailxml_base:chargeableEntryLevelTYpe	Refer 'chargeableEntryLevelTYpe' simple type	Required field; <BLANK> = NULL is not supported	Refer Appendix B
Containers	Double		Required field	
IssueDate	Date	YYYY-MM-DD	Required field	
IssueNumber	String, 6 characters		Optional field	
VolumeNumber	String, 5 characters		Optional field	
PalletContainerVersionRecords block ends				

Copyright © 2011 USPS®. All Rights Reserved.

Mail.XML 9.0C - ContainerBundleReportQueryResponse				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
BundleVersionRecord block begins			Optional block; 0 to many pairings can be submitted depending upon the number of BundleMPURecords (used for Bundle charges)	
DocumentVersionData	DocumentVersionData Type			See Appendix C for Details
PublicationInfo	permitPublicationDataType			See Appendix C for Details
PublicationTitle	String, 60 characters		Optional	
PostageStatementLineNumber	mailxml_base:postageStatementLineNumber3Type	Refer 'postageStatementLineNumber3Type' simple type	Optional field; uses the Container Level and Entry level to find the lines	Refer Appendix B
ChargeableContainerLevel	mailxml_base:chargeableContainerLevelType	Refer 'chargeableContainerLevelType' simple type	Required field; <BLANK> = NULL is not supported	Refer Appendix B
ChargeableBundleLevel	mailxml_base:chargeableBundleLevelType	Refer 'chargeableBundleLevelType' simple type	Required field; <BLANK> = NULL is not supported	Refer Appendix B
Bundles	Double		Required field	
IssueDate	Date	YYYY-MM-DD	Required field	
IssueNumber	String, 6 characters		Optional field	
VolumeNumber	String, 5 characters		Optional field	
BundleVersionRecord block ends				
ContainerBundleVersionRecords block ends				
ContainerBundleSummaryRecords block begins			Required block for each ContainerBundleMPURecord block	
SackTrayContainerRecord block begins			Optional block; 0 to many pairings can be submitted depending upon the number of SackTrayContainerMPURecords (used	

Copyright © 2011 USPS®. All Rights Reserved.

Mail.XML 9.0C - ContainerBundleReportQueryResponse				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
			for Sack or Tray charges)	
PublicationInfo	permitPublicationDataType			See Appendix C for Details
PublicationTitle	String, 60 characters		Optional	
PostageStatementLineNumber	mailxml_base:postageStatementLineNumber2Type	Refer 'postageStatementLineNumber2Type' simple type	Optional field; uses the Container Level and Entry level to find the lines	Refer Appendix B
ChargeableContainerLevel	mailxml_base:chargeableContainerLevelTYpe	Refer 'chargeableContainerLevelTYpe' simple type	Required field; <BLANK> = NULL is not supported	Refer Appendix B
ChargeableEntryLevel	mailxml_base:chargeableEntryLevelType	Refer 'chargeableEntryLevelTYpe' simple type	Required field; <BLANK> = NULL is not supported	Refer Appendix B
Containers	Double		Required field	
IssueDate	Date	YYYY-MM-DD	Required field	
IssueNumber	String, 6 characters		Optional field	
VolumeNumber	String, 5 characters		Optional field	
SackTrayContainerRecord block ends				
PalletContainerRecord block begins			Optional block; 0 to many pairings can be submitted depending upon the number of PalletMPURecords (used for Pallet charges)	
PublicationInfo	permitPublicationDataType			See Appendix C for Details
PublicationTitle	String, 60 characters		Optional	
PostageStatementLineNumber	mailxml_base:postageStatementLineNumber1Type	Refer 'postageStatementLineNUmber1Type' simple type	Optional field; uses the Container Level and Entry level to find the lines	Refer Appendix B
ChargeableContainerLevel	mailxml_base:chargeableCOntainerLevelType	Refer 'chargeableContainerLevelType' simple type	Required field; <BLANK> = NULL is not supported	Refer Appendix B
ChargeableEntryLevel	mailxml_base:ch	Refer	Required field;	Refer

Copyright © 2011 USPS®. All Rights Reserved.

Mail.XML 9.0C - ContainerBundleReportQueryResponse				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
	argeableEntryLevelType	'chargeableEntry LevelType' simple type	<BLANK> = NULL is not supported	Appendix B
Containers	Double		Required field	
IssueDate	Date	YYYY-MM-DD	Required field	
IssueNumber	String, 6 characters		Optional field	
VolumeNumber	String, 5 characters		Optional field	
PalletContainerRecord block ends				
BundleRecord block begins			Optional block; 0 to many pairings can be submitted depending upon the number of BundleMPURecords (used for Bundle charges)	
PublicationInfo	permitPublicationDataType			See Appendix C for Details
PublicationTitle	String, 60 characters		Optional	
PostageStatementLineNumber	mailxml_base:postageStatementLineNumber3Type	Refer 'postageStatementLineNumber3Type' simple type	Optional field; uses the Container Level and Entry level to find the lines	Refer Appendix B
ChargeableContainerLevel	mailxml_base:chargeableContainerLevelTYpe	Refer 'chargeableContainerLevelType' simple type	Required field; <BLANK> = NULL is not supported	Refer Appendix B
ChargeableBundleLevel	mailxml_base:chargeableBundleLevelType	Refer 'chargeableBundleLevelType' simple type	Required field; <BLANK> = NULL is not supported	Refer Appendix B
Bundles	Double		Required field	
IssueDate	Date	YYYY-MM-DD	Required field	
IssueNumber	String, 6 characters		Optional field	
VolumeNumber	String, 5 characters		Optional field	
BundleRecord block ends				
ContainerBundleSummaryRecords block ends				
ReturnInfo Block	ReturnInfo			See Appendix C for Details

Copyright © 2011 USPS®. All Rights Reserved.

Mail.XML 9.0C - ContainerBundleReportQueryResponse				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
QueryResults block begins				
QueryError block begins			Required when the query data cannot be provided; provides a reason for the error	
ReturnInfo Block	ReturnInfo			See Appendix C for Details
QueryError block ends				
Choice Block ENDS				
Sequence Block ENDS				
ContainerBundleReportQueryResponse Message ENDS				

2.4.12 – ContainerBundleReportQueryResponse

4.17 ContainerStatusQueryRequest

The container status message set for PS Form 8017 and PS form 8125 containers allows a mailer, mail owner, or consolidator to provide container key information and find out if the container has any eDropShip-related or any other issues prior to shipping the container to the USPS.

4.17.1 ContainerStatusQueryRequest Data Structure

Field Description

Mail.XML 9.0C - ContainerStatusQueryRequest				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
StatusQueryMsgHeaderInfo block Opens				
CreatorSchedulerCorpID	String, 12 characters		Required (attribute)	
CreatorSchedulerID	String, 12 characters		Non required (attribute)	
StatusQueryMsgHeaderInfo block Closes				
SubmittingParty	ParticipantIDType		Identifies the customer submitting the message	Refer 'ParticipantID Type' complex type

Copyright © 2011 USPS®. All Rights Reserved.

Mail.XML 9.0C - ContainerStatusQueryRequest				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
				in Appendix D.
SubmittingSoftware	SubmittingSoftwareType		Identifies the software submitting the message	Refer 'SubmittingSoftware' complex type in Appendix D.
ContainerID Block Opens				
MaildatContainer Block Opens				
UserLicenceCode	String, 4 characters		Required (attribute)	
MaildatJobID	String, 8 characters		Required (attribute)	
DatabaseContainerID	Non Negative Integer, 6 digits		Required (attribute)	
UniqueContainerBarcode	String, 24 characters		Optional (attribute)	
MaildatContainer Block Closes				
MailXMLContainer Block Opens				
MailingGroupID	Non Negative Integer		Required	
CustomerGroupID	String, 25 characters		Required	
ContainerBarcode	Container24CharacterBarcodeType		Optional	
ContainerID	String, 6 characters		Required	
MailXMLContainer Block Closes				
ContainerID Block Closes				
ConsigneeApptID	String, 12 characters		Required. 1 to many allowed	
ContentID Block Opens			Required. 1 to many block allowed	
ConsigneeContentID	String, 12 characters		Required (attribute)	
SchedulerContentID	String, 12 characters		Optional (attribute)	
ContentID Block Closes				

2.3.63 - ContainerStatusQueryRequest

Copyright © 2011 USPS®. All Rights Reserved.

4.18 ContainerStatusQueryResponse

The following eDropShip issues can stop the creation of an electronic 8125 (e8125) are:

invalid barcode – the barcode data format is not valid

payment not finalized – the clerk has not yet finalized payment

payment not yet processed – the electronic data has not been updated by the mailer to make the container in a ready to pay status

entry point payment discount error – the entry point discount filed vs. the physical facility where mail is scheduled through FAST for delivery does not support the discount type

In all of these cases, unless the issues are resolved electronically through an update of data or through the clerk finalizing the postage, the containers' e8125 or e8017 will not be generated and sent to the Surface Visibility (SV) devices for induction. When that container shows up without an e8125 at the plant, the container can be stopped and its processing can be delayed or it can be returned to the shipper.

4.18.1 ContainerStatusQueryResponse Data Structure

Field Description

Mail.XML 9.0C - ContainerStatusQueryResponse				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
StatusQueryMsgHeaderInfo block Opens				
CreatorSchedulerCorpID	String, 12 characters		Required (attribute)	
CreatorSchedulerID	String, 12 characters		Optional (attribute)	
StatusQueryMsgHeaderInfo block Closes				
QueryResults Block Opens				
UniqueContainerBarcode	String, 24characters		Optional	
ConsigneeFacility Block Opens				
CompanyName	String, 40 characters		Optional	
FacilityNumber	String, 15 characters		Optional	
FacilityAddress Block Opens				
CommunicationRole	mailxml_base:communicationRoleType	Refer 'communicationRoleType' simple type	Required (attribute)	Refer Appendix B
Address1	String, 64 characters		Optional	
Address2	String, 64 characters		Optional	

Copyright © 2011 USPS®. All Rights Reserved.

Mail.XML 9.0C - ContainerStatusQueryResponse				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
Address3	String, 40 characters		Optional	
Address4	String, 40 characters		Optional	
City	String, 45 characters		Optional	
County	String, 45 characters		Optional	
State	mailxml_base:stateCode	Refer 'stateCode' simple type	Optional	Refer Appendix B
ZipCode	Number, 9 digits		Optional	
GPSCoordinates	gPSCoordinates			Refer 'GPSCoordinates' complex type in Appendix D.
FacilityAddress Block Closes				
FacilityName	String, 40 characters		Optional	
FacilityType	String, 15 characters		Optional	
URL	url		Optional	
CommonContact Block Opens				
ContactType	Mailxml_base:contactType	Refer 'contactType' simple type	Required (attribute)	Refer Appendix B
ContactName	String, 60 characters		Optional	
Telephone	String, 25 characters		Optional	
MobilePhone	String, 25 characters		Optional	
Email	String		Optional	
Fax	String, 25 characters		Optional	
GPSCoordinates	gPSCoordinates			Refer 'GPSCoordinates' complex type in Appendix D.
ContactID Block Opens				
IDValue	String, 30 characters		Optional	

Copyright © 2011 USPS®. All Rights Reserved.

Mail.XML 9.0C - ContainerStatusQueryResponse				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
IDValueTypes	mailxml_base:IDType	Refer 'IDType' simple type	Optional	Refer Appendix B
ContactID Block Closes				
CommonContact Block Closes				
ConsigneeFacility Block Closes				
ContainerStatus	mailxml_base:containerStatusType	Refer 'containerStatusType' simple type	Optional	Refer Appendix B
ReturnInfo	ReturnInfo		Required	Refer 'ReturnInfo' complex type in Appendix D.
QueryResults Block Closes				
QueryError Block Opens				
ReturnInfo	ReturnInfo		Required	Refer 'ReturnInfo' complex type in Appendix D.
QueryError Block Closes				

2.3.64 – ContainerStatusQueryResponse

4.19 CustomerMailReportCreateRequest

Purpose
This report is used mainly for Permit/Customer Identification. This report allows the specific customer identification and permit identification who may need to be charged for paying the shortage of postage.

Business Rules

- This report is required for MLOCR mailing
- Message cannot be sent until a QualificationReportCreateRequest message has been accepted and the customer receives an acceptance message through the QualificationReport CreateResponse message
- Message cannot be sent until a PostageSatementCreateRequest message has been accepted and the customer receives an acceptance message through the PostageStatementCreate Response message
- Will accept if the CustomerGroupID, MailingGroupID, and SubmittingParty information matches an existing mailing group.
- Will validate that the OnePassPlannedOrActual element within the CustomerMailReportCreateRequest matches the OnePassPlannedOrActualFlag element within the QualificationReportCreateRequest message
- Will reject if invalid values are provided

Copyright © 2011 USPS®. All Rights Reserved.

4.19.1 CustomerMailReportCreateRequest Data Structure

Field Description

Mail.XML 9.0C - CustomerMailReportCreateRequest				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
SubmittingParty	Mailxml:participantIDType		Required Block but all attributes within this block are optional	Refer 'ParticipantIDType' complex type in Appendix E
SubmittingSoftware	Mailxml:submittingSoftwareType		Required	Refer 'SubmittingParty' complex type in Appendix E
CustomerGroupID	String 25		Required	
MailingGroupID	nonnegative Integer		Required	
OnePassPlannedOrActual	Boolean	Yes/No	Optional	
OnePassOrTwoPass	Mailxml_base:onePassOrTwoPasSType	Refer 'onePassOrTwoPassType' simple type		Refer Appendix B
CustomerMailReportInfo Block BEGIN			Required 1 to many allowed	
CustomerName	String 50		Optional	
PermitInfo	Complex Type		Optional	Refer 'permitPublicationDataType' complex in Appendix E
Weight	Double		Optional The value of Weight must be in Pounds.	
RateAffixed	Double		Optional	
AdditionalPermitInfo	Complex Type		Optional Cannot populate PublicationNumber.	Refer 'permitPublicationDataType' complex in Appendix E
NumberOfPieces	nonnegative Integer		Optional	
PostageAffixed	Double		Optional	
TotalPostage	Double		Optional	

Copyright © 2011 USPS®. All Rights Reserved.

Mail.XML 9.0C - CustomerMailReportCreateRequest				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
RunningTotalNumberOfPieces	nonnegative Integer		Optional	
CustomerMailReportInfo Block END				

2.3.03 - CustomerMailReportCreateRequest

4.20 CustomerMailReportCreateResponse

Purpose
This is a response message to CustomerMailReportCreateRequest

Business Rules

- This report is required for MLOCR mailing

4.20.1 CustomerMailReportCreateResponse Data Structure

Field Description

Mail.XML 9.0C - CustomerMailReportCreateResponse				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
CustomerMailReportCreate Accept Block BEGIN			Either Accept or Reject Block is returned	
ReturnInfo	Complex Type		Optional	Refer 'ReturnInfo' complex in Appendix E
CustomerMailReportCreate Accept Block END				
CustomerMailReportCreate Reject Block BEGIN			Either Accept or Reject Block is returned	
ReturnInfo	Complex Type		Optional	Refer 'ReturnInfo' complex in Appendix E
CustomerMailReportCreate Reject Block END				

2.3.04 - CustomerMailReportCreateResponse

Copyright © 2011 USPS®. All Rights Reserved.

4.21 EndCombinedMailingRequest

Purpose
The endCombinedMailing method is used to mark when postage statements for a combined mailing have all been submitted.

Business Rules

- BeginCombinedMailingRequest must be accepted before submitting the EndCombinedMailingRequest message for the specified MailingGroupID and CustomerGroupID
- All postage statements to be combined must be submitted before sending the end request
- This message is used to combine statements from the PostageStatementCreateRequest.
- This message is used to combine statements from the PeriodicalStatementCreateRequest and/or the ConsolidatedPeriodicalStatementCreateRequest
- All postage statements within the combined mailing must have the same FormType
- All periodical statements within a Combined Periodical mailing must have the same CombinedMailingID
- All postage statements within the combined mailing must be accepted before the submission of the EndCombinedMailingRequest message. The postage statement will not be included in the combined mailing if it is submitted after the EndCombinedMailingRequest message is submitted or if it was rejected.
- Beginning in Release 26.1, First-Class Commerical Plus Parcels will be accepted when the following conditions are met:
    - FormType in the CreatePostageStatement block is FC (First-Class)
    - PresentationCategory in the CreatePostageStatement block is PF (Parcel, First-Class)
    - PriceType in the CreatePostageStatement block is commercialplus

Note - Important information on combined and consolidated postage statements:

Part A – Currently, the Mail.XML specs allows the user to provide different data for the fields listed in Part C below for each postage statement request. During a Combined Mailing Request or during a Consolidated Periodical Postage Statement Request, the values of these fields (listed in Part C) have to be same from a business and processing stand-point. The current implementation of Mail.XML does not provide a feature where the user could supply this data for all of the postage statements that are consolidated or combined. A future release of Mail.XML and *PostalOne!* will cater to this requirement where the user will be required to provide with only one set of data (listed in Part C) for the whole message set of combined or consolidated postage statements. However, in the current implementation, USPS recommends all users to follow the set of instructions provided in section.

Part B – For the following set of postage statement message requests, follow the instructions documented in Part C below.

- BeginCombinedMailingRequest
- EndCombinedMailingRequest
- ConsolidatedPeriodicalStatementCreateRequest
- PeriodicalStatementCreateRequest
- PostageStatementCreateRequest

Part C – For all of the postage statement create requests (items 3, 4, and 5 from above), during a Combined Mailing request (meaning postage statements enclosed in between items 1 and 2 from above) and for ConsolidatedPeriodicalStatementCreateRequest user must provide the same values inside all of the postage statements for the following fields.

Copyright © 2011 USPS®. All Rights Reserved.

- IssueDate
- IssueNumber
- VolumeNumber
- CustomerReferenceID
- AgencyCostCode
- PermitPublicationData *(block of PermitHolderData block)*
- PostagePaymentMethod
- RateType
- ProcessingCategory

4.21.1 EndCombinedMailingRequest Data Structure

Field Description

Mail.XML 9.0C - EndCombinedMailingRequest				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
MailXMLPostageStatementRequestHeaderInfo block	MailXMLPostageStatementRequestHeaderInfo		Attributes block	See Appendix E for Details
SubmittingParty Block	ParticipantIDType		Required block; Identifies the customer submitting the message	See Appendix E for Details
SubmittingSoftware Block	SubmittingSoftwareType		Required block; Identifies the software submitting the message	See Appendix E for Details
CombinedMailingID	Non-negative Integer		Required	

2.3.65 - EndCombinedMailingRequest

4.22 EndCombinedMailingResponse

Purpose
The EndCombinedMailingResponse will be used by USPS to notify the customer if their request to end a combined mailing has been accepted or rejected.

Error/Return Codes

Refer Section 2.6 to learn shared error/return codes and also list of error/return codes tied this message.

Business Rules

- Will accept if a combined mailing is open for the mailing group and more than one postage statement has been submitted
- Will reject if a combined mailing is NOT already open for the mailing group
- Will reject if a more than one postage statement has NOT been submitted for the mailing group
- Upon accepting, the *PostalOne!* system will be able to display the combined postage statements
- The ReturnInfo block will have a description for rejection

Copyright © 2011 USPS®. All Rights Reserved.

- This message is used to combine statements from the PostageStatementCreateRequest.
- This message is used to combine statements from the PeriodicalStatementCreateRequest and/or the ConsolidatedPeriodicalStatementCreateRequest
- Beginning in Release 25.0.0, the Periodical Verification statement will be generated immediately after receiving an EndCombinedMailingResponse accept message.

4.22.1 EndCombinedMailingResponse Data Structure

Field Description

Mail.XML 9.0C - EndCombinedMailingResponse				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
EndCombinedMailingAccept Block begins			Block received upon accepting request	
MailXMLMsgResponseHeaderInfo Block	MailXMLMsgResponseHeaderInfo		Attributes block	See Appendix E for Details
CombinedMailingID	Non-negative integer		Required	
ReturnInfo Block	ReturnInfo		Optional Provides reason for return Required Multiple pairings of ReturnCode and ReturnDescription can be provided in the block	See Appendix E for Details
EndCombinedMailingAccept Block ends				
EndCombinedMailingReject Block begins			Block received upon accepting request	
MailXMLMsgResponseHeaderInfo Block	MailXMLMsgResponseHeaderInfo		Attributes block	See Appendix E for Details
ReturnInfo Block	ReturnInfo		Required Provides reason for return Required Multiple pairings of ReturnCode and ReturnDescription can be provided in the block	See Appendix E for Details
EndCombinedMailingAccept Block ends				

2.3.66 - EndCombinedMailingResponse

4.23 ContainerUpdateRequest

Purpose
Allows USPS customers to update a container originally submitted through Mail.dat or Mail.XML.

Copyright © 2011 USPS®. All Rights Reserved.

Business Rules

Mail.dat Business Rules:

- Must be submitted after a Mail.dat file submission has occurred
- The container must already exist in the *PostalOne!* system
- The container must not have any finalized postage
- All additional business rules that apply to Mail.dat file based container updates apply to the Mail.XML container update message set
    - All fields for Full and Mixed Service processing must be provided prior to submission
    - A matching ID in the ContainerID field in the FullContainerID block must exist.
- The CRID must match the Mailing Facility ID in the .seg file
- The following elements can be submitted in the ContainerUpdateRequest to update the value originally submitted in the .csm file (indicated in parenthesis):
    - ReservationNumber (Reservation Number)
    - IMBarcode (Label: IM™ Container Or IM™ Tray Barcode)
    - ScheduledInductionDate (Scheduled Induction Date)
    - ScheduledInductionTime (Scheduled Induction Time)
    - CSATripID (CSA Trip ID)
    - USPSPickUp (USPS Pick UP)
    - ConsigneeContentID (FAST Content ID)
    - FASTScheduerID (FAST Scheduler ID)
    - EntryPointADLocaleKey (Entry Point - Actual / Delivery - Locale Key)
    - EntryPointADPostalCode (Entry Point - Actual / Delivery - Postal Code)
    - ScheduledShipDate (Scheduled Ship Date)
    - ScheduledShipTime (Scheduled Ship Time)
    - TruckDispatchNumber (Truck or Dispatch Number)
    - StopDesignator (Stop Designator)
- Beginning in Release 26.0.0, a Transportation Update will not be accepted when a container is identified as having a parent container through the Parent Container Reference ID originally submitted in the in the .csm file.
- Beginning in Release 26.0.0, a Transportation Update will not be accepted when a container is identified as having a sibling logical container through the Sibling Container Reference ID and Sibling Container Indicator originally submitted in the .csm file.

Mail.XML Business Rules:

- Must be submitted after the QualificationReportCreateRequest message has been accepted
- The container must already exist in the *PostalOne!*
- All of the data element within the SummaryRecordUpdate block should be treated as Optional except for the ContainerStatus element.
- The system shall track every container data updated through Mail.XML by user/company that has sent the update. It will also flag the transaction that are being updated with Mail.XML instead of Mail.dat
- The following elements can be submitted in the ContainerUpdateRequest to update the value originally submitted in the QualificationReportCreateRequest (indicated in parenthesis):
    - IMBarcode (ContainerBarcode)
    - EntryPointADLocaleKey (EntryLocaleKey)
    - EntryPointADPostalCode (PhysicalPostalCodeEntryPoint)
    - ScheduledInductionDate (ScheduleInductionDateTime)
    - ScheduledInductionTime (ScheduleInductionDateTime)
    - CSADispatchNumber (CSADispatchNumber)
    - USPSPickUp (USPSPickUp)
    - ConsigneeContentID (ConsigneeContentID)
    - ScheduledShipDate (ScheduledShipDateTime)

Copyright © 2011 USPS®. All Rights Reserved.

  - ScheduledShipTime (ScheduledShipDateTime)
  - TruckDispatchNumber (TruckAndDispatchNumber)

- Beginning in Release 25.0.0, for Transportation Updates, all fields provided in the ContainerUpdateRequest message will be validated, but only the valid Transportation Update fields will be updated in the database. Any additional fields provided will be ignored.
- Beginning in Release 26.0.0, a Transportation Update when ContainerStatus is T cannot be submitted more than 30 calendar days after the PostageStatementMaililngDate.
- Beginning in Release 26.0.0, the *PostalOne!* system will only support Transportation Updates submitted within 30 days of the Postage Statement Mailing Date. If the Submission Date for the Mail.dat file or Mail.XML ContainerUpdateRequest message is more than 30 days after the Postage Statement Mailing Date, the file and/or message will be rejected.
- Beginning in Release 26.0.0, a Transportation Update will not be accepted when a container is identified as having a parent container through the ParentContainerRefID originally submitted in the original QualificationReportCreateRequest.
- Beginning in Release 26.0.0, a Transportation Update will not be accepted when a container is identified as having a sibling container through the SiblingContainerID submitted in the original QualificationReportCreateRequest.

4.23.1 ContainerUpdateRequest Data Structure

Field Description

Mail.XML 9.0C - ContainerUpdateRequest				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
SubmittingParty Block	ParticipantIDType		Required block; Identifies the customer submitting the message	Refer 'ParticipantID Type' complex type in Appendix C.
SubmittingSoftware Block	SubmittingSoftwareType		Required block; Identifies the software submitting the message	Refer 'SubmittingSoftware' complex type in Appendix C.
SummaryRecordUpate Block begins			Contains all information to be updated 1 to many can be submitted	
FullContainerID block begins				
UserLicenseCode	userLicenseCodeType		Required for Mail.dat updates	Refer appendix B
MaildatJobID	jobIDType		Required for Mail.dat updates	Refer Appendix B

Copyright © 2011 USPS®. All Rights Reserved.

Mail.XML 9.0C - ContainerUpdateRequest				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
CustomerGroupID	String 25		Required for Mail.XML updates	
MailingGroupID	nonNegative Integer		Required for Mail.XML updates	
ContainerID	String 6	1, 2, 3, 4, 5, E, F, L, O, P, S, T, V, B, U, Z, X, H, A, G, D, R, C, M	Required 1 to many allowed	
UniqueContainerBarcode	Mailxml_base:IMCBType	-	Optional	Refer appendix B
FullContainerID block ends				
Choice Block BEGIN			Optional Block 0 to 2 allowed. Either provide ENtryPointEDPostalCode and EntryPointEDFacilityTYpe OR EntryPointADLocaleKey and EntryPointADPostalCode	
EntryPointEDPostalCode	Mailxml_base:entryPointEDPostalCodeType		Conditionally required if EntryPointEDFacilityType is populated Ignored for Mail.XML transportation updates	Refer Appendix B
EntryPointEDFacilityType	mailxml_base:entryPointEDPostalCodeType	Refer 'entryPointEDPOstalCodeType' simple type	Conditionally required if EntryPointEDPostalCode is populated Ignored for Mail.XML transportation updates	Refer Appendix B
EntryPointADLocaleKey	entryPointADLocaleKeyType		Conditionally required if EntryPointADPostal	Refer Appendix B

Copyright © 2011 USPS®. All Rights Reserved.

Mail.XML 9.0C - ContainerUpdateRequest				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
			Code is populated Original data will be updated for Mail.XML transportation updates (this updates the PhysicalPostalCode EntryPoint from the Qualification Report message)	
EntryPointADPostalCode	entryPointADPostalCodeType		Conditionally required if EntryPointADLocaleKey is populated Original data will be updated for Mail.XML transportation updates	Refer Appendix B
Choice Block END				
ContainerGroupingDescription	String, 9 characters		Not required Ignored for Mail.XML transportation updates	
ParentContainerRefID	String, 6 characters		Not required Ignored for Mail.XML transportation updates	
TruckDispatchNumber	truckDispatchNumberType		Not required Ignored for Mail.XML transportation updates	Refer Appendix B
StopDesignator	stopDesignatorType		Not required Ignored for Mail.XML transportation updates	Refer Appendix B
ReservationNumber	ReservationNUmberType		Not required Original data will be	Refer Appendix B

Copyright © 2011 USPS®. All Rights Reserved.

Mail.XML 9.0C - ContainerUpdateRequest				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
			updated for Mail.XML transportation updates	
Sequence Block # 1 BEGIN			Optional	
ContainerShipDate	Date	YYYY-MM-DD	Conditionally required if ContainerShipTime is populated Ignored for Mail.XML transportation updates	
ContainerShipTime	Time	HH:MM:SS	Conditionally required if ContainerShipDate is populated Ignored for Mail.XML transportation updates	
Sequence Block # 1 END				
Sequence Block # 2 BEGIN			Optional	
ScheduledShipDate	Date	YYYY-MM-DD	Conditionally required if ScheduledShipTim e is populated Original data will be updated for Mail.XML transportation updates	
ScheduledShipTime	Time	HH:MM:SS	Conditionally required if ScheduledShipDate is populated Original data will be updated for Mail.XML transportation updates	

Copyright © 2011 USPS®. All Rights Reserved.

Mail.XML 9.0C - ContainerUpdateRequest				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
Sequence Block # 2 END				
Sequence Block # 3 BEGIN			Optional	
ActualContainerShipDate	Date	YYYY-MM-DD	Conditionally required if ActualContainerShipTime is populated Ignored for Mail.XML transportation updates	
ActualContainerShipTime	Time	HH:MM:SS	Conditionally required if ActualContainerShipDate is populated Ignored for Mail.XML transportation updates	
Sequence Block # 4 END				
Sequence Block # 5 BEGIN			Optional	
ScheduledContainerPickupDate	Date	YYYY-MM-DD	Conditionally required if ScheduledContainerPickupTime is populated Ignored for Mail.XML transportation updates	
ScheduledContainerPickupTime	Time	HH:MM:SS	Conditionally required if ScheduledContainerPickupDate is populated Ignored for Mail.XML transportation updates	
Sequence Block # 5 END				

Copyright © 2011 USPS®. All Rights Reserved.

Mail.XML 9.0C - ContainerUpdateRequest				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
Sequence Block # 6 BEGIN			Optional	
ActualContainerPickupDate	Date	YYYY-MM-DD	Conditionally required if ActualContainerPickupTime is populated Ignored for Mail.XML transportation updates	
ActualContainerPickupTime	Time	HH:MM:SS	Conditionally required if ActualContainerPickupDate is populated Ignored for Mail.XML transportation updates	
Sequence Block # 6 END				
ContainerAcceptanceDate	Date	YYYY-MM-DD	Not required Ignored for Mail.XML transportation updates	
ScheduledInHomeDate	Date	YYYY-MM-DD	Not required Ignored for Mail.XML transportation updates	
AdditionalInHomeRange	String, 1 character		Not required Ignored for Mail.XML transportation updates	
Sequence Block # 7 BEGIN			Optional	
ScheduledInductionDate	Date	YYYY-MM-DD	Conditionally required if ScheduledInductionTime is populated	

Copyright © 2011 USPS®. All Rights Reserved.

Mail.XML 9.0C - ContainerUpdateRequest				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
			Original data will be updated for Mail.XML transportation updates	
ScheduledInductionTime	Time	HH:MM:SS	Conditionally required if ScheduledInduction Date is populated Original data will be updated for Mail.XML transportation updates	
Sequence Block # 7 END				
Sequence Block # 8 BEGIN			Optional	
ActualInductionDate	Date	YYYY-MM-DD	Conditionally required if ActualInductionTim e is populated Ignored for Mail.XML transportation updates	
ActualInuctionTime	Time	HH:MM:SS	Conditionally required if ActualInductionDat e is populated Ignored for Mail.XML transportation updates	
Sequence Block # 8 END				
Sequence Block # 9 BEGIN			Optional	
PostageStatementMailingD ate	Date	YYYY-MM-DD	Conditionally required if PostageStatement MailingTime is populated Ignored for Mail.XML	

Copyright © 2011 USPS®. All Rights Reserved.

Mail.XML 9.0C - ContainerUpdateRequest				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
			transportation updates	
PostageStatementMailingTime	Time	HH:MM:SS	Conditionally required if PostageStatement MailingDate is populated Ignored for Mail.XML transportation updates	
Sequence Block # 9 END				
ContainerReadyToPayTransactionID	Number, 6 characters		Not required Ignored for Mail.XML transportation updates	
TransportationCarrierID	String, 15 characters		Not required Ignored for Mail.XML transportation updates	
CSATripID	String, 10 characters		Not required Original data will be updated for Mail.XML transportation updates	
InternalDate	Date	YYYY-MM-DD	Not required Ignored for Mail.XML transportation updates	
TotalWeight	Number, 5 characters		Not required Ignored for Mail.XML transportation updates. The value of TotalWeight must be in Pounds.	

Copyright © 2011 USPS®. All Rights Reserved.

Mail.XML 9.0C - ContainerUpdateRequest				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
UniqueContainerID	String, 12 characters		Not required	
ContainerStatus	mailxml_base:maildatContainerStatusType	Refer 'maildatContainerStatusTYpe' simple type	Required Must be 'T' for Mail.XML updates	Refer Appendix B
TransShipBoLNumber	String, 5 characters		Not required Ignored for Mail.XML transportation updates	
PostageGroupingID	String, 8 characters		Not required Ignored for Mail.XML transportation updates	
ContainerGrossWeight	String, 5 characters		Not required Ignored for Mail.XML transportation updates. The value of ContainerGrossWeight must be in Pounds.	
ContainerHeight	Number, 3 characters		Not required Ignored for Mail.XML transportation updates	
ContainerHeightSource	mailxml_base:containerHeightSourceType	Refer 'containerHeightSourceType' simple type	Not required Ignored for Mail.XML transportation updates	Refer Appendix B
TransportDUNSNumber	String, 15 characters		Not required Ignored for Mail.XML transportation updates	
IMBarcode	IMCBType		Not required Original data will be	Refer Appendix B

Copyright © 2011 USPS®. All Rights Reserved.

Mail.XML 9.0C - ContainerUpdateRequest				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
			updated for Mail.XML transportation updates	
UserInformationLine1	String, 40 characters		Not required Ignored for Mail.XML transportation updates	
UserInformationLine2	String, 40 characters		Not required Ignored for Mail.XML transportation updates	
ConsigneeContentID	String, 9 characters		Not required Original data will be updated for Mail.XML transportation updates	
FASTSchedulerID	String, 12 characters		Not required Original data will be updated for Mail.XML transportation updates.	
USPSPickUp	String, 1 character	Y = Yes N = No	Not required Original data will be updated for Mail.XML transportation updates	
CarrierRouteNumber	String exactly 4		Optional Ignored for Mail.XML transportation updates	
CinCode	String 3		Optional Ignored for Mail.XML transportation updates	
ContainerDisplayName	String 50		Optional	

Copyright © 2011 USPS®. All Rights Reserved.

Mail.XML 9.0C - ContainerUpdateRequest				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
			Ignored for Mail.XML transportation updates	
ContainerType	Mailxml_base:mailXMLContainerType		Optional Ignored for Mail.XML transportation updates	Refer Appendix B
IncludedInOtherDoc	includedinotherdocType		Optional Ignored for Mail.XML transportation updates	Refer Appendix B
SiblingContainerID	String 6		Optional Ignored for Mail.XML transportation updates	
SortationLevel	Mailxml_base:ContainerLevelType		Optional Ignored for Mail.XML transportation updates	Refer Appendix B
OverflowIndicator	Mailxml_base:yes No	Yes No	Optional Ignored for Mail.XML transportation updates	Refer Appendix B
SummaryRecordUpate Block ends				

2.4.13 – ContainerUpdateRequest

4.24 ContainerUpdateResponse

Purpose
The MailDatContainerUpdateResonse will be used by USPS to notify the customer if their request to update a container originally submitted via Mail.dat has been accepted or rejected.

Error/Return Codes
Refer Section 2.6 to view shared error/return codes and also a list of error/return codes tied this message.

Copyright © 2011 USPS®. All Rights Reserved.

Business Rules
Mail.dat Business Rules:

- Will accept if original container exists and valid values are passed in updated fields
- Will reject if original container does not exist or invalid values are passed in updated fields
- If accepted, container information returned will reflect updated values in *PostalOne!*
- If rejected, container information returned will reflect attempted updated values from the request
- Will reject if attempting to update the logical facility after payment has been received on a container
- Will only allow T status after an R or X
- Will reject if deleted containers are attempted to be re-used
- The ReturnInfo block will have a description for rejection

- Postage statement will be cancelled if ContainerStatus is updated to C or D and PostageStatementStatus is UPD and ContainerStatus is R
- EntryPointEDPostalCode and EntryPointEDFacility fields cannot be updated when the original container has a ContainerStatus of R
- Only the Full Container Block will be returned to a mailer to confirm requested updates if the message is accepted
- Postage statement will be cancelled and the associated Reconciliation Report will be updated for the specified CRID if PosatageStatementStatus is UPD and all SummaryRecordUpdate block are updated to D
- The ContainerStatus field in the SummaryRecordUpdate block can only be populated with R if it is updating a container that has the ContainerStatus populated with C for Cancel in the prior update
- Transportation update information is not sent to the Full-Service system for Full-Service appointment or CSA compliance checking

4.24.1 ContainerUpdateResponse Data Structure

Field Description

Mail.XML 9.0C - ContainerUpdateResponse				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
ContainerUpdateAccept Block begins			Block received upon accepting request	
FullContainerID block begins				
Choice Block BEGIN				
UserLicenseCode			Required	
MaildatJobID			Required	
CustomerGroupID	String 25		Required	
MailingGroupID	369nonnegative Integer		Required	

Copyright © 2011 USPS®. All Rights Reserved.

Mail.XML 9.0C - ContainerUpdateResponse				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
Choice Block END				
ContainerID	String	1, 2, 3, 4, 5, E, F, L, O, P, S, T, V, B, U, Z, X, H, A, G, D, R, C, M	Required 1 to many allowed	
UniqueContainerBarcode	24 Character Barcode		Optional	
FullContainerID block ends				
ReturnInfo block	ReturnInfo		Optional	See Appendix E for Details
MaildatContainerUpdateAccept block ends				
MaildatContainerUpdateReject block begins				
ReturnInfo block	ReturnInfo		Required	See Appendix E for Details
FullContainerID Block BEGIN				
Choice Block BEGIN				
UserLicenseCode			Required	
MaildatJobID			Required	
CustomerGroupID	String 25		Required	
MailingGroupID	nonnegative Integer		Required	
Choice Block END				
ContainerID	String	1, 2, 3, 4, 5, E, F, L, O, P, S, T, V, B, U, Z, X, H, A, G, D, R, C, M	Required 1 to many allowed	
UniqueContainerBarcode	24 Character Barcode		Optional	
FullContainerID block ends				
ContainerUpdateReject block ends				

2.3.67 - ContainerUpdateResponse

Copyright © 2011 USPS®. All Rights Reserved.

4.25 MailingGroupQueryRequest

The MailingGroupQueryRequest message will allow the customer to provide a Customer Group ID (Customer Job ID) to request the information on a mailing group in the *PostalOne!* system.
For more details on required vs. optional fields and blocks as well as the data types, please review the *Mail.XML Transaction Message Protocol Messaging Specification*.

4.25.1 MailingGroupQueryRequest Data Structure

Field Description

Mail.XML 9.0C - MailingGroupQueryRequest				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
SubmittingParty	ParticipantIDType		Identifies the customer submitting the message	Refer 'ParticipantID Type' complex type in Appendix D.
SubmittingSoftware	SubmittingSoftwareType		Identifies the software submitting the message	Refer 'SubmittingSoftware' complex type in Appendix D.
MailXMLMailGroupRequest HeaderInfo Block Opens				
CustomerGroupID	String, 25 characters		Required (attribute)	
MailingGroupID	Non Negative Integer		Required (attribute)	
MailXMLMailGroupRequest HeaderInfo Block Close				

2.3.68 - MailingGroupQueryRequest

4.26 MailingGroupQueryResponse

The MailingGroupQueryResponse message will allow the USPS *PostalOne!* system to sends back basic information about the mailer, including Permit or Publication Number information, mailing acceptance office ZIP Code, and the type of presort used in the mailing while assigning a MailingGroupID.
For more details on required vs. optional fields and blocks as well as the data types, please review the *Mail.XML Transaction Message Protocol Messaging Specification*.

4.26.1 MailingGroupQueryResponse Data Structure

Field Description

Mail.XML 9.0C - MailingGroupQueryResponse

Copyright © 2011 USPS®. All Rights Reserved.

Field	Format	Acceptable Values	Business Rules	Comments
MailXMLMailGroupRequest HeaderInfo block Opens				
CustomerGroupID	String, 25 characters		Required (attribute)	
MailingGroupID	Non Negative Integer		Required (attribute)	
MailXMLMailGroupRequest HeaderInfo block Opens				
Status	mailxml_base:statusType	Refer 'statusType' simple type	Optional (attribute)	Refer Appendix B
QueryResults Block Opens				
MailingGroup Block Opens				
CustomerDescription	String, 50 characters		Optional	
SubmitterCRID	String, 10 characters		Optional	
PermitPublicationData	PermitPublication Data			Refer 'PermitPublicationData' complex type in Appendix D.
PostOfficeOfMailingZip	String, 5 characters		Must be exactly 5 characters	
MailingFacility	String, 10 characters		Optional	
MailXmlPresentationCategory	mailxml_base:mailXMLPresentationCategoryType	Refer 'mailXMLPresentationCategoryType' simple type	Optional	Refer Appendix B
MailerID	String		Optional	
FullServiceParticitpationIndicator	mailxml_base:fspiTYpe	Refer 'fspiType' simple type	Optional	Refer Appendix B
MailAgreementType	mailxml_base:mailAgreementTypeType	Refer 'mailAgreementTypeTYpe' simple type	Optional	Refer Appendix B
ContractNumber	String, 20 characters		Optional	
OnePassIndicator	String	Yes, No	Optional	
LogicalPhysicalContainerIndicator	mailxml_base:logicalPhysicalContainerIndicatorType	Refer 'logicalPhysicalContainerIndicatorType' simple type	Optional	Refer Appendix B
MailingGroup Block Closes			Optional	
ReturnInfo	ReturnInfo		Required	Refer 'ReturnInfo'

Copyright © 2011 USPS®. All Rights Reserved.

Mail.XML 9.0C - MailingGroupQueryResponse				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
				complex type in Appendix D.
QueryResults Block Closes				
QueryError Block Opens				
ReturnInfo	ReturnInfo		Required	Refer 'ReturnInfo' complex type in Appendix D.
QueryError Block Closes				

2.3.69 - MailingGroupQueryResponse

4.27 MailPieceCancelRequest

Purpose
Used to cancel a previously created mailpiece or piece range

Business Rules

- Must be submitted to a currently existing mailpiece or piece range
- MailingGroupID and CustomerGroupID must exist for an open mailing
- Cannot cancel a mailpiece if the 'W' or 'S' indicators for WastedPieceIndicator have resulted in adjusting an already finalized postage statement
- Cannot cancel a mailpiece or piece range if postage has been finalized on its corresponding container

4.27.1 MailPieceCancelRequest Data Structure

Field Description

Mail.XML 9.0C - MailPieceCancelRequest				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
CustomerGroupID	String 25		Optional	
MailingGroupID	nonNegative Integer		Optional	
MaildatJobID			Optional	
UserLicenseCode			Optional	
SubmittingParty Block	ParticipantIDType		Required block; Identifies the customer submitting the message	Refer 'ParticipantID Type' complex type in Appendix E.
SubmittingSoftware Block	SubmittingSoftwareType		Required block; Identifies the	Refer 'SubmittingS

Copyright © 2011 USPS®. All Rights Reserved.

Mail.XML 9.0C - MailPieceCancelRequest				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
			software submitting the message	oftware' complex type in Appendix E.
UserLicenseCode			Field not being supported	
MaildatJobID			Field not being supported	
TransmittedCount	nonNegative Integer		Optional	
PDRMailPieceBlock			Block not being supported	
PackageID				
CQTDatabaseID				
MailPiece block begins			Required	
ServiceLevelIndicator			Required	
Choice Block BEGIN			Optional Choice Block. If used then either provide LOTSequenceDirectionCode and LOTSequenceNumber OR WalkSequenceNumber	
LOTSequenceDirectionCode	String 1		Required	
LOTSequenceNumber	Ns04		Required	
WalkSequenceNumber	Ns05		Required	
Choice Block END				
Choice Block BEGIN			Optional Choice block. If used, provide either IMB Block data OR PlanetCode (Optional) with DeliveryPointZip data OR DeliveryContainerId with DeliveryPointZip data.	
IMB block	IntelligentMailBarcodeType		Required	See Appendix E for Details
PlanetCode			Optional	

Copyright © 2011 USPS®. All Rights Reserved.

Mail.XML 9.0C - MailPieceCancelRequest				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
DeliveryPointZip	Mailxml_base:RoutingZipCodeType	Refer 'RoutingZipCode Type' simple type	Required	Appendix B
DeliveryContainerID	Numeric String 22		Required	
DeliveryPointZip	Mailxml_base:RoutingZipCodeType	Refer 'RoutingZipCode Type' simple type	Required	Appendix B
Choice Block END				
PieceID	String 22		Required	
WastedPieceIndicator			Optional	
MLOCRrateANDpostageMarking	String 7		Optional	
MoveComplianceUpdateMethod			Optional	
MailOwner block	ParticipantIDType		Optional	See Appendix E for Details
BarCodeApplicator block	ParticipantIDType		Optional	See Appendix E for Details
MachineID	String 4		Optional	
ACSKeyline	String 16		Optional	
MailPiece block ends				
PDRMailPieceBlock block ends				
PDRRangePieceBlock block begins			Block not being supported	
DatabaseContainerID				
PieceRangeBlock block begins			Required	
IMbarcodeLowerSerialization block begins				
MailerID6			Required	
SerialNumber9			Required	
MailerID9			Required	
SerialNumber6			Required	
IMbarcodeLowerSerialization block ends				
IMBarcodeUpperSerialization block begins				
MailerID6			Required	
SerialNumber9			Required	
MailerID9			Required	
SerialNumber6			Required	
IMBarcodeUpperSerialization block ends				

Copyright © 2011 USPS®. All Rights Reserved.

Mail.XML 9.0C - MailPieceCancelRequest				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
MailPreparer block	ParticipantIDType			See Appendix E for Details
MailOwner block	ParticipantIDType			See Appendix E for Details
ServiceTypeCode			Required	
MailClass			Required	
ServiceLevelIndicator			Required	
Pieces	nonNegative Integer		Required	
Copies	nonNegative Integer		Required	
PieceRangeBlock block ends				
PDRRangePieceBlock block Ends				
MailPieceID Block begins				
IMB block begins	IntelligentMailBarcodeType			See Appendix E for Details
PlanetCode			Optional	
DeliveryPointZip	Mailxml_base:RoutingZipCodeType	Refer 'RoutingZipCode Type' simple type	Conditionally required for Full-Service / Mixed Service mailings.	Appendix B
DeliveryContainerID	Ns22		Required	
DeliveryPointZip	Mailxml_base:RoutingZipCodeType	Refer 'RoutingZipCode Type' simple type	Conditionally required for Full-Service / Mixed Service mailings.	Appendix B
MailPieceID Block ends				
PieceRangeID	String 22		Required	
CustomerGroupID	String, 25 characters		Required field; must be populated with the same value as the CustomerGroupID in the MailPieceCreateResponse message	
MailingGroupID	Non-negative Integer		Required field; must be populated with the same value as the MailingGroupID in the MailPieceCreateRe	

Copyright © 2011 USPS®. All Rights Reserved.

Mail.XML 9.0C - MailPieceCancelRequest				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
			sponse message	
TransmittedCount	Non-negative Integer		Not required Count of records transmitted in message	
MailPieceBlockGroup Block begins			1 to many can be submitted Either MailPieceBlock or MailXMLPieceRangeBlock submitted	
ContainerID	String 6		Required	
BundleID	String 12		Optional	
MailPieceBlock block begins				
ServiceLevelIndicator	mailxml_base:serviceLevelIndicatorType	Refer 'serviceLevelIndicatorType' simple type	Required	Refer Appendix B
LOTSequenceDirectionCode	String, 1 character		Not required Either WalkSequenceNumber or pair of LOTSequenceDirectionCode and LOTSequenceNumber	
LOTSequenceNumber	Number, 4 characters		Not required Either WalkSequenceNumber or pair of LOTSequenceDirectionCode and LOTSequenceNumber	
WalkSequenceNumber	Number, 5 characters		Not required Either WalkSequenceNumber or pair of LOTSequenceDirectionCode and LOTSequenceNumber	
IntelligentMailBarcodeType Block	IntelligentMailBarcodeType			See Appendix E for Details
PlanetCode	Number, 13 characters		Not required	
DeliveryPointZIP	Number, 11		Conditionally	

Copyright © 2011 USPS®. All Rights Reserved.

Mail.XML 9.0C - MailPieceCancelRequest				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
	characters		required if PlanetCode is submitted	
DeliveryContainerID			Field not being supported	
DeliveryPointZIP			Field not being supported in conjunction with DeliveryContainerID	
PieceID	String, 22 characters		Required	
WastedPieceIndicator	mailxml_base:wastedPieceIndicatorTYpe	Refer 'wastedPieceIndicatorType' simple type	Not required	Refer Appendix B
MLOCRrateANDpostageMarking	String, 7 characters	Letters/Flats P1/F1 = Barcoded 1-ounce Permit Imprint P2/F2 = Barcoded 2-ounce Permit Imprint P3/F3 = Barcoded 3-ounce Permit Imprint P4/F4 = Barcoded 4-ounce Permit Imprint /F5 = Barcoded 5-ounce Permit Imprint /F6 = Barcoded 6-ounce Permit Imprint /F7 = Barcoded 7-ounce Permit Imprint /F8 = Barcoded 8-ounce Permit Imprint /F9 = Barcoded 9-ounce Permit Imprint /F0 = Barcoded 10-ounce Permit	Not required	

Copyright © 2011 USPS®. All Rights Reserved.

Mail.XML 9.0C - MailPieceCancelRequest				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
		Imprint /FA = Barcoded 11-ounce Permit Imprint /FB = Barcoded 12-ounce Permit Imprint /FC = Barcoded 13-ounce Permit Imprint 51/MF = Barcoded 5-Digit Meter Postage Affixed - 1 ounce 52/ = Barcoded 5-Digit Meter Postage Affixed - 2 ounces 53/ = Barcoded 5-Digit Meter Postage Affixed - 3 ounces 54/ = Barcoded 5-Digit Meter Postage Affixed - 4 ounces 31/MT = Barcoded 3-Digit Meter Postage Affixed - 1 ounce 32/ = Barcoded 3-Digit Meter Postage Affixed - 2 ounces 33/ = Barcoded 3-Digit Meter Postage Affixed - 3 ounces 34/ = Barcoded 3-Digit Meter Postage Affixed - 4 ounces A1/MD = Barcoded AADC Meter Postage Affixed - 1 ounce A2/ = Barcoded AADC Meter Postage Affixed - 2 ounces A3/ = Barcoded		

Copyright © 2011 USPS®. All Rights Reserved.

Mail.XML 9.0C - MailPieceCancelRequest				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
		AADC Meter Postage Affixed - 3 ounces A4/ = Barcoded AADC Meter Postage Affixed - 4 ounces M1/MX = Barcoded Mixed AADC Meter Postage Affixed - 1 ounce M2/ = Barcoded Mixed AADC Meter Postage Affixed - 2 ounces M3/ = Barcoded Mixed AADC Meter Postage Affixed - 3 ounces M4/ = Barcoded Mixed AADC Meter Postage Affixed - 4 ounces 11/ = Presorted Meter Postage Affixed - 1 ounce 12/ = Presorted Meter Postage Affixed - 2 ounces 13/ = Presorted Meter Postage Affixed - 3 ounces 14/ = Presorted Meter Postage Affixed - 4 ounces S1/ = Precanceled $0.15 Stamp Affixed (card) S2/ = S2 Precanceled $0.25 Stamp Affixed		

Copyright © 2011 USPS®. All Rights Reserved.

Mail.XML 9.0C - MailPieceCancelRequest				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
MoveComplianceUpdateMethod	mailxml_base:moveUpdateMethodType	Refer 'moveUpdateMethodType' simple type	Not required	Refer Appendix B
MailOwner Block	ParticipantIDType			See Appendix E for Details
BarCodeApplicator Block	ParticipantIDType			See Appendix E for Details
MachineID	String, 4 characters		Not required	
CustomerBundleID	String, 12 characters		Not required	
ACSKeyline	String, 16 characters		Not required	
MailPieceBlock Block ends				
MailPieceBlockGroup Block ends				
MailXMLPieceRangeBlock Block begins			0 to 1 can be submitted Either MailPieceBlock or MailXMLPieceRangeBlock submitted	
PieceRangeID	String 22			
ContainerID	Char 24			
IMBarcodeLowerSerialization Block begins			Required Only one can be submitted	
MailerID6	Number, 6 characters		Required Only one pairing of MailerID and SerialNumber is required	
SerialNumber9	Number, 9 characters		Required Only one pairing of MailerID and SerialNumber is required	
MailerID9	Number, 9 characters		Required Only one pairing of MailerID and SerialNumber is required	
SerialNumber6	Number, 6 characters		Required Only one pairing of MailerID and SerialNumber is	

Copyright © 2011 USPS®. All Rights Reserved.

Mail.XML 9.0C - MailPieceCancelRequest				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
			required	
IMBarcodeLowerSerialization Block ends				
IMBarcodeUpperSerialization Block begins			Required Only one can be submitted	
MailerID6	Number, 6 characters		Required Only one pairing of MailerID and SerialNumber is required	
SerialNumber9	Number, 9 characters		Required Only one pairing of MailerID and SerialNumber is required	
MailerID9	Number, 9 characters		Required Only one pairing of MailerID and SerialNumber is required	
SerialNumber6	Number, 6 characters		Required Only one pairing of MailerID and SerialNumber is required	
IMBarcodeUpperSerialization Block ends				
MailPreparer Block	ParticipantIDType			See Appendix E for Details
MailOwner Block	ParticipantIDType			See Appendix E for Details
ServiceTypeCode	Number, 3 characters		Conditionally required if Mail Class is not provided	
MailClass	Number, 1 character		Conditionally required if Service Type Code is not provided	
ServiceLevelIndicator	mailxml_base:serviceLevelIndicatorType	Refer 'serviceLevelIndicatorType' simple type	Required	Refer Appendix B
Pieces	nonNegative Integer		Required	
Copies	nonNegative		Required	

Copyright © 2011 USPS®. All Rights Reserved.

Mail.XML 9.0C - MailPieceCancelRequest				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
	Integer			
PieceRangeBlock Block ends				
MailXMLPieceRangeBlock Block ends				

2.3.70 - MailPieceCancelRequest

4.28 MailPieceCancelResponse

Purpose
Accept or reject a request to cancel a mailpiece or piece range

Error/Return Codes
Refer Section 2.6 to view shared error/return codes and also a list of error/return codes tied this message.

Business Rules
- Will accept if the mailpiece or piece range exists
- Will accept if Postage StatementStatus is UPD for USPS Processing Due
- Will reject if the mailpiece or piece range does not exist
- Will reject if a mailpiece 'W' or 'S' indicators for WastedPieceIndicator have resulted in adjusting an already finalized postage statement
- Will reject if Postage StatementStatus is FIN for finalized or FPP for finalized pending payment
- For mail piece and piece range cancellation QualificationReportCreateRequest and BundleDetailCreateRequest messages have not been accepted
- The MailPieceBlock for the MailPieceCancelRequest and MailPieceCreateRequest must be the same for the specified MailingGroupID and CustomerGroupID
- The MailXMLPieceRangeBlock for the MailPieceCancelRequest and MailPieceCreateRequest must be the same for the specified MailingGroupID and CustomerGroupID
- The ReturnInfo block will have a description for rejection

4.28.1 MailPieceCancelResponse Data Structure

Field Description

Mail.XML 9.0C - MailPieceCancelResponse				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
MailPieceCreateAccept Block begins			Block received upon accepting request 1 to many can be submitted	
MailXMLHeaderInfo block begins				
CustomerGroupID	String 25		Optional	
MailingGroupId	nonNegative Integer		Optional	

Copyright © 2011 USPS®. All Rights Reserved.

Mail.XML 9.0C - MailPieceCancelResponse				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
MaildatJobID			Optional	
UserLicenseCode			Optional	
MailXMLHeaderInfo block ends				
CancelConfirmID	String, 12 characters		Required	
ReturnInfo Block	ReturnInfo		Optional	See Appendix B for Details
MailPieceCreateAccept Block ends				
MailPieceCreateReject Block begins			Block received upon rejecting request 1 to many can be submitted	
MailXMLHeaderInfo block begins				
CustomerGroupID	String 25		Optional	
MailingGroupId	nonNegative Integer		Optional	
MaildatJobID			Optional	
UserLicenseCode			Optional	
MailXMLHeaderInfo block ends				
ReturnInfo Block	ReturnInfo		Required	See Appendix B for Details
MailPieceCreateReject Block ends				

2.3.71 - MailPieceCancelResponse

4.29 MailPieceCreateRequest

Purpose
Used to create mailpieces or piece ranges for a mailing group. Piece Range records should represent the maximum number of pieces for a handling unit/container for a particular service level. To ensure efficient Full-Service processing, single pieces should be represented by Mail Pieces instead of the same Upper and Lower Piece Ranges.

Business Rules

- The MailPieceCreateRequest message can only be submitted when the FullServiceParticipationIndicator in the OpenMailingGroupRequest message is set to F (Full-Service) or M (Mixed Service).
- Must be submitted after all QualificationReportCreateRequest messages have been accepted
- MailingGroupID and CustomerGroupID must exist for an open mailing

Copyright © 2011 USPS®. All Rights Reserved.

- In November – for the WastedPieceIndicator field; only 'X' and 'T' are recommended at this time. If 'W' or 'S' is provided then system will ignore those values and those will be treated as blank by the system.
- Beginning in Release 25.0.0, the system will support shortage and spoilage that do not trigger postage adjustment with WastedPieceIndicator field set to X and T. The system will validate that the number of MailPieceBlock blocks without WastedPieceIndicator set to X and T equals the sum of the TotalPieces fields, the TotalCopies fields, or a value in between the sum of these fields in the ContainerDetailData blocks in the QualificationReportCreateRequest message.
- For full-service and mixed service mailings, each container ID in the MailPieceCreateRequest message must exist in a previously submitted QualificationReportCreateRequest message.
- For full-service and mixed service mailings, the total number of pieces per container ID in the MailPieceCreateRequest message cannot exceed the total number of pieces per container in the previously submitted QualificationReportCreateRequest message (for mail piece or piece range).
- Beginning in Release 25.0.0, for Full-Service and Mixed Service mailings, at least one of CRID, MailOwnerMID6, MailOwnerMID9, PermitNumber, or PublicationNumber must be provided,
- Beginning in Release 25.0.0, for MLOCR mailings, either the BarcodeID, ServiceTypeCode, MailerID6, and SerialNumber9 fields or the BarcodeID, ServiceTypeCode, MailerID9, and SerialNumber6 fields must be populated.
- Beginning in Release 25.0.0, for MLOCR mailings, the IMBUpperSerialization block and IMBLowerSerialization block must be populated.
- Beginning in Release 26.0.0, the MailPieceCreateRequest messages will be rejected when the sum of the MailXMLPieceRangeBlock IMbarcodeUpperSerialization minus the MailXMLPieceRangeBlocks IMbarcodeLowerSerialization plus 1 (one) for all Full-Service blocks within the mailing group is either:
    - 20% or more greater than the larger of either (1) the sum of the Pieces field for all full-service PieceRangeBlocks or (2) the sum of Copies field for all full-service PieceRangeBlocks, or
    - Less than the smaller of either (1) the sum of the Pieces field for all full-service PieceRangeBlocks or (2) the sum of Copies field for all full-service PieceRangeBlocks.
- Beginning in Release 28.0.0, MailPieceCreateRequest messages can be submitted before or after the Postage/Periodical/Consolidated Statements. If they are submitted after, it must be before finalization. Full-service or mixed service mailings cannot be finalized until all pieces are submitted via the MailPieceCreateRequest messages. All piece counts must match between the MailPieceCreateRequest, Postage/Periodical/Consolidated Statements and QualificationReportCreateRequest messages.
- Beginning in Release 28.0.0, the ContainerDetailID field in the MailXMLPieceRange block will not be accepted.

4.29.1 MailPieceCreateRequest Data Structure

Field Description

Mail.XML 9.0C - MailPieceCreateRequest				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
MailPieceCreateRequest Message BEGINS				
SubmittingParty Block	ParticipantIDType		Required block; Identifies the	Refer 'ParticipantID

Copyright © 2011 USPS®. All Rights Reserved.

Mail.XML 9.0C - MailPieceCreateRequest				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
			customer submitting the message	Type' complex type in Appendix C.
SubmittingSoftware Block	SubmittingSoftwareType		Required block; Identifies the software submitting the message	Refer 'SubmittingSoftware' complex type in Appendix C.
UserLicenseCode	Mailxml_base:userLicenseCodeType		Field not being supported	Refer Appendix B
MaildatJobID	Mailxml_base:jobIDType		Field not being supported	Refer Appendix B
TransmittedCount	nonNegative Integer		Optional	
Choice Block BEGINS			Either PDRMailPIeceBlock or PDRRangePieceBlock	Currently this block is not supported.
PDRMailPieceBlock			Block not being supported	
PDRRangePieceBlock			Block not being supported	
Choice Block ENDS				
CustomerGroupID	String, 25 characters		Required field; must be populated with the same value as the CustomerGroupID in the QualificationReportCreateResponse message	
MailingGroupID	Non-negative Integer		Required field; must be populated with the same value as the MailingGroupID in the QualificationReportCreateResponse message	

Copyright © 2011 USPS®. All Rights Reserved.

Mail.XML 9.0C - MailPieceCreateRequest				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
TransmittedCount	Non-negative Integer		Optional Count of records transmitted in message	
Choice Block BEGINS			Either MailPieceBlockGroup or MailXMLPieceRangeBlock	
MailPieceBlockGroup block BEGINS				
ContainerID	String 6		Required	
ContainerDetailID	String 9		Optional. Links QUal, Postage, and Mailpiece data	-
BundleID	String 12		Optional	
MailPieceBlock Block begins			1 to many can be submitted Either MailPieceBlock or MailXMLPieceRangeBlock submitted	
ServiceLevelIndicator	mailxml_base:serviceLevelIndicatorType	Refer 'serviceLevelIndicatorType' simple type	Required For Full-Service / Mixed Service mailings, the ServiceLevelIndicator field must be populated with 'F' when its associated ContainerID has the ServiceLevelIndicator field in the QualificationReportCreateRequest message populated with 'F'.	Refer Appendix B
Choice Block BEGINS			OPTIONAL. If provided then either LOTSequenceData or WalkSequence	-

Copyright © 2011 USPS®. All Rights Reserved.

Mail.XML 9.0C - MailPieceCreateRequest				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
			data should be provided.	
Sequence Block BEGINS				
LOTSequenceDirectionCode	String, 1 character		Either WalkSequenceNumber or combination of LOTSequenceDirectionCode and LOTSequenceNumber should be provided.	
LOTSequenceNumber	Number, 4 characters		Either WalkSequenceNumber or combination of LOTSequenceDirectionCode and LOTSequenceNumber should be provided	
Sequence Block ENDS				
WalkSequenceNumber	Number, 5 characters		Either WalkSequenceNumber or combination of LOTSequenceDirectionCode and LOTSequenceNumber	
Choice Block ENDS				
Choice Block BEGINS			Optional Either IMB or PlantCode with DeliveryPointZip OR DeliveryCOntainerID with DeliveryPointZip is required, if this choice block is used.	
IMB Block	IntelligentMailBar	This is a complex	Required Block.	See

Copyright © 2011 USPS®. All Rights Reserved.

Mail.XML 9.0C - MailPieceCreateRequest				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
	codeType	type	Only one occurrence is allowed	Appendix C for Details
Sequence Block BEGINS				
PlanetCode	mailxml_base:planetCodeType	Refer 'planetCodeType' simple type	Not required	Refer appendix B
DeliveryPointZIP	Mailxml_base:routingZipCodeType	Refer 'routingZipCodeType' simple type	Conditionally required if PlanetCode is submitted	See Appendix B
Sequence Block ENDS				
Sequence Block BEGINS				
DeliveryContainerID	Numeric string, 22 characters		Field not being supported	
DeliveryPointZIP	Mailxml_base:routingZipCodeType	Refer 'routingZipCodeType' simple type	Field not being supported in conjunction with DeliveryContainerID	See Appendix B
Sequence Block ENDS				
Choice Block ENDS				
PieceID	String, 22 characters		Required	
WastedPieceIndicator	mailxml_base:wastedPieceIndicatorType	Refer 'wastedPieceIndicatorType' simple type	Not required	Refer Appendix B
MLOCRrateANDpostageMarking	String, 7 characters	Letters/Flats P1/F1 = Barcoded 1-ounce Permit Imprint P2/F2 = Barcoded 2-ounce Permit Imprint P3/F3 = Barcoded 3-ounce Permit Imprint P4/F4 = Barcoded 4-ounce Permit Imprint /F5 = Barcoded	Not required	

Copyright © 2011 USPS®. All Rights Reserved.

Mail.XML 9.0C - MailPieceCreateRequest				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
		5-ounce Permit Imprint /F6 = Barcoded 6-ounce Permit Imprint /F7 = Barcoded 7-ounce Permit Imprint /F8 = Barcoded 8-ounce Permit Imprint /F9 = Barcoded 9-ounce Permit Imprint /F0 = Barcoded 10-ounce Permit Imprint /FA = Barcoded 11-ounce Permit Imprint /FB = Barcoded 12-ounce Permit Imprint /FC = Barcoded 13-ounce Permit Imprint 51/MF = Barcoded 5-Digit Meter Postage Affixed – 1 ounce 52/ = Barcoded 5-Digit Meter Postage Affixed – 2 ounces 53/ = Barcoded 5-Digit Meter Postage Affixed – 3 ounces 54/ = Barcoded 5-Digit Meter Postage Affixed – 4 ounces 31/MT = Barcoded 3-Digit Meter Postage Affixed – 1 ounce 32/ = Barcoded 3-Digit Meter Postage Affixed – 2 ounces 33/ = Barcoded		

Copyright © 2011 USPS®. All Rights Reserved.

Mail.XML 9.0C - MailPieceCreateRequest				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
		3-Digit Meter Postage Affixed – 3 ounces 34/ = Barcoded 3-Digit Meter Postage Affixed – 4 ounces A1/MD = Barcoded AADC Meter Postage Affixed – 1 ounce A2/ = Barcoded AADC Meter Postage Affixed – 2 ounces A3/ = Barcoded AADC Meter Postage Affixed – 3 ounces A4/ = Barcoded AADC Meter Postage Affixed – 4 ounces M1/MX = Barcoded Mixed AADC Meter Postage Affixed – 1 ounce M2/ = Barcoded Mixed AADC Meter Postage Affixed – 2 ounces M3/ = Barcoded Mixed AADC Meter Postage Affixed – 3 ounces M4/ = Barcoded Mixed AADC Meter Postage Affixed – 4 ounces 11/ = Presorted Meter Postage Affixed – 1 ounce 12/ = Presorted Meter Postage Affixed – 2 ounces 13/ = Presorted		

Copyright © 2011 USPS®. All Rights Reserved.

Mail.XML 9.0C - MailPieceCreateRequest				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
		Meter Postage Affixed – 3 ounces 14/ = Presorted Meter Postage Affixed – 4 ounces S1/ = Precanceled $0.15 Stamp Affixed (card) S2/ = S2 Precanceled $0.25 Stamp Affixed		
MoveComplianceUpdateMethod	mailxml_base:moveUpdateMethodType	Refer 'moveUpdateMethodType' simple type	Not required	Refer Appendix B
MailOwner Block	mailOwnerBlockType	Refer complex type in Appendix C	Optional Block	See Appendix C for Details
BarCodeApplicator Block	ParticipantIDType			See Appendix C for Details
MachineID	String, 4 characters		Optional	
ACSKeyline	String, 16 characters		Optional	
MailPieceBlock Block ends				
MailPieceBlockGroup block ends				
MailXMLPieceRangeBlock Block begins			1 to many can be submitted Either MailPieceBlock or MailXMLPieceRangeBlock submitted	
ContainerID	Char 24		Required 1 to many allowed	
ContainerDetailID	String 9	-	Optional 0 to many allowed	
PieceRangeBlock Block			Required	

Copyright © 2011 USPS®. All Rights Reserved.

Mail.XML 9.0C - MailPieceCreateRequest				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
begins			1 to many can be submitted	
PieceRangeID	String 22		Required	
IMBarcodeLowerSerialization Block begins			Required Only one can be submitted	
Choice Block BEGINS				
Sequence Block # 1 BEGINS				
MailerID6	mailerID6Type		Required Only one pairing of MailerID and SerialNumber is required If provided, MailerID6 fields must be the same in the IMbarcodeUpperSerialization and IMbarcodeLowerSerialization blocks	Refer Appendix B
SerialNumber9	iMBSerialNumber9Type		Required Only one pairing of MailerID and SerialNumber is required	Refer Appendix B
Sequence Block # 1 ENDS				
Sequence Block # 2 BEGINS				
MailerID9	mailerID9Type		Required Only one pairing of MailerID and SerialNumber is required If provided, MailerID9 fields must be the same in the IMbarcodeUpperSerialization and IMbarcodeLowerSerialization blocks	Refer Appendix B
SerialNumber6	iMBSerialNumber6Type		Required Only one pairing of	Refer Appendix B

Copyright © 2011 USPS®. All Rights Reserved.

Mail.XML 9.0C - MailPieceCreateRequest				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
			MailerID and SerialNumber is required	
Sequence Block # 2 ENDS				
Choice Block ENDS				
IMBarcodeLowerSerialization Block ends				
IMBarcodeUpperSerialization Block begins			Required Only one can be submitted	
Choice Block BEGINS				
Sequence Block BEGINS				
MailerID6	mailerID6Type		Required Only one pairing of MailerID and SerialNumber is required If provided, MailerID6 fields must be the same in the IMbarcodeUpperSerialization and IMbarcodeLowerSerialization blocks	Refer Appendix B
SerialNumber9	iMBSerialNumber9Type		Required Only one pairing of MailerID and SerialNumber is required	
Sequence Block ENDS				
Sequence Block BEGINS				
MailerID9	mailerID9Type		Required Only one pairing of MailerID and SerialNumber is required If provided, MailerID9 fields must be the same in the IMbarcodeUpperSerialization and IMbarcodeLowerSerialization blocks	Refer Appendix B

Copyright © 2011 USPS®. All Rights Reserved.

Mail.XML 9.0C - MailPieceCreateRequest				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
SerialNumber6	iMBSerialNumber6Type		Required Only one pairing of MailerID and SerialNumber is required	
Sequence Block ENDS				
Choice Block ENDS				
IMBarcodeUpperSerialization Block ends				
MailPreparer Block	ParticipantIDType		Conditionally required for Full-Service mailings. If not provided then user will get Full-Service compliance error and no Full-Service data feedback will be available to the mailer.	See Appendix C for Details
MailOwner Block	ParticipantIDType		Conditionally required for Full-Service mailings. If not provided then user will get Full-Service compliance error and no Full-Service data feedback will be available to the mailer.	See Appendix C for Details
Choice Block BEGINS			Required ServiceCode or MailClass	
ServiceTypeCode	serviceTypeCodeType		Conditionally required for Full-Service / Mixed Service mailings if Mail Class is not provided.	Refer Appendix B
MailClass	mailClassType		Conditionally required for Full-Service / Mixed Service mailings if	Refer Appendix B

Copyright © 2011 USPS®. All Rights Reserved.

Mail.XML 9.0C - MailPieceCreateRequest				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
			Service Type Code is not provided.	
Choice Block ENDS				
ServiceLevelIndicator	mailxml_base:serviceLevelIndicatorType	Refer 'serviceLevelIndicatorType' simple type	Required For Full-Service / Mixed Service mailings, the ServiceLevelIndicator field must be populated with 'F' when its associated ContainerID has the ServiceLevelIndicator field in the QualificationReportCreateRequest message populated with 'F'.	Refer Appendix B
Pieces	Non-Negative Integer		Required 1 to many allowed If the FullServiceParticipationIndicator field is populated with a 'F', then the IMbarcodeUpperSerialization block minus the IMbarcodeLowerSerialization block is equal to the piece count and the copy count.	
Copies	Non-Negative Integer		Required 1 to many allowed If the FullServiceParticipationIndicator field is populated with a 'F', then the IMbarcodeUpperSerialization block	

Copyright © 2011 USPS®. All Rights Reserved.

Mail.XML 9.0C - MailPieceCreateRequest				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
			minus the IMbarcodeLowerSerialization block is equal to the piece count and the copy count.	
PieceRangeBlock Block ends				
MailXMLPieceRangeBlock Block ends				
MailXMLLargeTransactionDividerGroupOptionalType block begins			Not currently supported	
MessageGroupID	String 20		Not currently supported	
TotalMessageCount	Positive Integer		Not currently supported	
MessageSerialNumber	Positive Integer		Not currently supported	
TransmittedRecordCount	Positive Integer		Not currently supported	
TotalRecordsAcrossMessages	Positive Integer		Not currently supported	
LastMessage	Yes/No	Yes No	Not currently supported	
MailXMLLargeTransactionDividerGroupOptionalType block ends			Not currently supported	
MailXMLHeaderInfo block begins				
CustomerGroupID	String 25		Optional	
MailingGroupID	nonNegativeInteger		Optional	
MaildatJobID			Optional	
UserLicenceCode			Optional	
MailXMLHeaderInfo block ends				
MailPieceCreateRequest Message ENDS				

2.4.14 – MailPieceCreateRequest

4.30 MailPieceCreateResponse

Purpose

Copyright © 2011 USPS®. All Rights Reserved.

Accept or reject a request to create a mailpiece or piece range

Error/Return Codes

Refer Section 2.6 to view shared error/return codes and also a list of error/return codes tied this message.

Business Rules

- Will accept if all required fields are populated and values are valid
- Will reject if all required fields are not populated
- Will reject if invalid values are provided
- Will reject if FullServiceParticipationIndicator is NOT F for Full-Service or M for Mixed Service
- Mail Pieces and piece ranges for a specified MailingGroupID and CustomerGroupID must have an accepted QualificationReportCreateRequest and BundleDetailCreatRequest
- The ReturnInfo block will have a description for rejection

4.30.1 MailPieceCreateResponse Data Structure

Field Description

Mail.XML 9.0C - MailPieceCreateResponse				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
MailPieceCreateAccept Block begins			Block received upon accepting request 1 to many can be submitted	
MailXMLHeaderInfo block begins				
CustomerGroupID	String 25		Optional	
MailingGroupId	nonNegative Integer		Optional	
MaildatJobID			Optional	
UserLicenseCode			Optional	
MailXMLHeaderInfo block ends				
ReturnInfo Block	ReturnInfo		Optional	See Appendix B for Details
MailPieceCreateAccept Block ends				
MailPieceCreateReject Block begins			Block received upon rejecting request Only one can be submitted	
MailXMLHeaderInfo block begins				
CustomerGroupID	String 25		Optional	
MailingGroupId	nonNegative Integer		Optional	
MaildatJobID			Optional	

Copyright © 2011 USPS®. All Rights Reserved.

Mail.XML 9.0C - MailPieceCreateResponse				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
UserLicenseCode			Optional	
MailXMLHeaderInfo block ends				
ReturnInfo Block	ReturnInfo		Required	See Appendix B for Details
MailPieceCreateReject Block ends				

2.3.72 - MailPieceCreateResponse

4.31 MailPieceUpdateRequest

Purpose
Used to update a previously created mailpiece or piece range

Business Rules

- Must be submitted to a currently existing mailpiece or piece range
- MailingGroupID and CustomerGroupID must exist for an open mailing
- The MailPieceBlock for the MailPieceUpdateRequest and MailPieceCreateRequest must be the same for the specified MailingGroupID and CustomerGroupID
- The MailXMLPieceRangeBlock for the MailPieceUpdateRequest and MailPieceCreateRequest must be the same for the specified MailingGroupID and CustomerGroupID
- Cannot update a mailpiece if the 'W' or 'S' indicators for WastedPieceIndicator have resulted in adjusting an already finalized postage statement
- Cannot update a mailpiece or piece range if postage has been finalized on its corresponding container
- Beginning in Release 26.0.0, the MailPieceUpdateRequest messages will be rejected where the sum of the MailXMLPieceRangeBlock IMbarcodeUpperSerialization minus the MailXMLPieceRangeBlocks IMbarcodeLowerSerialization plus 1 (one) for all Full-Service blocks within the mailing group is either:
    - 20% or more greater than the larger of either (1) the sum of the Pieces field for all full-service PieceRangeBlocks or (2) the sum of Copies field for all full-service PieceRangeBlocks, or
    - Less than the smaller of either (1) the sum of the Pieces field for all full-service PieceRangeBlocks or (2) the sum of Copies field for all full-service PieceRangeBlocks.
- Beginning in Release 28.0.0, the ContainerDetailID field in the MailXMLPieceRange block will not be accepted.

4.31.1 MailPieceUpdateRequest Data Structure

Field Description

Mail.XML 9.0C - MailPieceUpdateRequest				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
MailPieceUpdateRequest Message BEGINS				

Copyright © 2011 USPS®. All Rights Reserved.

Mail.XML 9.0C - MailPieceUpdateRequest				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
SubmittingParty Block	ParticipantIDType		Required block; Identifies the customer submitting the message	Refer 'ParticipantID Type' complex type in Appendix C.
SubmittingSoftware Block	SubmittingSoftwareType		Required block; Identifies the software submitting the message	Refer 'SubmittingSoftware' complex type in Appendix C.
UserLicenseCode	Mailxml_base:userLicenseCodeType		Field not being supported	Refer Appendix B
MaildatJobID	Mailxml_base:jobIDType		Field not being supported	Refer Appendix B
TransmittedCount	nonNegative Integer		Optional	
Choice Block BEGINS			Either PDRMailPIeceBlock or PDRRangePieceBlock	Currently this block is not supported.
PDRMailPieceBlock			Block not being supported	
PDRRangePieceBlock			Block not being supported	
Choice Block ENDS				
CustomerGroupID	String, 25 characters		Required field; must be populated with the same value as the CustomerGroupID in the QualificationReportCreateResponse message	
MailingGroupID	Non-negative Integer		Required field; must be populated with the same value as the MailingGroupID in the QualificationReportCreateResponse	

Copyright © 2011 USPS®. All Rights Reserved.

Mail.XML 9.0C - MailPieceUpdateRequest				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
			message	
TransmittedCount	Non-negative Integer		Optional Count of records transmitted in message	
Choice Block BEGINS			Either MailPieceBlockGroup or MailXMLPieceRangeBlock	
MailPieceBlockGroup block BEGINS				
ContainerID	String 6		Required	
ContainerDetailID	String 9		Optional. Links Qual, Postage, and Mailpiece data	-
BundleID	String 12		Optional	
MailPieceBlock Block begins			1 to many can be submitted Either MailPieceBlock or MailXMLPieceRangeBlock submitted	
ServiceLevelIndicator	mailxml_base:serviceLevelIndicatorType	Refer 'serviceLevelIndicatorType' simple type	Required For Full-Service / Mixed Service mailings, the ServiceLevelIndicator field must be populated with 'F' when its associated ContainerID has the ServiceLevelIndicator field in the QualificationReportCreateRequest message populated with 'F'.	Refer Appendix B
Choice Block BEGINS			OPTIONAL. If provided then either LOTSequence	-

Copyright © 2011 USPS®. All Rights Reserved.

Mail.XML 9.0C - MailPieceUpdateRequest				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
			Data or WalkSequence data should be provided.	
Sequence Block BEGINS				
LOTSequenceDirectionCode	String, 1 character		Either WalkSequenceNumber or combination of LOTSequenceDirectionCode and LOTSequenceNumber should be provided.	
LOTSequenceNumber	Number, 4 characters		Either WalkSequenceNumber or combination of LOTSequenceDirectionCode and LOTSequenceNumber should be provided	
Sequence Block ENDS				
WalkSequenceNumber	Number, 5 characters		Either WalkSequenceNumber or combination of LOTSequenceDirectionCode and LOTSequenceNumber	
Choice Block ENDS				
Choice Block BEGINS			Optional Either IMB or PlantCode with DeliveryPointZip OR DeliveryCOntainerID with DeliveryPointZip is required, if this choice block is used.	

Copyright © 2011 USPS®. All Rights Reserved.

Mail.XML 9.0C - MailPieceUpdateRequest				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
IMB Block	IntelligentMailBarcodeType	This is a complex type	Required Block. Only one occurrence is allowed	See Appendix C for Details
Sequence Block BEGINS				
PlanetCode	mailxml_base:planetCodeType	Refer 'planetCodeType' simple type	Not required	Refer appendix B
DeliveryPointZIP	Mailxml_base:routingZipCodeType	Refer 'routingZipCodeType' simple type	Conditionally required if PlanetCode is submitted	See Appendix B
Sequence Block ENDS				
Sequence Block BEGINS				
DeliveryContainerID	Numeric string, 22 characters		Field not being supported	
DeliveryPointZIP	Mailxml_base:routingZipCodeType	Refer 'routingZipCodeType' simple type	Field not being supported in conjunction with DeliveryContainerID	See Appendix B
Seuqnce Block ENDS				
Choice Block ENDS				
PieceID	String, 22 characters		Required	
WastedPieceIndicator	mailxml_base:wastedPieceIndicatorType	Refer 'wastedPieceIndicatorType' simple type	Not required	Refer Appendix B
MLOCRrateANDpostageMarking	String, 7 characters	Letters/Flats P1/F1 = Barcoded 1-ounce Permit Imprint P2/F2 = Barcoded 2-ounce Permit Imprint P3/F3 = Barcoded 3-ounce Permit Imprint P4/F4 = Barcoded 4-ounce Permit	Not required	

Copyright © 2011 USPS®. All Rights Reserved.

Mail.XML 9.0C - MailPieceUpdateRequest				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
		Imprint /F5 = Barcoded 5-ounce Permit Imprint /F6 = Barcoded 6-ounce Permit Imprint /F7 = Barcoded 7-ounce Permit Imprint /F8 = Barcoded 8-ounce Permit Imprint /F9 = Barcoded 9-ounce Permit Imprint /F0 = Barcoded 10-ounce Permit Imprint /FA = Barcoded 11-ounce Permit Imprint /FB = Barcoded 12-ounce Permit Imprint /FC = Barcoded 13-ounce Permit Imprint 51/MF = Barcoded 5-Digit Meter Postage Affixed – 1 ounce 52/ = Barcoded 5-Digit Meter Postage Affixed – 2 ounces 53/ = Barcoded 5-Digit Meter Postage Affixed – 3 ounces 54/ = Barcoded 5-Digit Meter Postage Affixed – 4 ounces 31/MT = Barcoded 3-Digit Meter Postage Affixed – 1 ounce 32/ = Barcoded 3-Digit Meter Postage Affixed –		

Copyright © 2011 USPS®. All Rights Reserved.

Mail.XML 9.0C - MailPieceUpdateRequest				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
		2 ounces 33/ = Barcoded 3-Digit Meter Postage Affixed – 3 ounces 34/ = Barcoded 3-Digit Meter Postage Affixed – 4 ounces A1/MD = Barcoded AADC Meter Postage Affixed – 1 ounce A2/ = Barcoded AADC Meter Postage Affixed – 2 ounces A3/ = Barcoded AADC Meter Postage Affixed – 3 ounces A4/ = Barcoded AADC Meter Postage Affixed – 4 ounces M1/MX = Barcoded Mixed AADC Meter Postage Affixed – 1 ounce M2/ = Barcoded Mixed AADC Meter Postage Affixed – 2 ounces M3/ = Barcoded Mixed AADC Meter Postage Affixed – 3 ounces M4/ = Barcoded Mixed AADC Meter Postage Affixed – 4 ounces 11/ = Presorted Meter Postage Affixed – 1 ounce 12/ = Presorted Meter Postage Affixed – 2		

Copyright © 2011 USPS®. All Rights Reserved.

Mail.XML 9.0C - MailPieceUpdateRequest				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
		ounces 13/ = Presorted Meter Postage Affixed – 3 ounces 14/ = Presorted Meter Postage Affixed – 4 ounces S1/ = Precanceled $0.15 Stamp Affixed (card) S2/ = S2 Precanceled $0.25 Stamp Affixed		
MoveComplianceUpdateMethod	mailxml_base:moveUpdateMethodType	Refer 'moveUpdateMethodType' simple type	Not required	Refer Appendix B
MailOwner Block	mailOwnerBlockType	Refer complex type in Appendix C	Optional Block	See Appendix C for Details
BarCodeApplicator Block	ParticipantIDType			See Appendix C for Details
MachineID	String, 4 characters		Optional	
ACSKeyline	String, 16 characters		Optional	
MailPieceBlock Block ends				
MailPieceBlockGroup block ends				
MailXMLPieceRangeBlock Block begins			1 to many can be submitted Either MailPieceBlock or MailXMLPieceRangeBlock submitted	
ContainerID	Char 24		Required 1 to many allowed	
ContainerDetailID	String 9	-	Optional 0 to many allowed	

Copyright © 2011 USPS®. All Rights Reserved.

Mail.XML 9.0C - MailPieceUpdateRequest				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
PieceRangeBlock Block begins			Required 1 to many can be submitted	
PieceRangeID	String 22		Required	
IMBarcodeLowerSerialization Block begins			Required Only one can be submitted	
Choice Block BEGINS				
Sequence Block # 1 BEGINS				
MailerID6	mailerID6Type		Required Only one pairing of MailerID and SerialNumber is required If provided, MailerID6 fields must be the same in the IMbarcodeUpperSerialization and IMbarcodeLowerSerialization blocks	Refer Appendix B
SerialNumber9	iMBSerialNumber9Type		Required Only one pairing of MailerID and SerialNumber is required	Refer Appendix B
Sequence Block # 1 ENDS				
Sequence Block # 2 BEGINS				
MailerID9	mailerID9Type		Required Only one pairing of MailerID and SerialNumber is required If provided, MailerID9 fields must be the same in the IMbarcodeUpperSerialization and IMbarcodeLowerSerialization blocks	Refer Appendix B

Copyright © 2011 USPS®. All Rights Reserved.

Mail.XML 9.0C - MailPieceUpdateRequest				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
SerialNumber6	iMBSerialNumber6Type		Required Only one pairing of MailerID and SerialNumber is required	Refer Appendix B
Sequence Block # 2 ENDS				
Choice Block ENDS				
IMBarcodeLowerSerialization Block ends				
IMBarcodeUpperSerialization Block begins			Required Only one can be submitted	
Choice Block BEGINS				
Sequence Block BEGINS				
MailerID6	mailerID6Type		Required Only one pairing of MailerID and SerialNumber is required If provided, MailerID6 fields must be the same in the IMbarcodeUpperSerialization and IMbarcodeLowerSerialization blocks	Refer Appendix B
SerialNumber9	iMBSerialNumber9Type		Required Only one pairing of MailerID and SerialNumber is required	
Sequence Block ENDS				
Sequence Block BEGINS				
MailerID9	mailerID9Type		Required Only one pairing of MailerID and SerialNumber is required If provided, MailerID9 fields must be the same in the IMbarcodeUpperSerialization and	Refer Appendix B

Copyright © 2011 USPS®. All Rights Reserved.

Mail.XML 9.0C - MailPieceUpdateRequest				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
			IMbarcodeLowerSerialization blocks	
SerialNumber6	iMBSerialNumber6Type		Required Only one pairing of MailerID and SerialNumber is required	
Sequence Block ENDS				
Choice Block ENDS				
IMBarcodeUpperSerialization Block ends				
MailPreparer Block	ParticipantIDType		Conditionally required for Full-Service mailings. If not provided then user will get Full-Service compliance error and no Full-Service data feedback will be available to the mailer.	See Appendix C for Details
MailOwner Block	ParticipantIDType		Conditionally required for Full-Service mailings. If not provided then user will get Full-Service compliance error and no Full-Service data feedback will be available to the mailer.	See Appendix C for Details
Choice Block BEGINS			Required ServiceCode or MailClass	
ServiceTypeCode	serviceTypeCodeType		Conditionally required for Full-Service / Mixed Service mailings if Mail Class is not provided.	Refer Appendix B
MailClass	mailClassType		Conditionally required for Full-	Refer Appendix B

Copyright © 2011 USPS®. All Rights Reserved.

Mail.XML 9.0C - MailPieceUpdateRequest				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
			Service / Mixed Service mailings if Service Type Code is not provided.	
Choice Block ENDS				
ServiceLevelIndicator	mailxml_base:serviceLevelIndicatorType	Refer 'serviceLevelIndicatorType' simple type	Required For Full-Service / Mixed Service mailings, the ServiceLevelIndicator field must be populated with 'F' when its associated ContainerID has the ServiceLevelIndicator field in the QualificationReportCreateRequest message populated with 'F'.	Refer Appendix B
Pieces	Non-Negative Integer		Required 1 to many allowed If the FullServiceParticipationIndicator field is populated with a 'F', then the IMbarcodeUpperSerialization block minus the IMbarcodeLowerSerialization block is equal to the piece count and the copy count.	
Copies	Non-Negative Integer		Required 1 to many allowed If the FullServiceParticipationIndicator field is populated with a 'F', then the	

Copyright © 2011 USPS®. All Rights Reserved.

Mail.XML 9.0C - MailPieceUpdateRequest				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
			IMbarcodeUpperSerialization block minus the IMbarcodeLowerSerialization block is equal to the piece count and the copy count.	
PieceRangeBlock Block ends				
MailXMLPieceRangeBlock Block ends				
MailXMLHeaderInfo block begins				
CustomerGroupID	String 25		Optional	
MailingGroupID	nonNegativeInteger		Optional	
MaildatJobID	Mailxml_base:jobIDType		Optional	Refer Appendix B
UserLicenceCode	Mailxml_base:userLicenseCodeType		Optional	Refer Appendix B
MailXMLHeaderInfo block ends				

2.4.15 – MailPieceUpdateRequest

4.32 MailPieceUpdateResponse

Purpose
Accept or reject a request to update a mailpiece or piece range

Error/Return Codes
Refer Section 2.6 to view shared error/return codes and also a list of error/return codes tied this message.

Business Rules
- Will accept if the mailpiece or piece range exists
- Will accept if postage statement is USPS Processing Due
- Will reject if the mailpiece or piece range does not exist
- Will reject if a mailpiece 'W' or 'S' indicators for WastedPieceIndicator have resulted in adjusting an already finalized postage statement
- Will reject if postage statement is finalized or finalized pending payment on the mailpiece or piece range's corresponding container

Copyright © 2011 USPS®. All Rights Reserved.

- The ReturnInfo block will have a description for rejection

4.32.1 MailPieceUpdateResponse Data Structure

Field Description

Mail.XML 9.0C - MailPieceUpdateResponse				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
MailPieceCreateAccept Block begins			Block received upon accepting request 1 to many can be submitted	
MailXMLHeaderInfo block begins				
CustomerGroupID	String 25		Optional	
MailingGroupID	nonNegative Integer		Optional	
MaildatJobID			Optional	
UserLicenseCode			Optional	
MailXMLHeaderInfo block ends				
ReturnInfo Block	ReturnInfo		Optional	See Appendix B for Details
MailPieceCreateAccept Block ends				
MailPieceCreateReject Block begins			Block received upon rejecting request 1 to many can be submitted	
MailXMLHeaderInfo block begins				
CustomerGroupID	String 25		Optional	
MailingGroupID	nonNegative Integer		Optional	
MaildatJobID			Optional	
UserLicenseCode			Optional	
MailXMLHeaderInfo block begins				
ReturnInfo Block	ReturnInfo		Required	See Appendix B for Details
MailPieceCreateReject Block ends				

2.3.73 - MailPieceUpdateResponse

Copyright © 2011 USPS®. All Rights Reserved.

4.33 OpenMailingGroupRequest

Purpose
Allows USPS customers to create mailing groups to submit qualification report, mailpiece, and postage statement information.

Business Rules

- Must be submitted before all other messages for eDoc with the exception of SiblingContainerCreate or ContainerUpdate message
- Multiple mailing groups can be opened for a distinct SubmitterCRID, Permit Number or Publication Number, PostOfficeOfMailingZip, MailingFacility, and MailXMLPresentationCategory
- The dashboard will not display empty mailing groups
- Letters and Flats can both be part of the same mailing group but both require separate postage statements by shape.

4.33.1 OpenMailingGroupRequest Data Structure

Field Description

Mail.XML 9.0C - OpenMailingGroupRequest				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
MailXMLOpenMailGroupRequestHeaderInfo Block begins			Attributes block	
CustomerGroupID	String, 25 characters		Required (attribute)	This is a user/customer identified sequence number that should be tracked internally by customer software.
MailXMLOpenMailGroupRequestHeaderInfo Block ends				
SubmittingParty Block	ParticipantIDType		Required block; Identifies the customer submitting the message	Refer 'ParticipantID Type' complex type in Appendix E.
SubmittingSoftware Block	SubmittingSoftwareType		Required block; Identifies the software submitting the message	Refer 'SubmittingSoftware' complex type in Appendix E.
MailingGroupData Block begins			Provides the basic information for the mailing group Only one must be submitted with OpenMailingGroup	

Copyright © 2011 USPS®. All Rights Reserved.

Mail.XML 9.0C - OpenMailingGroupRequest				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
			Request message	
CustomerDescription	String, 50 characters		Not required	
SubmitterCRID	String, 10 characters		Required	
PermitPublicationData Block	PermitPublication DataType			See Appendix B for Details
PostOfficeOfMailingZip	String, 5 characters		Required	
MailingFacility	String, 10 characters		Conditionally required for a Full-Service/Mixed Service mailing	
MailXmlPresentationCategory	mailxml_base:mailXMLPresentationCategoryType	Refer 'mailXMLPresentationCategoryType' simple type	Required	Refer Appendix B
MailerID	String, 9 characters		Not required	
FullServiceParticipationIndicator	mailxml_base:fspiType	Refer 'fspiType' simple type	Conditionally required for Full-Service/Mixed Service mailing; <BLANK> field is invalid	Refer Appendix B
MailAgreementType	mailxml_base:mailAgreementTypeType	Refer 'mailAgreementTypeType' simple type	Not required	Refer Appendix B
ContractNumber	String, 20 characters		Not required	
OnePassIndicator	Boolean	Yes/No	Conditionally required when MailXMLPresentationCategory is 'M'	
LogicalPhysicalContainerIndicator	mailxml_base:logicalPhysicalContainerIndicatorType	Refer 'logicalPhysicalContainerIndicatorType' simple type	Conditionally required for a Full-Service/Mixed Service mailing	Refer Appendix B
MailingGroupData Block ends				

2.3.74 - OpenMailingGroupRequest

4.34 OpenMailingGroupResponse

Purpose

Copyright © 2011 USPS®. All Rights Reserved.

The OpenMailingGroupResponse will be used by USPS to notify the customer if their request to open a mailing group has been accepted or rejected.

Error/Return Codes

Refer Section 2.6 to view shared error/return codes, Cross message validations, and a list of error/return codes tied this message.

Business Rules

- Will reject if invalid values are provided in the request
- Will reject if MailingGroupData required data does not exist in database
- The ReturnInfo block will have a description for rejection

4.34.1 OpenMailingGroupResponse Data Structure

Field Description

Mail.XML 9.0C - OpenMailingGroupResponse				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
OpenMailingGroupAccept Block begins			Block received upon accepting request	
MailXMLOpenMailGroupResponseHeaderInfo Block begins			Attributes block	
CustomerGroupID	String, 25 characters		Required (attribute)	
MailingGroupID	Non-negative Integer		Required (attribute)	
Status	mailxml_base:statusType	Refer 'statusType' simple type	Not required (attribute)	Refer Appendix B
MailXMLOpenMailGroupResponseHeaderInfo Block ends				
ReturnInfo Block	ReturnInfo			See Appendix B for Details
OpenMailingGroupAccept Block ends				
OpenMailingGroupReject Block begins			Block received upon rejecting request	
MailXMLOpenMailGroupResponseHeaderInfo Block ends				
CustomerGroupID	String, 25 characters		Required (attribute)	

Copyright © 2011 USPS®. All Rights Reserved.

Mail.XML 9.0C - OpenMailingGroupResponse				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
MailingGroupID	Non-negative Integer		Not required (attribute)	
Status	mailxml_base:statusType	Refer 'statusType' simple type	Not required (attribute)	Refer Appendix B
PostOfficeMailingZip	String Exactly 5		Required	
ReturnInfo Block	ReturnInfo			See Appendix B for Details
MailXMLOpenMailGroupResponseHeaderInfo Block ends				
OpenMailingGroupReject Block ends				

2.3.75 - OpenMailingGroupResponse

4.35 OriginalContainerLinkageCancelRequest

Purpose
Used to cancel an existing Container Linkage

Business Rules

- MailingGroupID and CustomerGroupID must exist for an open mailing group
- OriginalContainerLinkageCreateRequest message must be accepted before submitting the OriginalContainerLinkageCancelRequest for the specified MailingGroupID and CustomerGroupID
- Original container and linked container must be on a postage statement with PostageStatementStatus populated with UPD and not undergoing finalization
- Original container submitted through Mail.dat before Ready to Pay status
- Original container submitted through Mail.XML before Ready to Pay status
- Linked container submitted through Mail.dat before Ready to Pay status
- Linked container created through Mail.XML must be on a postage statement with PostageStatementStatus populated with UPD for USPS Processing Due for the specified MailingGroupID
- Cannot cancel linked containers for Bundle-Based Co-Palletization after postage statement finalization

Copyright © 2011 USPS®. All Rights Reserved.

- Cannot cancel linked containers for Tray-Based Co-Palletization after OriginalContainerLinkageCreateRequest has been accepted

4.35.1 OriginalContainerLinkageCancelRequest Data Structure

Field Description

Mail.XML 9.0C - OriginalContainerLinkageCancelRequest				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
OriginalContainerLinkageCreateHeaderInfo block begins			Attributes block	
CustomerGroupID	String, 25 characters		Required field	
MailingGroupID	Non-Negative integer		Required field	
OriginalContainerLinkageCreateHeaderInfo block ends				
SubmittingParty Block	ParticipantIDType		Required block; Identifies the customer submitting the message	Refer 'ParticipantID Type' complex type in Appendix E.
SubmittingSoftware Block	SubmittingSoftwareType		Required block; Identifies the software submitting the message	Refer 'SubmittingSoftware' complex type in Appendix E.
CancelLinkage Block	LinkageType		Required field;	See Appendix E for Details

2.3.76 - OriginalContainerLinkageCancelRequest

4.36 OriginalContainerLinkageCancelResponse

Purpose
Accept or reject a request to cancel a Container Linkage

Error/Return Codes
Refer Section 2.6 to view shared error/return codes and also a list of error/return codes tied this message.

Business Rules
- The ReturnInfo block will have a description for rejection
- Original container created through Mail.dat must exist within the database for the specified UserLicenseCode, MaildatJobID, ContainerID, and UniqueContainerBarcode
- Original Container created through Mail.XML must exist within the database for the specified MailingGroupID and CustomerGroupID

Copyright © 2011 USPS®. All Rights Reserved.

- Linkage created through Mail.XML must exist within the database for the specified MailingGroupID and CustomerGroupID

4.36.1 OriginalContainerLinkageCancelResponse Data Structure

Field Description

Mail.XML 9.0C - OriginalContainerLinkageCancelResponse				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
OriginalContainerLinkageCancelAccept block begins			Response from USPS indicating that the OriginalContainerLinkageCancelRequest message was accepted	
OriginalContainerLinkageHeaderInfo block begins			Attributes block	
CustomerGroupID	String, 25 characters		Required field; must be populated with the same value as the CustomerGroupID in the OriginalContainerLinkageCreateRequest message	
MailingGroupID	Non-Negative integer		Required field; must be populated with the same value as the MailingGroupID in the OriginalContainerLinkageCreateRequest message	
OriginalContainerLinkageHeaderInfo block ends				
CancelLinkage Block	LinkageType		Required field;	See Appendix B for Details
OriginalContainerLinkageCancelAccept block ends				
OriginalContainerLinkageCancelReject block begins			Response from USPS indicating that the OriginalContainerLinkageCancelRequest message was rejected	
OriginalContainerLinkageH			Attributes block	

Copyright © 2011 USPS®. All Rights Reserved.

Mail.XML 9.0C - OriginalContainerLinkageCancelResponse				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
eaderInfo block begins				
CustomerGroupID	String, 25 characters		Required field; must be populated with the same value as the CustomerGroupID in the OriginalContainerLinkageCreateRequest message	
MailingGroupID	Non-Negative integer		Required field; must be populated with the same value as the MailingGroupID in the OriginalContainerLinkageCreateRequest message	
OriginalContainerLinkageHeaderInfo block ends				
CancelLinkage Block	LinkageType		Required field;	See Appendix B for Details
ReturnInfo Block	ReturnInfo		Required field;	See Appendix B for Details
OriginalContainerLinkageCancelReject block ends				

2.3.77 - OriginalContainerLinkageCancelResponse

4.37 OriginalContainerLinkageCreateRequest

Purpose
Used to create a co-palletized container relationship

Business Rules

- Only one OriginalContainer block can be linked to only one LinkedContainer block
- MailingGroupID and CustomerGroupID must exist for an open mailing group
- QualificationReportCreateRequest message must be accepted before submitting the OriginalContainerLinkageCreateRequest message for the specified MailingGroupID and CustomerGroupID
- FormType in the ContainerInfoData block within the QualificationReport block in the QualificationReportCreateRequest message must be populated with FC for First Class, SM for Standard Mail, and PE for Periodicals and Pending Periodicals to link a Mail.XML container through the OriginalContainerLinkageCreateRequest message
- Class from the .mpu file must be populated with 1 for First Class, 2 for Periodicals, 3 for Standard Mail, 5 for Pending Periodicals to link a Mail.dat container through OriginalContainerLinkageCreateRequest message

Copyright © 2011 USPS®. All Rights Reserved.

- Mail Class must be same across a Co-Palletized mailing.
- IncludedInOtherDoc field within the ContainerInfoData block in the QualificationReport block in the QualificationReportCreateRequest message must be populated with O for Original or L for Linked to link a Mail.XML container through the OriginalContainerLinkageCreateRequest message
- Included In Other Documentation field in the .csm file must be populated with O for Original or L for Linked to link a Mail.dat container through the OriginalContainerLinkageCreateRequest message
- Original Container submitted through Mail.XML can be linked to a MailXMLContainer through the OriginalContainerLinkageCreateRequest message
- Original Container submitted through Mail.dat can be linked to a MailXMLContainer through the OriginalContainerLinkageCreateRequest message
    - Users are allowed to submit origin files through either form of eDocumentation (Mail.dat and Mail.XML) for a single consolidated mailing to be submitted with consolidator's Mail.XML file. One option is all origin files are submitted via Mail.dat and the consolidator submits a Mail.XML file for the consolidated job. Another option is some origin files submitted via Mail.dat and other origin files submitted via Mail.XML and the consolidator submits a Mail.XML file for the consolidated job. A consolidator can combine Mail.dat origin containers with Mail.XML origin containers onto the same pallet. In this case, the Consolidator's OriginalContainerLinkageCreateRequest message shall contain both OriginalContainer, MaildatContainer blocks and OriginalContainer, MailXMLContainer blocks which will reference the origin mailings that were previously submitted.

- OriginalContainerLinkageCreateRequest message cannot link Mail.dat container to an original container submitted through Mail.dat or Mail.XML container
- It is strongly recommended to use OriginalContainerLinkageCreateRequest message whenever Copalletizing the mail even when the mailing is a non full-service mailing.
- When Copalletizing Full-Service mailings then this message is required.
- OriginalContainerID, OriginalMailingGroup, and OriginalJobID cannot have been previously linked to a consolidator MailingGroupID
- ContainerID in the OriginalContainer block must be associated to a finalized postage statement for Tray-Based Co-Palletization
- Presentation Category must be the same between the original and linked containers
- Service Level for the linked container cannot be higher than the original container

4.37.1 OriginalContainerLinkageCreateRequest Data Structure

Field Description

Mail.XML 9.0C - OriginalContainerLinkageCreateRequest				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
OriginalContainerLinkageCreateHeaderInfo block begins			Attributes block	
CustomerGroupID	String, 25 characters		Required field	
MailingGroupID	Non-Negative integer		Required field	
OriginalContainerLinkageCreateHeaderInfo block ends				

Copyright © 2011 USPS®. All Rights Reserved.

Mail.XML 9.0C - OriginalContainerLinkageCreateRequest				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
SubmittingParty Block	ParticipantIDType		Required block; Identifies the customer submitting the message	Refer 'ParticipantID Type' complex type in Appendix E.
SubmittingSoftware Block	SubmittingSoftwareType		Required block; Identifies the software submitting the message	Refer 'SubmittingSoftware' complex type in Appendix E.
CreateLinkage Block	LinkageType		Required field;	See Appendix E for Details

2.3.78 - OriginalContainerLinkageCreateRequest

4.38 OriginalContainerLinkageCreateResponse

Purpose
Accept or reject a request Container Linkage request

Error/Return Codes
Refer Section 2.6 to view shared error/return codes and also a list of error/return codes tied this message.

Business Rules
- The ReturnInfo block will have a description for rejection
- Response – Original Container for the specified UserLicenseCode, MaildatJobID, ContainerID, and UniqueContainerBarcode must exist in the database if submitted through Mail.dat
- Response – Original Container for the specified MailingGroupID and CustomerGroupID must exist in the database if submitted through Mail.XML

4.38.1 OriginalContainerLinkageCreateResponse Data Structure

Field Description

Mail.XML 9.0C - OriginalContainerLinkageCreateResponse				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
LinkedContainerCreateAccept Block begins			Response from USPS indicating that the OriginalConatinerLinkageCreateRequest message was accepted	
OriginalContainerLinkageHeaderInfo block begins			Attributes block	

Copyright © 2011 USPS®. All Rights Reserved.

Mail.XML 9.0C - OriginalContainerLinkageCreateResponse				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
CustomerGroupID	String, 25 characters		Required field; must be populated with the same value as the CustomerGroupID in the OriginalContainerLinkageCreateRequest message	
MailingGroupID	Non-Negative integer		Required field; must be populated with the same value as the MailingGroupID in the OriginalContainerLinkageCreateRequest message	
OriginalContainerLinkageHeaderInfo block ends				
LinkageCreated Block	LinkageType		Required field;	See Appendix E for Details
ReturnInfo Block	ReturnInfo		Required field;	See Appendix B for Details
LinkedContainerCreateAccept block ends				
LinkedContainerCreateReject			Response from USPS indicating that the OriginalConatinerLinkageCreateRequest message was rejected	
OriginalContainerLinkageCreateHeaderInfo			Attributes block	
CustomerGroupID	String, 25 characters		Required field	
MailingGroupID	Non-Negative integer		Required field	
OriginalContainerLinkageCreateHeaderInfo				
LinkageRejected Block	LinkageType		Required field	See Appendix E for Details
ReturnInfo Block	ReturnInfo		Required field	See Appendix B for Details

Copyright © 2011 USPS®. All Rights Reserved.

Mail.XML 9.0C - OriginalContainerLinkageCreateResponse				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
LinkedContainerCreateReject block ends				

2.3.79 - OriginalContainerLinkageCreateResponse

4.39 PaymentMessageQueryRequest

After paying for postage, send the PaymentMessageQueryRequest. The request requires the Statement ID, tracking ID, mailing and Customer group ID besides the submitting party and submitting software.

4.39.1 PaymentMessageQueryRequest Data Structure

Field Description

Mail.XML 9.0C - PaymentMessageQueryRequest				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
SubmittingParty	ParticipantIDType		Identifies the customer submitting the message	Refer 'ParticipantID Type' complex type in Appendix D.
SubmittingSoftware	SubmittingSoftwareType		Identifies the software submitting the message	Refer 'SubmittingSoftware' complex type in Appendix D.
PostageMessageHeaderInfo block Opens				
CustomerGroupID	String, 25 characters		Required (attribute)	
MailingGroupID	Non Negative Integer		Required (attribute)	
PostageMessageHeaderInfo block Closes				

2.3.80 - PaymentMessageQueryRequest

4.40 PaymentMessageQueryResponse

PaymentMessageQueryResponse includes a QueryResponseResponse and a QueryError block. The QueryResponse includes Postage statement data blocks for postage statement(s). Each Postage statement data block includes PostageStatementTransactionNumber, CustomerReferenceTransactionNumber, MailingFacility, PostageAmountPaid, DateOfTransaction, and TimeOfTransaction. Both messages include ReturnInfo.

Copyright © 2011 USPS®. All Rights Reserved.

4.40.1 PaymentMessageQueryResponse Data Structure

Field Description

Mail.XML 9.0C - PaymentMessageQueryResponse				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
PostageMessageHeaderInfo block Opens				
CustomerGroupID	String, 25 characters		Required (attribute)	
MailingGroupID	Non Negative Integer		Required (attribute)	
PostageMessageHeaderInfo block Closes				
QueryResults Block Opens				
PaymentMessage Block Opens				
PostageStatementTransactionNumber	String		Optional	
CustomerReferenceTransactionNumber	String		Optional	
MailingFacility	String		Optional	
PostageAmountPaid	Double		Optional	
DateOfTransaction	Date	YYYY-MM-DD	Optional	
TimeOfTransaction	Time	HH:MM:SS	Optional	
PaymentMessage Block Closes				
ReturnInfo	ReturnInfo		Required	Refer 'ReturnInfo' complex type in Appendix D.
QueryResults Block Closes				
QueryError Block Opens				
ReturnInfo	ReturnInfo		Required	Refer 'ReturnInfo' complex type in Appendix D.
QueryError Block Closes				

2.3.81 - PaymentMessageQueryResponse

4.41 PeriodicalStatementCreateRequest

Purpose
Allows the USPS customer to submit a Periodicals postage statement to a mailing group

Business Rules

Copyright © 2011 USPS®. All Rights Reserved.

- Mail owner or preparer must send the OpenMailingGroupRequest message and open a mailing group successfully (receive a MailingGroupID) in an acceptance message before sending this message
- Mail owner or preparer must send the QualificationReportCreateRequest message and receive an accepted response that the mailing is qualified before sending this message
- Mail owner or preparer must send the ContainerBundleReportCreateRequest message and receive an accept response before sending this message
- Mail owner or preparer must send this message before sending the ConsolidatedPeriodicalStatementRequest message
- For full-service or mixed service mailings, there are two options for how to populate the required container information:
    - PeriodicalLineItemData block
        - Include one PeriodicalLineItemData block for each container represented on each line of the postage statement. The container IDs must match an ID of a container from a previously submitted qualification report.
        - Do not include ContainerPostage block. If provided, it will be ignored.
    - ContainerPostage block
        - All containers are represented in the ContainerPostage blocks with the number of pieces and copies for each container. The container IDs must match an ID of a container from a previously submitted qualification report.
        - Do not provide Container IDs in the PeriodicalLineItemData blocks. Lines could potentially then be collapsed together as they would not need to be broken out by container. (If any Container ID is provided, the Container Postage block will be disregarded).
    - Notes:
        - Parent and sibling containers do not need to be represented in either option.
        - Any full-service or mixed service container that is not represented via one of the two above methods will not be sent to SASP and will not receive full-service feedback.
- For full-service and mixed service mailings, each container ID in the postage statement message (either in the PeriodicalLineItemData block or in the ContainerPostage block) must exist in a previously submitted QualificationReportCreateRequest message.
- For full-service and mixed service mailings, each container ID in the postage statement message (either in the PeriodicalLineItemData block or in the ContainerPostage block) must exist in a MailPieceCreateRequest message submitted either before or after the Periodical Statement.
- For full-service and mixed service mailings, the total number of pieces per container ID in the postage statement message must not exceed the total number of pieces per container ID in the QualificationReportCreateRequest message.
- For full-service and mixed service mailings, the total number of pieces in the QualificationReportCreateRequest message exactly match the total number of pieces in the MailPieceCreateRequest message for each container ID included in the postage statement message.
- Firm Bundles and Addressed Supplements;
    - For a mailing that includes neither Addressed Supplements nor Firm Bundles, the number of copies must equal the number of pieces
    - For a mailing including Firm Bundles and no Addressed Supplements, the number of pieces cannot exceed the number of copies
    - For a mailing including Addressed Supplements and no Firm Bundles, the number of copies cannot exceed the number of pieces
    - The number of In-County Copies and Outside-County Copies must match between Piece and Pound postage lines.

Copyright © 2011 USPS®. All Rights Reserved.

    - The sum of InCountyAddressedSupplementPieces, OutsideCountyAddressedSupplementPieces, and PiecesExcludingAddressedSupplmentPieces must equal the total pieces submitted
    - The number of InCountyAddressedSupplementPieces and OutsideCountyAddressedSupplementPieces cannot exceed the number of In-County and Outside-County pieces, respectively
- Beginning in Release 25.0.0, the system will support government Inside-County Periodical and Pending Periodical mailings.
- Beginning in Release 26.0.0, Rate Categories AF, BF, DF, GF, and KF are not supported for First-Class Mail, Standard Mail, or Periodicals submitted after the January 2, 2011 price changed.
- Beginning in Release 26.0.0, the number of pieces must equal the number of copies when the mailing does not include Firm Bundles or Addressed Supplements and InOutCountyIndicator is N when the Postage Statement Mailing date is after the January 2, 2011 price change date
- Beginning in Release 26.0.0, the number of pieces must be less than or equal to the number of copies when the mailing includes Firm Bundles but does not have any Addressed Supplements and InOutCountyIndicator is N.
- Beginning in Release 26.0.0, the number of pieces must be greater than or equal to the number of copies when the mailing includes Addressed Supplements but does not have Firm Bundles and InOutCountyIndicator is N.
- For the Combined/Commingled Mailing – user must first send the BeginCombinedMailingRequest message prior to sending the PostageStatement messages.
- Beginning in Release 28.0.0, the *PostalOne!* system will not store an update made to the AdPercent field that was submitted in the DocumentVersionData block in the PeriodicalStatementCreateRequest message submitted after the first PeriodicalStatementCreateRequest message has been submitted to a mailing group for each unique version in that mailing group.
- The *PostalOne!* system will store the AdPercent submitted in the first PeriodicalStatementCreateRequest when it does not match the value submitted in the last accepted qualification report message.
- Beginning in Release 28.0.0, the *PostalOne!* system will not store an update made to the PieceWeight field that was submitted in the DocumentVersionData block in the PeriodicalStatementCreateRequest message submitted after the first PeriodicalStatementCreateRequest message has been submitted to a mailing group for each unique version in that mailing group.

Note - Important information on combined and consolidated postage statements:

(This note comprised of the following three parts, please review)

Part A – Currently, the Mail.XML specs allows the user to provide different data for the fields listed in Part C below for each postage statement request. During a Combined Mailing Request or during a Consolidated Periodical Postage Statement Request, the values of these fields (listed in Part C) have to be same from a business and processing stand-point. The current implementation of Mail.XML does not provide a feature where the user could supply this data for all of the postage statements that are consolidated or combined. A future release of Mail.XML and *PostalOne!* will cater to this requirement where the user will be required to provide with only one set of data (listed in Part C) for the whole message set of combined or consolidated postage statements. However, in the current implementation, USPS recommends all users to follow the set of instructions provided in section.

Part B – For the following set of postage statement message requests, follow the instructions documented in Part C below.

- BeginCombinedMailingRequest

Copyright © 2011 USPS®. All Rights Reserved.

- EndCombinedMailingRequest
- ConsolidatedPeriodicalStatementCreateRequest
- PeriodicalStatementCreateRequest
- PostageStatementCreateRequest

Part C – For all of the postage statement create requests (items 3, 4, and 5 from above), during a Combined Mailing request (meaning postage statements enclosed in between items 1 and 2 from above) and for ConsolidatedPeriodicalStatementCreateRequest user must provide the same values inside all of the postage statements for the following fields.

- IssueDate
- IssueNumber
- VolumeNumber
- CustomerReferenceID
- AgencyCostCode
- PermitPublicationData *(block of PermitHolderData block)*
- PostagePaymentMethod
- RateType
- ProcessingCategory

4.41.1 PeriodicalStatementCreateRequest Data Structure

Field Description

Mail.XML 9.0C - PeriodicalStatementCreateRequest				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
PeriodicalStatementCreate Request Message BEGINS				
MailXMLPostageStatement RequestHeaderInfo block	Attributes		Attributes block	See Appendix C for Details
SubmittingParty Block	ParticipantIDType		Required block; Identifies the customer submitting the message	See Appendix C for Details
SubmittingSoftware Block	SubmittingSoftwa reType		Required block; Identifies the software submitting the message	See Appendix C for Details
CreatePeriodicalStatement block begins			Required block; contains data critical to postage statement calculation	
AdvertisingPercentage	Mailxml_base:Per		Required field; 5	Refer simple

Copyright © 2011 USPS®. All Rights Reserved.

Mail.XML 9.0C - PeriodicalStatementCreateRequest				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
	centageType		total digits with a max value of 100.00	type 'Percentage Type' in Appendix B
DeliveryStatisticsFileDate	Date	-	Optional To allow USPS to validate the correct file for simplified addresses.	-
AutomationAddressMatchDate	Date	YYYY-MM-DD	Optional field; Required for Automation mailings. The system will validate that this field cannot be more than 90 calendar days before the PostageStatement MailingDate for Carrier Route mail (RateCategory A, B, D, AF, BF, or DF). The field cannot be more than 180 calendar days before the PostageStatement MailingDate for non-Carrier Route Mail (RateCategory E, H, L, L1, L2, L3, or L4).	
CustomerReferenceID	String, 40 characters		Optional field; Used to populate Customer Reference ID. Mailers may submit up to 999 unique CustomerReferenceIDs.	CustomerReferenceID represents CAPS Account Number
UserPostageStatementID	String, 10 characters		Optional field; Used to populate User Postage Statement ID to uniquely	

Copyright © 2011 USPS®. All Rights Reserved.

Mail.XML 9.0C - PeriodicalStatementCreateRequest				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
			identify postage statement	
CarrierRouteAddressMatchDate	Date	YYYY-MM-DD	Optional field; Required for Carrier Route Automation pieces	
CarrierRouteSequencingDate	Date	YYYY-MM-DD	Optional field; Required for Carrier Route Sequencing pieces	
CertificationData block	CertificationDataType		Required block; data used in the certification statement section of the postage statement	See Appendix C for Details
ContainerCount block	mailxml:containerCountType		Required block; at least one of the fields in this block must be populated with a nonzero value	Refer Appendix C
CopyWeight	Double		Required field; used for *PostalOne!* postage calculation, accepts up to four decimal places. The value of CopyWeight must be in Pounds.	
EditionCode	String, 20 characters		Optional field; printed on postage statement if provided	
FirstIssueDate	Date	YYYY-MM-DD	Optional field; not used by *PostalOne!*	
FormType	mailxml_base:formType	Refer 'formType' simple type	Required field	Refer Appendix B
IssueDate	Date	YYYY-MM-DD	Required field	
IssueFrequency	String, 20 characters		Optional field; populated with the frequency the postage statement comes from Publication data	
LastIssueDate	Date	YYYY-MM-DD	Optional field; not used by *PostalOne!*	
PostageStatementMailingDate	Date	YYYY-MM-DD	Required field; Used to determine	

Copyright © 2011 USPS®. All Rights Reserved.

Mail.XML 9.0C - PeriodicalStatementCreateRequest				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
			prices and display on postage statement It may be up to one year in future or back dated to the most recent price change	
Over10	Mailxml_base:yesNo	Yes = Subscribers or Requesters over the 10% rule No = No subscribers or requesters over the 10% rule	Required field	
LimitedCirculationDiscountClaimed	yesNo	Yes = discount claimed No = no discount claimed	Required field	
PeriodicalLineItemData block begins			Required block; data used to generate specific line items of postage statement (0 to many pairings)	
Copies	Non-negative Integer		Optional field; total copies for pound postage lines	
ContainerDetailID	String, 9	-	Optional to link qualification report to periodical statement	-
DiscountQty	Double		Optional field; Required when PeriodicalPrice is 1 to indicate In County number of addressed DDU pieces; must be a Non-negative integer.	
PeriodicalPrice	mailxml_base:periodicalPriceType	Refer 'periodicalPriceType' simple type	Optional field *PostalOne!* allows only the value 1 in the request message to indicate the	Refer Appendix B

Copyright © 2011 USPS®. All Rights Reserved.

Mail.XML 9.0C - PeriodicalStatementCreateRequest				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
			Addressed DDU Pieces discount. The system will validate that Zone is DDU, InOutCountyIndicator is I, and DiscountQuantity is populated.	
InOutCountyIndicator	Mailxml_base:inCountyOutCountyIndicatorType	Refer 'inCountyOutCountyIndicatorType' simple type	Required field	Refer Appendix B
LineLabel	String, 80 characters		Optional field; this field may be overwritten during postage statement calculation	

Copyright © 2011 USPS®. All Rights Reserved.

LineNumber	String, 3 characters		Optional field; this field may be overwritten during postage statement calculation This field will be ignored if populated; LineNumber will only be taken into account for Full-Service discount lines	
NonCopies	Non-negative Integer		Optional field; Required for NonSubscriber copies or NonRequester copies for piece and pound postage lines. At least one of SubReqCopies and NonCopies must be populated with a non-negative integer.	
PieceRate	Double		Optional field; not used by *PostalOne!* If populated up to three decimal places are accepted.	
Pieces	Non-negative Integer		Optional field; Required for piece postage lines (i.e. when RateCategory is populated)	
PostageAmount	Double		Optional field; not used by *PostalOne!* Accepts up to four decimals when populated.	
PoundRate	Double		Optional field; not used by *PostalOne!* If populated up to three decimal places are accepted.	

Copyright © 2011 USPS®. All Rights Reserved.

RateCategory	Mailxml_base:rateCategoryType	Refer 'rateCategoryType' simple type	Optional field required for piece postage lines. It cannot be populated when Zone, PeriodicalPrice, or ChargeableContainerLevel are populated.	Refer Appendix B
Section	String, 1 character		Optional field; not used by *PostalOne!* This field will be ignored if populated; Section will only be taken into account for Full-Service discount lines	
SubReqCopies	Non-negative Integer		Optional field; Required for Subscriber copies or Requester copies for piece and pound postage lines. At least one of SubReqCopies and NonCopies must be populated with a non-negative integer.	
Zone	mailxml_base:zoneICType	Refer 'zoneICType' simple type	Optional field; Required for pound postage lines. It cannot be populated when RateCategory is populated.	Refer Appendix B
ChargeableContainerType	mailxml_base:chargeableContainerType	Refer 'chargeableContainerType' simple type	Optional field; Required for Outside County Container charge lines. Must also populate ChargeableContain	Refer Appendix B

Copyright © 2011 USPS®. All Rights Reserved.

			erLevel, ChargeableEntryLevel, and Containers.	
ChargeableContainerLevel	mailxml_base:chargeableContainerLevelType	Refer 'chargeableContainerLevelTYpe' simple type	Optional field; Required for Outside County container and bundle charge lines. Must also populate containers or Bundles. Cannot be populated if RateCategory or PeriodicalPrice are populated. (<BLANK> is not a value being supported)	Refer Appendix B
ContainerID	String 6 characters		Optional field	
ChargeableBundleLevel	mailxml_base:chargeableBundleLevelType	refer 'chargeableBundleLevelType' simple type	Optional field; Required for Outside County container and bundle charge lines. Must also populate bundles and ChargeableCOntainerLevel. (<BLANK> is not a value being supported)	Refer Appendix B
Bundles	Double		Optional field; Required for Outside County bundle charge lines. Must also populate ChargeableBundleLevel and ChargeableContainerLevel. Cannot be populated if Containers is populated. (*PostalOne!* accepts up to four decimal places on	

Copyright © 2011 USPS®. All Rights Reserved.

			each line)	
ChargeableEntryLevel	mailxml_base:chargeableEntryLevelType	Refer 'chargeableEntryLevelType' simple type	Optional field; Required for Outside County container charge lines. Must also populate ChargeableContainerLevel, ChargeableContainerType, and Containers.	Refer Appendix B
Containers	Double		Optional field; Required for Outside County container charge lines . Must also populate ChargeableContainerLevel, ChargeableContainerType, and ChargeableEntryLevel. Cannot be populated if Bundles is populated (*PostalOne!* accepts up to four decimal places on each line)	
MachinableFlag	Mailxml_base:yesNo	Yes No	Optional field; Required for piece postage lines with processing category flats.	
FullServiceParticipationIndicator	Mailxml_base:fspiType	Refer 'fspiType' simple type	Optional field, used for a piece postage line to indicate Full-Service pieces.	Refer Appendix B
USPSPackageUniqueCharacteristic	Mailxml_base:uspsPackageUniqueCharacteristicType	Simple type	Optional	Refer Appendix B
USPSPriceIncentiveType	Mailxml_base:USPSPriceIncentiveType	Simple Type	Optional The *PostalOne!* system does not perform any validation on PermitNumber when this field data	Refer Appendix B

Copyright © 2011 USPS®. All Rights Reserved.

			is provided. The Mailer can use "PostageAffixedReplyRidesFree" only for First Class Mail Letters and must be Full-Service IMb mail pieces weighing between 1 to 1.2 Oz but will be processed at 2Oz price rate. Reply Rides Free is not supported for metered mailings with mail piece weights reported as 1 oz.	
PeriodicalLineItemData block ends				
PostagePaymentMethod	Mailxml_base:postagePaymentMethodType	Refer 'postagePaymentMethodType' simple type	Required field	Refer Appendix B
ProcessingCategory	Mailxml_base:processingCategoryType	Refer 'processingCategoryType' simple type	Required field	Refer Appendix B
PublicationTitle	String, 60 characters		Optional field, *PostalOne!* uses this to get the Title	
CombinedMailingID	Non-negative Integer		Optional, required for combined mailing. See BeginCombinedMailingRequest for business rules.	
RateType	Mailxml_base:rateType	Refer 'rateType' simple type	Required field	Refer Appendix B
SingleRideAlongWeight	Double		Optional, required for a Ride Along weight in pounds. *PostalOne!* accepts up to four decimal places. * Populating this field indicates ride-along in mailing. The value of	

Copyright © 2011 USPS®. All Rights Reserved.

			SingleRideAlongWeight must be in Pounds.	
StatementSequenceNumber	String, 20 characters		Optional field; displayed on postage statement if provided	
EntryFacilityType	Mailxml_base:entryFacilityType	Refer 'entryFacilityType' simple type	Optional field; Required for discounts on dropping to entry facility type	Refer Appendix B
EntryZIP	Numeric, exactly 5 characters		Optional field; displayed on the postage statement register info if provided	
AgencyCostCode	Mailxml_base:agencyCostCodeType	Numeric, 5 or 6 characters	Optional field; Required if a government publication (can start with leading zeros)	Refer Appendix B
RepositionableNotesIndicator	Mailxml_base:yesNo	No = no repositionable notes Yes = repositionable notes	Required field	
DocumentVersionData block BEGIN	DocumentVersionData Type		Optional Block	See Appendix B for Details
VersionID	String, 10 characters		Required;	
VersionName	String, 12 characters		Required;	
VersionDescription	String, 30 characters		Optional	
PieceWeight	Decimal		Required PieceWeight must be provided must be in Pounds.	
AdPercent	Mailxml_base:percentageType		Optional field. Must match AdvertisingPercentage when provided.	Refer 'percentageType' simple type in Appendix B
RateAffixed	Decimal	-	Optional field. Required when PermitType is MT or PC. Accepts up to three decimals	-

Copyright © 2011 USPS®. All Rights Reserved.

			when populated.	
ContentOfMailType	Mailxml_base:contentofmailtype	Refer this simple type in Appendix C	Optional	Refer Appendix B
StandardFlatType	Mailxml_base:standardFlatTypeType	Refer this simple type in Appendix C	Optional	Refer Appendix B
USPSPriceIncentiveType	Mailxml_base:USPSPriceIncentiveType	Simple Type	Optional The *PostalOne!* system does not perform any validation on PermitNumber when this field data is provided. The Mailer can use "PostageAffixedReplyRidesFree" only for First Class Mail Letters and must be Full-Service IMb mail pieces weighing between 1 to 1.2 oz but will be processed at 2Oz price rate.	Refer Appendix B
USPSPriceIncentiveID	Mailxml_base:USPSPriceIncentiveIDType	Simple Type	Optional This field is ignored.	Refer Appendix B
DocumentVersionData Block END				
MoveUpdateMethod	Mailxml_base:moveUpdateMethodType	Refer 'moveUpdateMethodType'	Optional field; does not apply for Periodicals	Refer Appendix B
VolumeNumber	String, 5 characters		Optional field	
IssueNumber	String, 6 numbers		Optional field	
InCountyAddressedSupplementPieces	Non-negative Integer		Optional field	
OutsideCountyAddressedSupplementPieces	Non-negative Integer		Optional field	
PiecesExcludingAddressedSupplementPieces	Non-negative Integer		Required field, replaces total pieces in postage statement	
ContainerPostage Block	Mailxml:containerPostageType		Required by the *PostalOne! for Full-*	Refer 'containerPos

Copyright © 2011 USPS®. All Rights Reserved.

			Service or Mixed mailings (Full-Service plus another type)	tageType' complex in Appendix C
MailingAgentData block	mailerDataRequestType		Required field; Required if there is a mailing agent for the mail owner	See Appendix C for Details
PublisherData block	MailerDataRequestType		Required block; *PostalOne!* uses this data to bill the postage statement. must contain the Publication Number of the Periodical or the combination of PermitNumber, PermitType with value PP, and PermitZIP4 representing pending Periodical.	See Appendix C for Details
PendingPostageAmount	Double	-	Optional, required for pending Periodical permit type PP, up to two decimal places accepted.	
CreatePeriodicalStatement Data block ends				
PeriodicalStatementCreate Request Message ENDS				

4.42 PeriodicalStatementCreateResponse

Purpose
Response to the customer's request to create a Periodical Postage Statement

Error/Return Codes
Refer Section 2.6 to view shared error/return codes and also a list of error/return codes tied this message.

Business Rules
- Message will be sent in response to and must follow the PeriodicalStatementCreateRequest

4.42.1 PeriodicalStatementCreateResponse Data Structure

Field Description

Copyright © 2011 USPS®. All Rights Reserved.

Mail.XML 9.0C - PeriodicalStatementCreateResponse				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
PeriodicalStatementCreateAccept block begins			Response from USPS indicating that the PeriodicalStatementCreateRequest message was accepted and a Periodical Postage Statement was created (choice between StatementID, UserPostageStatementID, TotalPostage, TotalPostageDue, and ReturnInfo block or TrackingID and ReturnInfo block)	
MailXMLPostageStatementResponseHeaderInfo block	MailXMLPostageStatementResponseHeaderInfo		Attributes block	See Appendix E for Details
StatementID	Non-negative integer		Required field	
UserPostageStatementID	String, 10 characters		Optional field	
TotalPostage	Double		Required field, two decimal points provided. If not generated for Statement ID there will be a reject block.	
TotalPostageDue	Double		Required field, may be zero, two decimal points provided. If not generated for Statement ID there will be a reject block.	
ReturnInfo block	ReturnInfo		Optional block; paired with StatementID, UserPostageStatementID, TotalPostage, and TotalPostageDue	See Appendix E for Details
PeriodicalStatementCreate				

Copyright © 2011 USPS®. All Rights Reserved.

Mail.XML 9.0C - PeriodicalStatementCreateResponse				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
Accept block ends				
PeriodicalStatementCreateReject block begins			Response from USPS indicating that the PeriodicalStatementCreateRequest message was rejected and a Periodical Postage Statement was not created and the reason why	
MailXMLPostageStatementResponseHeaderInfo block	MailXMLPostageStatementResponseHeaderInfo			See Appendix E for Details
ReturnInfo block	ReturnInfo		Required block	See Appendix E for Details
PeriodicalStatementCreateReject block ends				

2.3.82 - PeriodicalStatementCreateResponse

4.43 PeriodicalStatementQueryRequest

Purpose
Allows the USPS customer to retrieve a Periodicals postage statement

Business Rules

- Must be submitted after a periodical postage statement has been created (after the PeriodicalStatementCreateRequest message has been accepted)

4.43.1 PeriodicalStatementQueryRequest Data Structure

Field Description

Mail.XML 9.0C - PeriodicalStatementQueryRequest				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
MailXMLPostageStatementRequestHeaderInfo block	MailXMLPostageStatementRequestHeaderInfo		Attributes block	See Appendix E for Details
SubmittingParty Block	ParticipantIDType		Required block; Identifies the customer submitting the message	See Appendix E for Details
SubmittingSoftware Block	SubmittingSoftwareType		Required block; Identifies the software submitting	See Appendix E for Details

Copyright © 2011 USPS®. All Rights Reserved.

Mail.XML 9.0C - PeriodicalStatementQueryRequest				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
			the message	
StatementID	Non-negative integer		Required field	
IncludeChildStatement	yesNo	Yes/No	Required field, if No only the requested Statement ID is returned. If Yes, the statement ID requested and its child statements are returned.	

2.3.83 - PeriodicalStatementQueryRequest

4.44 PostageStatementCreateRequest

Purpose
Allows the USPS customer to submit a 3600-series postage statement to a mailing group. This message allows the customer to submit either the basic-form or extended-form of the 3600-series postage statement, in order to accommodate either singular or multiple entries for each line item, which allows the customer to submit non-identical piece weight mailings.

Business Rules

- Must be submitted after all mailpieces or piece ranges are submitted for a mailing group
- Postage adjustments will be expected for postage statements with wasted or spoiled pieces
- The 'Section' and 'Line Number' elements will be corrected if an error is made in submitting
- The only instance where ‘Section’ and ‘Line Number’ will be taken as submitted (and not corrected/changed) is for the Full-Service discount lines. Otherwise, the full-service discount lines will be generated based on a FullServiceParticipationIndicator of ‘F’ in the PostageStatementLineItemData block.
- The PermitHolderforAPData block will be required for Postage Payment Method of 'S' or 'M' and cannot be a meter. It must be either an OI or PI permit.

The FormType field cannot be 'PE' = Periodicals Class for a PostageStatementCreateRequest. In this case use the PeriodicalStatementCreateRequest message.

- For full-service or mixed service mailings, there are two options for how to populate the required container information:
    - LineItemData block
        - Include one PostageStatementLineItemData block for each container represented on each line of the postage statement. The container IDs must match an ID of a container from a previously submitted qualification report.
        - Do not include ContainerPostage block. If provided, it will be ignored.
    - ContainerPostage block
        - All containers are represented in the ContainerPostage blocks with the number of pieces and copies for each container. The container IDs must match an ID of a container from a previously submitted qualification report.
        - Do not provide Container IDs in the LineItemData blocks. Lines could potentially then be collapsed together as they would not need to be broken out by container. (If any Container ID is provided, the Container Postage block will be disregarded).
    - Notes:

Copyright © 2011 USPS®. All Rights Reserved.

        - Parent and sibling containers do not need to be represented in either option.
        - Any full-service or mixed service container that is not represented via one of the two above methods will not be sent to SASP and will not receive full-service feedback.
- For full-service and mixed service mailings, each container ID in the postage statement message (either in the LineItemData block or in the ContainerPostage block) must exist in a previously submitted QualificationReportCreateRequest message.
- For full-service and mixed service mailings, each container ID in the postage statement message (either in the LineItemData block or in the ContainerPostage block) must exist in a MailPieceCreateRequest message submitted either before or after the Postage Statement.
- For full-service and mixed service mailings, the total number of pieces per container ID in the postage statement message must not exceed the total number of pieces per container ID in the QualificationReportCreateRequest message.
- For full-service and mixed service mailings, the total number of pieces in the QualificationReportCreateRequest message exactly match the total number of pieces in the MailPieceCreateRequest message for each container ID included in the postage statement message.
- PublicationNumber cannot be populated in a PostageStatementCreateRequest message
- For MLOCR First-Class mailings claiming Single Piece prices, the PermitType in the PermitHolderData block in the PostageStatementCreateRequest message must be set to Permit Imprint (PI), Metered (MT), or PC (Precanceled Stamps). At least one SortationLevel in QualificationReportCreateRequest message must be set to “AN.”
  NOTE: Wherever SortationLevel is used, it is defined as Type=ContainerLevelType.

- Beginning in Release 26.0.0, FormType PM for Priority Mail is not supported after the January 2, 2011 price change date.
- Beginning in Release 26.0.0, FormType PP for Package Services Parcel Post is not supported after the January 2, 2011 price change date.
- Beginning in Release 26.0.0, Standard Mail Parcels are not supported for 7.0 and 8.0 version files that are submitted after the January 2, 2011 price change date.
- Beginning in Release 26.0.0, Rate Categories AF, BF, DF, GF, and KF are not supported for First-Class Mail, Standard Mail, or Periodicals submitted after the January 2, 2011 price change date.
- Beginning in Release 26.0.0, the ProcessingCategory field cannot be populated with IR for Bound Printed Matter Package Service mailings submitted after the January 2, 2011 price change date.
- Beginning in Release 26.1, First-Class Commercial Plus Parcels will be accepted after the April 2011 price change date when the following conditions are met:
    - FormType in the CreatePostageStatement block is FC (First-Class)
    - PresentationCategory in the CreatePostageStatement block is PF (Parcel, First-Class)
    - PriceType in the CreatePostageStatement block is commercialplus
- Beginning in Release 26.1, the following ServiceCode values will be supported for First-Class Commercial Plus Parcels:
    - CM – Certified Mail
    - COD – Collect on Delivery
    - COM – Certificate of Mailing
    - DC – Delivery Confirmation
    - IM – Insured Mail
    - RD – Restricted Delivery
    - RR – Return Receipt
    - RRE – Return Receipt Electronic
    - SC – Signature Confirmation
- SH – Special Handling

Copyright © 2011 USPS®. All Rights Reserved.

Note - Important information on combined and consolidated postage statements:

Part A – Currently, the Mail.XML specs allows the user to provide different data for the fields listed in Part C below for each postage statement request. During a Combined Mailing Request or during a Consolidated Periodical Postage Statement Request, the values of these fields (listed in Part C) have to be same from a business and processing stand-point. The current implementation of Mail.XML does not provide a feature where the user could supply this data for all of the postage statements that are consolidated or combined. A future release of Mail.XML and *PostalOne!* will cater to this requirement where the user will be required to provide with only one set of data (listed in Part C) for the whole message set of combined or consolidated postage statements. However, in the current implementation, USPS recommends all users to follow the set of instructions provided in section.

Part B – For the following set of postage statement message requests, follow the instructions documented in Part C below.

- BeginCombinedMailingRequest
- EndCombinedMailingRequest
- ConsolidatedPeriodicalStatementCreateRequest
- PeriodicalStatementCreateRequest
- PostageStatementCreateRequest

Part C – For all of the postage statement create requests (items 3, 4, and 5 from above), during a Combined Mailing request (meaning postage statements enclosed in between items 1 and 2 from above) and for ConsolidatedPeriodicalStatementCreateRequest user must provide the same values inside all of the postage statements for the following fields.

- IssueDate
- IssueNumber
- VolumeNumber
- CustomerReferenceID
- AgencyCostCode
- PermitPublicationData *(block of PermitHolderData block)*
- PostagePaymentMethod
- RateType
- ProcessingCategory

4.44.1 PostageStatementCreateRequest Data Structure

Field Description

Mail.XML 9.0C - PostageStatementCreateRequest				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
PostageStatementCreate Request BEGINS				
MailXMLPostageStatement RequestHeaderInfo	MailXMLPostage StatementReque stHeaderInfo attribute	-	Required	Refer this attribute in Appendix D
SubmittingParty	ParticipantIDType	-	Required block;	Refer this

Copyright © 2011 USPS®. All Rights Reserved.

Mail.XML 9.0C - PostageStatementCreateRequest				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
	complex type		Identifies the customer submitting the message	complex type in Appendix D
SubmittingSoftware	SubmittingSoftwareType complex type		Required block; Identifies the software submitting the message	Refer this complex type in Appendix D
CreatePostageStatment	CreatePostageStatementType complex type		Required Only one can be submitted	Refer this complex type in Appendix D
PostageStatementCreate Request ENDS				

2.3.01 – PostageStatementCreateRequest

4.45 PeriodicalStatementQueryResponse

Purpose
Return either the postage statement query results data or the reason why there was a query error

Error/Return Codes
Refer Section 2.6 to view shared error/return codes and also a list of error/return codes tied this message.

Business Rules
- Will accept if StatementID or TrackingID exists
- Will reject if StatementID or TrackingID does not exist
- The ReturnInfo block will have a description for a QueryError

4.45.1 PeriodicalStatementQueryResponse Data Structure

Field Description

Mail.XML 9.0C - PeriodicalStatementQueryResponse				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
PeriodicalStatementQueryResponse Message BEGINS				
MailXMLPostageStatementResponseHeaderInfo block	MailXMLPostageStatementResponseHeaderInfo		Attributes block	See Appendix C for Details

Copyright © 2011 USPS®. All Rights Reserved.

Mail.XML 9.0C - PeriodicalStatementQueryResponse				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
Sequence Block BEGINS				
TrackingID	String, 12	-	Optional. Provides the tracking ID when message fails to get delivered	-
Choice Block BEGINS				
QueryResults block begins			Required block; accepting the query request message and returning the query for a successful PeriodicalStatementQueryRequest message	
PeriodicalStatementDataType Block BEGINS				
AdvertisingPercentage	Mailxml_base:PercentageType		Required field; 5 total digits with a max value of 100.00	*Refer this simple type in Appendix C*
DeliveryStatisticsFileDate	Date	-	Optional. Allows USPS to validate the correct file date for simplified addresses.	-
AutomationAddressMatchDate	Date	YYYY-MM-DD	Optional field; Required for Automation mailings The system will validate that this field cannot be more than 90 calendar days before the PostageStatement	

Copyright © 2011 USPS®. All Rights Reserved.

Mail.XML 9.0C - PeriodicalStatementQueryResponse				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
			MailingDate for Carrier Route mail (RateCategory A, B, D, AF, BF, or DF). The field cannot be more than 180 calendar days before the PostageStatement MailingDate for non-Carrier Route Mail (RateCategory is E, H, L, L1, L2, L3, or L4).	
CustomerReferenceID	String, 40 characters		Optional field; Used to populate Customer Reference ID	CustomerReferenceID represents CAPS Account Number
UserPostageStatementID	String, 10 characters		Optional field; Used to populate User Postage Statement ID to uniquely identify postage statement	
CarrierRouteAddressMatchDate	Date	YYYY-MM-DD	Optional field; Required for Carrier Route Automation pieces	
CarrierRouteSequencingDate	Date	YYYY-MM-DD	Optional field; Required for Carrier Route Sequencing pieces	
CertificationData block	CertificationDataType		Required block; data used in the certification statement section of the postage statement	See Appendix C for Details
ContainerCount block	ContainerCountType		Required block; at least one of the fields in this block must be populated with a nonzero value	See Appendix C for Details
CopyWeight	Double		Required field; used for *PostalOne!* postage calculation,	

Copyright © 2011 USPS®. All Rights Reserved.

Mail.XML 9.0C - PeriodicalStatementQueryResponse				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
			PostalOne! accepts up to four decimals. The value of CopyWeight must be in Pounds.	
EditionCode	String, 20 characters		Optional field; printed on postage statement if provided	
FirstIssueDate	Date	YYYY-MM-DD	Optional field; not used by *PostalOne!*	
FormType	Mailxml_base:formType	Refer 'formType' simple type	Required field	Refer Appendix B
IssueDate	Date	YYYY-MM-DD	Required field	
IssueFrequency	String, 20 characters		Optional field; populated with the frequency the postage statement comes from Publication data	
LastIssueDate	Date	YYYY-MM-DD	Optional field; not used by *PostalOne!*	
PostageStatementMailingDate	Date	YYYY-MM-DD	Required field; Used to determine prices and display on postage statement It may be up to one year in future or back dated to most recent price change	
Over10	Mailxml_base:yes No	Yes = Subscribers or Requesters over the 10% rule No = No subscribers or requesters over the 10% rule	Required field	
LimitedCirculationDiscountClaimed	Mailxml_base:yes No	Yes No	Required field	
PeriodicalLineItemData block begins			Required block; data used to generate specific line items of postage statement (one to many	

Copyright © 2011 USPS®. All Rights Reserved.

Mail.XML 9.0C - PeriodicalStatementQueryResponse				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
			pairings)	
Copies	Non-negative Integer		Optional field; total copies for pound postage lines	
ContainerDetailID	String 9	-	Optional to link qual report to periodical statement	-
DiscountQty	Double		Optional field; Required for corresponding PeriodicalPrice	
PeriodicalPrice	Mailxml_base:periodicalPriceType	Refer 'periodicalPriceType' simple type	Optional field, used if the Periodical Postage Statement line in acceptable values is present.	Refer Appendix B
InOutCountyIndicator	mailxml_base:inCountyOutCountyIndicatorType	Refer 'inCountyOutCountyIndicatorType' simple type	Required field	Refer Appendix B
LineLabel	String, 80 characters		Optional field; this field will be overwritten during postage statement calculation	
LineNumber	String, 3 characters		Optional field; this field will be overwritten during postage statement calculation This field will be ignored if populated; LineNumber will only be taken into account for Full-Service discount lines	
NonCopies	Non-negative Integer		Optional field; Required for NonSubscriber copies or NonRequester copies for pound postage lines	
PieceRate	Decimal		Optional field	

Copyright © 2011 USPS®. All Rights Reserved.

Mail.XML 9.0C - PeriodicalStatementQueryResponse				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
Pieces	Non-negative Integer		Optional field; Required for Piece Postage lines	
PostageAmount	Decimal		Optional field	
PoundRate	Decimal		Optional field	
RateCategory	mailxml_base:rateCategory	Refer 'rateCategory' simple type	Optional field, required for piece postage lines	Refer Appendix B

Copyright © 2011 USPS®. All Rights Reserved.

Section	String, 1 character		Optional field; not used by *PostalOne!* This field will be ignored if populated; Section will only be taken into account for Full-Service discount lines	
SubReqCopies	Non-negative Integer		Optional field; Required for pound postage lines	
Zone	mailxml_base:zoneICType	Refer 'zoneICType' simple type	Optional field; Required for pound postage lines	Refer Appendix B
ChargeableContainerType	mailxml_base:chargeableContainerType	Refer 'chargeableContainerType' simple type	Optional field; Required for Outside County Container charge lines.	Refer Appendix B
ChargeableContainerLevel	mailxml_base:chargeableContainerLevelType	Refer 'chargeableContainerLevelType' simple type	Optional field; Required for Outside County container and bundle charge lines	Refer Appendix B
ContainerID	String, 6		Optional	
ChargeableBundleLevel	mailxml_base:chargeableBundleLevelType	Refer 'chargeableBundleLevelType' simple type	Optional field; Required for Outside County container and bundle charge lines	Refer Appendix B
Bundles	Decimal		Optional field; Required for Outside County bundle charge lines (*PostalOne!* provides four decimal places on each line)	
ChargeableEntryLevel	mailxml_base:chargeableEntryLevelType	Refer 'chargeableEntryLevelType' simple type	Optional field; Required for Outside County container charge lines	Refer Appendix B

Copyright © 2011 USPS®. All Rights Reserved.

Containers	Decimal		Optional field; Required for Outside County container charge lines (*PostalOne!* provides four decimal places on each line)	
MachinableFlag	Mailxml_base:yesNo	Yes No	Optional field; Required for piece postage lines where processing category is flats.	
FullServiceParticipationIndicator	mailxml_base:fspiType	Refer 'fspiType' simple type	Optional	Refer Appendix B
USPSPackageUniqueCharacteristic	Mailxml_base:uspsPackageUniqueCharacteristicType	Refer this simple type in Appendix C	Optional	Refer Appendix B
USPSPriceIncentiveType	Mailxml_base:USPSPriceIncentiveType	Simple Type	Optional The *PostalOne!* system does not perform any validation on PermitNumber when this field data is provided. The Mailer can use "PostageAffixedReplyRidesFree" only for First Class Mail Letters and must be Full-Service IMb mail pieces weighing between 1 to 1.2 oz but will be processed at 2Oz price rate.	Refer Appendix B
USPSPriceIncentiveID	Mailxml_base:USPSPriceIncentiveIDType	Simple Type	Optional This field is ignored.	Refer Appendix B
PeriodicalLineItemData block ends				
PostagePaymentMethod	Mailxml_base:postagePaymentMethodType	Refer 'postagePaymentMethodType'	Required field	

Copyright © 2011 USPS®. All Rights Reserved.

		simple type		
ProcessingCategory	Mailxml_base:processingCategoryType	Refer 'processingCategoryType' simple type	Required field	Refer Appendix B
PublicationTitle	String, 60 characters		Optional field, *PostalOne!* uses this to get the Title	
CombinedMailingID	Non-negative Integer		Optional field, required if a combined mailing	
RateType	Mailxml_base:rateType	Refer 'rateType' simple type	Required field	Refer Appendix B
SingleRideAlongWeight	Decimal		Optional The value of SingleRideAlongWeight must be in Pounds.	
StatementSequenceNumber	String, 20 characters		Optional field; displayed on postage statement if provided	
EntryFacilityType	mailxml_base:entryFacilityType	Refer 'entryFacilityType' simple type	Optional field; Required for discounts on dropping to entry facility type	Refer Appendix B
EntryZip	Numeric, exactly 5 characters		Optional field; displayed on the postage statement register info if provided	
AgencyCostCode	Mailxml_base:agencyCostCodeType		Optional field; Required if a government publication (can start with leading zeros)	Refer this simple type in Appendix C
RepositionableNotesIndicator	Mailxml_ase:yesNo	NO = no repositionable notes Yes = repositionable notes	Required field	
DocumentVersionData block	DocumentVersionData Type		Optional block; Required for Version Summary	See Appendix C for Details

Copyright © 2011 USPS®. All Rights Reserved.

			Report	
MoveUpdateMethod	Mailxml_base:moveUpdateMethodType	Refer 'moveUpdateMethodType' simple type	Optional field; does not apply for Periodicals	Refer Appendix B
VolumeNumber	String, 5	-	Optional	-
IssueNumber	String, 6	-	Optional	-
InCountyAddressedSupplementPieces	Non-negative Integer		Optional	
OutsideCountyAddressedSupplementPieces	Non-negative Integer		Optional	
PiecesExcludingAddressedSupplementPIeces	Non-negative Integer		Required	
ContainerPostage Block	containerPostageType	-	Optional. Allow 0 to many	Refer "containerPostageType" in the Appendix C
StatementID	Non-negative integer		Optional field	
MailClass	mailxml_base:mailClassType	Refer 'mailClassType' simple type	Optional field	Refer Appendix B
Origin	String, 6 characters		Optional field	
PostageStatementStatus	Mailxml_base:postageStatementStatusType		Optional field	Refer Appendix B
TotalCopies	Non-negative Integer		Required field	
TotalPieces	Non-negative Integer		Required field	
TotalPostageAmount	Double		Required field, two decimal places	
TotalWeight	Double		Required field, no decimal places. The value of TotalWeight must be in Pounds.	
MailingAgentData block	mailerDataType		Required field; Required if there is a mailing agent for the mail owner	Refer this complex type in Appendix C
PublisherData block	mailerDataType		Required block; *PostalOne!* uses this data to bill the postage statement	Refer this complex type in Appendix C
PendingPostageAmount	Double	-	Optional, required	

Copyright © 2011 USPS®. All Rights Reserved.

			for pending Periodicals, two decimal places provided.	
PeriodicalStatementData block ends				
ReturnInfo block	basicReturnInfoType		Optional block	See Appendix C for Details
QueryResults block ends				
QueryError block begins			Required block if there are any failed validations in the PeriodicalStatementQueryRequest message or when the query data cannot be provided	
ReturnInfo block	basicReturnInfoType		Required block	See Appendix C for Details
QueryError block ends				
PeriodicalStatementQueryResponse Message ENDS				

2.4.08 – PeriodicalStatementQueryResponse

4.46 PostageAdjustmentCreateRequest

Purpose
Customer provides PostageAdjustmentCreateRequest message to document spoilage and shortage pieces

Business Rules

- Postage adjustment can only occur for the latest mailing date associated with the StatementID in the PostageAdjustment block
- Mail.dat fields cannot be accepted in the PostageAdjustmentCreateRequest message
- PostageAdjustmentCreateRequest will support postage adjustments for both postage statements and periodical postage adjustments
- Beginning in Release 26.1, First-Class Commerical Plus Parcels will be accepted when the following conditions are met:
    - FormType in the CreatePostageStatement block is FC (First-Class)
    - PresentationCategory in the CreatePostageStatement block is PF (Parcel, First-Class)
    - PriceType in the CreatePostageStatement block is commercialplus

4.46.1 PostageAdjustmentCreateRequest Data Structure

Copyright © 2011 USPS®. All Rights Reserved.

Field Description

Mail.XML 9.0C - PostageAdjustmentCreateRequest				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
SubmittingParty Block	ParticipantIDType		Required block; Identifies the customer submitting the message	Refer 'ParticipantID Type' complex type in Appendix E.
SubmittingSoftware Block	SubmittingSoftwareType		Required block; Identifies the software submitting the message	Refer 'SubmittingSoftware' complex type in Appendix E.
UserLicenseCode	String, 4 characters		Field not being supported; using the CustomerGroupID and MailingGroupID	
MaildatJobID	String, 8 characters		Field not being supported; using the CustomerGroupID and MailingGroupID	
CustomerGroupID	String, 25 characters		Required field; must be populated with the same value as the value populated in the CustomerGroupID field in the PostagestatementCreateResponse message	
MailingGroupID	Non-negative Integer		Required field; must be populated with the same value as the value populated in the MailingGroupID field in the PostagestatementCreateResponse message	
PostageAdjustment Block begins			Required field; 1 to many pairings can be submitted	
PostageAdjustmentUserID	String, 12 characters		Required field	

Copyright © 2011 USPS®. All Rights Reserved.

Mail.XML 9.0C - PostageAdjustmentCreateRequest				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
StatementID	Non-negative Integer		Required field; must be populated with the same value as the value populated in the StatementID field in the PostageStatement CreateAccept block of the PostageStatement CreateResponse	
RateType	mailxml_base:rateType	Refer 'rateType' simple type	Optional field	Refer Appendix B
AdjustmentDate	Date	YYYY-MM-DD	Required field Must be populated with a date later than the latest mailing date for the specified MailingGroup, StatementID, and CustomerGroupID	
AdjustmentType	mailxml_base:adjustmentType	Refer 'adjustmentType' simple type	Required field.	Refer Appendix B
AdjustmentAmount	Number		Required field. Accepts up to two decimals. Cannot exceed the total postage on the postage statement.	
CreditDebitIndicator	mailxml_base:creditDebitIndicator	Refer 'creditDebitIndicator' simple type	Required field	Refer Appendix B
TotalPiecesAffected	Non-negative Integer		Required field Cannot exceed the total pieces on the postage statement.	
UserComments	String, 20 characters		Optional field	
UserPostageStatementID	String, 10 characters		Optional field	
AdjustmentStatus	mailxml_base:adjustmentStatusType	refer 'adjustmentStatusTYpe' simple	Optional field	Refer Appendix B

Copyright © 2011 USPS®. All Rights Reserved.

Mail.XML 9.0C - PostageAdjustmentCreateRequest				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
		type		
PostageAdjustment Block ends				

2.3.84 - PostageAdjustmentCreateRequest

4.47 PostageAdjustmentCreateResponse

Purpose
Response from the *PostalOne!* system informing the customer of whether the postage adjustment data sent in the PostageAdjustmentCreateRequest message has been accepted

Error/Return Codes
Refer Section 2.6 to view shared error/return codes and also a list of error/return codes tied this message.

Business Rules
- Must be returned to the customer after the PostageAdjustementCreateRequest message is sent by the customer to *PostalOne!*
- PostageStatementCreateRequest or PeriodicalStatementCreateRequest must be accepted before submitting the PostageAdjustmentCreateRequest for the specified MailingGroupID and CustomerGroupID
- StatementID or UserPostageStatementID specified must exist for a postage statement or periodical postage statement
- Mailing date given must be the latest mailing date for the StatementID specified
- MLOCR mailings cannot have postage adjusted
- PostageStatementStatus must be UPD for USPS Processing Due for the specified StatementID

4.47.1 PostageAdjustmentCreateResponse Data Structure

Field Description

Mail.XML 9.0C - PostageAdjustmentCreateResponse				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
PostageAdjustmentCreateAccept Block begins			Response from USPS indicating that the data in the PostageAdjustment CreateRequest message was accepted	
UserLicenseCode			Field not being supported; using the CustomerGroupID and MailingGroupID	
MaildatJobID			Field not being supported; using	

Copyright © 2011 USPS®. All Rights Reserved.

Mail.XML 9.0C - PostageAdjustmentCreateResponse				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
			the CustomerGroupID and MailingGroupID	
CustomerGroupID	String, 25 characters		Required field; must be populated with the same value as the value populated in the CustomerGroupID field in the PostageStatement CreateAccept block of the PostageStatement CreateResponse	
MailingGroupID	Non-negative Integer		Required field; must be populated with the same value as the value populated in the MailingGroupID field in the PostageStatement CreateAccept block of the PostageStatement CreateResponse	
PostageAdjustmentUserID	String, 12 characters		Required field; 1 to many pairings of PostageAdjustment UserID, PostageAdjustment ConfirmID and ReturnInfo Block can be submitted	
	Non-negative Integer		Required field; must be populated with the same value as the value populated in the StatementID field in the PostageStatement CreateAccept block of the PostageStatement CreateResponse	
ReturnInfo Block	ReturnInfo			See Appendix B

Copyright © 2011 USPS®. All Rights Reserved.

Mail.XML 9.0C - PostageAdjustmentCreateResponse				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
				for Details
PostageAdjustmentCreateAccept Block ends				
PostageAdjustmentCreateReject Block begins			Response from USPS indicating that the PostageAdjustment CreateRequest message was rejected	
UserLicenseCode			Field not being supported	
MaildatJobID			Field not being supported	
CustomerGroupID	String, 25 characters		Required field; must be populated with the same value as the value populated in the CustomerGroupID field in the PostageStatement CreateAccept block of the PostageStatement CreateResponse	
MailingGroupID	Non-negative Integer		Required field; must be populated with the same value as the value populated in the CustomerGroupID field in the PostageStatement CreateAccept block of the PostageStatement CreateResponse	
PostageAdjustmentUserID	String, 12 characters		Required field; 1 to many pairings of PostageAdjustment UserID and ReturnInfo Block can be submitted	
ReturnInfo Block	ReturnInfo		Required field;	See Appendix B for Details
PostageAdjustmentCreateReject Block ends				

Copyright © 2011 USPS®. All Rights Reserved.

2.3.85 - PostageAdjustmentCreateResponse

4.48 PostageStatementCancelRequest

Purpose
Allows the USPS customer to cancel a submitted postage statement (including a Periodicals statement) that has not already been reversed or finalized

Business Rules

- Must be submitted after a postage statement has been created (PeriodicalStatementCreateResponse or PostageStatementCreateResponse indicates accepted)
- Will not be accepted after a postage statement has been finalized (PostageStatementStatus is FIN or FPP.)
- All postage statements in a mailing group is cancelled if a StatementID is not submitted
- Beginning in Release 26.1, First-Class Commerical Plus Parcels will be accepted after the April 2011 price change date when the following conditions are met:
    - FormType in the CreatePostageStatement block is FC (First-Class)
    - PresentationCategory in the CreatePostageStatement block is PF (Parcel, First-Class)
    - PriceType in the CreatePostageStatement block is commercialplus

4.48.1 PostageStatementCancelRequest Data Structure

Field Description

Mail.XML 9.0C - PostageStatementCancelRequest				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
MailXMLPostageStatement RequestHeaderInfo Block			Attributes block	See Appendix E for Details
SubmittingParty Block	ParticipantIDType		Required block; Identifies the customer submitting the message	See Appendix E for Details
SubmittingSoftware Block	SubmittingSoftwa reType		Required block; Identifies the software submitting the message	See Appendix E for Details
StatementID	Non-negative Integer		*PostalOne!* assigned postage statement ID Optional	

2.3.86 - PostageStatementCancelRequest

4.49 PostageStatementCancelResponse

Purpose
Accept or reject a request to cancel postage statement (including a periodical statement)

Copyright © 2011 USPS®. All Rights Reserved.

Error/Return Codes

Refer Section 2.6 to view shared error/return codes and also a list of error/return codes tied this message.

Business Rules

- Will accept if postage statements exist in the mailing group and postage is not finalized
- Will reject if postage statements do not exist in the mailing group or the StatementID requested does not exist.
- Will reject if postage is finalized (PostageStatementStatus is FIN or FPP.)
- The ReturnInfo block will have a description for rejection

4.49.1 PostageStatementCancelResponse Data Structure

Field Description

Mail.XML 9.0C - PostageStatementCancelResponse				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
PostageStatementCancelAccept Block begins			Block received upon accepting request	
MailXMLMsgResponseHeaderInfo Block	MailXMLMsgResponseHeaderInfo		Attributes block	See Appendix E for Details
UserPostageStatementID	String, 10 characters		User created postage statement ID Optional	
StatementID	Non-negative Integer		*PostalOne!* assigned postage statement ID Required	
PostageStatementCancelAccept Block ends				
PostageStatementCancelReject Block begins				
MailXMLMsgResponseHeaderInfo Block	MailXMLMsgResponseHeaderInfo		Attributes block	See Appendix E for Details
ReturnInfo Block	basicReturnInfoType		Provides reason for return Required Multiple pairings of ReturnCode and ReturnDescription can be provided in the block	See Appendix
PostageStatementCancelReject Block ends				

2.3.87 - PostageStatementCancelResponse

Copyright © 2011 USPS®. All Rights Reserved.

4.50 PostageStatementCreateResponse

Purpose
The PostageStatementCreateResponse will be used by USPS to notify the customer if their request to submit a 3600-series postage statement to a mailing group has been accepted or rejected.

Error/Return Codes
Refer Section 2.6 to view shared error/return codes and also a list of error/return codes tied this message.

Business Rules
- Will accept if all required fields are provided and values are valid
- Will reject if a required field is not provided
- Will reject if a value provided is invalid
- Will reject if not all pieces are accounted for from submitted mailpieces or piece ranges
- Will reject if FormType is 'PE' for Periodicals
- Will reject if PostagePaymentMethod is 'S' or 'M' and PermitHolderForAPData Block is not provided
- The ReturnInfo block will have a description for rejection

4.50.1 PostageStatementCreateResponse Data Structure

Field Description

Mail.XML 9.0C - PostageStatementCreateResponse				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
PostageStatementCreateAccept Block begins			Either StatementID, UserPostageStatementID, TotalPostage, TotalPostageDue and ReturnInfo Block group or TrackingID and ReturnInfo Block group is submitted in the PostageStatement CreateAccept Block	
MailXMLPostageStatement ResponseHeaderInfo block	Attributes		Attributes block	See Appendix E for Details
StatementID	Non-negative Integer		Required field; paired with UserPostageStatementID, TotalPostage, TotalPostageDue, and ReturnInfo block	
UserPostageStatementID	String, 10 characters		Optional field; paired with	

Copyright © 2011 USPS®. All Rights Reserved.

Mail.XML 9.0C - PostageStatementCreateResponse				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
			StatementID, TotalPostage, TotalPostageDue, and ReturnInfo block	
TotalPostage	Double		Two decimals Required field; paired with StatementID, UserPostageStatementID, TotalPostageDue, and ReturnInfo block	
TotalPostageDue	Double		Required field; paired with StatementID, UserPostageStatementID, TotalPostage and ReturnInfo block	
ReturnInfo Block	basicReturnInfoType		Optional block; paired with StatementID, UserPostageStatementID, TotalPostage, and TotalPostageDue	See Appendix E for Details
PostageStatementCreateAccept Block ends				
PostageStatementCreateReject Block begins			Response from USPS indicating that the PostageStatementCreateRequest message was rejected and a Postage Statement was not created and the reason why	
CustomerGroupID	String, 25 characters		Required field; must be populated with the same value as the CustomerGroupID in the MailXMLPostageStatementRequestHeaderInfo block of the	

Copyright © 2011 USPS®. All Rights Reserved.

Mail.XML 9.0C - PostageStatementCreateResponse				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
			PostageStatement CreateRequest message	
MailXMLPostageStatement ResponseHeaderInfo block	MailXMLPostage StatementRespo nseHeaderInfo		Attributes block	See Appendix E for Details
ReturnInfo Block	basicReturnInfoT ype		Provides reason for return Required Multiple pairings of ReturnCode and ReturnDescription can be provided in the block	See Appendix E for Details
PostageStatementCreateR eject Block ends				

2.3.88 - PostageStatementCreateResponse

4.51 PostageStatementQueryResponse

Purpose
Accept or reject a request to create a combined mailing

Error/Return Codes
Refer Section 2.6 to view shared error/return codes and also a list of error/return codes tied this message.

Business Rules
- Will accept if PostageStatementID or TrackingID exists
- Will reject if PostageStatementID or TrackingID does not exist
- The ReturnInfo block will have a description for a Query Error

4.51.1 PostageStatementQueryResponse Data Structure

Field Description

Mail.XML 9.0C - PostageStatementQueryResponse				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
PostageStateQueryRespon se Message BEGINS				
MailXMLPostageStatement ResponseHeaderInfo Block	MailXMLPostage StatementRespo nseHeaderInfo		Attributes block	Refer this attribute in Appendix C

Copyright © 2011 USPS®. All Rights Reserved.

Mail.XML 9.0C - PostageStatementQueryResponse				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
Sequence Block BEGINS				
TrackingID	String,12	-	Optional.	-
Choice Block BEGINS				
QueryResults Block begins				
PostageStatementData Block	postageStatementDataType		Required. Only 1 occurrence	Refer 'postageStatementDataType' complex in Appendix C
ReturnInfo Block	basicReturnInfoType		Optional	See Appendix C for Details
QueryResults Block ends				
QueryError Block begins				
ReturnInfo Block	basicReturnInfoType		Provides reason for return Required Multiple pairings of ReturnCode and ReturnDescription can be provided in the block	See Appendix C for Details
QueryError Block ends				
Choice Block ENDS				
Sequence Block ENDS				
PostageStatementQueryResponse Message ENDS				

2.4.06 – PostageStatementQueryResponse

4.52 PostageStatementQueryResponse

Purpose
Accept or reject a request to create a combined mailing

Error/Return Codes
Refer Section 2.6 to view shared error/return codes and also a list of error/return codes tied this message.

Business Rules
- Will accept if PostageStatementID or TrackingID exists
- Will reject if PostageStatementID or TrackingID does not exist

Copyright © 2011 USPS®. All Rights Reserved.

- The ReturnInfo block will have a description for a Query Error

4.52.1 PostageStatementQueryResponse Data Structure

Field Description

Mail.XML 9.0C - PostageStatementQueryResponse				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
MailXMLPostageStatement ResponseHeaderInfo Block begins	MailXMLPostage StatementRespo nseHeaderInfo		Attributes block	
QueryResults Block begins				
PostageStatementData Block begins	postageStatemen tDataType			
AgencyCostCode	agencyCostCode Type	Number 5 or 6 digits	Optional field, required for OI or OM government permit types	
AutomationAddressMatchD ate	Date	YYYY-MM-DD	Optional field; required for automation rate pieces The mailer must specify the date when the address list was generated.	
CustomerReferenceID	String, 40 characters		Optional	CustomerRe ferenceID represents CAPS Account Number
UserPostageStatementID	String, 10 characters		Optional	
CarrierRouteAddressMatch Date	Date	YYYY-MM-DD	Optional field; required for Carrier Route rate pieces	
CarrierRouteSequencingDa te	Date	YYYY-MM-DD	Optional field; required for Carrier Route rate pieces	
CertificationData Block begins	certificationData Type		Required	See Appendix B for Details
ContainerCount Block begins	containerCountT ype		Required block; at least one of the fields in this block must be populated with a nonzero value	
Trays2mm	Non-negative		Optional field;	

Copyright © 2011 USPS®. All Rights Reserved.

Mail.XML 9.0C - PostageStatementQueryResponse				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
	Integer		Required if no other fields are populated with a nonzero value	
EnclosedBy	mailxml_base:enclosedByType	Refer 'enclosedByType' simple type	Optional Generated field	Refer Appendix B
DalPieces	Non-negative Integer		Optional Generated if Detached Address Labels	
ExtendedForm	Boolean	True, False	Required Generated according to PostageStatement CreateRequest data input	
FormType	Mailxml_base:formType	Refer 'formType' simple type	Required Generated according to PostageStatement CreateRequest data input	Refer Appendix B
LineItemSummaryData Block begins			Optional 1 to many can be generated for Extended form = False according to PostageStatement CreateRequest data input	
ProcessingCategory	Mailxml_base:processingCategory Type	Refer 'processingCategoryType' simple type	Required field Generated according to PostageStatement CreateRequest data input If FormType = BP, then the following values are valid: FL, NP, MP, IR If FormType = FC, then the following values are valid: LT, FL, CD, PF If FormType = ML, then the following values are valid: FL, NP, MP, IR If FormType = PM,	Refer Appendix B

Copyright © 2011 USPS®. All Rights Reserved.

Mail.XML 9.0C - PostageStatementQueryResponse				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
			then the following values are valid: LT, FL, PF If FormType = PP, then the following values are valid: MP, IR, NP If FormType = SM, then the following values are valid: LT, FL, MP, IR, NP, CM, NA, NB	
BarcodeRate	Mailxml_base:barcodeRateType	Refer 'barcodeRateType' simple type	Required Generated according to PostageStatement CreateRequest data input	
EntryDiscount	Mailxml_base:entryDiscountType	Refer 'entryDiscountType' simple type	Required Generated according to PostageStatement CreateRequest data input	Refer Appendix B
LineLabel	String, 80 characters		Optional	
LineNumber	String, 3 characters		Optional This field will be ignored if populated; LineNumber will only be taken into account for Full-Service discount lines	
PiecePostage	Double		Optional, up to four decimals	
PieceRate	Double		Optional, up to three decimals	
PostageAmount	Double		Required, up to four decimals	
PoundPostage	Double		Optional, up to four decimals	
PoundRate	Double		Optional, up to three decimals	
PreparedAsSM	Boolean	True, False	Required Generated according to PostageStatement	

Copyright © 2011 USPS®. All Rights Reserved.

Mail.XML 9.0C - PostageStatementQueryResponse				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
			CreateRequest data input The “True” indicates that mail is actually prepared as Standard when the RateCategory=S The “False” indicates that mail is actually prepared as First Class when the RateCategory=S	
RateCategory	Mailxml_base:rateCategoryType	Refer ‘rateCategoryType’ simple type	Required field If FormType = BP, then this field must be D, N, or S If FormType = FC, then this field must be E, H, L1, L2, L3, L4, N, or S If FormType = ML, then this field must be G, N, S If FormType = PM, then this field must be S If FormType = PP, then this field must be G, K, S, Z1, or Z2 If FormType = SM, then this field must be A, B, E, H, N, AF, BF, DF, L1, L2, L5, L6, L7, L8, NG, NK, N5, N6, PI, PM, P7, P8, PE, PQ, PR, PG, PK, P5, or P6	Refer Appendix B
Section	String, 1 character		Optional This field will be ignored if populated; Section	

Copyright © 2011 USPS®. All Rights Reserved.

Mail.XML 9.0C - PostageStatementQueryResponse				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
			will only be taken into account for Full-Service discount lines	
SurchargeType	Mailxml_base:surchargeType	Refer 'surchargeType' simple type	Required If FormType = BP, this field must be N If FormType = FC, this field must be A, E, N, or R If FormType = ML, this field must be N If FormType = PM, this field must be D, E, N, or P If FormType = PP, this field must be 2 or N If FormType = SM, this field must be L or N Generated according to PostageStatement CreateRequest data input	Refer Appendix B
TotalPieces	Non-negative Integer		Required Generated according to PostageStatement CreateRequest data input	
TotalWeight	Double		Optional The value of TotalWeight must be in Pounds.	
WeightBreakType	Mailxml_base:weightBreakType	Refer 'weightBreakTYpe' simple type	Optional field If FormType is BP this field must be N. If FormType is FC this field must be A, B or N. If FormType is ML this field must be N. If FormType is PM this field must be N. If FormType is PP	Refer Appendix B

Copyright © 2011 USPS®. All Rights Reserved.

Mail.XML 9.0C - PostageStatementQueryResponse				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
			this field must be N. If FormType is SM this field must be A, B or H. Generated according to PostageStatement CreateRequest data input	
Zone	Mailxml_base:zoneICType	Refer 'zoneICType' simple type	Optional Generated according to PostageStatement CreateRequest data input	Refer Appendix B
FlatRateIndicator	Mailxml_base:flatRateIndicatorType	Refer 'flatRateIndicatorType' simple type	Optional Generated according to PostageStatement CreateRequest data input	Refer Appendix B
FullServiceParticipationIndicator	Mailxml_base:fspiType	Refer 'fspiType' simple type	Optional field, Generated according to PostageStatement CreateRequest data input	Refer Appendix B
SinglePieceDimensionalWeight	Double		Optional, required for balloon or oversize prices up to four decimals. The value of SinglePieceDimensionWeight must be in Pounds.	
LineItemSummaryData Block ends				
PostageStatementLineItem Data Block begins			Optional 1 to many can be generated for Extended form =True according to PostageStatement CreateRequest data input	
ProcessingCategory	Mailxml_base:processingCategoryType	Refer 'processingCategoryType' simple type	Optional Generated according to PostageStatement	Refer Appendix B

Copyright © 2011 USPS®. All Rights Reserved.

Mail.XML 9.0C - PostageStatementQueryResponse				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
			CreateRequest data input	
BarcodeRate	Mailxml_base:barcodeRateType	Refer 'barcodeRateType' simple type	Required Generated according to PostageStatement CreateRequest data input	Refer Appendix B
ContainerDisplayName	String, 50 characters		Optional	
ContainerID	String, 6 characters		Optional	
EntryDiscount	Mailxml_base:entryDiscountType	Refer 'entryDiscountType' simple type	Required	Refer Appendix B
EntryFacilityType	Mailxml_base:entryFacilityType	Refer 'entryFacilityType' simple type	Optional	Refer Appendix B
EntryZip	Mailxml_base:zipCodeThreeOrFiveDigit	Refer 'zipCodeThreeDigitOrFiveDigit' simple type	Optional	Refer Appendix B
Heavy Letter	Boolean	True, False	Required	
LineLabel	String, 80 characters		Optional	
LineNumber	String, 3 characters		Optional This field will be ignored if populated; LineNumber will only be taken into account for Full-Service discount lines	
PieceRate	Double		Optional, up to three decimals	
PostageAmount	Decimal		Optional up to four decimals	
PoundRate	Decimal		Optional up to three decimals	
PreparedAsSM	Boolean	True, False	Required The "True" indicates that mail is actually prepared as Standard when the	

Copyright © 2011 USPS®. All Rights Reserved.

Mail.XML 9.0C - PostageStatementQueryResponse				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
			RateCategory=S The “False” indicates that mail is actually prepared as First Class when the RateCategory=S	
RateCategory	Mailxml_base:rateCategoryType	Refer ‘rateCategoryType’ simple type	Required field If FormType = BP, then this field must be D, N, or S If FormType = FC, then this field must be E, H, L1, L2, L3, L4, N, or S If FormType = ML, then this field must be G, N, S If FormType = PM, then this field must be S If FormType = PP, then this field must be G, K, S, Z1, or Z2 If FormType = SM, then this field must be A, B, E, H, N, AF, BF, DF, L1, L2, L5, L6, L7, L8, NG, NK, N5, N6, PI, PM, P7, P8, PE, PQ, PR, PG, PK, P5, or P6	Refer Appendix B
Section	String, 1 character		Optional This field will be ignored if populated; Section will only be taken into account for Full-Service discount lines	
SinglePieceWeight	Double		Required up to four decimals	

Copyright © 2011 USPS®. All Rights Reserved.

Mail.XML 9.0C - PostageStatementQueryResponse				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
			The value of SinglePieceWeight must be in Pounds.	
SurchargeType	Mailxml_base:surchargeType	Refer 'surchargeType' simple type	Required If FormType = BP, this field must be N If FormType = FC, this field must be A, E, N, or R If FormType = ML, this field must be N If FormType = PM, this field must be D, E, N, or P If FormType = PP, this field must be 2 or N If FormType = SM, this field must be L or N	Refer Appendix B
TotalPieces	Non-negative Integer		Required	
TotalWeight	Double		Optional The value of TotalWeight must be in Pounds.	
Zone	Mailxml_base:zoneICType	Refer 'zoneICType' simple type	Optional	Refer Appendix B
VersionID	String, 10 characters		Optional	
ContainerType	Mailxml_base:mailXMLContainerType	Refer 'mailXMLContainerType' simple type	Optional field	Refer Appendix B
FlatRateIndicator	Mailxml_base:flatRateIndicatorType	Refer 'flatRateIndicatorType' simple type	Optional	Refer Appendix B
FullServiceParticipationIndicator	Mailxml_base:fspiType	Refer 'fspiType' simple type	Optional Generated according to postage statement input.	Refer Appendix B
SinglePieceDimensionalWeight	Double		Optional, required for balloon or oversize prices up to four decimals.	

Copyright © 2011 USPS®. All Rights Reserved.

Mail.XML 9.0C - PostageStatementQueryResponse				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
			The value of SinglePieceDimensionWeight must be in Pounds.	
PostageStatementLineItem Data Block ends				
PostageStatementMailingDate	Date	YYYY-MM-DD	Required It may be up to one year in future or back dated to most recent price change	
PackagingMethod	packagingMethodType	0 = Piece Count 1 = Weight 2 = Both	Optional	
PostageAffixedAmount	Double		Optional up to three decimals	
PostagePaymentMethod	Mailxml_base:postagePaymentMethodType	Refer 'packagingPaymentMethodType' simple type	Required	Refer Appendix B
ProcessingCategory	Mailxml_base:processingCategoryType	Refer 'processingCategoryType' simple type	Required	Refer Appendix B
RateType	Mailxml_base:rateType	Refer 'rateType' simple type	Required	Refer Appendix B
RegisterOfMailing	Boolean	True, False	Required	
SackingBasis	Mailxml_base:sackingBasisType	Refer 'sackingBasisType' simple type	Optional	Refer Appendix B
SinglePieceWeight	Double		Required up to four decimal places The value of SinglePieceWeight must be in Pounds.	
ExtraServiceData Block begins			Optional 0 to many can be generated according to postage statement input	
ServiceCode	Mailxml_base:serviceCodeType	Refer 'serviceCodeType' simple type	Required	Refer Appendix B
ServiceRate	Double		Optional up to three decimals	

Copyright © 2011 USPS®. All Rights Reserved.

Mail.XML 9.0C - PostageStatementQueryResponse				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
ServiceSubCode	Mailxml_base:serviceSubCodeType	Refer 'serviceSubCodeType' simple type	Required	Refer Appendix B
ServiceValue	Double		Required up to three decimals	
TotalAmount	Double		Optional up to three decimals	
TotalPieces	Non-negative Integer		Required	
ExtraServiceData Block ends				
ExtraServiceSummaryData Block begins			Optional 0 to many can be submitted	
LineLabel	String, 80 characters		Optional	
LineNumber	String, 3 characters		Optional This field will be ignored if populated; LineNumber will only be taken into account for Full-Service discount lines	
Section	String, 1 character		Optional This field will be ignored if populated; Section will only be taken into account for Full-Service discount lines	
ServiceCode	Mailxml_base:serviceCodeType	Refer 'serviceCodeType' simple type	Required	Refer Appendix B
TotalAmount	Double		Required up to three decimal places	
TotalPieces	Non-negative Integer		Required	
ExtraServiceSummaryData ends				
StatementSequenceNumber	String, 20 characters		Optional	

Copyright © 2011 USPS®. All Rights Reserved.

Mail.XML 9.0C - PostageStatementQueryResponse				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
RepositionableNotesIndicator	Boolean		Required	
DocumentVersionDataBlock	DocumentVersionData		Optional 0 to many can be submitted	See Appendix E
MeteredAffixedMethod	Mailxm_base:meteredAffixedMethodType	–Refer 'meteredAffixedMethodType' simple type	Optional	Refer Appendix B
CombinedMailingID	Non-negative Integer		Optional field; required for combined mailings	
SinglePieceDimensionalWeight	Double		Optional up to four decimal places. The value of SinglePieceDimensionWeight must be in Pounds.	
EnclosingVolumeNo	String, 5 characters		Optional	
EnclosingIssueNo	String, 6 characters		Optional	
EnclosingIssueDate	Date	YYYY-MM-DD	Optional	
PriceType	priceType	commercial,commercialplus	Optional	
MoveUpdateMethod	Mailxml_base:moveUpdateMethodType	Refer 'moveUpdateMethodType' simple type	Optional	Refer Appendix B
StatementID	Non-negative integer		Optional	
MailClass	mailClassType		Required	
Origin	String		Optional	
SpecialFeesAmount	Double		Required	
PostageStatementStatus	postageStatementStatusType	See Appendix B for Details for values	Optional	See Appendix B for Details for values
TotalPieces	Non-negative integer		Required	
TotalPostageAmount	Double		Required up to two decimal places	
TotalPostageAmountDue	Double		Required up to two decimal places, may be 0.00.	
TotalWeight	Double		Required The value of	

Copyright © 2011 USPS®. All Rights Reserved.

Mail.XML 9.0C - PostageStatementQueryResponse				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
			TotalWeight must be in Pounds.	
PermitHolderData Block	mailerDataType		Required	See Appendix E for Details
MailingOwnerData Block	mailerDataType		Optional	See Appendix E for Details
MailingAgentData Block	mailerDataType		Required	See Appendix
PermitHolderForAPData Block begins	mailerDataType		Optional	See Appendix
ReturnInfo Block	basicReturnInfoType			See Appendix E for Details
QueryResults Block ends				
QueryError Block begins				
ReturnInfo Block	basicReturnInfoType		Provides reason for return Required Multiple pairings of ReturnCode and ReturnDescription can be provided in the block	See Appendix E for Details
QueryError Block ends				

2.3.89 - PostageStatementQueryResponse

4.53 PostageStatementStatusQueryRequest

Purpose
Used to query the status of a postage statement

Business Rules

- Must be submitted after a postage statement has been created
- Beginning in Release 26.1, First-Class Commerical Plus Parcels will be accepted after the April 2011 price change date when the following conditions are met:
    - FormType in the CreatePostageStatement block is FC (First-Class)
    - PresentationCategory in the CreatePostageStatement block is PF (Parcel, First-Class)
    - PriceType in the CreatePostageStatement block is commercialplus

4.53.1 PostageStatementStatusQueryRequest Data Structure

Field Description

Mail.XML 9.0C - PostageStatementStatusQueryRequest

Copyright © 2011 USPS®. All Rights Reserved.

Field	Format	Acceptable Values	Business Rules	Comments
MailXMLDashboardHeaderInfo Block	Complex		Attributes block	
SubmittingParty			Required block; Identifies the customer submitting the message	
SubmittingSoftware			Required block; Identifies the software submitting the message	
StatementID	Non-negative Integer		Required if the TrackingID is not provided	
IncludeChildStatement	yesNo	Yes, No	Optional, only used for Periodicals Consolidated postage statements. If yes, the child statements will be returned in the response, else child statements will not be returned.	

2.3.90 - PostageStatementStatusQueryRequest

4.54 PostageStatementStatusQueryResponse

Purpose
Accept or reject a query for postage statement status

Error/Return Codes
Refer Section 2.6 to view shared error/return codes and also a list of error/return codes tied this message.

Business Rules
- Will accept if postage statement exists in the mailing group
- Will reject if postage statement does not exist in the mailing group
- The ReturnInfo block will have a description for a QueryError

4.54.1 PostageStatementStatusQueryResponse Data Structure

Field Description

Mail.XML 9.0C - PostageStatementStatusQueryResponse				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
MailXMLDashboardHeaderInfo Block	Attributes		Attributes block	See Appendix E

Copyright © 2011 USPS®. All Rights Reserved.

Mail.XML 9.0C - PostageStatementStatusQueryResponse				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
				for Details
QueryResults Block begins				
MailingGroup Block begins			Optional 0 to many can be submitted	
MailingGroup Block begins			Optional, only one may be submitted	
CustomerDescription	String, 50 characters		Optional	
SubmitterCRID	CRIDType		Required	
PermitPublicationData Block begins	permitPublication DataType		Required	See Appendix E for Details
PostOfficeOfMailingZip	String, 5 characters		Required	
MailingFacility	CRIDType		Optional	
MailXMLPresentationCategory	Mailxml_base:mailXMLPresentationCategoryType	Refer 'mailXMLPresentationCategoryType' simple type	Required	Refer Appendix B
MailerID	String, 9 characters		Optional	
FullServiceParticipationIndicator	Mailxml_base:fspiType	Refer 'fspiType' simple type	Optional	Refer Appendix B
MailAgreementType	Mailxml_base:mailAgreementTypeType	Refer 'mailAgreementTypeType' simple type	Optional	Refer Appendix B
ContractNumber	String, 20 characters		Optional	
OnePassIndicator	String, 3 characters	Yes, No	Optional	
LogicalPhysicalContainerIndicator	Mailxml_base:logicalPhysicalContainerIndicatorType	Refer 'logicalPhysicalContainerIndicatorType' simple type	Optional	Refer Appendix B
MailingGroup Block ends				
~~UserPostageStatementID~~	~~String, 10 characters~~	-	~~Optional~~	
PostageStatementSummary Block begins			Required 1 to many can be submitted	
StatementID	Non-negative Integer		Optional	
UserPostageStatementID	String, 10 characters		Optional	
UserPostageStatementSequenceID	Numeric String 10		Optional	

Copyright © 2011 USPS®. All Rights Reserved.

Mail.XML 9.0C - PostageStatementStatusQueryResponse				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
USPSPostageStatementSequenceNumber	Numeric String, 10 characters		Optional	
PostageStatementStatus	String, 15 characters	See Appendix B for Details for values	Required	
PostageStatementSummary Block ends				
ReturnInfo Block	basicReturnInfoType		Provides reason for return Optional Multiple pairings of ReturnCode and ReturnDescription can be provided in the block	See Appendix E for Details
QueryResults Block ends				
QueryError Block begins				
ReturnInfo Block	ReturnInfo		Provides reason for return Required Multiple pairings of ReturnCode and ReturnDescription can be provided in the block	See Appendix E for Details
QueryError Block ends				

2.3.91 - PostageStatementStatusQueryResponse

4.55 QualificationReportCreateRequest

Purpose
The Qualification Report is used to submit standardized documentation compliant with the DMM 708.1. A mailing group may have multiple qualification reports.

Business Rules

- Cannot be sent until an OpenMailingGroupRequest message has been sent and accepted
- No updates can be made to the QualificationReportCreateRequest message. Beginning with Release 24, transportation updates can be submitted via the Mail.XML ContainerUpdateRequest message for certain business scenarios that require container update, such as logical mailings.
- Changes to a Qualification Report can be made when the customer closes a mailing group through the CloseMailingGroupRequest message and opens a new mailing group with the OpenMailingGroupRequest message
- QualificationReportCreateRequest message must be accepted before the BundleDetailCreateRequest message can be sent.
- Qualification report data cannot be used to send transportation data to the FAST system
- Beginning in Release 26.0.0, FormType PM for Priority Mail is not supported after the January 2, 2011 price change date.

Copyright © 2011 USPS®. All Rights Reserved.

- Beginning in Release 26.0.0, FormType PP for Package Services Parcel Post is not supported after the January 2, 2011 price change date.
- Beginning in Release 26.0.0, Standard Mail Parcels are not supported for 7.0 and 8.0 version files that are submitted after the January 2, 2011 price change date.
- Beginning in Release 26.0.0, Rate Categories AF, BF, DF, GF, and KF are not supported for First-Class Mail, Standard Mail, or Periodicals submitted after the January 2, 2011 price changed.
- Beginning in Release 26.0.0, the ProcessingCategory cannot be populated with NA or NB for Standard Mail submitted after the January 2, 1011 price change date.
- Beginning in Release 26.0.0, the ProcessingCategory field cannot be populated with IR for Bound Printed Matter Package Service mailings submitted after the January 2, 2011 price change date
- Beginning in Release 26.1, First-Class Commercial Plus Parcels will be accepted when the following conditions are met:
    - FormType in the CreatePostageStatement block is FC (First-Class)
    - PresentationCategory in the CreatePostageStatement block is PF (Parcel, First-Class)
    - PriceType in CreatePostageStatement block is commercialplus
- Beginning in Release 28.0.0, the *PostalOne!* system will ignore the QualificationReportCreateRequest message if it is submitted after the PeriodicalStatementCreateRequest or ConsolidatedPeriodicalStatementCreateRequest and the AdPercent field in the DocumentVersionDataWithPermit block does not match the AdPercent of the previously submitted PeriodicalStatementCreateRequest or ConsolidatedPeriodicalStatementCreateRequest.
- Beginning in Release 28.0.0, the *PostalOne!* system will ignore the QualificationReportCreateRequest message if it is submitted after the PeriodicalStatementCreateRequest or ConsolidatedPeriodicalStatementCreateRequest and the PieceWeight field in the DocumentVersionDataWithPermit block does not match the PieceWeight of the previously submitted PeriodicalStatementCreateRequest or ConsolidatedPeriodicalStatementCreateRequest.
- Beginning in Release 28.0.0, the CSADispatchNumber field in the ContainerInfoData block will be ignored.

4.55.1 QualificationReportCreateRequest Data Structure

Field Description

Mail.XML 9.0C - QualificationReportCreateRequest				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
QualificationReportCreateRequest BEGINS				
MailXMLQualReportRequestHeaderInfo	MailXMLQualReportRequestHeaderInfo attribute		Attributes block; 0 to 1	Refer this attribute in Appendix D
SubmittingParty	ParticipantIDType		Required block; Identifies the customer submitting the message	Refer this complex type in Appendix D
SubmittingSoftware	SubmittingSoftwareType		Required block; Identifies the software submitting the message	Refer this complex type in Appendix D

Copyright © 2011 USPS®. All Rights Reserved.

Mail.XML 9.0C - QualificationReportCreateRequest				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
OnePassPlannedOrActualFlag	onePassPlannedOrActualFlagType	A = Actual P = Planned	Optional field. Must submit a Qualification Report with this field set to P before submitting one with this field set to A.	Refer Appendix B for the complete list of accepted values
QualificationReport	qualificationReportDataType complex type		Required block; contains the values necessary to populate a Qualification Report	Refer this complex type in Appendix D
QualificationReportCreate Request ENDS				

2.3.02 – QualificationReportCreateRequest

4.56 QualificationReportCreateResponse

Purpose
The QualificationReportCreateResponse will be used by USPS to notify the customer if their request to create a qualification report has been accepted or rejected.

Error/Return Codes
Refer Section 2.6 to view shared error/return codes and also a list of error/return codes tied this message.

Business Rules
- Must be returned to the customer after the QualificationReportCreateRequest message is sent by the customer to *PostalOne!*
- OpenMailingGroupResponse must respond with an accept block
- PermitNumber must map back to FinanceNumber
- TotalCopies can be greater that the TotalPieces in the same messages for periodical using Firm Bundles
- Version ID must exist in DocumentVersionDataWithPermit

4.56.1 QualificationReportCreateResponse Data Structure

Field Description

Mail.XML 9.0C - QualificationReportCreateResponse				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**

Copyright © 2011 USPS®. All Rights Reserved.

Mail.XML 9.0C - QualificationReportCreateResponse				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
QualificationReportCreateAccept block begins			Response from USPS indicating that the QualificationReportCreateRequest message was accepted and a Qualification Report was created	
MailXMLQualReportResponseHeaderInfo block begins			Attributes block	
CustomerGroupID	String, 25 characters		Required field; must be populated with the same value as the CustomerGroupID in the MailXMLQualReportRequestHeaderInfo block of the QualificationReportCreateRequest message	
MailingGroupID	Non-negative integer		Required field; must be populated with the same value as the MailingGroupID in the MailXMLQualReportRequestHeaderInfo block of the QualificationReportCreateRequest message	
MailXMLQualReportResponseHeaderInfo block ends			End of block	
CustomerQualificationReportID	String, 66 characters		Optional field	
ReturnInfo block	ReturnInfo		Optional block	See Appendix E for Details
QualificationReportCreateAccept block ends			End of block	
QualificationReportCreateReject block begins			Response from USPS indicating that the QualificationReportCreateRequest message was	

Copyright © 2011 USPS®. All Rights Reserved.

Mail.XML 9.0C - QualificationReportCreateResponse				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
			rejected and a Qualification Report was not created and the reason why	
MailXMLQualReportResponseHeaderInfo block begins			Attributes block	
CustomerGroupID	String, 25 characters		Required field; must be populated with the same value as the CustomerGroupID in the MailXMLQualReportRequestHeaderInfo block of the QualificationReportCreateRequest message	
MailingGroupID	Non-negative integer		Required field; must be populated with the same value as the MailingGroupID in the MailXMLQualReportRequestHeaderInfo block of the QualificationReportCreateRequest message	
MailXMLQualReportResponseHeaderInfo block ends			End of block	
ReturnInfo block	ReturnInfo		Required block	See Appendix E for Details
QualificationReportCreateReject block ends			End of block	

2.3.92 - QualificationReportCreateResponse

4.57 QualificationReportQueryRequest

Purpose
This message should be sent when customer would like to request the qualification Report.

Business Rules
- Cannot be sent until the QualificationReportCreateRequest has been successful.

Copyright © 2011 USPS®. All Rights Reserved.

4.57.1 QualificationReportQueryRequest Data Structure

Field Description

Mail.XML 9.0C - QualificationReportQueryRequest				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
QualificationReportQueryRequest Message BEGINS				
MailXMLMessageHeaderInfo block begins			Attributes block	
CustomerGroupID	String, 25 characters		Required field	
MailingGroupID	Non-Negative Integer		Required field	
MailXMLMessageHeaderInfo block ends				
Sequence Block BEGINS				
SubmittingParty	participantIDType	-	Required	Refer Appendix C
SubmittingSoftware	submittingSoftwareType	-	Required	Refer Appendix C
MailingFacility	Mailxml_base:CRIDType	Simple type	Required	Refer “CRIDType” simple type in Appendix B
PostageStatementStatus	Mailxml_base:postageStatementStatusType	Simple Type	Optional	Refer this simple type in Appendix C
QualificationReportClass	Mailxml_base:qualificationReportClassType	Simple Type	Optional	Refer this simple type in Appendix C
CustomerQualificationReportID	String, 66	-	Optional	
BeginDate	Date/Time	-	Optional	-
EndDate	Date/Time	-	Optional	-
Preparer Block	permitPublicationDataType	Complex Type	Optional	Refer this complex type in Appendix C
PermitHolder Block	permitPublicationDataType	Complex Type	Optional	Refer this complex type in Appendix

Copyright © 2011 USPS®. All Rights Reserved.

Mail.XML 9.0C - QualificationReportQueryRequest				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
				C
IssueBeginDate	Date/Time	-	Optional	-
IssueEndDate	Date/Time	-	Optional	-
IssueNumber	String, 6	-	Optional	-
VolumeNumber	String, 5	-	Optional	-
DestinationFacilityZip	String, 9	Up to nine digit zip code of the destination facility	Required	
Sequence Block ENDS				
QualificationReportQueryRequest Message ENDS				

2.4.02 – QualificationReportQueryRequest

4.58 QualificationReportQueryResponse

Purpose
This is a response message returned from USPS to the requester who sends the QualificationReportQueryRequest message.

Business Rules
- Cannot be sent until QualificationReportQueryRequest message is received
- USPS collects the data based on the QueryRequest and return all data in this message.

4.58.1 QualificationReportQueryResponse Data Structure

Field Description

Mail.XML 9.0C - QualificationReportQueryResponse				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
QualificationReportQueryResponse Message BEGINS				
MailXMLMessageHeaderInfo block begins			Attributes block	
CustomerGroupID	String, 25 characters		Required field	
MailingGroupID	Non-Negative Integer		Required field	
MailXMLMessageHeaderInf				

Copyright © 2011 USPS®. All Rights Reserved.

Mail.XML 9.0C - QualificationReportQueryResponse				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
o block ends				
Sequence Block BEGINS				
TrackingID	String, 12	-	Optional. Returns the tracking ID when an error is occurred or when message is too large and request cannot be completed	
Choice Block BEGINS				
QueryResult Block BEGINS	-	-	Required Block	
Sequence Block BEGINS				
QualificationReport block	qualificationReportDataType	Complex Type	Required block; contains the values necessary to populate a Qualification Report	Refer “qualificationReportData Type” complex in Appendix C
ReturnInfo	basicReturnInfoType	-	Optional Block Allow 0 to many occurrence	Refer “ReturnInfo” or “basicReturnInfoData” block in Appendix C
Sequence Block ENDS				
QueryResults block ENDS				
QueryError Block BEGINS			Required Block	
ReturnInfo	basicReturnInfoType		Required block when error occurs	Refer “ReturnInfo” or “basicReturnInfoData” block in Appendix C
Choice Block ENDS				
Sequence Block ENDS				
QualificationReportQueryResponse				

Copyright © 2011 USPS®. All Rights Reserved.

Mail.XML 9.0C - QualificationReportQueryResponse				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
Message ENDS				

2.4.03 – QualificationReportQueryResponse

4.59 ReconciliationReportQueryRequest

The customer cannot update the Qualification report once filed. After the customer goes through the process of printing and delivering the mail to the USPS, the Reconciliation report is created that shows how much mail was planned and how much was mailed. In the ReconciliationReportQueryRequest, the customer is required to provide the mailing group ID and Customer group ID besides the mandatory elements of Submitting party and Submitting software.

4.59.1 ReconciliationReportQueryRequest Data Structure

Field Description

Mail.XML 9.0C - ReconciliationReportQueryRequest				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
MailXMLDashboardtHeader Info block Opens				
CustomerGroupID	String, 25 characters		Required (attribute)	
MailingGroupID	Non Negative Integer		Required (attribute)	
MailXMLDashboardtHeader Info block Closes				
SubmittingParty	ParticipantIDType		Identifies the customer submitting the message	Refer 'ParticipantID Type' complex type in Appendix D.
SubmittingSoftware	SubmittingSoftwareType		Identifies the software submitting the message	Refer 'SubmittingSoftware' complex type in Appendix D.
QualificationReportClass	mailxml_base:qualificationReportClassType	Refer 'qualificationReportClassType' simple type	Optional	Refer Appendix B
BeginDate	DateTime	YYYY-MM-DDTHH:MM:SS	Optional	
EndDate	DateTime	YYYY-MM-	Optional	

Copyright © 2011 USPS®. All Rights Reserved.

Mail.XML 9.0C - ReconciliationReportQueryRequest				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
		DDTHH:MM:SS		
Preparer Block Opens				
PermitNumber	String, 8 characters		Optional	
PermitType	mailxml_base:permitTypeType	Refer 'permitTypeType' simple type	Optional	Refer Appendix B
PermitZip4	Number, 9 digits		Optional	
PublicationNumber	Number, 9 digits		Optional	
Preparer Block Closes				
PermitHolder Block Opens				
PermitNumber	String, 8 characters		Optional	
PermitType	mailxml_base:permitTypeType	Refer 'permitTypeTYpe' simple type	Optional	Refer Appendix B
PermitZip4	Number, 9 digits		Optional	
PublicationNumber	Number, 9 digits		Optional	
PermitHolder Block Closes				
IssueBeginDate	DateTime	YYYY-MM-DDTHH:MM:SS	Optional	
IssueEndDate	DateTime	YYYY-MM-DDTHH:MM:SS	Optional	
IssueNumber	String, 6		Optional	
VolumeNumber	String, 5		Optional	

2.3.93 - ReconciliationReportQueryRequest

4.60 ReconciliationReportQueryResponse

In the ReconciliationReportQueryResponse message the *PostalOne!* system responds back with a reconciliation report for every qualification report within the Job/mailing group. The USPS responds back with one Mailing Group Summary and one or more Reconciliation Summary reports. The message also includes an optional Return Code and description. If there are issues, the USPS responds back with the Query Error block and provides one or more Return codes and descriptions to explain the errors.

4.60.1 ReconciliationReportQueryResponse Data Structure

Field Description

Mail.XML 9.0C - ReconciliationReportQueryResponse				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
MailXMLDashboardtHeader Info block Opens				

Copyright © 2011 USPS®. All Rights Reserved.

Mail.XML 9.0C - ReconciliationReportQueryResponse				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
CustomerGroupID	String, 25 characters		Required (attribute)	
MailingGroupID	Non Negative Integer		Required (attribute)	
MailXMLDashboardtHeader Info block Closes				
QueryResults Block Opens				
MailingGroupSummary block Opens				
MailerJobID	String, 12 characters		Optional	
BeginDate	DateTime	YYYY-MM-DDTHH:MM:SS	Optional	
EndDate	DateTime	YYYY-MM-DDTHH:MM:SS	Optional	
OpenDate	DateTime	YYYY-MM-DDTHH:MM:SS	Optional	
CloseDate	DateTime	YYYY-MM-DDTHH:MM:SS	Optional	
PreparerName	String		Optional	
PreparerCRID	String, 15 characters		Optional	
Origin	String		Optional	
Description	String		Optional	
MailingGroupSummary block Closes				
QualificationSummaryReport block Opens				
RateCategory	mailxml_base:rateCategoryType	Refer 'rateCategoryType' simple type	Optional	Refer Appendix B
Pieces	Non Negative Integer		Optional	
ClosedPieces	Non Negative Integer		Optional	
FormType	mailxml_base:formType	Refer 'formTYpe' simple type	Optional	Refer Appendix B
TotalPieces	Non Negative Integer		Optional	
TotalClosedPieces	Non Negative Integer		Optional	

Copyright © 2011 USPS®. All Rights Reserved.

Mail.XML 9.0C - ReconciliationReportQueryResponse				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
PostageStatements block Opens				
Line	String, 2 characters		Optional	
USPSProcessingDue block Opens				
Pieces	Non Negative Integer		Optional	
Postage	Decimal		Optional	
TotalPieces	Non Negative Integer		Optional	
TotalPostage	Decimal		Optional	
USPSProcessingDue block Closes				
Finalize block Opens				
Pieces	Non Negative Integer		Optional	
Postage	Decimal		Optional	
TotalPieces	Non Negative Integer		Optional	
TotalPostage	Decimal		Optional	
Finalize block Closes				
PostageStatements block Closes				
QualificationSummaryReport block Closes				
ReconciliationReport block Opens				
OriginalPieces	Non Negative Integer		Optional	
ActualPieces	Non Negative Integer		Optional	
Postage	Decimal		Optional	
ClosedContainer block Opens				
OriginalPieces	Non Negative Integer		Optional	
ActualPieces	Non Negative Integer		Optional	
Postage	Decimal		Optional	
ClosedContainer block Closes				
PostageStatementCanceled block Opens				
OriginalPieces	Non Negative Integer		Optional	
ActualPieces	Non Negative		Optional	

Copyright © 2011 USPS®. All Rights Reserved.

Mail.XML 9.0C - ReconciliationReportQueryResponse				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
	Integer			
Postage	Decimal		Optional	
PostageStatementCanceled Closes				
PostageStatementUSPSPr ocessingDue block Opens				
OriginalPieces	Non Negative Integer		Optional	
ActualPieces	Non Negative Integer		Optional	
Postage	Decimal		Optional	
PostageStatementUSPSPr ocessingDue block Closes				
PostageStatementReworke d block Opens				
OriginalPieces	Non Negative Integer		Optional	
ActualPieces	Non Negative Integer		Optional	
Postage	Decimal		Optional	
PostageStatementReworke d block Closes				
PostageStatementFinalized block Opens				
OriginalPieces	Non Negative Integer		Optional	
ActualPieces	Non Negative Integer		Optional	
Postage	Decimal		Optional	
PostageStatementFinalized block Closes				
PostageStatementReverse d block Opens				
OriginalPieces	Non Negative Integer		Optional	
ActualPieces	Non Negative Integer		Optional	
Postage	Decimal		Optional	
PostageStatementReverse d block Closes				
PostageStatementNotAvail able block Opens				
OriginalPieces	Non Negative Integer		Optional	
ActualPieces	Non Negative Integer		Optional	
Postage	Decimal		Optional	

Copyright © 2011 USPS®. All Rights Reserved.

Mail.XML 9.0C - ReconciliationReportQueryResponse				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
PostageStatementNotAvailable block Closes				
TotalPieces	Non Negative Integer		Optional	
TotalActualPieces	Non Negative Integer		Optional	
TotalPostage	Decimal		Optional	
ReconciliationReport block Closes				
ReturnInfo	ReturnInfo			Refer 'ReturnInfo' complex type in Appendix D.
QueryResults Block Closes				
QueryError Block Opens				
ReturnInfo	ReturnInfo			Refer 'ReturnInfo' complex type in Appendix D.
QueryError Block Closes				

2.3.94 - ReconciliationReportQueryResponse

4.61 SiblingContainerCancelRequest

Purpose
Cancel sibling containers that are tied to the original container and are not necessary

Business Rules

- Must have previously provided the original container information and the sibling container information to the *PostalOne!* system
- ContainerIDs deleted may NOT be reused within a mailing group
- Customer will be allowed to remove one or more sibling containers from a single original container through a single SiblingContainerCancelRequest message
- The system validates that one or more sibling containers are sent with unique barcodes for cancellation/deletion if the original container is a Full-Service, Mixed Full-Service, or Basic container and that it does not belong to an MLOCR category
- Sibling containers submitted through Mail.dat or Mail.XML can be cancelled through the SiblingContainerCancelRequest message
- Cannot remove a sibling container that is in Ready to Pay status
- Cannot remove logical containers with ContainerType L, V, or M

4.61.1 SiblingContainerCancelRequest Data Structure

Field Description

Copyright © 2011 USPS®. All Rights Reserved.

Mail.XML 9.0C - SiblingContainerCancelRequest				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
SubmittingParty Block	ParticipantIDType		Required block; Identifies the customer submitting the message	Refer 'ParticipantID Type' complex type in Appendix E.
SubmittingSoftware Block	SubmittingSoftwareType		Required block; Identifies the software submitting the message	Refer 'SubmittingSoftware' complex type in Appendix E.
OriginalContainer Block	FullContainerIDType		Required field;	See Appendix E for Details
SiblingToDelete Block	FullContainerIDType		Required field;	See Appendix E for Details

2.3.95 - SiblingContainerCancelRequest

4.62 SiblingContainerCancelResponse

Purpose
Responds to the customer's request to determine if the sibling containers can be cancelled

Error/Return Codes
Refer Section 2.6 to view shared error/return codes and also a list of error/return codes tied this message.

Business Rules

- Must be returned to the customer after the SiblingContainerCancelRequest message is sent by the customer to *PostalOne!*
- Will reject if any of the containers have been finalized
- Will reject if original container information does not exist in *PostalOne!* system
- SiblingContainerCreateRequest must be accepted for the specific CRID if the sibling container is created through Mail.XML
- Sibling to be deleted must tie to an existing sibling container in the *PostalOne!* database
- Original container must be tied to an existing original container in the *PostalOne!* database
- Sibling to be deleted and the original container must be on a postage statement with UPD status for USPS Processing Due
- Sibling to be deleted and the original container cannot be on a postage statement with FIN status for Finalized or FPP status for Finalized Pending Payment

4.62.1 SiblingContainerCancelResponse Data Structure

Field Description

Mail.XML 9.0C - SiblingContainerCancelResponse

Copyright © 2011 USPS®. All Rights Reserved.

Field	Format	Acceptable Values	Business Rules	Comments
SIblingContainerCancelAccept Block begins			Response from USPS indicating that the SiblingContainerCancelRequest message was accepted	
CancelledSiblingContainer Block	FullContainerIDType		Required field;	See Appendix E for Details
ReturnInfo Block	ReturnInfo		Required field;	See Appendix B for Details
SIblingContainerCancelAccept block ends			End of block	
SiblingContainerCancelReject block begins			Response from USPS indicating that the SiblingContainerCancelRequest message was rejected	
CancelledSiblingContainer block	FullContainerIDType			See Appendix E for Details
SiblingToDelete Block	FullContainerIDType		Required field;	See Appendix B for Details
ReturnInfo Block	ReturnInfo		Required field;	See Appendix B for Details
SiblingContainerCancelReject block ends			End of block	

2.3.96 - SiblingContainerCancelResponse

4.63 SiblingContainerCreateRequest

Purpose
Message allows customers to add sibling containers to original containers when the a container in the mailing cannot support all mail pieces/handling units. The same message is used for Mail.XML Qualification data update when adding physical containers and handling units for Logical containers and handling units

Business Rules

- Must previously provide the original container information to the *PostalOne!* system for the specified CRID
- Must be sent before original container has been finalized
- Only logical containers can have siblings for MLOCR mailings
- Customer will be allowed to add one or more sibling containers to a single container through one SiblingContainerCreateRequest message

Copyright © 2011 USPS®. All Rights Reserved.

•

4.63.1 SiblingContainerCreateRequest Data Structure

Field Description

Mail.XML 9.0C - SiblingContainerCreateRequest				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
SubmittingParty Block	ParticipantIDType		Required block; Identifies the customer submitting the message	Refer 'ParticipantID Type' complex type in Appendix E.
SubmittingSoftware Block	SubmittingSoftwareType		Required block; Identifies the software submitting the message	Refer 'SubmittingSoftware' complex type in Appendix E.
OriginalContainer Block	LinkingContainerIDType		Required field;	See Appendix E for Details
UserLicenseCode	UserLicenseCode Type		Either the UserLicenseCode and MaildatJobID or the CustomerGroupID and MailingGroupID are required.	
MaildatJobID	JobIDType		Either the UserLicenseCode and MaildatJobID or the CustomerGroupID and MailingGroupID are required.	
CustomerGroupID	Alphanumeric, 25 characters		Either the UserLicenseCode and MaildatJobID or the CustomerGroupID and MailingGroupID are required.	
MailingGroupID	Non-negative integer		Either the UserLicenseCode and MaildatJobID or the	

Copyright © 2011 USPS®. All Rights Reserved.

Mail.XML 9.0C - SiblingContainerCreateRequest				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
			CustomerGroupID and MailingGroupID are required.	
ContainerID	Alphanumeric, 6 characters		Required	
UniqueContainerBarcode	Container24CharacterBarcodeType		Optional	
NewSiblingContainer Block	FullContainerIDType		Required field;	See Appendix E for Details
UserLicenseCode	UserLicenseCodeType		Either the UserLicenseCode and MaildatJobID or the CustomerGroupID and MailingGroupID are required.	
MaildatJobID	JobIDType		Either the UserLicenseCode and MaildatJobID or the CustomerGroupID and MailingGroupID are required.	
CustomerGroupID	Alphanumeric, 25 characters		Either the UserLicenseCode and MaildatJobID or the CustomerGroupID and MailingGroupID are required.	
MailingGroupID	Non-negative integer		Either the UserLicenseCode and MaildatJobID or the CustomerGroupID and MailingGroupID are required.	
ContainerID	Alphanumeric, 6 characters		Required	
UniqueContainerBarcode	Container24CharacterBarcodeType		Conditionally required for Full-Service physical sibling containers	

Copyright © 2011 USPS®. All Rights Reserved.

Mail.XML 9.0C - SiblingContainerCreateRequest				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
ContainerType	mailxml_base:mailXMLContainerType	Refer 'mailXMLContainerType' simple type	Required field;	Refer Appendix B
End Sequence Block				

2.3.97 - SiblingContainerCreateRequest

4.64 SiblingContainerCreateResponse

Purpose
Responds to the customer's request to determine if the sibling containers are valid

Error/Return Codes
Refer Section 2.6 to view shared error/return codes and also a list of error/return codes tied this message.

Business Rules
- Must be returned to the customer after the SiblingContainerCreateRequest message is sent by the customer to *PostalOne!*
- Sibling Container must not be finalized
- Will reject if ContainerID in NewSiblingContainer block exist in the *PostalOne!* system
- Will reject if original container information does not exist in *PostalOne!* system

4.64.1 SiblingContainerCreateResponse Data Structure

Field Description

Mail.XML 9.0C - SiblingContainerCreateResponse				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
SiblingContainerCreateAccept Block begins			Response from USPS indicating that the SiblingContainerCreateRequest message was accepted	
NewSiblingContainer Block	FullContainerIDType		Required field;	See Appendix E for Details
AcceptedSiblingContainer Block	FullContainerIDType		Required field;	See Appendix E for Details
ReturnInfo Block	ReturnInfo			See Appendix B for Details
SiblingContainerCreateAccept Block ends				

Copyright © 2011 USPS®. All Rights Reserved.

Mail.XML 9.0C - SiblingContainerCreateResponse				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
SiblingContainerCreateReject Block begins			Response from USPS indicating that the SiblingContainerCreateRequest message was rejected	
RejectedSiblingContainer block	FullContainerIDType		Required field;	See Appendix E for Details.
ReturnInfo Block	ReturnInfo		Required field;	See Appendix B for Details
SiblingContainerCreateReject block ends			End of block	

2.3.98 - SiblingContainerCreateResponse

4.65 SummaryZipDestinationReportCreateRequest

Purpose
This report is used by the USPS to identify all pieces of the postage statements are correctly calculated and can be verified through this report against all postage statements.

Business Rules

- This report is required for MLOCR mailings
- A QualificationReportCreateRequest and PostageStatementCreateRequest message must be submitted prior to submitting the SummaryZipDestinationReportCreateRequest
- The *PostalOne!* system will validate the fields in the SummaryZipDestinationReportCreate Request message
- The *PostalOne!* system will generate the SummaryZipDestinationReportCreateAccept block in the SummaryZipDestinationCreateResponse message if the SummaryZipDestinationReportCreateRequest message is accepted
- The *PostalOne!* system will generate the SummaryZipDestinationReportCreateReject block in the SummaryZipDestinationCreateResponse message if the SummaryZipDestinationReportCreateRequest message is rejected
- Beginning in Release 26.0.0, the *PostalOne!* system will continue to support NFM Processing Category (i.e. NA or NB)

4.65.1 SummaryZipDestinationReportCreateRequest Data Structure

Field Description

Mail.XML 9.0C - SummaryZipDestinationReportCreateRequest

Copyright © 2011 USPS®. All Rights Reserved.

Field	Format	Acceptable Values	Business Rules	Comments
SummaryZipDestinationReportCreateRequest Message BEGINS				
SubmittingParty	Mailxml:participantIDType		Required Block but all attributes within this block are optional	Refer 'ParticipantIDType' complex type in Appendix C
SubmittingSoftware	Mailxml:submittingSoftwareType		Required	Refer 'SubmittingParty' complex type in Appendix C
CustomerGroupID	String 25		Required	
MailingGroupID	nonnegative Integer		Required	
OnePassPlannedOrActual	Mailxml_base:yesNo	Yes/No	Optional	
OnePassOrTwoPass	Mailxml_base:onePassOrTwoPassType	Refer 'onePassOrTwoPassType' simple type	Optional	Refer Appendix B
Sequence Block BEGIN			1 to many allowed	
EntryPointZip	Mailxml_base:zipCodeThreeOrFiveDigit	Refer 'zipCodeThreeOrFiveDigit' simple type		Refer Appendix B
EntryFacilityType	Mailxml_base:EntryFacilityType	Refer 'entryFacilityType' simple type	Optional	Refer Appendix B
SummaryZipDestinationReport Block BEGIN			Required 1 to many allowed	
DestinationZip	Mailxml_base:zipCodeThreeOrFiveDigit	Refer 'zipCodeThreeOrFiveDigit' simple type	Required	Refer Appendix B
ProcessingCategory	Mailxml_base:processingCategoryType	Refer 'processingCategoryType' simple type	Optional	Refer Appendix B
PostagePaymentMethod	Mailxml_base:postagePaymentMe	Refer 'postagePayment	Required	Refer Appendix B

Copyright © 2011 USPS®. All Rights Reserved.

Mail.XML 9.0C - SummaryZipDestinationReportCreateRequest				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
	thodType	MethodTYpe' simple type		
MLOCRRateType	Mailxml_base:mlocrRateType	Refer simple type definition in appendix B	Optional	Refer Appendix B
Weight	Double		Optional The value of Weight must be in Pounds.	
RateAffixed	Double		Optional	
NumberOfPieces	nonnegative Integer		Optional	
NumberOfPiecesDifference	nonnegative Integer		Optional	
PostageAffixed	Double		Optional	
CumulativePostageAffixed	Double		Optional	
TotalPostage	Double		Optional	
NetPostageDue	Double		Optional	
CumulativePostageDue	Double		Optional	
RunningTotalPieces	nonnegative Integer		Optional	
SortationLevel	Mailxml_base:containerLevelType		Required	Refer simple type containerLevelType in Appendix B
SummaryZipDestinationReport Block END				
Sequence Block END				
SummaryZipDestinationReportCreateRequest Message ENDS				

2.4.10 – SummaryZipDestionationReportCreateRequest

4.66 SummaryZipDestinationReportCreateResponse

Purpose
This is the response message to SummaryZipDestinationReportCreateRequest message

Business Rules

- This message is required for MLOCR mailing.
- The *PostalOne!* System will generate the SummaryZipDestinationReportCreateAccept block in the SummaryZipDestinationCreateResponse message if the SummaryZipDestinationReportCreateRequest message is accepted

Copyright © 2011 USPS®. All Rights Reserved.

- The *PostalOne!* System will generate the SummaryZipDestinationReportCreateReject block in the SummaryZipDestinationCreateResponse message if the SummaryZipDestinationReportCreateRequest message is rejected

4.66.1 SummaryZipDestinationReportCreateResponse Data Structure

Field Description

Mail.XML 9.0C - SummaryZipDestinationReportCreateResponse				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
SummaryZipDestinationReportCreateAccept Block BEGIN			Either Accept or Reject Block is returned	
ReturnInfo	Complex Type		Optional	Refer 'ReturnInfo' complex in Appendix E
SummaryZipDestinationReportCreateAccept Block END				
SummaryZipDestinationReportCreateReject Block BEGIN			Either Accept or Reject Block is returned	
ReturnInfo	Complex Type		Optional	Refer 'ReturnInfo' complex in Appendix E
SummaryZipDestinationReportCreateReject Block END				

2.3.6565 - SummaryZipDestinationReportCreateResponse

Copyright © 2011 USPS®. All Rights Reserved.

5. Additional Rules/Constraints

5.1.1 Container Status Messages

The *PostalOne!* system will support status checking through Container Status Query Request and Response messages in this release by the originator of the data and by the entity identified as the Scheduler or Carrier in the eDocumentation. Status checking allows mailers to view the status of any given container(s) and ensure that the container is validated during the pre-induction and post-induction process

The *PostalOne!* system upon receiving the container status message shall go to the container management system of eInduction to find out all validation status of the requested container(s) and respond to the customer with the status information.

If there are any issues or validation errors for one or more containers, then the *PostalOne!* system shall respond back to the customer with validation failures for one or more container(s).

5.1.1 ContainerStatusQueryResponse Error Codes / Return Values

Error Code	Error Message
4050	Unauthorized Access Error
4051	Invalid Barcode
4052	Duplicate Barcode
4053	Scheduling Error
4054	Entry Point Discount Error
4055	No records were found for the given search criteria
4056	Payment is not finalized for pallet containers. No induction validation information is available
4057	Payment is not finalized for tray containers. No induction validation information is available

1.2 Error Codes/Return Values

Faults, such as a message timeout or invalid XML are to be communicated using the <fault element and returned within the detail section of the SOAP fault. The fault consists of a tracking ID and one or more fault codes and optional fault descriptions.

Below is the list of the error codes that will be used by USPS when deploying the eDocumentation Messages starting in November 2009.

Error Code	Error Message	Messages
8000	CustomerGroupID in the HeaderInfo block must be the same for all messages in a mailing group.	Multiple
8002	CRID field within the SubmittingParty block must be the same for all request messages in a mailing group.	Multiple

Copyright © 2011 USPS®. All Rights Reserved.

Error Code	Error Message	Messages
8003	All fields within the DocumentVersionData block must match the corresponding fields in DocumentVersionData blocks and DocumentVersionDataWithPermit blocks with the same VersionID, except Periodicals with Non-Incidental Enclosures.	Multiple
8006	MailingGroupData block must be populated with a combination of values that exist in the *PostalOne!* Mail.dat database within the OpenMailingGroupRequest message.	OpenMailingGroup Response
8007	PermitNumber field within the PermitPublicationData block must map to the SubmitterCRID within the MailingGroupData block for preparing electronic documentation.	OpenMailingGroup Response
8008	PermitNumber field within the PermitPublicationData block must map to the SubmitterCRID within the MailingGroupData block must be unique when combined with the PermitType and PostOfficeOfMailingZip fields of the OpenMailingGroupRequest message.	OpenMailingGroup Response
8009	The first 5 characters of the PermitZIP4 field within the PermitPublicationData block must match the PostOfficeOfMailingZip field within the MailingGroupData block.	OpenMailingGroup Response
8010	MailingFacility field within the MailingGroupData block must be populated with a value that is the same as the CRID of the SubmittingParty block.	OpenMailingGroup Response
8011	OnePassIndicator field must be populated if the MailXMLPresentationCategory field in the MailingGroupData block is populated with M.	OpenMailingGroup Response
8012	OpenMailingGroupRequest message must be accepted before submitting the CloseMailingGroupRequst message for the specified MailingGroupID.	OpenMailingGroup Response, CloseMailingGroupResponse
8013	The fields within the SubmittingParty block in the CloseMailingGroupRequest message must be populated with the same values as the fields within the SubmittingParty block of an open mailing group.	CloseMailingGroupResponse
8014	CustomerGroupID field in the CloseMailingGroupRequest must be populated with the same value as the CustomerGroupID in the OpenMailingGroupRequest.	CloseMailingGroupResponse
8015	MailingGroupID field in the CloseMailingGroupRequest must be populated with the same value as the MailingGroupID in the OpenMailingGroupResponse.	CloseMailingGroupResponse
8016	MailingGroupID and CustomerGroupID in the CloseMailingGroupRequest must be populated with the same value as the MailingGroupID and CustomerGroupID of an accepted OpenMailingGroupRequest.	CloseMailingGroupResponse
8017	OpenMailingGroupRequest message must be accepted before submitting the QualificationReportCreateRequest message for the specified MailingGroupID and CustomerGroupID.	QualificationReportCreateResponse
8018	ContainerInfoData block(s) is required for each container/handling unit for a qualification report.	QualificationReportCreateResponse
8020	Each ContainerInfoData block needs the ContainerDetailData block populated except when it is a Parent Container or it is a Sibling Container.(Container ID: %%1).	QualificationReportCreateResponse, QualificationReportDetailCreateResponse (10.0)

Copyright © 2011 USPS®. All Rights Reserved.

Error Code	Error Message	Messages
8022	ActualContainerShipDate is required when USPSPickup field in the ContainerInfoData block in the QualificationReport block is Y. (Container ID: %%1)	QualificationReportCreateResponse, QualificationReportDetailCreateResponse (10.0)
8023	ContainerBarcode field in the ContainerInfoData block in the QualificationReport block cannot be populated when the ContainerType field value is L, M, or V. (Container ID: %%1)	QualificationReportCreateResponse, QualificationReportDetailCreateResponse (10.0)
8026	ParentContainerID field in the ContainerInfoData block in the QualificationReport block cannot be populated if the SiblingContainerID field is populated. (Container ID: %%1)	QualificationReportCreateResponse, QualificationReportDetailCreateResponse (10.0)
8027	ParentContainerID in the ContainerInfoData block in the QualificationReport block must point to another existing ParentContainerID within the QualificationReportCreateRequest message. (Container ID: %%1)	QualificationReportCreateResponse
8028	SiblingContainerID field in the ContainerInfoData block in the QualificationReport block must point to a different container also in the QualificationReportCreateRequest message. (Container ID: %%1)	QualificationReportCreateResponse
8030	EntryLocaleKey must contain 6 characters. (Container ID: %%1)	QualificationReportCreateResponse, QualificationReportDetailCreateResponse (10.0)
8032	AdditionalTrayPostageAmount must contain less than or equal to 4 decimal characters. (Container ID: %%1)	QualificationReportCreateResponse, QualificationReportDetailCreateResponse (10.0)
8033	PermitNumber within the PermitPublicationData block in the MailingGroupData block must be populated with a value combined with the PostOfficeOfMailingZIP in the MailingGroupData block that maps to a single active Finance Number.	OpenMailingGroupResponse
8035	InOutCountyIndicator field in the ContainerDetailData block in the ContainerInfoData block in the QualificationReport block is required when FormType is PE. (Container ID: %%1)	QualificationReportCreateResponse
8037	Only one ContainerID field in the MailXMLPieceRange block can be populated.	MailPieceCreateResponse
8039	BundleDetailCreateRequest message must be accepted before submitting the MailPieceCreateRequest message when BundleID in the MailPieceBlockGroup is populated for the specified MailingGroupID and CustomerGroupID.. (BundleID: %%1, ContainerID: %%2)	MailPieceCreateResponse
8040	PublicationNumber field in the QualificationReportPreparer block in the QualificationReport block cannot be populated when the FormType is not populated with PE for Periodicals.	QualificationReportCreateResponse, QualificationReportSummaryCreateResponse (10.0)

Copyright © 2011 USPS®. All Rights Reserved.

Error Code	Error Message	Messages
8041	PermitNumber field in the QualificationReportPreparer block in the QualificationReport block is required when the FormType is not PE for Periodicals or Pending Periodicals.	QualificationReportCreateResponse, QualificationReportSummaryCreateResponse (10.0)
8042	PermitType field within the QualificationReportPreparer in the QualificationReport block is required when the FormType is not PE for Periodicals or Pending Periodicals.	QualificationReportCreateResponse, QualificationReportSummaryCreateResponse (10.0)
8043	PermitZIP4 field within the QualificationReportPreparer block in the QualificationReport block is required when the FormType is not PE for Periodicals or Pending Periodicals.	QualificationReportCreateResponse, QualificationReportSummaryCreateResponse (10.0)
8045	VersionID field value within the DocumentVersionDataWithPermit block in the QualificationReport block must be referenced in at least one VersionID in the ContainerDetailData block. (Version ID: %%1)	QualificationReportCreateResponse, QualificationReportDetailCreateResponse (10.0)
8046	PieceWeight field within the DocumentVersionDataWithPermit block in the QualificationReport block must contain less than or equal to 4 decimal characters. (Version ID: %%1)	QualificationReportCreateResponse, QualificationReportDetailCreateResponse (10.0)
8047	AdPercent field value within the DocumentVersionDataWithPermit block in the QualificationReport block cannot be more than 4 decimals. (Version ID: %%1)	QualificationReportCreateResponse, QualificationReportDetailCreateResponse (10.0)
8048	AdPercent field value within the DocumentVersionDataWithPermit block in the QualificationReport block cannot be more than 100.00. (Version ID: %%1)	QualificationReportCreateResponse, QualificationReportDetailCreateResponse (10.0)
8049	RateAffixed field within the DocumentVersionDataWithPermit block in the QualificationReport block cannot be more than 3 decimal characters. (Version ID: %%1)	QualificationReportCreateResponse, QualificationReportDetailCreateResponse (10.0)
8050	RateAffixed field within the DocumentVersionDataWithPermit block in the QualificationReport block is required when the PermitType field is set to MT, PC, or OM. (Version ID: %%1)	QualificationReportCreateResponse, QualificationReportDetailCreateResponse (10.0)
8051	PermitNumber field in the DocumentVersionDataWithPermit block in the QualificationReport block is required when the FormType is FC, SM, BP, ML, PM, or PP. The PermitNumber field cannot be populated when FormType is PE for Periodicals. Form type is: %%2	QualificationReportCreateResponse

Copyright © 2011 USPS®. All Rights Reserved.

Error Code	Error Message	Messages
8053	PermitType field within PermitPublicationData block in the DocumentVersionDataWithPermit block in the QualificationReport block cannot be populated when the PublicaitonNumber is populated. (Version ID: %%1)	QualificationReportCreateResponse, QualificationReportDetailCreateResponse (10.0)
8055	PermitZIP4 field within PermitPublicationData block in the DocumentVersionDataWithPermit block in the QualificationReport block is required when the FormType is: PM, FC, SM, BP, PP, or ML.	QualificationReportCreateResponse
8058	PublicationNumber field in the PermitPublicationData block in the DocumentVersionDataWithPermit block in the QualificationReport data block should not be populated when the FormType is not populated with PE for Periodicals or Pending Periodicals.	QualificationReportCreateResponse
8061	QualificationReportCreateRequest message must be accepted before submitting the BundleDetailCreateRequest message for the specified CustomerGroupID and MailingGroupID.	BundleDetailCreateResponse
8062	CustomerBundleID is a required field.	BundleDetailCreateResponse
8063	BundleZIP must be populated with either 3 or 5 characters.	BundleDetailCreateResponse
8064	BundleCarrierRoute is required when the SortationLevel in the BundleDetail block of the BundleDetailCreateRequest message is populated with A, B, C, D, or U.	BundleDetailCreateResponse
8065	MailingGroupID and Customer GroupID in the BundleCreateRequestHeaderInfo block must be populated with the same values as the MailingGroupID and CustomerGroupID of an accepted OpenMailingGroupRequest message.	BundleDetailCreateResponse
8066	ContainerID must be populated with the same value as the ContainerID in the ContainerInfoData block of the QualificationReportCreateRequest message for the specified MailingGroupID and CustomerGroupID. Found Missing ContainerID: %%1	BundleDetailCreateResponse
8067	VersionID must be populated with the same value as the VersionID in the ContainerDetailData block of the QualificationReportCreateRequest message for the specified MailingGroupID and CustomerGroupID. Found Missing VersionID: %%1	BundleDetailCreateResponse
8068	BundleDetailCreateRequest message with the updated number of pieces for the specified combination of MailingGroupID, CustomerGroupID, and BundleID must be accepted before submitting the BundleDetailCancelRequest message. (BundleID '%%1')	BundleDetailCreateResponse, BundleDetailCancelRequest
8069	MailPieceCancelRequest message with the updated number of cancelled pieces for the specified combination of MailingGroupID, CustomerGroupID, and BundleID must be accepted before submitting the BundleDetailCancelRequest message.	BundleDetailCancelRequest
8070	BundleDetailCreateRequest message must be accepted before submitting the BundleDetailCancelRequest message.	BundleDetailCancelRequest
8071	BundleID is a required field.	BundleDetailCancelRequest

Copyright © 2011 USPS®. All Rights Reserved.

Error Code	Error Message	Messages
8073	ContainerID must match the ContainerID in the BundleDetail block of the BundleDetailCreateRequest message for the specified MailingGroupID and CustomerGroupID. ContainerID %%1 was not found.	BundleDetailCancelRequest
8074	BundleID must match the BundleID in the BundleDetail block of the BundleDetailCreateRequest message for the specified MailingGroupID and CustomerGroupID.	BundleDetailCancelRequest
8075	OriginalContainer block must contain fields that are populated with the values that exist for the specified CRID.	SiblingContainerCreateResponse
8076	NewSiblingContainer block must be populated with values that tie to the values populated in the OriginalContainer block.	SiblingContainerCreateResponse
8077	CRID in the SubmittingParty block must be populated with the same value as the Mailing Facility ID in the .seg file for the specified information in the OriginalContainer block.	SiblingContainerCreateResponse
8078	UserLicenseCode field in the OriginalContainer block must be populated with the same value as the value populated in the User License Code field from the .hdr file of the existing container.	SiblingContainerCreateResponse
8079	MaildatJobID field in the OriginalContainer block must be populated with the same value as the value populated in the Job ID field from the .csm file of the existing container.	SiblingContainerCreateResponse
8080	ContainerID field in the OriginalContainer block must be populated with the same value as the value populated in the Container ID field in the .csm file of the existing container.	SiblingContainerCreateResponse
8081	UniqueContainerBarcode field in the OriginalContainer block, if populated, is populated with the same value as the Label: IM Container or IM Tray Barcode field in the .csm file of the existing container.(UniqueContainerBarcode %%1)	SiblingContainerCreateResponse
8082	UserLicenseCode field in the NewSiblingContainer block must be populated with the same value as the value populated in the UserLicenseCode field in the OriginalContainer block.	SiblingContainerCreateResponse
8083	MaildatJobID field in the NewSiblingContainer block must be populated with the same value as the value populated in the MaildatJobID field in the OriginalContainer block.	SiblingContainerCreateResponse
8084	MaildatJobID field in the NewSiblingContainer block must be populated with the same value as the value populated in the MaildatJobID field in the OriginalContainer block.	SiblingContainerCreateResponse
8087	ContainerID in the NewSiblingContainer block must be unique within the MaildatJobID. (ContainerID: %%1)	SiblingContainerCreateResponse
8088	The SiblingContainerCreateRequest messsage for this combination of CRID, MaildatJobID, ContainerId and SiblingContainerID does not exist.(Original ContainerID: %%1, Sibling ContainerID: %%2, CRID: %%3)	SiblingContainerCancelResponse
8089	SiblingToDelete block must be tied to an existing sibling container in the *PostalOne!* Mail.dat database for the specified CRID. (Sibling ContainerID: %%1)	SiblingContainerCancelReseponse
8090	UserLicenseCode field in the OriginalContainer block must be populated with the same value as the value populated in the UserLicenseCode field in the OriginalContainer block of the SiblingContainerCreateRequest message.	SiblingContainerCreateResponse

Copyright © 2011 USPS®. All Rights Reserved.

Error Code	Error Message	Messages
8091	MaildatJobID field in the OriginalContainer block must be populated with the same value as the value populated in the MaildatJobID field in the OriginalContainer block of the SiblingContainerCreateRequest message.	SiblingContainerCancelReseponse
8092	ContainerID field in the OriginalContainer block must be populated with the same value as the value populated in the ContainerID field in the OriginalContainer block of the SiblingContainerCreateRequest message.	SiblingContainerCancelReseponse
8093	UniqueContainerBarcode field in the OriginalContainer block, if populated, is populated with the same value as the value populated in the UniqueContainerBarcode field in the OriginalContainer block of the SiblingContainerCreateRequest message.	SiblingContainerCancelReseponse
8094	UserLicenseCode field in the SiblingToDelete block must be populated with the same value as the value populated in the UserLicenseCode field in the NewSiblingContainer block of the SiblingContainerCreateRequest message for the specified CRID.	SiblingContainerCancelReseponse
8095	MaildatJobID field in the SiblingToDelete block must be populated with the same value as the value populated in the MaildatJobID field in the NewSiblingContainer block of the SiblingContainerCreateRequest message for the specified CRID.	SiblingContainerCancelReseponse
8096	ContainerID field in the SiblingToDelete block must be populated with the same value as the value populated in the ContainerID field in the NewSiblingContainer block of the SiblingContainerCreateRequest message for the specified CRID.	SiblingContainerCancelReseponse
8097	UniqueContainerBarcode field in the SiblingToDelete block must be populated with the same value as the value populated in the UniqueContainerBarcode field in the NewSiblingContainer block of the SiblingContainerCreateRequest message for a specified CRID.	SiblingContainerCancelReseponse
8098	The ContainerID field in the SibilingToDelete block cannot have ContainerType set to L, V, or M. (Sibling ContainerID: %%1)	SiblingContainerCancelRequest
8100	OpenMailingGroupRequest message must be accepted before submitting the PostageStatementCreateRequest message for the specified CustomerGroupID and MailingGroupID.	Postage Statement Messages
8101	BeginCombinedMailingRequest message must be accepted before submitting the PostageStatementCreateRequest message for the specified CustomerGroupID and MailingGroupID for a combined mailing.	Postage Statement Messages
8102	LineItemSummaryData block is required when the ExtendedForm in the CreatePostageStatement block is populated with False.	Postage Statement Messages
8103	PostageStatementLineItemData is required when the ExtendedForm in the CreatePostageStatement block is populated with True.	Postage Statement Messages
8104	PermitHolderForAPData is required when the PostagePaymentMethod in the CreatePostageStatement block is populated with M or S.	Postage Statement Messages
8105	MailingGroupID and Customer GroupID in the MailXMLPostageStatementRequestHeaderInfo block must be populated with the same values as the MailingGroupID and CustomerGroupID of an accepted OpenMailingGroupRequest message.	Multiple

Copyright © 2011 USPS®. All Rights Reserved.

Error Code	Error Message	Messages
8106	AgencyCostCode in the CreatePostageStatement block must contain less than or equal to 5 characters.	Postage Statement Messages
8107	AgencyCostCode in the CreatePostageStatement block is required when the PermitType in the PermitPublicationData block in the MailingGroupData block is populated with OI or OM.	Postage Statement Messages
8113	CarrierRouteSequencingDate is required when the RateCategory in the PostageStatementLineItemData block is populated with A, B, D, O, A1, B1, or D1.	Postage Statement Messages
8114	PiecePostage in the LineItemSummaryData block must contain less than or equal to 4 decimal characters.	Postage Statement Messages
8115	PieceRate in the LineItemSummaryData block must contain less than or equal to 3 decimal characters.	Postage Statement Messages
8116	PostageAmount in the LineItemSummaryData block must contain less than or equal to 4 decimal characters.	Postage Statement Messages
8117	PoundPostage in the LineItemSummaryData block must contain less than or equal to 4 decimal characters.	Postage Statement Messages
8118	PoundRate in the LineItemSummaryData block must contain less than or equal to 3 decimal characters.	Postage Statement Messages
8119	PreparedAsSM must be populated with Yes when the FormType in the CreatePostageStatement block is populated with SM.	Postage Statement Messages
8121	TotalWeight in the LineItemSummaryData block must contain less than or equal to 4 decimal characters.	Postage Statement Messages
8123	ContainerDisplayName is required when the RegisterOfMailing in the CreatePostageStatement block is populated with True.	Postage Statement Messages
8124	ContainerID is required when the RegisterOfMailing in the CreatePostageStatement block is populated with True.	Postage Statement Messages
8125	EntryFacilityType is required when the RegisterOfMailing in the CreatePostageStatement block is populated with True.	Postage Statement Messages
8126	EntryZIP is required when the RegisterOfMailing in the CreatePostageStatement block is populated with True.	Postage Statement Messages
8128	PieceRate in the PostageStatementLineItemData block must contain less than or equal to 3 decimal characters.	Postage Statement Messages
8129	PostageAmount in the PostageStatementLineItemData block must contain less than or equal to 4 decimal characters.	Postage Statement Messages
8130	PoundRate in the PostageStatementLineItemData block must contain less than or equal to 3 decimal characters.	Postage Statement Messages

Copyright © 2011 USPS®. All Rights Reserved.

Error Code	Error Message	Messages
8131	When PreparedAsSM is True and Form Type is FC, then ProcessingCategory must be FL, LT, or PF, and RateCategory must be S.	Postage Statement Messages
8133	SinglePieceWeight in the PostageStatementLineItemData block must contain less than or equal to 4 decimal characters.	Postage Statement Messages
8134	TotalWeight in the PostageStatementLineItemData block must contain less than or equal to 4 decimals characters.	Postage Statement Messages
8135	Zone can only be populated with N, 1, 3, 4, 5, 6, 7, 8, DDU, or SCF in the PostageStatementCreateRequest message.	Postage Statement Messages
8136	VersionID is required when the PostageAffixedAmount in the CreatePostageStatement block is not provided.	Postage Statement Messages
8137	ContainerType is required when the RegisterOfMailing in the CreatePostageStatement block is populated with True.	Postage Statement Messages
8138	SinglePieceDimensionalWeight in the PostageStatementLineItemData block must contain less than or equal to 4 decimal characters.	Postage Statement Messages
8139	SinglePieceDimensionalWeight in the PostageStatementLineItemData block must be populated with a value greater than zero when the SurchargeType in the *PostageStatementLineItemData* block is populated with D.	Postage Statement Messages
8140	PostageAffixedAmount is required when the PostagePaymentMethod in the CreatePostageStatement block is populated with M or S.	Postage Statement Messages
8141	When SinglePieceWeight in the CreatePostageStatement block is provided, it must match all SinglePieceWeight fields in the PostageStatementLineItemData block.	Postage Statement Messages
8142	ServiceRate in the ExtraServiceData block must contain less than or equal to 3 decimal characters.	Postage Statement Messages
8143	ServiceValue in the ExtraServiceDatamust block must contain less than or equal to 4 decimal characters.	Postage Statement Messages
8144	TotalAmount in the ExtraServiceData block must contain less than or equal to 4 decimal characters.	Postage Statement Messages
8145	TotalAmount in the ExtraServiceSummaryData block must contain less than or equal to 4 decimal characters.	Postage Statement Messages
8146	PieceWeight in the DocumentVersionData block must contain less than or equal to 4 decimal characters.	Postage Statement Messages
8147	RateAffixed is required when the PostagePaymentMethod in the CreatePostageStatement block is populated with M or S.	Postage Statement Messages
8148	RateAffixed in the DocumentVersionData block must contain less than or equal to 3 decimal characters.	Postage Statement Messages

Copyright © 2011 USPS®. All Rights Reserved.

Error Code	Error Message	Messages
8149	SinglePieceDimensionalWeight CreatePostageStatement must contain less than or equal to 4 decimal characters.	Postage Statement Messages
8153	MoveUpdateMethod is required when the FormType in the CreatePostageStatement block is populated with SM.	Postage Statement Messages
8155	The PermitNumber and PermitZIP4 or PublicationNumber in the PermitHolderData or PublisherData blocks and the MailingAgentData block must map to the same Finance Number and must be active.	Postage Statement Messages
8156	PermitType must be populated with MT or OM when the MeteredAffixedMethod in the CreatePostageStatement block is populated with M.	Postage Statement Messages
8157	PermitType must be populated with PC when the PostagePaymentMethod in the CreatePostageStatement block is populated with S.	Postage Statement Messages
8158	PublicationNumber cannot be populated in the PermitPublicationData block in the PermitHolderData block of the PostageStatementCreateRequest.	Postage Statement Messages
8159	PublicationNumber cannot be populated in the PermitPublicationData block in the MailingOwnerData block of the PostageStatementCreateRequest.	Postage Statement Messages
8160	PublicationNumber cannot be populated in the PermitPublicationData block in the MailingAgentData block of the PostageStatementCreateRequest.	Postage Statement Messages
8161	PermitType field in the PermitPublicationData block in the PermitHolderForAPData block must be populated with PI or OI.	Postage Statement Messages
8162	PublicationNumber cannot be populated in the PermitPublicationData block in the PermitHolderForAPData block of the PostageStatementCreateRequest.	Postage Statement Messages
8163	PostageStatementMailingDate in the CreatePostageStatement block must match the PostageStatementMailingDate in the QualificationReportCreateRequest message when it is populated for the same ContainerID for the specified MailingGroupID and CustomerGroupID.	Postage Statement Messages
8164	CombinedMailingID in the CreatePostageStatement block must match the CombinedMailingID in the BeginCombinedMailingAccept block of the BeginCombinedMailingResponse message for the specified MailingGroupID and CustomerGroupID.	Postage Statement Messages
8165	ServiceSubCode must be populated with N when ServiceCode in the ExtraServiceData block is populated with CM. Extra Service Data block number %%1 contains an invalid Sub Service Code %%2 for Service Code %%3.	Postage Statement Messages
8166	ServiceSubCode must be populated with N or R when ServiceCode in the ExtraServiceData block is populated with COD. Extra Service Data block number %%1 contains an invalid Sub Service Code %%2 for Service Code %%3.	Postage Statement Messages
8167	ServiceSubCode must be populated with N when ServiceCode in the ExtraServiceData block is populated with COM. Extra Service Data block number %%1 contains an invalid Sub Service Code %%2 for Service Code %%3.	Postage Statement Messages

Copyright © 2011 USPS®. All Rights Reserved.

Error Code	Error Message	Messages
8168	ServiceSubCode must be populated with E or R when ServiceCode in the ExtraServiceData block is populated with DC. Extra Service Data block number %%1 contains an invalid Sub Service Code %%2 for Service Code %%3.	Postage Statement Messages
8169	ServiceSubCode must be populated with N when ServiceCode in the ExtraServiceData block is populated with IM. Extra Service Data block number %%1 contains an invalid Sub Service Code %%2 for Service Code %%3.	Postage Statement Messages
8170	ServiceSubCode must be populated with N when ServiceCode in the ExtraServiceData block is populated with PAL. Extra Service Data block number %%1 contains an invalid Sub Service Code %%2 for Service Code %%3.	Postage Statement Messages
8171	ServiceSubCode must be populated with N when ServiceCode in the ExtraServiceData block is populated with RD. Extra Service Data block number %%1 contains an invalid Sub Service Code %%2 for Service Code %%3.	Postage Statement Messages
8172	ServiceSubCode must be populated with N when ServiceCode in the ExtraServiceData block is populated with RM. Extra Service Data block number %%1 contains an invalid Sub Service Code %%2 for Service Code %%3.	Postage Statement Messages
8173	ServiceSubCode must be populated with T when ServiceCode in the ExtraServiceData block is populated with RR. Extra Service Data block number %%1 contains an invalid Sub Service Code %%2 for Service Code %%3.	Postage Statement Messages
8174	ServiceSubCode must be populated with E when ServiceCode in the ExtraServiceData block is populated with RRE. Extra Service Data block number %%1 contains an invalid Sub Service Code %%2 for Service Code %%3.	Postage Statement Messages
8175	ServiceSubCode must be populated with N when ServiceCode in the ExtraServiceData block is populated with RRM. Extra Service Data block number %%1 contains an invalid Sub Service Code %%2 for Service Code %%3.	Postage Statement Messages
8176	ServiceSubCode must be populated with E or R when ServiceCode in the ExtraServiceData block is populated with SC. Extra Service Data block number %%1 contains an invalid Sub Service Code %%2 for Service Code %%3.	Postage Statement Messages
8177	ServiceSubCode must be populated with N when ServiceCode in the ExtraServiceData block is populated with SH. Extra Service Data block number %%1 contains an invalid Sub Service Code %%2 for Service Code %%3.	Postage Statement Messages
8178	SinglePieceWeight in the CreatePostageStatement block must be populated with the same value as the SinglePieceWeight in the PostageStatementLineItemData block for the specified MailingGroupID and CustomerGroupID.	Postage Statement Messages
8179	SinglePieceWeight in the CreatePostageStatement block must be populated with the same value as the PieceWeight in the DocumentVersionData block of the CreatePostageStatement block when the DocumentVersionData block is populated.	Postage Statement Messages
8181	DalPieces must be populated with a value that is equal to the total number of pieces with ProcessingCategory FL, MP, IR, or NP and RateCategory A, B, D, or O for the specified MailingGroupID and CustomerGroupID when provided.	Postage Statement Messages

Copyright © 2011 USPS®. All Rights Reserved.

Error Code	Error Message	Messages
8182	Pieces greater than 3.3 ounces and less than 16 ounces and pieces less than or equal to 3.3 ounces cannot be submitted together within a mailing when DalPieces is populated.	Postage Statement Messages
8184	StatementID in the PostageStatementQueryRequest message must exist for the specified MailingGroupID and CustomerGroupID.	Postage Statement Messages
8185	PeriodicalStatementID can only be submitted in the PeriodicalStatementQueryRequest.	Postage Statement Messages
8186	PostageStatementCreateRequest message or PeriodicalStatementCreateRequest message must be accepted before submitting the PostageStatementStatusQueryRequest message for the specified MailingGroupID, CustomerGroupID and StatementID.	Postage Statement Messages
8191	StatementID in the PostageStatementCancelRequest message must exist for the specified MailingGroupID and CustomerGroupID.	Postage Statement Messages
8193	OpenMailingGroupRequest message must be accepted before submitting the BeginCombinedMailingRequest for the specified MailingGroupID and CustomerGroupID.	BeginCombinedMailingResponse
8194	MailingGroupID and CustomerGroupID of the BeginCombinedMailingRequest must be populated with the same values as the value populated in MailingGroupID and CustomerGroupID for an accepted OpenMailingGroupRequest message.	BeginCombinedMailingResponse
8195	All PostageStatementCreateRequest messages must be submitted for the specified MailingGroupID, CustomerGroupID,and CombinedMailingID before submitting the EndCombinedMailingRequest message.	EndCombinedMailingResponse
8196	BeginCombinedMailingRequest message must be accepted for the specified MailingGroupID, CustomerGroupID, and CombinedMailingID before submitting the EndCombinedMailingRequest message.	EndCombinedMailingResponse
8197	MailingGroupID and CustomerGroupID in the of the EndCombinedMailingRequest must be populated with the same values as the value populated in MailingGroupID and CustomerGroupID for an accepted OpenMailingGroupRequest message.	EndCombinedMailingResponse
8198	OpenMailingGroupRequest message must be accepted before submitting the PeriodicalStatementCreateRequest message for the specified CustomerGroupID and MailingGroupID. (User Postage Statement ID: %%1).	Postage Statement Messages
8199	DocumentVersionData block in the CreatePeriodicalStatementData block is required. (User Postage Statement ID: %%1).	Postage Statement Messages
8200	AdvertisingPercentage in the CreatePeriodicalStatementData block must contain less than or equal to 2 decimal characters. (User Postage Statement ID: %%1).	Postage Statement Messages
8204	CopyWeight in the CreatePeriodicalStatementData block must contain less than or equal to 4 decimal characters. (User Postage Statement ID: %%1).	Postage Statement Messages

Copyright © 2011 USPS®. All Rights Reserved.

Error Code	Error Message	Messages
8205	DiscountQty in the PeriodicalLineItemData block is required when the PeriodicalPrice in the PeriodicalLineItemData block is populated with 1. (User Postage Statement ID: %%1).	Postage Statement Messages
8206	DiscountQty in the PeriodicalLineItemData block cannot contain decimal characters. (User Postage Statement ID: %%1).	Postage Statement Messages
8207	PeriodicalPrice in the PeriodicalLineItemData block can only be populated with Blank, 1, 5, 9, C, D, E, R, or Z. (User Postage Statement ID: %%1).	Postage Statement Messages
8210	Pieces in the PeriodicalLineItemData block is required when RateCategory in the PeriodicalLineItemData block is populated. (User Postage Statement ID: %%1).	Postage Statement Messages
8213	RateCategory in the PeriodicalLineItemData block can only be populated with A, B, D, O, FB, E, G, H, K, L1, L2, L3, L4, L5, L6, L, N in the PeriodicalLineItemData block. (User Postage Statement ID: %%1).	Postage Statement Messages
8214	At least one of the SubReqCopies or the NonCopies field is required and must be populated with a non-zero integer when both bundles and containers are not populated (User Postage Statement ID: %%1).	Postage Statement Messages
8217	ChargeableContainerLevel is required when InOutCountyIndicator is populated with N and ChargeableEntryLevel and ChargeableContainerType and Containers in the PeriodicalLineItemData block are populated. (User Postage Statement ID: %%1).	Postage Statement Messages
8218	ChargeableBundleLevel in the PeriodicalLineItemData block is required when InOutCountyIndicator is populated with N and ChargeableContainerLevel and Bundles in the PeriodicalLineItemData block are populated. (User Postage Statement ID: %%1).	Postage Statement Messages
8219	Bundles in the PeriodicalLineItemData block must contain less than or equal to 4 decimal characters. (User Postage Statement ID: %%1).	Postage Statement Messages
8220	Bundles in the PeriodicalLineItemData block is required when InOutCountyIndicator is populated with N and ChargeableContainerLevel and ChargeableBundleLevel in the PeriodicalLineItemData block are populated. (User Postage Statement ID: %%1).	Postage Statement Messages
8221	ChargeableEntryLevel is required when InOutCountyIndicator is populated with N and ChargeableContainerLevel and ChargeableContainerType and Containers in the PeriodicalLineItemData block are populated. (User Postage Statement ID: %%1).	Postage Statement Messages
8222	Containers in the PeriodicalLineItemData block must contain less than or equal to 4 decimal characters. (User Postage Statement ID: %%1).	Postage Statement Messages
8223	Containers in the PeriodicalLineItemData block is required when is populated with N and ChargeableContainerLevel, ChargeableEntryLevel and ChargeableContainerType in the PeriodicalLineItemData block are populated. (User Postage Statement ID: %%1).	Postage Statement Messages

Copyright © 2011 USPS®. All Rights Reserved.

Error Code	Error Message	Messages
8224	MachinableFlag in the PeriodicalLineItemData block is required when the RateCategory in the PeriodicalLineItemData block is populated and the processing category is flats. (User Postage Statement ID: %%1).	Postage Statement Messages
8225	PostagePaymentMethod in the CreatePeriodicalStatementData block can only be populated with P. (User Postage Statement ID: %%1).	Postage Statement Messages
8226	ProcessingCategory in the CreatePeriodicalStatementData block can only be populated with LT, FL, IR, MP, or NP. (User Postage Statement ID: %%1).	Postage Statement Messages
8227	RateType in the CreatePeriodicalStatementData block can only be populated with R, N, S, C, W, or Y. (User Postage Statement ID: %%1).	Postage Statement Messages
8228	SingleRideAlongWeight is required when the PeriodicalPrice in the PeriodicalLineItemData block is populated with 9. (User Postage Statement ID: %%1).	Postage Statement Messages
8229	SingleRideAlongWeight must contain less than or equal to 4 decimal characters. (User Postage Statement ID: %%1).	Postage Statement Messages
8234	CombinedMailingID in the CreatePeriodicalStatementData block must be populated with the same value as the CombinedMailingID of the BeginCombinedMailingRequest message for a specified MailingGroupID and CustomerGroupID. (User Postage Statement ID: %%1).	Postage Statement Messages
8235	AdPercent in the DocumentVersionData block must contain less than or equal to 2 decimal characters. (User Postage Statement ID: %%1).	Postage Statement Messages
8236	AdPercent in the DocumentVersionData block must be populated with the same value as the AdvertisingPercentage in the CreatePeriodicalStatementData block. (User Postage Statement ID: %%1).	Postage Statement Messages
8237	RateAffixed in the DocumentVersionData block must contain less than or equal to 3 decimal characters. (User Postage Statement ID: %%1).	Postage Statement Messages
8238	RateAffixed in the DocumentVersionData block is not required when the PermitType in the PermitPublicationData block within the CreatePeriodicalStatementData block is populated with PI. (User Postage Statement ID: %%1).	Postage Statement Messages
8239	PermitType in the PermitPublicationData block in the PublisherData block in the CreatePeriodicalStatementData block must be populated with PP. (User Postage Statement ID: %%1).	Postage Statement Messages
8240	PendingPostageAmount in the CreatePeriodicalStatementData block is required when the PermitType in the PermitPublicationData block within the CreatePeriodicalStatementData block is populated with PP. (User Postage Statement ID: %%1).	Postage Statement Messages
8241	PendingPostageAmount in the CreatePeriodicalStatementData block must contain exactly 2 decimal characters. (User Postage Statement ID: %%1).	Postage Statement Messages

Copyright © 2011 USPS®. All Rights Reserved.

Error Code	Error Message	Messages
8242	MailingGroupID and CustomerGroupID in the PeriodicalStatementCreateRequest message must be the same values as the MailingGroupID and CustomerGroupID of an accepted OpenMailingGroupRequest message. (User Postage Statement ID: %%1).	Postage Statement Messages
8243	RateCategory in the PeriodicalLineItemData block and ChargeableContainerLevel in the PeriodicalLineItemData block cannot be populated in the same line. (User Postage Statement ID: %%1).	Postage Statement Messages
8244	RateCategory in the PeriodicalLineItemData block and Zone in the PeriodicalLineItemData block cannot be populated in the same line. (User Postage Statement ID: %%1).	Postage Statement Messages
8245	Containers in the PeriodicalLineItemData block and Bundles in the PeriodicalLineItemData block cannot be populated in the same line. (User Postage Statement ID: %%1).	Postage Statement Messages
8246	RateCategory in the PeriodicalLineItemData block and PeriodicalPrice in the PeriodicalLineItemData block cannot be populated in the same line. (User Postage Statement ID: %%1).	Postage Statement Messages
8247	ChargeableContainerLevel in the PeriodicalLineItemData block and PeriodicalPrice in the PeriodicalLineItemData block cannot be populated in the same line. (User Postage Statement ID: %%1).	Postage Statement Messages
8248	The Pending Periodical PermitZIP+4 or Periodical Publication number must map to the same finance number as the OpenMailingGroupRequest for a specified MailingGroupID and CustomerGroupID and must be active. (User Postage Statement ID: %%1).	Postage Statement Messages
8250	PeriodicalStatementCreateRequest must be accepted prior to submitting the PeriodicalStatementQueryRequest message for the specified MailingGroupID, CustomerGroupID, and StatementID.	Postage Statement Messages
8252	Postage StatementID in the PeriodicalStatementQueryRequest message must match the StatementID provided in the PeriodicalStatementCreateResponse message for the specified MailingGroupID and CustomerGroupID.	Postage Statement Messages
8255	AdvertisingPercentage in the PeriodicalStatement block must contain less than or equal to 2 decimal characters. (User Postage Statement ID: %%1).	Postage Statement Messages
8258	CarrierRouteAddressMatchingDate in the PeriodicalStatement block is required when the RateCategory in the LineItemSummaryData block is populated with A, B, or D. (User Postage Statement ID: %%1).	Postage Statement Messages
8259	CarrierRouteAddressMatchingDate in the PeriodicalStatement block is required when the RateCategory in the PeriodicalLineItemData block is populated with A, B, or D. (User Postage Statement ID: %%1).	Postage Statement Messages
8260	CarrierRouteSequencingDate in the PeriodicalStatement block is required when the RateCategory in the LineItemSummaryData block is populated with A, AF, B, BF, D, or DF. (User Postage Statement ID: %%1).	Postage Statement Messages
8261	CarrierRouteSequencingDate in the PeriodicalStatement block is required when the RateCategory in the PeriodicalLineItemData block is populated with A, B, or D. (User Postage Statement ID: %%1).	Postage Statement Messages

Copyright © 2011 USPS®. All Rights Reserved.

Error Code	Error Message	Messages
8262	CopyWeight in the PeriodicalStatement block must contain less than or equal to 4 decimal characters. (User Postage Statement ID: %%1).	Postage Statement Messages
8263	FormType in the PeriodicalStatement block must be populated with PE. (User Postage Statement ID: %%1).	Postage Statement Messages
8264	PostagePaymentMethod in the PeriodicalStatement block must be populated with P. (User Postage Statement ID: %%1).	Postage Statement Messages
8265	ProcessingCategory in the PeriodicalStatement block must be populated with LT, FL, IR, MP, or NP. (User Postage Statement ID: %%1).	Postage Statement Messages
8267	SingleRideAlongWeight in the PeriodicalStatement block is required when the PeriodicalPrice in the PeriodicalLineItemData block is populated with 9. (User Postage Statement ID: %%1).	Postage Statement Messages
8268	SingleRideAlongWeight in the PeriodicalStatement block must contains less than or equal to 4 decimal characters. (User Postage Statement ID: %%1).	Postage Statement Messages
8272	AgencyCostCode in the PeriodicalStatement block must contain 6 characters when mapped to USPS. (User Postage Statement ID: %%1).	Postage Statement Messages
8273	AdPercent in the DocumentVersionData block must be populated with the same value as the AdvertisingPercentage in the PeriodicalStatement block. (User Postage Statement ID: %%1).	Postage Statement Messages
8274	RateAffixed in the DocumentVersionData block is not required when the PermitType in the PermitPublicationData block within the PeriodicalStatement block is populated with PI. (User Postage Statement ID: %%1).	Postage Statement Messages
8275	PermitType in the PermitPublicationData block within the ConsolidatedPeriodicalStatementCreateRequest message must be populated with PP.	Postage Statement Messages
8276	PendingPostageAmount in the PeriodicalStatement block is required when the PermitType in the PermitPublicationData block within the PeriodicalStatement block is populated with PP. (User Postage Statement ID: %%1).	Postage Statement Messages
8277	PendingPostageAmount in the PeriodicalStatement block must contain exactly 2 decimal characters. (User Postage Statement ID: %%1).	Postage Statement Messages
8279	Bundles in the PeriodicalLineItemData block of the CreateConsolidatedPeriodicalStatementData block must contain less than or equal to 4 decimal characters. (User Postage Statement ID: %%1).	Postage Statement Messages
8281	MailingGroupID and CustomerGroupID in the ConsolidatedPeriodicalStatementCreateRequest message must be the same values as the MailingGroupID and CustomerGroupID of an accepted OpenMailingGroupRequest message. (User Postage Statement ID: %%1).	Postage Statement Messages
8282	QualificationReportCreateRequest message must be accepted before submitting the ContainerBundleReportCreateRequest message for the specified MailingGroupID and CustomerGroupID.	ContainerBundleQueryResponse

Copyright © 2011 USPS®. All Rights Reserved.

Error Code	Error Message	Messages
8283	Either the SackTrayContainerVersionRecord block, the PalletContainerVersionRecord block, or the BundleVersionRecord block is required when the ContainerBundleVersionRecords block is sent.	ContainerBundleQueryResponse
8286	Either the SackTrayContainerRecord block, the PalletContainerRecord block, or the BundleRecord block is required when the ContainerBundleSummaryRecords block is sent.	ContainerBundleQueryResponse
8288	ContainerBundleReportCreateRequest message can only be provided when the FormType in the QualificationReportCreateRequest message is PE.	ContainerBundleQueryResponse
8289	Containers field in the SackTrayContainerVersionRecord block in the ContainerBundleVersionRecords block must contain less than or equal to 4 decimal characters.	ContainerBundleQueryResponse
8290	Containers field in the PalletContainerVersionRecord block in the ContainerBundleVersionRecords block must contain less than or equal to 4 decimal characters.	ContainerBundleQueryResponse
8291	Bundles field in the BundleVersionRecord block in the ContainerBundleVersionRecords block must contain less than or equal to 4 decimal characters.	ContainerBundleQueryResponse
8292	Containers field in the SackTrayContainerRecord block in the ContainerBundleSummaryRecords block must contain less than or equal to 4 decimal characters.	ContainerBundleQueryResponse
8293	Containers field in the PalletContainerRecord block in the ContainerBundleSummaryRecords block must contain less than or equal to 4 decimal characters.	ContainerBundleQueryResponse
8294	Bundles field in the BundleRecord block in the ContainerBundleSummaryRecords block must contain less than or equal to 4 decimal characters.	ContainerBundleQueryResponse
8295	The specified combination of MailingGroupID and CustomerGroupID in the ContainerBundleReportHeaderInfo block must match the values as that of the open mailing group.	ContainerBundleQueryResponse
8296	ContainerBundleReportCreateRequest message must be accepted before submitting the ContainerBundleReportQueryRequest message for the specified MailingGroupID and CustomerGroupID.	ContainerBundleReportQueryResponse
8297	CustomerGroupID and MailingGroupID must exist for an accepted ContainerBundleReportCreateRequest message.	ContainerBundleReportQueryResponse
8298	ContainerBundleReportCreateRequest message must be accepted before submitting the ContainerBundleCancelRequest message for the specified MailingGroupID and CustomerGroupID.	ContainerBundleReportCancelResponse
8299	The specified combination of CustomerGroupID and MailingGroupID must be populated with the same combination of CustomerGroupID and MailingGroupID as an accepted ContainerBundleReportCreateRequest message.	ContainerBundleReportCancelResponse
8300	QualificationReportCreateRequest message must be accepted before submitting the MailPieceCreateRequest message to create a mail piece for the specified MailingGroupID and CustomerGroupID. (PieceID not found: %%1)	MailPieceCreateResponse
8301	QualificationReportCreateRequest message must be accepted before submitting the MailPieceCreateRequest message to create a piece range for the specified MailingGroupID and CustomerGroupID. (PieceRangeID not found: %%1)	MailPieceCreateResponse

Copyright © 2011 USPS®. All Rights Reserved.

Error Code	Error Message	Messages
8302	LOTSequenceDirectionCode in the MailPieceBlock must be populated when combined with the LOTSequenceNumber is populated and when Carrier Route LOT is used. (Piece ID: %%1).	Multiple
8304	LOTSequenceNumber in the MailPieceBlock must be populated when the LOTSequenceDirection is populated.	Multiple
8306	WalkSequenceNumber in the MailPieceBlock must be populated when Carrier Route LOT is used and the LOTSequenceDirection is not populated.	Multiple
8307	DeliveryPointZIP in the MailPieceBlock block must contain 0, 5, 9, or 11 characters.	MailPieceCreateResponse
8309	DeliveryPointZIP in the MailPieceBlock block must be populated when the IMB block is not used and combined with the PlanetCode field. (Piece ID: %%1)	MailPieceCreateResponse
8310	MailerID6 in the IMbarcodeUpperSerialization block in the MailXMLPieceRangeBlock must match the MailerID6 in the IMbarcodeLowerSerialization block in the MailXMLPieceRangeBlock.(Piece Range ID is %%1)	Multiple
8311	MailerID9 in the IMbarcodeUpperSerialization block in the MailXMLPieceRangeBlock must match the MailerID9 in the IMbarcodeLowerSerialization block in the MailXMLPieceRangeBlock.(Piece Range ID is %%1)	Multiple
8312	SerialNumber6 in the IMbarcodeUpperSerialization block must be populated with a value greater than or equal to the SerialNumber6 in the IMbarcodeLowerSerialization block. (Piece Range ID is %%1)	Multiple
8313	SerialNumber9 in the IMbarcodeUpperSerialization block must be populated with a value greater than or equal to the SerialNumber9 in the IMbarcodeLowerSerialization block. (Piece Range ID is %%1)	Multiple
8314	MailerID6 fields must be blank when the ServiceLevelIndicator is populated with P. (piece_range_id: %%1)	MailPieceCreateResponse
8315	MailerID9 must be blank when the ServiceLevelIndicator is populated with P. (Found: %%1)	MailPieceCreateResponse
8316	SerialNumber6 must be blank when the ServiceLevelIndicator is populated with P. (Found: %%1)	MailPieceCreateResponse
8317	SerialNumber9 must be blank when the ServiceLevelIndicator is populated with P. (Found: %%1)	MailPieceCreateResponse
8318	The specified combination of MailingGroupID and CustomerGroupID in the MailPieceCreateRequest message must match the values of the accepted OpenMailingGroupRequest message.	MailPieceCreateResponse
8319	MailPieceCreateRequest must be accepted to create a mail piece before submitting a MailPieceUpdateRequest message for the specified MailingGroupID and CustomerGroupID.	MailPieceUpdateResponse
8320	MailPieceCreateRequest must be accepted to create a piece range before submitting a MailPieceUpdateRequest message for the specified MailingGroupID and CustomerGroupID.	MailPieceUpdateResponse
8325	MailPieceCreateRequest must be accepted to create a mail piece before submitting a MailPieceCancelRequest message for the specified MailingGroupID and CustomerGroupID.	MailPieceCancelResponse

Copyright © 2011 USPS®. All Rights Reserved.

Error Code	Error Message	Messages
8326	MailPieceCreateRequest must be accepted to create a piece range before submitting a MailPieceCancelRequest message for the specified MailingGroupID and CustomerGroupID.	MailPieceCancelResponse
8329	MailPieceBlock in the MailPieceCancelRequest message must be populated with the same values as the fields within the MailPieceBlock of the MailPieceCreateRequest message for the specified combination of MailingGroupID and CustomerGroupID.	MailPieceCancelResponse
8330	MailXMLPieceRangeBlock in the MailPieceCancelRequest message must be populated with the same values as the fields within the MailXMLPieceRangeBlock of the MailPieceCreateRequest message for the specified combination of MailingGroupID and CustomerGroupID.	MailPieceCancelResponse
8332	PostageStatementCreateRequest or PeriodicalStatementCreateRequest message must be accepted before submitting the PostageAdjustmentCreateRequest for the specified MailingGroupID and CustomerGroupID.	Postage Statement Messages
8333	StatementID in the PostageAdjustment block must be populated with the same value as the StatementID in the PostageStatementCreateResponse or PeriodicalStatementCreateResponse for a specified MailingGroupID and CustomerGroupID. (Statment ID: %%1)	Postage Statement Messages
8334	AdjustmentAmount in the PostageAdjustment block must contain less than or equal to 2 decimal characters. (Statment ID: %%1)	Postage Statement Messages
8335	AdjustmentAmount field in the PostageAdjustment block must be less than the PostageAmount field in the PostageStatementCreateRequest message or PeriodicalStatementCreateRequest message. (Statment ID: %%1)	Postage Statement Messages
8336	TotalPiecesAffected field within the PostageAdjustment block must be less than the TotalPieces field in the PostageStatementCreateRequest message or PeriodicalStatementCreateRequest message. (Statment ID: %%1)	Postage Statement Messages
8337	UserPostageStatementID in the PostageAdjustment block must be populated with the same value as the UserPostageStatementID in the PostageStatementCreateResponse message or the PeriodicalStatementCreateResponse message. (Statment ID: %%1)	Postage Statement Messages
8338	AdjustmentDate in the PostageAdjustment block must be populated with a date later than the latest mailing date for the specified StatementID, MailingGroupID and CustomerGroupID. (Statment ID: %%1)	Postage Statement Messages
8339	PostageAdjustment block AdjustmentAmount must be less than the TotalPostage generated by the system on the PostageStatementCreateRequest or PeriodicalStatementCreateRequest for a specified MailingGroupID and CustomerGroupID. (Statment ID: %%1)	Postage Statement Messages
8342	Mail.dat Job ID: %%1 and User License Code: %%2 not found. Values must be populated with the same value in the .hdr file from the original Mail.dat submission.	ContainerUpdateResponse
8343	ContainerID %%1 must be populated with the same value as the Container ID in the .csm file from the original Mail.dat job submission for the specified CRID.	ContainerUpdateResponse

Copyright © 2011 USPS®. All Rights Reserved.

Error Code	Error Message	Messages
8344	UniqueContainerBarcode %%1 must be populated with same value as the Label: IM Container Or IM Tray Barcode field in the .csm file from the original Mail.dat job submission for the specified CRID.	ContainerUpdateResponse
8345	EntryPointEDPostalCode must contain exactly 5 characters (Container ID: %%1).	ContainerUpdateResponse
8346	EntryPointEDPostalCode is required when the EntryPointEDFacilityType is populated. (Container ID: %%1)	ContainerUpdateResponse
8347	EntryPointEDFacilityType is required when the EntryPointEDPostalCode is populated. (Container ID: %%1)	ContainerUpdateResponse
8348	EntryPointADLocaleKey must contain exactly 6 characters. (Container ID: %%1)	ContainerUpdateResponse
8349	EntryPointADLocaleKey is required when the EntryPointADPostalCode is populated. (Container ID: %%1)	ContainerUpdateResponse
8350	EntryPointADPostalCode is required when the EntryPointADLocaleKey is populated. (Container ID: %%1)	ContainerUpdateResponse
8351	ParentContainerReferenceID is required when a Parent Container exists. (Container ID: %%1)	ContainerUpdateResponse
8352	ContainerStatus previously populated with C can only be updated to R or D for the specified CRID. (Container ID: %%1)	ContainerUpdateResponse
8353	ContainerStatus previously populated with D cannot be updated for the specified CRID. (Container ID: %%1)	ContainerUpdateResponse
8354	ContainerStatus previously populated with R can only be updated to D, X, T, or C for the specified CRID. (Container ID: %%1)	ContainerUpdateResponse
8355	ContainerStatus previously populated with T can only be updated to D, X, or C for the specified CRID. (Container ID: %%1)	ContainerUpdateResponse
8356	ContainerStatus previously populated with X can only be updated to T for the specified CRID. (Container ID: %%1)	ContainerUpdateResponse
8358	IMBarcode field must be populated with either 21 or 24 characters. (Container ID: %%1)	ContainerUpdateResponse
8360	ContainerStatus cannot be updated to R when the Container Status of the original Mail.dat submission is populated with R. (Container ID: %%1)	ContainerUpdateResponse
8361	StopDesignator field cannot be updated when updating an original Mail.XML job. (Container ID: %%1)	ContainerUpdateResponse
8362	The StopDesignator field can only be updated when the ContainerStatus in the SummaryRecordUpdate block of the ContainerUpdateRequest message is populated with T. (Container ID: %%1, ContainerStatus: %%2)	ContainerUpdateResponse
8363	The TruckDispatchNumber field can only be updated when the ContainerStatus in the SummaryRecordUpdate block of the ContainerUpdateRequest message is populated with T. (Container ID: %%1, ContainerStatus: %%2)	ContainerUpdateResponse
8378	ServiceLevelIndicator in at least one ContainerDetailData block must be populated with F when the FullServiceParticipationIndicator in the MailingGroupData block of the OpenMailingGroupRequest message is populated with M.	QualificationReportCreateResponse, QualificationReportDetailCreateResponse (10.0)
8379	ServiceLevelIndicator in the ContainerDetailData block must be populated with F when the FullServiceParticipationIndicator in the MailingGroupData block of the OpenMailingGroupRequest message is populated with F.	QualificationReportCreateResponse, QualificationReportDetailCreateResponse (10.0)

Copyright © 2011 USPS®. All Rights Reserved.

Error Code	Error Message	Messages
8380	At least one QualificationReportCreateRequest ContainerInfoData block must have a ContainerType of L or M if the LogicalPhysicalIndicator in the OpenMailingGroupRequest is L, MailXMLPresentationCategory is P, FullServiceParticipationIndicator is F or M.	QualificationReportCreateResponse
8381	ContainerType must be populated with S, 1, 2, 3, 4, 5, E, F, O, T, B, U, Z, P, H, A, G, D, R, or C if the LogicalPhysicalContainerIndicator in the OpenMailingGroupRequest message is populated with P and FullServiceParticipationIndicator is F or M.	QualificationReportCreateResponse, QualificationReportDetailCreateResponse (10.0)
8382	FormType in the QualifcationReport block must be populated with FC, SM, BP, or PE when the FullServiceParticipationIndicator in the MailingGroupData block of the OpenMailingGroupRequest message is populated with F or M.	QualificationReportCreateResponse, QualificationReportSummaryCreateResponse (10.0)
8383	ContainerInfoData block ProcessingCategory must be LT, FL, or CD when the QualificationReport block FormType is FC and FullServiceParticipationIndicator in the MailingGroupData block is F or M for the specified MailingGroupID and CustomerGroupID.	QualificationReportCreateResponse, QualificationReportDetailCreateResponse (10.0)
8384	ContainerInfoData block ProcessingCategory must be populated with LT or FL when the QualificationReport block FormType is SM and FullServiceParticipationIndicator in the MailingGroupData block is F or M for a specified MailingGroupID and CustomerGroupID.	QualificationReportCreateResponse, QualificationReportDetailCreateResponse (10.0)
8385	ContainerInfoData block ProcessingCategory must be populated with LT or FL when the QualificationReport block FormType is PE and FullServiceParticipationIndicator in the MailingGroupData block is F or M for a specified MailingGroupID and CustomerGroupID.	QualificationReportCreateResponse, QualificationReportDetailCreateResponse (10.0)
8386	ContainerInfoData block ProcessingCategory must be populated with FL when the QualificationReport block FormType is BP and FullServiceParticipationIndicator in the MailingGroupData block is F or M for the specified MailingGroupID and CustomerGroupID.	QualificationReportCreateResponse, QualificationReportDetailCreateResponse (10.0)
8387	CSAID is required when mail is DMU verified, mail is origin-entered, and FullServiceParticipationIndicator in the MailingGroupData block is F or M.	QualificationReportCreateResponse, QualificationReportDetailCreateResponse (10.0)
8388	CSAID is required when the mailer is a large volume mailer, mail is entered at a BMEU at an agreed upon time prior to CET, and FullServiceParticipationIndicator in the MailingGroupData block is F or M. (Container ID %%1)	QualificationReportCreateResponse, QualificationReportDetailCreateResponse (10.0)
8390	CSAID is required when the EntryPointFacilityType in the ContainerInfoData block is populated with O and the ConsigneeApptID in the ContainerInfoData block is populated and FullServiceParticipationIndicator in the MailingGroupData block is F or M.	QualificationReportCreateResponse, QualificationReportDetailCreateResponse (10.0)

Copyright © 2011 USPS®. All Rights Reserved.

Error Code	Error Message	Messages
8392	ScheduledInductionDateTime is required when the ConsigneeApptID in the ContainerInfoData block is populated and FullServiceParticipationIndicator in the MailingGroupData block is F or M. (Container ID: %%1).	QualificationReportCreateResponse, QualificationReportDetailCreateResponse (10.0)
~~8394~~	~~ScheduledInductionDateTime is required when the CSAID in the ContainerInfoData block is populated and the USPSPickup field in the ContainerInfoData block is populated with N and FullServiceParticipationIndicator in the MailingGroupData block is F or M.~~	~~QualificationReportCreateResponse~~
8396	ScheduledShipDateTime is required when the EntryPointFacilityType is O, USPSPickup is populated with Y, and FullServiceParticipationIndicator in the MailingGroupData block is F or M.	QualificationReportCreateResponse, QualificationReportDetailCreateResponse (10.0)
8399	ContainerDetailData block TotalPieces must be 0 when the ContainerDetailData block is provided, ContainerInfoData block SiblingContainerID is populated, and MailingGroupData block FullServiceParticipationIndicator is F or M. (Container ID: %%1)	QualificationReportCreateResponse, QualificationReportDetailCreateResponse (10.0)
8400	ContainerBarcode must be populated with 21 characters when the ContainerType in the ContainerInfoData block is populated with B, U, P, H, A, G, D, R, or C and FullServiceParticipationIndicator in the MailingGroupData block is F or M.	QualificationReportCreateResponse, QualificationReportDetailCreateResponse (10.0)
8401	ContainerBarcode must be populated with 24 characters when the ContainerType in the ContainerInfoData block is populated with S, 1, 2, 3, 4, 5, E, F, O, or T and FullServiceParticipationIndicator in the MailingGroupData block is F or M.	QualificationReportCreateResponse, QualificationReportDetailCreateResponse (10.0)
8402	UniqueContainerBarcode is required when the SiblingContainerCreateRequest ContainerType is B, U, P, H, A, G, D, R, C, S, 1, 2, 3, 4, 5, E, F, O, or T and the Full-Service Participation Indicator in the .seg file is F or M. (ContainerID: %%1)	SiblingContainerCreateResponse
8405	BarcodeID in the IMB block is required when the MailPieceBlock is provided.	MailPieceCreateResponse
8406	ServiceTypeCode field is required when the MailPieceBlock is provided and the MailClass in the IMB block is not populated.	MailPieceCreateResponse
8407	MailClass field is required when the MailPieceBlock is provided and the ServiceTypeCode in the IMB block is not populated.	MailPieceCreateResponse
8412	DeliveryPointZIP in the IMB block is required when the IMB block is provided. (Piece_id: %%1)	MailPieceCreateResponse
8413	At least one of CRID, MailerID6, MailerID9, PermitNumber or PublicationNumber in the QualificationReportPreparer block must be populated when the FullServiceParticipationIndicator in the OpenMailingCreateRequest is F or M	QualificationReportCreateResponse, QualificationReportSummaryCreateResponse (10.0)
8414	At least one of CRID, MailOwnerMID6, MailOwnerMID9, PermitNumber, or PublicationNumber in the MailOwner block of the MailPieceCreateRequest message must be populated when the MailPieceBlock is populated and the MailPieceBlock ServiceLevelIndicator is F.	MailPieceCreateResponse

Copyright © 2011 USPS®. All Rights Reserved.

Error Code	Error Message	Messages
8416	At least one of CRID, MailerID6, or MailerID9 in the MailOwner block of the MailPieceCreateRequest message must be populated when the MailXMLRangeBlock is populated	MailPieceCreateResponse
8417	MailerID9 must be populated with the same value as the MailerID9 in the IMbarcodeLowerSerialization block when submitted instead of the MailerID6. (ContainerID: %%1)	MailPieceCreateResponse
8418	MailerID6 must be populated with the same value as the MailerID6 in the IMbarcodeLowerSerialization block when submitted instead of the MailerID9. (ContainerID: %%1)	MailPieceCreateResponse
8419	For all Full-Service MailXMLPieceRangeBlocks, the sum of the IMbarcodeUpperSerialization minus the IMbarcodeLowerSerialization plus one must be between the smaller of the sum of Pieces or Copies and 20% more than the larger of the sum of Pieces or Copies.	MailPieceCreateResponse
8420	IMbarcodeUpperSerialization subtracted by the IMbarcodeLowerSerialization must equal the piece count and copy count when the PieceRange block is provided.	MailPieceUpdateResponse
8421	The number of MailPieceBlocks associated to a ContainerID must equal the sum or between TotalPieces and TotalCopies in the ContainerDetailData block in the Qual Report for the ContainerID, MailingGroupID, and CustomerGroupID. (Container ID: %%1)	MailPiececreateResponse
8422	The number of pieces in PieceRangeBlocks associated to a ContainerID cannot exceed the value in the ContainerDetailData block TotalPieces when the PieceRange Block is populated for a specified MailingGroupID and CustomerGroupID. (Container ID: %%1)	MailPieceCreateResponse
8423	PostageStatementLineItemData block is required when the FullServiceParticipationIndicator in the MailingGroupData block is populated with F or M.	Postage Statement Messages
~~8425~~	~~When the FullServiceParticipationIndicator in the MailingGroupData block is populated with F or M, the MailPieceCreateRequest message must be accepted before submitting the PostageStatementCreateRequest message.~~	~~MailPieceCreateResponse~~
8427	The pieces associated to a ContainerID in the Postage-, Periodical-, or ConsolidatedPeriodicalStatementCreateRequest message cannot exceed the sum of TotalPieces for that ContainerID in the Qualification Report (ContainerID %%1).	Postage Statement Messages
8428	MailXMLPieceBlock ServiceLevelIndicator must be F when the ContainerDetailData block ServiceLevelIndicator fields are all populated with F for the specified ContainerID within a specified MailingGroupID and CustomerGroupID. (ContainerID: %%1)	Multiple Messages
8429	MailXMLPieceRangeBlock ServiceLevelIndicator must be F when the ContainerDetailData block ServiceLevelIndicator fields are all populated with F for the specified ContainerID within a specified MailingGroupID and CustomerGroupID. (ContainerID: %%1)	MailPieceCreateResponse
8432	QualificationReportCreateRequest message must be accepted before submitting the PostageStatementCreateRequest message as for the specified MailingGroupID and CustomerGroupID when the FullServiceParticipationIndicator is F.	Postage Statement Messages
8434	ServiceLevelIndicator in the PieceRangeBlock must be populated with F, B, P, or O when the FullServiceParticipationIndicator field within the MailingGroupData block is M.	MailPieceCreateResponse

Copyright © 2011 USPS®. All Rights Reserved.

Error Code	Error Message	Messages
8435	At least one PieceRangeBlock must have the ServiceLevelIndicator field populated with F when the FullServiceParticipationIndicator field within the MailingGroupData block is populated with M.	MailPieceCreateResponse
8436	ServiceLevelIndicator in the ContainerDetailData block must be populated with F, B, P, or O when the FullServiceParticipationIndicator field within the MailingGroupData block is M.	QualificationReportCreateResponse, QualificationReportDetailCreateResponse (10.0)
8438	ContainerType must be populated with L when the PresentationCategory is populated with M and LogicalPhysicalContainerIndicator is populated with L in the MailingGroupData block.	QualificationReportCreateResponse, QualificationReportDetailCreateResponse (10.0)
8439	ContainerType must be populated with E, F, O, M, P, T, H, A, G, D, R or C in the ContainerInfoData block when another ContainerType field in the ContainerInfoData block is populated with L for the specified MailingGroupID and CustomerGroupID.	QualificationReportCreateResponse, QualificationReportDetailCreateResponse (10.0)
8440	At least one ContainerDetailData block must exist for each ContainerInfoData block in the Qual Reportwhen the ContainerType is L and the OpenMailingGroupRequest MailXMLPresentationCategory is M for the specified MailingGroupID and CustomerGroupID.	QualificationReportCreateResponse, QualificationReportDetailCreateResponse (10.0)
8441	CustomerQualificationReportID field in the QualificationReport block is required when the MailXMLPresentationCategory field within the MailingGroupData block of the OpenMailingGroupRequest message is M.	QualificationReportCreateResponse
8443	CustomerQualificationReportID field in the QualificationReport block is required for a MLOCR One-Pass mailing.	QualificationReportCreateResponse
8444	The OnePassPlannedOrActualFlag in the QualificationReportCreateRequest message is required when the OnePassIndicator field in the OpenMailingGroupRequest message is Yes for the specified MailingGroupID and CustomerGroupID.	QualificationReportCreateResponse
8445	PostageStatementLineItemData Containers for an MLOCR mailing must be in the QualificationReportCreateRequest message when the OnePassPlannedOrActualFlag is A for the specified MailingGroupID and CustomerGroupID. (ContainerID %%1 was not found)	Postage Statement Messages
8446	Mailing must be a One Pass MLOCR when OnePassPlannedOrActualFlag in the QualificationReportCreateRequest message is populated with A in the second submission for the specified MailingGroupID and CustomerGroupID.	QualificationReportCreateResponse
8449	FormType in the QualificationReport bock must be FC for First-Class or SM for Standard Mail.	QualificationReportCreateResponse
8451	No more than one LineItemSummaryData block in the CreatePostageStatement block can have the RateCategory populated with S for the specified MailingGroupID and CustomerGroupID.	Postage Statement Messages
8452	PostageAdjustmentCreateRequest message cannot be submitted for MLOCR mailings.	Postage Statement Messages

Copyright © 2011 USPS®. All Rights Reserved.

Error Code	Error Message	Messages
8453	ProcessingCategory must be LT, FL, or CD when the FormType in the QualificationReport block is FC and MailXMLPresentationCategory in the MailingGroupData block is M for the specified MailingGroupID and CustomerGroupID.	QualificationReportCreateResponse
8454	DocumentVersionData or -DataWithPermit PieceWeight cannot exceed 13oz when the QualificationReportCreateRequest FormType is FC and the ProcessingCategory is FL.	QualificationReportCreateResponse
8456	PostagePaymentMethod in the PostageStatementCreateRequest must be P or M when the FormType is FC and ProcessingCategory is FL for the specified MailingGroupID and CustomerGroupID.	Postage Statement Messages
8460	ProcessingCategory in the ContainerInfoData block must be populated with LT when the FormType QualificationReport block is populated with SM for an MLOCR mailing.	QualificationReportCreateResponse
8461	PieceWeight in the DocumentVersionData block or the DocumentVersionDataWithPermit block must be less than or equal to 3.3 ounces when the ProcessingCategory is LT and FormType is SM in the QualificationReportCreateRequest message.	QualificationReportCreateResponse
8467	PostageAffixedAmount must be populated with a value greater than 0 when the PostagePaymentMethod in the CreatePostageStatement block is populated with M or S.	Postage Statement Messages
8469	MeteredAffixedMethod is required when the PostagePaymentMethod in the CreatePostageStatement block is populated with M.	Postage Statement Messages
8470	PermitHolderData block in the CreatePostageStatement block is required when the PostagePaymentMethod in the CreatePostageStatement block is populated with M or S.	Postage Statement Messages
8475	StatementID in the PostageAdjustment block must be populated with a value that references a postage statement where the Stage is not populated with FIN. (Statment ID: %%1)	Postage Statement Messages
8480	StatementID in the PostageAdjustment block must be populated with a value that references a postage statement that has not already been adjusted. (Statment ID: %%1)	Postage Statement Messages
8481	A PeriodicalStatementCreateRequest must be accepted before sumbitting a PostageStatementCreateRequest message with the EnclosedBy field set to PE for the same MailingGroupID and CustomerGroupID.	Postage Statement Messages
8482	OpenMailingGroupRequest message must be accepted before submitting the PeriodicalStatementCreateRequest for the specified MailingGroupID and CustomerGroupID.	Periodical Postage Statement Messages
8485	ProcessingCategory must be populated with FL, NP, MP, or IR when the FormType is BP.	Multiple
8486	Zone must be populated with N, 1, 3, 4, 5, 6, 7, 8, DDU or SCF when FormType is BP and Processing Category is FL, MP, IR, or NP.	Multiple
8490	EntryDiscount must be populated with N, B, S or D when FormType is BP.	Multiple
8491	RateCategory must be populated with D, N, or S when the FormType is BP.	Postage Statement Messages
8492	SurchargeType must be populated with N when the FormType is BP.	Postage Statement Messages

Copyright © 2011 USPS®. All Rights Reserved.

Error Code	Error Message	Messages
8493	WeightBreakType must be populated with N when the FormType is BP.	Postage Statement Messages
8494	BarcodeRate must be populated with Y or N when the FormType is BP.	Postage Statement Messages
8497	PostagePaymentMethod must be populated with P when the FormType is BP.	Postage Statement Messages
8498	RateType must be populated with B when FormType is BP.	Postage Statement Messages
8500	SinglePieceWeight must be populated with a value less than or equal to 15 pounds when the FormType is BP.	Postage Statement Messages
8501	TotalPieces and TotalCopies must be populated with the same values when FormType is BP.	Multiple
8502	ServiceCode must be populated with COD, COM, DC, IM, PAL, RD, RR, RRE, RRM, SC, or SH when FormType is BP.	Postage Statement Messages
8503	ProcessingCategory must be populated with LT, FL, CD, or PF when FormType is FC.	Multiple
8504	Zone must be populated with N when FormType is FC and ProcessingCategory is LT, FL, CD, or PF.	Multiple
8505	RateType must be populated with R or M when FormType is FC and ProcessingCategory is LT.	Postage Statement Messages
8506	RateCategory must be populated with E, H, L1, L2, N, PR, or S when FormType is FC and ProcessingCategory is LT.	Postage Statement Messages
8507	RateType must be populated with R or M when FormType is FC and ProcessingCategory is FL.	Postage Statement Messages
8508	RateCategory must be populated with E, H, L3, L4, N, PR, or S when FormType is FC and ProcessingCategory is FL.	Postage Statement Messages
8509	RateType must be populated with R or M when FormType is FC and ProcessingCategory is CD.	Postage Statement Messages
8510	RateCategory must be populated with E, H, L1, L2, N, or S when FormType is FC and ProcessingCategory is CD.	Postage Statement Messages
8511	RateType must be populated with R when FormType is FC and ProcessingCategory is PF.	Postage Statement Messages
8512	RateCategory must be populated with E, G, H, K, L3, L4, L5, L6, S, or N when FormType is FC and ProcessingCategory is PF.	Postage Statement Messages
8513	EntryDiscount must be populated with N when FormType is FC.	Postage Statement Messages

Copyright © 2011 USPS®. All Rights Reserved.

Error Code	Error Message	Messages
8515	SurchargeType must be populated with A, E, N, R or L when FormType is FC.	Postage Statement Messages
8516	WeightBreakType must be populated with A, B, or N when provided and when the FormType is FC.	Postage Statement Messages
8517	SinglePieceWeight must be populated with a value greater than 0.0625 pounds when FormType is FC and SurchargeType is E and WeightBreakType is A.	Postage Statement Messages
8518	SinglePieceWeight must be populated with a value less than or equal to 0.0625 pounds when FormType is FC and SurchargeType is E and WeightBreakType is B.	Postage Statement Messages
8519	BarcodeRate must be populated with N or O when FormType is FC.	Postage Statement Messages
8520	EntryFacilityType must be populated with O, B, S, or D when FormType is FC.	Postage Statement Messages
8521	PackagingMethod must be populated with 0, 1, or Blank when FormType is FC.	Postage Statement Messages
8522	PostagePaymentMethod must be populated with S, M, or P when FormType is FC.	Postage Statement Messages
8524	MoveUpdateMethod must be populated with ASE, ACS, ALT, FAST, MULT, or NCOA when FormType is SM.	Postage Statement Messages
8525	EnclosedBy must be populated with SM, BP, PE, or ML when FormType is FC.	Postage Statement Messages
8526	ServiceCode must be populated with SH, COM, COD, RR, RM, SC, DC, RRE, CM, IM, or RD when FormType is FC.	Postage Statement Messages
8527	ProcessingCategory must be populated with PF when FormType is FC and ServiceCode is SC.	Postage Statement Messages
8528	ProcessingCategory must be populated with FL, MP, NP, or IR when FormType is ML.	Multiple
8529	Zone must be populated with N when FormType is ML and ProcessingCategory is MP or IR.	Multiple
8530	ProcessingCategory must be populated with FL, MP, or IR when FormType is ML and RateType is F.	Postage Statement Messages
8531	Zone must be populated with N when FormType is ML and RateType is F.	Postage Statement Messages
8533	ProcessingCategory must be populated with FL, MP, or IR when FormType is ML and RateType is L.	Postage Statement Messages
8536	EntryDiscount must be populated with N when FormType is ML.	Multiple

Copyright © 2011 USPS®. All Rights Reserved.

Error Code	Error Message	Messages
8537	RateCategory must be populated with G, N, S, or E when FormType is ML.	Postage Statement Messages
8538	SurchargeType must be populated with N when FormType is ML.	Postage Statement Messages
8539	WeightBreakType must be populated with N when FormType is ML.	Postage Statement Messages
8540	BarcodeRate must be populated with Y or N when FormType is ML.	Postage Statement Messages
8541	EntryFacilityType must be populated with A, O, B, S, or D when FormType is ML.	Postage Statement Messages
8542	PackagingMethod must be populated with 0, 1, 2, or Blank when FormType is ML.	Postage Statement Messages
8543	PostagePaymentMethod must be populated with M or P when FormType is ML.	Postage Statement Messages
8544	RateType must be populated with L or F when FormType is ML.	Postage Statement Messages
8545	SackingBasis must be populated with 0 or 1 when FormType is ML.	Postage Statement Messages
8546	SinglePieceWeight must be less than or equal to 35 pounds when FormType is ML and BarcodeRate is Yes.	Postage Statement Messages
8547	SinglePieceWeight must be less than or equal to 70 pounds when FormType is ML and BarcodeRate is No.	Postage Statement Messages
8548	TotalPieces and TotalCopies must be populated with the same values when the FormType is ML.	Multiple
8549	ServiceCode must be populated with COD, COM, DC, IM, PAL, RD, RR, RRE, RRM, SC, or SH when FormType is ML.	Postage Statement Messages
8550	ProcessingCategory must be populated with LT, FL, MP, IR, or NP when FormType is PE.	QualificationReportCreateResponse
8551	Zone must be populated with N, 1, 3, 4, 5, 6, 7, 8, ICD, ADC, DDU, or SCF when FormType is PE and Zone is provided.	Multiple
8554	EntryFacilityType must be populated with O, B, D, A, or S when FormType is PE. (User Postage Statement ID: %%1).	Periodical Postage Statement Messages
8557	LimitedCirculationDiscountClaimed must be populated with Yes when the FormType is PE and RateType is W or Y. (User Postage Statement ID: %%1).	Periodical Postage Statement Messages
8558	ContainerChargeContainerLevel must be populated with 3, 5, A, or M when FormType is PE.	QualificationReportCreateResponse
8559	InOutCountyIndicator must be populated with N or I when FormType is PE.	Multiple

Copyright © 2011 USPS®. All Rights Reserved.

Error Code	Error Message	Messages
8560	AdPercent is required when FormType is PE. (User Postage Statement ID: %%1).	Periodical Postage Statement Messages
8562	EntryFacilityType must be populated with O, B, S, D, or A when FormType is PE or Pending Periodicals. (User Postage Statement ID: %%1).	Periodical Postage Statement Messages
8563	RateCategory must be populated with A, B, D, E, G, H, K, L, L1, L2, L3, L4, L5, L6, L7, L8, FB, N, or O when mailing is identified as Periodicals. (User Postage Statement ID: %%1).	Periodical Postage Statement Messages
8564	When populated, Zone must be populated with DDU, 1, 3, 4, 5, 6, 7, 8, SCF, ADC, or N when FormType is PE and InOutCountyIndicator is I. (User Postage Statement ID: %%1).	Periodical Postage Statement Messages
8567	ProcessingCategory can only be populated with FL, MP, or LT when FormType is PE and InOutCountyIndicator is I and RateCategory is L, H, or E. (User Postage Statement ID: %%1).	Periodical Postage Statement Messages
8571	RateCategory must be populated with A, B, D, FB, E, G, H, K, L3, L4, L5, or L6 when FormType is PE, and InOutCountyIndicator is N, and MachinableFlag is N, and ProcessingCategory is FL. (User Postage Statement ID: %%1).	Periodical Postage Statement Messages
8572	RateCategory must be populated with A, B, D, FB, E, G, H, K, L3, L4, L5, or L6 when FormType is PE and InOutCountyIndicator is N and MachinableFlag is Blank and ProcessingCategory is IR, MP, or NP. (User Postage Statement ID: %%1).	Periodical Postage Statement Messages
8573	RateCategory must be populated with A, B, D, FB, E, G, H, K, L1, L2, L3, L4, L5, or L6 when FormType is PE and InOutCountyIndicator is N and MachinableFlag is Blank and ProcessingCategory is LT. (User Postage Statement ID: %%1).	Periodical Postage Statement Messages
8574	ChargeableContainerLevel must be populated with M when FormType is PE and InOutCountyIndicator is N and ChargeableBundleLevel is M. (User Postage Statement ID: %%1).	Periodical Postage Statement Messages
8575	ChargeableContainerLevel must be populated with M or A when FormType is PE and InOutCountyIndicator is N and ChargeableBundleLevel is A. (User Postage Statement ID: %%1).	Periodical Postage Statement Messages
8576	ChargeableContainerLevel must be populated with M, A, or 3 when FormType is PE and InOutCountyIndicator is N and ChargeableBundleLevel is 3. (User Postage Statement ID: %%1).	Periodical Postage Statement Messages
8577	ChargeableContainerLevel must be populated with M, A, 3, or 5 when FormType is PE and InOutCountyIndicator is N and ChargeableBundleLevel is 5. (User Postage Statement ID: %%1).	Periodical Postage Statement Messages
8578	ContainerType must be populated with Pallets-Sacks-Trays when FormType is PE and Containers is populated. (User Postage Statement ID: %%1).	Periodical Postage Statement Messages
8579	ChargeableEntryLevel must be populated with C, J, or O when FormType is PE and ChargeableContainerLevel is M. (User Postage Statement ID: %%1).	Periodical Postage Statement Messages
8581	ChargeableEntryLevel must be populated with B, C, J, K, O, or R when FormType is PE and ChargeableContainerLevel is A. (User Postage Statement ID: %%1).	Periodical Postage Statement Messages
8583	ChargeableEntryLevel must be populated with B, C, J, K, O, R, or S when FormType is PE and ChargeableContainerLevel is 3. (User Postage Statement ID: %%1).	Periodical Postage Statement Messages

Copyright © 2011 USPS®. All Rights Reserved.

Error Code	Error Message	Messages
8585	ChargeableEntryLevel must be populated with B, C, D, J, K, O, R, or S when FormType is PE and ChargeableContainerLevel is 5. (User Postage Statement ID: %%1).	Periodical Postage Statement Messages
8586	ProcessingCategory must be populated with LT, FL or PF when FormType is PM.	Postage Statement Messages
8587	Zone must be populated with N, 1, 3, 4, 5, 6, 7, or 8 when FormType is PM and ProcessingCategory is LT, FL, or PF.	Postage Statement Messages
8588	RateType must be C, E, L, or T when FormType is PM and ProcessingCategory is FL	Postage Statement Messages
8589	RateCategory must be S, PR, P10, P11, P12, P13, P14, P15, or P16 when FormType is PM and ProcessingCategory is FL..	Postage Statement Messages
8590	RateType must be C or T when FormType is PM and ProcessingCategory is LT	Postage Statement Messages
8591	RateCategory must be S when FormType is PM and ProcessingCategory is LT.	Postage Statement Messages
8592	RateType must be E, G, J, K, L, X, or T when FormType is PM and ProcessingCategory is PF.	Postage Statement Messages
8593	RateCategory must be S, P10, P11, P12, P13, P14, P15, or P16 when FormType is PM and ProcessingCategory is PF.	Postage Statement Messages
8594	EntryDiscount must be populated with N when FormType is PM.	Postage Statement Messages
8595	RateCategory must be populated with S, PR, P10, P11, P12, P13, P14, P15, or P16 when FormType is PM.	Postage Statement Messages
8596	SurchargeType must be populated with D, E, N, or P when FormType is PM.	Postage Statement Messages
8597	WeightBreakType must be populated with N when FormType is PM.	Postage Statement Messages
8598	FlatRateIndicator must be populated with B, C, E, F, L, M, O, P, or S when FormType is PM.	Postage Statement Messages
8599	BarcodeRate must be populated with N or O when FormType is PM.	Postage Statement Messages
8600	EntryFacilityType must be populated with O, B, S, or D when FormType is PM.	Postage Statement Messages
8601	PostagePaymentMethod must be populated with P when FormType is PM.	Postage Statement Messages

Copyright © 2011 USPS®. All Rights Reserved.

Error Code	Error Message	Messages
8602	RateType must be populated with C, L, T, E, G, J, K, or X when FormType is PM.	Postage Statement Messages
8603	PriceType must be populated with Commercial, Commercial Plus, or Retail when FormType is PM.	Postage Statement Messages
8605	ServiceCode must be populated with AS, RAS, CM, COD, COM, DC, IM, RD, RM, RR, RRE, RRM, SC, or SH when FormType is PM.	Postage Statement Messages
8606	ProcessingCategory must be populated with MP, IR, or NP when FormType is PP.	Postage Statement Messages
8607	Zone must be populated with N, 1, 3, 4, 5, 6, 7, 8, DDU or SCF when FormType is PP.	Postage Statement Messages
8611	ProcessingCategory must be populated with MP, NP or IR when FormType is PP and RateType is P.	Postage Statement Messages
8612	Zone must be populated with 1, 3, 4, 5, 6, 7, or 8 when FormType is PP and RateType is P.	Postage Statement Messages
8613	RateCategory must be populated with S when FormType is PP and RateType is P.	Postage Statement Messages
8616	SurchargeType must be populated with 2 or N when FormType is PP.	Postage Statement Messages
8617	WeightBreakType must be populated with N when FormType is PP.	Postage Statement Messages
8618	BarcodeRate must be populated with N when FormType is PP and RateType is P.	Postage Statement Messages
8620	PostagePaymentMethod must be populated with M or P when FormType is PP.	Postage Statement Messages
8621	RateType must be populated with P when FormType is PP.	Postage Statement Messages
8626	SinglePieceWeight must be populated with a value less than or equal to 70 pounds when FormType is PP, RateType is P, SurchargeType is N, RateCategory is S, and BarcodeRate is Y.	Postage Statement Messages
8627	SinglePieceWeight must be populated with a value less than or equal to 70 pounds when FormType is PP, RateType is P, SurchargeType is N, RateCategory is S, and BarcodeRate is N.	Postage Statement Messages
8628	SinglePieceWeight must be populated with a value less than or equal to 70 pounds when FormType is PP, RateType is P, SurchargeType is P, and RateCategory is S.	Postage Statement Messages
8629	SinglePieceWeight must be populated with a value less than or equal to 70 pounds when FormType is PP RateType is P, SurchargeType is 2, and RateCategory is S.	Postage Statement Messages

Copyright © 2011 USPS®. All Rights Reserved.

Error Code	Error Message	Messages
8630	SinglePieceWeight must be populated with a value less than or equal to 70 pounds when FormType is PP, RateType is P, SurchargeType is N or 2, and RateCategory is Z1 or Z2.	Postage Statement Messages
8631	SinglePieceWeight must be populated with a value less than or equal to 70 pounds when FormType is PP and RateType is P and SurchargeType is P or 2 and RateCategory is Z1 or Z2.	Postage Statement Messages
8632	TotalPieces and TotalCopies must be populated with the same values when FormType is PP.	Multiple
8633	If populated, ServiceCode must be populated with COD, COM, DC, IM, PAL, RD, RR, RRE, RRM, SC, or SH when FormType is PP.	Postage Statement Messages
8634	ProcessingCategory must be populated with LT, FL, MP, IR, NP, CM, NA, or NB when FormType is SM. (User Postage Statement ID: %%1).	Multiple
8635	Zone must be populated with N when FormType is SM and ProcessingCategory is LT, FL, MP, IR, or CM. (User Postage Statement ID: %%1).	Multiple
8637	RateCategory must be populated with N when FormType is SM and ProcessingCategory is CM. (User Postage Statement ID: %%1).	Postage Statement Messages
8638	EntryDiscount must be populated with N when FormType is SM and ProcessingCategory is CM. (User Postage Statement ID: %%1).	Postage Statement Messages
8640	RateCategory must be populated with A, B, D, O, E, G, H, K, L3, L4, L5, or L6 when FormType is SM and ProcessingCategory is FL. (User Postage Statement ID: %%1).	Postage Statement Messages
8642	RateCategory must be populated with A, B, D, O, P5, P6, P7, P8, PG, PI, PK, or PM when FormType is SM and ProcessingCategory is IR. (User Postage Statement ID: %%1).	Postage Statement Messages
8644	RateCategory must be populated with A, A1, B, B1, D, D1, O, E, G, H, K, L1, L2, L5, L6, L7, L8, NG, NK, N5, or N6 when FormType is SM and ProcessingCategory is LT. (User Postage Statement ID: %%1).	Postage Statement Messages
8646	RateCategory must be populated with A, B, D, PE, PQ, or PR when FormType is SM and ProcessingCategory is MP. (User Postage Statement ID: %%1).	Postage Statement Messages
8648	RateCategory must be populated with N5, N6, NG, or NK when FormType is SM and ProcessingCategory is NA or NB. (User Postage Statement ID: %%1).	Postage Statement Messages
8649	EntryDiscount must be populated with N, B, S, or D when FormType is SM. (User Postage Statement ID: %%1).	QualificationReportCreateResponse
8650	RateCategory must be populated with A, B, D, O, E, G, H, K, N, L1, L2, L3, L4, L5, L6, L7, L8, PE, PG, PI, PK, PM, PQ, PR, P5, P6, P7, or P8 when FormType is SM. (User Postage Statement ID: %%1).	Postage Statement Messages
8651	SurchargeType must be populated with L or N when FormType is SM. (User Postage Statement ID: %%1).	Postage Statement Messages
8652	WeightBreakType must be populated with A, B, or H when FormType is SM. (User Postage Statement ID: %%1).	Postage Statement Messages

Copyright © 2011 USPS®. All Rights Reserved.

Error Code	Error Message	Messages
8653	PieceWeight must be populated with a value greater than 0.2063 pounds when FormType is SM and WeightBreakType is A. (User Postage Statement ID: %%1).	Postage Statement Messages
8654	PieceWeight must be populated with a value less than or equal to 0.2063 pounds when FormType is SM and WeightBreakType is B. (User Postage Statement ID: %%1).	Postage Statement Messages
8655	PieceWeight must be populated with a value greater than 0.2063 pounds when FormType is SM and WeightBreakType is H and ProcessingCategory is LT. (User Postage Statement ID: %%1).	Postage Statement Messages
8656	BarcodeRate must be populated with Y, N, or O when FormType is SM. (User Postage Statement ID: %%1).	Postage Statement Messages
8657	EntryFacilityType must be populated with O, B, S, or D when FormType is SM. (User Postage Statement ID: %%1).	Postage Statement Messages
8658	PackagingMethod must be populated with 0, 1, 2, or Blank when FormType is SM. (User Postage Statement ID: %%1).	Postage Statement Messages
8659	PostagePaymentMethod must be populated with S, M, or P when FormType is SM. (User Postage Statement ID: %%1).	Postage Statement Messages
8660	RateType must be populated with R or N when FormType is SM. (User Postage Statement ID: %%1).	Postage Statement Messages
8661	SackingBasis must be populated with 0, 1, 2, 3, 4, or Blank when FormType is SM. (User Postage Statement ID: %%1).	Postage Statement Messages
8662	EnclosedBy must be populated with SM, BP, PE, PP, or ML when FormType is SM. (User Postage Statement ID: %%1).	Postage Statement Messages
8663	ServiceCode must be populated with DC, IM, RRM, or RD when FormType is SM. (User Postage Statement ID: %%1).	Postage Statement Messages
8665	The MailingGroupID in the OriginalContainerLinkageCancelRequest must be populated with the Consolidator MailingGroupID.	OriginalContainerLinkageCancelResponse
8666	OpenMailingGroupRequest message must be accepted before submitting the OriginalContainerLinkageCreateRequest message for the specified CRID when a Mail.dat container is being linked.	OriginalContainerLinkageCreateResponse
8667	QualificationReportCreateRequest must be accepted before submitting the OriginalContainerLinkageCreateRequest for the specified CRID when a Mail.XML container is being linked. (Linked Mailing Group: %%1, Linked Container ID: %%2).	OriginalContainerLinkageCreateResponse
8668	Values populated in the MailDatContainer block must exist when the original container was submitted through Mail.dat. (Original Mail.dat Job ID: %%1, Original Mail.dat Container ID: %%2).	OriginalContainerLinkageCreateResponse
8669	Values populated in the MailXMLContainer block must exist when the original container was submitted through Mail.XML. (Original Mailing Group: %%1, Original Container ID: %%2).	OriginalContainerLinkageCreateResponse
8670	Either the MailDatContainer block or the MailXMLContainer block of the OriginalContainer block is required.	OriginalContainerLinkageCreateResponse

Copyright © 2011 USPS®. All Rights Reserved.

Error Code	Error Message	Messages
8672	Populated fields in the MailXMLContainer block in the LinkedContainer block must link to fields in a MailXMLContainer block in the OriginalContainer block. (Linked Mailing Group: %%1, Linked Container ID: %%2).	OriginalContainerLinkageCreateResponse
8673	CustomerGroupID in the OriginalContainerLinkageCreateHeaderInfo block is required.	OriginalContainerLinkageCreateResponse
8674	MailingGroupID in the OriginalContainerLinkageCreateHeaderInfo block is required.	OriginalContainerLinkageCreateResponse
8675	OriginalContainerLinkageCreateRequest message must be accepted before the OriginalContainerLinkageCancelRequest message for the specified CRID when the linked container is created through Mail.XML. (Reason: %%1)	OriginalContainerLinkageCancelResponse
8676	OpenMailingGroupRequest message must be accepted before submitting the OriginalContainerCancelLinkageRequest message for the specified CRID when the linked container is created through Mail.dat.	OriginalContainerLinkageCancelResponse
8677	OpenMailingGroupRequest message must be accepted before submitting the OriginalContainerCreateLinkageRequest message for the specified CRID when the linked container is created through Mail.dat.	OriginalContainerLinkageCreateResponse
8678	PublicationNumber within the PermitPublicationData block in the MailingGroupData block must be populated with a value combined with the PostOfficeOfMailingZIP in the MailingGroupData block that maps to a single active Finance Number.	OpenMailingGroupResponse
8679	PermitNumber field within the PermitPublicationData block in the DocumentVersionDataWithPermit block must exist and map back to a Finance Number. (Version ID: %%1)	QualificationReportCreateResponse, QualificationReportDetailCreateResponse (10.0)
8680	MailPieceBlock or MailXMLPieceRangeBlock is required when the FullServiceParticipationIndicator is populated with M.	MailPieceCreateResponse
8689	BundleID must be a unique value within a ContainerID in the BundleDetail block across the mailing group. (ContainerID: %%1, BundleID: %%2).	BundleDetailCreateResponse
8692	OriginalContainer block must contain fields that are populated with the values that exist in the *PostalOne!* Mail.dat database for the specified CRID.	SiblingContainerCancelResponse
8693	ContainerID value that has been deleted within the SiblingContainerCancelRequest message cannot be reused within a mailing group. (Sibling Container ID: %%1 was previously cancelled.)	SiblingContainerCreateaResponse
8694	UserPostageStatementID must be unique within the MailingGroupID. (User Postage Statement ID: %%1).	Periodical Postage Statement Messages
8695	ServiceCode must be populated with CM, COD, DC, IM, RD, RM, RR, RRE, RRM, SC, or SH when FormType is PM.	Postage Statement Messages
8696	CustomerQualificationReportID in the QualificationReport must be a unique value within the MailingGroupID.	QualificationReportCreateResponse

Copyright © 2011 USPS®. All Rights Reserved.

Error Code	Error Message	Messages
8697	ContainerID in the QualificationReport must be a unique value within the MailingGroupID. (Container ID: %%1)	QualificationReportCreateResponse, QualificationReportDetailCreateResponse (10.0)
8698	VersionID in the ContainerDetailData must be populated and referenced with a VersionID in at least one DocumentVersionDataWithPermit block associated to a Qualification Report. (Container ID: %%1)	QualificationReportCreateResponse, QualificationReportDetailCreateResponse (10.0)
8702	ContainerPostage is required when the FullServiceParticipationIndicator is F or M except when the ContainerID is populated for all PeriodicalStatementLineItemData blocks for the specified StatementSequenceNumber. (User Postage Statement ID: %%1).	Periodical Postage Statement Messages
8715	SiblingContainerCancelRequest message cannot be submitted when the original container and sibling container have the ContainerStatus of Ready to Pay. (Orig ContainerID: %%1, Sibling ContainerID: %%2)	SiblingContainerCancelResponse
8717	When the USPSPriceIncentiveType in the DocumentVersionData, LineItemSummaryData, or PostageStatementLineItemData block is provided, it must be set to Saturation-HDSCF, Saturation-HDTotal, PostageAffixedReplyRidesFree, MobileBarcode, or SummerSale.	Postage Statement Messages
8718	The maximum weight for First-Class Mail Automation Letters and Cards is 3.5 ounces.	Postage Statement Messages
8719	The maximum weight for First-Class Mail Non-Automation Letters is 13 ounces.	Postage Statement Messages
8720	The maximum weight for First-Class Mail Automation Flats is 13 ounces.	Postage Statement Messages
8721	The maximum weight for First-Class Mail Non-Automation Flats is 13 ounces.	Postage Statement Messages
8724	The StandardFlatType field in the LineItemSummary or PostageStatementLineItemData blocks must be populated when FormType is SM and ProcessingCategory is FL.	Postage Statement Messages
8725	The StandardFlatType field in the DocumentVersionDataWithPermit block must be populated when FormType is SM and ProcessingCategory is FL.	QualificationReportCreateResponse
8726	The RateCategory must be E, H, L3, L4, A, B, D, or O for Standard Mail Flat Catalogs.	Postage Statement Messages
8728	The Maximum weight for Standard Mail Letters is 16 ounces.	Postage Statement Messages
8729	The Maximum weight for Standard Mail Flats is 16 ounces.	Postage Statement Messages

Copyright © 2011 USPS®. All Rights Reserved.

Error Code	Error Message	Messages
8731	The maximum weight for Package Services Bound Printed Matter is 20 ounces.	Postage Statement Messages
8732	The version weight for Periodical and Pending Periodical Letters cannot be greater than 16 ounces (Postg Stmt. %%1).	Postage Statement Messages
8733	The version weight for Periodical and Pending Periodical machinable Flats cannot be greater than 22 ounces (Postg Stmt. %%1).	Postage Statement Messages
8734	Rate Categories AF, BF, DF, GF, and KF are not supported for First-Class Mail, Standard Mail, or Periodicals.	Multiple
8735	A ContainerDetailID field submitted in the MailPieceCreateRequest message must match a ContainerDetailID field submitted in the associated QualificationReportCreateRequestMessage. (ContainerDetailID %%1 missing for ContainerID %%2)	MailPieceCreateResponse
8736	A ContainerDetailID field submitted in the PostageStatementCreateRequest message must match a ContainerDetailID field submitted in the associated QualificationReportCreateRequestMessage. (ContainerDetailID %%1 missing for ContainerID %%2)	Postage Statement Messages
8737	A ContainerDetailID field submitted in the Periodical- or ConsolidatedPeriodicalStatementCreateRequest must match a ContainerDetailID field submitted in the associated QualificationReportCreateRequest. (ContainerDetailID %%1 missing for ContainerID %%2)	Postage Statement Messages
8738	The number of pieces for a ContainerDetailID submitted in the MailPieceCreateRequest cannot exceed the number of pieces associated to that ContainerDetailID field in the QualificationReportCreateRequest. (ContainerDetailID %%1 within ContainerID %%2)	MailPieceCreateResponse
~~8739~~	~~The number of pieces for the ContainerDetailID field submitted in the PostageStatementCreateRequest cannot exceed the pieces for that ContainerDetailID in the MailPieceCreateRequest. (ContainerDetailID %%1 missing for ContainerID %%2)~~	~~Postage Statement Messages~~
~~8740~~	~~The ContainerDetailID number of pieces in the Periodical- or ConsolidatedPeriodicalStatementCreateRequest cannot exceed the number of pieces associated to the MailPieceCreateRequest ContainerDetailID. (ContainerDetailID %%1 missing for ContainerID %%2)~~	~~Postage Statement Messages~~
8765	ParentContainerID field in the QualificationReportCreateRequest message is required when the IncludedinOtherDoc field is L and the SiblingContainerID is null. (ContainerDetailID %%1 missing for ContainerID %%2)	QualificationReportCreateResponse
8767	SiblingContainerID is an optional field and cannot be populated if the ParentContainerID field is populated. When populated its length should be between 1 and 6 characters. (Found SiblingContainerID %% for ContainerID %%2)	QualificationReportCreateResponse, QualificationReportDetailCreateRespose (10.0)
8768	The system only supports Transportation Update with Container Status T in the ContainerUpdateRequest message.	ContainerUpdateResponse

Copyright © 2011 USPS®. All Rights Reserved.

Error Code	Error Message	Messages
8769	The system supports Transportation Update with Container Status T and Submission Date is within 30 days of the Postage Statement Mailing Date.	ContainerUpdateResponse
8809	A postage statement line did not map to a valid rate.	Postage Statement Messages
8810	The Permit Number, Type and Zip4 Option of the Permit Holder block must be populated in a PostageStatementCreateRequest message.	Postage Statement Messages
8811	Verify that at least one Permit block was submitted.	Postage Statement Messages
8812	FullServiceParticipationIndicator in the MailingGroupData block of the OpenMailingGroupRequest message must be populated with F or M for mail piece or piece range creation.	MailPieceCreateResponse
8813	OriginalContainerCancelRequest message cannot cancel linked containers when the PostageStatementStatus in the PostageStatementSummary block is UPD and the ContainerType is V. (Linked Mailing Group: %%1, Linked Container ID: %%2).	OriginalContainerLinkageCancelResponse
8814	OriginalContainerCancelRequest message cannot cancel linked containers when the ContainerType of the original and linked container is O, T, E, or L. (Linked Mailing Group: %%1, Linked Container ID: %%2).	OriginalContainerLinkageCancelResponse
8815	At least one Extra Service Summary Data Block does not match the expected Rates.	Postage Statement Messages
8817	EnclosedBy in the CreatePostageStatement block must be populated with PE for Enclosures.	Postage Statement Messages
8818	EnclosingIssueDate is required when EnclosedBy in CreatePostageStatement block is populated with PE for Enclosures.	Postage Statement Messages
8819	FormType in the CreatePostageStatement block must be populated with FC or SM when EnclosedBy in CreatePostageStatement block is populated with PE.	Postage Statement Messages
8820	EntryLocaleKey field in the ContainerInfoData block must be populated for drop shipped mail. (Container ID: %%1)	QualificationReportCreateResponse, QualificationReportDetailCreateRespose (10.0)
8821	PostageStatementLineData does not match the Extended form setting in the header.	Postage Statement Messages
8822	More than %%1 failures for error code: %%2	All Request Messages
8823	Version ID must be unique within the submitted message. (Version ID: %%1).	Multiple
8824	An error occurred when parsing the message.	Multiple
8826	SiblingContainerCreateRequest message must be sent before the original container has ContainerStatus populated with R.	ContainerUpdateResponse
8827	The MaildatJobID and UserLicenseCode provided did not map to a valid job.	ContainerUpdateResponse

Copyright © 2011 USPS®. All Rights Reserved.

Error Code	Error Message	Messages
8828	The new linked ctr id is already assigned to a different original ctr. (Linked ctr: %%1)	OriginalContainerLinkageCreateResponse
8831	When provided, RateCategory must be A, B, D, E, H, O, L1, L2, L3, or L4 when the FormType is PE, the InOutCountyIndicator is I, and the ServiceLevelIndicator for the associated ContainerID is F.	Postage Statement Messages
8832	When provided, RateCategory must be A, B, D, E, H, O, L1, L2, L3, L4, or FB when the FormType is PE, the InOutCountyIndicator is N, and the ServiceLevelIndicator for the associated ContainerID is F.	Postage Statement Messages
8833	RateCategory can only be E, H, L1, or L2 when FormType is FC, ProcessingCategory is CD, and the ServiceLevelIndicator for the associated ContainerID is F.	Postage Statement Messages
8834	RateCategory can only be E, H, L1, or L2 when FormType is FC, ProcessingCategory is LT, and the ServiceLevelIndicator for the associated ContainerID is F.	Postage Statement Messages
8835	RateCategory can only be E, H, L3, or L4 when FormType is FC, ProcessingCategory is FL, and the ServiceLevelIndicator for the associated ContainerID is F.	Postage Statement Messages
8836	RateCategory can only be A, B, D, O, E, H, L1 or L2 when FormType is SM, ProcessingCategory is LT, and the ServiceLevelIndicator for the associated ContainerID is F.	Postage Statement Messages
8837	The RateCategory field can only be populated with A,B, D, O, E, H, L3 or L4 when the FormType is SM, ProcessingCategory is FL, and the ServiceLevelIndicator for the associated ContainerID is F.	Postage Statement Messages
8838	RateCategory can only be A, B, D, O, E, H, L3 or L4 when FormType is BP, ProcessingCategory is FL, and the ServiceLevelIndicator for the associated ContainerID is F.	Postage Statement Messages
8839	A Header record for Periodical Statement %%1 failed to generate.	Postage Statement Messages
8840	Only one Pieces field in the MailXMLPieceRange block can be populated.	MailPieceCreateResponse
8841	Only one Copies field in the MailXMLPieceRange block can be populated.	MailPieceCreateResponse
8842	The Origin Container Barcode specified in the Original Container Linkage message does not match the submitted Origin Container Barcode: %%1	OriginalContainerLinkageCreateResponse
8843	The Linked Container Barcode specified in the Original Container Linkage message does not match the submitted Linked Container Barcode: %%1	OriginalContainerLinkageCreateResponse
8844	The ProcessingCategory of child containers must match the ProcessingCategory of their respective parent container.	QualificationReportCreateResponse, QualificationReportDetailCreateRespose (10.0)
8845	The CinCode field in in the ContainerInfoData can only contain numeric characters.	QualificationReportCreateResponse, QualificationReportDetailCreateRespose (10.0)

Copyright © 2011 USPS®. All Rights Reserved.

Error Code	Error Message	Messages
8846	The FormType must be PE for a Periodical Statement.	Postage Statement Messages
8847	The mail class must be the same across a co-palletized mailing.	OriginalContainerLinkageCreateResponse
8849	The Permit with Number %%1, and Type %%2 does not map to the same Finance Number as the permit for the Mailing Group.	QualificationReportCreateResponse
8850	An OriginalContainerID and OriginalMailingGroup or a OriginalJobID in the OriginalContainerLinkageCreateRequest can not have been previously linked to a consolidator MailingGroup. Container Id %%1	OriginalContainerLinkageCreateResponse
8851	The ContainerID field in the OriginalContainer block does not have a finalized postage statement associated to it, which is needed for Tray-Based Co-Palletization. Container Id: %%1	OriginalContainerLinkageCreateResponse
8856	The Total Postage for line block %%1 must be between the Postage calculated at the minimum and maximum rates for Section %%2, Line Number %%3	Postage Statement Messages
8857	The number of pieces in the InCountyAddressedSupplementPieces field cannot exceed the sum of all pieces in PeriodicalLineItemData blocks where InOutCountyIndicator is set to I. (User Postage Statement ID: %%1)	Postage Statement Messages
8858	The service level of the Linked Container may not be higher than that of the Original Container. Original Container Service Level: %%1, Linked Container Service Level: %%2	OriginalContainerLinkageCreateResponse
8859	When populated, the ContainerType field in SiblingContainerCreateRequest message must be populated with 1, 2, 3, 4, 5, E, F, O, P, S, T, B, U, Z, H, A, G, D, R, or C.	SiblingContainerCreateaResponse
8860	The number of pieces in the OutsideCountyAddressedSupplementPieces field cannot exceed the sum of all pieces in PeriodicalLineItemData blocks where InOutCountyIndicator is set to N. (User Postage Statement ID: %%1)	Postage Statement Messages
8861	For Copalletization, the linked container must have an Included In Other Documentation value of L. Container ID: %%1	OriginalContainerLinkageCreateResponse
8862	For Copalletization, the original container must have an Included In Other Documentation value of O. Container ID: %%1	OriginalContainerLinkageCreateResponse
8864	Each Periodical Statement submitted in a PeriodicalStatementCreateRequest or a ConsolidatedStatementCreateRequest must contain at least one PeriodicalLineItemData block.	Postage Statement Messages
8865	Each Postage Statement submitted in a PostageStatementCreateRequest must contain at least one PostageStatementLineItemData block or one LineItemSummaryData block.	Postage Statement Messages
8866	Invalid permit information was entered to claim the Science and Agriculture rate.	Postage Statement Messages
8867	Invalid permit information was entered to claim the Non-Profit rate.	QualificationReportCreateResponse

Copyright © 2011 USPS®. All Rights Reserved.

Error Code	Error Message	Messages
8868	Invalid permit information was entered to claim the Classroom rate.	QualificationReportCreateResponse
8869	An Internal Error occured during the %%1 step while processing your message.	Postage Statement Messages
8870	A QualificationReportCreateRequest with the OnePassPlannedOrActualFlag with A must be preceded by a QualificationReportCreateRequest with the OnePassPlannedOrActualFlag set to P .	QualificationReportCreateResponse
8871	All Postage Statements in a Combined Mailing must have the same Form Type. The Form Type for this Combined Mailing is %%1.	Postage Statement Messages
8873	Invalid permit information was entered to claim the Science of Agriculture Limited Circulation rate.	QualificationReportCreateResponse
8874	Invalid permit information was entered to claim the Regular Limited Circulation rate.	QualificationReportCreateResponse
8875	All Periodical Statements in a ConsolidatedPeriodicalStatementCreateRequest must have the same Combined Mailing ID.	Multiple
8876	The QualificationReportCreateRequest message cannot have the records with the IncludedInOtherDoc field values set to O and L.	QualificationReportCreateResponse
8877	The LineItemSummaryData block must have the PiecePostage field populated when the single piece weight is not provided.	Postage Statement Messages
8878	The PostageAmount in the LineItemSummaryData block must equal the PiecePostage plus the PoundPostage when the single piece weight is not provided.	Postage Statement Messages
8879	The PostageAmount in the LineItemSummaryData block cannot be greater than the PiecePostage amount when the single piece weight is not provided.	Postage Statement Messages
8880	The Piece Postage for line block %%1 must be between the Postage calculated at the minimum and maximum rates for Section %%2, Line Number %%3	Postage Statement Messages
8881	The Pound Postage for line block %%1 must be between the Postage calculated at the minimum and maximum rates for Section %%2, Line Number %%3	Postage Statement Messages
8882	Tray based copal container linkages cannot be cancelled. (ContainerID: %%1)	OriginalContainerLinkageCancelResponse
8883	Bundle based copal container linkages cannot be cancelled after the associated postage statements have been finalized. (ContainerID: %%1	OriginalContainerLinkageCancelResponse
8884	The Original Container and Linked Container must have the same Container Barcodes required for Fullservice and Mixed Service containers. %%1	OriginalContainerLinkageCreateResponse
8885	When populated, the FullServiceParticipationIndicator field must be set to F.	Postage Statement Messages
8886	The Permit Holder Permit Type cannot equal PE or PP in a PostageStatementCreateRequest message.	Postage Statement Messages

Copyright © 2011 USPS®. All Rights Reserved.

Error Code	Error Message	Messages
8887	The finance number %%1 associated with .mpa permit number %%2 and permit type %%3 does not have a non-profit status.	Postage Statement Messages
8888	Container updates to origin containers in a co-pal tray job are not allowed after the consolidator job has been submitted. (Container ID: %%1)	ContainerUpdateResponse
8889	The number of pieces must equal the number of copies when the mailing does not include Firm Bundles or Addressed Supplements and InOutCountyIndicator is N.	Postage Statement Messages
8890	The number of pieces must be less than or equal to the number of copies when the mailing includes Firm Bundles but does not have any Addressed Supplements and InOutCountyIndicator is N.	Postage Statement Messages
8891	The number of pieces must be greater than or equal to the number of copies when the mailing includes Addressed Supplements but does not have Firm Bundles and InOutCountyIndicator is N.	Postage Statement Messages
8900	The CRID in the SubmittingParty block of the SiblingContainerCreateRequest message must match the CRID of the mailer that created the MailingGroup. (CRID: %%1)	SiblingContainerCreateResponse
8901	The CustomerGroupID field within the OriginalContainer block of the SiblingContainerCreateRequest message must be a string between 1 and 25 characters and match the CustomerGroupID of the existing container. (Container GroupID: %%1)	SiblingContainerCreateResponse
8902	The MailingGroupID field within the OriginalContainer block of the SiblingContainerCreateRequest message must be a non-negative integer and match the MailingGroupID of the existing container. (Mailing Group ID: %%1)	SiblingContainerCreateResponse
8903	The ContainerID fields in the OriginalContainer block of the SiblingContainerCreateRequest message must match the ContainerID fields in the QualificationReportCreateRequest message for the existing container. (Container ID: %%1)	SiblingContainerCreateResponse
8906	The ProcessingCategory field in the SummaryZipDestinationReport block of the SummaryZipDestinationReportCreateRequest message must be populated with LT, FL, CD, MP, IR, PF, CM, NP, NA, or NB.	SummaryZipDestinationReportCreateResponse
8907	The PostagePaymentMethod field in the SummaryZipDestinationReport block of the SummaryZipDestinationReportCreateRequest message must be populated with S, M or P.	SummaryZipDestinationReportCreateResponse
8908	The combination of MailingGroupID and CustomerGroupID in the SummaryZipDestinationReportCreateRequest message must be populated with the same values as that of the open mailing group.	SummaryZipDestinationReportCreateResponse
8909	The QualificationReportCreateRequest message must be accepted before submitting the SummaryZipDestinationReportCreateRequest message for that specified MailingGroupID.	SummaryZipDestinationReportCreateResponse
8910	The PostageStatementCreateRequest message must be accepted before submitting the SummaryZipDestinationReportCreateRequest message for that specified MailingGroupID.	SummaryZipDestinationReportCreateResponse

Copyright © 2011 USPS®. All Rights Reserved.

Error Code	Error Message	Messages
8911	The CustomerGroupID field within the NewSiblingContainer block of the SiblingContainerCreateRequest message is the same value as the CustomerGroupID in the OriginalContainer block. (Container ID: %%1 , Customer Group ID: %%2)	SiblingContainerCreateaResponse, SiblingContainerCancelResponse
8912	The MailingGroupID field within the NewSiblingContainer block of the SiblingContainerCreateRequest message is the same value as the MailingGroupID in the OriginalContainer block. (Container ID: %%1 , Mailing Group ID: %%2)	SiblingContainerCreateResponse
8915	The UniqueContainerBarcode field in the NewSiblingContainer block of the SiblingContainerCreateRequest message is a required field when the FullServiceParticipationIndicator in the OpenMailingGroupRequest message was F. (Container ID: %%1)	SiblingContainerCreateResponse
8916	The UniqueContainerBarcode field in the NewSiblingContainer block of the SiblingContainerCreateRequest message is a required field when the FullServiceParticipationIndicator in the OpenMailingGroupRequest message was M. (Container ID: %%1)	SiblingContainerCreateResponse
8930	The combination of MailingGroupID and CustomerGroupID in the CustomerMailReportCreateRequest message must be populated with the same values as that of the OpenMailing Group.	CustomerMailReportCreateResponse
8931	The QualificationReportCreateRequest message must be accepted before submitting the CustomerMailReportCreateRequest message for that specified MailingGroupID.	CustomerMailReportCreateResponse
8932	The PostageStatementCreateRequest message must be accepted before submitting the CustomerMailReportCreateRequest message for that specified MailingGroupID.	CustomerMailReportCreateResponse
8935	The PermitType field in the PermitInfo block in the CustomerMailReportInfo block of the CustomerMailReportCreateRequest message must be PI, MT, PC, BR, GH, OI or OM when the PermitNumber field is populated.	CustomerMailReportCreateResponse
8936	The PermitType field in the AdditionalPermitInfo block in the CustomerMailReportInfo block of the CustomerMailReportCreateRequest message must be PI, MT, PC, BR, GH, OI or OM when the PermitNumber field is populated.	CustomerMailReportCreateResponse
8937	The SiblingContainerCreateRequest message cannot be processed after the PostageStatementCreateRequest has been submitted for this Mailing Group. (Orig Container ID: %%1)	SiblingContainerCreateaResponse
8938	The CRID in the SubmittingParty block of the SiblingContainerCancelRequest message must match the CRID of the mailer that created the MailingGroup. (CRID: %%1)	SiblingContainerCancelResponse
8939	The CustomerGroupID field within the OriginalContainer block of the SiblingContainerCancelRequest message is a string between 1 and 25 characters and must match the CustomerGroupID of the existing container. (Container GroupID: %%1)	SiblingContainerCancelResponse
8940	The MailingGroupID field within the OriginalContainer block of the SiblingContainerCancelRequest message is a non-negative integer and must match the MailingGroupID of the existing container. (Mailing Group ID: %%1)	SiblingContainerCancelResponse
8941	The ContainerID fields in the OriginalContainer block of the SiblingContainerCancelRequest message must match the ContainerID fields in the QualificationReportCreateRequest message for the existing container. (Container ID: %%1)	SiblingContainerCancelResponse

Copyright © 2011 USPS®. All Rights Reserved.

Error Code	Error Message	Messages
8942	The CustomerGroupID field within the SiblingToDelete block of the SiblingContainerCancelRequest message must match the CustomerGroupID in the OriginalContainer block. (Container ID: %%1 , Customer Group ID: %%2)	SiblingContainerCancelResponse
8943	The MailingGroupID field within the SiblingToDelete block of the SiblingContainerCancelRequest message must be populated with the same value as the MailingGroupID in the OriginalContainer block. (Container ID: %%1 , Mailing Group ID: %%2)	SiblingContainerCancelResponse
8944	The SiblingContainerCancel message must be submitted and processed before finalization of the postage statement associated to the oldest sibling for Full-Service and Mixed mailings. (Orig Container ID: %%1)	SiblingContainerCancelRequest
8945	The CustomerGroupID in the FullContainerID Block of the ContainerUpdateRequest message must match the CustomerGroupID of the existing container. (Container ID: %%1 , Customer Group ID: %%2)	ContainerUpdateResponse
8946	The MailingGroupID in the FullContainerID Block of the ContainerUpdateRequest message must match the MailingGroupID of the existing container. (MailingGroup ID: %%1)	ContainerUpdateResponse
8947	The ContainerID in the FullContainerID Block of the ContainerUpdateRequest message must match the ContainerID in the QualificationReportCreateRequestMessage for the specified MailingGroupID. (Container ID: %%1)	ContainerUpdateResponse
8948	The UniqueContainerBarcode in the ContainerUpdateRequest FullContainerID block must match the existing container in the Qual Report message for the MailingGroupID and ContainerID. (Container ID: %%1, UniqueContainerBarcode: %%2)	ContainerUpdateResponse
8949	The Reservaton field can only be updated when the ContainerStatus in the SummaryRecordUpdate block of the ContainerUpdateRequest message is populated with T. (Container ID: %%1)	ContainerUpdateResponse
8950	The IMBarcode field can only be updated when the ContainerStatus in the SummaryRecordUpdate block of the ContainerUpdateRequest message is populated with T. (Container ID: %%1)	ContainerUpdateResponse
8951	The ScheduledInductionDateTIme field can only be updated when the ContainerStatus in the SummaryRecordUpdate block of the ContainerUpdateRequest message is populated with T. (Container ID: %%1)	ContainerUpdateResponse
8952	The CSATripID field can only be updated when the ContainerStatus in the SummaryRecordUpdate block of the ContainerUpdateRequest message is populated with T. (Container ID: %%1)	ContainerUpdateResponse
8953	The USPSPickUp field can only be updated when the ContainerStatus in the SummaryRecordUpdate block of the ContainerUpdateRequest message is populated with T. (Container ID: %%1)	ContainerUpdateResponse
8954	The ConsigneeContentID field can only be updated when the ContainerStatus in the SummaryRecordUpdate block of the ContainerUpdateRequest message is populated with T. (Container ID: %%1)	ContainerUpdateResponse

Copyright © 2011 USPS®. All Rights Reserved.

Error Code	Error Message	Messages
8955	The EntryPointADLocaleKey field can only be updated when the ContainerStatus in the SummaryRecordUpdate block of the ContainerUpdateRequest message is populated with T. (Container ID: %%1)	ContainerUpdateResponse
8956	The EntryPointADPostalCode field can only be updated when the ContainerStatus in the SummaryRecordUpdate block of the ContainerUpdateRequest message is populated with T. (Container ID: %%1)	ContainerUpdateResponse
8957	The ScheduledShipDateTIme field can only be updated when the ContainerStatus in the SummaryRecordUpdate block of the ContainerUpdateRequest message is populated with T. (Container ID: %%1)	ContainerUpdateResponse
8958	The ContainerStatus field in the SummaryRecordUpdate block of the ContainerUpdateRequest message must be populated with T when updating a Mail.XML job. (Container ID: %%1, ContainerStatus: %%2)	ContainerUpdateResponse
8959	The PostageStatementMailingDate in the ContainerInfoData block cannot be more than %%1 days in the future of the submission date and cannot be backdated prior to %%2.	QualificationReportCreateResponse, QualificationReportDetailCreateResponse (10.0)
8960	The ScheduledInductionDateTime field in the ContainerInfoData block must be within 30 days of the past or present of the PostageStatementMailingDate.	QualificationReportCreateResponse, QualificationReportDetailCreateResponse (10.0)
8961	The ScheduledShipDateTime field in the ContainerInfoData block must be within 30 days of the past or present of the PostageStatementMailingDate.	QualificationReportCreateResponse, QualificationReportDetailCreateResponse (10.0)
8962	The EntryLocaleKey field in the ContainerInfoData block is required unless the EntryFacilityType field in the ContainerInfoData block is populated with O and no appointment is provided.	QualificationReportCreateResponse, QualificationReportDetailCreateResponse (10.0)
8963	The ScheduledInductionDate field in the SummaryRecordUpdate block of the ContainerUpdateRequest message must be within 30 days of PostageStatementMailingDate field in the QualificationReportCreateRequest message for a Full-Service mailing.	ContainerUpdateResponse
8964	The ScheduledShipDate field in the SummaryRecordUpdate block of the ContainerUpdateRequest message must be within 30 days of the PostageStatementMailingDate field in the QualificationReportCreateRequest message for a Full-Service mailing.	ContainerUpdateResponse
8965	The PublicationNumber in the PermitInfo block or the AdditionalPermitInfo block in the CustomerMailReportInfo block of the CustomerMailReportCreateRequest message cannot be populated.	CustomerMailReportCreateResponse
8967	The ContainerID field of the NewSiblingContainer must be unique within the mailing group. (Container ID: %%1).	SiblingContainerCreateResponse

Copyright © 2011 USPS®. All Rights Reserved.

Error Code	Error Message	Messages
8968	The ContainerID field in the PostageStatementLineItemData block in the PostageStatementCreateRequest message referenced as a sibling container with a ContainerType of M must be linked to an existing physical container. (Container ID: %%1).	PostageStatement CreateResponse
8969	The ContainerID field in the PostageStatementLineItemData block in the PostageStatementCreateRequest message referenced as a sibling container with a ContainerType of L must be linked to an existing physical handling unit. (Container ID: %%1).	Postage Statement Messages
8970	The MailXMLPresentationCategory in the OpenMailingGroupRequest must be populated with M for the SummaryZIPDestinationReportCreateRequest message to be processed.	SummaryZipDestinationReportCreateResponse
8971	The MailXMLPresentationCategory in the OpenMailingGroupRequest must be populated with M for the CustomerMailReportCreateRequest message to be processed.	CustomerMailReportCreateResponse
8972	If the OriginalContainer block UniqueContainerBarcode field is populated in the SiblingContainerCreateRequest or -CancelRequest, it must match the Qual Report ContainerBarcode field. (Container ID: %%1, UniqueContainerBarcode: %%2).	SiblingContainerCreateaResponse, SiblingContainerCancelRequest
8973	Transportation updates cannot be performed on linked containers created at the Consolidator level for all Mail.XML Tray-Based Co-Palletized Full or Mixed-Service mailings. (Container ID: %%1).	OriginalContainerLinkageCreateResponse
8974	A linked container cannot be updated after the associated Postage Statement has been finalized for all Mail. XML Bundle-Based Co-Palletized Full or Mixed-Service mailings. (Container ID: %%1).	OriginalContainerLinkageCreateResponse
8975	Each container in the PostageStatementCreateRequest message must have been submitted in a QualificationReportCreateRequest message.	Postage Statement Messages
8984	Average piece range count error	MailPieceCreateResponse
8985	Duplicate Tray barcode error	QualificationReportCreateResponse, QualificationReportDetailCreateResponse (10.0)
8986	The PermitHolderData block PermitType in the PostageStatementCreateRequest message must be PI, PC, or MT when the PostageStatementCreateRequest RateCategory is S and the OpenMailingGroupRequest MailXMLPresentationCategory is M.	Postage Statement Messages
8987	The SortationLevel must be AJ when the RateLevel is SP in the QualificationReportCreateRequest message and FormType is FC in the QualificationReportCreateRequest message and the MailXMLPresentationCategory is M in the OpenMailingGroupRequest.	QualificationReportCreateResponse
8988	At least one SortationLevel in the QualificationReportCreateRequest message must be set to AJ when the RateCategory is S and the FormType is FC in the PostageStatementCreateRequest and the PresentationCategory is M in the OpenMailingGroupRequest.	Postage Statement Messages

Copyright © 2011 USPS®. All Rights Reserved.

Error Code	Error Message	Messages
8989	The BarcodeID, ServiceTypeCode, MailerID6 or -9, and SerialNumber9 or -6 fields in the MailPieceCreateRequest IMB block must be populated when the OpenMailingGroupRequest MailXMLPresentationCategory is M and FullServiceParticipationIndicator is F or M.	MailPieceCreateResponse
8990	The MailPieceCreateRequest message IMbarcodeLowerSerialization and IMbarcodeUpperSerialization block fields must be populated when the OpenMailingGroupRequest message MailXMLPresentationCategory is M and the FullServiceParticipationIndicator is F or M.	MailPieceCreateResponse
8991	The AutomationAddressMatchDate cannot be more than 90 calendar days before the PostageStatementMailingDate when RateCategory is A, B, D, or O for carrier route mail.	Postage Statement Messages
8992	The AutomationAddressMatchDate cannot be more than 180 calendar days before the PostageStatementMailingDate when RateCategory is E, H, L, L1, L2, L3, or L4 for non-carrier route automation mail.	Postage Statement Messages
8993	When the PeriodicalPrice field within the PeriodicalLineItemData block is set to 1, the sum of DiscountQty must be greater than 0 and less than or equal to the sum of Pieces for In-County Piece Prices.	Postage Statement Messages
8994	The InOutCountyIndicator field must be set to I when the PeriodicalPrice field is set to 1 within the PeriodicalLineItemData block of the PeriodicalStatementCreateRequest message.	Postage Statement Messages
8995	The Zone field must be set to DDU when the PeriodicalPrice field is set to 1 within the PeriodicalLineItemData block of the PeriodicalStatementCreateRequest message.	Postage Statement Messages
8996	The InOutCountyIndicator field must be set to I when the PeriodicalPrice field is set to 1 within the PeriodicalLineItemData block within the PeriodicalStatement block of the ConsolidatedPeriodicalStatementCreateRequest message.	Postage Statement Messages
8997	The Zone field must be set to DDU when the PeriodicalPrice field is set to 1 within the PeriodicalLineItemData block within the PeriodicalStatement block of the ConsolidatedPeriodicalStatementCreateRequest message.	Postage Statement Messages
8998	When the PeriodicalPrice field is set to 1 and the mailing does not contain In-County Addressed Supplements, the sum of DiscountQty must be greater than 0 and less than or equal to the number of Copies for In-County Pound Prices.	Postage Statement Messages
8999	The postage statement with statement ID: %%1, has been frozen and cannot be cancelled.	Postage Statement Messages
9000	PendingPostageAmount cannot be provided when the PublicationNumber is provided in the PermitPublicationData block within the CreatePeriodicalStatementData block of the PeriodicalStatementCreateRequest message. (User Postage Statement ID: %%1)	Postage Statement Messages

Copyright © 2011 USPS®. All Rights Reserved.

Error Code	Error Message	Messages
9001	PendingPostageAmount cannot be provided when the PublicationNumber is provided in the PermitPublicationData block within the PeriodicalStatement block of the ConsolidatedPeriodicalStatementCreateRequest message. (User Postage Statement ID: %%1)	Postage Statement Messages
9002	There can be no more than 999 unique CustomerReferenceIDs submitted in the PostageStatementCreateRequest, PeriodicalStatementCreateRequest, or ConsolidatedPeriodicalStatementCreateRequest messages submitted to a single Mail.XML MailingGroupID.	Postage Statement Messages
9003	The PostageStatementMailingDate field in the ContainerInfoData block in the QualificationReportCreateRequest message cannot span the price change date; within a job these dates must either be all before or all after %%1.	QualificationReportCreateResponse
9004	The PostageStatementMailingDate field cannot be more than %%1 days in the future of the submission date and cannot be backdated prior to %%2.	QualificationReportCreateResponse, QualificationRaeportDetailCreateResponse (10.0)
9005	The PostageStatementMailingDate fields within a Mailing Group cannot span a price change date; they must be populated with all dates either before or after %%1.	Multiple
9006	The Zone field in the ContainerDetailData block must be populated when the FormType is PE for Periodicals.	QualificationReportCreateResponse
9008	A Transportaion Update when ContainerStatus is T cannot be submitted more than 30 calendar days after the PostageStatementMailingDate.	ContainerUpdateResponse
9012	StandardFlatType must be the same for all DocumentVersionData, PostageStatementLineItemData, and LineItemSummaryData blocks within a PostageStatementCreateRequest message.	Postage Statement Messages
9013	The ContainerType field in the ContainerInfoData block contains an invalid value; ContainerType AB is not supported.	QualificationReportCreateResponse, QualificationReportDetailCreateResponse (10.0)
9014	The maximum weight for Standard Mail Automation Carrier Route Letters is 3.5 ounces.	Postage Statement Messages
9015	The ProcessingCategory in the PeriodicalStatement or CreatePeriodicalStatement blocks must be set to FL when the SortationLevel in the QualificationReportCreateRequest or BundleDetailCreateRequest is set to E or F.	Postage Statement Messages
9016	The ProcessingCategory in the PeriodicalStatement or CreatePeriodicalStatement blocks must be set to FL when the BundleLevel in the BundleDetail block in the BundleDetailCreateRequest is set to X.	Postage Statement Messages
9017	The BundleLevel in the BundleDetailCreateRequest must be set to X when the associated SortationLevel in the QualificationReportCreateRequest or BundleDetailCreateRequest is set to E or F for Periodicals.	BundleDetailCreateResponse

Copyright © 2011 USPS®. All Rights Reserved.

Error Code	Error Message	Messages
9018	The ContainerType in the QualificationReportCreateRequest must be set to P, Z, H, A, G, D, R, or C when the associated SortationLevel in the QualificationReportCreateRequest is set to E or F for Periodicals.	QualificationReportCreateResponse
9019	The FormType field must be set to First-Class Mail or Standard Mail for a co-palletized mailing with the Container Type field set to F, O or T	QualificationReportCreateResponse
9023	The EntryPointFacilityType in the ContainerInfoData block cannot be populated with N when the FullServiceParticipationIndicator in the OpenMailingGroupRequest message is F or M.	QualificationReportCreateResponse
9024	The CSAID in the ContainerInfoData block must be populated with a 10 digit numeric between 1000000000 and 9999999999 when the FullServiceParticipationIndicator in the OpenMailingGroupRequest message is F or M.	QualificationReportCreateResponse, QualificationReportDetailCreateResponse (10.0)
9026	When the mailing is Full-Service or Mixed Service, the ConsigneeApptID in the ContainerInfoData block must be populated with one of the formats specified in the Mail.XML Tech Spec.	QualificationReportCreateResponse, QualificationReportDetailCreateResponse (10.0)
9027	The EntryPointADLocaleKey in the SummaryRecordUpdate block must be populated with 6 alphanumeric characters and cannot be populated with ORIGIN when the EntryPointFacilityType is O, the ContainerStatus is T and the mailing is Mixed or Full -Service.	ContainerUpdateResponse
9029	When the mailing is Full-Service or Mixed Service and the ContainerStatus in the SummaryRecordUpdate block is T, the ReservationNumber in the SummaryRecordUpdate block must be populated with one of the formats specified in the Mail.XML Tech Spec.	ContainerUpdateResponse
9031	The piece weight for First-Class Commercial Plus Parcels must be greater than or equal to 3.5oz and less than 16oz.	Postage Statement Messages
9032	The SurchargeType in the PostageStatementLineItemData or LineItemSummaryData block must be populated with N for First-Class Commercial Plus Parcels.	Postage Statement Messages
9033	PermitType field in the PermitPublicationData block in the PermitHolderForAPData block must be populated with PI or OI.	Postage Statement Messages
9034	The maximum weight for Package Services Bound Printed Matter non-barcoded Flats is 15 pounds.	Postage Statement Messages
9035	The maximum weight for Package Services Media/ Library Mail non-barcoded Flats is 70 pounds.	Postage Statement Messages
9036	The version weight for Periodical and Pending Periodical non-machinable Flats cannot be greater than 4.4 pounds (Postg Stmt. %%1).	Postage Statement Messages
9037	When submitting multiple MailPieceCreateRequest messages, the messages may only contain MailPieceBlockGroups or MailXMLPieceRangeBlockGroups, but not both within the same Mailing Group.	MailPieceCreateResponse

Copyright © 2011 USPS®. All Rights Reserved.

Error Code	Error Message	Messages
9038	The ContainerBarcode in the ContainerInfoData block must be unique below the configurable threshold (%%1) when the mailing is Full-Service or Mixed Service. (Container Barcode: %%2).	QualificationReportCreateResponse, QualificationReportDetailCreateResponse (10.0)
9040	The FormType field contains an invalid value; it must contain FC or SM when the USPSPriceIncentiveType field is populated with MobileBarcode.	Multiple
9041	The PermitType field contains an invalid value; it must contain PI when the USPSPriceIncentiveType field is populated with MobileBarcode.	Multiple
9042	The ProcessingCategory field contains an invalid value; it must contain FL,LT, or CD when the USPSPriceIncentiveType field is populated with MobileBarcode.	Multiple
9043	The PostageStatementMailingDateTime field must be populated with a date between %%1 and %%2.	Multiple
9045	The PostageStatementMailingDateTime field must be populated with a date between %%1 and %%2 for an update submission when the USPSPriceIncentiveType field is populated with MobileBarcode.	ContainerUpdateResponse
9046	The PostageStatementMailingDateTime field must be populated between %%1 and %%2 for an update submission when the .cpt Postal Price Incentive Type of the Mail.dat original submission is populated with MB.	ContainerUpdateResponse
9061	ScheduledInductionDateTime field in the ContainerInfoData block is required when USPSPickUp field in the ContainerInfoData block is No and the FullServiceParticipationIndicator in the OpenMailingGroupRequest message is F or M.	QualificationReportCreateResponse (9.0)
9061	ScheduledInductionDateTime field in the ContainerInfoData block is required when USPSPickUp field in the ContainerInfoData block is No and the FullServiceParticipationIndicator field in the OpenMailingGroupRequest message is F or M.	QualificationReportDetailCreateResponse (10.0)
9062	The EntryPointFacilityType field in the ContainerInfoData block cannot be populated with B, D, or S when the FormType field in the QualificationReport block of the QualificationReportCreateRequest message is populated with FC.	OpenMailingGroupRequest, QualificationReportCreateResponse
9063	The EntryPointFacilityType field in the ContainerInfoData block cannot be populated with B, D, or S when the FormType field in the QualificationReport block of the QualificationReportSummaryCreateRequest message is populated with FC.	QualificationReportDetailCreateResponse (10.0)
9064	The CSAID field in the ContainerInfoData block is required when the FormType field in the QualificationReport block is FC and the SortationLevel in the ContainerInfoData block is AK, AL, AM, AN, AO, AP, or AQ.	QualificationReportDetailCreateResponse (9.0C)
9065	The CSAID field in the ContainerInfoData block is required when the FormType in the QualificationReport block of the QualificationReportSummaryCreateRequest message is FC and SortationLevel in the ContainerInfoData block is AK, AL, AM, AN, AO, AP or AQ.	QualificationReportDetailCreateResponse (10.0)

Copyright © 2011 USPS®. All Rights Reserved.

Error Code	Error Message	Messages
9067	OpenMailingGroupRequest message must be accepted before submitting the QualificationReportSummaryCreateRequest message for the specified MailingGroupID and CustomerGroupID.	QualificationReportDetailCreateResponse (10.0)
9068	The CustomerQualificationReportID field in the QualificationReportSummary block of the QualificationReportSummaryCreateRequest message must be populated with a unique value within a MailingGroupID.	QualificationReportSummaryCreateResponse (10.0)
9070	The FormType field in the QualificationReportSummary block contains an invalid value; it must contain FC, PE, PP, SM, BP, ML, or PM.	QualificationReportSummaryCreateResponse (10.0)
9072	OpenMailingGroupRequest message must be accepted before submitting the QualificationReportDetailCreateRequest message for the specified MailingGroupID and CustomerGroupID.	QualificationReportDetailCreateResponse (10.0)
9073	The CustomerQualificationReportID field in the QualificationReportDetailCreateRequest message must match an existing CustomerQualificationReportID from an accepted QualificationReportSummaryCreateRequest message within a MailingGroupID.	QualificationReportDetailCreateResponse (10.0)
9074	InOutCountyIndicator field in the ContainerDetailData block in the ContainerInfoData block in the QualificationReport block is required when FormType in the QualificationReportSummaryRequest message is PE. (Container ID: %%1)	QualificationReportDetailCreateResponse (10.0)
9075	PermitNumber field in the DocumentVersionDataWithPermit block in the QualificationReport block is required when the FormType in the QualificationReportSummaryCreateRequest message is PM, FC, SM, BP, PP, or ML. Form type is: %%2	QualificationReportDetailCreateResponse (10.0)
9076	PermitZIP4 field within PermitPublicationData block in the DocumentVersionDataWithPermit block in the QualificationReport block is required when the FormType in the QualificationReportSummaryCreateRequest message is PM, FC, SM, BP, PP, or ML.	QualificationReportDetailCreateResponse (10.0)
9077	PublicationNumber field in the PermitPublicationData block in the DocumentVersionDataWithPermit block should not be populated when the FormType in the QualificationReportSummaryRequest message is not populated with PE for Periodicals or Pending Periodicals.	QualificationReportDetailCreateResponse (10.0)
9078	All QualificationReportDetailCreateRequest messages must be accepted before submitting the associated BundleDetailCreateRequest message for the specified MailingGroupID and CustomerGroupID.	BundleDetailCreateResponse
9079	All QualificationReportDetailCreateRequest messages must be accepted before submitting the associated ContainerBundleReportCreateRequest message for the specified MailingGroupID and CustomerGroupID.	ContainerBundleReportCreateResponse
9080	ContainerBundleReportCreateRequest message can only be provided when the FormType in the QualificationReportSummaryCreateRequest message is PE.	ContainerBundleReportCreateResponse
9081	All QualificationReportDetailCreateRequest messages must be accepted before submitting the associated MailPieceCreateRequest message to create a piece range for the specified MailingGroupID and CustomerGroupID.	MailPieceCreateResponse

Copyright © 2011 USPS®. All Rights Reserved.

Error Code	Error Message	Messages
9082	All QualificationReportDetailCreateRequest messages must be accepted before submitting the associated MailPieceCreateRequest message to create a mail piece for the specified MailingGroupID and CustomerGroupID.	MailPieceCreateResponse
9083	At least one QualificationReportDetailCreateRequest ContainerInfoData block must have a ContainerType of L or M if the LogicalPhysicalIndicator in the OpenMailingGroupRequest is L, MailXMLPresentationCategory is P, FullServiceParticipationIndicator is F or M.	QualificationReportDetailCreateRequest (10.0)
9084	All QualificationReportDetailCreateRequest messages must be accepted before submitting the associated PostageStatementCreateRequest message for the specified MailingGroupID and CustomerGroupID.	Postage Statement Messages
9085	PieceWeight field in the DocumentVersionDataWithPermit block must be less than or equal to 13 oz when the ProcessingCategory field is populated with FL and the FormType field in the QualificationReportSummaryCreateRequest message is populated with FC.	QualificationReportDetailCreateRequest (10.0)
9088	ProcessingCategory field in the ContainerInfoData block must be populated with LT when the FormType field in the QualificationReportSummaryCreateRequest message is populated with ‘SM’ for MLOCR mailings.	QualificationReportDetailCreateRequest (10.0)
9089	PieceWeight field in the DocumentVersionDataWithPermit block cannot exceed 3.3 ounces when the ProcessingCategory field in the ContainerInfoData block is LT and the FormType field in the QualificationReportSummaryCreateRequest message is SM.	QualificationReportDetailCreateRequest (10.0)
9090	All QualificationReportDetailCreateRequest messages must be accepted before submitting the associated OriginalContainerLinkageCreateRequest message for the specified MailingGroupID and CustomerGroupID.	OriginalContainerLinkageCreateResponse
9091	A ContainerDetailID field submitted in the MailPieceCreateRequest message must match a ContainerDetailID field submitted in the associated QualificationReportDetailCreateRequest message. (ContainerDetailID %%1 missing for ContainerID %%2)	MailPieceCreateResponse
9092	A ContainerDetailID field submitted in the PostageStatementCreateRequest message must match a ContainerDetailID field submitted in the associated QualificationReportDetailCreateRequest message. (ContainerDetailID %%1 missing for ContainerID %%2)	Postage Statement Messages
9093	A ContainerDetailID field submitted in the PeriodicalStatementCreateRequest message must match a ContainerDetailID field submitted in the associated QualificationReportDetailCreateRequest message. (ContainerDetailID %%1 missing for ContainerID %%2)	Postage Statement Messages
9094	A ContainerDetailID field submitted in the ConsolidatedPeriodicalStatementCreateRequest message must match a ContainerDetailID field in the associated QualificationReportDetailCreateRequest message. (ContainerDetailID %%1 missing for ContainerID %%2)	Postage Statement Messages

Copyright © 2011 USPS®. All Rights Reserved.

Error Code	Error Message	Messages
9095	The number of pieces for a ContainerDetailID submitted in the MailPieceCreateRequest cannot exceed number of pieces associated to that ContainerDetailID field in the QualificationReportDetailCreateRequest. (ContainerDetailID %%1 within ContainerID %%2)	MailPieceCreateResponse
9096	ParentContainerID field in the QualificationReportDetailCreateRequest message is required when the IncludedInOtherDoc field is L and the SiblingContainerID is null. (ContainerDetailID %%1 missing for ContainerID %%2)	QualificationReportDetailCreateResponse (10.0)
9098	The ContainerID fields in the OriginalContainer block of the SiblingContainerCreateRequest message must match the ContainerID fields in the QualificationReportDetailCreateRequest message for the existing container. (Container ID: %%1)	SiblingContainerCreateResponse
9099	All QualificationReportDetailCreateRequest messages must be accepted before submitting the associated SummaryZipDestinationReportCreateRequest message for the specified MailingGroupID and CustomerGroupID.	SummaryZipDetaintationReportCreateResponse
9100	All QualificationReportDetailCreateRequest messages must be accepted before submitting the associated CustomerMailReportCreateRequest message for the specified MailingGroupID and CustomerGroupID.	CustomerMailReportCreateResponse
9101	The ContainerID fields in the FullContainer block of the ContainerUpdateRequest message must match the ContainerID fields in the Qualification Report for the existing container. (Container ID: %%1)	ContainerUpdateResponse
9102	The ScheduledInductionDate field in the SummaryRecordUpdate block of the ContainerUpdateRequest message must be within 30 days of PostageStatementMailingDate field in the QualificationReportDetailCreateRequest message for a Full-Service mailing.	ContainerUpdateResponse
9103	The ScheduledShipDate field in the SummaryRecordUpdate block of the ContainerUpdateRequest message must be within 30 days of PostageStatementMailingDate field in the QualificationReportDetailCreateRequest message for a Full-Service mailing.	ContainerUpdateResponse
9105	The SortationLevel must be AJ when the RateLevel is SP in the QualificationReportDetailCreateRequest message and FormType is FC in the QualificationReportSummaryCreateRequest message and the MailXMLPresentationCategory is M in the OpenMailingGroupRequest.	QualificationReportDetailCreateResponse (10.0)
9106	At least one SortationLevel in the Qualification Report message must be AJ when the RateCategory is S and the FormType is FC in the PostageStatementCreateRequest and the MailXMLPresentationCategory is M in the OpenMailingGroupRequest.	QualificationReportDetailCreateResponse (10.0)
9107	The ProcessingCategory in the PeriodicalStatement or CreatePeriodicalStatement blocks must be set to FL when the SortationLevel in the Qualification Report or BundleDetailCreateRequest is set to E or F.	Postage Statement Messages

Copyright © 2011 USPS®. All Rights Reserved.

Error Code	Error Message	Messages
9109	The ContainerType in the QualificationReportDetailCreateRequest must be set to P, Z, H, A, G, D, R, or C when the associated SortationLevel in the QualificationReportDetailCreateRequest is set to E or F for Periodicals.	QualificationReportDetailCreateResponse (10.0)
9111	PostageStatementMailingDate in the CreatePostageStatement block must match the PostageStatementMailingDate in QualificationReportDetailCreateRequest message when it's populated for the same ContainerID for the specified MailingGroupID and CustomerGroupID.	Postage Statement Messages
9112	The ContainerID fields in the OriginalContainer block of the SiblingContainerCancelRequest message must match the ContainerID fields in the QualificationReportDetailCreateRequest message for the existing container. (Container ID: %%1)	SiblingContainerCancelResponse
9113	ContainerID must be populated with the same value as the ContainerID in the ContainerInfoData block of the QualificationReportDetailCreateRequest message for the specified MailingGroupID and CustomerGroupID. Found Missing ContainerID: %%1	BundleDetailCreateResponse
9114	VersionID must be populated with the same value as the VersionID in the ContainerDetailData block of the QualificationReportDetailCreateRequest message for the specified MailingGroupID and CustomerGroupID. Found Missing VersionID: %%1	BundleDetailCreateResponse
9115	The count of the Copies field in the PeriodicalLineItemData block must be equal to the sum of NonCopies and SubreqCopies in the PeriodicalStatementCreateRequest message.	Postage Statement Messages
9116	The count of the Copies field in the PeriodicalLineItemData block must be equal to the sum of NonCopies and SubreqCopies in the ConsolidatedPeriodicalStatementCreateRequest message.	Postage Statement Messages
9130	The FormType field in the CreatePostageStatement block must be populated with PM when the ContainerType field in the PostageStatementLineItemData block is 6, 7, 8, 9, 10, or 11.	Postage Statement Messages
9132	The FormType field in the QualificationReport block of the QualificationReportSummaryCreateRequest message must be populated with PM when the ContainerType field in the ContainerInfoData block is 6, 7, 8, 9, 10, or 11.	Postage Statement Messages
9133	The FormType field in the CreatePostageStatement block must be populated with PM when the RateCategory field in the associated postage statement is P10, P11, P12, P13, P14, P15, or P16.	Postage Statement Messages
9136	The maximum weight for a Priority Mail cubic mail piece is 20lbs.	Postage Statement Messages
9137	The CRID field within the QualificationReportPreparer block in the QualificationReport block is required.	QualificationReportSummaryCreateResponse (10.0)
9138	The FormType in the qualification report must be set to FC when the SortationLevel in the is set to AK, AL, AM, AN, AO, AP, or AQ.	QualificationReportCreateResponse, QualificationReportDetailCreateResponse (10.0)

Copyright © 2011 USPS®. All Rights Reserved.

Error Code	Error Message	Messages
9139	The PMODIndicator field in the DocumentVersionData block must be populated with Yes when the ContainerType is populated with 6, 7, 8, 9, 10, or 11.	Postage Statement Messages
9140	The PMODIndicator field in the DocumentVersionData block must be populated with Yes when the RateCategory is populated with P12, P13, P14, P15, or P16.	Postage Statement Messages
9141	The FormType field in the CreatePostageStatement block must be populated with PM when the FlatRateIndicator is populated with O, C, P, or F.	Postage Statement Messages
9142	The IssueDate field in the MailXMLPostageStatementRequestHeaderInfo block of the ConsolidatedPeriodicalStatementCreateRequest message must match IssueDate field in the MailXMLPostageStatementRequestHeaderInfo block of BeginCombinedMailingRequest message.	Postage Statement Messages
9143	IssueNumber field in the MailXMLPostageStatementRequestHeaderInfo block of the ConsolidatedPeriodicalStatementCreateRequest message must match IssueNumber field in the MailXMLPostageStatementRequestHeaderInfo block of BeginCombinedMailingRequest message.	Postage Statement Messages
9144	VolumeNumber field in MailXMLPostageStatementRequestHeaderInfo block of the ConsolidatedPeriodicalStatementCreateRequest message must match VolumeNumber field in the MailXMLPostageStatementRequestHeaderInfo block of BeginCombinedMailingRequest message.	Postage Statement Messages
9145	CustomerReferenceID field in MailXMLPostageStatementRequestHeaderInfo block of ConsolidatedPeriodicalStatementCreateRequest message must match CustomerReferenceID in MailXMLPostageStatementRequestHeaderInfo block of BeginCombinedMailingRequest message.	Postage Statement Messages
9146	AgencyCostCode field in MailXMLPostageStatementRequestHeaderInfo block of the ConsolidatedPeriodicalStatementCreateRequest message must match AgencyCostCode field in MailXMLPostageStatementRequestHeaderInfo block of BeginCombinedMailingRequest message.	Postage Statement Messages
9147	PermitNumber field in MailXMLPostageStatementRequestHeaderInfo block of the ConsolidatedPeriodicalStatementCreateRequest message must match PermitNumber field in MailXMLPostageStatementRequestHeaderInfo block of BeginCombinedMailingRequest message.	Postage Statement Messages
9148	PermitType field in the MailXMLPostageStatementRequestHeaderInfo block of the ConsolidatedPeriodicalStatementCreateRequest message must match PermitType field in the MailXMLPostageStatementRequestHeaderInfo block of BeginCombinedMailingRequest message.	Postage Statement Messages

Copyright © 2011 USPS®. All Rights Reserved.

Error Code	Error Message	Messages
9149	PermitZip4 field in MailXMLPostageStatementRequestHeaderInfo block of the ConsolidatedPeriodicalStatementCreateRequest message must match PermitZip4 field in MailXMLPostageStatementRequestHeaderInfo block of BeginCombinedMailingRequest message.	Postage Statement Messages
9150	PublicationNumber field in MailXMLPostageStatementRequestHeaderInfo block of the ConsolidatedPeriodicalStatementCreateRequest message must match PublicationNumber in MailXMLPostageStatementRequestHeaderInfo block of BeginCombinedMailingRequest message.	Postage Statement Messages
9151	PostageStatementMethod in MailXMLPostageStatementRequestHeaderInfo block of ConsolidatedPeriodicalStatementCreateRequest message must match PostageStatementMethod in MailXMLPostageStatementRequestHeaderInfo block of BeginCombinedMailingRequest message.	Postage Statement Messages
9152	RateType field in the MailXMLPostageStatementRequestHeaderInfo block of the ConsolidatedPeriodicalStatementCreateRequest message must match RateType field in the MailXMLPostageStatementRequestHeaderInfo block of BeginCombinedMailingRequest message.	Postage Statement Messages
9153	ProcessingCategory field in MailXMLPostageStatementRequestHeaderInfo block of the ConsolidatedPeriodicalStatementCreateRequest message must match ProcessingCategory MailXMLPostageStatementRequestHeaderInfo block of BeginCombinedMailingRequest message.	Postage Statement Messages
9154	IssueDate field in the MailXMLPostageStatementRequestHeaderInfo block of the ConsolidatedPeriodicalStatementCreateRequest message must match IssueDate field in the MailXMLPostageStatementRequestHeaderInfo block of EndCombinedMailingRequest message.	Postage Statement Messages
9155	IssueNumber field in the MailXMLPostageStatementRequestHeaderInfo block of the ConsolidatedPeriodicalStatementCreateRequest message must match IssueNumber field in the MailXMLPostageStatementRequestHeaderInfo block of EndCombinedMailingRequest message.	Postage Statement Messages
9156	VolumeNumber field in MailXMLPostageStatementRequestHeaderInfo block of the ConsolidatedPeriodicalStatementCreateRequest message must match VolumeNumber field in the MailXMLPostageStatementRequestHeaderInfo block of EndCombinedMailingRequest message.	Postage Statement Messages
9157	CustomerReferenceID field in MailXMLPostageStatementRequestHeaderInfo block of ConsolidatedPeriodicalStatementCreateRequest message must match CustomerReferenceID in MailXMLPostageStatementRequestHeaderInfo block of EndCombinedMailingRequest message.	Postage Statement Messages

Copyright © 2011 USPS®. All Rights Reserved.

Error Code	Error Message	Messages
9158	AgencyCostCode field in MailXMLPostageStatementRequestHeaderInfo block of the ConsolidatedPeriodicalStatementCreateRequest message must match AgencyCostCode field in MailXMLPostageStatementRequestHeaderInfo block of EndCombinedMailingRequest message	Postage Statement Messages
9159	PermitNumber field in MailXMLPostageStatementRequestHeaderInfo block of the ConsolidatedPeriodicalStatementCreateRequest message must match PermitNumber field in MailXMLPostageStatementRequestHeaderInfo block of EndCombinedMailingRequest message.	Postage Statement Messages
9160	PermitType field in the MailXMLPostageStatementRequestHeaderInfo block of the ConsolidatedPeriodicalStatementCreateRequest message must match PermitType field in the MailXMLPostageStatementRequestHeaderInfo block of EndCombinedMailingRequest message.	Postage Statement Messages
9161	The PermitZip4field in MailXMLPostageStatementRequestHeaderInfo block of the ConsolidatedPeriodicalStatementCreateRequest message must match PermitZip4field in MailXMLPostageStatementRequestHeaderInfo block of EndCombinedMailingRequest message.	Postage Statement Messages
9162	PublicationNumber field in MailXMLPostageStatementRequestHeaderInfo block of the ConsolidatedPeriodicalStatementCreateRequest message must match PublicationNumber in MailXMLPostageStatementRequestHeaderInfo block of EndCombinedMailingRequest message.	Postage Statement Messages
9163	PostageStatementMethod in MailXMLPostageStatementRequestHeaderInfo block of ConsolidatedPeriodicalStatementCreateRequest message must match PostageStatementMethod in MailXMLPostageStatementRequestHeaderInfo block of EndCombinedMailingRequest message.	Postage Statement Messages
9164	RateType field in the MailXMLPostageStatementRequestHeaderInfo block of the ConsolidatedPeriodicalStatementCreateRequest message must match RateType field in the MailXMLPostageStatementRequestHeaderInfo block of EndCombinedMailingRequest message.	Postage Statement Messages
9165	ProcessingCategory field in MailXMLPostageStatementRequestHeaderInfo block of the ConsolidatedPeriodicalStatementCreateRequest message must match ProcessingCategory MailXMLPostageStatementRequestHeaderInfo block of EndCombinedMailingRequest message.	Postage Statement Messages
9167	The FormType field in the QualificationReport block of the QualificationReportSummaryCreateRequest message must be populated with FC when the ContentOfMail field in the DocumentVersionWithPermit block is populated with F.	QualificationReportSummaryCreateResponse (10.0)

Copyright © 2011 USPS®. All Rights Reserved.

Error Code	Error Message	Messages
9168	The FormType field in the CreatePostageStatement block must be populated with FC when the ContentOfMailType field in the DocumentVersionData block is populated with F.	Postage Statement Messages
9170	The ProcessingCategory field in the ContainerInfoData block must be populated with LT or FL when the ContentOfMail field in the DocumentVersionDataWithPermit block is populated with F.	QualificationReportDetailCreateResponse (10.0)
9171	The ProcessingCategory field must be populated with LT or FL when the ContentOfMailType field in the DocumentVersionData block is populated with F.	QualificationReportDetailCreateResponse (10.0)
9173	When ContentOfMail in the DocumentVersionDataWithPermit block or ContentOfMailType in the DocumentVersionData block is set to F, then all instances of those fields in the Mailing Group must also be set to F.	QualificationReportDetailCreateResponse (10.0)
9175	A postage statement may not be resubmitted with the EstimateIndicator field in the CreatePostageStatement block populated with Yes after the postage statement was previously submitted with an EstimateIndicator value of No.	Postage Statement Messages
9179	For eInduction processing, the ContainerBarcode field in the ContainerInfoData block must be populated when the corresponding ContainerType in the ContainerInfoData block is P, H, A, G, D, R, C, or Z.	QualificationReportCreateResponse (9.0C) QualificationReportDetailCreateResponse (10.0C)
9180	For eInduction processing, the EntryLocaleKey field in the ContainerInfoData block must be populated when the corresponding ContainerType is P, H, A, G, D, R, C, Z, M, T, O, E, F, S, 1, 2, 3, or L and the container is not a sibling. Note: This validation will be configurable in that it can be turned on or off as necessary.	QualificationReportCreateResponse (9.0C) QualificationReportDetailCreateResponse (10.0C)
9181	For eInduction processing, the ContainerBarcode field in the ContainerInfoData block must contain exactly 21 characters when the corresponding ContainerType in the ContainerInfoData block is P, H, A, G, D, R, C, or Z.	QualificationReportCreateResponse (9.0C) QualificationReportDetailCreateResponse (10.0C)
9182	For eInduction processing, the ContainerBarcode field in the ContainerInfoData block must begin with ‘99M’ when the corresponding ContainerType in the ContainerInfoData block is P, H, A, G, D, R, C, or Z.	QualificationReportCreateResponse (9.0C) QualificationReportDetailCreateResponse (10.0C)
9183	For eInduction processing, the ContainerBarcode field in the ContainerInfoData block for IMcb(s)/pallets must be unique within the mailing group and amongst all containers associated to the SubmittingParty CRID that were finalized within the last 45 days.	QualificationReportCreateResponse (9.0C) QualificationReportDetailCreateResponse (10.0C)

Copyright © 2011 USPS®. All Rights Reserved.

Error Code	Error Message	Messages
9184	For eInduction processing, the ContainerBarcode field in the ContainerInfoData block for IMcb(s)/pallets must be unique within the mailing group and amongst all containers finalized within the last 45 days. Note: This validation will be a warning. In addition, this validation will be configurable in that it can be turned on or off as necessary.	QualificationReportCreateResponse (9.0C) QualificationReportDetailCreateResponse (10.0C)
9185	The CustomerReferenceID field in the PeriodicalStatement block must contain one value in the ConsolidatedPeriodicalStatementCreateRequest message.	Postage Statement Messages
9188	The MixedMailFlag field in the MailXMLQualReportRequestHeaderInfo block of the QualificationReportDetailCreateRequest must match the MixedMailFlag field in MailXMLQualReportRequestHeaderInfo block of QualificationReportSummaryCreateRequest message.	QualificationReportCreateResponse (9.0C) QualificationReportDetailCreateResponse (10.0C)
9191	The MailerID6 field in the SubmittingParty block of the QualificationReportDetailCreateRequest message must match the MailerID6 field in the SubmittingParty block of the QualificationReportSummaryCreateRequest message.	QualificationReportDetailCreateResponse (10.0C)
9192	The MailerID9 field in the SubmittingParty block of the QualificationReportDetailCreateRequest message must match the MailerID9 field in the SubmittingParty block of the QualificationReportSummaryCreateRequest message.	QualificationReportDetailCreateResponse (10.0C)
9194	The ShippingAgent field in the SubmittingParty block of the QualificationReportDetailCreateRequest message must match the ShippingAgent field in the SubmittingParty block of the QualificationReportSummaryCreateRequest message.	QualificationReportDetailCreateResponse (10.0C)
9195	The ReceivingAgent field in the SubmittingParty block of the QualificationReportDetailCreateRequest message must match the ReceivingAgent field in the SubmittingParty block of the QualificationReportSummaryCreateRequest message.	QualificationReportDetailCreateResponse (10.0C)
9196	The SoftwareName field in the SubmittingSoftware block of the QualificationReportDetailCreateRequest message must match the SoftwareName field in the SubmittingSoftware block of the QualificationReportSummaryCreateRequest message.	QualificationReportDetailCreateResponse (10.0C)
9197	The Vendor field in the SubmittingSoftware block of the QualificationReportDetailCreateRequest message must match the Vendor field in the SubmittingSoftware block of the QualificationReportSummaryCreateRequest message.	QualificationReportDetailCreateResponse (10.0C)
9198	The Version field in the SubmittingSoftware block of the QualificationReportDetailCreateRequest message must match the Version field in the SubmittingSoftware block of the QualificationReportSummaryCreateRequest message.	QualificationReportDetailCreateResponse (10.0C)
9199	The ApprovalDate field in the SubmittingSoftware block of the QualificationReportDetailCreateRequest message must match the ApprovalDate field in the SubmittingSoftware block of the QualificationReportSummaryCreateRequest message.	QualificationReportDetailCreateResponse (10.0C)

Copyright © 2011 USPS®. All Rights Reserved.

Error Code	Error Message	Messages
9200	The ApprovalKey field in the SubmittingSoftware block of the QualificationReportDetailCreateRequest message must match the ApprovalKey field in the SubmittingSoftware block of the QualificationReportSummaryCreateRequest message.	QualificationReportDetailCreateResponse (10.0C)
9204	A PMOD package cannot be placed inside a PMOD container for Priority Mail.	Postage Statement Messages
9205	ParentContainerID in the ContainerInfoData block in the QualificationReport block must point to another existing ParentContainerID within the Qualification Report. (Container ID: %%1)	QualificationReportDetailCreateResponse (10.0)
9206	SiblingContainerID field in the ContainerInfoData block in the QualificationReport block must point to a different container within the Qualification Report. (Container ID: %%1)	QualificationReportDetailCreateResponse (10.0)
9208	The PMODIndicator must be populated with the same value for all postage statements in a mailing group.	Postage Statement Messages
9209	The submitted StatementID does not exist.	ContainerManifestCreateResponse (10.0)
9210	At least one ContainerID submitted in the ContainerManifestCreateRequest must be associated to an IM Container Barcode provided in the IMcb field.	ContainerManifestCreateResponse (10.0)
9211	The combination of ContainerID and StatementID must be unique within the submitted ContainerManifestCreateRequest message.	ContainerManifestCreateResponse (10.0)
9213	The TotalDocVersionWithPermitBlocksCount must match number of DocumentVersionDataWithPermit blocks submitted in the QualificationReportDetailCreateRequest message.	QualificationReportDetailCreateResponse (10.0)
9215	ProcessingCategory must be populated with FL, NP, MP, or IR when the FormType in the QualificationReportSummaryCreateRequest message is BP.	QualificationReportDetailCreateResponse (10.0)
9216	Zone must be populated with N, 1, 3, 4, 5, 6, 7, 8, DDU or SCF when FormType field in the QualificationReportSummaryCreateRequest message is BP and Processing Category is FL, MP, IR, or NP.	QualificationReportDetailCreateResponse (10.0)
9217	EntryDiscount must be populated with N, B, S or D when FormType field in the QualificationReportSummaryCreateRequest message is BP.	QualificationReportDetailCreateResponse (10.0)
9218	TotalPieces and TotalCopies must be populated with the same values when FormType field in the QualificationReportSummaryCreateRequest message is BP.	QualificationReportDetailCreateResponse (10.0)
9219	ProcessingCategory must be populated with LT, FL, CD, or PF when FormType field in the QualificationReportSummaryCreateRequest message is FC.	QualificationReportDetailCreateResponse (10.0)

Copyright © 2011 USPS®. All Rights Reserved.

Error Code	Error Message	Messages
9220	Zone must be populated with N when FormType field in the QualificationReportSummaryCreateRequest message is FC and ProcessingCategory is LT, FL, CD, or PF.	QualificationReportDetailCreateResponse (10.0)
9221	EntryDiscount must be populated with N when FormType field in the QualificationReportSummaryCreateRequest message is FC.	QualificationReportDetailCreateResponse (10.0)
9222	ProcessingCategory must be populated with FL, MP, NP, or IR when FormType field in the QualificationReportSummaryCreateRequest message is ML.	QualificationReportDetailCreateResponse (10.0)
9223	Zone must be populated with N when FormType field in the QualificationReportSummaryCreateRequest message is ML and ProcessingCategory is MP or IR.	QualificationReportDetailCreateResponse (10.0)
9224	EntryDiscount must be populated with N when FormType field in the QualificationReportSummaryCreateRequest message is ML.	QualificationReportDetailCreateResponse (10.0)
9225	TotalPieces and TotalCopies must be populated with the same values when the FormType field in the QualificationReportSummaryCreateRequest message is ML.	QualificationReportDetailCreateResponse (10.0)
9226	ProcessingCategory must be populated with LT, FL, MP, IR, or NP when FormType field in the QualificationReportSummaryCreateRequest message is PE.	QualificationReportDetailCreateResponse (10.0)
9227	Zone must be populated with N, 1, 3, 4, 5, 6, 7, 8, ICD, ADC, DDU, or SCF when FormType field in the QualificationReportSummaryCreateRequest message is PE and Zone is provided.	QualificationReportDetailCreateResponse (10.0)
9228	ContainerChargeContainerLevel must be populated with 3, 5, A, or M when FormType field in the QualificationReportSummaryCreateRequest message is PE.	QualificationReportDetailCreateResponse (10.0)
9229	InOutCountyIndicator must be populated with N or I when FormType field in the QualificationReportSummaryCreateRequest message is PE.	QualificationReportDetailCreateResponse (10.0)
9230	ProcessingCategory must be populated with LT, FL, MP, IR, NP, CM, NA, or NB when FormType field in the QualificationReportSummaryCreateRequest message is SM. (User Postage Statement ID: %%1).	QualificationReportDetailCreateResponse (10.0)
9231	Zone must be populated with N when FormType FormType field in the QualificationReportSummaryCreateRequest message is SM and ProcessingCategory is LT, FL, MP, IR, or CM. (User Postage Statement ID: %%1).	QualificationReportDetailCreateResponse (10.0)
9232	EntryDiscount must be populated with N, B, S, or D when FormType FormType field in the QualificationReportSummaryCreateRequest message is SM. (User Postage Statement ID: %%1).	QualificationReportDetailCreateResponse (10.0)
9233	The Zone field in the ContainerDetailData block must be populated when the FormType field in the QualificationReportSummaryCreateRequest message is PE for Periodicals.	QualificationReportDetailCreateResponse (10.0)

Copyright © 2011 USPS®. All Rights Reserved.

Error Code	Error Message	Messages
9235	The StandardFlatType field in the DocumentVersionDataWithPermit block must be populated when FormType field in the QualificationReportSummaryCreateRequest message is SM and ProcessingCategory is FL.	QualificationReportDetailCreateResponse (10.0)
9236	A Qualification Report cannot have records with the IncludedInOtherDoc field values set to both O and L.	QualificationReportDetailCreateResponse
9237	QualificationReportDetailCreateRequest for a co-palletized mailing with the ContainerType set to F, O, or T can only be submitted when the FormType in the associated QualificationReportSummaryCreateRequest is FC or SM.	QualificationReportDetailCreateResponse (10.0)
9238	PostageStatementMailingDate in the CreatePeriodicalStatement block must match the PostageStatementMailingDate in QualificationReportDetailCreateRequest message when it's populated for the same ContainerID for the specified MailingGroupID and CustomerGroupID.	Postage Statement Messages
9239	PostageStatementMailingDate in the PeriodicalStatement block must match the PostageStatementMailingDate in QualificationReportDetailCreateRequest message when it's populated for the same ContainerID for the specified MailingGroupID and CustomerGroupID.	Postage Statement Messages
9241	ProcessingCategory field in the ContainerInfoData block must be LT, FL, or CD when the FormType field in the QualificationReportSummaryCreateRequest message is FC and the MailXMLPresentationCategory field in the OpenMailingGroupRequest message is 'M'.	QualificationReportDetailCreateResponse (10.0)
9242	The fields within the DocumentVersionDataWithPermit block for each unique VersionID must match for all QualificationReportDetailCreateRequest messages associated to the same Qualification Report. VersionID (%%1)	QualificationReportDetailCreateResponse (10.0)
9243	The QualificationReportCreateRequest message is not supported in Mail.XML 10.0C.	QualificationReportCreateResponse
9244	The maximum weight for a Priority Mail Regional Rate Box A mail piece is 15 lbs.	Postage Statement Messages
9245	The maximum weight for a Priority Mail Regional Rate Box B mail piece is 20 lbs.	Postage Statement Messages
9246	The PostageStatementMailingDate field in the ContainerInfoData block in the QualificationReportDetailCreateRequest message cannot span the price change date; within a job these dates must either be all before or all after %%1.	QualificationReportDetailCreateResponse (10.0)
9247	The pieces associated to a ContainerDetailID in the Postage-, Periodical-, or ConsolidatedPeriodicalStatementCreateRequest cannot exceed the sum of TotalPieces for that ContainerDetailID in the Qualification Report (ContainerID %%1 ContainerDetailID %%2).	Postage Statement Messages
9248	A ContainerID in the MailPieceCreateRequest must exist in an accepted Qualification Report (Container ID %%1).	MailPieceCreateResponse
9249	A ContainerID in the Postage-, Periodical-, or ConsolidatedPeriodicalStatementCreateRequest must exist in an accepted Qualification Report (Container ID %%1).	Postage Statement Messages

Copyright © 2011 USPS®. All Rights Reserved.

Error Code	Error Message	Messages
9250	FormType field in the QualificationReportSummaryCreateRequest message must be FC or SM when the MailXMLPresentationCategory field in the OpenMailingGroupRequest message is populated with M.	QualificationReportSummaryCreateResponse (10.0)
9251	The number of QualificationReportDetailCreateRequest messages associated to a QualificationReportSummaryCreateRequest message cannot exceed the value populated in the TotalMessageCount field in the QualificationReportSummaryCreateRequest.	QualificationReportDetailCreateResponse
9252	The PostageStatementMailingDate cannot be set to a date on or after the upcoming price change date - %%1	Postage Statement Messages
9254	When PreparedAsSM is True and FormType is PM, then ProcessingCategory must be FL, LT, or PF, and RateCategory must be S.	Postage Statement Messages
9255	For MLOCR mailings, the rate category must be one of E, H, L3, L4, N, or S for Flats or one of E, H, L1, L2, L3, L4, N, or S for Letters.	Postage Statement Messages
9256	The container status cannot be updated to C or D when the container is paid for on a Finalized Postage Statement (CTR ID %%1).	ContainerUpdateCreateResponse
9257	The IMB block must be populated in the MailPieceBlock of the MailPieceCreateRequest message.	MailPieceCreateResponse
9308	The OpenMailingGroupCreateRequest message is no longer accepted for Mail.XML version 7.0C or 8.0B after %SubmitDateCutoff%.	OpenMailingGroupResponse
8004	More than %%1 failures for Warning code: %%2	Multiple Messages

Code	Warning Message	Messages
8357	When ContainerStatus is T, the ContainerUpdate message can only update the the Transportation Update fields listed in the Mail.XML Technical Specification. (Container ID: %%1)	ContainerUpdateResponse
8359	Postage cancellation will occur when the ContainerStatus is C or D and the Container Status from the original Mail.dat job is R and the postage statement status from the original Mail.dat job is UPD. (Container ID: %%1)	ContainerUpdateResposne
8852	The number of In County Copies does not match between the Piece and Pound charge lines for User Postage Stmt %%1. Piece: %%2, Pound: %%3.	Postage Statement Messages
8853	The number of Out County Copies does not match between the Piece and Pound charge lines for User Postage Stmt %%1. Piece: %%2, Pound: %%3	Postage Statement Messages
8872	The PDRMailPieceBlock block and the PDRRangePieceBlock block are not supported.	Multiple
9022	The EntryPointLocaleKey in the ContainerInfoData block must be populated with alphanumeric characters and cannot be populated with ORIGIN when the EntryPointFacilityType in the ContainerInfoData block is O and the mailing is Full-Service or Mixed Service.	QualificationReportCreateResponse

Copyright © 2011 USPS®. All Rights Reserved.

Code	Warning Message	Messages
9049	The AdPercent field in the DocumentVersionData block does not match the previously stored advertising percentage for VersionID (%%1)	Postage Statement Messages
9057	The PieceWeight field in the DocumentVersionData block does not match the previously stored edition weight for VersionID (%%1)	Postage Statement Messages

5.2 Additional Constraints

N/A

5.3 *PostalOne!* WSDL Information

All web services transactions that are made with the USPS should comply with the WSDL specification that are posted on RIBBS® and can be downloaded from the following location:
http://ribbs.usps.gov/intelligentmail_guides/documents/tech_guides/xmlspec/wsdls/wsdls.htm

A web services request must include a valid and active USPS User ID and Password as defined in the UserAuthenticationInfo.xsd file that is provided as part of the WSDL downloable files. A typical web service message construct defined is as follows:

```
<wsdl:message name="DeliveryApptContentUpdateRequest">
        <wsdl:part name="authInfo" element="auth:AuthenticationInfo"/>
        <wsdl:part name="apptContentUpdate" element="tns:apptContentUpdate"/>
</wsdl:message>
```

With the following

String-typed WSDL:

```
        <wsdl:message name="StartTheClockQueryRequest">
                <wsdl:part element="auth:AuthenticationInfo" name="authInfo"/>
                <wsdl:part element="tns:startTheClockQuery" name="startTheClockQuery"/>
        </wsdl:message>
```

XSD-typed WSDL:

```
        <wsdl:message name="FullServiceStartTheClockQueryRequest">
                <wsdl:part element="uspsmxml:FullServiceStartTheClockQueryRequest"
                name="FullServiceStartTheClockQueryRequest"/>
        </wsdl:message>
```

USPS will validate and authenticate the user information before processing the request. An error message will be returned in response to the web service request for invalid user information.

Types of WSDLS

Copyright © 2011 USPS®. All Rights Reserved.

There are two types of WSDLs, the String-Type WSDL and Message-Type WSDL. The following is basic information on each of the WSDL types to help customers understand the advantages and disadvantages of consuming the string versus message type WSDL.

- **Consuming String-Type WSDLs:**

  The string-type is a more generalized method, in which a customer needs to manually register each message type and register all services in their environment to later use for invoking the remote service. This is a manual process and cannot be automated easily. This is the major disadvantage of using this method. The advantage is that one string type WSDL can be used for any version of Mail.XML but they need to be manually registered in the code. As of the Mail.XML 9.0X implementation, the USPS only supports Message-Type WSDLs.

- **Consuming Message-Type WSDLs:**

  The message-type eliminates the need to manually registering each service and message type. With this method, a customer can use an automated tool that can setup their environment without the manually registering each service. However, this approach requires updates to WSDLs every time a new Mail.XML version is released. In other words, it is tightly coupled with the Mail.XML Specification Version. The USPS is transitioning to this type of Message WSDLs to remove manual editing and registering of messages. As of the Mail.XML 9.0 release, USPS no longer supports String-Type WSDLs.

The customer must use either string-type or message-type to consume the services. The URLs to download all WSDLs are provided in Appendix A.

5.4 Permit Information

Permit Holder – This is the permit charged for the postage statement. The *PostalOne!* system uses the PermitHolderData block to reference the PermitNumber or PublicationNumber for a Periodicals postage statement. The 'PermitType' and 'PermitZip4' fields are also available in the PermitHolderData block and is associated to the 'Permit Number'. This information is displayed in the 'Permit Holder' section of a postage statement.

PermitHolderData

- MID – Optional block
- CRID – Optional field
- ContactName – Required field
- PermitPublicationData
  - PermitNumber – Required field
  - PermitType – Required field
  - PermitZip4 – Required field
  - PublicationNumber – Required for Periodicals

Mailing Agent - This identifies the organization that prepared the mailing and/or delivered it to the postal service for mailing. This information is linked to the user's login account. The *PostalOne!* system looks up the Company Name, Address Line 1, Address Line2, City, State, Zip Code, Zip Code4, Contact Phone, and Contact Email using the PermitNumber and PermitZip4 fields within th MailingAgentData block. This information is displayed in the Mailing Agent section of a postage statement.

MailingAgentData

Copyright © 2011 USPS®. All Rights Reserved.

- MID – Optional block
- CRID – Optional field
- ContactName – Required field
- PermitPublicationData
    - PermitNumber – Required field
    - PermitType – Required field
    - PermitZip4 – Required field
    - PublicaitonNumber – Required for Periodicals

Mail Owner - This identifies the organization who owns the mail being sent. The *PostalOne!* system looks up the Company_Name, Address_Line1, Address_Line2, City, State, Zip_Code, Zip_Code4, Contact_Phone, and Contact_Email in the P_Finance, P_Permit, and P_Company tables using the PermitNumber and PermitZip4 fields within the PermitPublicationData block within the MailingOwnerData block within the CreatePostageStatement block in the PostageStatementCreateRequest message. The State is determined from the Zip_Code. The *PostalOne!* system will populate the Mail Owner (Organization for Mailing is Prepared is Prepared) information with Permit Holder information. This information is displayed in the Org. For Mailing is Prepared section of a postage statement.

MailingOwnerData

- MID – Optional block
- CRID – Optional field
- ContactName – Required field
- PermitPublicationData
    - PermitNumber – Required field
    - PermitType – Required field
    - PermitZip4 – Required field
    - PublicationNumber – Required for Periodicals

Publisher Data - The *PostalOne!* system looks up the Company_Name, Address_Line1, Address_Line2, City, State, Zip_Code, Zip_Code4, Contact_Phone, and Contact_Email in the P_Finance, P_Permit, and P_Company tables using the PublicationNumber or PermitNumber field within the PermitPublicationData block within PublisherData block within the CreatePeriodicalStatement block. This information is displayed in the Publication Title and Owner or News Agent's Name section of a periodicals postage statement.

PublisherData

- MID – Optional block
- CRID – Optional field
- ContactName – Required field
- PermitPublicationData
    - PermitNumber – Required for Pending Periodicals
    - PermitType – Required for Pending Periodicals
    - PermitZip4 – Required for Pending Periodicals
    - PublicationNumber – Required for Periodicals

SubmittingParty Block (All Messages):

- MailerID6 – Optional field
- MailerID9 – Optional field
- CRID – Optional field
- SchedulerID – field is ignored

Copyright © 2011 USPS®. All Rights Reserved.

- MaildatUserLicenseCode – field is ignored

The information in the SubmittingParty block is not displayed on postage statements or reports on the *PostalOne!* Dashboard.

SubmittingSoftware Block (All Messages):
- SoftwareName – Required field
- Vendor – Required field
- Version – Required field
- ApprovalDate – Optional field
- ApprovalKey – Optional field

The information in the SubmittingSoftware block is not displayed on postage statements or reports on the *PostalOne!* Dashboard.

OpenMailingGroupRequest

PermitPublicationData – fields should be populated with Mailing Agent permit information:
- PermitNumber – Required field
- PermitType – Required field
- PermitZip4 – Required field
- PublicationNumber – Required for Periodicals

QualificationReportCreateRequest

MailOwner Block – fields should be populated with Mail Owner permit information:
- PermitNumber – Required field
- PermitType – Required field
- PermitZip4 – Required field
- PublicationNumber – Required for Periodicals

QualificationReportPreparer Block – fields should be populated with Mailing Agent permit information:
- PermitNumber – Required field
- PermitType – Required field
- PermitZip4 – Required field
- PublicationNumber – Required for Periodicals
- MailerID6 – Optional field
- MailderID9 – Optional field
- CRID – Optional field

PermitPublicationData Block – fields should be populated with Permit Holder permit information:
- PermitNumber – Required field
- PermitType – Required field
- PermitZip4 – Required field
- PublicationNumber – Required for Periodicals

PostageStatementCreateRequest

PermitHolderData Block – fields should be populated with Permit Holder permit information:

Copyright © 2011 USPS®. All Rights Reserved.

- MID – Optional block
- CRID – Optional field
- ContactName – Required field
- PermitPublicationData
    - PermitNumber – Required field
    - PermitType – Required field
    - PermitZip4 – Required field
    - PublicationNumber – Required for Periodicals

MailingOwnerData Block – fields should be populated Mail Owner permit information:

- MID – Optional block
- CRID – Optional field
- ContactName – Required field
- PermitPublicationData
    - PermitNumber – Required field
    - PermitType – Required field
    - PermitZip4 – Required field
    - PublicationNumber – Required for Periodicals

MailingAgentData block – fields should be populated with Mailing Agent permit information:

- MID – Optional block
- CRID – Optional field
- ContactName – Required field
- PermitPublicationData
    - PermitNumber – Required field
    - PermitType – Required field
    - PermitZip4 – Required field
    - PublicationNumber – Required for Periodicals

PermitHolderForAPData block – fields should be populated with Permit Holder permit information:

- MID – Optional block
- CRID – Optional field
- ContactName – Required field
- PermitPublicationData
    - PermitNumber – Required field
    - PermitType – Required field
    - PermitZip4 – Required field
    - PublicationNumber – Required for Periodicals

PeriodicalStatementCreateRequest

MailingAgentData block – fields should be populated with Mailing Agent permit information:

- MID – Optional block
- CRID – Optional field
- ContactName – Required field
- PermitPublicationData
    - PermitNumber – Required field

Copyright © 2011 USPS®. All Rights Reserved.

- PermitType – Required field
- PermitZip4 – Required field
- PublicationNumber – Required for Periodicals

PublisherData block – fields should be populated with Permit Holder permit information:

- MID – Optional block
- CRID – Optional field
- ContactName – Required field
- PermitPublicationData
  - PermitNumber – Required for Pending Periodicals
  - PermitType – Required for Pending Periodicals
  - PermitZip4 – Required for Pending Periodicals
  - PublicationNumber – Required for Periodicals

ConsolidatedPeriodicalStatementCreateRequest

MailingAgentData block – fields should be populated with Mailing Agent permit information:

- MID – Optional block
- CRID – Optional field
- ContactName – Required field
- PermitPublicationData
  - PermitNumber – Required field
  - PermitType – Required field
  - PermitZip4 – Required field
  - PublicationNumber – Required for Periodicals

PublisherData block – fields should be populated with Permit Holder permit information:

- MID – Optional block
- CRID – Optional field
- ContactName – Required field
- PermitPublicationData
  - PermitNumber – Required for Pending Periodicals
  - PermitType – Required for Pending Periodicals
  - PermitZip4 – Required for Pending Periodicals
  - PublicationNumber – Required for Periodicals

Copyright © 2011 USPS®. All Rights Reserved.

6. Appendix A – Mail.XML 9.0B Complex and Attribute Data Types Data Structure

6.1 complexType: AddressType

Mail.XML 9.0B - complexType: AddressType				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
AddressType Block begins				
Address1	String 1-64 characters		Required;	
Address2	String 1-64 characters		Optional;	
Address3	String 1-40 characters		Optional;	
Address4	String 1-40 characters		Optional;	
City	String 1-45 characters		Required;	
County	String 1-45 characters		Optional;	
State	String 2 Characters	AA, AE, AL, AK, AP, AS, AZ, AR, CA, CO, CT, DE, DC, FM, FL, GA, GU, HI, IL, IN, IA, ID, KS, KY, LA, MH, MD, MA, ME, MO, MI, MN, MS, MT, NE, NH, NV, NJ, NM, NY, NC, ND, MP, OH, OR, OK, PW, PA, PR, RI, SC, SD, TN, TX, UT, VT, VI, VA, WA, WV, WI, WY"/>	Required;	
ZipCode	Numeric String 9 characters		Required;	
GPSCoordinates	Complex			See GPSCoordinates in Appendix E
CommunicationRole	Attribute, String	From, To, CC	Required;	
AddressType ends				

Copyright © 2011 USPS®. All Rights Reserved.

6.2 complexType: CertificationDataType

Blocks Included:
CertificationData

Mail.XML 9.0B - complexType: CertificationDataType				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
CertificationDataType Block begins				
ContactName	String,40 characters		Required;	
PhoneAreaCode	Numeric, 3 characters		Required field; must be exactly 3 characters	
PhoneLast4	Numeric, 4 characters		Required field; must be exactly 4 characters	
PhonePrefix	Numeric, 3 characters		Required field; must be exactly 3 characters	
CertificationDataType ends				

6.3 complexType: CommonContactType

Blocks Included:
CommonContact

Mail.XML 9.0B - complexType: CommonContactType				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
CommonContactType Block begins				
ContactName	String,1-60 characters		Required;	
Telephone	String 1-25 characters		Optional;	
MobilePhone	String 1-25 characters		Optional;	
Email	String		Optional;	
Fax	String 1-25 characters		Optional;	
GPSCoordinates	Complex			See GPSCoordinates in Appendix E
ContactID	Complex			See ContactIDType in Appendix E

Copyright © 2011 USPS®. All Rights Reserved.

Mail.XML 9.0B - complexType: CommonContactType				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
ContactType	Attribute	AccountManager, Carrier, CrossDock, CustomerService, HelpDesk, DropShipCoordinator, ApptCoordinator, Plant, InboundFreightCoordinator, SalesOffice, TruckDriver, Warehouse, Other,	Required;	
CommonContactType ends				

6.4 complexType: ContactIDType

Blocks Included:
ContactID

Mail.XML 9.0B - complexType: ContactIDType				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
ContactIDType Block begins				
IDValue	String,1-30 characters		Required;	
IDValueType	String;	DriversLicense, EmployeeID	Required;	
ContactIDType ends				

6.5 complexType: ContainerCountType

Blocks Included:
ContainerCount
Required at least one of the fields in this block must be populated with a non-zero value

Mail.XML 9.0B - complexType: ContainerCountType				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
ContainerCountType Block begins			Required block; at least one of the fields in this block must be populated	

Copyright © 2011 USPS®. All Rights Reserved.

Mail.XML 9.0B - complexType: ContainerCountType				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
			with a nonzero value	
OtherType	Non-Negative Integer		Conditionally required if no other fields are populated with a nonzero value	
Pallets	Non-Negative Integer		Conditionally required if no other fields are populated with a nonzero value	
Sacks	Non-Negative Integer		Conditionally required if no other fields are populated with a nonzero value	
Trays1mm	Non-Negative Integer		Conditionally required if no other fields are populated with a nonzero value	
Trays2emm	Non-Negative Integer		Conditionally required if no other fields are populated with a nonzero value	
Trays2mm	Non-Negative Integer		Conditionally required if no other fields are populated with a nonzero value	
TraysFlat	Non-Negative Integer		Conditionally required if no other fields are populated with a nonzero value	
ContainerCountType ends				

6.6 complexType: ContainerPostageType

Mail.XML 9.0B - complexType: ContainerPostageType				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
ContainerPostageType Block begins			Required by *PostalOne!*	
ContainerID	String 6	-	Required	
Pieces	Non Negative Integer	-	Required	
Copies	Non Negative	-	Required	

Copyright © 2011 USPS®. All Rights Reserved.

Mail.XML 9.0B - complexType: ContainerPostageType				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
	Integer			

6.7 complexType: DocumentVersionData

Mail.XML 9.0B - complexType: DocumentVersionData				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
DocumentVersionData block begins			Optional block; contains Version Summary Report information (0 to many pairings)	
VersionID	String, 10 characters		Required;	
VersionName	String, 12 characters		Required;	
VersionDescription	String, 30 characters		Optional	
PieceWeight	Decimal		Optional The value of PieceWeight must be in Pounds.	
AdPercent	Decimal, 5 total digits		Optional; Percentage - max value 100.00.	
RateAffixed	Decimal		Optional;	
PermitPublicationData	Complex		Optional;	See permitPublication DataType Appendix E for Details
TotalCopies	Non-negative numeric		Required;	
TotalPieces	Non-negative numeric		Required;	
DocumentVersionData Block ends	Complex			

6.8 complexType: FullContainerIDType

Blocks Included:
OriginalContainer

Copyright © 2011 USPS®. All Rights Reserved.

CancelledSiblingContainer
SiblingToDelete
AcceptedSiblingContainer
NewSiblingContainer
RejectedSiblingContainer

Mail.XML 9.0B - complexType: FullContainerIDType				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
FullContainerIDType Block begins			Attributes block	
UserLicenseCode	String, 4 characters		Required; references existing Mail.dat container	
MaildatJobID	String, 8 characters		Required for Mail.dat submitted containers; references existing Mail.dat container	
ContainerGroupID	String 25		Required;	
MailingGroupID	Non Negative Integer		Required for Mail.XMl submitted containers.	
ContainerID	ContainerType		Required. Cannot use existing ContainerID to identify a new container.	
UniqueContainerBarcode	String, 24 characters		Optional field; references existing Mail.dat container	
FullContainerIDType Block ends			End of block	

6.9 complexType: GPSCoordinates

Mail.XML 9.0B - complexType: GPSCoordinates				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
GPSCoordinates Block begins				
Latitude	Numeric; maximum 18 digits; 8 decimals;		Required;	
Longitude	Numeric; maximum 18 digits; 8 decimals;		Required	

Copyright © 2011 USPS®. All Rights Reserved.

Mail.XML 9.0B - complexType: GPSCoordinates				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
Height	Numeric; maximum 18 digits; 8 decimals;		Optional;	
GPSSystem	String	ECEF, HAE, MSL	Required	
GPSCoordinates ends				

6.10 complexType: IntelligentMailBarcodeType

Mail.XML 9.0B - complexType: IntelligentMailBarcodeType				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
IntelligentMailBarcodeType Block begins			Required Only one block submitted	
BarcodeID	Number, 2 characters		Not required	
ServiceTypeCode	Number, 3 characters		Conditionally required if Mail Class is not provided	
MailClass	Number, 1 character		Conditionally required if Service Type Code is not provided	
MailerID6	Number, 6 characters		Required Only one pairing of MailerID and SerialNumber is required	
SerialNumber9	Number, 9 characters		Required Only one pairing of MailerID and SerialNumber is required	
MailerID9	Number, 9 characters		Required Only one pairing of MailerID and SerialNumber is required	
SerialNumber6	Number, 6 characters		Required Only one pairing of MailerID and SerialNumber is required	

Copyright © 2011 USPS®. All Rights Reserved.

Mail.XML 9.0B - complexType: IntelligentMailBarcodeType				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
DeliveryPointZIP	Number, 11 characters		Not required	
IntelligentMailBarcodeType Block ends				

6.11 complexType: LargeTransactionDividerGroupType

Blocks Included:
LargeTransactionDividerGroupType
LargeTransactionDividerGroupOptionalType

Mail.XML 9.0B - complexType: LargeTransactionDividerGroupType				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
Message Group ID	String, Length 20	-	Not currently supported	-
Total Message Count	Positive Integer	-	Not currently supported	-
Message Serial Number	Positive Integer	-	Not currently supported	-
Transmitted Record Count	Positive Integer	-	Not currently supported	-
Total Records Across Message	Positive Integer	-	Not currently supported	-
Last Message	Boolean	Yes/No	Not currently supported	-

6.12 complexType: LinkageType

Blocks Included:
CreateLinkage
LinkageCreated
CancelLinkage
LinkageRejected

Mail.XML 9.0B - complexType: LinkageType				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
OriginalContainer block begins			Required block; block of data the has been stored in the *PostalOne!* system	
MailDatContainer Block	Complex			See Appendix D

Copyright © 2011 USPS®. All Rights Reserved.

Mail.XML 9.0B - complexType: LinkageType				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
				for Details
MailXMLContainer block	Complex			See Appendix D for Details
ContainerBarcode	String, 24 characters		Optional if filled in MaildatContainer block or MailXMLContainer block	
OriginalContainer block ends				

6.13 complexType: LinkingContainerIDType

Blocks Included:
OriginalContainer
LinkedContainer

Mail.XML 9.0B - complexType: LinkingContainerIDType				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
OriginalContainer block begins			Required block; block of data the has been stored in the *PostalOne!* system	
MailDatContainer Block	Complex			See Appendix D for Details
MailXMLContainer block	Complex			See Appendix D for Details
ContainerBarcode	String, 24 characters		Optional if filled in MaildatContainer block or MailXMLContainer block	
OriginalContainer block ends				

6.14 complexType: MaildatContainerIDType

Blocks Included:
MaildatContainer

Mail.XML 9.0B - complexType: MaildatContainerIDType

Copyright © 2011 USPS®. All Rights Reserved.

Field	Format	Acceptable Values	Business Rules	Comments
MailDatContainer Block begins			Contains original container identifiers Required Only one block can be submitted	
UserLicenseCode	String, 4 characters		Required field; must match the User License Code from the .hdr file in Mail.dat	
MaildatJobID	String, 8 characters		Required field; must match the Job ID from the .csm file in Mail.dat	
ContainerID	String, 6 characters		Required field; must match the Container ID from the .csm file in Mail.dat	
UniqueContainerBarcode	String, 24 characters		Not required (attribute)	
MailDatContainer Block ends				

6.15 complexType: MailerDataRequestType

Mail.XML 9.0B - complexType: MailerDataRequestType				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
MailerDataRequestType Block begins				
MID Block	Complex		Optional Block	See MIDType in Appendix E for Details
ContactName	String, 60 characters		Required	
PermitPublicationData Block	Complex		Required Block	See PermitPublicationDataType in Appendix E for Details

Copyright © 2011 USPS®. All Rights Reserved.

6.16 complexType: MailerDataType

Blocks Included:
PermitHolderData
MailingOwnerData
MailingAgentData
PermitHolderForAPData
PublisherData

Mail.XML 9.0B - complexType: MailerDataType				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
MailerDataType Block begins				
Address1	String 64		(1-1) Required	
Address2	String 64		(0-1) Optional	
City	String 45		(0-1) Optional	
Country	String 45		(0-1) Optional	
DunsNumber	String 20		(0-1) Optional	
Email	Email		(0-1) Optional	
MID Block	Complex			See MIDType in Appendix E for Details
CRID	CRID		(0-1) Optional	
ContactName	String, 60 characters		Required	USPS ignores this contact name and picks up the contact info tied to the permit in the permit system.
PermitPublicationData Block	Complex			See PermitPublicationDataType in Appendix E for Details
PhoneAreaCode	String Exactly 3		Required	
PhoneExtension	String 5		Optional	
PhoneLast4	String Exactly 4		Required	
PhonePrefix	String Exactly 3		Required	
State	StateCode		Optional	
ZipCode	ZipCode		Required	
ZipCode4	String Exactly 4		Optional	
MIDType Block ends				

Copyright © 2011 USPS®. All Rights Reserved.

6.17 complexType: MailXMLContainerIDType

Blocks Included:
MailXMLContainer

Mail.XML 9.0B - complexType: MailXMLContainerIDType				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
MailXMLContainer block begins			Required block; MaildatContainer or MailXMLContainer block must be submitted	
MailingGroupID	Non-Negative integer		Required field; MailingGroupID and CustomerGroupID must be populated	
CustomerGroupID	String, 25 characters		Required field; MailingGroupID and CustomerGroupID must be populated	
ContainerID	String, 6 characters		Field not supported; using the CustomerContainer ID	
ContainerBarcode	String, 24 characters		Required field	
MailXMLContainer block ends				

6.18 attributeGroup: MailXMLMsgResponseHeaderInfo

Mail.XML 9.0B - attributeGroup: MailXMLMsgResponseHeaderInfo				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
MailXMLMsgResponseHeaderInfo Block begins			Attributes block	
CustomerGroupID	String, 25 characters		Required (attribute)	
MailingGroupID	Non-negative Integer		Required (attribute)	
TrackingID	String, 12 characters		For asynchronous transactions Not required (attribute)	
Status		Accepted, Amended, Cancelled,	Not required (attribute)	

Copyright © 2011 USPS®. All Rights Reserved.

Mail.XML 9.0B - attributeGroup: MailXMLMsgResponseHeaderInfo				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
		Counterproposal, New, NoAction, Original, PartiallyAccepted, Pending, Rejected, Replaced		
MailXMLMsgResponseHeaderInfo Block ends				

6.19 attributeGroup: MailXMLPostageStatementRequestHeaderInfo

Mail.XML 9.0B - attributeGroup: MailXMLPostageStatementRequestHeaderInfo				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
MailXMLPostageStatementRequestHeaderInfo Block begins			Attributes block	
CustomerGroupID	String, 25 characters		Required (attribute)	
MailingGroupID	Non-negative Integer		Required (attribute)	
MailXMLPostageStatementRequestHeaderInfo Block ends				

6.20 complexType: MIDType

Blocks Included:
MID

Mail.XML 9.0B - complexType: MIDType				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
MIDType Block begins			Contains six or nine digit MIDs	
MID6	String, 6 characters		Conditionally required if MID9 is not submitted	
MID9	String, 9 characters		Conditionally required if MID6 is not submitted	
MIDType Block ends				

Copyright © 2011 USPS®. All Rights Reserved.

6.21 complexType: ParticipantIDType

Blocks Included:
SubmittingParty
BarCodeApplicator
participantIDType
MailPreparer
MailOwner

Mail.XML 9.0B - complexType: ParticipantIDType				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
ParticipantIDType Block begins			Identifies the customer submitting the message	
MailerID6	String, 6 characters		Not required (attribute) Either MailerID6 or MailerID9 can be provided, not both	
MailerID9	String, 9 characters		Not required (attribute) Either MailerID6 or MailerID9 can be provided, not both	
CRID	String, 10 characters		Not required (attribute), Either CRID or MID can be provided for authorization	
SchedulerID	String 1-12 characters		Not supported for eDoc messages	
MaildatUserLicense	String 1-4 characters		Not supported for eDoc messages	
ParticipantIDType Block ends				

6.22 complexType: PermitPublicationDataType

Blocks Included:
PermitPublicationData

Mail.XML 9.0B - complexType: PermitPublicationDataType				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
PermitPublicationDataType Block begins			Provides identifying information for the Permit Number or Publication Number being used	

Copyright © 2011 USPS®. All Rights Reserved.

Mail.XML 9.0B - complexType: PermitPublicationDataType				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
PermitNumber	String, 8 characters		Conditionally required field; must be populated if PublicationNumber not populated and must be unique with PermitType and PermitZIP4	
PermitType	String, 2 characters	PI = Permit Imprint MT = Metered Tape PC = Precanceled Stamps BR = Business Reply PE = Periodicals GH = Ghost OI = Official Imprint OM = Official Metered	Conditionally required field; must be populated if PublicationNumber not populated and must be unique with PermitNumber and PermitZIP4	
PermitZip4	Numeric String, 9 characters		Conditionally required field; must be populated if PublicationNumber not populated and must be unique with PermitNumber and PermitType	
PublicationNumber	String, 8 characters		Conditionally required field; must be populated if PermitNumber not populated (must not be populated if PermitNumber is populated)	
PermitPublicationDataType Block ends				

6.23 complexType: ReturnInfo

Mail.XML 9.0B - complexType: ReturnInfo

Copyright © 2011 USPS®. All Rights Reserved.

Field	Format	Acceptable Values	Business Rules	Comments
ReturnInfo Block begins			Provides reason for return Not required can be provided Multiple pairings of ReturnCode and ReturnDescription in the block	
Sequence Block Begins			The is sequence is optional and the maximum number is unbounded	
ReturnCode			Not required	
ReturnDescription	String, 260 characters		Required	
Sequence Block Ends				
ReturnInfo Block ends				

6.24 complexType: SubmittingSoftwareType

Blocks Included:
submittingSoftware

Mail.XML 9.0B - complexType: SubmittingSoftwareType				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
SoftwareName	String		Required	
Vendor	String		Required	
Version	String		Required	
ApprovalDate	Date	YYYY-MM-DD	Not required	
ApprovalKey	String		Not required	

Copyright © 2011 USPS®. All Rights Reserved.

Copyright © 2011 USPS®. All Rights Reserved.

7. Appendix B - Mail.XML 9.0C Complex and Attribute Data Types Data Structure

Copyright © 2011 USPS®. All Rights Reserved.

8. Appendix C – Mail.XML 9.0B/9.0C Simple Types Data Structure

The simple types below list variation of validation in Mail.XML for each version of the Mail.XML (i.e. 9.0B, 9.0C, and 10.0). A column highlighted in YELLOW indicates that there is at least one change made from previous version. For example – if Mail.XML 9.0B column is highlighted in YELLOW, it means that at least one change is made in v10.0 from v9.0C. Another variation in the table below is when both v9.0C and v10.0 columns are highlighted in YELLOW. It means that there is at least one change made in v9.0C from v8.0B and then there was another change made in v10.0 from v8.0B.

NOTE#1: Mail.XML 6.0D version will no longer be supported from January 2011 thus all of the references of 6.0D have been removed from this guide including the simple types definitions.

NOTE#2: Mail.XML 7.0C and 8.0B versions will no longer be supported from October 2011 thus all of the references of 7.0C and 8.0B have been removed or limited to the minimum possible from this guide including the simple types definitions.

NOTE#3 Mail.XML 9.0B and Mail.XML 9.0C have the same Simple Types with the exception of updates introduced in 9.0C through USPSPriceIncentiveType(support for new incentive " SummerSale" and "MobileBarcode") as a new type in 9.0C and ContainerLevelType(new enumerations:
AR = Origin SCF
AS = Origin Mixed ADC Surface
AT = Mixed ADC Air

8.1 simpleType: actionCodeType

Tag	Mail.XML 9.0B/9.0C
Base	xs:string
enumeration	F = Forwarded
enumeration	W = Wasted
enumeration	R = Returned
enumeration	U = Unable to determine action

8.2 simpleType: addressCorrectionMoveType

Tag	Mail.XML 9.0B/9.0C
Base	xs:string
enumeration	F = Family Move
enumeration	I = Individual Move
enumeration	B = Business Move

8.3 simpleType: additionalInHomeRangeType

Tag	Mail.XML 9.0B/9.0C
Base	mailxml_base:n01

Copyright © 2011 USPS®. All Rights Reserved.

8.4 simpleType: adjustmentStatusType

Tag	Mail.XML 9.0B/9.0C
Base	xs:string
enumeration	R = Ready to Pay
enumeration	X = Paid
enumeration	C = Cancel
enumeration	P = Preliminary Postage Statement
enumeration	T = Transportation

8.5 simpleType: adjustmentType

Tag	Mail.XML 9.0B/9.0C
Base	xs:string
enumeration	1 = Re-order in excess of tolerance
enumeration	2 = “Average Remail” Add-on
enumeration	3 = Spoilage
enumeration	4 = Shortage

8.6 simpleType: agencyCostCodeType

Tag	Mail.XML 9.0B/9.0C
Base	xs:string
pattern	[0-9]{5}|[0-9]{6}

8.7 simpleType: apptMethodType

Tag	Mail.XML 9.0B/9.0C
Base	xs:string
enumeration	Online
enumeration	Phone
enumeration	Webservices - Detail
enumeration	Webservices - No Detail

8.8 simpleType: apptStateType

Tag	Mail.XML 9.0B/9.0C
Base	xs:string
enumeration	Scheduled
enumeration	Arrived
enumeration	ApptValidated
enumeration	WaitingToBeUnloaded
enumeration	Unloading
enumeration	FinishedUnloading
enumeration	ResolvingProblems
enumeration	Rejected
enumeration	Closed

Copyright © 2011 USPS®. All Rights Reserved.

8.9 simpleType: apptStatusType

Tag	Mail.XML 9.0B/9.0C
Base	xs:string
enumeration	Open
enumeration	Closed
enumeration	No Show
enumeration	Unscheduled
enumeration	Rejected

8.10 simpleType: apptTypeType

Tag	Mail.XML 9.0B/9.0C
Base	xs:string
enumeration	Pallet
enumeration	DropAndPick
enumeration	Speedline
enumeration	Bedload

8.11 simpleType: barcodeRateType

Tag	Mail.XML 9.0B/9.0C
Base	xs:string
enumeration	Y = Yes
enumeration	N = No
enumeration	O = Other

8.12 simpleType: billReasonCodeType

Tag	Mail.XML 9.0B/9.0C
Base	xs:string
enumeration	E
enumeration	F
enumeration	M
enumeration	N

8.13 simpleType: bundleDetailLevelType

Tag	Mail.XML 9.0B/9.0C
Base	xs:string
enumeration	A = Firm
enumeration	B = Carrier Route
enumeration	C = 5-Digit
enumeration	D = Unique 3-Digit
enumeration	E
enumeration	F
enumeration	G
enumeration	H
enumeration	I
enumeration	J

Copyright © 2011 USPS®. All Rights Reserved.

enumeration	K
enumeration	L
enumeration	M
enumeration	N
enumeration	O
enumeration	P
enumeration	Q
enumeration	R
enumeration	S
enumeration	T
enumeration	U
enumeration	V
enumeration	W
enumeration	

8.14 simpleType: bundleLevelType

Tag	Mail.XML 9.0B/9.0C
Base	Removed
enumeration	
enumeration	

8.15 simpleType: bundleRecordStatusType

Tag	Mail.XML 9.0C
Base	xs:string
enumeration	O = Original
enumeration	D = Delete
enumeration	I = Insert
enumeration	U = Update

8.16 simpleType: bundleStatusType

Tag	Mail.XML 9.0B/9.0C
Base	xs:string
enumeration	Blank
enumeration	C

8.17 simpleType: chargeableBundleLevelType

Tag	Mail.XML 9.0B/9.0C
Base	xs:string
enumeration	3 = 3-Digit/SCF
enumeration	5 = 5-Digit/Carrier Route
enumeration	A = ADC/AADC
enumeration	C = Carrier Route
enumeration	F = Firm
enumeration	M = Mixed ADC and Mixed AADC

Copyright © 2011 USPS®. All Rights Reserved.

8.18 simpleType: chargeableContainerType

Tag	Mail.XML 9.0B/9.0C
Base	xs:string
enumeration	Sacks-Trays
enumeration	Pallets

8.19 simpleType: chargeableContainerLevelType

Tag	Mail.XML 9.0B/9.0C
Base	xs:string
enumeration	3 = 3-Digit/SCF
enumeration	5 = 5-Digit/Carrier Route
enumeration	A = ADC/AADC
enumeration	M = Mixed ADC & Mixed AADC

8.20 simpleType: chargeableEntryLevelType

Tag	Mail.XML 9.0B/9.0C
Base	xs:string
enumeration	B = Destination NDC (Previously BMC)
enumeration	C = Origin SCF
enumeration	D = DDU
enumeration	J = Origin ADC
enumeration	K = Origin NDC (previously BMC)
enumeration	O = Origin Post Office/ DMU
enumeration	R = Destination ADC
enumeration	S = Destination SCF

8.21 simpleType: classNotificationType

Tag	Mail.XML 9.0B/9.0C
Base	xs:string
enumeration	A = (Reserved for future use)
enumeration	B = First-Class Mail
enumeration	C = Periodicals, Initial Notification
enumeration	D = Standard Mail
enumeration	E = Package Services
enumeration	

8.22 simpleType: closeoutIrregularitiesType

Tag	Mail.XML 9.0B/9.0C
Base	xs:string
enumeration	B = Broken Pallet
enumeration	C = Count don't Match 8125
enumeration	D = Damaged Mail
enumeration	DR = Driver Refused to Assist
enumeration	G = Good

Copyright © 2011 USPS®. All Rights Reserved.

enumeration	IA = Improper Appointment Type
enumeration	IM = Improper Mail Class
enumeration	I = Improper Mail Makeup
enumeration	IF = Incorrect Mail Facility
enumeration	L = Load Unsafe
enumeration	M = Mailing not separated by 8125
enumeration	MI = Miscellaneous
enumeration	NP = No Paperwork (Missing Paperwork)
enumeration	O = Others
enumeration	OW = Overweight Pallets
enumeration	NM = Package on NDC non-machinable
enumeration	P = Pallet Too Tall
enumeration	VS = Vehicle Size
enumeration	CP = Courtesy Pallets
enumeration	CM = Container do not match 8017
enumeration	SM = Separation do not match 8107

8.23 simpleType: closeoutResolutionType

Tag	Mail.XML 9.0B/9.0C
Base	xs:string
enumeration	DCD = Driver Contracted Dispatch Office
enumeration	DCO = Destination Contacted Origin
enumeration	DRL = Driver Reconciled Load
enumeration	INR = Irregularities Count Not be Resolved on Dock

8.24 simpleType: communicationRoleType

Tag	Mail.XML 9.0C
Base	xs:string
enumeration	From
enumeration	To
enumeration	CC

8.25 simpleType: componentIDType

Tag	Mail.XML 9.0C
Base	Removed
maxLength	
minLength	
whiteSpace	

8.26 simpleType: componentWeightType

Tag	Mail.XML 9.0C
Base	Removed

Copyright © 2011 USPS®. All Rights Reserved.

maxLength	
minLength	
whiteSpace	

8.27 simpleType: componentWeightSourceType

Tag	Mail.XML 9.0C
Base	Removed
enumeration	
enumeration	
enumeration	
enumeration	

8.28 simpleType: componentWeightStatusType

Tag	Mail.XML 9.0C
Base	Removed
enumeration	
enumeration	
enumeration	
enumeration	

8.29 simpleType: consigneeContentIDType

Tag	Mail.XML 9.0B/9.0C
Base	mailxml_base:s09

8.30 simpleType: containerBundleStatusType

Tag	Mail.XML 9.0B/9.0C
Base	xs:string
enumeration	-1 = Failed
enumeration	0 = Pending
enumeration	1 = Success

8.31 simpleType: container24CharacterBarcodeType

Tag	Mail.XML 9.0C
Base	Removed
maxLength	
minLength	
whiteSpace	

8.32 simpleType: containerAcceptanceDateType

Tag	Mail.XML 9.0B/9.0C
Base	xs:date

Copyright © 2011 USPS®. All Rights Reserved.

8.33 simpleType: cccLevelType

Tag	Mail.XML 9.0B/9.0C
Base	xs:string
enumeration	3 = 3-Digit/SCF
enumeration	5 = 5-Digit/Carrier Route
enumeration	A = ADC/AADC
enumeration	M = Mixed ADC & Mixed AADC

8.34 simpleType: containerGroupingDescriptionType

Tag	Mail.XML 9.0B/9.0C
Base	Removed

8.35 simpleType: containerGrossWeightType

Tag	Mail.XML 9.0B/9.0C
Base	mailxml_base:s05

8.36 simpleType: containerHeightType

Tag	Mail.XML 9.0B/9.0C
Base	mailxml_base:n03

8.37 simpleType: containerLevelType

How to Read:
Each Container Level Type Code shows the English translation of the code. Underneath the code there is “Eligibility Type” codes of “S” for Sack, “T” for Trays and “P” for Pallets. The Mailer must understand that to use any specific container level, the container type must be one of the following: Sack, Tray, or Pallet or all of the following or combination of some. For example – Container Level Code “A” means “CR-Direct” and it can only be used if the container types are: Sack, Tray, and Pallet.

For some Container Level Code – there is an asterisk (*) followed by “Not Supported Enumeration” text. This means that the code is not currently supported by *PostalOne!*

Tag	Mail.XML 9.0C	Mail.XML 9.0B
Base	xs:string	xs:string
enumeration	A = CR-Direct Eligibility Type = S, T, P	A = CR-Direct Eligibility Type = S, T, P
enumeration	B = Mixed CR in 5 Digit Eligibility Type = S, T, P	B = Mixed CR in 5 Digit Eligibility Type = S, T, P
enumeration	C = Mixed CR in 3 Digit Eligibility Type = S, T	C = Mixed CR in 3 Digit Eligibility Type = S, T
enumeration	D = CR – 5D Scheme Eligibility Type = S, T, P	D = CR – 5D Scheme Eligibility Type =

Copyright © 2011 USPS®. All Rights Reserved.

		S, T, P
enumeration	E = FSS Scheme	E = FSS Scheme
enumeration	F = FSS Facility	F = FSS Facility
enumeration	G = 5 Digit (Auto/Presort) Eligibility Type = S, T, P	G = 5 Digit (Auto/Presort) Eligibility Type = S, T, P
enumeration	H = 5 Digit (Merged) Eligibility Type = S, T, P	H = 5 Digit (Merged) Eligibility Type = S, T, P
enumeration	I = 5 Digit (Presort Only) Eligibility Type = S, T, P	I = 5 Digit (Presort Only) Eligibility Type = S, T, P
enumeration	J = 5 Digit (Barcode Only) Eligibility Type = S, T, P	J = 5 Digit (Barcode Only) Eligibility Type = S, T, P
enumeration	K = Metro Scheme Eligibility Type = P	K = Metro Scheme Eligibility Type = P
enumeration	~~L = Mixed RDC~~ ~~*** Not Supported Enumeration**~~	~~L = Mixed RDC~~ ~~*** Not Supported Enumeration**~~
enumeration	M = 5D Scheme (Presort) Eligibility Type = S, T, P	M = 5D Scheme (Presort) Eligibility Type = S, T, P
enumeration	N = 5D Scheme (Auto/Presort) Eligibility Type = S, T, P	N = 5D Scheme (Auto/Presort) Eligibility Type = S, T, P
enumeration	~~O =~~ ~~***Not Supported Enumeration**~~	~~O =~~ ~~***Not Supported Enumeration**~~
enumeration	P = 5D Scheme (Barcode) Eligibility Type = S, T, P	P = 5D Scheme (Barcode) Eligibility Type = S, T, P
enumeration	Q = 5D Scheme (Merged) Eligibility Type = S, T, P	Q = 5D Scheme (Merged) Eligibility Type = S, T, P
enumeration	R = 3 Digit (Auto, Presort) Eligibility Type = S, T	R = 3 Digit (Auto, Presort) Eligibility Type = S, T

Copyright © 2011 USPS®. All Rights Reserved.

enumeration	S = 3 Digit (Barcode) Eligibility Type = S, T	S = 3 Digit (Barcode) Eligibility Type = S, T
enumeration	T = 3 Digit (Presort) Eligibility Type = S, T	T = 3 Digit (Presort) Eligibility Type = S, T
enumeration	U = 3 Digit (CR, Auto, Presort) Eligibility Type = S, T, P	U = 3 Digit (CR, Auto, Presort) Eligibility Type = S, T, P
enumeration	V = 3 Digit Scheme Eligibility Type = T	V = 3 Digit Scheme Eligibility Type = T
enumeration	W	W
enumeration	X = SCF Eligibility Type = S, P	X = SCF Eligibility Type = S, P
enumeration	Y = Protected SCF Eligibility Type = P	Y = Protected SCF Eligibility Type = P
enumeration	Z = ADC Eligibility Type = S, T, P	Z = ADC Eligibility Type = S, T, P
enumeration	AA = AADC Eligibility Type = T	AA = AADC Eligibility Type = T
enumeration	AB = Mixed ADC Eligibility Type = S, T, P	AB = Mixed ADC Eligibility Type = S, T, P
enumeration	AC = Mixed AADC Eligibility Type = T	AC = Mixed AADC Eligibility Type = T
enumeration	AD = ASF Eligibility Type = S, P	AD = ASF Eligibility Type = S, P
enumeration	AE = NDC (previously known as BMC) Eligibility Type = S, P	AE = NDC (previously known as BMC) Eligibility Type = S, P
enumeration	AF = Protected NDC Eligibility Type = P	AF = Protected NDC Eligibility Type = P
enumeration	AG = Mixed NDC Eligibility Type = S, P	AG = Mixed NDC Eligibility Type = S, P
enumeration	AH = Origin MxADC	AH = Origin MxADC
enumeration	AI = Protected ADC	AI = Protected ADC
enumeration	AJ = Single Piece Container Eligibility Type = S, T	AJ = Single Piece Container

Copyright © 2011 USPS®. All Rights Reserved.

		Eligibility Type = S, T
enumeration	AK = MXDS – Mixed Surface Eligibility Type = P	AK = MXDS – Mixed Surface Eligibility Type = P
enumeration	AL = MXDA – Mixed Air CSA FCM Only AL	AL = MXDA – Mixed Air CSA FCM Only AL
enumeration	AM = Working Eligibility Type = P	AM = Working Eligibility Type = P
enumeration	AN = Single Piece – First Class Eligibility Type = P	AN = Single Piece – First Class Eligibility Type = P
enumeration	AO = Surface Eligibility Type = P	AO = Surface Eligibility Type = P
enumeration	AP = Air Eligibility Type = P	AP = Air Eligibility Type = P
enumeration	AQ = Local Eligibility Type = P	AQ = Local Eligibility Type = P
enumeration	AR = Origin SCF	Doesn't exist
enumeration	AS = Origin Mixed ADC Surface	Doesn't exist
enumeration	AT = Mixed ADC Air	Doesn't exist
enumeration	BA = Urban Direct Eligibility Type = S, T	BA = Urban Direct Eligibility Type = S, T
enumeration	BB = Rural Direct Eligibility Type = S, T	BB = Rural Direct Eligibility Type = S, T
enumeration	BC = Station Eligibility Type = S, T, P	BC = Station Eligibility Type = S, T, P
enumeration	BD = City Eligibility Type = S, T, P	BD = City Eligibility Type = S, T, P
enumeration	BE = FSA Eligibility Type = P	BE = FSA Eligibility Type = P
enumeration	BF = DCF Eligibility Type = S, T, P	BF = DCF Eligibility Type = S, T, P
enumeration	BG = FCP Eligibility Type = S, T, P	BG = FCP Eligibility Type = S, T, P

Copyright © 2011 USPS®. All Rights Reserved.

enumeration	BH = Province Eligibility Type = P	BH = Province Eligibility Type = P
enumeration	BI = Residual Eligibility Type = S, T, P	BI = Residual Eligibility Type = S, T, P
enumeration	BJ = Foreign Eligibility Type = S, T, P	BJ = Foreign Eligibility Type = S, T, P
enumeration	BK = Country Eligibility Type = S, T, P	BK = Country Eligibility Type = S, T, P
enumeration	BL = Mixed Country Eligibility Type = S, T, P	BL = Mixed Country Eligibility Type = S, T, P
enumeration	BM = M Bags Eligibility Type = S	BM = M Bags Eligibility Type = S

8.38 simpleType: containerPickupDateType

Tag	Mail.XML 9.0B/9.0C
Base	xs:date

8.39 simpleType: containerPickupTimeType

Tag	Mail.XML 9.0B/9.0C
Base	xs:time

8.40 simpleType: containerShipDateType

Tag	Mail.XML 9.0B/9.0C
Base	xs:date

8.41 simpleType: containerShipTimeType

Tag	Mail.XML 9.0B/9.0C
Base	xs:time

8.42 simpleType: contactType

Tag	Mail.XML 9.0B/9.0C
Base	xs:string
enumeration	AccountManager
enumeration	Carrier
enumeration	CrossDock
enumeration	CustomerService

Copyright © 2011 USPS®. All Rights Reserved.

enumeration	HelpDesk
enumeration	DropShipCoordinator
enumeration	ApptCoordinator
enumeration	Plant
enumeration	InboundFreightCoordinator
enumeration	SalesOffice
enumeration	TruckDriver
enumeration	Warehouse
enumeration	Other

8.43 simpleType: containerType

Tag	Mail.XML 9.0B/9.0C
Base	Removed
enumeration	
enumeration	
enumeration	
enumeration	

8.44 simpleType: containerStatusType

Tag	Mail.XML 9.0B/9.0C
Base	xs:string
enumeration	Accepted
enumeration	OnHold
enumeration	Rejected

8.45 simpleType: containerHeightSourceType

Tag	Mail.XML 9.0B/9.0C
Base	xs:string
enumeration	A = Actual
enumeration	E = Estimated

8.46 simpleType: cptPeriodicalAdPercentageType

Tag	Mail.XML 9.0C
Base	Removed
maxLength	
minLength	
whiteSpace	

8.47 simpleType: cptPeriodicalAdPercentageBasisType

Tag	Mail.XML 9.0C
Base	Removed
totalDigits	

Copyright © 2011 USPS®. All Rights Reserved.

8.48 simpleType: cptPeriodicalAdPercentageStatusType

Tag	Mail.XML 9.0C
Base	Removed
maxLength	
minLength	
whiteSpace	

8.49 simpleType: CQTdatabaseIDType

Tag	Mail.XML 9.0B/9.0C
Base	xs:nonNegativeInteger
totalDigits	8
whiteSpace	collapse

8.50 simpleType: creditDebitIndicator

Tag	Mail.XML 9.0B/9.0C
Base	xs:string
enumeration	C = Credit
enumeration	D = Debit

8.51 simpleType: CRIDType

Tag	Mail.XML 9.0B/9.0C
Base	xs:string
maxLength	15
minLength	1
pattern	([0-9])*

8.52 simpleType: cRIDStatusType

Tag	Mail.XML 9.0B/9.0C
Base	xs:string
enumeration	New
enumeration	Existing

8.53 simpleType: csaTemplateType

Tag	Mail.XML 9.0B/9.0C
Base	xs:string
enumeration	PVDS-PER
enumeration	DMU-C
enumeration	DMU-P
enumeration	BMEU
enumeration	UPVDS-PER
enumeration	UDMU-C
enumeration	UDMU-P

Copyright © 2011 USPS®. All Rights Reserved.

enumeration	UBMEU
enumeration	U

8.54 simpleType: csaStatusType

Tag	Mail.XML 9.0B/9.0C
Base	xs:string
enumeration	ACT
enumeration	PEN
enumeration	INACT
enumeration	INCOMP
enumeration	PREAPP

8.55 simpleType: databaseContainerIDType

Tag	Mail.XML 9.0B/9.0C
Base	xs:nonNegativeInteger
totalDigits	6

8.56 simpleType: dayFrequencyType

Tag	Mail.XML 9.0B/9.0C
Base	xs:string
enumeration	Daily
enumeration	Monday
enumeration	Tuesday
enumeration	Wednesday
enumeration	Thursday
enumeration	Friday
enumeration	Saturday
enumeration	Sunday

8.57 simpleType: daysOfWeekType

Tag	Mail.XML 9.0B/9.0C
Base	xs:string
enumeration	MON
enumeration	TUE
enumeration	WED
enumeration	THU
enumeration	FRI
enumeration	SAT
enumeration	SUN
enumeration	MF
enumeration	MS
enumeration	ALL
enumeration	H

Copyright © 2011 USPS®. All Rights Reserved.

8.58 simpleType: daysType

Tag	Mail.XML 9.0B/9.0C
Base	Removed
maxInclusive	
minInclusive	

8.59 simpleType: dec03-2

Tag	Mail.XML 9.0B/9.0C
Base	Removed
totalDigits	
fractionDigits	

8.60 simpleType: dec04-3

Tag	Mail.XML 9.0B/9.0C
Base	Removed
totalDigits	
fractionDigits	

8.61 simpleType: dec18-6

Tag	Mail.XML 9.0B/9.0C
Base	Removed
totalDigits	
fractionDigits	

8.62 simpleType: dec10-4

Tag	Mail.XML 9.0B/9.0C
Base	Removed
totalDigits	
fractionDigits	

8.63 simpleType: dec18-8

Tag	Mail.XML 9.0B/9.0C
Base	xs:decimal
totalDigits	18
fractionDigits	8

8.64 simpleType: deliverabilityCodeType

Tag	Mail.XML 9.0B/9.0C

Copyright © 2011 USPS®. All Rights Reserved.

Base	xs:string
enumeration	K = COA Match, No Forwarding Address
enumeration	G = COA Match, PO Box Closed, No Forwarding Address
enumeration	W = COA Match with a temporary COA

8.65 simpleType: electronicFileType

Tag	Mail.XML 9.0B/9.0C
Base	String 1
enumeration	1=Postage & Tracking File
enumeration	2=Tracking File
enumeration	3=Return Service
enumeration	4=Corrections
enumeration	5=Electronic Verification
enumeration	C=Parcel Return Service

8.66 simpleType: emailType

Tag	Mail.XML 9.0B/9.0C
Base	xs:string

8.67 simpleType: eMD8125ASNBarcodeType

Tag	Mail.XML 9.0B/9.0C
Base	Removed

8.68 simpleType: enclosedByType

Tag	Mail.XML 9.0B/9.0C
Base	xs:string
enumeration	SM = Standard Mail
enumeration	BP = Bound Printed Matter
enumeration	PE = Periodicals
enumeration	PP = Parcel Post
enumeration	ML = Media/Library Mail

8.69 simpleType: entryDiscountType

Tag	Mail.XML 9.0B/9.0C
Base	xs:string
enumeration	N = None
enumeration	B = DNDC (previous DBMC)
enumeration	S = DSCF
enumeration	D = DDU
enumeration	A = DADC

Copyright © 2011 USPS®. All Rights Reserved.

enumeration	Doesn't exist
enumeration	Doesn't exist

8.70 simpleType: entryFacilityType

Tag	Mail.XML 9.0B/9.0C
Base	xs:string
enumeration	O = Origin
enumeration	B = NDC (Previous BMC)
enumeration	S = SCF
enumeration	D = DDU
enumeration	A = ADC

8.71 simpleType: entryPointEDPostalCodeType

Tag	Mail.XML 9.0B/9.0C
Base	mailxml_base:s06

8.72 simpleType: entryPointEDFacilityTypeType

Tag	Mail.XML 9.0B/9.0C
Base	mailxml_base:s01

8.73 simpleType: entryPointADLocaleKeyType

Tag	Mail.XML 9.0B/9.0C
Base	mailxml_base:s09

8.74 simpleType: entryPointADPostalCodeType

Tag	Mail.XML 9.0B/9.0C
Base	mailxml_base:s09

8.75 simpleType: es2

Tag	Mail.XML 9.0B/9.0C
Base	Removed
maxLength	
minLength	
whiteSpace	

Copyright © 2011 USPS®. All Rights Reserved.

8.76 simpleType: es3

Tag	Mail.XML 9.0B/9.0C
Base	xs:string
maxLength	3
minLength	3
whiteSpace	preserve

8.77 simpleType: es4

Tag	Mail.XML 9.0B/9.0C
Base	xs:string
maxLength	4
minLength	4
whiteSpace	preserve

8.78 simpleType: es5

Tag	Mail.XML 9.0B/9.0C
Base	xs:string
maxLength	5
minLength	5
whiteSpace	preserve

8.79 simpleType: es31

Tag	Mail.XML 9.0B/9.0C
Base	Removed
maxLength	
minLength	
whiteSpace	

8.80 simpleType: exemptionCodeType

Tag	Mail.XML 9.0B/9.0C
Base	xs:string
enumeration	APO
enumeration	APS
enumeration	CAPC
enumeration	DUE
enumeration	HC

8.81 simpleType: fASTContentIDType

Tag	Mail.XML 9.0B/9.0C

Copyright © 2011 USPS®. All Rights Reserved.

Base	Removed

8.82 simpleType: fASTSchedulerIDType

Tag	Mail.XML 9.0B/9.0C
Base	mailxml_base:s12

8.83 simpleType: feeNotificationType

Tag	Mail.XML 9.0B/9.0C
Base	Removed
enumeration	
enumeration	
enumeration	
enumeration	

8.84 simpleType: flatRateIndicatorType

Tag	Mail.XML 9.0B/9.0C
Base	xs:string
enumeration	B = Box – Priority Mail Flat Rate Only
enumeration	C = Priority Mail Critical Mail – Letter
enumeration	E = Envelope – Priority Mail Flat Rate Only
enumeration	F = Priority Mail Critical Mail – Flat
enumeration	L = Box – Large Priority Mail Flat Rate Only
enumeration	M = Box – Large Military Destination Priority Mail Flat Rate Only
enumeration	P = Priority Mail Legal Flat Rate Envelope
enumeration	S = Small – Priority Mail Flat Rate Only

8.85 simpleType: formType

8.86 simpleType: fullServiceComplianceIndicatorType

Tag	Mail.XML 9.0B/9.0C
Base	mailxml_base:yesNo
enumeration	
enumeration	

8.87 simpleType: fspiType

Tag	Mail.XML 9.0B/9.0C
Base	xs:string
enumeration	M = Mixed
enumeration	F = Full-Service

Copyright © 2011 USPS®. All Rights Reserved.

8.88 simpleType: gPSSystemType

Tag	Mail.XML 9.0B/9.0C
Base	xs:string
enumeration	ECEF
enumeration	HAE
enumeration	MSL

8.89 simpleType: IDType

Tag	Mail.XML 9.0B/9.0C
Base	xs:string
enumeration	DriversLicense
enumeration	EmployeeID

8.90 simpleType: iMBType

Tag	Mail.XML 9.0B/9.0C
Base	xs:string
maxLength	34
minLength	20
pattern	([0-9])+

8.91 simpleType: IMcbType

Tag	Mail.XML 9.0B/9.0C
Base	xs:string
maxLength	24
minLength	21

8.92 simpleType: IMpbType

Tag	Mail.XML 9.0B/9.0C
Base	String
maxLength	34
minLength	34

8.93 simpleType: iMBarcodeIDType

Tag	Mail.XML 9.0B/9.0C
Base	mailxml_base:ns02

Copyright © 2011 USPS®. All Rights Reserved.

8.94 simpleType: iMBSerialNumber6Type

Tag	Mail.XML 9.0B/9.0C
Base	mailxml_base:ns06

8.95 simpleType: iMBSerialNumber9Type

Tag	Mail.XML 9.0B/9.0C
Base	mailxml_base:ns09

8.96 simpleType: iMBUpperSerializationType

Tag	Mail.XML 9.0B/9.0C
Base	mailxml_base:s18

8.97 simpleType: iMBLowerSerializationType

Tag	Mail.XML 9.0B/9.0C
Base	mailxml_base:s18

8.98 simpleType: IMtbType

Tag	Mail.XML 9.0B/9.0C
Base	String
maxLength	24
minLength	24

8.99 simpleType: incentiveTypeType

Tag	Mail.XML 9.0B/9.0C
Base	Does not exists
enumeration	
enumeration	
enumeration	
enumeration	

8.100 simpleType: includedInOtherDocType

Tag	Mail.XML 9.0B/9.0C
Base	xs:string

Copyright © 2011 USPS®. All Rights Reserved.

enumeration	L = Linked
enumeration	O = Original

8.101 simpleType: inOutCountyIndicatorType

Tag	Mail.XML 9.0B/9.0C
Base	Removed
enumeration	
enumeration	
enumeration	
enumeration	

8.102 simpleType: inCountyOutCountyIndicatorType

Tag	Mail.XML 9.0B/9.0C
Base	xs:string
enumeration	I – In County
enumeration	N = Outside County
enumeration	

8.103 simpleType: int04

Tag	Mail.XML 9.0B/9.0C
Base	Removed
TotalDigits	

8.104 simpleType: jobIDType

Tag	Mail.XML 9.0B/9.0C
Base	xs:string
maxLength	8
minLength	1
whiteSpace	preserve

8.105 simpleType: localeKeyType

Tag	Mail.XML 9.0B/9.0C
Base	mailxml_base:s09

8.106 simpleType: inductionStatusType

Tag	Mail.XML 9.0B/9.0C
Base	xs:string
enumeration	A = Accepted
enumeration	N = Rejected

Copyright © 2011 USPS®. All Rights Reserved.

8.107 simpleType: logicalPhysicalBundleIndicatorType

Tag	Mail.XML 9.0B/9.0C
Base	xs:string
enumeration	P = Physical
enumeration	L = Logical

8.108 simpleType: logicalPhysicalContainerIndicatorType

Tag	Mail.XML 9.0B/9.0C
Base	xs:string
enumeration	P = Physical
enumeration	L = Logical

8.109 simpleType: mailAgreementTypeType

Tag	Mail.XML 9.0B/9.0C
Base	xs:string
enumeration	A = Alternate Mailing System
enumeration	B = Optional Procedure
enumeration	C = Manifest Mailing
enumeration	D = Value Added
enumeration	E = Combined Mail
enumeration	F = Combined and Value Added

8.110 simpleType: mailClassType

Tag	Mail.XML 9.0B/9.0C
Base	xs:string
enumeration	1 = First-Class Mail
enumeration	2 = Periodicals
enumeration	3 = Standard Mail
enumeration	4 = Package Services
enumeration	6 = (Future Placeholder)

8.111 simpleType: maildatContainerStatusType

Tag	Mail.XML 9.0B/9.0C
Base	xs:string
enumeration	R = Ready to Pay
enumeration	X = Paid
enumeration	C = Cancel
enumeration	D = Delete
enumeration	P = Preliminary Postage Statement
enumeration	T = Transportation Information Update

8.112 simpleType: maildatRecordStatus

Tag	Mail.XML

Copyright © 2011 USPS®. All Rights Reserved.

	9.0B/9.0C
Base	Removed
enumeration	

8.113 simpleType: mailerID6Type

Tag	Mail.XML 9.0B/9.0C
Base	mailxml_base:ns06

8.114 simpleType: mailerID9Type

Tag	Mail.XML 9.0B/9.0C
Base	mailxml_base:ns09

8.115 simpleType: mailIssueType

Tag	Mail.XML 9.0B/9.0C
Base	Removed
maxLength	
minLength	
whiteSpace	

8.116 simpleType: mailXMLContainerType

Tag	Mail.XML 9.0B/9.0C
Base	xs:string
enumeration	1 = #1 Sack
enumeration	2 = #2 Sack
enumeration	3 = #3 Sack
enumeration	4 = 01V Sack
enumeration	5 = 03V Sack
enumeration	E = EMM Tray
enumeration	F = Flat Tub
enumeration	L = Logical Tray
enumeration	O = 1’ Tray
enumeration	P = Pallet
enumeration	S = Sack (General)
enumeration	T = 2’ Tray
enumeration	V = Sack (Virtual)
enumeration	B = Bedload
enumeration	U – Unit Load Device
enumeration	Z = User Pallet
enumeration	X = (Future Placeholder)
enumeration	H = EIRS 61 – Hamper, Large Canvas

Copyright © 2011 USPS®. All Rights Reserved.

enumeration	A = EIRS 61P – Hamper, Large Plastic
enumeration	G = EIRS 66 – General Purpose Mail Container w/Gate
enumeration	D = EIRS 68 – Eastern Region Mail Container w/Web Door
enumeration	R = EIRS 84 – Wire Container Rigid
enumeration	C = EIRS 84C – Collapsible Wire Container
enumeration	M = Logical Pallet (MLOCR)
enumeration	Y = PMOD Sack

8.117 simpleType: mailXMLPresentationCategoryType

Tag	Mail.XML 9.0B/9.0C
Base	xs:string
enumeration	M = MLOCR
enumeration	P = Conventional Presort
enumeration	I = Manifest Individual
enumeration	N = Single Piece
enumeration	S = Manifest Summary

8.118 simpleType: mailXMLStatusType

Tag	Mail.XML 9.0B/9.0C
Base	Removed
enumeration	

8.119 simpleType: mIDStatusType

Tag	Mail.XML 9.0B/9.0C
Base	xs:string
enumeration	New
enumeration	Existing

8.120 simpleType: meteredAffixedMethodType

Tag	Mail.XML 9.0B/9.0C
Base	xs:string
enumeration	C = Metered - Correct
enumeration	L = Metered – Lowest
enumeration	M = Metered - Neither

8.121 simpleType: monthType

Tag	Mail.XML 9.0B/9.0C

Copyright © 2011 USPS®. All Rights Reserved.

Base	xs:nonNegativeInteger
maxInclusive	12
minInclusive	1

8.122 simpleType: moveUpdateMethodType

Tag	Mail.XML 9.0B/9.0C
Base	xs:integer
enumeration	0 = None
enumeration	1 = ACS
enumeration	2 = NCOA
enumeration	3 = FAST Forward
enumeration	4 = Mailer Move Update Process
enumeration	5 = Ancillary Service Endorsement
enumeration	6 = Multiple
enumeration	7 = N/A
enumeration	8 = OneCode ACS

8.123 simpleType: moveUpdateType

Tag	Mail.XML 9.0B/9.0C
Base	Removed
enumeration	
enumeration	

8.124 simpleType: MPUIDType

Tag	Mail.XML 9.0B/9.0C
Base	xs:nonNegativeInteger
totalDigits	5

8.125 simpleType: ns02

Tag	Mail.XML 9.0B/9.0C
Base	xs:string
pattern	[0-9]{2}

8.126 simpleType: ns03

Tag	Mail.XML 9.0B/9.0C
Base	xs:string
pattern	[0-9]{3}

Copyright © 2011 USPS®. All Rights Reserved.

8.127 simpleType: ns04

Tag	Mail.XML 9.0B/9.0C
Base	xs:string
pattern	[0-9]{4}

8.128 simpleType: ns05

Tag	Mail.XML 9.0B/9.0C
Base	xs:string
pattern	[0-9]{5}

8.129 simpleType: ns06

Tag	Mail.XML 9.0B/9.0C
Base	xs:string
pattern	[0-9]{6}

8.130 simpleType: ns08

Tag	Mail.XML 9.0B/9.0C
Base	Removed
pattern	

8.131 simpleType: ns09

Tag	Mail.XML 9.0B/9.0C
Base	xs:string
pattern	[0-9]{9}

8.132 simpleType: ns10

Tag	Mail.XML 9.0B/9.0C
Base	xs:string
pattern	[0-9]{10}

8.133 simpleType: ns11

Tag	Mail.XML 9.0B/9.0C
Base	xs:string
pattern	[0-9]{11}

Copyright © 2011 USPS®. All Rights Reserved.

8.134 simpleType: ns13

Tag	Mail.XML 9.0B/9.0C
Base	Removed
pattern	

8.135 simpleType: ns22

Tag	Mail.XML 9.0B/9.0C
Base	xs:string
pattern	[0-9]{22}

8.136 simpleType: n01

Tag	Mail.XML 9.0B/9.0C
Base	xs:positiveInteger
totalDigits	1

8.137 simpleType: n02

Tag	Mail.XML 9.0B/9.0C
Base	xs:positiveInteger
totalDigits	2

8.138 simpleType: n03

Tag	Mail.XML 9.0B/9.0C
Base	xs:nonNegativeInteger
totalDigits	3

8.139 simpleType: n04

Tag	Mail.XML 9.0B/9.0C
Base	Removed
totalDigits	

8.140 simpleType: n05

Tag	Mail.XML 9.0B/9.0C
Base	xs:nonNegativeInteger

Copyright © 2011 USPS®. All Rights Reserved.

totalDigits	5

8.141 simpleType: n06

Tag	Mail.XML 9.0B/9.0C
Base	xs:nonNegativeInteger
totalDigits	6

8.142 simpleType: newAddressType

Tag	Mail.XML 9.0B/9.0C
Base	Removed
enumeration	
enumeration	

8.143 simpleType: addressType

Tag	Mail.XML 9.0B/9.0C
Base	xs:string
enumeration	F = Foreign
enumeration	G = General Delivery
enumeration	H = Highway Route Contract
enumeration	P = Post Office Box
enumeration	R = Rural Route
enumeration	S = Street Address
enumeration	U = Urbanization Name
enumeration	V = Highway Contract Route with box number
enumeration	X = Rural Route with box number

8.144 simpleType: onePassPlannedOrActualFlagType

Tag	Mail.XML 9.0B/9.0C
Base	xs:string
enumeration	A = Actual
enumeration	P = Planned

8.145 simpleType: packageIDType

Tag	Mail.XML 9.0B/9.0C
Base	mailxml_base:s06

8.146 simpleType: PackageServicesType

Tag	Mail.XML

Copyright © 2011 USPS®. All Rights Reserved.

	9.0B/9.0C
Base	xs:string
enumeration	PS
enumeration	BPM
enumeration	LIB
enumeration	MEDIA
enumeration	PP

8.147 simpleType: packagingMethodType

Tag	Mail.XML 9.0B/9.0C
Base	xs:string
enumeration	0 = Piece Count
enumeration	1 = Weight
enumeration	2 = Both

8.148 simpleType: palletHandlingUnitType

Tag	Mail.XML 9.0B/9.0C
Base	xs:string
enumeration	Sacks
enumeration	Bundles
enumeration	MixedLengthTrays
enumeration	1ft Tray
enumeration	2ft Tray
enumeration	EMM Tray
enumeration	Flat Tub
enumeration	Parcels

8.149 simpleType: palletType

Tag	Mail.XML 9.0B/9.0C
Base	xs:string
enumeration	Pallet
enumeration	EIRS 61 - Hamper, Large Canvas
enumeration	EIRS 61P - Hamper, Large Plastic
enumeration	EIRS 66 - General Purpose Mail Container w/Gate
enumeration	EIRS 68 - Eastern Region Mail Container w/Web Door
enumeration	EIRS 84 - Wire Container Rigid
enumeration	EIRS 84C - Collapsible Wire Container

8.150 simpleType: parentContainerRefIDType

Tag	Mail.XML 9.0B/9.0C

Copyright © 2011 USPS®. All Rights Reserved.

Base	mailxml_base:s06

8.151 simpleType: percentageType

Tag	Mail.XML 9.0B/9.0C
Base	xs:decimal
totalDigits	5
fractionDigits	2
minInclusive	0.00
maxInclusive	100.00

8.152 simpleType: periodicalPriceType

Tag	Mail.XML 9.0B/9.0C
Base	xs:string
enumeration	D = Non-Advertising Pound Rate – DSCF (B13)
enumeration	C = Non-advertising Pound Rate – DDU (B12)
enumeration	E = Non-Advertising Pound Rate – DADC (B14)
enumeration	R = Repositionable notes (surcharge) (A21, F2)
enumeration	Z = Non-Advertising Pound Rate – All Others (B15)
enumeration	5 = Non-Advertising Piece Rate (C30)
enumeration	9 = Ride-along Surcharge (A20, F1)
enumeration	1 = DDU (A17)

8.153 simpleType: periodicalStatementType

Tag	Mail.XML 9.0B/9.0C
Base	xs:string
enumeration	N

8.154 simpleType: permitTypeType

Tag	Mail.XML 9.0B/9.0C
Base	xs:string
enumeration	PI = Permit Imprint
enumeration	MT = Metered Tape
enumeration	PC = Pre-cancelled Stamps
enumeration	BR = Business Reply
enumeration	PE = Periodicals
enumeration	GH = Ghost
enumeration	OI = Official Imprint
enumeration	OM = Official Imprint
enumeration	PP = Pending Periodicals

Copyright © 2011 USPS®. All Rights Reserved.

8.155 simpleType: phoneNumberType

Tag	Mail.XML 9.0B/9.0C
Base	xs:string
maxLength	25
minLength	1
whiteSpace	preserve

8.156 simpleType: pickupOrDeliveryType

Tag	Mail.XML 9.0B/9.0C
Base	xs:string
enumeration	Pickup
enumeration	Delivery

8.157 simpleType: planetCodeType

Tag	Mail.XML 9.0B/9.0C
Base	xs:string
maxLength	13
minLength	11
pattern	[0-9]{2}

8.158 simpleType: postageGroupingIDType

Tag	Mail.XML 9.0B/9.0C
Base	mailxml_base:s08

8.159 simpleType: postagePaymentMethodType

Tag	Mail.XML 9.0B/9.0C
Base	xs:string
enumeration	S
enumeration	M
enumeration	P

8.160 simpleType: postageStatementLineNumber1Type

Tag	Mail.XML 9.0B/9.0C
Base	xs:string
enumeration	E26
enumeration	E27
enumeration	E28
enumeration	E29

Copyright © 2011 USPS®. All Rights Reserved.

enumeration	E30
enumeration	E31
enumeration	E32
enumeration	E33
enumeration	E34
enumeration	E35
enumeration	E36
enumeration	E37
enumeration	E38
enumeration	E39
enumeration	E40
enumeration	E41
enumeration	E42
enumeration	E43
enumeration	E44
enumeration	E45
enumeration	E46

8.161 simpleType: postageStatementLineNumber2Type

Tag	Mail.XML 9.0B/9.0C
Base	xs:string
enumeration	E1
enumeration	E2
enumeration	E3
enumeration	E4
enumeration	E5
enumeration	E6
enumeration	E7
enumeration	E8
enumeration	E9
enumeration	E10
enumeration	E11
enumeration	E12
enumeration	E13
enumeration	E14
enumeration	E15
enumeration	E16
enumeration	E17
enumeration	E18
enumeration	E19
enumeration	E20
enumeration	E21
enumeration	E22
enumeration	E23
enumeration	E24

Copyright © 2011 USPS®. All Rights Reserved.

8.162 simpleType: postageStatementLineNumber3Type

Tag	Mail.XML 9.0B/9.0C
Base	xs:string
enumeration	D1
enumeration	D2
enumeration	D3
enumeration	D4
enumeration	D5
enumeration	D6
enumeration	D7
enumeration	D8
enumeration	D9
enumeration	D10
enumeration	D11
enumeration	D12
enumeration	D13
enumeration	D14
enumeration	D15
enumeration	D16
enumeration	D17

8.163 simpleType: postageStatementStateType

Tag	Mail.XML 9.0B/9.0C
Base	Removed

8.164 simpleType: postageStatementStatusType

Tag	Mail.XML 9.0B/9.0C
Base	xs:string
enumeration	UPD = Updated
enumeration	FIN = Finalized
enumeration	REW = Rework
enumeration	REV = Reversed
enumeration	CAN = Cancelled
enumeration	FAI = Failed Verification
enumeration	PEN = Pending
enumeration	PAS = Passed
enumeration	INC = Incomplete
enumeration	NAP = Not Available for Processing
enumeration	EST = Estimate Postage
enumeration	CON = Consolidated Postage Statement
enumeration	ERR = Error
enumeration	COM = Complete
enumeration	AVW = Address Verification Warning
enumeration	PAV = Pending Address Verification
enumeration	FPP = Finalized Pending Payment

Copyright © 2011 USPS®. All Rights Reserved.

8.165 simpleType: priceType

Tag	Mail.XML 9.0B/9.0C
Base	xs:string
enumeration	commercial
enumeration	commercialplus
enumeration	retail

8.166 simpleType: primarySecondaryIndicatorType

Tag	Mail.XML 9.0B/9.0C
Base	xs:string
enumeration	P = Primary
enumeration	S = Secondary

8.167 simpleType: processingCategoryType

Tag	Mail.XML 9.0B/9.0C
Base	xs:string
enumeration	LT = Letter
enumeration	FL = Flat
enumeration	CD = Card
enumeration	OS = Outside Parcel
enumeration	MP = Machinable Parcel
enumeration	IR = Irregular Parcel
enumeration	PF = Parcel, First Class
enumeration	CM = Custom Mail
enumeration	NP = Non-Machinable Parcel
enumeration	NA = Non-Flat Machinable Piece < 6oz
enumeration	NB = Non-Flat Machinable Piece > 6oz
enumeration	-
enumeration	-

8.168 simpleType: processingCodeType

Tag	Mail.XML 9.0B/9.0C

Copyright © 2011 USPS®. All Rights Reserved.

Base	xs:string
enumeration	S = Surface
enumeration	MXDS = Mixed Surface
enumeration	L = Locale
enumeration	WKG = Working Mail
enumeration	A = Air Separation
enumeration	MXDA = Mixed Air
enumeration	SP = Single Piece

8.169 simpleType: pvdsContainerType

Tag	Mail.XML 9.0B/9.0C
Base	Removed
enumeration	

8.170 simpleType: pvdsContainerSubType

Tag	Mail.XML 9.0B/9.0C
Base	Removed
enumeration	
enumeration	

8.171 simpleType: qualificationReportClassType

Tag	Mail.XML 9.0B/9.0C
Base	xs:string
enumeration	FC = First Class
enumeration	S = Standard
enumeration	P = Periodicals
enumeration	PM = Priority Mail
enumeration	PP = Parcel Post
enumeration	A = Air Mail

8.172 simpleType: rateCategoryType

Tag	Mail.XML 9.0B/9.0C
Base	xs:string
enumeration	A
Enumeration	-
enumeration	AF
enumeration	B
Enumeration	-

Copyright © 2011 USPS®. All Rights Reserved.

enumeration	BF
enumeration	D
enumeration	-
enumeration	DF
enumeration	E
enumeration	FB
enumeration	G
enumeration	GF
enumeration	H
enumeration	K
enumeration	KF
enumeration	L
enumeration	L1
enumeration	L2
enumeration	L3
enumeration	L4
enumeration	L5
enumeration	L6
enumeration	L7
enumeration	L8
enumeration	Doesn’t exist
enumeration	Doesn’t exist
enumeration	Doesn’t exist
enumeration	Doesn’t exist
enumeration	N
enumeration	-
enumeration	-
enumeration	NG
enumeration	NK
enumeration	N5
enumeration	N6
enumeration	PI
enumeration	PM
enumeration	P7
enumeration	P8
enumeration	PE
enumeration	PQ
enumeration	PR
enumeration	PG
enumeration	PK
enumeration	P5
enumeration	P6
enumeration	S
enumeration	Z1
enumeration	Z2
enumeration	-
enumeration	-
enumeration	-

Copyright © 2011 USPS®. All Rights Reserved.

8.173 simpleType: rateLevelType

Tag	Mail.XML 9.0B/9.0C
Base	xs:string
enumeration	SP = Single Piece
enumeration	5B = Auto 5 Digit
enumeration	3B = Auto 3 Digit
enumeration	AB = Auto ADC/AADC
enumeration	PSRT = Presort
enumeration	5D = Presort 5 Digit
enumeration	3D = Presort 3 Digit
enumeration	NDC = NDC Presort
enumeration	ONDC = ONDC Presort
enumeration	BP = Standard Mail NDC
enumeration	MP = Mixed NDC Standard
enumeration	AD = ADC Presort
enumeration	MD = Mixed ADC Presort
enumeration	WS = Carrier Route Saturation
enumeration	HD = Carrier Route High Density
enumeration	CR = Carrier Route Basic
enumeration	MB = Auto Mixed ADC/AADC
enumeration	FB = Firm Bundle
enumeration	BB = Barcode Basic

8.174 simpleType: rateLevelIndicatorType

Tag	Mail.XML 9.0B/9.0C
Base	xs:string
enumeration	A = Auto (use with Rate Level 5B, 3B, AB, MB)
enumeration	B = Non-Auto (use with Rate Level 5D, 3D, AD, MD)
enumeration	C = ECR (use with Rate Level WS, HD, CR)
enumeration	M = Machinable (use with Rate Level AB, MB)
enumeration	N = Non-Machinable (use with Rate Level 5D, 3D, AD, MD)

8.175 simpleType: rateType

Tag	Mail.XML 9.0B/9.0C
Base	xs:string
enumeration	R = Regular
enumeration	L = Library Mail
enumeration	B = Bound Printed Matter
enumeration	C = Classroom
enumeration	S = Science of

Copyright © 2011 USPS®. All Rights Reserved.

	Agriculture
enumeration	F = Media Mail
enumeration	A = Alt Delivery
enumeration	N = Non-Profit
enumeration	P = Parcel Post
enumeration	T = Priority Mail
enumeration	X = Other
enumeration	H = (Placeholders)
enumeration	M = (Placeholders)
enumeration	Z = (Placeholders)
enumeration	E = Priority Mail Flat Fixed (Rate Envelope)
enumeration	G = Priority Mail Flat Fixed (rate Box)
enumeration	1 = UA (International)
enumeration	2 = UL (International)
enumeration	3 = UM (International)
enumeration	4 = UR (International)
enumeration	J = Priority Mail Flat – Large Box
enumeration	K = Priority Mail Flat – Large Box APO/FPO
enumeration	Doesn't exist
enumeration	W = Science and Agriculture Limited
enumeration	Y = Regular Limited Circulation

8.176 simpleType: reasonCodeType

Tag	Mail.XML 9.0B/9.0C
Base	xs:string
enumeration	A = Attempted – Not Known
enumeration	B = Returned for Better Address
enumeration	D = Outside Delivery Limits
enumeration	E = In Dispute
enumeration	I = Insufficient Address
enumeration	L = Illegible

Copyright © 2011 USPS®. All Rights Reserved.

enumeration	M = No Mail Receptacle
enumeration	N = No such number
enumeration	P = Deceased
enumeration	Q = Not Deliverable as Addressed/ Unable to Forward
enumeration	R = Refused
enumeration	S = No Such Street
enumeration	U = Unclaimed
enumeration	V = Vacant
enumeration	X = No Such Office

8.177 simpleType: recipientType

Tag	Mail.XML 9.0B/9.0C
Base	Removed
enumeration	

8.178 simpleType: recurringStatusType

Tag	Mail.XML 9.0B/9.0C
Base	xs:string
enumeration	Active
enumeration	Pending
enumeration	All

8.179 simpleType: reservationNumberType

Tag	Mail.XML 9.0B/9.0C
Base	mailxml_base:s15

8.180 simpleType: roleType

Tag	Mail.XML 9.0B/9.0C
Base	xs:string
enumeration	Data Update Agent
enumeration	Owner
enumeration	Confirm Subscriber
enumeration	Confirm Data Receiver
enumeration	ACS Data Receiver
enumeration	ACS Subscriber
enumeration	List Owner
enumeration	Mail Creator
enumeration	Addressor

Copyright © 2011 USPS®. All Rights Reserved.

enumeration	Comail
enumeration	CoMingler
enumeration	MLOCR
enumeration	Mail Owner
enumeration	Mail Agent
enumeration	Entry Point Planner
enumeration	Shipment Planner
enumeration	Consolidator
enumeration	Secondary Consolidator
enumeration	Appointment Management Receiver
enumeration	Consignee/Product Receiver
enumeration	Dispatcher
enumeration	Tracker CONFIRM-scan
enumeration	Tracker CONFIRM-payer
enumeration	Tracker Seed Source
enumeration	Tracker Piece-level-scan
enumeration	Tracker ASN-scan
enumeration	Tracker Induction-scan
enumeration	Tracker Planet-code
enumeration	ACS receiver
enumeration	ACS payer
enumeration	Seamless Acceptance
enumeration	Seamless Verification
enumeration	Security
enumeration	Logistics Provider
enumeration	Carrier
enumeration	Data Brokering Agent
enumeration	Nixie
enumeration	StartTheClock
enumeration	ContainerVisibility
enumeration	DeliveryPointValidation

8.181 simpleType: responsibleTransportationPartyType

Tag	Mail.XML 9.0B/9.0C

Copyright © 2011 USPS®. All Rights Reserved.

Base	xs:string
enumeration	Shipper
enumeration	Consignee

8.182 simpleType: RoutingZipCodeType

Tag	Mail.XML 9.0B/9.0C
Base	xs:string
maxLength	11
minLength	0

8.183 simpleType: s01

Tag	Mail.XML 9.0B/9.0C
Base	xs:string
maxLength	1
minLength	1
whiteSpace	preserve

8.184 simpleType: s02

Tag	Mail.XML 9.0B/9.0C
Base	xs:string
maxLength	2
minLength	1
whiteSpace	preserve

8.185 simpleType: s03

Tag	Mail.XML 9.0B/9.0C
Base	xs:string
maxLength	3
minLength	1
whiteSpace	preserve

8.186 simpleType: s04

Tag	Mail.XML 9.0B/9.0C
Base	xs:string
maxLength	4
minLength	1
whiteSpace	preserve

8.187 simpleType: s05

Tag	Mail.XML

Copyright © 2011 USPS®. All Rights Reserved.

	9.0B/9.0C
Base	xs:string
maxLength	5
minLength	1
whiteSpace	preserve

8.188 simpleType: s06

Tag	Mail.XML 9.0B/9.0C
Base	xs:string
maxLength	6
minLength	1
whiteSpace	preserve

8.189 simpleType: s07

Tag	Mail.XML 9.0B/9.0C
Base	xs:string
maxLength	7
minLength	1
whiteSpace	preserve

8.190 simpleType: s08

Tag	Mail.XML 9.0B/9.0C
Base	xs:string
maxLength	8
minLength	1
whiteSpace	preserve

8.191 simpleType: s09

Tag	Mail.XML 9.0B/9.0C
Base	xs:string
maxLength	9
minLength	1
whiteSpace	preserve

8.192 simpleType: s10

Tag	Mail.XML 9.0B/9.0C
Base	xs:string
maxLength	10
minLength	1
whiteSpace	preserve

Copyright © 2011 USPS®. All Rights Reserved.

8.193 simpleType: s11

Tag	Mail.XML 9.0B/9.0C
Base	xs:string
maxLength	11
minLength	1
whiteSpace	preserve

8.194 simpleType: s12

Tag	Mail.XML 9.0B/9.0C
Base	xs:string
maxLength	12
minLength	1
whiteSpace	preserve

8.195 simpleType: s15

Tag	Mail.XML 9.0B/9.0C
Base	xs:string
maxLength	15
minLength	1
whiteSpace	preserve

8.196 simpleType: s16

Tag	Mail.XML 9.0B/9.0C
Base	xs:string
maxLength	16
minLength	1
whiteSpace	preserve

8.197 simpleType: s18

Tag	Mail.XML 9.0B/9.0C
Base	xs:string
maxLength	18
minLength	1
whiteSpace	preserve

8.198 simpleType: s20

Tag	Mail.XML 9.0B/9.0C
Base	xs:string
maxLength	20

Copyright © 2011 USPS®. All Rights Reserved.

minLength	1
whiteSpace	preserve

8.199 simpleType: s22

Tag	Mail.XML 9.0B/9.0C
Base	xs:string
maxLength	22
minLength	1
whiteSpace	preserve

8.200 simpleType: s25

Tag	Mail.XML 9.0B/9.0C
Base	xs:string
maxLength	25
minLength	1
whiteSpace	preserve

8.201 simpleType: s28

Tag	Mail.XML 9.0B/9.0C
Base	xs:string
maxLength	28
minLength	1
whiteSpace	preserve

8.202 simpleType: s30

Tag	Mail.XML 9.0B/9.0C
Base	xs:string
maxLength	30
minLength	1
whiteSpace	preserve

8.203 simpleType: s31

Tag	Mail.XML 9.0B/9.0C
Base	Removed
maxLength	
minLength	
whiteSpace	

Copyright © 2011 USPS®. All Rights Reserved.

8.204 simpleType: s37

Tag	Mail.XML 9.0B/9.0C
Base	xs:string
maxLength	37
minLength	1
whiteSpace	preserve

8.205 simpleType: s40

Tag	Mail.XML 9.0B/9.0C
Base	xs:string
maxLength	40
minLength	1
whiteSpace	preserve

8.206 simpleType: s45

Tag	Mail.XML 9.0B/9.0C
Base	xs:string
maxLength	45
minLength	1
whiteSpace	preserve

8.207 simpleType: s50

Tag	Mail.XML 9.0B/9.0C
Base	xs:string
maxLength	50
minLength	1
whiteSpace	preserve

8.208 simpleType: s60

Tag	Mail.XML 9.0B/9.0C
Base	xs:string
maxLength	60
minLength	1
whiteSpace	preserve

8.209 simpleType: s64

Tag	Mail.XML 9.0B/9.0C
Base	xs:string

Copyright © 2011 USPS®. All Rights Reserved.

maxLength	64
minLength	1
whiteSpace	preserve

8.210 simpleType: s66

Tag	Mail.XML 9.0B/9.0C
Base	xs:string
maxLength	66
minLength	1
whiteSpace	preserve

8.211 simpleType: s72

Tag	Mail.XML 9.0B/9.0C
Base	Removed
maxLength	
minLength	
whiteSpace	

8.212 simpleType: s80

Tag	Mail.XML 9.0B/9.0C
Base	xs:string
maxLength	80
minLength	1
whiteSpace	preserve

8.213 simpleType: s255

Tag	Mail.XML 9.0B/9.0C
Base	Removed
maxLength	
minLength	
whiteSpace	

8.214 simpleType: s256

Tag	Mail.XML 9.0B/9.0C
Base	xs:string
maxLength	256
minLength	1
whiteSpace	preserve

Copyright © 2011 USPS®. All Rights Reserved.

8.215 simpleType: s260

Tag	Mail.XML 9.0B/9.0C
Base	xs:string
maxLength	260
minLength	1
whiteSpace	preserve

8.216 simpleType: sackingBasisType

Tag	Mail.XML 9.0B/9.0C
Base	xs:string
enumeration	0 = Piece Count
enumeration	1 = 20 lbs.
enumeration	2 = 125 Pieces
enumeration	3 = 15 lbs.
enumeration	4 = Both

8.217 simpleType: scheduledInductionDateType

Tag	Mail.XML 9.0B/9.0C
Base	xs:date

8.218 simpleType: scheduledInductionTimeType

Tag	Mail.XML 9.0B/9.0C
Base	xs:time

8.219 simpleType: scheduledInHomeDateType

Tag	Mail.XML 9.0B/9.0C
Base	xs:date

8.220 simpleType: segmentIDType

Tag	Mail.XML 9.0B/9.0C
Base	Removed
maxLength	
minLength	
whiteSpace	

8.221 simpleType: serviceLevelIndicatorType

Tag	Mail.XML 9.0B/9.0C
Base	xs:string
enumeration	F = Full-Service

Copyright © 2011 USPS®. All Rights Reserved.

enumeration	B = Basic
enumeration	P = POSTNET
enumeration	O = Other

8.222 simpleType: serviceCodeType

Tag	Mail.XML 9.0B/9.0C
Base	xs:string
enumeration	CM = Certified Mail
enumeration	COD = Collect on Delivery
enumeration	COM = Certificate of Mailing
enumeration	DC = Delivery Confirmation
enumeration	IM = Insured Mail
enumeration	PAL = Parcel Airlift
enumeration	RD = Restricted Delivery
enumeration	RM = Registered Mail
enumeration	RR = Return Receipt
enumeration	RRE = Return Receipt Electronic
enumeration	RRM = Return Receipt for Merchandise
enumeration	SC = Signature Confirmation
enumeration	SH = Special Handling

8.223 simpleType: ServiceTypeCodeType

Tag	Mail.XML 9.0B/9.0C
Base	mailxml_base:ns03

8.224 simpleType: sortationLevelType

NOTE:
a-The SortationLevelType is no longer used. It is replaced by ContainerLevelType.
b- Wherever SortationLevel is used, it is defined as Type=ContainerLevelType.

Tag	Mail.XML 9.0B/9.0C
Base	xs:string
enumeration	CRD
enumeration	5DG
enumeration	CR5
enumeration	5DGS
enumeration	CR5S
enumeration	M5D
enumeration	M5DS
enumeration	MET
enumeration	3DG

Copyright © 2011 USPS®. All Rights Reserved.

enumeration	CR3
enumeration	3DGS
enumeration	ADC
enumeration	AADC
enumeration	MADC
enumeration	MAAD
enumeration	SCF
enumeration	PSCF
enumeration	NDC
enumeration	PNDC
enumeration	MNDC
enumeration	ASF
enumeration	OMX
enumeration	PADC
enumeration	MRDC
enumeration	SP
enumeration	MXDS
enumeration	MXDA
enumeration	WORKING
enumeration	SINGLEPIECE
enumeration	SURFACE
enumeration	AIR
enumeration	LOCAL

8.225 simpleType: serviceSubCodeType

Tag	Mail.XML 9.0B/9.0C
Base	xs:string
enumeration	N = None or Not Bulk
enumeration	E = Electronic
enumeration	R = Retail or Registered
enumeration	T = Requested at Time of Mailing
enumeration	B = Bulk

8.226 simpleType: standardFlatTypeType

Tag	Mail.XML 9.0B/9.0C
Base	xs:string
enumeration	Catalog
enumeration	NotCatalog

8.227 simpleType: stateCode

Tag	Mail.XML 9.0B/9.0C
Base	xs:string
enumeration	AA
enumeration	AE

Copyright © 2011 USPS®. All Rights Reserved.

enumeration	AP
enumeration	AL
enumeration	AK
enumeration	AS
enumeration	AZ
enumeration	AR
enumeration	CA
enumeration	CO
enumeration	CT
enumeration	DE
enumeration	DC
enumeration	FM
enumeration	FL
enumeration	GA
enumeration	GU
enumeration	HI
enumeration	IL
enumeration	IN
enumeration	IA
enumeration	ID
enumeration	KS
enumeration	KY
enumeration	LA
enumeration	MH
enumeration	MD
enumeration	MA
enumeration	MO
enumeration	MI
enumeration	MN
enumeration	MS
enumeration	MT
enumeration	NE
enumeration	NH
enumeration	NV
enumeration	NJ
enumeration	NM
enumeration	NY
enumeration	NC
enumeration	ND
enumeration	MP
enumeration	OH
enumeration	OR
enumeration	OK
enumeration	PW
enumeration	PA
enumeration	PR
enumeration	RI
enumeration	SC
enumeration	SD

Copyright © 2011 USPS®. All Rights Reserved.

enumeration	TN
enumeration	TX
enumeration	UT
enumeration	VT
enumeration	VI
enumeration	VA
enumeration	WA
enumeration	WV
enumeration	WI
enumeration	WY

8.228 simpleType: statusType

Tag	Mail.XML 9.0B/9.0C
Base	xs:string
enumeration	Accepted
enumeration	Amended
enumeration	Cancelled
enumeration	Counterproposal
enumeration	New
enumeration	NoAction
enumeration	Original
enumeration	PartiallyAccepted
enumeration	Pending
enumeration	Rejected
enumeration	Replaced

8.229 simpleType: stopDesignatorType

Tag	Mail.XML 9.0B/9.0C
Base	mailxml_base:s02

8.230 simpleType: surchargeType

Tag	Mail.XML 9.0B/9.0C
Base	xs:string
enumeration	2 = Oversized Surcharge
enumeration	A = First-Class Mail Parcel Surcharge
enumeration	D = Dimensional Rate
enumeration	N = Not Oversized
enumeration	P = Balloon Surcharge
enumeration	E = Permit Reply Mail
enumeration	R = First-Class Mail Non-machinable Letters (0.0625 lbs or less)
enumeration	L = Detached Address Labels

Copyright © 2011 USPS®. All Rights Reserved.

	Used

8.231 simpleType: totalWeightType

Tag	Mail.XML 9.0B/9.0C
Base	mailxml_base:s05

8.232 simpleType: trailerLengthType

Tag	Mail.XML 9.0B/9.0C
Base	xs:string
enumeration	20ft
enumeration	40ft
enumeration	45ft
enumeration	48ft
enumeration	53ft

8.233 simpleType: transportationMethodType

Tag	Mail.XML 9.0B/9.0C
Base	xs:string
enumeration	USPS
enumeration	Mailer

8.234 simpleType: transShipBoLNumberType

Tag	Mail.XML 9.0B/9.0C
Base	mailxml_base:s05

8.235 simpleType: trayType

Tag	Mail.XML 9.0B/9.0C
Base	xs:string
enumeration	MixedLengthTrays
enumeration	1ft Tray
enumeration	2ft Tray
enumeration	EMM Tray
enumeration	Flat Tub

8.236 simpleType: truckDispatchNumberType

Tag	Mail.XML 9.0B/9.0C

Copyright © 2011 USPS®. All Rights Reserved.

Base	mailxml_base:s10

8.237 simpleType: unitLoadType

Tag	Mail.XML 9.0B/9.0C
Base	xs:string
enumeration	CrossDockPallets
enumeration	WorkingPallets
enumeration	Trailers

8.238 simpleType: unloadStateType

Tag	Mail.XML 9.0B/9.0C
Base	Removed
enumeration	
enumeration	
enumeration	

8.239 simpleType: uOMType

Tag	Mail.XML 9.0B/9.0C
Base	xs:string
enumeration	AirDryMetricTonne
enumeration	AirDryPercent
enumeration	AirDryShortTon
enumeration	Bale
enumeration	BoardFoot
enumeration	BookUnit
enumeration	Box
enumeration	Bundle
enumeration	C-Size
enumeration	Centimeter
enumeration	Cord
enumeration	CubicFoot
enumeration	CubicMeter
enumeration	Cubit
enumeration	Day
enumeration	DotsPerInch
enumeration	Foot
enumeration	Gallon
enumeration	Gram
enumeration	GramsPerSquareMeter
enumeration	Hour

Copyright © 2011 USPS®. All Rights Reserved.

enumeration	HundredBoardFeet
enumeration	HundredLinealFeet
enumeration	HundredPound
enumeration	HundredSquareFeet
enumeration	Inch
enumeration	Kilogram
enumeration	KilogramsPerDay
enumeration	KilogramsPerWeek
enumeration	KnownBreaks
enumeration	Layer
enumeration	Leaves
enumeration	LinearFoot
enumeration	LinesPerInch
enumeration	Load
enumeration	MagazineUnit
enumeration	Megabyte
enumeration	Meter
enumeration	MetricTon
enumeration	MetricTonsPerDay
enumeration	MetricTonsPerWeek
enumeration	Micron
enumeration	Millimeter
enumeration	Minute
enumeration	Month
enumeration	None
enumeration	Package
enumeration	Page
enumeration	PagesPerInch
enumeration	PalletUnit
enumeration	Percentage
enumeration	PerThousand
enumeration	Picas
enumeration	Piece
enumeration	PixelsPerInch
enumeration	Pound
enumeration	PoundsPerDay
enumeration	PoundsPerHour
enumeration	PoundsPerWeek
enumeration	PulpUnit
enumeration	Ream
enumeration	Reel
enumeration	Set

Copyright © 2011 USPS®. All Rights Reserved.

enumeration	Sheet
enumeration	ShortTon
enumeration	ShortTonsPerDay
enumeration	ShortTonsPerHour
enumeration	ShortTonsPerWeek
enumeration	Signature
enumeration	Skid
enumeration	SquareInch
enumeration	SquareFeet
enumeration	SquareMeter
enumeration	ThousandBoardFeet
enumeration	ThousandLinealFeet
enumeration	ThousandPieces
enumeration	ThousandSquareCentimeters
enumeration	ThousandSquareFeet
enumeration	ThousandSquareInch
enumeration	Ton
enumeration	TonsPerHour
enumeration	Unit
enumeration	UnknownBreaks
enumeration	Week
enumeration	Yard

8.240 simpleType: uniqueContainerIDType

Tag	Mail.XML 9.0B/9.0C
Base	xs:string
maxLength	12
minLength	1
whiteSpace	preserve

8.241 simpleType: userInformationLine1Type

Tag	Mail.XML 9.0B/9.0C
Base	mailxml_base:s40

Copyright © 2011 USPS®. All Rights Reserved.

8.242 simpleType: userInformationLine2Type

Tag	Mail.XML 9.0B/9.0C
Base	mailxml_base:s40

8.243 simpleType: userLicenseCodeType

Tag	Mail.XML 9.0B/9.0C
Base	xs:string
maxLength	4
minLength	1
whiteSpace	preserve

8.244 simpleType: uspsPickupType

Tag	Mail.XML 9.0B/9.0C
Base	xs:string
enumeration	Y
enumeration	N

8.245 simpleType: verificationLocationType

Tag	Mail.XML 9.0B/9.0C
Base	xs:string
enumeration	BMEU
enumeration	DMU

8.246 simpleType: verificationReportType

Tag	Mail.XML 9.0B/9.0C
Base	xs:string
enumeration	CSAVerification
enumeration	ContainerBarcodeVerification
enumeration	HandlingUnitBarcodeVerification
enumeration	PieceBarcodeVerification
enumeration	ByForConflictVerification
enumeration	ServiceTypeVerification
enumeration	AppointmentVerification
enumeration	MailerIDVerificati

Copyright © 2011 USPS®. All Rights Reserved.

	on
Enumeration	Doesn't Exist
enumeration	Doesn't Exist
enumeration	Doesn't Exist
enumeration	Doesn't Exist
enumeration	Doesn't Exist
enumeration	All
enumeration	NoErrors

8.247 simpleType: wastedPieceIndicatorType

Tag	Mail.XML 9.0B/9.0C
Base	xs:string
enumeration	W
enumeration	S
enumeration	X
enumeration	T

8.248 simpleType: weekFrequencyType

Tag	Mail.XML 9.0B/9.0C
Base	xs:string
enumeration	Weekly
enumeration	Bi-Weekly
enumeration	First
enumeration	Second
enumeration	Third
enumeration	Fourth
enumeration	Fifth
enumeration	Sixth

8.249 simpleType: weightBreakType

Tag	Mail.XML 9.0B/9.0C
Base	xs:string
enumeration	A = For standard Mail Non-Letters, Piece Weight is over 0.2063 lbs. For First-Class Mail Permit Reply, piece weight is over 0.0625 lbs.
enumeration	B = For standard mail, piece weight is 0.2063 lbs or less For First-Class Mail Permit Reply, piece weight is 0.0625 lbs or less.
enumeration	H = For standard Mail Letters, piece weight is over 0.2063 lbs
enumeration	N = None

Copyright © 2011 USPS®. All Rights Reserved.

8.250 simpleType: yesNo

Tag	Mail.XML 9.0B/9.0C
Base	xs:string
enumeration	Yes
enumeration	No

8.251 simpleType: zipCodeThreeOrFiveDigit

Tag	Mail.XML 9.0B/9.0C
Base	xs:string
pattern	"[0-9]{3}|[0-9]{5}" - Space removed

8.252 simpleType: zoneICType

8.253 simpleType: onePassOrTwoPassType

Tag	Mail.XML 9.0B/9.0C
Base	xs:string
enumeration	One
enumeration	Two

8.254 simpleType: uspsPackageUniqueCharacteristicType

Tag	Mail.XML 9.0B/9.0C
Base	Doesn't exist

8.255 simpleType: StandardFlatTypeType

Tag	Mail.XML 9.0B/9.0C
Base	xs:string
enumeration	Catalog
enumeration	NonCatalog

8.256 simpleType: MarketingOrFulfillmentType

Tag	Mail.XML 9.0B/9.0C
Base	xs:string
enumeration	Marketing
enumeration	Fulfillment

8.257 simpleType: MLOCRRateType

Tag	Mail.XML 9.0B/9.0C

Copyright © 2011 USPS®. All Rights Reserved.

Base	xs:string
enumeration	R
enumeration	N

8.258 simpleType: USPSPriceIncentiveType

Tag	Mail.XML 9.0B	Mail.XML 9.0C
Base	xs:string	xs:string
enumeration	PostageAffixedReplyRidesFree	PostageAffixedReplyRidesFree
enumeration	Saturation-HDTotal	Saturation-HDTotal
enumeration	Saturation-HDSCF	Saturation-HDSCF
enumeration	Doesn't exist	SummerSale
enumeration	Doesn't exist	MobileBarcode

Copyright © 2011 USPS®. All Rights Reserved.

Appendix D - eDocumentation Form Values

The appendix lists the values associated with the following Mail.XML messages: MailingGroupQueryRequest, MailingGroupQueryResponse, PaymentMessageQueryRequest, PaymentMessageQueryResponse, ReconciliationReportQueryRequest, ReconciliationReportQueryResponse, ContainerStatusQueryRequest, and ContainerStatusQueryResponse.

eDoc Form Values

8.259 Container Status Type

Value	Description
Accepted	Accepted for Induction, passed validation
OnHold	Waiting for Induction validation to complete
Rejected	Didn't satisfy the induction validation rules

8.260 Entry Facility Type Values

Value	Description
Accepted	Accepted for Induction, passed validation
OnHold	Waiting for Induction validation to complete
Rejected	Didn't satisfy the induction validation rules

8.261 Entry Facility Type

Value	Description
O	Origin
B	BMC
S	SCF
D	DDU

8.262 Form Type

Value	Description	Postage Statement
PM	Priority Mail	3600
FC	First-Class Mail	3600
SM	Standard Mail	3602
BP	Bound Printed Matter	3605
PP	Package Services	3605
PE	Periodicals	3541
ML	Media/Library Mail	3605

Copyright © 2011 USPS®. All Rights Reserved.

8.263 Full-Service Indicator

Value	Description
Blank/Null/Nil	Null
F	Full-Service
B	Basic
P	PostNet
O	Other

8.264 Postage Statement Status Definitions

Status	Definition
AVW	Address verification resulted in warnings.
CAN	A mailer canceled the postage statement.
COM	Awaiting completion of combined mailing.
CON	This statement is part of a consolidated postage statement and cannot be individually updated.
ERR	A USPS clerk was unable to finalize a statement due to a system error.
EST	The postage is an estimate based on preliminary postage data, not an actual postage statement. This is only available for postage statements submitted by mailers using Mail.dat files.
FAI	The postage statement failed verification.
FIN	The postage statement has been finalized.
FPP	Finalized pending payment – only Centralized Postage Payment for Periodicals
INC	Postage statement entry is incomplete - initial entry was interrupted.
NAP	The statement is not available for processing by the system. This usually indicates a type of postage statement not currently supported.
PAS	The postage statement passed MERLIN verification, but was not finalized at the machine.
PAV	The postage statement is pending address verification.
PEN	The postage statement is pending finalization.
QMR	A postal employee has performed a *Quality Mail Review*. The QMR stage only appears on a verification receipts entered by postal employees and does not affect postage statements submitted electronically.
REV	A postal employee has reversed the postage statement transaction.
REW	A verification issue has been identified and the mailing has been returned to the mailer for correction or rework.
UPD	A file has been received and a postage statement is available for processing (USPS Processing is Due).

Copyright © 2011 USPS®. All Rights Reserved.

8.265 Rate Category

Value	Description
Blank/Null/Nil	Null
A	Saturation ECR
AF	Standard Mail Saturation ECR Letter Paid As Flat
B	High Density ECR
BF	Standard Mail High Density ECR Letter Paid As Flat
D	Basic ECR (Carrier Route)
DF	Standard Mail Basic ECR Letter Paid As Flat
E	5-Digit Automation (5-Digit Barcode)
FB	Firm Bundle Outside County
G	5-Digit Non Barcode(Auto)
GF	5-Digit Non Barcode (Auto) Letter Paid As Flat
H	3-Digit Automation (3-Digit Barcode)
K	3-Digit Non Barcode(Auto)
KF	3-Digit Non Barcode (Auto) Letter Paid As Flat
L	Basic Automation (Basic Barcode)
L1	AADC Barcode
L2	Mixed AADC Barcode
L3	ADC Barcode
L4	Mixed ADC Barcode
L5	ADC Non-Barcode
L6	Mixed ADC Non-Barcode
L7	AADC Non-Barcode
L8	Mixed AADC Non-Barcode
N	Basic Nonautomation (Basic Presorted)
NG	5-Digit Not Flat Machinable
NK	3-Digit Not Flat Machinable
N5	ADC/BMC Not Flat Machinable
N6	Mixed ADC/BMC Not Flat Machinable
PI	5-Digit Parcel 0.2063 pounds or less
PM	3-Digit Parcel 0.2063 pounds or less
P7	ADC Parcel 0.2063 pounds or less
P8	Mixed ADC Parcel 0.2063 pounds or less
PE	5-Digit Machinable Parcel over 0.2063 pounds
PQ	BMC Machinable Parcel over 0.2063 pounds
PR	Mixed BMC Machinable Parcel over 0.2063 pounds
PG	5-Digit Irregular Parcel over 0.2063 pounds
PK	3-Digit Irregular Parcel over 0.2063 pounds
P5	ADC Irregular Parcel over 0.2063 pounds

Copyright © 2011 USPS®. All Rights Reserved.

Value	Description
P6	Mixed ADC Irregular Parcel over 0.2063 pounds
S	Single Piece
Z1	BMC Presort
Z2	OBMC Presort

8.266 First Class Mail – Rate Category and Corresponding Rate Level

Rate Category	Rate Category Description	Processing Category	Rate Level	Rate Level Description
E	5-Digit Barcode	FL	5B	Auto 5-Digit
H	3-Digit Barcode	FL	3B	Auto 3-Digit
L3	ADC Barcode	FL	AB	Auto ADC/AADC
L4	Mixed ADC Barcode	FL	MB	Auto Mixed ADC/AADC
N	Basic (1C/4C Presort)	FL	PSRT	Presorted
S	Single Piece	FL	SP	Single-Piece
E	5-Digit Barcode	LT	5B	Auto 5-Digit
H	3-Digit Barcode	LT	3B	Auto 3-Digit
L1	AADC Barcode	LT	AB	Auto ADC/AADC
L2	Mixed AADC Barcode	LT	MB	Auto Mixed ADC/AADC
N	Basic (1C/4C Presort)	LT	PSRT	Presorted
S	Single Piece	LT	SP	Single-Piece
G	5-Digit Barcode	PF	5D	Presort 5-Digit
K	3-Digit Non-Barcode	PF	3D	Presort 3-Digit
S	Single Piece	PF	SP	Single-Piece
L5	ADC	PF	AD	ADC Presort

8.267 Periodicals In-County – Rate Category and Corresponding Rate Level

For Periodicals Mail, the RateLevel in the ContainerDetailData in the ContainerInfo in the QualificationReportCreateRequest must correspond to the RateCategory for the piece postage lines in the PeriodicalStatementCreateRequest. The following tables for Periodicals In-County – Rate Category and Corresponding Rate Level and Periodicals Outside-County – Rate Category and Corresponding Rate Level show the correspondence for each processing category FL = Flats, IR = Parcels and LT = Letters.

Rate Category	Rate Category Description	Processing Category	Rate Level	Rate Level Description
A	Saturation ECR	FL	WS	Carrier Route Saturation

Copyright © 2011 USPS®. All Rights Reserved.

Rate Category	Rate Category Description	Processing Category	Rate Level	Rate Level Description
B	High Density ECR	FL	HD	Carrier Route High Density
D	Carrier Route	FL	CR	Carrier Route Basic
E	5-Digit Barcode	FL	5B	Auto 5-Digit
H	3-Digit Barcode	FL	3B	Auto 3-Digit
L	Basic Barcode	FL	BB	Barcode Basic
G	5-Digit Non-Barcode	FL	5D	Presort 5-Digit
K	3-Digit Non-Barcode	FL	3D	Presort 3-Digit
N	Basic Nonautomation	FL	PSRT	Presorted
A	Saturation ECR	IR	WS	Carrier Route Saturation
B	High Density ECR	IR	HD	Carrier Route High Density
D	Carrier Route	IR	CR	Carrier Route Basic
E	5-Digit Barcode	IR	5B	Auto 5-Digit
H	3-Digit Barcode	IR	3B	Auto 3-Digit
L	Basic Automation	IR	BB	Barcode Basic
G	5-Digit Non-Barcode	IR	5D	Presort 5-Digit
K	3-Digit Non-Barcode	IR	3D	Presort 3-Digit
N	Basic Nonautomation	IR	PSRT	Presorted
A	Saturation ECR	LT	WS	Carrier Route Saturation
AF	Saturation Letter - ECR (Pd Flt)	LT	WS	Carrier Route Saturation
B	High Density ECR	LT	HD	Carrier Route High Density
BF	High Density Letter - ECR (Pd Flt)	LT	HD	Carrier Route High Density
D	Carrier Route	LT	CR	Carrier Route Basic
DF	Carrier Route Letter (Pd Flt)	LT	CR	Carrier Route Basic
E	5-Digit Barcode	LT	5B	Auto 5-Digit
H	3-Digit Barcode	LT	3B	Auto 3-Digit
L	Basic Automation	LT	BB	Barcode Basic
G	5-Digit Non-Barcode	LT	5D	Presort 5-Digit
GF	5-Digit Letter (Pd Flt)	LT	5D	Presort 5-Digit
K	3-Digit Non-Barcode	LT	3D	Presort 3-Digit
KF	3-Digit Letter (Pd Flt)	LT	3D	Presort 3-Digit
N	Basic Nonautomation	LT	PSRT	Presorted
NF	Basic Letter (Pd Flt)	LT	PSRT	Presorted

8.268 Periodicals Outside-County – Rate Category and Corresponding Rate Level

Copyright © 2011 USPS®. All Rights Reserved.

Rate Category	Rate Category Description	Processing Category	Rate Level	Rate Level Description
A	Saturation ECR	FL	WS	Carrier Route Saturation
B	High Density ECR	FL	HD	Carrier Route High Density
D	Carrier Route	FL	CR	Carrier Route Basic
E	5-Digit Barcode	FL	5B	Auto 5-Digit
H	3-Digit Barcode	FL	3B	Auto 3-Digit
L3	ADC Barcode	FL	AB	Auto ADC/AADC
L4	Mixed ADC Barcode	FL	MB	Auto Mixed ADC/AADC
G	5-Digit Non-Barcode	FL	5D	Presort 5-Digit
K	3-Digit Non-Barcode	FL	3D	Presort 3-Digit
L5	ADC Non-Barcode	FL	AD	ADC Presort
L6	Mixed ADC Non-Barcode	FL	MD	Mixed ADC Presort
FB	Outside County Firm Bundle	FL	FB	Firm Bundle
A	Saturation ECR	IR	WS	Carrier Route Saturation
B	High Density ECR	IR	HD	Carrier Route High Density
D	Carrier Route	IR	CR	Carrier Route Basic
E	5-Digit Barcode	IR	5B	Auto 5-Digit
H	3-Digit Barcode	IR	3B	Auto 3-Digit
L3	ADC Barcode	IR	AB	Auto ADC/AADC
L4	Mixed ADC Barcode	IR	MB	Auto Mixed ADC/AADC
G	5-Digit Non-Barcode	IR	5D	Presort 5-Digit
K	3-Digit Non-Barcode	IR	3D	Presort 3-Digit
L5	ADC Non-Barcode	IR	AD	ADC Presort
L6	Mixed ADC Non-Barcode	IR	MD	Mixed ADC Presort
FB	Outside County Firm Bundle	IR	FB	Firm Bundle
A	Saturation ECR	LT	WS	Carrier Route Saturation
AF	Saturation Letter - ECR (Pd Flt)	LT	WS	Carrier Route Saturation
B	High Density ECR	LT	HD	Carrier Route High Density
BF	High Density Letter - ECR (Pd Flt)	LT	HD	Carrier Route High Density
D	Carrier Route	LT	CR	Carrier Route Basic
DF	Carrier Route Letter (Pd Flt)	LT	CR	Carrier Route Basic
E	5-Digit Barcode	LT	5B	Auto 5-Digit

Copyright © 2011 USPS®. All Rights Reserved.

Rate Category	Rate Category Description	Processing Category	Rate Level	Rate Level Description
H	3-Digit Barcode	LT	3B	Auto 3-Digit
L1	AADC Barcode	LT	AB	Auto ADC/AADC
L2	Mixed AADC Barcode	LT	MB	Auto Mixed ADC/AADC
G	5-Digit Non-Barcode	LT	5D	Presort 5-Digit
GF	5-Digit Letter (Pd Flt)	LT	5D	Presort 5-Digit
K	3-Digit Non-Barcode	LT	3D	Presort 3-Digit
KF	3-Digit Letter (Pd Flt)	LT	3D	Presort 3-Digit
L7	AADC Non-Barcode	LT	AD	ADC Presort
L8	Mixed AADC Non-Barcode	LT	MD	Mixed ADC Presort
NF	Basic Letter (Pd Flt)	LT	PSRT	Presorted
FB	Outside County Firm Bundle	LT	FB	Firm Bundle

8.269 Standard Mail – Rate Category and Corresponding Rate Level

For Standard Mail, the RateLevel in the ContainerDetailData in the ContainerInfo in the QualificationReportCreateRequest must correspond to the RateCategory for the piece postage lines in the PostageStatementCreateRequest. The following table for Standard Mail – Rate Category and Corresponding Rate Level show the correspondence for each processing category FL = Flats, IR = Parcels, LT = Letters, MP = Machinable Parcel, NF = Not Flat Machinable.

Rate Category	Rate Category Description	Processing Category	Rate Level	Rate Level Description
N	Basic (1C/4C Presort)	CM	PSRT	Presorted
A	Saturation ECR	FL	WS	Carrier Route Saturation
B	High Density ECR	FL	HD	Carrier Route High Density
D	Carrier Route	FL	CR	Carrier Route Basic
E	5-Digit Barcode	FL	5B	Auto 5-Digit
H	3-Digit Barcode	FL	3B	Auto 3-Digit
L3	ADC Barcode	FL	AB	Auto ADC/AADC
L4	Mixed ADC Barcode	FL	MB	Auto Mixed ADC/AADC
G	5-Digit Non-Barcode	FL	5D	Presort 5-Digit
K	3-Digit Non-Barcode	FL	3D	Presort 3-Digit
L5	ADC Non-Barcode	FL	AD	ADC Presort
L6	Mixed ADC Non-Barcode	FL	MD	Mixed ADC Presort
PG	5-Digit Non-Machinable	IR	5D	Presort 5-Digit

Copyright © 2011 USPS®. All Rights Reserved.

Rate Category	Rate Category Description	Processing Category	Rate Level	Rate Level Description
PI	5-Digit (Std Prcl Piece Rate)	IR	5D	Presort 5-Digit
PK	3-Digit Non-Machinable	IR	3D	Presort 3-Digit
PM	3-Digit	IR	3D	Presort 3-Digit
P5	ADC Non-Machinable	IR	AD	ADC Presort
P6	Mixed ADC Non-Machinable	IR	MD	Mixed ADC Presort
P7	ADC	IR	AD	ADC Presort
P8	Mixed ADC	IR	MD	Mixed ADC Presort
A	Saturation ECR	LT	WS	Carrier Route Saturation
B	High Density ECR	LT	HD	Carrier Route High Density
D	Carrier Route	LT	CR	Carrier Route Basic
AF	Saturation Letter - ECR (Pd Flt)	LT	WS	Carrier Route Saturation
BF	High Density Letter - ECR (Pd Flt)	LT	HD	Carrier Route High Density
DF	Carrier Route Letter (Pd Flt)	LT	CR	Carrier Route Basic
E	5-Digit Barcode	LT	5B	Auto 5-Digit
H	3-Digit Barcode	LT	3B	Auto 3-Digit
L1	AADC Barcode	LT	AB	Auto ADC/AADC
L2	Mixed AADC Barcode	LT	MB	Auto Mixed ADC/AADC
L7	AADC Non-Barcode	LT	AD	ADC Presort
L8	Mixed AADC Non-Barcode	LT	MD	Mixed ADC Presort
N5	BMC	LT	BP	Standard Mail BMC
N6	Mixed BMC	LT	MP	Mixed BMC Standard
G	5-Digit Non-Barcode	LT	5D	Presort 5-Digit
K	3-Digit Non-Barcode	LT	3D	Presort 3-Digit
L5	ADC Non-Barcode	LT	AD	ADC Presort
L6	Mixed ADC Non-Barcode	LT	MD	Mixed ADC Presort
GF	5-Digit Letter (Pd Flt)	LT	5D	Presort 5-Digit
KF	3-Digit Letter (Pd Flt)	LT	3D	Presort 3-Digit
N	Basic (1C/4C Presort)	LT	PSRT	Presorted
NF	Basic Letter (Pd Flt)	LT	PSRT	Presorted
PE	5-Digit Machinable	MP	5D	Presort 5-Digit
PQ	BMC Machinable	MP	BP	Standard Mail BMC

Copyright © 2011 USPS®. All Rights Reserved.

Rate Category	Rate Category Description	Processing Category	Rate Level	Rate Level Description
PR	Mixed BMC Machinable	MP	MP	Mixed BMC Standard
NG	5-Digit	NF	5D	Presort 5-Digit
NK	3-Digit	NF	3D	Presort 3-Digit
N5	ADC	NF	AD	ADC Presort
N6	Mixed ADC	NF	MD	Mixed ADC Presort

8.270 Add pricing for Outside County Periodicals prepared as FSS

The *PostalOne!* system shall support bundle and container prices for Outside County Periodicals flats (MailClass = 2, ProcessingCategory = FL, and formType = PM) prepared as FSS and mapped to Periodical Statement lines as follows for all applicable sack, tray and pallet types per the current mapping:

Table 1 Added Pricing for Outside-County FSS Bundles and Containers

PeriodicalLineItemData >> Section	PeriodicalLineItemData >> InOutCountyIndicator	PostageStatementLineNumber (2)	EntryDiscount (3)	Sortation Level (ContainerLevelType)	BundleLeve (BundleDetailLevelType)
D (Part D - Outside County Bundle Prices)	N = Outside-County	D15 (for 5-digit, 5-digit container)	N (None)	E-FSS Scheme	X = FSS or B = Carrier Route or C = 5 Digit
D (Part D - Outside County Bundle Prices)	N = Outside-County	D12 (for 5-digit, SCF container)	N (None)	F – FSS Facility	X = FSS or B = Carrier Route or C = 5 Digit
E (Part E - Outside County Container Prices)	N = Outside-County	E15 (for SCF DADC)	A (DADC) (1)	F – FSS Facility	X = FSS or B = Carrier Route or C = 5 Digit
E (Part E - Outside County Container Prices)	N = Outside-County	E16 (for SCF DSCF)	S (DSCF)	F – FSS Facility	X = FSS or B = Carrier Route or C = 5 Digit
E (Part E - Outside County Container Prices)	N = Outside-County	E22 (for 5-digit DADC)	A (DADC) (1)	E-FSS Scheme	X = FSS or B = Carrier Route or C = 5 Digit

Copyright © 2011 USPS®. All Rights Reserved.

E (Part E - Outside County Container Prices)	N = Outside-County	E23 (for 5-digit SCF)	S (DSCF)	E-FSS Scheme	E = FSS or B = Carrier Route or C = 5 Digit

The meaning of A is Destination ADC (DADC) and it is defined as DADC in the IDEAlliance Mail.XML specification.

The PostageStatementLineNumber could be a value in one of the following blocks:

a. ContainerBundleReportCreateRequest >> ContainerBundleVersionRecord >> SackTrayContainerVersionRecord >> PostageStatementLineNumber
b. ContainerBundleReportCreateRequest >> ContainerBundleVersionRecord >> BundleVersionRecord >> PostageStatementLineNumber
c. ContainerBundleReportCreateRequest >> ContainerBundleSummaryRecord >> BundleRecord >> PostageStatementLineNumber
d. ContainerBundleReportCreateRequest >> ContainerBundleSummaryRecord >> SackTrayContainerRecord >> PostageStatementLineNumber

The EntryDiscount field could be a value in one of the following blocks:

e. QualificationReportCreateRequest >> ContainerInfoData >> ContainerDetailData >> EntryDiscountType
f. PostageStatementCreateRequest >> LineItemSummaryData >> EntryDiscount
g. PostageStatementCreateRequest >> PostageStatementLineItemData >> EntryDiscount
h. BundleDetailCreateRequest >> BundleDetailType >> DestinationEntry

8.271 Add FSS Preparation

The following values are valid in FSS Preparation. Note that the ContainerLevelType (a.k.a. SortationLevel) values F – FSS Facility, and E – FSS Scheme and the ContainerLevel Package Level X – FSS are only available in the Mail.dat version 11-1 file.

Table 2 **containerLevelType** valid for FSS

Value	Definition	FSS Level
A	CR-Direct Eligibility Type = S, T, P	FSS Scheme
B	Mixed CR in 5 Digit Eligibility Type = S, T, P	FSS Scheme
C	Mixed CR in 3 Digit Eligibility Type = S, T	FSS Scheme
E	FSS Scheme	FSS Scheme
J	5 Digit (Barcode Only) Eligibility Type = S, T, P	FSS Scheme
P	5D Scheme (Barcode) Eligibility Type = S, T, P	FSS Scheme
F	FSS Facility	FSS Facility
X	SCF Eligibility Type = S, P	FSS Facility
Y	Protected SCF	FSS Facility

Copyright © 2011 USPS®. All Rights Reserved.

	Eligibility Type = P	

Table 3 **BundleDetailLevelType** Valid for FSS

Value	Definition	FSS Level
B	Carrier Route	FSS Scheme
C	5 Digit	FSS Scheme
X	FSS Scheme	FSS Scheme

B Mixed D CR in 5 Digit or CR - 5D Scheme or J CR - 5D Scheme or P 5D Scheme (Barcode) For the FS

NOTE: Periodical postage statement sections not included do not have changes to the postage statement generation logic and are therefore not included.

Flats Sequencing System (FSS) Preparation

The *PostalOne!* system shall support FSS preparation for Mail.XML requests for all classes of mail with .seg Principal Processing Category value FL = Flats, .csm Container Type value equivalent to pallet, .pqt Package Level value X – FSS and .csm Container Levels values E – FSS Sort Plan and F – FSS Facility. For non Periodicals mail classes, .csm Entry Point for Entry Discount - Facility Type must be value S – DSCF. For Periodicals mail class, .csm Entry Point for Entry Discount - Facility Type must be value S – DSCF or R – ADC. [SRS 431: REQ 24 and REQ 27]

The *PostalOne!* system shall support FSS preparation for Mail.XML requests for bundle and container prices for Outside County Periodicals flats (MailClass = 2, ProcessingCategory = FL, and formType = PM) prepared as FSS and mapped to Periodical Statement lines as follows for all applicable sack, tray and pallet types per the current mapping

8.272 Fault Codes

Faults, such as a message timeout or invalid XML are to be communicated using the <fault element and returned within the detail section of the SOAP fault. The fault is made up of a tracking ID and one or more fault codes and optional fault descriptions.

Below is the list of fault codes that are applicable to all Mail.XML messages, they are sent whenever a fault occurs in the transmission of the message.

Code	Description	Messages
402	Not Well Formed XML	Fault (All Mail.XML Messages)
403	Validation Failure – {specific error message thrown by parser}	Fault (All Mail.XML Messages)
412	Unauthorized – Required SubmittingParty	Fault (All Mail.XML Messages)
412	Unauthorized – User does not have access to specified SubmittingParty	Fault (All Mail.XML Messages)
412	Unauthorized – User does not have access to “Manage Mailing Activity” service	Fault (All Mail.XML Messages)

Copyright © 2011 USPS®. All Rights Reserved.

412	Unauthorized - Invalid user ID	Fault (All Mail.XML Messages)
412	Unauthorized - Invalid user password	Fault (All Mail.XML Messages)
412	Unauthorized - Account disabled	Fault (All Mail.XML Messages)
412	Unauthorized - Maximum password retries reached	Fault (All Mail.XML Messages)
412	Unauthorized - Profile not found	Fault (All Mail.XML Messages)
440	Sorry - Mail.XML version is not supported	Fault (All Mail.XML Messages)
500	Generic Internal Responder Error	Fault (All Mail.XML Messages)
500	Your request has been accepted for processing by USPS. Use the attached Tracking ID with a MessageResponseRetrievalRequest message to get the status of your request.	Fault (All Mail.XML Messages)
500	Generic Internal Responder Error (Authentication Service Failed)	Fault (All Mail.XML Messages)
503	Not Implemented - Mail.XML message received is not supported (MessageName)	Fault (All Mail.XML Messages)

Copyright © 2011 USPS®. All Rights Reserved.

9. Appendix E – Postage Statement Mappings

9.1 Mailing Information – Non Periodicals

Mailing Group Summary Information
The *PostalOne!* system will populate the Mailing Group Summary Information section of the Postage Statement based on the information that is provided in the Mail.XML messages.

The fields listed in the table below will determine the values that will be populated in the Mailing Group Summary Information section.

Mailing Group Summary Information Fields	Message/Field	Notes
Mailing Group ID	MailingGroupID	Mailing Group Unique Sequence Number
Preparer	PostageStatementCreateRequest	Looks up the Permit_No and Permit_Type in the P_Finance, P_Company, and P_Permit using the PermitNumber and PermitZip4 fields within the PermitPublicationData block within the MailingAgentData block within the CreatePostageStatement block and the CustomerReferenceID field within the CreatePostageStatement block. If the MailingAgentData block is not provided, the *PostalOne!* system looks up the Permit_No and Permit_Type in the P_Sec_User, P_Sec_User_Corp_Loc_Link, P_Company, and P_Permit tables using the PermitNumber field within the PermitPublicationData block within the MailingGroupData block within the OpenMailingGroupRequest message, the CustomerReferenceID field within the CreatePostageStatement block in the PostageStatementCreateRequest message, and the determined Finance Number.
Description	OpenMailingGroupRequest - CustomerDescription	
Mailer's Job #	OpenMailingGroupRequest - CustomerGroupID	
Finance No:	OpenMailingGroupRequest	The *PostalOne!* system looks up the Finance_No in the P_Finance table using two fields in the OpenMailingGroupRequest message: the PermitNumber field within the

Copyright © 2011 USPS®. All Rights Reserved.

Mailing Group Summary Information Fields	Message/Field	Notes
		PermitPublicationData block within the MailingGroupData block and the PostOfficeOfMailingZip field within the MailingGroupData block.
Open Date	N/A	Date the mailing group was opened
Close Date	N/A	Date the PS was Finalized

Mailer Information
The *PostalOne!* system will populate the Mailer Information section of the Postage Statement based on information that is provided in the Mail.XML messages.

The fields listed in the table below will determine the values that will be populated in the Mailer Information section.

Mailer Information Fields	Field	Notes
Permit Holder		The *PostalOne!* system looks up the Company_Name, Address_Line1, Address_Line2, City, State, Zip_Code, Zip_Code4, Contact_Phone, and Contact_Email in the P_Finance, P_Permit, and P_Company table using the PermitNumber and PermitZip4 fields within the PermitPublicationData block within the PermitHolderData block within the CreatePostageStatement block in the PostageStatementCreateRequest message. The State is determined from the Zip_Code.
Mailing Agent		The *PostalOne!* system looks up the Company_Name, Address_Line1, Address_Line2, City, State, Zip_Code, Zip_Code4, Contact_Phone, and Contact_Email in the P_Finance, P_Permit, and P_Company tables using the PermitNumber and PermitZip4 fields within the MailingAgentData within the CreatePostageStatement block in the PostageStatementCreateRequest message. The State is determined from the Zip_Code. -or- If the MailingAgentData block is not provided, the *PostalOne!* system looks up the

Copyright © 2011 USPS®. All Rights Reserved.

Mailer Information Fields	Field	Notes
		Company_Name, Address_Line1, Address_Line2, City, State, Zip_Code, Zip_Code4, Contact_Phone, and Contact_Email in the P_Sec_User, P_Sec_User_Corp_Loc_Link, P_Company, and P_Permit tables using the PermitNumber field within the PermitPublicationData block within the MailingGroupData block within the OpenMailingGroupRequest message, the CustomerReferenceID field within the CreatePostageStatement block in the PostageStatementCreateRequest message, and the determined Finance Number. The State is determined from the Zip_Code.
Org. For Mailing is Prepared	PostageStatementCreateRequest	The *PostalOne!* system looks up the Company_Name, Address_Line1, Address_Line2, City, State, Zip_Code, Zip_Code4, Contact_Phone, and Contact_Email in the P_Finance, P_Permit, and P_Company tables using the PermitNumber and PermitZip4 fields within the PermitPublicationData block within the MailingOwnerData block within the CreatePostageStatement block in the PostageStatementCreateRequest message. The State is determined from the Zip_Code. -or- If the MailingOwnerData block is not provided, the *PostalOne!* system populates the Organization for Mailing is Prepared information with Permit Holder information.
Permit Holder's Permit	PostageStatementCreateRequest - PermitNumber	
Mailing Agent's Permit	PostageStatementCreateRequest - PermitType, PermitNumber	If the PermitType field is not provided within PermitPublicationData block within the MailingAgent block, the *PostalOne!* system looks up the Permit_Type in the P_Permit table using the PermitNumber field within the PermitPublicationData block within the MailingAgentData block within the CreatePostageStatement block. -or- If the MailingAgentData block is not provided, the *PostalOne!* system looks up the Permit_No and Permit_Type in the P_Sec_User, P_Sec_User_Corp_Loc_Link, P_Company, and P_Permit tables using the

Copyright © 2011 USPS®. All Rights Reserved.

Mailer Information Fields	Field	Notes
		PermitNumber field within the PermitPublicationData block within the MailingGroupData block within the OpenMailingGroupRequest message, the CustomerReferenceID field within the CreatePostageStatement block in the PostageStatementCreateRequest message, and the determined Finance Number.

Postage Summary Information
The *PostalOne!* system will populate that Postage Summary information section of the Postage Statement based on the information that is provided in the Mail.XML messages.

The fields listed in the table below will determine that values that will be populated in the Postage Summary section.

Postage Summary Information Fields	Message/Field	Notes
Post Office of Mailing	OpenMailingGroupRequest	The *PostalOne!* system looks up the City, State, and Zip_Code in the P_Company table using the PostOfficeOfMailingZip field within the MailingGroupData block in the OpenMailingGroupRequest message. The State is determined from the Zip_Code.
Processing Category	PostageStatementCreateRequest – ProcessingCategory	
Mailer's Mailing Date	PostageStatementCreateRequest – PostageStatementMailingDate	
Federal Agency Cost Code	PostageStatementCreateRequest – AgencyCostCode	
Statement Seq. No	N/A	System generated sequence number
No. & type of Containers	PostageStatementCreateRequest – ContainerCount	Sum of containers grouped by Container Type
Type of Postage	PostageStatementCreateRequest – PostagePaymentMethod	
Weight of a Single Piece	PostageStatementCreateRequest –	

Copyright © 2011 USPS®. All Rights Reserved.

Postage Summary Information Fields	Message/Field	Notes
	SinglePieceWeight or SinglePieceDimensional Weight	
Hold For Pickup	PostageStatementCreate Request - HoldForPickUp	First-Class Mail, Priority Mail, and Package Services only
Combined Mailing	PostageStatementCreate Request – PermitNumber	Combined Mailing checkbox will be checked when a Mail.dat job is submitted with multiple values populated in the Permit Holder field.
Total Pieces	PostageStatementCreate Request - TotalPieces	First-Class Mail, Standard Mail, and Package Services only
Of Total Pieces, # With Simplified Addresses	PostageStatementCreate Request - NumberOfPiecesSimplifiedAddress	Standard Mail Only
Total Weight	PostageStatementCreate Request – TotalWeight	
For Mail Enclose Within Another Class	PostageStatementCreate Request - FormType	First-Class Mail, Priority Mail, and Standard Mail only
If Sacked, Based On	PostageStatementCreate Request - SackingBasis	Standard Mail and Priority Mail only
Packaging Based on	PostageStatementCreate Request - PackagingMethod	Package Services only
For Automation Price Pieces, Enter Date of Address Matching and Coding	PostageStatementCreate Request - AutomationAddressMatchDate	
For Carrier Route Price Piece, Enter Date for Address Matching and Coding	PostageStatementCreate Request - CarrierRouteAddressMatchDate	Standard Mail only
For Carrier Route Price Pieces, Enter Date of Carrier Route Sequencing	PostageStatementCreate Request - CarrierRouteSequencingDate	Standard Mail only
For pieces bearing a simplified address enter data of delivery statistics file or alternative method	PostageStatementCreate Request - DeliveryStatisticsFileDate	Standard Mail only
For Barcoded Pieces, Enter Date of Address	PostageStatementCreate Request -	Priority Mail only

Copyright © 2011 USPS®. All Rights Reserved.

Postage Summary Information Fields	Message/Field	Notes
Matching and Coding	AutomationAddressMatchDate	
Move Update Method	PostageStatementCreateRequest - MoveUpdateMethod	First-Class Mail and Standard Mail only
Priority Mail Open and Distribute (PMOD)	PostageStatementCreateRequest - PMODIndicator	Priority Mail only
Total Postage	N/A	Sum of all parts of a postage statement
Address Matching Date – Automation	PostageStatementCreateRequest – AutomationAddressMatchDate	
Address Matching Date – Carrier Route	PostageStatementCreateRequest - CarrierRouteAddressMatchDate	
Customer Reference ID	PostageStatementCreateRequest - CustomerReferenceID	
Incentive Claimed	PostageStatementCreateRequest - USPSPriceIncentiveType	

Mailing Information – Periodicals

Mailing Group Summary Information
The *PostalOne!* system will populate the Mailing Group Summary Information section of the Periodicals Postage Statement based on the information that is provided in the Mail.XML messages.

The fields listed in the table below will determine the values that will be populated in the Mailing Group Summary Information section.

Mailing Group Summary Information Fields	Message/Field	Notes
Mailing Group ID	MailingGroupID	Mailing Group Unique Sequence Number
Preparer	PeriodicalStatementCreateRequest	Looks up the Permit_No and Permit_Type in the P_Finance, P_Company, and P_Permit using the PermitNumber and PermitZip4 fields within the PermitPublicationData block within the MailingAgentData block within the CreatePostageStatement block and the CustomerReferenceID field within the

Copyright © 2011 USPS®. All Rights Reserved.

Mailing Group Summary Information Fields	Message/Field	Notes
		CreatePostageStatement block. If the MailingAgentData block is not provided, the *PostalOne!* system looks up the Permit_No and Permit_Type in the P_Sec_User, P_Sec_User_Corp_Loc_Link, P_Company, and P_Permit tables using the PermitNumber field within the PermitPublicationData block within the MailingGroupData block within the OpenMailingGroupRequest message, the CustomerReferenceID field within the CreatePostageStatement block in the PostageStatementCreateRequest message, and the determined Finance Number.
Description	OpenMailingGroupRequest - CustomerDescription	
Mailer's Job #	OpenMailingGroupRequest - CustomerGroupID	
Finance No:	OpenMailingGroupRequest	The *PostalOne!* system looks up the Finance_No in the P_Finance table using two fields in the OpenMailingGroupRequest message: the PermitNumber field within the PermitPublicationData block within the MailingGroupData block and the PostOfficeOfMailingZip field within the MailingGroupData block.
Open Date	N/A	Date the mailing group was opened
Close Date	N/A	Date the PS was Finalized

Mailer Information
The *PostalOne!* system will populate the Mailer Information section of the Periodicals Postage Statement based on the information that is provided in the Mail.XML messages.

The fields listed in the table below will determine the values that will be populated in the Mailer Information section.

Mailer Information Fields	Message/Field	Notes
Publication Title and Owner or News Agent's Name	PeriodicalStatementCreateRequest	The *PostalOne!* system looks up the Company_Name, Address_Line1, Address_Line2, City, State, Zip_Code,

Copyright © 2011 USPS®. All Rights Reserved.

Mailer Information Fields	Message/Field	Notes
		Zip_Code4, Contact_Phone, and Contact_Email in the P_Finance, P_Permit, and P_Company tables using the PublicationNumber or PermitNumber field within the PermitPublicationData block within PublisherData block within the CreatePeriodicalStatement block.
Mailer's Name, Address, Telephone Number, and Email	PeriodicalStatementCreateRequest	The *PostalOne!* system looks up Company_Name, Address_Line1, Address_Line2, City, State, Zip_Code, Zip_Code4, Contact_Phone, and Contact_Email in the P_Finance, P_Permit, and P_Company tables using the PermitNumber or PublicationNumber field within the PermitPublicationData block within the MailingAgentData block within the CreatePeriodicalStatement block in the PeriodicalStatementCreateRequest message, the CustomerReferenceID field within the CreatePeriodicalStatement block in the PeriodicalStatementCreateRequest message, and the determined Finance Number.-or-If the MailingAgentData block is not provided, the *PostalOne!* system looks up Company_Name, Address_Line1, Address_Line2, City, State, Zip_Code, Zip_Code4, Contact_Phone, and Contact_Email in the P_Sec_User, P_Sec_User_Corp_Loc_Link, P_Company, and P_Permit tables using the PermitNumber or PublicationNumber field within the PermitPublicationData block within the MailingGroupData block within the OpenMailingGroupRequest message, the CustomerReferenceID field within the CreatePostageStatement block in the PeriodicalStatementCreateRequest message, and the determined Finance Number.
Entry Post Office Name, State, and ZIP+4	OpenMailingGroupRequest	The *PostalOne!* system looks up the City, State, Zip_Code, and Zip_Code4 in the P_Company table using the PostOfficeOfMailingZip field within the MailingGroupData block. The State is determined from the Zip_Code.

Mailing Information

Copyright © 2011 USPS®. All Rights Reserved.

The *PostalOne!* system will populate the Mailing Information section of the Periodicals Postage Statement based on the information that is provided in the Mail.XML messages.

The fields listed in the table below will determine the values that will be populated in the Mailing Information section.

Mailing Information Fields	Message/Field	Notes
Applicable Part Completed	N/A	Sections of the postage statement that were completed
Statement for bundles/containers only	N/A	
Price Category	PeriodicalStatementCreateRequest - RateType	
Combined Mailing	PeriodicalStatementCreateRequest – PublicationNumber	Combined Mailing checkbox will be checked when a Mail.XML mailings is submitted with multiple values populated in the Permit Holder field.
Consolidated Postage Statement	ConsolidatedPeriodicalStatementCreateRequest	Consolidated Mailing checkbox will be checked when a ConsolidatedPeriodicalStatementCreateRequest message is submitted
Publication No.	PeriodicalStatementCreateRequest - PublicationNumber	
Edition/Code	PeriodicalStatementCreateRequest - EditionCode	
Mailer's Mailing Date:	PeriodicalStatementCreateRequest – PostageStatementMailingDate	
Processing Category	PeriodicalStatementCreateRequest - ProcessingCategory	
No. of Addressed Pieces Excluding Address Supplements	N/A	Sum of the number of pieces for each line item for each completed part of the postage statement (excluding Addressed Supplements)
In-County Addressed Supplements	PeriodicalStatementCreateRequest – InCountryAddressedSupplementPieces	Sum of the number of In-County Addressed Supplements
Out-County Addressed Supplements	PeriodicalStatementCreateRequest – OutCountyAddressedSupplementPieces	Sum of the number of Out-County Addressed Supplements

Copyright © 2011 USPS®. All Rights Reserved.

Mailing Information Fields	Message/Field	Notes
Issue Date	PeriodicalStatementCreateRequest – IssueDate	
Volume Number	PeriodicalStatementCreateRequest – VolumeNumber	
Issue Number	PeriodicalStatementCreateRequest – IssueNumber	
Issue Frequency	PeriodicalStatementCreateRequest - IssueFrequency	
Statement Sequence No.	N/A	System generated sequence number
Weight of Single Ride-Along Piece	PeriodicalStatementCreateRequest - SingleRideAloneWeight	Calculated when Rate Type 'H' (Ride Along Weight)
Weight per Copy for Issue	PeriodicalStatementCreateRequest – CopyWeight	
Advertising Percentage in This Issue	PeriodicalStatementCreateRequest – AdvertisingPercentage	
Number and Type of Containers	PeriodicalStatementCreateRequest - ContainerCount	Sum of containers grouped by Container Type
Total Postage	N/A	Calculated by summing the total postage for all parts of the postage statement
For Automation Price Pieces, Enter Date for Address Matching and Coding	PeriodicalStatementCreateRequest - AutomationAddressMatchDate	
For Carrier Route Price Piece, Enter Date for Address Matching and Coding	PeriodicalStatementCreateRequest - CarrierRouteAddressMatchDate	
For Carrier Route Price Pieces, Enter Date of Carrier Route Sequencing	PeriodicalStatementCreateRequest - CarrierRouteSequencingDate	
For pieces bearing a simplified address enter data of delivery statistics file or	PeriodicalStatementCreateRequest - DeliveryStatisticsFileDate	

Copyright © 2011 USPS®. All Rights Reserved.

Mailing Information Fields	Message/Field	Notes
alternative method		

Copyright © 2011 USPS®. All Rights Reserved.

10. Appendix F - WSDLs and XSDs

The WSDL specification are posted on RIBBS® and can be downloaded from the following location:
http://ribbs.usps.gov/intelligentmail_guides/documents/tech_guides/xmlspec/wsdls/wsdls.htm

The above RIBBS® URL provides WSDLs for both TEM and production environments. User should always use this link to access the correct and updated version of WSDLs in future.
PULL WSDL LINKS FOR TEM ENVIRONMENT

To consume the WSDL services, the customer must use one of the following URLs in the TEM environments:

STRING-TYPE WSDL URL Link(s)

https://mailxmltem.uspspostalone.com/MLXMLServicesWeb/services/POAppointmentServices/wsdl/POAppointmentServices-MailXML60.wsdl

The USPS is no longer supporting the string type as of the Mail.XML 9.0X implementation. Currently, the USPS only accepts Message-Types WSDLs.

MESSAGE-TYPE WSDL URL Link(s)

The following link supports Mail.XML 8.1 version:
https://mailxmltem.uspspostalone.com/MailXML81ALLMsgType/WebServices/wsdl/USPSMailXML81ALLMsgType.wsdl

The following link supports Mail.XML Modular Specification (9.x and above):

On the Modular XSD, we support following WSDL points based on the Messages Group (Mailing, Supply Chain, Transportation, Data Distribution, and Identification). The WSDL endpoint for the message group will not change, will support multiple versions of Modular spec. In Release 25 – only Mailing, Supply Chain and Transportation (limited messages) will be supported.

Mailing:
https://mailxmltem.uspspostalone.com/Mailing/WebServices/wsdl/Mailing.wsdl

Supply Chain:
https://mailxmltem.uspspostalone.com/SupplyChain/WebServices/wsdl/SupplyChain.wsdl

Transportation:
https://mailxmltem.uspspostalone.com/Transportation/WebServices/wsdl/Transportation.wsdl

Data Distribution:
https://mailxmltem.uspspostalone.com/DataDistribution/WebServices/wsdl/DataDistribution.wsdl

Identification:
https://mailxmltem.uspspostalone.com/Identification/WebServices/wsdl/Identification.wsdl

Copyright © 2011 USPS®. All Rights Reserved.

PULL WSDL LINKS FOR PRODUCTION ENVIRONMENT

To consume the WSDL services, the customer must use one of the following URLs in the Production environments:

STRING-TYPE WSDL URL Link(s)

https://fast.uspspostalone.com/MLXMLServicesWeb/services/POAppointmentServices/wsdl/POAppointmentServices-MailXML60.wsdl

MESSAGE-TYPE WSDL URL Link(s)

The following link supports Mail.XML 8.1 version:
https://p1webservices.uspspostalone.com/MailXML81ALLMsgType/WebServices/wsdl/USPSMailXML81ALLMsgType.wsdl

The following link supports Mail.XML Modular Specification (9.x and above):

On the Modular XSD, we support following WSDL points based on the Messages Group (Mailing, Supply Chain, Transportation, Data Distribution, and Identification). The WSDL endpoint for the message group will not change, will support multiple versions of Modular spec. In Release 25 – only Mailing, Supply Chain and Transportation (limited messages) will be supported.

Mailing:
https://p1webservices.uspspostalone.com/Mailing/WebServices/wsdl/Mailing.wsdl

Supply Chain:
https://p1webservices.uspspostalone.com/SupplyChain/WebServices/wsdl/SupplyChain.wsdl

Transportation:
https://p1webservices.uspspostalone.com/Transportation/WebServices/wsdl/Transportation.wsdl

Data Distribution:
https://p1webservices.uspspostalone.com/DataDistribution/WebServices/wsdl/DataDistribution.wsdl

Identification:
https://p1webservices.uspspostalone.com/Identification/WebServices/wsdl/Identification.wsdl

PUSH WSDLs INFORMATION

Customers interested in using the Push Subscription model to receive the data feedback automatically at a specified time to their servers must understand the following WSDL name change information for both string-type and message-type WSDLs:

STRING-TYPE PUSH WSDL

Copyright © 2011 USPS®. All Rights Reserved.

The customer need to provide URL for their Web Server and uses the following WSDL for all Mail.XML versions i.e. 8.1.The String-type Push WSDL will retire after Mail.XML 9.0X release. USPS encourages users to move to message-type WSDL as soon as possible.

WSDL NAME: POCustomerMailXMLServices.wsdl

MESSAGE-TYPE PUSH WSDL

The customer need to provide URL for their Web Server and uses the following WSDL that only supports Mail.XML version 8.1. The Message-type WSDL will be strictly implemented post Mail.XML 9.0X version

For Mail.XML 8.1 – following WSDL name shall be used:
WSDL NAME: UserMailXML81PushMsgType.wsdl

For Mail.XML 10.A & 11.0 and future versions – following WSDL name shall be used:
WSDL NAME for Data Distribution: DataDistributionPush.wsdl
WSDL NAME for Transportation: TransportationPush.wsdl.

PUSH MESSAGES XSD NAME CHANGES INFORMATION

The USPS is implementing a new XSD name to support Mail.XML 8.1, and Mail.XML 9.0B Push subscription messages.

Copyright © 2011 USPS®. All Rights Reserved.

INDEX

A

ACS, 28, 617, 631, 632
asynchronous, 22, 39, 584

B

BeginCombinedMailingRequest, 29, 31, 32, 34, 36, 37, 38, 110, 112, 113, 238, 309, 310, 311, 436
BeginCombinedMailingResponse, 36, 37, 38, 110, 113, 114, 309, 311, 312, 313
bundle reports, 23
BundleDetail, 117, 118, 315, 316
BundleDetailCancelRequest, 30, 31, 33, 34, 110, 115, 117, 309, 313, 315, 316
BundleDetailCancelResponse, 110, 117, 118, 309, 315, 316
BundleDetailCreateRequest, 29, 30, 31, 32, 33, 34, 111, 115, 118, 120, 121, 185, 284, 309, 313, 316, 318, 319, 320, 383, 482
BundleDetailCreateResponse, 111, 115, 119, 120, 309, 313, 314, 318, 320
BundleID, 115, 116, 118, 179, 189, 203, 313, 314, 315, 316, 377, 387, 401
bundles, 38, 134, 332

C

cancelled, 115, 132, 171, 263, 298, 299, 313, 330, 369, 461, 495, 496, 622
Cast of Characters, 23
CloseMailingGroupRequest, 29, 31, 33, 34, 111, 122, 284, 309, 320, 321, 482
CloseMailingGroupResponse, 111, 123, 127, 309, 321, 322
combined mailing, 112, 310
CombinedMailingID, 36, 37, 38, 114, 157, 158, 238, 255, 280, 312, 355, 356, 436, 453, 478
ConsolidatedPeriodicalStatementCreateRequest, 111, 112, 114, 124, 157, 309, 311, 312, 323, 325, 355, 356
ConsolidatedPeriodicalStatementCreateResponse, 111, 129, 130, 309, 327, 328, 329
container, 23, 38, 39, 40, 118, 124, 125, 129, 131, 132, 133, 143, 149, 151, 158, 159, 170, 171, 175, 186, 187, 201, 214, 219, 220, 222, 227, 228, 236, 237, 244, 245, 253, 254, 284, 298, 299, 300, 303, 316, 323, 324, 327, 329, 330, 331, 341, 347, 349, 356, 357, 368, 369, 373, 384, 385, 399, 411, 416, 417, 419, 420, 425, 434, 435, 442, 443, 451, 452, 482, 495, 496, 497, 500, 505, 578, 582, 598
ContainerBundleReportCancelRequest, 31, 34, 111, 131, 132, 309, 329, 330
ContainerBundleReportCancelResponse, 111, 132, 133, 140, 309, 330, 331
ContainerBundleReportCreateRequest, 30, 31, 35, 36, 37, 38, 111, 124, 131, 133, 134, 140, 141, 143, 227, 309, 323, 329, 332, 338, 339, 341, 425
ContainerBundleReportCreateResponse, 35, 36, 37, 38, 111, 133, 140, 142, 143, 309, 331, 338, 340, 341
ContainerBundleReportQueryRequest, 31, 34, 111, 142, 143, 149, 309, 340, 341
ContainerID, 116, 118, 150, 159, 161, 172, 179, 183, 189, 194, 198, 203, 208, 212, 220, 223, 236, 253, 275, 301, 302, 303, 314, 315, 316, 348, 357, 359, 370, 377, 381, 387, 392, 396, 401, 406, 410, 417, 421, 434, 451, 473, 499, 500, 576, 578, 582, 584
ContainerPostage, 124, 125, 227, 241, 244, 245, 323, 425, 438, 442, 443
ContainerStatusQueryRequest, 111, 149, 309, 347, 348, 652
ContainerStatusQueryResponse, 111, 150, 151, 153, 309, 349, 351, 652
ContainerUpdateRequest, 29, 31, 33, 34, 111, 158, 160, 284, 309, 356, 358, 482
copalletization, 23, 38
Copalletized, 37
CustomerGroupID, 35, 36, 37, 115, 116, 118, 119, 120, 121, 122, 123, 124, 131, 132, 133, 134, 140, 141, 142, 143, 150, 153, 154, 160, 171, 172, 173, 174, 175, 178, 185, 186, 188, 199, 200, 201, 202, 213, 214, 215, 217, 218, 219, 220, 221, 222, 223, 224, 225, 226, 258, 260, 261, 262, 267, 286, 288, 290, 291, 293, 294, 301, 302, 305, 313, 314, 316, 317, 319, 320, 321, 322, 329, 330, 331, 332, 338, 339, 340, 341, 348, 351, 352, 359, 369, 370, 371, 372, 373, 376, 383, 384, 386, 397, 398, 399, 400, 411, 412, 413, 415, 416, 417, 418, 419, 420, 421, 422, 423, 424, 456, 458, 459, 460, 464, 485, 486, 487, 488, 490, 492, 498, 499, 502, 584, 585
customers, 22, 27, 39, 104, 110, 158, 215, 300, 356, 413, 497, 568

D

DMM, 38, 284, 482
duplicate, 38

Copyright © 2011 USPS®. All Rights Reserved.

E

eDoc, 1, 23, 27, 32, 33, 34, 39, 110, 122, 215, 308, 320, 413, 586, 652
eDropShip, 23, 39, 40, 149, 150, 347, 349, 505
EndCombinedMailingRequest, 29, 31, 32, 34, 36, 37, 38, 111, 155, 157, 309, 354, 355

F

flats, 38, 237, 254, 435, 452
Full-Service, 23, 27, 28, 29, 30, 31, 32, 33, 34, 35, 36, 37, 38, 39, 110, 171, 178, 186, 189, 197, 198, 200, 203, 211, 212, 216, 222, 237, 241, 244, 298, 302, 369, 376, 384, 387, 395, 396, 398, 401, 409, 410, 414, 420, 435, 438, 442, 495, 499, 610, 639, 653
Full-Service mailing, 32

I

IDEAlliance, 22, 27
irregular, 38

M

machinable, 38, 596, 643
Mail.dat, 22, 23, 27, 28, 37, 39, 158, 159, 160, 170, 171, 219, 220, 222, 223, 257, 298, 356, 357, 358, 368, 369, 416, 417, 419, 420, 421, 455, 495, 578, 582, 653
Mail.XML, 1, 22, 23, 24, 27, 28, 37, 38, 39, 104, 110, 122, 142, 158, 159, 160, 161, 162, 163, 164, 165, 166, 167, 168, 169, 170, 173, 219, 220, 222, 223, 284, 298, 299, 300, 308, 309, 320, 340, 356, 357, 359, 360, 361, 362, 363, 364, 365, 366, 367, 368, 371, 416,417, 418, 419, 420, 421, 482, 495, 496, 497, 568, 573, 590, 591, 592, 593, 594, 595, 596, 597, 598, 602, 603, 604, 605, 606, 607, 608, 609, 610, 611, 612, 613, 614, 615, 616, 617, 618, 619, 620, 621, 622, 623, 624, 625, 626, 627, 629, 630, 631, 632, 633, 634, 635, 636, 637, 638, 639, 640, 641, 643, 644, 645, 647, 648, 649, 650, 651, 652, 662, 663, 675, 676, 677
MaildatJobID, 116, 118, 119, 120, 122, 131, 132, 133, 134, 141, 142, 144, 150, 160, 171, 172, 175, 176, 186, 188, 199, 200, 201, 202, 213, 214, 220, 223, 258, 261, 262, 301, 302, 314, 317, 319, 320, 329, 331, 332, 339, 340, 342, 348, 358, 369, 370, 373, 374, 384, 386,397, 398, 400, 411, 412, 417, 421, 456, 458, 460, 498, 499, 578, 582
mailing, 22, 23, 27, 32, 33, 34, 37, 38, 110, 112, 113, 114, 118, 119, 122, 123, 128, 129, 130, 131, 132, 133, 134, 142, 153, 155, 157, 173, 175, 186, 201, 215, 216, 217, 219, 222, 225, 227, 238, 241, 244, 255, 256, 257, 260, 263, 264, 265, 267, 269, 282, 284, 293, 294, 298, 300, 304, 306, 310, 311, 312, 316, 318, 320, 321, 326, 327, 328, 329, 330, 331, 332, 340, 351, 353, 354, 355, 371, 373, 384, 399, 413, 414, 415, 416, 419, 420, 423, 424, 425, 436, 439, 442, 453, 454, 455, 458, 461, 462, 463, 465, 466, 480, 482, 490, 491, 495, 497, 501, 503, 653
MailingGroupID, 35, 36, 37, 115, 116, 118, 119, 120, 121, 122, 123, 131, 132, 133, 134, 140, 141, 142, 143, 144, 150, 153, 154, 161, 171, 172, 173, 174, 175, 178, 185, 186, 188, 199, 200, 201, 202, 213, 214, 217, 218, 219, 220, 221, 222, 223, 224, 225, 226, 227, 258, 260, 261, 262, 286, 288, 289, 290, 291, 293, 294, 301, 302, 305, 313, 314, 316, 317, 319, 320, 321, 322, 329, 330, 331, 332, 338, 339, 340, 341, 342, 348, 351, 352, 359, 369, 370, 371, 372, 373, 376, 383, 384, 386, 397, 398, 399, 400, 411, 412, 415, 416, 417, 418, 419, 420, 421, 422, 423, 424, 425, 456, 458, 459, 460, 485, 486, 487, 488, 490, 492, 498, 499, 502, 578, 584, 585
MailingGroupQueryRequest, 29, 31, 33, 34, 111, 173, 309, 371, 652
MailingGroupQueryResponse, 111, 173, 175, 309, 371, 373, 652
mailpiece, 175, 185, 200, 201, 213, 214, 215, 373, 383, 398, 399, 411, 413
MailPieceCancelRequest, 30, 31, 33, 34, 111, 175, 185, 186, 199, 213, 241, 309, 373, 383
MailPieceCreateRequest, 29, 30, 31, 32, 34, 35, 36, 111, 125, 185, 186, 187, 201, 227, 228, 245, 309, 323, 324, 383, 384, 385, 399, 425, 443
MailXMLMailGroupRequestHeaderInfo Block Opens, 173, 371
manifest, 23
mixed service, 29, 30, 31, 34, 124, 125, 187, 227, 228, 244, 245, 323, 324, 385, 425, 442, 443
Mixed Service, 29, 30, 31, 38, 159, 178, 189, 197, 198, 200, 203, 211, 212, 216, 357, 376, 387, 395, 396, 398, 401, 409, 410, 414
MLOCR, 23, 38, 153, 155, 260, 298, 300, 304, 306, 351, 353, 458, 495, 497, 501, 503, 616, 632
MLOCRrateANDpostageMarking, 177, 180, 191, 205, 375, 378, 389, 403
mother containers, 38

O

OpenMailingGroupRequest, 29, 30, 31, 32, 33, 34, 35, 36, 37, 111, 124, 215, 216, 217, 227, 284, 286, 310, 323, 413, 414, 425, 482
OriginalContainerLinkageCancelRequest, 30, 32, 33, 34, 111, 218, 219, 220, 221, 310, 416, 417, 418
OriginalContainerLinkageCreate, 29, 30, 31, 32, 33, 34

Copyright © 2011 USPS®. All Rights Reserved.

P

Package Services, 29, 32, 595, 614, 652
Pallets, 37, 576, 595, 596, 598
parcels, 38
PaymentMessageQueryRequest, 30, 31, 33, 34, 111, 225, 226, 310, 423, 652
PaymentMessageQueryResponse, 111, 226, 227, 310, 423, 424, 652
Periodicals, 30, 31, 33, 34, 35, 36, 37, 38, 124, 128, 142, 222, 227, 240, 243, 244, 256, 263, 265, 282, 323, 326, 340, 419, 424, 438, 441, 442, 454, 461, 463, 480, 587, 595, 607, 614, 622, 627, 652, 653, 655, 656
PeriodicalStatementCreateRequest, 30, 31, 33, 34, 35, 36, 37, 38, 111, 112, 114, 124, 128, 129, 156, 157, 227, 229, 242, 243, 244, 260, 310, 311, 312, 323, 326, 327, 354, 356, 424, 439, 440, 441, 442, 458, 655
PeriodicalStatementQueryRequest, 31, 34, 111, 243, 244, 248, 257, 310, 441, 442, 446, 455
piece detail, 23
piece ranging, 23
PieceID, 177, 180, 191, 205, 375, 378, 389, 403
pieces, 23, 32, 33, 34, 37, 38, 110, 115, 117, 125, 186, 187, 222, 227, 228, 231, 233, 237, 240, 244, 245, 249, 250, 257, 265, 269, 300, 304, 313, 315, 323, 324, 384, 385, 420, 425, 429, 430, 435, 438, 442, 443, 447, 455, 463, 467, 497, 501
PlanetCode, 176, 177, 178, 179, 180, 191, 205, 374, 376, 377, 389, 403
postage, 23, 28, 36, 37, 38, 110, 112, 117, 123, 124, 125, 128, 129, 151, 153, 155, 156, 157, 159, 175, 185, 201, 213, 214, 215, 219, 225, 226, 227, 228, 230, 231, 232, 233, 234, 235, 237, 239, 240, 241, 243, 244, 245, 247, 249, 250, 251, 252, 253, 254, 255, 256,257, 260, 263, 264, 265, 278, 281, 282, 299, 304, 309, 311, 315, 322, 323, 324, 326, 327, 349, 351, 354, 355, 357, 373, 383, 399, 411, 413, 416, 423, 424, 425, 427, 428, 429, 430, 431, 432, 433, 435, 437, 438, 439, 441, 442, 443, 445, 447, 448, 449, 450, 451, 452, 453, 454, 455, 458, 461, 462, 463, 475, 476, 479, 480, 496, 501, 653, 655, 658
Postage, 1, 23, 38, 125, 130, 132, 171, 180, 185, 191, 205, 226, 227, 231, 241, 242, 243, 244, 245, 249, 251, 252, 257, 266, 295, 296, 297, 323, 328, 330, 369, 378, 383, 389, 403, 423, 425, 428, 439, 440, 441, 442, 447, 449, 450, 455, 464, 493, 494, 592, 614, 625, 652, 653
postage adjustments, 23, 257, 455
postage statements, 23, 28, 36, 37, 38, 110, 123, 128, 155, 156, 157, 215, 244, 257, 263, 264, 282, 304, 322, 326, 354, 355, 413, 442, 455, 461, 462, 480, 501, 653
Postage Statements, 38
postage status, 23
PostageAdjustmentCreateRequest, 29, 31, 32, 34, 111, 257, 258, 260, 262, 310, 455, 458, 460
PostageStatementCancelRequest, 30, 31, 33, 34, 111, 263, 310, 461
PostageStatementCreateRequest, 29, 30, 32, 33, 35, 36, 37, 112, 114, 156, 157, 244, 247, 260, 266, 267, 270, 271, 272, 273, 274, 275, 310, 312, 354, 356, 442, 444, 458, 464, 468, 469, 471, 472, 473, 658
PostageStatementQueryRequest, 29, 33, 112, 310
PostageStatementStatusQueryRequest, 29, 31, 33, 34, 112, 281, 282, 310, 479, 480
PostalOne!, 22, 27, 28, 39, 40, 103, 110, 115, 117, 118, 120, 121, 122, 133, 157, 159, 171, 173, 231, 232, 233, 234, 235, 236, 237, 238, 241, 250, 253, 254, 255, 256, 260, 263, 264, 287, 294, 298, 299, 300, 303, 304, 306, 309, 313, 315, 316, 318, 319, 320, 332, 355,357, 369, 371, 429, 430, 432, 433, 434, 435, 436, 438, 439, 447, 448, 451, 452, 453, 454, 458, 461, 462, 484, 491, 495, 496, 497, 500, 501, 503, 504, 505, 567, 576, 580, 581, 598
protocol, 22

Q

qualification, 23, 39, 115, 118, 124, 125, 215, 227, 244, 245, 284, 287, 294, 313, 316, 323, 413, 425, 442, 482, 484, 491
Qualification, 38, 122, 161, 284, 286, 287, 288, 292, 293, 300, 320, 359, 482, 484, 485, 489, 490, 497
qualification reports, 23, 39, 284, 482
QualificationReportCreateRequest, 29, 30, 31, 32, 33, 34, 35, 36, 37, 112, 118, 124, 125, 134, 140, 153, 159, 185, 187, 189, 198, 200, 203, 212, 222, 227, 228, 245, 284, 287, 288, 289, 310, 316, 323, 324, 332, 338, 351, 357, 383, 385, 387, 396, 398, 401, 410, 419, 420, 425, 443, 482, 484, 485, 486, 655, 658

R

ReconciliationReportQueryRequest, 30, 31, 33, 34, 112, 293, 294, 310, 490, 491, 652
ReturnInfo, 114, 117, 121, 122, 123, 124, 130, 131, 133, 141, 142, 148, 149, 153, 155, 157, 158, 171, 172, 174, 175, 185, 186, 200, 201, 214, 217, 218, 220, 221, 223, 224, 225, 226, 242, 243, 248, 257, 261, 262, 264, 265, 266, 267, 268, 269, 281, 282, 284, 288, 289,297, 298, 300, 303, 307, 312, 313, 316, 319, 320, 322, 328, 329, 331, 339, 340, 346, 347, 351, 353, 355, 356, 369, 370, 372, 373, 383, 384, 398, 399, 412, 415, 416, 417, 419, 421, 422, 423, 424, 440, 441, 445, 455, 459, 460, 462, 463, 464, 465, 466, 467, 479, 480, 482, 485, 486, 495, 497, 500, 501, 504, 587, 588

Copyright © 2011 USPS®. All Rights Reserved.

S

SASP, 125, 227, 245, 323, 425, 443
Services Oriented Architecture. *See* SOA
Sibling Container ID, 38
SiblingContainerCancelRequest, 30, 32, 33, 34, 112, 298, 299, 300, 310, 495, 496, 497
SiblingContainerCreateRequest, 29, 30, 31, 32, 33, 34, 112, 299, 300, 302, 303, 310, 496, 497, 498, 500, 501
SOA, 22
SOAP, 40, 505, 662
SortationLevel, 170, 306, 368, 503
spoilage, 23, 257, 455
Standard Mail, 29, 32, 37, 38, 222, 419, 595, 607, 614, 629, 652, 654, 658, 659
SubmittingParty, 28, 113, 116, 118, 122, 123, 127, 131, 134, 143, 149, 153, 154, 157, 160, 173, 175, 188, 202, 215, 219, 223, 225, 230, 244, 247, 258, 263, 282, 286, 293, 298, 301, 304, 312, 314, 317, 321, 325, 330, 332, 341, 347, 351, 352, 355, 358, 371, 373, 385, 400, 413, 417, 421, 423, 427, 441, 444, 456, 461, 480, 483, 490, 496, 498, 502, 586, 662
SubmittingSoftware, 113, 116, 119, 122, 127, 132, 134, 143, 150, 154, 157, 160, 173, 176, 188, 202, 216, 219, 223, 225, 230, 244, 247, 258, 263, 282, 286, 293, 298, 301, 304, 312, 314, 317, 321, 325, 330, 332, 341, 348, 352, 355, 358, 371, 373, 386, 400, 413, 417, 421, 423,427, 441, 445, 456, 461, 480, 483, 490, 496, 498, 502
supplement, 27, 39
supply chain, 22, 23
synchronous, 22

T

technology, 22, 39
Test Environment for Mailers Checklist and Troubleshooting Guide, 27
threshold, 32
TotalCopies, 256, 287, 454, 484, 577
TotalPieces, 256, 273, 277, 279, 280, 287, 295, 296, 297, 454, 471, 475, 477, 478, 484, 492, 493, 495, 577
Tracking ID, 39, 141, 339, 663
Tray Barcodes, 38
Trays, 37, 595, 598, 603

U

United States Postal Service, 22
UPD, 123, 132, 171, 185, 219, 260, 299, 321, 330, 369, 383, 416, 458, 496, 625, 653
UserLicenseCode, 116, 118, 119, 121, 122, 131, 133, 134, 141, 142, 144, 160, 171, 172, 175, 176, 186, 188, 200, 201, 202, 214, 220, 223, 258, 260, 262, 301, 302, 314, 317, 319, 320, 329, 331, 332, 339, 340, 342, 358, 369, 370, 373, 374, 384, 386, 398, 399, 400, 412, 417,421, 456, 458, 460, 498, 499, 578, 582
USPS, 22, 23, 27, 28, 33, 34, 37, 38, 39, 40, 103, 104, 113, 117, 120, 121, 122, 123, 124, 128, 132, 149, 157, 158, 170, 173, 185, 213, 215, 217, 219, 220, 221, 224, 227, 242, 243, 244, 260, 262, 263, 265, 266, 287, 288, 293, 294, 299, 300, 303, 304, 312, 315,316, 318, 319, 320, 321, 323, 326, 330, 347, 355, 356, 368, 371, 383, 411, 413, 415, 416, 418, 421, 422, 424, 440, 441, 442, 458, 460, 461, 463, 464, 484, 485, 490, 491, 496, 497, 500, 501, 505, 567, 568, 583, 644, 653, 663, 677

V

VersionID, 118, 239, 277, 316, 437, 475, 577
VersionName, 239, 437, 577
volumes, 23

W

web services, 22, 39, 103, 110, 567
Web services. *See* web services
Wizard Web Services. *See* WWS
WSDL, 103, 104, 567, 568, 675, 676, 677
WWS, 39, 110

Z

Zone, 235, 253, 274, 277, 433, 451, 472, 475

Copyright © 2011 USPS®. All Rights Reserved.