Mail.XML 13.0B Technical Specification

eDoc

September 26, 2014

Prepared by

United States Postal Service

Release Version Support

This document contains information pertaining to Mail.XML release version 13.0B and the following USPS *PostalOne!* Release:

- Release 35 July 2013
- Release 36 October 2013
- Release 37 January 2014
- Release 38 August 2014

Technical Support from the USPS Help Desk and Tier 2 Support:

The USPS provides Mail.XML technical support for mailers/vendors and support is only specific to the business rules it pertains to implementation of business transactions, error codes/descriptions and exception handling with the Mail.XML implementations.

The USPS does not provide nor it is equipped to provide technical support for software development tools or IDEs (Integrated Development Environments) like Visual Studio, and software development related activities as they pertain to different technology specific programming environments for different companies, such as .Net, Java, Visual Basic, Power Builder, C, C++ etc.

The Mailer/Vendor is responsible for obtaining technical support and assistance directly from the IDE vendor such as Microsoft, IBM or Sun/Oracle for software development related help needs.

Trademarks

The following trademarks are owned by the United States Postal Service:

ACS®, CASS™, CASS Certified™, Certified Mail™, DMM®, FAST®, First-Class™, First-Class Mail®, Full-Service ACS™, IM®, IMb™, IMb Tracing™, Intelligent Mail®, OneCode ACS®, OneCode Solution®, PLANET Code®, *PostalOne!*®, POSTNET™, Postal Service™, Priority Mail®, Registered Mail™, RIBBS™, Standard Mail®, The Postal Service®, United States Postal Service®, USPS®, USPS.COM®, ZIP®, ZIP Code™, ZIP + 4® and ZIP+4™.

IDEAlliance and Mail.dat are registered trademarks of the International Digital Enterprise Alliance, Inc. (IDEAlliance).

Sun, Sun Microsystems, and Java are trademarks or registered trademarks of Sun Microsystems, Inc.

Microsoft, Microsoft Windows, and Microsoft Internet Explorer are registered trademarks of Microsoft Corporation.

All other trademarks used are the property of their respective owners.

TABLE OF CONTENTS

Table of Contents i

Document Change History xvii

1. Postal Service Mail.XML Technical Specification 1

1.1 Program Overview 1
1.2 About Schema Modularization 2
1.3 What Schemas Cover Electronic Documentation (eDoc) Functionality? 3
1.4 USPS Limitation Rule on Transaction Requests 3
1.5 Recommended File Sizes for Optimum Mail.XML Performance 3
1.6 Roadmap of Mail.XML 3
1.7 Purpose 4
1.8 Intended Audience 4
1.9 About This Document 4
1.10 How to Read Data Structure 5
1.11 Issue Resolution 5
1.12 Mail.XML Message Hierarchy 5
1.12.1 Full-Service & Mixed Service Mailings for First-Class, Standard Mail, and Package Services 5
1.12.2 Full-Service & Mixed Service Mailings for Periodicals 7
1.12.3 First-Class Mail, Standard Mail, and Package Services Mailings 8
1.13 Workflows 11
1.13.1 Non-Periodicals without Full-Service 11
1.13.2 Periodicals without Full-Service 12
1.13.3 Non-Periodicals with Full-Service 12
1.13.4 Periodicals with Full-Service 12
1.13.5 Combined/ Commingled Mailing - non-Periodicals 13
1.13.6 Combined/ Commingled Mailing - Periodicals 14
1.13.7 Copalletized Mailing for Trays on Pallets - non-Periodicals 14
1.13.8 Copalletized Mailing for Bundles on Pallets - Standard Mail 14
1.13.9 Copalletized Mailing for Bundles on Pallets - Periodicals Mail 15
1.14 Acceptance of less than 10,000 mailpieces 15
1.15 Exceptions 16
1.16 Incentive Programs Enrollment 16
1.17 Incentives 16

2. *PostalOne!* – eDoc Mail.XML Messages 18

2.1 Overview 18
2.2 Message Response Retrieval Request Processing 19
2.2.1 Fault and Fault Recovery Messages 19
2.3 Additional Rules/Constraints 19
2.3.1 Container Status Messages 19
2.3.2 ContainerStatusQueryResponse Error Codes / Return Values 19
2.4 *PostalOne!* WSDL Information 19

Copyright © 2014 USPS®. All Rights Reserved

2.5 WSDLs and XSDs 20
2.5.1 Pull WSDL Information 20
2.5.2 PUSH WSDLs Information 20
2.6 Permit Information 20
2.6.1 Postage Statement By/For Information 25
3. Mail.XML 13.0B eDoc and Miscellaneous Messages 27
3.1 BeginCombinedMailingRequest 27
3.1.1 BeginCombinedMailingRequest Data Structure 28
3.2 BeginCombinedMailingResponse 28
3.2.1 BeginCombinedMailingResponse Data Structure 29
3.3 BundleDetailCancelRequest 30
3.3.1 BundleDetailCancelRequest Data Structure 30
3.4 BundleDetailCancelResponse 31
3.5 BundleDetailCreateRequest 32
3.5.1 BundleDetailCancelRequest Data Structure 32
3.6 BundleDetailCreateResponse 33
3.6.1 BundleDetailCreateResponse Data Structure 33
3.7 CloseMailingGroupRequest 34
3.7.1 CloseMailingGroupRequest Data Structure 34
3.8 CloseMailingGroupResponse 34
3.8.1 CloseMailingGroupResponse 35
3.9 ConsolidatedPeriodicalStatementCreateRequest 35
3.9.1 ConsolidatedPeriodicalStatementCreateRequest Data Structure 37
3.10 ConsolidatedPeriodicalStatementCreateResponse 39
3.11 ContainerBundleReportCancelRequest 40
3.11.1 ContainerBundleReportCancelRequest Data Structure 41
3.12 ContainerBundleReportCancelResponse 41
3.12.1 ContainerBundleReportCancelResponse Data Structure 41
3.13 ContainerBundleReportCreateRequest 42
3.13.1 ContainerBundleReportCreateRequest Data Structure 42
3.14 ContainerBundleReportCreateResponse 44
3.14.1 ContainerBundleReportCreateResponse Data Structure 44
3.15 ContainerBundleReportQueryRequest 45
3.15.1 ContainerBundleReportQueryRequest Data Structure 45
3.16 ContainerBundleReportQueryResponse 46
3.16.1 ContainerBundleReportQueryResponse Data Structure 46
3.17 ContainerManifestCreateRequest 48
3.17.1 ContainerManifestCreateRequest Data Structure 48
3.18 ContainerManifestCreateResponse 49
3.18.1 ContainerManifestCreateResponse Data Structure 49
3.19 ContainerManifestUpdateRequest 49
3.19.1 ContainerManifestUpdateRequest Data Structure 50
3.20 ContainerManifestUpdateResponse 50
3.20.1 ContainerManifestUpdateResponse Data Structure 50

Copyright © 2014 USPS®. All Rights Reserved

3.21 ContainerStatusNotification 51
3.21.1 ContainerStatusNotification Data Structure 51
3.22 ContainerStatusQueryRequest 52
3.22.1 ContainerStatusQueryRequest Data Structure 52
3.23 ContainerStatusQueryResponse 53
3.23.1 ContainerStatusQueryResponse Data Structure 54
3.24 ContainerUpdateRequest 54
3.24.1 ContainerUpdateRequest Data Structure 56
3.25 ContainerUpdateResponse 56
3.25.1 ContainerUpdateResponse Data Structure 57
3.26 CustomerMailReportCreateRequest 57
3.26.1 CustomerMailReportCreateRequest Data Structure 58
3.27 CustomerMailReportCreateResponse 59
3.27.1 CustomerMailReportCreateResponse Data Structure 59
3.28 EndCombinedMailingRequest 59
3.28.1 EndCombinedMailingRequest Data Structure 60
3.29 EndCombinedMailingResponse 61
3.29.1 EndCombinedMailingResponse Data Structure 61
3.30 MailingGroupQueryRequest 62
3.30.1 MailingGroupQueryRequest Data Structure 62
3.31 MailingGroupQueryResponse 63
3.31.1 MailingGroupQueryResponse Data Structure 63
3.32 MailPieceCancelRequest 63
3.32.1 MailPieceCancelRequest Data Structure 63
3.33 MailPieceCancelResponse 66
3.33.1 MailPieceCancelResponse Data Structure 67
3.34 MailPieceCreateRequest 67
3.34.1 MailPieceCreateRequest Data Structure 69
3.35 MailPieceCreateResponse 70
3.35.1 MailPieceCreateResponse Data Structure 70
3.36 MailPieceUpdateRequest 71
3.36.1 MailPieceUpdateRequest Data Structure 72
3.37 MailPieceUpdateResponse 74
3.37.1 MailPieceUpdateResponse Data Structure 75
3.38 OpenMailingGroupRequest 75
3.38.1 OpenMailingGroupRequest Data Structure 75
3.39 OpenMailingGroupResponse 76
3.39.1 OpenMailingGroupResponse Data Structure 76
3.40 PeriodicalStatementCreateRequest 77
3.40.1 PeriodicalStatementCreateRequest Data Structure 79
3.41 PeriodicalStatementCreateResponse 80
3.41.1 PeriodicalStatementCreateResponse Data Structure 80
3.42 PeriodicalStatementQueryRequest 82
3.42.1 PeriodicalStatementQueryRequest Data Structure 82

Copyright © 2014 USPS®. All Rights Reserved

3.43 PeriodicalStatementQueryResponse 82
3.43.1 PeriodicalStatementQueryResponse Data Structure 83
3.44 PostageStatementCancelRequest 84
3.44.1 PostageStatementCancelRequest Data Structure 84
3.45 PostageStatementCancelResponse 84
3.45.1 PostageStatementCancelResponse Data Structure 84
3.46 PostageStatementCreateRequest 85
3.46.1 PostageStatementCreateRequest Data Structure 88
3.47 PostageStatementCreateResponse 88
3.47.1 PostageStatementCreateResponse Data Structure 88
3.48 PostageStatementQueryRequest 90
3.48.1 PostageStatementQueryRequest Data Structure 90
3.49 PostageStatementQueryResponse 91
3.49.1 PostageStatementQueryResponse Data Structure 91
3.50 PostageStatementStatusQueryRequest 92
3.50.1 PostageStatementStatusQueryRequest Data Structure 92
3.51 PostageStatementStatusQueryResponse 93
3.51.1 PostageStatementStatusQueryResponse Data Structure 93
3.52 QualificationReportCreateRequest 94
3.52.1 QualificationReportCreateRequest Data Structure 94
3.53 QualificationReportCreateResponse 94
3.53.1 QualificationReportCreateResponse Data Structure 94
3.54 QualificationReportQueryRequest 95
3.54.1 QualificationReportQueryRequest Data Structure 95
3.55 QualificationReportQueryResponse 96
3.55.1 QualificationReportQueryResponse Data Structure 96
3.56 QualificationReportSummaryCreateRequest 97
3.56.1 QualificationReportSummaryCreateRequest Data Structure 97
3.57 QualificationReportSummaryCreateResponse 98
3.57.1 QualificationReportSummaryCreateResponse Data Structure 98
3.58 QualificationReportDetailCreateRequest 99
3.58.1 QualificationReportDetailCreateRequest Data Structure 99
3.59 QualificationReportDetailCreateResponse 99
3.59.1 QualificationReportDetailCreateResponse Data Structure 99
3.60 SummaryZipDestinationReportCreateRequest 100
3.60.1 SummaryZipDestinationReportCreateRequest Data Structure 101
3.61 SummaryZipDestinationReportCreateResponse 102
3.61.1 SummaryZipDestinationReportCreateResponse Data Structure 102
3.62 ReconciliationReportQueryRequest 103
3.62.1 ReconciliationReportQueryRequest Data Structure 103
3.63 ReconciliationReportQueryResponse 104
3.63.1 ReconciliationReportQueryResponse Data Structure 104
3.64 Message Response Retrieval Request Processing 105
3.64.1 Fault and Fault Recovery Messages 105

Copyright © 2014 USPS®. All Rights Reserved

4. Complex and Attribute Data Types Data Structure for Mail.XML 13.0B 106
4.1 complexType: abstractPostageStatementDataType 106
4.2 complexType: AddressType 107
4.3 complexType: basicReturnInfoType 108
4.4 complexType: bundleRecordType 108
4.5 complexType: bundleVersionRecordType 109
4.6 complexType: CertificationDataType 109
4.7 complexType: CommonContactType 110
4.8 Complex Type: consigneeFacilityType 110
4.9 complexType: ContactIDType 111
4.10 complexType: ContainerCountType 111
4.11 complexType: ContainerIDType 112
4.12 complexType: containerKeysInfoType 112
4.13 complexType: containerPostInductionInfoType 113
4.14 complexType: ContainerStatusIDType 113
4.15 complexType: containerStatusInfoType 114
4.16 complexType: ContainerType 116
4.17 complexType: contentUspsSummaryType 116
4.18 complexType: ContainerPostageType 117
4.19 complexType: createPostageStatementType 117
4.20 Complex Type: errorWarningType 124
4.21 complexType: FullContainerIDType 125
4.22 complexType: GPSCoordinates 126
4.23 complexType: IntelligentMailBarcodeType 126
4.24 complexType: LargeTransactionDividerGroupType 127
4.25 complexType: LinkageType 127
4.26 complexType: LinkingContainerIDType 127
4.27 complexType: MaildatContainerIDType 128
4.28 complexType: MailerDataRequestType 128
4.29 complexType: MailerDataType 128
4.30 complexType: MailXMLContainerIDType 129
4.31 Complex Type: mailxmlDetailType 129
4.32 attributeGroup: MailXMLMsgResponseHeaderInfo 130
4.33 attributeGroup: MailXMLPostageStatementRequestHeaderInfo 130
4.34 complexType: MIDType 131
4.35 complexType: ParticipantIDType 131
4.36 complexType: PermitPublicationDataType 131
4.37 Complex Type: pickupApptBlockResponseType 133
4.38 complexType: ReturnInfo 133
4.39 complexType: SubmittingSoftwareType 134

Copyright © 2014 USPS®. All Rights Reserved

4.40 complexType: CertificationDataType 134
4.41 complexType: ContainerCountType 135
4.42 complexType: MailOwnerBlockType 135
4.43 complexType: MailerDataType 136
4.44 complexType: MailerDataRequestType 136
4.45 complexType: MailCharacteristicsType 137
4.46 attributeGroup: MailXMLPostageStatementResponseHeaderInfo 137
4.47 complexType: QualificationReportDataType 137
4.48 complexType: QualificationReportPreparerDataType 138
4.49 complexType: ContainerPostageType 139
4.50 complexType: bundleDetailType 140
4.51 complexType: IntelligentMailBarcodeType 142
4.52 complexType: ContainerCountType 143
4.53 complexType:ContainerErrorWarningBlockType 143
4.54 complexType: ContainerInfoData 144
4.55 attributeGroup: ContainerManifestHeaderInfo 150
4.56 complexType:ContainerPostageType 151
4.57 complexType: ContainerDetailData 151
4.58 complexType: ComponentPeriodicalAdPercentType 152
4.59 complexType: ComponentWeightUpdateType 153
4.60 complexType: CreatePeriodicalStatementType 153
4.61 complexType: containerInfoDataType 155
4.62 complexType: palletHandoffInfoType 156
4.63 attributeGroup: PalletInfoMsgHeaderInfo 156
4.64 complexType: containerPreInductionInfoType 157
4.65 complexType: containerReleaseInfoType 158
4.66 complexType: inductionCloseoutInfoType 158
4.67 complexType: inductionIssuesType 159
4.68 complexType: ConsolidatorCommunicationInfoType 159
4.69 complexType: CreatePostageStatementType 162
4.70 complexType: DataRecipient 168
4.71 complexType: DocumentVersionData 168
4.72 complexType: DocumentVersionDataWithPermit 168
4.73 complexType: ExtraServiceData 169
4.74 complexType: ExtraServiceSummaryData 169
4.75 Complex Type: Fault 170
4.76 complexType: FullContainerIDType 170
4.77 complexType: FullComponentType 171
4.78 complexType: IntelligentMailBarcodeType 171
4.79 complexType: IntelligentMailPackageBarcodeType 172

Copyright © 2014 USPS®. All Rights Reserved

4.80 complexType:LargeTransactionDividerGroupOptionalType 173
4.81 complexType: LargeQualReportTransDividerType 173
4.82 complexType: LineItemSummaryData 174
4.83 complexType: MailOwnerBlockType 177
4.84 complexType:MailPieceBlockGroupType 178
4.85 complexType:MailPieceBlockType 178
4.86 complexType: MailerDataType 180
4.87 complexType: MailerDataRequestType 181
4.88 complexType: MailerSerialNumberBlockType 181
4.89 complexType:MailingGroupDataType 182
4.90 complexType: MailingGroupSummary 182
4.91 complexType: MIDType 182
4.92 attributeGroup: MailXMLOpenMailGroupRequestHeaderInfo 183
4.93 attributeGroup: MailXMLMailOpenGroupResponseAcceptHeaderInfo 183
4.94 attributeGroup: MailXMLMailOpenGroupResponseRejectHeaderInfo 183
4.95 attributeGroup: MailXMLDashboardHeaderInfo 183
4.96 attributeGroup: MailXMLMailGroupRequestHeaderInfo 183
4.97 attributeGroup: MailXMLMailGroupResponseHeaderInfo 184
4.98 attributeGroup: MailXMLHeaderInfo 184
4.99 attributegroup: MailXMLMsgResponseHeaderInfo 184
4.100 attributeGroup: MailXMLPieceRangeBlockType 184
4.101 complexType: MPSRResponseBlockType 188
4.102 attributeGroup: MailXMLPostageStatementResponseHeaderInfo 188
4.103 attributeGroup: MailXMLPostageStatementRequestHeaderInfo 188
4.104 attributeGroup: MailXMLQualReportRequestHeaderInfo 189
4.105 attributeGroup: MailXMLQualReportResponseHeaderInfo 190
4.106 complexType: ManifestErrorWarningDetailType 190
4.107 complexType: ManifestErrorWarningSummaryType 191
4.108 complexType: manifestMailType 191
4.109 complexType: ManifestTrackingInformationType 192
4.110 complexType: palletContainerVersionRecordType 193
4.111 complexType: palletContainerRecordType 194
4.112 complexType: paymentInformationType 194
4.113 complexType: PieceBarcodeRecordBlockType 196
4.114 complexType: PieceBarcodeRecordBlockForMailXMLType 197
4.115 complexType: pieceLiteRecordBlockType 197
4.116 complexType: pieceLiteBlockType 198
4.117 complexType: PeriodicalLineItemData 198
4.118 complexType: PeriodicalStatementDataType 199
4.119 complexType: ParticipantIDType/ SubmittingParty 203

Copyright © 2014 USPS®. All Rights Reserved

4.120 complexType: PermitPublicationDataType 203
4.121 attributeGroup: PostageMessageHeaderInfo 204
4.122 complexType: PostageStatementSummaryType 204
4.123 complexType: PostageStatementDataType 204
4.124 complexType: PostageStatementLineItemData 211
4.125 complexType: PTPubDiscountsandFeesType 216
4.126 complexType: PTincentivesFeesKeysType 217
4.127 complexType: PTWithIncentivesFeesDeliveryType 218
4.128 complexType: PTpostageKeysType 218
4.129 complexType: PTpostagePricesType 219
4.130 complexType: PTincentivesFeesRulesBlockType 220
4.131 complexType: PTExtraServicesKeysType 220
4.132 complexType: PTExtraServicesPricesBlockType 221
4.133 complexType: QualificationReport 222
4.134 complexType: QualificationSummaryReport 223
4.135 complexType: QualificationReportDataType 224
4.136 complexType: QualificationReportDetailDataType 224
4.137 complexType: QualificationReportSummaryDataType 225
4.138 complexType: QualificationPreparerDataType 226
4.139 complexType: QualificationReportPreparerDataType 227
4.140 complexType: ReturnInfoType 228
4.141 complexType: SackTrayContainerVersionRecordType 229
4.142 complexType: SackTrayContainerRecordType 229
4.143 complexType: STCForContainerOrTrayType 230
4.144 complexType: MPSRequestType 230
4.145 complexType: MPSRBlockType 231
4.146 complexType: ReturnInfo 231
4.147 complexType: SubmittingSoftwareType 231
4.148 complexType: UspsSummaryType 231
4.149 complexType: SubmittingSoftwareType 232
4.150 complexType: SummaryRecordUpdateType 233

5. Mail.XML 13.0B Simple Types Data Structure 242

5.1 simpleType: actionCodeType 242
5.2 simpleType: addressCorrectionMoveType 242
5.3 simpleType: additionalInHomeRangeType 242
5.4 simpleType: adjustmentStatusType 242
5.5 simpleType: adjustmentType 242
5.6 simpleType: agencyCostCodeType 242
5.7 simpleType: apptMethodType 242
5.8 simpleType: apptStateType 243

Copyright © 2014 USPS®. All Rights Reserved

5.9 simpleType: apptStatusType 243
5.10 simpleType: apptTypeType 243
5.11 simpleType: barcodeRateType 243
5.12 simpleType: billReasonCodeType 243
5.13 simpleType: bundleDetailLevelType 243
5.14 simpleType: bundleLevelType 244
5.15 simpleType: bundleRecordStatusType 244
5.16 simpleType: bundleStatusType 244
5.17 simpleType: canadaAdMailOnlyType 244
5.18 simpleType: chargeableBundleLevelType 244
5.19 simpleType: chargeableContainerType 245
5.20 simpleType: chargeableContainerLevelType 245
5.21 simpleType: chargeableEntryLevelType 245
5.22 simpleType: characteristicContentType 245
5.23 simpleType: characteristicFeeType 245
5.24 simpleType: characteristicIncentiveType 245
5.25 simpleType: classNotificationType 246
5.26 simpleType: closeoutIrregularitiesType 246
5.27 simpleType: closeoutResolutionType 247
5.28 simpleType: communicationRoleType 247
5.29 simpleType: componentWeightSourceType 247
5.30 simpleType: componentWeightStatusType 247
5.31 simpleType: consigneeContentIDType 247
5.32 simpleType: containerBundleStatusType 247
5.33 simpleType: containerAcceptanceDateType 247
5.34 simpleType: cccLevelType 247
5.35 simpleType: containerGroupingDescriptionType 248
5.36 simpleType: containerGrossWeightType 248
5.37 simpleType: containerHeightType 248
5.38 simpleType: containerLevelType 248
5.39 simpleType: containerPickupDateType 250
5.40 simpleType: containerPickupTimeType 250
5.41 simpleType: containerShipDateType 250
5.42 simpleType: containerShipTimeType 250
5.43 simpleType: contactType 250
5.44 simpleType: containerStatusType 250
5.45 simpleType: containerHeightSourceType 251
5.46 simpleType: CQTdatabaseIDType 251
5.47 simpleType: creditDebitIndicator 251
5.48 simpleType: CRIDType 251

Copyright © 2014 USPS®. All Rights Reserved

5.49 simpleType: cRIDStatusType 251
5.50 simpleType: csaTemplateType 251
5.51 simpleType: csaStatusType 251
5.52 simpleType: databaseContainerIDType 252
5.53 simpleType: dayFrequencyType 252
5.54 simpleType: daysOfWeekType 252
5.55 simpleType: DirectOrMixedCategoryType 252
5.56 simpleType: dec18-8 252
5.57 simpleType: deliverabilityCodeType 252
5.58 simpleType: DMLType 252
5.59 simpleType: electronicFileType 253
5.60 simpleType: emailType 253
5.61 simpleType: enclosedByType 253
5.62 simpleType: entryDiscountType 253
5.63 simpleType: entryFacilityType 253
5.64 simpleType: entryPointEDPostalCodeType 253
5.65 simpleType: entryPointEDFacilityTypeType 254
5.66 simpleType: entryPointADLocaleKeyType 254
5.67 simpleType: entryPointADPostalCodeType 254
5.68 simpleType: ErrorWarningCodeType 254
5.69 simpleType: es3 254
5.70 simpleType: es4 254
5.71 simpleType: es5 254
5.72 simpleType: exemptionCodeType 254
5.73 simpleType: fASTSchedulerIDType 254
5.74 simpleType: feeNotificationType 255
5.75 simpleType: flatRateIndicatorType 255
5.76 simpleType: formType 255
5.77 simpleType: fullServiceComplianceIndicatorType 255
5.78 simpleType: fspiType 255
5.79 simpleType: gPSSystemType 255
5.80 simpleType: IDType 256
5.81 simpleType: iMBType 256
5.82 simpleType: IMcbType 256
5.83 simpleType: IMpbType 256
5.84 simpleType: iMBarcodeIDType 256
5.85 simpleType: iMBSerialNumber6Type 256
5.86 simpleType: iMBSerialNumber9Type 256
5.87 simpleType: iMBUpperSerializationType 256
5.88 simpleType: iMBLowerSerializationType 256

Copyright © 2014 USPS®. All Rights Reserved

5.89 simpleType: IMtbType 256
5.90 simpleType: includedInOtherDocType 257
5.91 simpleType: internalDateType 257
5.92 simpleType: internationalPSPartType 257
5.93 simpleType: internationalZoneType 257
5.94 simpleType: internationalPSPartSectionType 257
5.95 simpleType: internationalPriceGroupType 258
5.96 simpleType: inCountyOutCountyIndicatorType 258
5.97 simpleType: jobIDType 258
5.98 simpleType: localeKeyType 258
5.99 simpleType: inductionStatusType 258
5.100 simpleType: logicalPhysicalBundleIndicatorType 258
5.101 simpleType: logicalPhysicalContainerIndicatorType 258
5.102 simpleType: LowerDateRange 259
5.103 simpleType: mailAgreementTypeType 259
5.104 simpleType: mailClassType 259
5.105 simpleType: MailPieceScanAvailabilityDate 259
5.106 simpleType: MailPieceScanRecordCount 259
5.107 simpleType: maildatContainerStatusType 259
5.108 simpleType: mailerID6Type 259
5.109 simpleType: MID6 259
5.110 simpleType: mailerID9Type 260
5.111 simpleType: MID9 260
5.112 simpleType: mailXMLContainerType 260
5.113 simpleType: mailXMLPresentationCategoryType 260
5.114 simpleType: manifestType 261
5.115 simpleType: manifestMailClassType 261
5.116 simpleType: manifestRateLevelType 261
5.117 simpleType: manifestExtraServiceCode 262
5.118 simpleType: MarketingOrFulfillmentType 262
5.119 simpleType: mIDStatusType 262
5.120 simpleType: meteredAffixedMethodType 263
5.121 simpleType: MLOCRRateType 263
5.122 simpleType: monthType 263
5.123 simpleType: moveUpdateMethodType 263
5.124 simpleType: MPUIDType 263
5.125 simpleType: MPSQueryType 263
5.126 simpleType: MPSStateType 263
5.127 simpleType: ns01 264
5.128 simpleType: ns02 264

Copyright © 2014 USPS®. All Rights Reserved

5.129 simpleType: ns03 264
5.130 simpleType: ns04 264
5.131 simpleType: ns05 264
5.132 simpleType: ns06 264
5.133 simpleType: ns09 264
5.134 simpleType: ns10 264
5.135 simpleType: ns11 264
5.136 simpleType: ns14 264
5.137 simpleType: ns22 265
5.138 simpleType: n01 265
5.139 simpleType: n02 265
5.140 simpleType: n03 265
5.141 simpleType: n05 265
5.142 simpleType: n06 265
5.143 simpleType: addressType 265
5.144 simpleType: operatingModeType 265
5.145 simpleType: onePassPlannedOrActualFlagType 265
5.146 simpleType: onePassOrTwoPassType 266
5.147 simpleType: packageIDType 266
5.148 simpleType: PackageServicesType 266
5.149 simpleType: packageCountRangeType 266
5.150 simpleType: packagingMethodType 266
5.151 simpleType: palletHandlingUnitType 266
5.152 simpleType: palletType 266
5.153 simpleType: parentContainerRefIDType 267
5.154 simpleType: percentageType 267
5.155 simpleType: periodicalPriceType 267
5.156 simpleType: permitTypeType 267
5.157 simpleType: phoneNumberType 267
5.158 simpleType: pickupOrDeliveryType 267
5.159 simpleType: planetCodeType 268
5.160 SimpleType: postageAutoFinalizationType 268
5.161 simpleType: postageGroupingIDType 268
5.162 simpleType: postagePaymentMethodType 268
5.163 simpleType: postageStatementLineNumber1Type 268
5.164 simpleType: postageStatementLineNumber2Type 269
5.165 simpleType: postageStatementLineNumber3Type 269
5.166 simpleType: postageStatementStatusType 269
5.167 simpleType: priceType 270
5.168 simpleType: primarySecondaryIndicatorType 270

Copyright © 2014 USPS®. All Rights Reserved

5.169 simpleType: processingCategoryType 270
5.170 simpleType: processingCodeType 270
5.171 simpleType: PTFileIDType 271
5.172 simpleType: PTExtraServMinBrkGreaterThanoeEqlType 271
5.173 simpleType: PTExtraServMaxBrkLessThanorEqlType 271
5.174 simpleType: PTExtraServFlatFeeretailType 271
5.175 simpleType: PTExtraServIncrementFeeType 271
5.176 simpleType: PTMachinabilityPreparationType 271
5.177 simpleType: PTExtraServIncrementBreakType 271
5.178 simpleType: PTExtraServicesType 272
5.179 simpleType: PTContSortBundleSortType 272
5.180 simpleType: PTMailEntryType 273
5.181 simpleType: postagePaymentMethodType 273
5.182 simpleType: PTIncentiveFeeTypeType 273
5.183 simpleType: PTIncentiveFeeRuleType 273
5.184 simpleType: PTPriceType 274
5.185 simpleType: PTClassType 274
5.186 simpleType: PTMailShapePackagingType 274
5.187 simpleType: PTDicsountType 275
5.188 simpleType: PTPLBZNIndType 275
5.189 simpleType: PTPriceAmountType 275
5.190 simpleType: PTMinBreakType 275
5.191 simpleType: PTMaxBreakType 275
5.192 simpleType: PTPriceStructureType 275
5.193 simpleType: PTPerPriceType 276
5.194 simpleType: PTPerAdvType 276
5.195 simpleType: PTPerBarcodedType 276
5.196 simpleType: PTExtraServicePriceStructureType 276
5.197 simpleType: qualificationReportClassType 277
5.198 simpleType: rateCategoryType 277
5.199 simpleType: rateLevelType 279
5.200 simpleType: rateLevelIndicatorType 280
5.201 simpleType: rateType 280
5.202 simpleType: reasonCodeType 280
5.203 simpleType: recurringStatusType 281
5.204 simpleType: reservationNumberType 281
5.205 simpleType: retrieveDataBy 281
5.206 simpleType: roleType 281
5.207 simpleType: responsibleTransportationPartyType 282
5.208 simpleType: RoutingZipCodeType 282

Copyright © 2014 USPS®. All Rights Reserved

5.209 simpleType: s01 282
5.210 simpleType: s02 282
5.211 simpleType: s03 282
5.212 simpleType: s04 283
5.213 simpleType: s05 283
5.214 simpleType: s06 283
5.215 simpleType: s07 283
5.216 simpleType: s08 283
5.217 simpleType: s09 283
5.218 simpleType: s10 283
5.219 simpleType: s11 283
5.220 simpleType: s12 284
5.221 simpleType: s15 284
5.222 simpleType: s16 284
5.223 simpleType: s18 284
5.224 simpleType: s20 284
5.225 simpleType: s22 284
5.226 simpleType: s25 284
5.227 simpleType: s28 285
5.228 simpleType: s30 285
5.229 simpleType: s31 285
5.230 simpleType: s34 285
5.231 simpleType: s37 285
5.232 simpleType: s40 285
5.233 simpleType: s45 285
5.234 simpleType: s50 285
5.235 simpleType: s60 286
5.236 simpleType: s64 286
5.237 simpleType: s66 286
5.238 simpleType: s80 286
5.239 simpleType: s256 286
5.240 simpleType: s260 286
5.241 simpleType: s1000 286
5.242 simpleType: sackingBasisType 287
5.243 simpleType: ScanState 287
5.244 simpleType: scheduledInductionDateType 287
5.245 simpleType: scheduledInductionTimeType 287
5.246 simpleType: scheduledInHomeDateType 287
5.247 simpleType: serialNumberSevenOrEleven 287
5.248 simpleType: serialNumberTenOrFourteen 287

Copyright © 2014 USPS®. All Rights Reserved

5.249 simpleType: serviceLevelIndicatorType 287
5.250 simpleType: serviceCodeType 287
5.251 simpleType: ServiceTypeCodeType 288
5.252 simpleType: sortationLevelType 288
5.253 simpleType: serviceSubCodeType 289
5.254 simpleType: severityType 289
5.255 simpleType: simplifiedAddressType 289
5.256 simpleType: standardFlatType 289
5.257 simpleType: stateCode 289
5.258 simpleType: statusType 290
5.259 simpleType: stopDesignatorType 291
5.260 simpleType: surchargeType 291
5.261 simpleType: totalWeightType 291
5.262 simpleType: trailerLengthType 291
5.263 simpleType: transportationMethodType 291
5.264 simpleType: transportationModeType 291
5.265 simpleType: transShipBoLNumberType 291
5.266 simpleType: trayType 291
5.267 simpleType: trayTypeIndicatorType 292
5.268 simpleType: truckDispatchNumberType 292
5.269 simpleType: unitLoadType 292
5.270 simpleType: uOMType 292
5.271 simpleType: UpperDateRange 294
5.272 simpleType: uniqueContainerIDType 294
5.273 simpleType: userInformationLine1Type 294
5.274 simpleType: userInformationLine2Type 294
5.275 simpleType: userLicenseCodeType 294
5.276 simpleType: uspsPackageUniqueCharacteristicType 294
5.277 simpleType: uspsPickupType 294
5.278 simpleType: verificationLocationType 294
5.279 simpleType: verificationReportType 294
5.280 simpleType: wastedPieceIndicatorType 295
5.281 simpleType: weekFrequencyType 295
5.282 simpleType: weightBreakType 295
5.283 simpleType: yesNo 295
5.284 simpleType: zipCodeThreeOrFiveDigit 295
5.285 simpleType: zoneICType 296

6. eDocumentation Form Values 297

6.1 Container Status Type 297
6.2 Entry Facility Type Values 297

Copyright © 2014 USPS®. All Rights Reserved

6.3 Entry Facility Type 297
6.4 Form Type 297
6.5 Full-Service Indicator 297
6.6 Postage Statement Status Definitions 297
6.7 Rate Category 298
6.8 First Class Mail – Rate Category and Corresponding Rate Level 299
6.9 Periodicals In-County – Rate Category and Corresponding Rate Level 299
6.10 Periodicals Outside-County – Rate Category and Corresponding Rate Level 300
6.11 Standard Mail – Rate Category and Corresponding Rate Level 301
6.12 FSS Preparation - Add pricing for Outside County Periodicals prepared as FSS 303
6.13 Fault Codes 304
6.14 Support Mailer SubmitterTrackingID on MailXML 13.0B Messages 306
6.14.1 Business Requirements: 306
6.14.2 Business Rules/ Assumptions: 306
6.14.3 Duplicate Request Scenarios 307
6.14.4 MessageResponseRetrievalResponse Scenarios: 309

7. Postage Statement Mappings 312
7.1 Mailing Information – Non Periodicals 312
7.1.1 Mailing Group Summary Information 312
7.1.2 Mailer Information 312
7.1.3 Postage Summary Information 313
7.2 Mailing Information – Periodicals 315
7.2.1 Mailing Group Summary Information 315
7.2.2 Mailer Information 316
7.2.3 Mailing Information 316

8. Error Messages 319
8.1 Error Codes and Messages 319
8.2 Warning Codes and Messages 359

9. Change History Archive 364

INDEX ..... A

Copyright © 2014 USPS®. All Rights Reserved

DOCUMENT CHANGE HISTORY

Previous change history may be found in the Change History Archive, Section 9.

eDoc-13.0B-R17 Edition 4 Change 0

Date	Section	Title	Description
9/19/2014	N/A	N/A	No updates from last publication.

Copyright © 2014 USPS®. All Rights Reserved

1. Postal Service Mail.XML Technical Specification

1.1 Program Overview

The *PostalOne!*® system is an electronic suite of services being developed for business mailers by the United States Postal Service® to improve the mailing process. The system takes advantage of the advances in technology and leverages them to significantly improve and simplify the mailing experience.

Customers can electronically send detailed information to the *PostalOne!* system using the mailing industry's standardized Mail.XML™ format. Mail.XML is an XML-based IDEAlliance® specification for web services. Web services use simple HTTP(s) protocol to communicate data over the Internet, bypassing technology-specific restrictions and avoiding network-related security rules. See the IDEAlliance Mail.XML specifications at the IDEAlliance Web site

The *PostalOne!* system allows customers to submit electronic documentation through the use of Mail.XML messages. Many of these messages are used to interact with the mailing supply chain via web services for a number of important functions including FAST, Full Service™ data distribution, and electronic documentation. This document is dedicated to describing the use of Mail.XML for electronic documentation of qualification reports, piece detail and piece range data, container and bundle reports, and postage statements.

Mail.XML is an extremely fast and efficient way to present documentation. In many mailing scenarios – for example, “just in time” mail production of mailings of all sizes – there is no need to present an original file followed by a series of updates. In addition, the ability to query the *PostalOne!* system for status information about containers, handling units and postage statements allows mailers to automate processes and add considerable value to their postage reporting and documentation processes.

With Mail.XML, mailers can also update certain information about their mailings more quickly and more efficiently than Mail.dat, though there are certain rules and restrictions that will be discussed later in this document.

Mail.XML supports Full-Service, Mixed Service and Co-Palletized mailings. For Full and Mixed Service mailings, mailers will be required to submit qualification reports, piece information and postage statements for periodicals and non-periodicals mailings. Mailers will be required to submit qualification reports, piece information, postage statements and linkage information for Co-Palletized mailings.

All business functions supported by the USPS as part of the Mail.XML implementation are based upon SOA (Services Oriented Architecture). With this architecture, mailers’ software manages the data transactions for query, create, update, and cancel business functions as well as subscription models. Additionally, mailers’ software is able to receive synchronous and asynchronous transactions through Web Services protocol from the USPS in support of the just-in-time communication architecture.

The Postal Service implementation of Mail.XML is a complement to Mail.dat. Mailers using Mail.dat can continue to use it as a database, but can use Mail.XML for communication and automation of business to business processing. Mail.XML allows business function-specific communication and faster change management processes with little to no impact to other service providers. For example, you can add optional fields or new messages without requiring software in the mailing supply chain to change. This is a core improvement area for the Mail.dat® specification.

Mail.XML supports electronic documentation and end-to-end mailing supply chain, business process management for a multitude of business processes. Mail.XML includes qualification reports, container and bundle reports, spoilage, eInduction, containerization nesting, postage statements, postage adjustments, postage status query information, piece detail, piece ranging, and many other business process related communications. Mail.XML also provides the ability to electronically access USPS full-service data and to perform business functions related to full-service. Mail.XML allows create, update, and cancel transactions for the Cast of Characters (brokering of information) messages. Mail.XML supports copalletization, mixed mailing, manifest mailing, and business processes specific to MLOCR and continuous mailing environments.

One fundamental difference in the Mail.dat file and in Mail.XML messages is information content. For example, for qualification reports and postage statements, Mail.dat calculates from the raw data in several Mail.dat files the copies and pieces at each price level in the qualification report and the postage statements. This sometimes leads to round-off differences compared to qualification reports and postage statements calculated by the mailer using the same Mail.dat file. In Mail.XML, the mailer provides the numbers of copies and pieces for each price level directly and there is less round-off error.

There are two main types of Mail.XML messages that are used to share data between the mailer and the *PostalOne!* system. They are request messages and response messages.

Copyright © 2014 USPS®. All Rights Reserved

Request Messages

Mail.XML request messages are used to submit mailing information to the *PostalOne!* system. Mailers submit request messages to send container information, mailpiece and piece range information, and postage information.

Response Messages

Mailers will receive a response message from the *PostalOne!* system after they submit a request message. The response message is used to notify the customer of the status of their message.

- Accept Messages - Mailers will receive an Accept response if the request message that was submitted validated and uploaded successfully. After an Accept response is received, the mailer may continue submitting the remaining messages within that mailing group.
- Reject Messages - Mailers will receive a Reject response if the request message that was submitted did not validate and upload successfully. A ReturnCode and corresponding ReturnDescription, which describes the errors in the data, are provided in the response. The mailer must then update the data based on the error messages that were provided and resubmit.

The Postal Service Mail.XML Technical Specifications, 2014 is separated based on subject matter into the following volumes:

Postal Service Mail.XML Technical Specification for Postage Payment & Reporting (eDoc)

Postal Service Mail.XML Technical Specification for Appointment Scheduling (FAST)

Postal Service Mail.XML Technical Specification for Profiles & Full-Service Feedback(MID-CRID)

Postal Service Mail.XML Technical Specification for Postage Payment and Reporting (eDoc)

This document focuses solely on the eDoc message functionalities covering Mail.XML versions 13.0B

1.2 About Schema Modularization

Mail.XML messages are grouped into six sets:

- Transportation Messages
- Mailing Messages
- Data Distribution Messages
- Identification Messages
- Supply Chain Messages
- System Messages

The underlying schemas have been modularized to reflect these distinct message sets. Additionally, three “shared” or “common” schemas have been developed and they are:

1. One stores simple Mail.XML Mailing Message Specification type definitions that can be shared across message sets.
2. A second common module is made up of common elements and complex types that are shared across two or more message sets.
3. The final common module is made up of system messages and the attributes, elements and complex types that are unique to these messages.

Mail.XML schema modules are designed to stand alone, separated by business functions, enabling those interested in one or more message sets to develop and validate just those message sets without the requirement to address the entire Mail.XML specification. Each module will validate by itself or in combination with all other message sets when the entire Mail.XML Specification is considered. In addition each module will be versioned separately.

Version numbers are contained within the namespace designation. Modules will be documented individually as well.

The following Mail.XML XSD modules/namespaces have been developed:

mailxml_tm.xsd: This module contains all the transportation (or FAST) messages with their attributes, elements and complex types that are unique to these messages. **Namespace=mailxml_tm**

mailxml_mm .xsd: This module contains all the mailing messages (eDoc) with their attributes, elements and complex types that are unique to these messages. **Namespace=mailxml_mm**

Copyright © 2014 USPS®. All Rights Reserved

mailxml_dd.xsd: This module contains all the data distribution messages with their attributes, elements and complex types that are unique to these messages. **Namespace=mailxml_dd**

mailxml_id.xsd: This module contains all the identification messages(CRID, MID etc.) with their attributes, elements and complex types that are unique to these messages. **Namespace=mailxml_id**

mailxml_sc.xsd: This module contains all the supply chain messages (Cross functional container based and other Mail.dat/mail.XML update functions) with their attributes, elements and complex types that are unique to these messages. **Namespace=mailxml_sc**

mailxml.xsd: This module contains all the system messages with their attributes, elements and complex types that are unique to these messages. Note that in order for the MessageResponseRetrievalResponse to work, all the other message modules are included by the system.xsd. **Namespace=mailxml**

mailxml_defs.xsd: This module contains all the common definitions of attributes, elements and complex types that are used across one or more message types. **Namespace=mailxml_defs**

mailxml_base.xsd: This module contains all the simple types that are used everywhere in the mailxml. These simple types are associated with every element of each message. **Namespace=mailxml_base**

1.3 What Schemas Cover Electronic Documentation (eDoc) Functionality?

With the breakdown of the XSD into multiple schemas – eDoc functionality will be covered by two separate modules. These modules are mailxml_mm.xsd and mailxml_sc.xsd.

In addition to the above modules, mailxml_base.xsd and mailxml_defs are common/shared XSD that will be referred by each of these individual eDoc-specific modules.

The mailxml.xsd module will be the source XSD that connects all messages to their system-level attributes. For example – MessageResponseRetrievalReponse is a shared attribute/complex type associated to almost every single Mail.XML message, regardless of whether it is Data Distribution, FAST or eDoc functionality. Other examples of shared attributes/types are: DeliveryResponse, NotificationResponse, Fault, etc.

1.4 USPS Limitation Rule on Transaction Requests

USPS has recently encountered unusual high volume with specific Mail.XML transactions by FAST and Full Service Data Distribution users, resulting in serious performance impact on several USPS servers that deal with authorization of all Mail.XML transactions.

The Postal Service is requiring that USPS Mail.XML customers update their Mail.XML software to query the USPS *PostalOne!*/FAST systems no more than seven times per hour. Similarly, USPS customers are required to set up their web services pull software to query the *PostalOne!* servers no more than 200 times in a given 24 hour period for their eDoc, FAST, or Full Service data queries. This is a required change for all customers, and will greatly assist in avoiding performance issues that can hinder quality of service; users still have many opportunities to query necessary data within these limitations. Likewise, to improve overall experience for all customers it is absolutely necessary that customers program their software to query the USPS systems for different transactions at different times; in other words, configure some queries to occur at odd times, such as FAST queries, and configure other queries, such as eDoc and Data distribution, to occur at even times.

1.5 Recommended File Sizes for Optimum Mail.XML Performance

USPS® recommends following eDoc file sizes for the optimum performance

eDoc Message	File Size	Job Characteristics
QualificationReportDetailCreateRequest	25 MB	Roughly 18,000 Containers (ContainerInfoData blocks)
MailPieceCreateRequest – MailPieceBlock	25 MB	Roughly 40,000 – 45,000 Mail Pieces (MailPieceBlocks)
PostageStatementCreateRequest	25 MB	Roughly 35,000 Postage Statement Lines (PostageStatementLineItemData blocks)

1.6 Roadmap of Mail.XML

The table below shows the roadmap of the Mail.XML versions, starting from currently supported versions to versions that will be supported in future.

Copyright © 2014 USPS®. All Rights Reserved

October 2013 Release 36.0	January 2014 Release 37.0	August 2014 Release 38.0
Mail.XML 12.0A Mail.XML 13.0A Mail.XML 13.0B	Mail.XML 12.0A* Mail.XML 13.0A Mail.XML 13.0B Mail.XML 15.0A**	Mail.XML 13.0A* Mail.XML 13.0B* Mail.XML 15.0A Mail.XML 16.0**

Note: *The version(s) flagged with single asterisk (*) were planned for de-commissioning*

Note: *The version(s) flagged with double asterisk (**) are new versions planned for implementation with the release date.*

Date in 2014	Mail.XML Versions
August 24th – September 7th	• 13.0A (partial support for mailing dates that are processed before September 7th, 2014 and to update previously submitted mailings • 13.0B (partial support for mailing dates that are processed before September 7th, 2014 and to update previously submitted mailings
August 24th and onwards	• 15.0A (new submissions and updates) The pricing structure introduced in August 2014 Price Change is not supported in 15.0A • 16.0 (new submissions and updates) New statement products and new pricing structure. The PostageStatementMailing date must be on or after the price change date (September 7th)

1.7 Purpose

The purpose of this Technical Specification is to supplement the IDEAlliance Mail.XML and to provide Mail.XML users with specific information regarding the USPS implementation. USPS will support Mail.XML versions for electronic documentation as outlined in the Section 1.6 above. The content in this document is subject to change as IDEAlliance updates Mail.XML Specification. This technical specification includes the return codes, error codes and their descriptions, as well the WSDLs links for all the supported version of Mail.XML.

The USPS supports a test and production environment.

- **TEM (Testing Environment for Mailers)**: This environment is used for software approval processes for all mailers prior to moving into the production environment. Mailers must work with the *PostalOne!* Help Desk to start the approval process for their software, and must be approved in the TEM environment, prior to sending data transactions in the Production environment. For more information regarding TEM, see the *Test Environment for Mailers: Checklist and Troubleshooting Guide*
- **Production Environment**: This environment will be used by all customers that have been approved in the TEM environment by the USPS to start sending the transaction/messages.

1.8 Intended Audience

The intended audience for this specification is technical programmers and technical managers. Prior knowledge of XML language and Mail.dat functionalities will greatly improve the understanding of this document.

1.9 About This Document

The data structure tables for all the eDoc messages in Section 2 reference complex types. The details of these complex types are included in Section 4. The USPS recommends that customers study the complex types provided in Section 4to understand the structure of the eDoc messages.

In the data structure tables for all eDoc messages in Section 2, under the acceptable values column, actual simple type names are used for some of the elements. Review all simple types listed in Section 5 to fully understand the acceptable values that are validated by *PostalOne!* system. In addition, you will notice that in the Section 5, simple type uses codes

Copyright © 2014 USPS®. All Rights Reserved

have now been updated with Mail.dat descriptions for your convenience. The USPS® recommends that you also read the Postal Service Mail.dat Technical Specification.

In the data structure tables, some field names may contain spaces for readability purposes (because the names of those fields are lengthy). In Mail.XML, spaces are not allowed in the element names. For example: “SubmittingParty” is the element name but in the data table, it may have been written as Submitting Party.

If you are using this document to code your software then use the latest version of Mail.XML XSD located on the IDEAlliance website to understand the name of the element, structure of every block and message and to minimize the impact of incorrect coding.

1.10 How to Read Data Structure

There are three possibilities for every element listed in the data structure table of each message. These possibilities are REQUIRED, OPTIONAL, and CONDITIONALLY REQUIRED.

The Required option means that mailer/preparer or sender of the message must provide data for the element.

The Optional option means the sender of the message has a choice to include the data or omit it from submission.

The third option of Conditionally Required means that if certain condition is met then the sender of the message must provide data for that particular element; for example - EntryPointEDPostalCode is conditionally required if EntryPointEDFacilityType is populated in the ContainerUpdateRequest message.

In addition to the above options, there are instances where the main block is marked as REQUIRED, but the elements within the block are OPTIONAL or vice versa. This means that sender of the message must include the block when sending the message, but can omit all elements within the block. A good example is the ‘SubmittingParty’ block, which is a REQUIRED block, but all elements within this block are OPTIONAL.

1.11 Issue Resolution

All issues where the USPS software may not comply with the business rules, the work-arounds for such issues are listed in the critical issues list on the RIBBS Intelligent Mail site under Latest News. For example – In some cases the work around for Full-Service ACS data is to receive the data through OneCode ACS method instead of Full-Service methods. Additionally, for postage statements too large, the work around is to divide the statements in multiple statements.

1.12 Mail.XML Message Hierarchy

The sections below provide list of required vs. optional messages based on different scenarios. Also, the sections provide the list of prerequisite message that must be sent prior to sending the actual required message.

It is strongly recommended that customer wait to receive the response acknowledgement from USPS before sending the next message to avoid network clogging. It may impact the response time from USPS if multiple requests arrive at USPS servers in a non-sequential order.

1.12.1 Full-Service & Mixed Service Mailings for First-Class, Standard Mail, and Package Services

For full-service and mixed service mailings, the following messages are required for First-Class Mail, Standard Mail, and Package Services mailings: OpenMailingGroupRequest, QualificationReportSummaryCreateRequest QualificationReportDetailCreateRequest, MailPieceCreateRequest, and PostageStatementCreateRequest. The messages that need to be submitted prior to each required message for full-service and mixed service mailings are listed below:

Message	Required Prerequisite Messages
OpenMailingGroupRequest	None
QualificationReportSummaryCreateRequest	OpenMailingGroupRequest
QualificationReportDetailCreateRequest	OpenMailingGroupRequest QualificationReportSummaryCreateRequest
MailPieceCreateRequest**	OpenMailingGroupRequest QualificationReportSummaryCreateRequest QualificationReportDetailCreateRequest
PostageStatementCreateRequest	OpenMailingGroupRequest QualificationReportSummaryCreateRequest QualificationReportDetailCreateRequest MailPieceCreateRequest (before or after)

Table 1-1 Required Full-Service/Mixed Service Messages for First-Class Mail, Standard Mail, or Package Services

Copyright © 2014 USPS®. All Rights Reserved

**The MailPieceCreateRequest message can be submitted before and after the postage statement is submitted, prior to finalization.

All other messages are optional for full-service and mixed service mailings. The messages that need to be submitted prior to each optional message are listed below:

Message	Required Prerequisite Messages
BundleDetailCreateRequest	OpenMailingGroupRequest
BeginCombinedMailingRequest	OpenMailingGroupRequest QualificationReportSummaryCreateRequest QualificationReportDetailCreateRequest MailPieceCreateRequest
EndCombinedMailingRequest	OpenMailingGroupRequest QualificationReportSummaryCreateRequest QualificationReportDetailCreateRequest MailPieceCreateRequest BeginCombinedMailingRequest PostageStatementCreateRequest
PostageAdjustmentCreateRequest	OpenMailingGroupRequest QualificationReportSummaryCreateRequest QualificationReportDetailCreateRequest MailPieceCreateRequest, PostageStatementCreateRequest
OriginalContainerLinkageCreate	OpenMailingGroupRequest QualificationReportSummaryCreateRequest QualificationReportDetailCreateRequest
CloseMailingGroupRequest	OpenMailingGroupRequest
SiblingContainerCreateRequest	None
ContainerUpdateRequest	None
MailingGroupQueryRequest	OpenMailingGroupRequest
PostageStatementQueryRequest	OpenMailingGroupRequest QualificationReportSummaryCreateRequest QualificationReportDetailCreateRequest MailPieceCreateRequest PostageStatementCreateRequest
PostageStatementStatusQueryRequest	OpenMailingGroupRequest QualificationReportSummaryCreateRequest QualificationReportDetailCreateRequest MailPieceCreateRequest PostageStatementCreateRequest
ReconciliationReportQueryRequest	
BundleDetailCancelRequest	OpenMailingGroupRequest QualificationReportSummaryCreateRequest QualificationReportDetailCreateRequest BundleDetailCreateRequest
MailPieceCancelRequest	OpenMailingGroupRequest QualificationReportSummaryCreateRequest QualificationReportDetailCreateRequest MailPieceCreateRequest
PostageStatementCancelRequest	OpenMailingGroupRequest QualificationReportSummaryCreateRequest QualificationReportDetailCreateRequest MailPieceCreateRequest PostageStatementCreateRequest
OriginalContainerLinkageCancelRequest	OpenMailingGroupRequest QualificationReportSummaryCreateRequest QualificationReportDetailCreateRequest OriginalContainerLinkageCreate
SiblingContainerCancelRequest	SiblingContainerCreateRequest
CustomerMailReportCreateRequest	OpenMailingGroupRequest QualificationReportSummaryCreateRequest

Copyright © 2014 USPS®. All Rights Reserved

Message	Required Prerequisite Messages
	QualificationReportDetailCreateRequest PostageStatementCreateRequest
SummaryZipDestinationReportCreateRequest	OpenMailingGroupRequest QualificationReportSummaryCreateRequest QualificationReportDetailCreateRequest PostageStatementCreateRequest

Table 1-2 Optional Full-Service/Mixed Service Messages for First-Class Mail, Standard Mail, or Package Services

**The MailPieceCreateRequest message can be submitted before and after a postage statement is submitted, prior to finalization.

1.12.2 Full-Service & Mixed Service Mailings for Periodicals

For full-service and mixed service mailings, the following messages are required for Periodicals mailings: OpenMailingGroupRequest, QualificationReportSummaryCreateRequest, QualificationReportDetailCreateRequest, ContainerBundleReportCreateRequest, MailPieceCreateRequest, and PeriodicalStatementCreateRequest. The messages that need to be submitted prior to each required message for full-service and mixed service mailings are listed below:

Message	Required Prerequisite Messages
OpenMailingGroupRequest	None
QualificationReportSummaryCreateRequest	OpenMailingGroupRequest
QualificationReportDetailCreateRequest	OpenMailingGroupRequest QualificationReportSummaryCreateRequest
ContainerBundleReportCreateRequest	OpenMailingGroupRequest QualificationReportSummaryCreateRequest QualificationReportDetailCreateRequest
MailPieceCreateRequest	OpenMailingGroupRequest QualificationReportSummaryCreateRequest QualificationReportDetailCreateRequest ContainerBundleReportCreateRequest
PeriodicalStatementCreateRequest	OpenMailingGroupRequest QualificationReportSummaryCreateRequest QualificationReportDetailCreateRequest ContainerBundleReportCreateRequest MailPieceCreateRequest**

Table 1-3 Required Full-Service/Mixed Service Messages for Periodicals

All other messages are optional for full-service and mixed service mailings. The messages that need to be submitted prior to each optional message are listed below:

Message	Required Prerequisite Messages
BundleDetailCreateRequest	OpenMailingGroupRequest
BeginCombinedMailingRequest	OpenMailingGroupRequest QualificationReportSummaryCreateRequest QualificationReportDetailCreateRequest MailPieceCreateRequest**
EndCombinedMailingRequest	OpenMailingGroupRequest QualificationReportSummaryCreateRequest QualificationReportDetailCreateRequest **MailPieceCreateRequest BeginCombinedMailingRequest PeriodicalStatementCreateRequest

Copyright © 2014 USPS®. All Rights Reserved

Message	Required Prerequisite Messages
PostageAdjustmentCreateRequest	OpenMailingGroupRequest QualificationReportSummaryCreateRequest QualificationReportDetailCreateRequest **MailPieceCreateRequest PeriodicalStatementCreateRequest
OriginalContainerLinkageCreate	OpenMailingGroupRequest QualificationReportSummaryCreateRequest QualificationReportDetailCreateRequest
CloseMailingGroupRequest	OpenMailingGroupRequest
SiblingContainerCreateRequest	None
ContainerUpdateRequest	None
MailingGroupQueryRequest	OpenMailingGroupRequest
ContainerBundleReportQueryRequest	OpenMailingGroupRequest
PeriodicalStatementQueryRequest	OpenMailingGroupRequest QualificationReportSummaryCreateRequest QualificationReportDetailCreateRequest ContainerBundleReportCreateRequest **MailPieceCreateRequest PeriodicalStatementCreateRequest
PostageStatementStatusQueryRequest	OpenMailingGroupRequest QualificationReportSummaryCreateRequest QualificationReportDetailCreateRequest ContainerBundleReportCreateRequest **MailPieceCreateRequest, PeriodicalStatementCreateRequest
ReconciliationReportQueryRequest	None
ContainerBundleReportCancelRequest	OpenMailingGroupRequest
BundleDetailCancelRequest	OpenMailingGroupRequest QualificationReportSummaryCreateRequest QualificationReportDetailCreateRequest BundleDetailCreateRequest
MailPieceCancelRequest	OpenMailingGroupRequest QualificationReportSummaryCreateRequest QualificationReportDetailCreateRequest **MailPieceCreateRequest
PostageStatementCancelRequest	OpenMailingGroupRequest QualificationReportSummaryCreateRequest QualificationReportDetailCreateRequest ContainerBundleReportCreateRequest **MailPieceCreateRequest PeriodicalStatementCreateRequest
OriginalContainerLinkageCancelRequest	OpenMailingGroupRequest QualificationReportSummaryCreateRequest QualificationReportDetailCreateRequest OriginalContainerLinkageCreate
SiblingContainerCancelRequest	SiblingContainerCreateRequest

Table 1-4 Optional Full-Service/Mixed Service Messages for Periodicals

**The MailPieceCreateRequest message can be submitted before and after a postage statement is submitted, prior to finalization.

1.12.3 First-Class Mail, Standard Mail, and Package Services Mailings

For eDoc mailings, the following messages are required for First-Class Mail, Standard Mail, and Package Services mailings: OpenMailingGroupRequest, QualificationReportSummaryCreateRequest, QualificationReportDetailCreateRequest, and PostageStatementCreateRequest except when the mailing is less than 10,000 pieces. The messages that need to be submitted prior to each required message for eDoc mailings are listed below.

The following are the rules that determine Required versus Optional eDoc Messages:

Copyright © 2014 USPS®. All Rights Reserved

When a mailing is less than 10,000 pieces and mailing is not a Full-Service then set of eDoc messages marked as required below are not applicable.

When a mailing is above 10,000 pieces then set of eDoc messages below are required as outlined.

When a mailing is Full-Service then set of eDoc messages below are required. The Full-Service mailing over-writes the 10,000 pieces threshold.

Message	Required Prerequisite Messages
OpenMailingGroupRequest	None
QualificationReportSummaryCreateRequest	OpenMailingGroupRequest
QualificationReportDetailCreateRequest	OpenMailingGroupRequest QualificationReportSummaryCreateRequest QualificationReportDetailCreateRequest
PostageStatementCreateRequest	OpenMailingGroupRequest QualificationReportSummaryCreateRequest QualificationReportDetailCreateRequest

Table 1-5 Required eDoc Messages for First-Class Mail, Standard Mail, or Package Services

All other messages are optional for eDoc mailings. The messages that need to be submitted prior to each optional message are listed below:

Message	Required Prerequisite Messages
BundleDetailCreateRequest	OpenMailingGroupRequest
MailPieceCreateRequest**	OpenMailingGroupRequest QualificationReportSummaryCreateRequest QualificationReportDetailCreateRequest
BeginCombinedMailingRequest * This is a required message for combined or commingled mailings	OpenMailingGroupRequest QualificationReportSummaryCreateRequest QualificationReportDetailCreateRequest
EndCombinedMailingRequest * This is required message for combined or commingle mailings.	OpenMailingGroupRequest QualificationReportSummaryCreateRequest QualificationReportDetailCreateRequest BeginCombinedMailingRequest PostageStatementCreateRequest
PostageAdjustmentCreateRequest	OpenMailingGroupRequest QualificationReportSummaryCreateRequest QualificationReportDetailCreateRequest PostageStatementCreateRequest
OriginalContainerLinkageCreate* ** USPS strongly recommends sending this message when Copalletizing the mail, even when the mailing is a Non-Full-service mailing.*	OpenMailingGroupRequest QualificationReportSummaryCreateRequest QualificationReportDetailCreateRequest
CloseMailingGroupRequest	OpenMailingGroupRequest
SiblingContainerCreateRequest	None
ContainerUpdateRequest	None
MailingGroupQueryRequest	OpenMailingGroupRequest
PostageStatementQueryRequest	OpenMailingGroupRequest QualificationReportSummaryCreateRequest QualificationReportDetailCreateRequest PostageStatementCreateRequest
PostageStatementStatusQueryRequest	OpenMailingGroupRequest QualificationReportSummaryCreateRequest QualificationReportDetailCreateRequest PostageStatementCreateRequest
ReconciliationReportQueryRequest	
BundleDetailCancelRequest	OpenMailingGroupRequest QualificationReportSummaryCreateRequest QualificationReportDetailCreateRequest

Copyright © 2014 USPS®. All Rights Reserved

Message	Required Prerequisite Messages
	BundleDetailCreateRequest
MailPieceCancelRequest	OpenMailingGroupRequest QualificationReportSummaryCreateRequest QualificationReportDetailCreateRequest
PostageStatementCancelRequest	OpenMailingGroupRequest QualificationReportSummaryCreateRequest QualificationReportDetailCreateRequest PostageStatementCreateRequest
OriginalContainerLinkageCancelRequest	OpenMailingGroupRequest QualificationReportSummaryCreateRequest QualificationReportDetailCreateRequest OriginalContainerLinkageCreate
SiblingContainerCancelRequest	SiblingContainerCreateRequest
CustomerMailReportCreateRequest	OpenMailingGroupRequest QualificationReportSummaryCreateRequest QualificationReportDetailCreateRequest PostageStatementCreateRequest
SummaryZipDestinationReportCreateRequest	OpenMailingGroupRequest QualificationReportSummaryCreateRequest QualificationReportDetailCreateRequest PostageStatementCreateRequest

Table 1-6 Optional eDoc Messages for First-Class Mail, Standard Mail, or Package Services

For eDoc mailings, the following messages are required for Periodicals mailings: OpenMailingGroupRequest, QualificationReportDetailCreateRequest, and PostageStatementCreateRequest. The messages that need to be submitted prior to each required message for eDoc mailings are listed below:

Message	Required Prerequisite Messages
OpenMailingGroupRequest	None
QualificationReportSummaryCreateRequest	OpenMailingGroupRequest
QualificationReportDetailCreateRequest	OpenMailingGroupRequest QualificationReportSummaryCreateRequest
ContainerBundleReportCreateRequest	OpenMailingGroupRequest QualificationReportSummaryCreateRequest QualificationReportDetailCreateRequest
PeriodicalStatementCreateRequest	OpenMailingGroupRequest QualificationReportSummaryCreateRequest QualificationReportDetailCreateRequest

Table 1-7 Required eDoc Messages for Periodicals

All other messages are optional for full-service and mixed service mailings. The messages that need to be submitted prior to each optional message are listed below:

Message	Required Prerequisite Messages
BundleDetailCreateRequest	OpenMailingGroupRequest
MailPieceCreateRequest**	OpenMailingGroupRequest QualificationReportSummaryCreateRequest QualificationReportDetailCreateRequest
BeginCombinedMailingRequest	OpenMailingGroupRequest QualificationReportSummaryCreateRequest QualificationReportDetailCreateRequest
EndCombinedMailingRequest	OpenMailingGroupRequest QualificationReportSummaryCreateRequest QualificationReportDetailCreateRequest BeginCombinedMailingRequest

Copyright © 2014 USPS®. All Rights Reserved

Message	Required Prerequisite Messages
	PeriodicalStatementCreateRequest
PostageAdjustmentCreateRequest	OpenMailingGroupRequest QualificationReportSummaryCreateRequest QualificationReportDetailCreateRequest PeriodicalStatementCreateRequest
OriginalContainerLinkageCreate* * USPS strongly recommends sending this message when Copalletizing the mail, even when the mailing is a Non-Full-service mailing.	OpenMailingGroupRequest QualificationReportSummaryCreateRequest QualificationReportDetailCreateRequest
CloseMailingGroupRequest	OpenMailingGroupRequest
SiblingContainerCreateRequest	None
ContainerUpdateRequest	None
MailingGroupQueryRequest	OpenMailingGroupRequest
ContainerBundleReportQueryRequest	OpenMailingGroupRequest
PeriodicalStatementQueryRequest	OpenMailingGroupRequest QualificationReportSummaryCreateRequest QualificationReportDetailCreateRequest PeriodicalStatementCreateRequest
PostageStatementStatusQueryRequest	OpenMailingGroupRequest QualificationReportSummaryCreateRequest QualificationReportDetailCreateRequest PeriodicalStatementCreateRequest
ReconciliationReportQueryRequest	
ContainerBundleReportCancelRequest	OpenMailingGroupRequest
BundleDetailCancelRequest	OpenMailingGroupRequest QualificationReportSummaryCreateRequest QualificationReportDetailCreateRequest BundleDetailCreateRequest
MailPieceCancelRequest	OpenMailingGroupRequest QualificationReportSummaryCreateRequest QualificationReportDetailCreateRequest MailPieceCreateRequest
PostageStatementCancelRequest	OpenMailingGroupRequest QualificationReportSummaryCreateRequest QualificationReportDetailCreateRequest, PeriodicalStatementCreateRequest
OriginalContainerLinkageCancelRequest	OpenMailingGroupRequest QualificationReportSummaryCreateRequest QualificationReportDetailCreateRequest OriginalContainerLinkageCreate
SiblingContainerCancelRequest	SiblingContainerCreateRequest

Table 1-8 Optional eDoc Messages for Periodicals

**The MailPieceCreateRequest message can be submitted before and after a postage statement is submitted, prior to finalization.

1.13 Workflows

1.13.1 Non-Periodicals without Full-Service

1. Send OpenMailingGroupRequest
2. Receive accepted OpenMailingGroupResponse with assigned MailingGroupID.
3. Use CustomerGroupID and MailingGroup in Attributes for additional messages.
4. Send QualificationReportSummaryCreateRequest
5. Receive accepted QualificationReportSummaryCreateResponse
6. Send QualificationReportDetailCreateRequest

Copyright © 2014 USPS®. All Rights Reserved

7. Receive accepted QualificationReportCreateResponse
8. Send PostageStatementCreateRequest
9. Receive accepted PostageStatementCreateResponse

1.13.2 Periodicals without Full-Service

1. Send OpenMailingGroupRequest
2. Receive accepted OpenMailingGroupResponse with assigned MailingGroupID.
3. Use CustomerGroupID and MailingGroup in Attributes for additional messages.
4. Send QualificationReportSummaryCreateRequest
5. Receive accepted QualificationReportSummaryCreateResponse
6. Send QualificationReportDetailCreateRequest
7. Receive accepted QualificationReportCreateResponse
8. Send ContainerBundleReportCreateRequest
9. Receive accepted ContainerBundleReportCreateResponse
10. Send PeriodicalStatementCreateRequest
11. Receive accepted PeriodicalStatementCreateResponse

1.13.3 Non-Periodicals with Full-Service

1. Send OpenMailingGroupRequest
2. Receive accepted OpenMailingGroupResponse with assigned MailingGroupID.
3. Use CustomerGroupID and MailingGroup in Attributes for additional messages.
4. Send QualificationReportSummaryCreateRequest
5. Receive accepted QualificationReportSummaryCreateResponse
6. Send QualificationReportDetailCreateRequest
7. Receive accepted QualificationReportCreateResponse
8. Send MailPieceCreateRequest
9. Receive accepted MailPieceCreateResponse.
10. Send PostageStatementCreateRequest
11. Receive accepted PostageStatementCreateResponse

The following will also be accepted:

1. Send OpenMailingGroupRequest
2. Receive accepted OpenMailingGroupResponse with assigned MailingGroupID
3. Use CustomerGroupID and Attributes for additional messages
4. Send QualificationReportSummaryCreateRequest
5. Receive accepted QualificationReportSummaryCreateResponse
6. Send QualificationReportDetailCreateRequest
7. Receive accepted QualificationReportCreateResponse
8. Send PostageStatementCreateRequest
9. Receive accepted PostageStatementCreateResponse
10. Send MailPieceCreateRequest (prior to finalization)
11. Receive accepted MailPieceCreateResponse

1.13.4 Periodicals with Full-Service

1. Send OpenMailingGroupRequest

Copyright © 2014 USPS®. All Rights Reserved

2. Receive accepted OpenMailingGroupResponse with assigned MailingGroupID.
3. Use CustomerGroupID and MailingGroup in Attributes for additional messages.
4. Send QualificationReportSummaryCreateRequest
5. Receive accepted QualificationReportSummaryCreateResponse
6. Send QualificationReportDetailCreateRequest
7. Receive accepted QualificationReportCreateResponse
8. Send ContainerBundleReportCreateRequest
9. Receive accepted ContainerBundleReportCreateResponse
10. Send MailPieceCreateRequest
11. Receive accepted MailPieceCreateResponse.
12. Send PeriodicalStatementCreateRequest
13. Receive accepted PeriodicalStatementCreateResponse

The following will also be accepted:

1. Send OpenMailingGroupRequest
2. Receive accepted OpenMailingGroupResponse with assigned MailingGroupID.
3. Use CustomerGroupID and MailingGroup in Attributes for additional messages.
4. Send QualificationReportSummaryCreateRequest
5. Receive accepted QualificationReportSummaryCreateResponse
6. Send QualificationReportDetailCreateRequest
7. Receive accepted QualificationReportCreateResponse
8. Send ContainerBundleReportCreateRequest
9. Receive accepted ContainerBundleReportCreateResponse
10. Send PeriodicalStatementCreateRequest
11. Receive accepted PeriodicalStatementCreateResponse
12. Send MailPieceCreateRequest (prior to finalization)
13. Receive accepted MailPieceCreateResponse.

For full-service in remaining scenarios insert send MailPieceCreateRequest and receive accepted MailPieceCreateResponse after receive accepted QualificationReportCreateResponse and either before or after the Postage/Periodical Statement Request and Response.

1.13.5 Combined/ Commingled Mailing - non-Periodicals

1. Send OpenMailingGroupRequest
2. Receive accepted OpenMailingGroupResponse with assigned MailingGroupID.
3. Use CustomerGroupID and MailingGroup in Attributes for additional messages.
4. Send QualificationReportSummaryCreateRequest
5. Receive accepted QualificationReportSummaryCreateResponse
6. Send QualificationReportDetailCreateRequest
7. Receive accepted QualificationReportCreateResponse
8. Send BeginCombinedMailingRequest
9. Receive accepted BeginCombinedMailingResponse
10. Use the CombinedMailingID in all the postage statements.
11. Send each PostageStatementCreateRequest

Copyright © 2014 USPS®. All Rights Reserved

12. Receive each PostageStatementCreateResponse
13. After last PostageStatementCreateResponse, send EndCombinedMailingRequest
14. Receive EndCombinedMailingResponse.

The only noted difference between Commingled and Combined mailings is that for a Commingled Mailing, the USPS requires a minimum of 150 pieces per Zip Code to achieve five-digit postal rates, whereas a Combined Mailing has no such requirement.

1.13.6 Combined/ Commingled Mailing - Periodicals

1. Send OpenMailingGroupRequest
2. Receive accepted OpenMailingGroupResponse with assigned MailingGroupID.
3. Use CustomerGroupID and MailingGroup in Attributes for additional messages.
4. Send QualificationReportSummaryCreateRequest
5. Receive accepted QualificationReportSummaryCreateResponse
6. Send QualificationReportDetailCreateRequest
7. Receive accepted QualificationReportCreateResponse
8. Send ContainerBundleReportCreateRequest
9. Receive accepted ContainerBundleReportCreateResponse
10. Send BeginCombinedMailingRequest
11. Receive accepted BeginCombinedMailingResponse
12. Use the CombinedMailingID in all the postage statements.
13. Send each ConsolidatedPeriodicalStatementCreateRequest
14. Receive each PeriodicalStatementCreateResponse
15. After last PeriodicalStatementCreateResponse, send EndCombinedMailingRequest
16. Receive EndCombinedMailingResponse.

The only noted difference between Commingled and Combined mailings is that for a Commingled Mailing, the USPS requires a minimum of 150 pieces per Zip Code to achieve five-digit postal rates, whereas a Combined Mailing has no such requirement.

1.13.7 Copalletized Mailing for Trays on Pallets - non-Periodicals

At consolidator (original site sending regular mailing via Mail.XML or Mail.dat)

1. Send OpenMailingGroupRequest
2. Receive accepted OpenMailingGroupResponse with assigned MailingGroupID.
3. Use CustomerGroupID and MailingGroup in Attributes for additional messages.
4. Send QualificationReportSummaryCreateRequest
5. Receive accepted QualificationReportSummaryCreateResponse
6. Send QualificationReportDetailCreateRequest
7. Receive accepted QualificationReportCreateResponse
8. Send OriginalContainerLinkageCreateRequest. (Required when mail contains Full-Service pieces and strongly recommended by the USPS when non-Full-service mail is copalletized)
9. Receive accepted OriginalContainerLinkageCreateResponse

1.13.8 Copalletized Mailing for Bundles on Pallets - Standard Mail

At consolidator (original site sending regular mailing via Mail.XML or Mail.dat)

1. Send OpenMailingGroupRequest
2. Receive accepted OpenMailingGroupResponse with assigned MailingGroupID.
3. Use CustomerGroupID and MailingGroup in Attributes for additional messages.

Copyright © 2014 USPS®. All Rights Reserved

4. Send QualificationReportSummaryCreateRequest
5. Receive accepted QualificationReportSummaryCreateResponse
6. Send QualificationReportDetailCreateRequest
7. Receive accepted QualificationReportCreateResponse
8. Send OriginalContainerLinkageCreateRequest. (Required when mail contains Full-Service pieces and strongly recommended by the USPS when non-Full-service mail is copalletized)
9. Receive accepted OriginalContainerLinkageCreateResponse
10. Send BeginCombinedMailingRequest
11. Receive accepted BeginCombinedMailingResponse
12. Use the CombinedMailingID in all the postage statements.
13. Send each PostageStatementCreateRequest
14. Receive each PostageStatementCreateResponse
15. After last PostageStatementCreateResponse, send EndCombinedMailingRequest
16. Receive EndCombinedMailingResponse.

1.13.9 Copalletized Mailing for Bundles on Pallets - Periodicals Mail

At consolidator (original site sends regular mailing via Mail.XML or Mail.dat)

1. Send OpenMailingGroupRequest
2. Receive accepted OpenMailingGroupResponse with assigned MailingGroupID.
3. Use CustomerGroupID and MailingGroup in Attributes for additional messages.
4. Send QualificationReportSummaryCreateRequest
5. Receive accepted QualificationReportSummaryCreateResponse
6. Send QualificationReportDetailCreateRequest
7. Receive accepted QualificationReportCreateResponse
8. Send ContainerBundleReportCreateRequest
9. Receive accepted ContainerBundleReportCreateResponse
10. Send OriginalContainerLinkageCreateRequest. (Required when mail contains Full-Service pieces and strongly recommended by the USPS when non-Full-service mail is copalletized)
11. Receive accepted OriginalContainerLinkageCreateResponse
12. Send BeginCombinedMailingRequest
13. Receive accepted BeginCombinedMailingResponse
14. Use the CombinedMailingID in all the postage statements.
15. Send each PeriodicalStatementCreateRequest
16. Receive each PeriodicalStatementCreateResponse
17. After last PostageStatementCreateResponse, send EndCombinedMailingRequest
18. Receive EndCombinedMailingResponse.

1.14 Acceptance of less than 10,000 mailpieces

- Accept without barcode uniqueness error a full-service Mail.XML mailing with less than 10,000 pieces when all MailPiece records have the same Mailer ID and Serial Number in the Intelligent Mail Barcode.
- Does not require that physical siblings be provided for logical trays or containers for a Mail.XML full-service mailing of less than 10,000 pieces.
- Does not require that a tray or container barcode be provided for a physical tray or pallet for a Maill.XML full-service mailing of less than 10,000 pieces.

Copyright © 2014 USPS®. All Rights Reserved

1.15 Exceptions

The following cases are not supported in the Mail.XML:

- Full-service logical mailers who do not have the physical tray information for a specific logical tray. Job ID, Container ID, and Sibling Container ID would be populated as normal. Container Type would be T and IM Container or Tray Barcode would be filled with 24 digits of digit '9'. The number of duplicate Tray Barcodes cannot exceed 1% for any Full-Service or Mixed Service mailing. This duplication will cause validation failures for Qualification Report.
- Mailings with multiple mail classes such as Periodicals and Standard mixed together. This includes the experiment for copalletization of Periodicals and Standard Mail is not supported.
- For Original Container Linkage – mother containers are not supported
- International mail is not supported.
- Sacking is not required for bundles prepared for and entered at a DDU when the mailer unloads bundles. Mail presented under this exception is not subject to the container charge (but is still subject to the bundle charges).
- Periodicals parcels that are not bundled. If Periodicals parcels are not bundled, even irregular parcels, validation rejects the Qualification report. To submit Periodicals parcels that are not bundled submit the mailing with the alternative standardized documentation and postage statements.
- For MLOCR mailings, postage statements cannot claim the "Single Piece" rate category until a later release.
- Non-incidental enclosures are eligible for the full-service discount when enclosed in host mail pieces that receive full-service discount and are letters or machinable flats. For Postage Statements submitted via Mail.XML, the full-service discount on the non-incidental enclosure when applicable is not supported at this time. Mailer must request a refund of the amount of this postage by the usual manual refund process.

1.16 Incentive Programs Enrollment

All participants can enroll in incentive programs through the Business Customer Gateway (BCG). Enrollment should be completed at least two hours prior to presenting the first qualifying mailing. During enrollment, mailing agents may select the Mail Service Provider (MSP) designation. Selecting the MSP designation enables mailing agents to use the eDoc enrollment feature (refer to next paragraph). If a participant is also a mail owner, the MSP designation should be selected. A mail owner is defined as the business entity, organization, or individual who makes business decisions regarding the mailpiece content, directly benefits from the mailing, and ultimately pays for postage on the mailpiece directly or by way of a mailing agent)

eDoc enrollment using Mail.XML requires the MSP to accept the MSP legal declaration and promotion terms through the BCG at least two hours prior to presenting the first qualifying mailing. An MSP can subsequently enroll their clients in real-time when submitting eDocs which are claiming an incentive discount. During postage statement finalization, *PostalOne!* will validate that the MSP Customer Registration ID (CRID) in the eDoc is enrolled as an MSP, proceed to enroll the client(s) in the incentive program based on the "For" field data in the eDoc. *PostalOne!* will only then calculate the discount if there are no system Warnings. *PostalOne!* will perform By/For validations and generates a Warning for MSP CRIDs that are not registered (Preparer field) and for invalid CRIDS or Mailer ID (MID). *PostalOne!* will process the eDoc in the case for Warnings (i.e., not fail files and not extend the promotion claimed in the eDoc). Note: Mail Owner (clients) need not be pre-registered if the MSP is pre-registered and the MSP purposely intends to use the eDoc enrollment functionality.

1.17 Incentives

- The MailCharacteristic Incentive and MailCharacteristic Fee blocks are supported for all Mail.XML versions of eDoc.
- Enrollment is based on the Customer Registration ID (CRID). CRIDs which have permits linked to them must be enrolled.
- The incentive discount will accrue to the permit populated in the Permit Holder information in the Mailing Group Summary Information block. The permit must be linked to an enrolled CRID. Otherwise, the (registered) mailing agent may use the eDoc enrollment feature, where *PostalOne!* system will apply the discount to the permit associated in Permit Holder information.
- The *PostalOne!* system will apply only one promotional discount to a given mailpiece at the postage statement line level.

Copyright © 2014 USPS®. All Rights Reserved

- For the Picture Permit Imprint promotion, use the MailCharacteristic Fee value of “PP” and MailCharacteristic Incentive value of “PP” for Picture Permit Indicia. During the promotion period, if the permit identified in the Permit Holder information is enrolled in the Picture Permit Imprint promotion, the *PostalOne!* system will be triggered to waive the Picture Permit Imprint fee if all other rules of the incentive program eligibility are met.

  Note: *Since Picture Permit Imprint is originally a Fee, when requesting for Picture Permit Imprint to be included as an incentive, the eDoc must capture it as both Fee and Incentive.*

- For the Product Sample Sale, pieces claiming the incentive must be submitted on a separate Postage Statement for Part H.
- For mobile barcode promotions, all pieces claiming the incentive must bear the mobile barcode and be submitted on a separate Postage Statement. Use the MailCharacteristic Incentive value of “ME” for Mobile Energy Technology for the Fall 2013 mobile barcode incentive and use “MI” for Mobile Interactive for the Winter 2013 mobile barcode incentive.
- For the Earned Value program, the permit in the Permit Holder must be registered for the Earned Value program. The Earned Value program is not supported by the eDoc enrollment feature. Participants must register on the Business Customer Gateway. When redeeming Earned Value credits, use the MailCharacteristic Incentive value of “RR” for Reply Envelope or Reply Card.
- The *PostalOne!* system shall be enabled such that the Emerging Technology (mobile barcode), Picture Permit Imprint and Earned Value will be applied to the same Form 3600, 3602 Regular or 3602 Non-profit if the MailCharacteristic Incentive value (or when required the MailCharacteristic Fee and Incentive value) is in the eDoc. Participants must meet business rules and enrollment criteria. Functionality for multiple incentives will be supported upon the July Release 35.
- For 13.0A/B submissions the value of MT is supported for indicating Branded Mobile Technology in the eDoc beginning January 26, 2014.
- For 13.0A/B submissions the value of IV is supported for indicating Premium Advertising in the eDoc beginning April 6, 2014.

The following use of the incentive and promotion content is supported as of January 2014. For more information on current Promotions see the Promotions and Incentive page online at USPS.com.

2014 Promotional Programs						
	Registration	**Promotion Period**	**Mail Class / Processing Category**	**Discount Calculation**	**Incentive Code Active Period and 2-digit Characteristic Type**	
Branded Color Mobile Technology	Dec 15 , 2013 – March 31, 2014	Feb 1-March 31, 2014	FCM Cards, Letters & Flats STD (R/N) / Letters & Flats (presort, automation, single piece)	% off at Postage Statement line level (Total Discount column)	Feb 1-March 31, 2014	CP MT [6]
Earned Value Reply Mail [1]	February 15 – March 31, 2014	April 1-June 30, 2014	FCM/Cards, Letters & Flats STD (R/N) / Letters & Flats (presort/machinable and automation in FS mailings)	Credit (Subtract Earned Value Credit value from Total Postage All Parts)	Redemption start: August 1	RR
Premium Advertising [2]	February 15 – June 30, 2014	April 1-June 30, 2014	FCM / Letters (presort, residual single piece and automation in FS mailings)	% off at Postage Statement line level (Total Discount column)	April 1-June 30, 2014	AD IV [7]

Copyright © 2014 USPS®. All Rights Reserved

Mail and Digital Personalization [3]	March 15 – June 30, 2014	May 1- June 30, 2014	FCM /Cards, Letters & Flats STD (R/N) / Letters & Flats (presort, residual single piece /machinable & automation in FS mailings)	% off at Postage Statement line level (Total Discount column)	May 1- June 30, 2014	MI
Emerging Technology (Near Field Communications)[3]	June 15 - September 30, 2014	August 1- September 30, 2014	STD (R/N) / Letters & Flats (machinable and automation in FS mailings)	% off at Postage Statement line level (Total Discount column)	August 1- September 30, 2014	ME
Color in First-Class Mail Transactions Promotion [5]	June 15 – December 31, 2014	August 1 – December 31, 2014	FCM Letters (presort and automation in FS mailings)	% off at Postage Statement line level (Total Discount column)	August 1 – December 31, 2014.	CP
Mail Drives Mobile Commerce [3, 4]	September 15 - December 31, 2014	November 1 - December 31, 2014	STD (R/N) / Letters & Flats (machinable and automation in FS mailings)	% off at Postage Statement line level (Total Discount column)	November 1 - December 31, 2014	MI

[1] Credits earned for qualifying First-Class Mail Business Reply Mail and Courtesy Reply Mail enclosures. Earned Value credits can be redeemed for mailings that are First-Class and Standard Mail. Requires mailing to be Full-Service compliant. No auto enrollment through electronic files.
[2] Open to customers who mailed $6 million or more in Standard Mail letter revenue from October 1, 2012 through September 20, 2013. Mail service providers are not eligible to participate. No auto enrollment through electronic files. Requires mailing to be Full-Service compliant.
[3] Mobile technology integration promotion same functionality as previous mobile barcode promotions.
[4] Mailers who meet Priority Mail Fulfillment threshold (0.5%) will receive an additional 1% rebate on the mailpiece postage paid during the Promotion Fulfillment Period (November 3– January 15, 2015).
[5] FCM letters auto/presort sent in Full-Service mailings. Residual pieces paying single-piece price that are part of an automation mailing may also qualify for the discount.
[6] For Mail.dat 13-1 and Mail.XML 13.0A/13.0B, the value “MT” is supported for indicating Branded Color Mobile Technology in the eDoc, beginning January 26, 2014
[7] For Mail.dat 13-1 and Mail.XML 13.0A/13.0B, the value “IV” is supported for indicating Premium Advertising in the eDoc, beginning April 6, 2014

2. *PostalOne!* – eDoc Mail.XML Messages

2.1 Overview

This section provides the technical information related to the *PostalOne!* - Mail.XML Web Services messages which support all electronic documentation (eDoc) and miscellaneous functionality related to mailer interaction with the *PostalOne!* system in managing, updating and querying mail contents. Web Services messages also supplement the Mail.dat functionality, such as payment message queries and container status checking for eInduction.

eDoc messages use the same technology concept of Web Services near real time messaging architecture. Customers are required to have Web Services capable software that can manage the data itself and be able to send and receive the Web Services Mail.XML based transactions from the USPS. Customers and vendors who have developed the WWS (Wizard Web Services) software are required to modify both their software to work with Mail.XML XSD and enhance WWS message names and implementation. The near real time architecture will allow sending final documentation transactions to the USPS and getting response in near real time in most cases. For large transactions, the asynchronous web services architecture provided through tracking ids in Mail.XML is available, which allows the customer’s software to query the USPS *PostalOne!* system again to find out if the piece data or qualification reports were processed with either accepted or rejected response.

Copyright © 2014 USPS®. All Rights Reserved

2.2 Message Response Retrieval Request Processing

2.2.1 Fault and Fault Recovery Messages

This series of messages is primarily used to support the Asynchronous communication when the response from the USPS may not be within a 7 seconds period and the USPS gives out a Tracking ID to the customer. The customer then uses the Tracking ID to get his message response back using the Message Response Retrieval Request/Response message. Please note all of the response messages now have a TrackingID though all messages are not specifically outlined above.

- Message Response Retrieval Request
- Message Response Retrieval Response

Customers have the ability to provide Tracking ID in the MessageResponseRetrievalRequest message to retrieve data for the entire Response message.

2.3 Additional Rules/Constraints

2.3.1 Container Status Messages

The *PostalOne!* system will support status checking through Container Status Query Request and Response messages by the originator of the data and by the entity identified as the Scheduler or Carrier in the eDocumentation. Status checking allows mailers to view the status of any given container(s) and ensure that the container is validated during the pre-induction and post-induction process

- The *PostalOne!* system upon receiving the container status message shall go to the container management system of eInduction to find out all validation status of the requested container(s) and respond to the customer with the status information.
- If there are any issues or validation errors for one or more containers, then the *PostalOne!* system shall respond back to the customer with validation failures for one or more container(s)
- Payment finalization status will also be supported with provided copal container barcodes in Container Status Query Request

2.3.2 ContainerStatusQueryResponse Error Codes / Return Values

Error Code	Error Message
4050	No records were found for the given search criteria.
4052	Invalid Barcode Error.
4053	Duplicate Barcode Error.
4054	Missing Barcode Error.
4055	Scheduling Error.
4056	Entry Point Discount Error.
4057	Appointment Verification Error.
4058	Payment Not Finalized Error.
4061	Labeling List Validation Error.
4062	Transported Mail Appointment Validation Error.
4063	Container Manifest Validation Error.
4064	New Zone Validation Error

2.4 *PostalOne!* WSDL Information

All web services transactions that are made with the USPS should comply with the WSDL specification that are posted on RIBBS and can be downloaded from the following location: Web Service Description Language (WSDLs)

A web services request must include a valid and active USPS User ID and Password as defined in the UserAuthenticationInfo.xsd file that is provided as part of the WSDL downloable files. A typical web service construct defined message is as follows:

```
<wsdl:message name="DeliveryApptContentUpdateRequest">

    <wsdl:part name="authInfo" element="auth:AuthenticationInfo"/>
    <wsdl:part name="apptContentUpdate" element="tns:apptContentUpdate"/>

</wsdl:message>
```


Copyright © 2014 USPS®. All Rights Reserved

With the following:

XSD-typed WSDL:

```
<wsdl:message name="FullServiceStartTheClockQueryRequest">
    <wsdl:part element="uspsmxml:FullServiceStartTheClockQueryRequest"
    name="FullServiceStartTheClockQueryRequest"/>
</wsdl:message>
```

USPS will validate and authenticate the user information before processing the request. An error message will be returned in response to the web service request for invalid user information.

2.4.1.1 Types of WSDLS

There are two types of WSDLs, the Message-Type WSDL and the String-Type WSDL. The USPS only supports the Message-Type WSDL. The following is basic information on the Message-Type WSDL types to help customers understand the Message Type WSDLs.

Consuming Message-Type wsDLs:

The message-type eliminates the need to manually register each service and message type. With this method, a customer can use an automated tool that can set up their environment without manually registering each service. However, this approach requires updates to WSDLs every time a new Mail.XML version is released. In other words, it is tightly coupled with the Mail.XML Specification Version. The USPS has transitioned to this type of Message WSDLs to remove manual editing and registering of messages.

Customers must use message-type URLs to consume these services. These URLs are provided in the WSDLs and XSDs section of the document.

2.5 WSDLs and XSDs

The WSDL specifications are posted on RIBBS® and can be downloaded from the following location: Web Service Description Language (WSDLs)

The above RIBBS® URL provides WSDLs for both TEM and production environments. User should always use this link to access the correct and updated version of WSDLs in future.

2.5.1 Pull WSDL Information

To consume the WSDL services, the customer should go to the above URL to find the correct link.

2.5.2 PUSH WSDLs Information

Customers interested in using the Push Subscription model to receive the data feedback automatically at a specified time to their servers must understand the following WSDL name change information for the message-type WSDLs:

> ***Note:*** *USPS no longer supports String-type WSDLs. Currently, the USPS only accepts Message-Types WSDLs.*

2.6 Permit Information

Permit Holder – This is the permit charged for the postage statement. The *PostalOne!* system uses the PermitHolderData block to reference the PermitNumber or PublicationNumber for a Periodicals postage statement. The ‘PermitType’ and ‘PermitZip4’ fields are also available in the PermitHolderData block and is associated to the ‘Permit Number’. This information is displayed in the ‘Permit Holder’ section of a postage statement.

- PermitHolderData
- MID – Optional block
- CRID – Optional field
- ContactName – Required field
- PermitPublicationData
  - PermitNumber – Required field
  - PermitType – Required field
  - PermitZip4 – Required field

Copyright © 2014 USPS®. All Rights Reserved

  - PublicationNumber – Required for Periodicals

Mailing Agent - This identifies the organization that prepared the mailing and/or delivered it to the postal service for mailing. This information is linked to the user's login account. The *PostalOne!* system looks up the Company Name, Address Line 1, Address Line2, City, State, Zip Code, Zip Code4, Contact Phone, and Contact Email using the PermitNumber and PermitZip4 fields within the MailingAgentData block. This information is displayed in the Mailing Agent section of a postage statement.

MailingAgentData

- MID – Optional block
- CRID – Optional field
- ContactName – Required field
- PermitPublicationData
  - PermitNumber – Required field
  - PermitType – Required field
  - PermitZip4 – Required field
  - PublicaitonNumber – Required for Periodicals

Mail Owner - This identifies the organization who owns the mail being sent. The *PostalOne!* system looks up the Company_Name, Address_Line1, Address_Line2, City, State, Zip_Code, Zip_Code4, Contact_Phone, and Contact_Email in the P_Finance, P_Permit, and P_Company tables using the PermitNumber and PermitZip4 fields within the PermitPublicationData block within the MailingOwnerData block within the CreatePostageStatement block in the PostageStatementCreateRequest message. The State is determined from the Zip_Code. The *PostalOne!* system will populate the Mail Owner (Organization for Mailing is Prepared is Prepared) information with Permit Holder information. This information is displayed in the Org. For Mailing is Prepared section of a postage statement.

- MailingOwnerData
- MID – Optional block
- CRID – Optional field
- ContactName – Required field
- PermitPublicationData
  - PermitNumber – Required field
  - PermitType – Required field
  - PermitZip4 – Required field
  - PublicationNumber – Required for Periodicals

Publisher Data - The *PostalOne!* system looks up the Company_Name, Address_Line1, Address_Line2, City, State, Zip_Code, Zip_Code4, Contact_Phone, and Contact_Email in the P_Finance, P_Permit, and P_Company tables using the PublicationNumber or PermitNumber field within the PermitPublicationData block within PublisherData block within the CreatePeriodicalStatement block. This information is displayed in the Publication Title and Owner or News Agent's Name section of a periodicals postage statement.

PublisherData

- MID – Optional block
- CRID – Optional field
- ContactName – Required field
- PermitPublicationData
  - PermitNumber – Required for Pending Periodicals
  - PermitType – Required for Pending Periodicals
  - PermitZip4 – Required for Pending Periodicals
  - PublicationNumber – Required for Periodicals

Copyright © 2014 USPS®. All Rights Reserved

SubmittingParty Block (All Messages):

- MailerID6 – Optional field
- MailerID9 – Optional field
- CRID – Optional field
- SchedulerID – field is ignored
- MaildatUserLicenseCode – field is ignored

The information in the SubmittingParty block is not displayed on postage statements or reports on the *PostalOne!* Dashboard.

SubmittingSoftware Block (All Messages):

- SoftwareName – Required field
- Vendor – Required field
- Version – Required field
- ApprovalDate – Optional field
- ApprovalKey – Optional field

The information in the SubmittingSoftware block is not displayed on postage statements or reports on the *PostalOne!* Dashboard.

OpenMailingGroupRequest

PermitPublicationData – fields should be populated with Mailing Agent permit information:

- PermitNumber – Required field
- PermitType – Required field
- PermitZip4 – Required field
- PublicationNumber – Required for Periodicals

QualificationReportSummaryCreateRequest/QualificationReportDetailCreateRequest

MailOwner Block – fields should be populated with Mail Owner permit information:

- PermitNumber – Required field
- PermitType – Required field
- PermitZip4 – Required field
- PublicationNumber – Required for Periodicals

QualificationReportPreparer Block – fields should be populated with Mailing Agent permit information:

- PermitNumber – Required field
- PermitType – Required field
- PermitZip4 – Required field
- PublicationNumber – Required for Periodicals
- MailerID6 – Optional field
- MailderID9 – Optional field
- CRID – Optional field

PermitPublicationData Block – fields should be populated with Permit Holder permit information:

- PermitNumber – Required field
- PermitType – Required field
- PermitZip4 – Required field

Copyright © 2014 USPS®. All Rights Reserved

- PublicationNumber – Required for Periodicals

QualificationReportSummaryCreateRequest

QualificationReportPreparer Block – fields should be populated with Mailing Agent permit information:

- PermitNumber – Required field
- PermitType – Required field
- PermitZip4 – Required field
- PublicationNumber – Required for Periodicals
- MailerID6 – Optional field
- MailderID9 – Optional field
- CRID – Optional field

QualificationReportDetailCreateRequest

MailOwner Block – fields should be populated with Mail Owner permit information:

- PermitNumber – Required field
- PermitType – Required field
- PermitZip4 – Required field
- PublicationNumber – Required for Periodicals

PermitPublicationData Block – fields should be populated with Permit Holder permit information:

- PermitNumber – Required field
- PermitType – Required field
- PermitZip4 – Required field
- PublicationNumber – Required for Periodicals

PostageStatementCreateRequest

PermitHolderData Block – fields should be populated with Permit Holder permit information:

- MID – Optional block
- CRID – Optional field
- ContactName – Required field
- PermitPublicationData
  - PermitNumber – Required field
  - PermitType – Required field
  - PermitZip4 – Required field
  - PublicationNumber – Required for Periodicals

MailingOwnerData Block – fields should be populated Mail Owner permit information:

- MID – Optional block
- CRID – Optional field
- ContactName – Required field
- PermitPublicationData
  - PermitNumber – Required field
  - PermitType – Required field
  - PermitZip4 – Required field

Copyright © 2014 USPS®. All Rights Reserved

  - PublicationNumber – Required for Periodicals

MailingAgentData block – fields should be populated with Mailing Agent permit information:

- MID – Optional block
- CRID – Optional field
- ContactName – Required field
- PermitPublicationData
  - PermitNumber – Required field
  - PermitType – Required field
  - PermitZip4 – Required field
  - PublicationNumber – Required for Periodicals

PermitHolderForAPData block – fields should be populated with Permit Holder permit information:

- MID – Optional block
- CRID – Optional field
- ContactName – Required field
- PermitPublicationData
  - PermitNumber – Required field
  - PermitType – Required field
  - PermitZip4 – Required field
  - PublicationNumber – Required for Periodicals

PeriodicalStatementCreateRequest

MailingAgentData block – fields should be populated with Mailing Agent permit information:

- MID – Optional block
- CRID – Optional field
- ContactName – Required field
- PermitPublicationData
  - PermitNumber – Required field
  - PermitType – Required field
  - PermitZip4 – Required field
  - PublicationNumber – Required for Periodicals

PublisherData block – fields should be populated with Permit Holder permit information:

- MID – Optional block
- CRID – Optional field
- ContactName – Required field
- PermitPublicationData
  - PermitNumber – Required for Pending Periodicals
  - PermitType – Required for Pending Periodicals
  - PermitZip4 – Required for Pending Periodicals
  - PublicationNumber – Required for Periodicals

ConsolidatedPeriodicalStatementCreateRequest

MailingAgentData block – fields should be populated with Mailing Agent permit information:

Copyright © 2014 USPS®. All Rights Reserved

- MID – Optional block
- CRID – Optional field
- ContactName – Required field
- PermitPublicationData
  - PermitNumber – Required field
  - PermitType – Required field
  - PermitZip4 – Required field
  - PublicationNumber – Required for Periodicals

PublisherData block – fields should be populated with Permit Holder permit information:

- MID – Optional block
- CRID – Optional field
- ContactName – Required field
- PermitPublicationData
  - PermitNumber – Required for Pending Periodicals
  - PermitType – Required for Pending Periodicals
  - PermitZip4 – Required for Pending Periodicals
  - PublicationNumber – Required for Periodicals

2.6.1 Postage Statement By/For Information

The *PostalOne!* system will use the order of precedence determined in the tables below to determine the Mail Preparer (By) and Mail Owner (For) for postage statement processing. If a CRID or MID provided in the By/For is determined to be invalid, the *PostalOne!* system will skip that By/For precedence and move on to the next precedence.

Mail.XML Message	Mail.XML Blocks	Mail.XML Fields	Identifies	Order of Precedence
QualificationReportSummaryCreateRequest	QualificationReportSummary > QualificationReportPreprer	MailerID6 or MailerID9	Preparer	First
QualificationReportSummaryCreateRequest	QualificationReportSummary > QualificationReportPreprer	CRID	Preparer	Second
PostageStatementCreateRequest	CreatePostageStatement > MailingAgentData	MID6 or MID9	Preparer	Third
PostageStatementCreateRequest	CreatePostageStatement > MailingAgentData	CRID	Preparer	Fourth

Mailing Agent Order of Precedence

This order of precedence applies when the MailPieceCreateRequest is submitted BEFORE the PostageStatementCreateRequest.

Mail.XML Message	Mail.XML Blocks	Mail.XML Fields	Identifies	Order of Precedence
MailPieceCreateRequest	MailPieceBlockGroup > MailPieceBlock > MailOwner	MailOwnerMID6 or MailOwnerMID9	Owner	First
MailPieceCreateRequest	MailPieceBlockGroup > MailPieceBlock > MailOwner	CRID	Owner	Second
QualificationReportDetailCreateRequest	ContainerInfoData	MailOwnerCRID	Owner	Third

Copyright © 2014 USPS®. All Rights Reserved

Mail.XML Message	Mail.XML Blocks	Mail.XML Fields	Identifies	Order of Precedence
MailPieceCreateRequest	MailPieceBlockGroup > MailPieceBlock > MailOwner > PermitPublicationData	PermitNumber/PermitType/PermitZip4 or PublicationNumber	Owner	Fourth

Mailing Owner Order of Precedence

This order of precedence applies when the MailPieceCreateRequest is submitted AFTER the PostageStatementCreateRequest

Mail.XML Message	Mail.XML Blocks	Mail.XML Fields	Identifies	Order of Precedence
PostageStatementCreateRequest	CreatePostageStatement > MailingOwnerData >PermitPublicationData	PermitNumber/PermitType/PermitZip4	Owner	First
PerioidcalStatementCreateRequest	CreatePeriodicalStatement > PublisherData > PermitPublicationData	Publication Number	Owner	Second

Mailing Owner Order of Precedence

Copyright © 2014 USPS®. All Rights Reserved

3. Mail.XML 13.0B eDoc and Miscellaneous Messages

The table below shows all messages implemented in Mail.XML 13.0B

Message		
BeginCombinedMailingRequest		MailPieceCreateRequest
BeginCombinedMailingResponse		MailPieceCreateResponse
BundleDetailCancelRequest		MailPieceUpdateRequest
BundleDetailCancelResponse		MailPieceUpdateResponse
BundleDetailCreateRequest		OpenMailingGroupRequest
BundleDetailCreateResponse		OpenMailingGroupResponse
CloseMailingGroupRequest		PeriodicalStatementCreateRequest
CloseMailingGroupResponse		PeriodicalStatementCreateResponse
ConsolidatedPeriodicalStatementCreateRequest		PeriodicalStatementQueryRequest
ConsolidatedPeriodicalStatementCreateResponse		PeriodicalStatementQueryResponse
ContainerBundleReportCancelRequest		PostageStatementCancelRequest
ContainerBundleReportCancelResponse		PostageStatementCancelResponse
ContainerBundleReportCreateRequest		PostageStatementCreateRequest
ContainerBundleReportCreateResponse		PostageStatementCreateResponse
ContainerBundleReportQueryRequest		PostageStatementQueryRequest
ContainerBundleReportQueryResponse		PostageStatementQueryResponse
ContainerManifestCreateRequest		PostageStatementStatusQueryRequest
ContainerManifestCreateResponse		PostageStatementStatusQueryResponse
ContainerUpdateRequest		QualificationReportQueryRequest
ContainerUpdateResponse		QualificationReportQueryResponse
CustomerMailReportCreateRequest		QualificationReportSummaryCreateRequest
CustomerMailReportCreateResponse		QualificationReportSummaryCreateResponse
EndCombinedMailingRequest		QualificationReportDetailCreateRequest
EndCombinedMailingResponse		QualificationReportDetailCreateResponse
MailingGroupQueryRequest		SummaryZipDestinationReportCreateRequest
MailingGroupQueryResponse		SummaryZipDestinationReportCreateResponse
MailPieceCancelRequest		ReconciliationReportQueryRequest
MailPieceCancelResponse		ReconciliationReportQueryResponse

3.1 BeginCombinedMailingRequest

Purpose

The beginCombinedMailing method sends the combined mailing ID information and starts a combined mailing.

Business Rules

- Will accept if a combined mailing is NOT already open for a mailing group
- Will reject if a combined mailing is already open for a mailing group
- This message is used to combine statements from the PostageStatementCreateRequest.
- This message is used to combine statements from the PeriodicalStatementCreateRequest and/or the ConsolidatedPeriodicalStatementCreateRequest
- All postage statement in a combined mailing must be the same form type

***Note**: Important information on combined and consolidated postage statements:*

Part A – Currently, the Mail.XML specs allows the user to provide different data for the fields listed in Part C below for each postage statement request. During a Combined Mailing Request or during a Consolidated Periodical Postage Statement Request, the values of these fields (listed in Part C) have to be same from a business and processing stand-point. The current implementation of Mail.XML does not provide a feature where the user could supply this data for all of the postage statements that are consolidated or combined. A future release of Mail.XML and *PostalOne!* will cater to this requirement where the user will be required to provide with only one set of data (listed in Part C) for the whole message set of combined or consolidated postage statements. However, in the current implementation, USPS recommends all users to follow the set of instructions provided in section.

Copyright © 2014 USPS®. All Rights Reserved

Part B – For the following set of postage statement message requests, follow the instructions documented in Part C below.

- BeginCombinedMailingRequest
- EndCombinedMailingRequest
- ConsolidatedPeriodicalStatementCreateRequest
- PeriodicalStatementCreateRequest
- PostageStatementCreateRequest

Part C – For all of the postage statement create requests (items 3, 4, and 5 from above), during a Combined Mailing request (meaning postage statements enclosed in between items 1 and 2 from above) and for ConsolidatedPeriodicalStatementCreateRequest user must provide the same values inside all of the postage statements for the following fields.

- IssueDate
- IssueNumber
- VolumeNumber
- CustomerReferenceID
- AgencyCostCode
- PermitPublicationData (block of PermitHolderData block)
- PostagePaymentMethod
- RateType
- ProcessingCategory

3.1.1 BeginCombinedMailingRequest Data Structure

Mail.XML 13.0B- BeginCombinedMailingRequest				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
MailXMLPostageStatementRequestHeaderInfo block	MailXMLPostageStatementRequestHeaderInfo attribute block		Attributes block	Refer this complex attribute in Section 7
SubmittingParty Block	participantIDType		Required block; Identifies the customer submitting the message	Refer to this complex type in Section 4
SubmittingSoftware Block	participantIDType		Required block; Identifies the software submitting the message	Refer to this complex type in Section 4
SubmitterTrackingID	String 20		Required	

3.2 BeginCombinedMailingResponse

Purpose

The BeginCombinedMailingResponse will be used by USPS to notify the customer if their request to create a combined mailing has been accepted or rejected.

Error/Return Codes

Refer to Section 8 for shared error/return codes and also a list of error/return codes tied to this message.

Business Rules

- Will accept if a combined mailing is NOT already open for a mailing group
- Will reject if a combined mailing is already open for a mailing group

Copyright © 2014 USPS®. All Rights Reserved

- This message is used to combine statements from the PostageStatementCreateRequest.
- This message is used to combine statements from the PeriodicalStatementCreateRequest and/or the ConsolidatedPeriodicalStatementCreateRequest
- The ReturnInfo block will have a description for rejection
- First-Class Commercial Plus Parcels will be accepted when the following conditions are met:
  - FormType in the CreatePostageStatement block is FC (First-Class)
  - PresentationCategory in the CreatePostageStatement block is PF (Parcel, First-Class)
  - PriceType in the CreatePostageStatement block is commercialplus

3.2.1 BeginCombinedMailingResponse Data Structure

Mail.XML 13.0B- BeginCombinedMailingResponse				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
TrackingID	String 12	-	Optional	Provide the Tracking ID for the user to re-query when an error occur during the transmission.
SubmitterTrackingID	String 20		Required	
Choice Block BEGINS			Required. Either Accept or Reject block is returned.	
BeginCombinedMailingAccept Block begins			Block received upon accepting request	
MailXMLMsgResponseHeaderInfo Block begins	MailXMLMsgResponseHeaderInfo attribute block		Attributes block	Refer this attribute in Section 7
CombinedMailingID	Non-negative Integer		Optional	
ReturnInfo Block	basicReturnInfo complex type		Optional Provides reason for return Not required Multiple pairings of ReturnCode and ReturnDescription can be provided in the block	Refer to this complex type in Section 4
BeginCombinedMailingAccept Block ends				
BeginCombinedMailingReject Block begins			Block received upon rejecting request	
MailXMLMsgResponseHeaderInfo Block	MailXMLMsgHeaderInfo attribute block		Attributes block	Refer this attribute block in Section 7
ReturnInfo Block	basicReturnInfo complex type		Required Provides reason for return Required Multiple pairings of ReturnCode and ReturnDescription can be provided in the block	Refer to this complex type in Section 4

Copyright © 2014 USPS®. All Rights Reserved

Mail.XML 13.0B- BeginCombinedMailingResponse				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
BeginCombinedMailingReject Block ends				

3.3 BundleDetailCancelRequest

Purpose

Message cancels the bundle detail data submitted related to a qualification report

Business Rules

- Message cannot be sent until the BundleDetailCreateRequest message has been filed in the *PostalOne!* system and accepted through the BundleDetailCreateResponse message
- Updated number of pieces must be received for the specified MailingGroupID, CustomerGroupID, and BundleID
- A MailPieceCancelRequest message must be accepted with the updated number of cancelled pieces in the specified bundle
- BundleID can be reused after it has been cancelled

3.3.1 BundleDetailCancelRequest Data Structure

Mail.XML 13.0B- BundleDetailCancelRequest				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
MailXMLHeaderInfo block	MailXMLHeaderInfo attribute block		Required	Refer this attribute in Section 7
SubmittingParty	ParticipantIDType		Required block; Identifies the customer submitting the message	Refer to this complex type in Section 4
SubmittingSoftware	SubmittingSoftwareType		Required block; Identifies the software submitting the message	Refer to this complex type in Section 4
Choice Block BEGINS			Either UserLicenseCode/MaildatJobID or CustomerGroupID/MailingGroupID are required	
SubmitterTrackingID	String 20		Required	
UserLicenseCode	userLicenseCodeType simple type		Required	Refer to this simple type in Section 5
MaildatJobID	jobIDType simple type		Required	Refer to this simple type in Section 5
CustomerGroupID	String, 25 characters		Required	
MailingGroupID	Non-Negative Integer		Required	-
Choice Block ENDS				
Sequence Block BEGIN			Required 1 to many allowed	Placed ContainerID and BundleID in a sequence block to create a link to establish relationship between BundleIDs and

Copyright © 2014 USPS®. All Rights Reserved

Mail.XML 13.0B- BundleDetailCancelRequest				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
				ContainerIDs
ContainerID	String, 6 characters		Required	
BundleID	String, 6 characters		XSD Stand-point: Optional 0 to many allowed Implementation Stand-point: REQUIRED field	-
Sequence Block END				

3.4 BundleDetailCancelResponse

Purpose

Accept or reject a request to cancel bundle detail data

Error/Return Codes

Refer Section 8 to view shared error/return codes and also a list of error/return codes tied this message.

Business Rules

- Will accept if the bundle detail data exists in the *PostalOne!* system
- Will reject if the bundle detail data does not exist in the *PostalOne!* system
- Will reject if any pieces in the BundleDetail block have finalized postage

Mail.XML 13.0B- BundleDetailCancelResponse				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
TrackingID	String 12	-	Optional	Allow users to re-query the message without actual sending the message.
SubmitterTrackingID	String 20		Required	
Choice Block BEGINS			Required. Either Accept or Reject block is required	
BundleDetailCancelAccept block begins			Response from USPS indicating that the BundleDetailCancelRequest message was accepted	
MailXMLMsgResponseHeaderInfo	MailXMLMsgResponseHeaderInfo attribute block			Refer this attribute in Section 7
ReturnInfo	basicReturnInfo complex type		Optional	Refer this attribute in Section 7
BundleDetailCancelAccept block ends				
BundleDetailCancelReject block begins			Response from USPS indicating that the BundleDetailCancelR	

Copyright © 2014 USPS®. All Rights Reserved

Mail.XML 13.0B- BundleDetailCancelResponse				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
			equest message was rejected	
MailXMLMsgRespons eHeaderInfo	MailXMLMsgRespons eHeaderInfo attribute block			Refer this attribute in Section 7
ReturnInfo	basicReturnInfo complex type			Refer this attribute in Section 7
BundleDetailCancelR eject block ends				
Choice Block ENDS				

3.5 BundleDetailCreateRequest

Purpose

Message sends bundle detail information associated to a qualification report to the *PostalOne!* system

Business Rules

- Message cannot be sent until a QualificationReportDetailCreateRequest message has been accepted and the customer receives an acceptance message through the QualificationReportCreateResponse
- Bundle detail data from this message must be tied to that of the QualificationReportDetailCreateRequest message (ContainerID)
- MailingGroupID and CustomerGroupID must exist for an open mailing
- VersionID must be the same for the BundleDetail and ContainerDetailData blocks
- BundleID in the BundleDetail block must be unique within each container

3.5.1 BundleDetailCancelRequest Data Structure

Mail.XML 13.0B- BundleDetailCreateRequest				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
BundleDetailCreate Request Message BEGINS				
MailXMLHeaderInfo	MailXMLHeaderInfo attribute	-	Required	Refer this attribute in Section 5
SubmittingParty Block	ParticipantIDType		Required block; Identifies the customer submitting the message	Refer 'ParticipantIDType' complex type in Section 7.
SubmittingSoftware Block	SubmittingSoftwareT ype		Required block; Identifies the software submitting the message	Refer 'SubmittingSoftware' complex type in Section 7.
SubmitterTrackingID	String 20		Required	
BundleDetail	BundleDetailType complex type		Required block; 1 to many pairings (Required block for any mailing that includes bundled mail)	Refer to this complex type in Section 4
BundleDetailCreate Request Message ENDS				

Copyright © 2014 USPS®. All Rights Reserved

3.6 BundleDetailCreateResponse

Purpose

Accept or reject a request to create bundle detail data

Error/Return Codes

Refer Section 8 to view shared error/return codes and also a list of error/return codes tied this message.

Business Rules

- Will accept if all required fields are populated and values are valid
- Will reject if all required fields are not populated
- Will reject if invalid values are provided

3.6.1 BundleDetailCreateResponse Data Structure

Mail.XML 13.0B- BundleDetailCreateResponse				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
TrackingID	String 12	-	Optional	Allow mailers to re-query using this ID in MRRR message rather than resending the request message again.
SubmitterTrackingID	String 20		Required	
Choice Block BEGINS			Required Either Accept or Reject block is returned.	
BundleDetailCreateAccept block begins			Response from USPS indicating that the BundleDetailCreateRequest message was accepted if the bundle detail matches the existing data in the *PostalOne!* system	
MailXMLHeaderInfo	MailXMLHeaderInfo attribute block		Required	Refer this attribute block in Section 7
Sequence Block BEGINS			Required 1 to many allowed	
ReturnInfo	basicReturnInfo		Optional block; 0 to many pairings of ReturnCode and ReturnDescription	Refer Section 7 for Details
Sequence Block ENDS				
BundleDetailCreateAccept block ends				
BundleDetailCreateReject block begins			Response from USPS indicating that the BundleDetailCreateRequest message was rejected since the bundle detail does not match the existing data in the	

Copyright © 2014 USPS®. All Rights Reserved

Mail.XML 13.0B- BundleDetailCreateResponse				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
			PostalOne! system	
MailXMLHeaderInfo	MailXMLHeaderInfo attribute block		Required	Refer this attribute block in Section 7
ReturnInfo	basicReturnInfo complex type		Required	Refer to this complex type in Section 4

3.7 CloseMailingGroupRequest

Purpose

If a mailing group was opened in error, the group can be closed through the CloseMailingGroupRequest by passing in the USPS mailing group ID. This prevents additional mailing documents from being added to the mailing group and mailing documents attached to the group from being processed further. This message can also be used if a Qualification Report message is submitted in error or needs to be updated, since there is currently no ability to update the Qualification Report in Mail.XML. After the CloseMailingGroupRequest is submitted, the job is no longer displayed on the *PostalOne!* dashboard.

Business Rules

- Request to close a mailing group must occur before any eDoc finalization within the mailing group
- Request to close a mailing group must be submitted against a currently open mailing group
- CustomerGroupID, MailingGroupID and SubmittingParty information must exactly match an existing mailing group
- MailingGroupIDs will not be reassigned and data from the closed mailing will be stored

3.7.1 CloseMailingGroupRequest Data Structure

Mail.XML 13.0B- CloseMailingGroupRequest				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
MailXMLMailGroupRequestHeaderInfo	MailXMLMailGroupRequestHeaderInfo attribute block		Required	Refer this attribute in Section 7
SubmittingParty Block	ParticipantIDType		Required block; Identifies the customer submitting the message	Refer to this complex type in Section 4
SubmittingSoftware Block	SubmittingSoftwareType		Required block; Identifies the software submitting the message	Refer this complex type in Section 7
SubmitterTrackingID	String 20		Required	

3.8 CloseMailingGroupResponse

Purpose

The CloseMailingGroupResponse will be used by USPS to notify the customer if their request to close a mailing group has been accepted or rejected.

Error/Return Codes

Refer Section 8 to view shared error/return codes and also a list of error/return codes tied this message.

Business Rules

- Will accept if the CustomerGroupID, MailingGroupID and SubmittingParty information matches an existing mailing group
- Will reject if the CustomerGroupID, MailingGroupID and SubmittingParty information does NOT match an existing mailing group
- Will reject if invalid values are provided in the request

Copyright © 2014 USPS®. All Rights Reserved

- Will reject if PostageStatementStatus is FPP or FIN
- Will reject if PostageStatementStatus is UPD while mailing is undergoing finalization
- Will reject if mail is being inducted
- All postage statements must have PostageStatementStatus of REV
- The ReturnInfo block will have a description for rejection

3.8.1 CloseMailingGroupResponse

Mail.XML 13.0B- CloseMailingGroupResponse				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
TrackingID	String 12	-	Optional	Allow mailers to re-query the message using this Tracking ID in MRRR message.
SubmitterTrackingID	String 20		Required	
Choice Block BEGINS			Required. Either Accept or Reject block is returned	
CloseMailingGroupAccept Block begins			Block received upon accepting request	
MailXMLMailGroupResponseHeaderInfo	MailXMLMailGroupResponseHeaderInfo attribute block		Required	Refer this attribute in Section 7
ReturnInfo	basicReturnInfo complex type		Optional	Refer to this complex type in Section 4
CloseMailingGroupAccept Block ends				
CloseMailingGroupReject Block begins			Block received upon rejecting request	
MailXMLMailGroupResponseHeaderInfo	MailXMLMailGroupResponseHeaderInfo attribute block		Required	Refer this attribute in Section 7
ReturnInfo	basicReturnInfo complex type		Required	Refer to this complex type in Section 4
CloseMailingGroupReject Block ends				
Choice Block ENDS				

3.9 ConsolidatedPeriodicalStatementCreateRequest

Purpose

Allows the USPS customer to create a consolidated statement by combining previously submitted Periodicals statements

Business Rules

- Must send a successful OpenMailingGroupRequest message before sending the ConsolidatedPeriodicalStatementCreateRequest message
- Must send a successful QualificationReportDetailCreateRequest message before sending the ConsolidatedPeriodicalStatementCreateRequest message
- Must send a successful ContainerBundleReportCreateRequest message before sending the ConsolidatedPeriodicalStatementCreateRequest message
- Must send a successful PeriodicalStatementCreateRequest message before sending the ConsolidatedPeriodicalStatementCreateRequest message

Copyright © 2014 USPS®. All Rights Reserved

- Consolidated Statement must consolidate all child statements with Statement Sequence Numbers between FirstStatementSequenceNumber and LastStatementSequenceNumber are required.
- For full-service or mixed service mailings, there are two options for how to populate the container information.
  - PeriodicalLineItemData block
    - Include one PeriodicalLineItemData block for each container represented on each line of the postage statement. ContainerID and ContainerDetailID must exist from a previously submitted qualification report.
    - Do not include ContainerPostage block. If provided, it will be ignored.
  - ContainerPostage block
    - All containers are represented in the ContainerPostage blocks with the number of pieces and copies for each container. The container IDs must match an ID of a container from a previously submitted qualification report.
    - Do not provide Container IDs in the LineItemData blocks. Lines could potentially then be collapsed together as they would not need to be broken out by container. (If any Container ID is provided, the Container Postage block will be disregarded).

  Notes: *Parent and sibling containers do not need to be represented.*
  Any full-service or mixed service container that is not represented will not be sent to SASP and will not receive full-service feedback. Per January 2014 requirements version 15.0A container information is to be populated using the PeriodicalLineItemData block.

- For full-service and mixed service mailings, ContainerID and ContainerDetailID in the PeriodicalLineItemData block or ContainerID in the ContainerPostage block in the postage statement message must exist in a previously submitted QualificationReportDetailCreateRequest message.
- For full-service and mixed service mailings, ContainerID and ContainerDetailID in the PeriodicalLineItemData block or ContainerID in the ContainerPostage block in the postage statement message must exist in a MailPieceCreateRequest message submitted either before or after the Postage Statement.
- For full-service and mixed service mailings, the total number of pieces associated to a ContainerDetailID in the postage statement message must be equal to the number of pieces for that ContainerDetailID in the QualificationReportDetailCreateRequest message.
- For full-service and mixed service mailings, the total number of pieces associated to a ContainerDetailID in the QualificationReportDetailCreateRequest message must match the total number of pieces per ContainerDetailID in the MailPieceCreateRequest message.
- ContainerDetailID must be unique and can only be submitted on one postage statement across the mailing group and must account for all associated mailpieces.
- The system will support government Inside-County Consolidated Periodical and Consolidated Pending Periodical mailings.
- Rate Categories AF, BF, DF, GF, and KF are not supported for First-Class Mail, Standard Mail, or Periodicals.
- The number of pieces must equal the number of copies when the mailing does not include Firm Bundles or Addressed Supplements and InOutCountyIndicator is N.
- The number of pieces must be less than or equal to the number of copies when the mailing includes Firm Bundles but does not have any Addressed Supplements and InOutCountyIndicator is N.
- The number of pieces must be greater than or equal to the number of copies when the mailing includes Addressed Supplements but does not have Firm Bundles and InOutCountyIndicator is N.

Note*: Important information on combined and consolidated postage statements:*

Part A – Currently, the Mail.XML specs allows the user to provide different data for the fields listed in Part C below for each postage statement request. During a Combined Mailing Request or during a Consolidated Periodical Postage Statement Request, the values of these fields (listed in Part C) have to be same from a business and processing stand-point. The current implementation of Mail.XML does not provide a feature where the user could supply this data for all of the postage statements that are consolidated or combined. A future release of Mail.XML and *PostalOne!* will cater to this requirement where the user will be required to provide with only one set of data (listed in Part C) for the whole message set of combined or consolidated postage statements. However, in the current implementation, USPS recommends all users to follow the set of instructions provided in section.

Copyright © 2014 USPS®. All Rights Reserved

Part B – For the following set of postage statement message requests, follow the instructions documented in Part C below.

- BeginCombinedMailingRequest
- EndCombinedMailingRequest
- ConsolidatedPeriodicalStatementCreateRequest
- PeriodicalStatementCreateRequest
- PostageStatementCreateRequest

Part C – For all of the postage statement create requests (items 3, 4, and 5 from above), during a Combined Mailing request (meaning postage statements enclosed in between items 1 and 2 from above) and for ConsolidatedPeriodicalStatementCreateRequest user must provide the same values inside all of the postage statements for the following fields.

- IssueDate
- IssueNumber
- VolumeNumber
- CustomerReferenceID
- AgencyCostCode
- PermitPublicationData (block of PermitHolderData block)
- PostagePaymentMethod
- RateType
- ProcessingCategory
- Apply an outside county container charge on all physical pallets or physical trays split across associated PeriodicalLineItemData blocks in a mailing when the following conditions are met:
  - InOutCountyIndicator is set to 'N'.
    - Option 1: The data provided for Container postage detail (containerPostageType) shall be used to validate the charges for Periodical postage.
    - Option 2: ContainerInfoData block shall be used to validate the charges for Periodical postage.
    - Option 3: when InOutCountyIndicator is provided. The InOutCountyIndicator set to N shall be combined with the Pieces and Containers to validate the charges for Periodical postage
  - Apply option 1, option 2, or option 3 to validate and calculate the charges for Consolidated Periodical postages.
- CreateConsolidatedPeriodicalStatementData in ConsolidatedPeriodicalStatementCreateRequest message contains the same data block, PeriodicalLineItemData, as in PeriodicalStatementCreateRequest. Therefore, both Option 2 and 3 are applicable for Consolidated Periodical postage allocation for Outside County containers following the logical/physical container relationship.

3.9.1 ConsolidatedPeriodicalStatementCreateRequest Data Structure

Mail.XML 13.0B- ConsolidatedPeriodicalStatementCreateRequest				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
ConsolidatedPeriodicalStatementCreateRequest Message BEGINS				
MailXMLPostageStatementRequestHeaderInfo block	MailXMLPostageStatementRequestHeaderInfo		Attributes block	See Section 7 for Details
SubmittingParty Block	ParticipantIDType		Required block; Identifies the customer submitting	See Section 7 for Details

Copyright © 2014 USPS®. All Rights Reserved

Mail.XML 13.0B- ConsolidatedPeriodicalStatementCreateRequest				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
			the message	
SubmittingSoftware Block	SubmittingSoftwareType		Required block; Identifies the software submitting the message	See Section 7 for Details
SubmitterTrackingID	String 20		Required	
CreateConsolidatedPeriodicalStatementData block begins			Required block; contains data for consolidated periodical statements	
PeriodicalStatement	createPeriodicalStatementType	Required block; contains data critical to postage statement calculation (one to many pairings can be submitted within the CreateConsolidatedPeriodicalStatementData block)	One too many child Periodicals postage statements for a consolidated periodicals postage statement. Child statements must be at the entry level and version level to produce a Periodicals postage statement register. For a single consolidated statement, the publisher data and the mailing agent data must be the same for all of the child statements.	Refer to this complex type in Section 4
FirstStatementSequenceNumber	String, 30 characters		Required field	
LastStatementSequenceNumber	String, 30 characters		Required field	
LimitedCirculationDiscountClaimed	yesNo	Yes No	Required field	
PublisherData	mailerDataRequestType complex type		Required field, there must be only one publication number for a Periodical or permit number with type PP for a pending Periodical in a consolidated statement.	Refer to this complex type in Section 4
MailingAgentData	mailerDataRequestType complex type		Required field, there must be only one mailing agent in a consolidated statement.	Refer to this complex type in Section 4
ContainerCount	ContainerCountType complex type		Required block; at least one of the fields in this block must be populated with a	Refer to this complex type in Section 4

Copyright © 2014 USPS®. All Rights Reserved

Mail.XML 13.0B- ConsolidatedPeriodicalStatementCreateRequest				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
			nonzero value	
PeriodicalLineItemData	PeriodicalLineItemData ELEMENT		Optional block; 0 to many allowed Data used to generate container and bundle charges at the parent statement level for a consolidated periodicals statement. (one to many pairings) Alternatively, there may be no container and bundle charges or container and bundle charges may be provided at the child statement level.	Refer the definition of this element in Section 7
CreateConsolidatedPeriodicalStatementData block ends				
ConsolidatedPeriodicalStatementCreateRequest Message ENDS				

3.10 ConsolidatedPeriodicalStatementCreateResponse

Purpose

Response on whether the consolidated periodical postage statement was accepted or rejected

Error/Return Codes

Refer Section 8 to view shared error/return codes and also a list of error/return codes tied this message.

Business Rules

- Will reject the request if the mailing group does not exist
- Will reject the request if there are no child statements to consolidate
- Will reject the request if one of the child statements with StatementSequenceNumber in between the First and Last Statement Sequence Number has For Consolidated field set to False
- Will accept the request if the TotalPostage field is populated with the same value as the sum of all values in the TotalPostage field for all child statements
- ConsolidatedPeriodicalStatementCreateResponse Data Structure

Mail.XML 13.0B- ConsolidatedPeriodicalStatementCreateResponse				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
TrackingID	String 12	-	Optional	Allow mailers to re-query the message using this ID in MRRR message.
SubmitterTrackingID	String 20		Required	
Choice Block BEGINS			Required. Wither Accept or Reject block is returned.	

Copyright © 2014 USPS®. All Rights Reserved

Mail.XML 13.0B- ConsolidatedPeriodicalStatementCreateResponse				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
ConsolidatedPeriodicalStatementCreateAccept block begins			Required block if the ConsolidatedPeriodicalStatementRequest has valid fields and the mailing group exists	
MailXMLPostageStatementResponseHeaderInfo block begins	MailXMLPostageStatementResponseHeaderInfo attribute block		Attributes block	See Section 7 or Details
StatementID	Non-negative integer		Required field; paired with TotalPostage and ReturnInfo block	
TotalPostage	Double		Required field; paired with StatementID and ReturnInfo block, two decimal places.	
PostageStatementStatus	postageStatementStatusType simple type		Optional	Refer to this simple type in Section 5
ReturnInfo block	basicReturnInfo complex type		Optional block; paired with StatementID and TotalPostage	Refer to this complex type in Section 4
ConsolidatedPeriodicalStatementCreateAccept block ends				
ConsolidatedPeriodicalStatementCreateReject block begins			Required block if the fields in the request message are not valid or if the mailing group does not exist	
MailXMLPostageStatementResponseHeaderInfo block	MailXMLPostageStatementResponseHeaderInfo attribute		Attributes block	Refer this attribute in Section 7
ReturnInfo block	basicReturnInfo complex type		Required block; zero to many pairings can be submitted between ReturnCode and ReturnDescription	Refer to this complex type in Section 4
ConsolidatedPeriodicalStatementCreateReject block ends				
Choice Block ENDS				

3.11 ContainerBundleReportCancelRequest

Purpose

Request to cancel the container and bundle report information within a mailing group

Business Rules

- ContainerBundleReportCreateRequest message must be submitted successfully by the customer
- MailingGroupID and CustomerGroupID must exist for an open mailing group
- ContainerBundleReportCreateRequest must be accepted before submitting the ContainerBundleCancelRequest message for the specified MailingGroupID and CustomerGroupID
- The specified ContainerBundleReportID will cancel all Container Bundle Reports for the specific MailingGroupID and CustomerGroupID when the ContainerBundleReportCancelRequest message has been accepted

Copyright © 2014 USPS®. All Rights Reserved

3.11.1 ContainerBundleReportCancelRequest Data Structure

Mail.XML 13.0B- ContainerBundleReportCancelRequest				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
MailXMLHeaderInfo	MailXMLHeaderInfo attribute	-	Attributes block	Refer this attribute block in Section 7
SubmittingParty Block	ParticipantIDType		Required block; Identifies the customer submitting the message	Refer to this complex type in Section 4
SubmittingSoftware Block	SubmittingSoftwareType		Required block; Identifies the software submitting the message	Refer to this complex type in Section 4
SubmitterTrackingID	String 20		Required	

3.12 ContainerBundleReportCancelResponse

Purpose

Response message to inform the customer of whether the container bundle report information has been cancelled or the reason why it was not

Error/Return Codes

Refer Section 8 to view shared error/return codes and also list a of error/return codes tied this message.

Business Rules

- Will accept if the container bundle report information exists within the mailing group
- Will reject if the container bundle report information does not exist within the mailing group
- Postage statement associated with the Container Bundle Report must have PostageStatementStatus populated with UPD for USPS Processing Due and not undergoing finalization within the specified MailingGroupID.

3.12.1 ContainerBundleReportCancelResponse Data Structure

Mail.XML 13.0B- ContainerBundleReportCancelResponse				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
TrackingID	String 12	-	Optional	Allow mailers to re-query the message using this ID in MRRR message
SubmitterTrackingID	String 20		Required	
Choice Block BEGINS			Required. Either Accept or Reject block is returned.	
ContainerBundleReportCancelAccept block begins			Required block if the container bundle report data exists in the mailing group	
MailXMLHeaderInfo	MailXMLHeaderInfo attribute	-	Attributes block	Refer this attribute block in Section 7
ContainerBundleRep	String, 12 characters		Required field; must	

Copyright © 2014 USPS®. All Rights Reserved

Mail.XML 13.0B- ContainerBundleReportCancelResponse				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
ortID			be populated with the same value as the CustomerBundleReportID field of the ContainerBundleReportCreateResponse message – a one to many ratio 1 to many allowed.	
ReturnInfo	basicReturnInfo complex type	-	Optional	Refer to this complex type in Section 4
ContainerBundleReportCancelAccept block ends				
ContainerBundleReportCancelReject block begins			Required block if the container bundle report data does not exists in the mailing group	
MailXMLHeaderInfo	MailXMLHeaderInfo attribute	-	Attributes block	Refer this attribute block in Section 7
ReturnInfo Block	basicReturnInfo complex type	-	Required	Refer to this complex type in Section 4
ContainerBundleReportCancelReject block ends				
Choice Block ENDS				

3.13 ContainerBundleReportCreateRequest

Purpose

Message is used to deliver the Container and Bundle Report information to the *PostalOne!* system

Business Rules

- ContainerBundleReportCreateRequest message can only be provided when the FormType in at least one QualificationReportDetailCreateRequest message is populated with PE for the specified MailingGroupID and CustomerGroupID.
- MailingGroupID and CustomerGroupID must exist for an open mailing group
- Multiple ContainerBundleReportCreateRequest messages can be submitted within the same MailingGroupID
- A ContainerBundleSummary can be submitted for all chargeable containers and bundles or a ContainerBundleVersionReport for the chargeable containers and bundles apportioned to each Version

3.13.1 ContainerBundleReportCreateRequest Data Structure

Mail.XML 13.0B- ContainerBundleReportCreateRequest				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
MailXMLHeaderInfo	MailXMLHeaderInfo attribute	-	Attributes block	Refer this attribute block in Section 7
SubmittingParty	ParticipantIDType complex type		Required block; Identifies the customer submitting the message	Refer to this complex type in Section 4
SubmittingSoftware	SubmittingSoftwareType complex type		Required block; Identifies the software submitting the message	Refer to this complex type in Section 4

Copyright © 2014 USPS®. All Rights Reserved

Mail.XML 13.0B- ContainerBundleReportCreateRequest				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
SubmitterTrackingID	String 20		Required	
Choice Block BEGINS			Required. Either VersionBlock or Summary Block must be included in the message	
ContainerBundleVersionRecords block begins				
Sequence Block BEGINS				
SackTrayContainerRecord	SackTrayContainerVersionRecordType complex type	-	Optional block; 0 to many pairings can be submitted depending upon the number of SackTrayContainerMPURecords (used for Sack or Tray charges)	Refer to this complex type in Section 4
PalletContainerRecord	PalletContainerVersionRecordType complex type	-	Optional block; 0 to many pairings can be submitted depending upon the number of PalletMPURecords (used for Pallet charges)	Refer to this complex type in Section 4
BundleRecord	bundleVersionRecordType complex type	-	Optional block; 0 to many pairings can be submitted depending upon the number of BundleMPURecords (used for Bundle charges)	Refer to this complex type in Section 4
Sequence Block ENDS				
ContainerBundleVersionRecords block ENDS				
ContainerBundleSummaryRecords block begins			Required block for each ContainerBundleMPURecord block	
Sequence Block BEGINS				
SackTrayContainerRecord	SackTrayContainerRecordType complex type	-	Optional block; 0 to many pairings can be submitted depending upon the number of SackTrayContainerMPURecords (used for Sack or Tray charges)	Refer to this complex type in Section 4
PalletContainerRecord	PalletContainerRecordType complex type	-	Optional block; 0 to many pairings can be submitted depending upon the number of PalletMPURecords	Refer to this complex type in Section 4

Copyright © 2014 USPS®. All Rights Reserved

Mail.XML 13.0B- ContainerBundleReportCreateRequest				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
			(used for Pallet charges)	
BundleRecord	bundleRecordType complex type	-	Optional block; 0 to many pairings can be submitted depending upon the number of BundleMPURecords (used for Bundle charges)	Refer to this complex type in Section 4
Sequence Block ENDS				
ContainerBundleSummaryRecords block ends				
Choice Block ENDS				

3.14 ContainerBundleReportCreateResponse

Purpose

ResponseResponse message to inform the customer whether the ContainerBundleReportCreateRequest was accepted or rejected

Error/Return Codes

Refer Section 8 to view shared error/return codes and also a list of error/return codes tied this message.

Business Rules

QualificationReportDetailCreateRequest message must be accepted before submitting the ContainerBundleReportCreateRequest message for the specified MailingGroupID and CustomerGroupID

3.14.1 ContainerBundleReportCreateResponse Data Structure

Mail.XML 13.0B- ContainerBundleReportCreateResponse				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
ContainerBundleReportCreateResponse message BEGINS				
TrackingID	String 12	-	Optional	Allow mailers to re-query the message using this ID in MRRR message.
SubmitterTrackingID	String 20		Required	
Choice Block BEGINS			Required block. Either Accept or Reject block is returned.	
ContainerBundleReportCreateAccept block begins			Required block if the ContainerBundleReportCreateRequest message has an existing MailingGroupID and the fields are valid	
MailXMLHeaderInfo	MailXMLHeaderInfo Attribute	-	Required	Refer this attribute in Section 7
Sequence Block BEGINS			Required.	
Choice Block BEGINS				

Copyright © 2014 USPS®. All Rights Reserved

Mail.XML 13.0B- ContainerBundleReportCreateResponse				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
Sequence Block BEGINS				
ContainerBundleReportID	String, 12 characters		Required field; Respond with either the ContainerBundleReportID and ContainerBundleStatus or just the Tracking ID	
ContainerBundleStatus	containerBundleStatusTYpe	Refer 'containerBundleStatusType' simple type	Required field; Respond with either the ContainerBundleReportID and ContainerBundleStatus or just the Tracking ID	Refer this simple type Section 5
Sequence Block ENDS				
Choice Block ENDS				
ReturnInfo Block	basicReturnInfo complex type	=	Optional	Refer to this complex type in Section 4
ContainerBundleReportCreateAccept block ends				
ContainerBundleReportCreateReject block begins			Required block if the ContainerBundleReportCreateRequest message does not have an existing MailingGroupID or the fields are not valid	
MailXMLHeaderInfo	MailXMLHeaderInfo Attribute	-	Required	Refer this attribute in Section 7
ReturnInfo Block	basicReturnInfo complex type		Required	Refer to this complex type in Section 4
ContainerBundleReporrtCreateReject block ENDS				
Choice Block ENDS				
ContainerBundleReportCreateResponse message ENDS				

3.15 ContainerBundleReportQueryRequest

Purpose

Request to retrieve all the Container and Bundle information for a Periodicals Outside County Container or Bundle report

Business Rules

- Submitted after a successful ContainerBundleReportCreateResponse message is returned to the customer
- MailingGroupID and CustomerGroupID must exist for an open mailing group
- QueryRequest message can only query the database for electronic documentation submitted through Mail.XML

3.15.1 ContainerBundleReportQueryRequest Data Structure

Copyright © 2014 USPS®. All Rights Reserved

Mail.XML 13.0B- ContainerBundleReportQueryRequest				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
MailXMLHeaderInfo	MailXMLHeaderInfo Attribute	-	Required	Refer this attribute in Section 7
SubmittingParty	ParticipantIDType complex type		Required block; Identifies the customer submitting the message	Refer to this complex type in Section 4
SubmittingSoftware	SubmittingSoftwareType complex type		Required block; Identifies the software submitting the message	Refer to this complex type in Section 4
SubmitterTrackingID	String 20		Required	

3.16 ContainerBundleReportQueryResponse

Purpose

Response to the customer displaying the container and bundle data query results or the reason why there was a query error

Error/Return Codes

Refer Section 8 to view shared error/return codes and also a list of error/return codes tied this message.

Business Rules

- Submitted after a successful ContainerBundleReportCreateResponse message is returned to the customer
- ContainerBundleReportCreateRequest must be accepted before submitting the ContainerBundleQueryRequest message for the specified MailingGroupID and CustomerGroupID
- Optional blocks and fields will only be generated in the QueryResults block when the value has been populated in the database
- Required blocks and fields will always be generated in the QueryResults block
- Data will be generated post-processing with converted values in the QueryResults block
- QueryResults block will generate one to many ContainerBundleReportIDs in the QueryResults block of the ContainerBundleReportQueryResponse message

3.16.1 ContainerBundleReportQueryResponse Data Structure

Mail.XML 13.0B- ContainerBundleReportQueryResponse				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
MailXMLHeaderInfo	MailXMLHeaderInfo Attribute	-	Required	Refer this attribute in Section 7
TrackingID	String 12	-	Optional	Allow mailers to re-query the message using this ID in MRRR message
SubmitterTrackingID	String 20		Required	
Choice Block BEGINS			Required. Either QueryResult or QueryError is returned.	
QueryResults block begins			Required block; either the QueryResults or QueryError block must be populated in the response	
ContainerBundleReports block BEGINS				
ContainerBundleRep	String, 12 characters		Optional field	

Copyright © 2014 USPS®. All Rights Reserved

Mail.XML 13.0B- ContainerBundleReportQueryResponse				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
ortID				
Choice Block BEGINS			Required. Either ContainerBundleVersionRecord or ContainerBundleSummary block is returned.	
ContainerBundleVersionRecords block begins				
SackTrayContainerVersionRecords	SackTrayContainerVersionRecordType complex type		Optional block; 0 to many pairings can be submitted depending upon the number of SackTrayContainerMPURecords (used for Sack or Tray charges)	Refer to this complex type in Section 4
PalletContainerVersionRecords	PalletContainerVersionRecordType complex type		Optional block; 0 to many pairings can be submitted depending upon the number of PalletMPURecords (used for Pallet charges)	Refer to this complex type in Section 4
BundleVersionRecord	BundleVersionRecordType complex type		Optional block; 0 to many pairings can be submitted depending upon the number of BundleMPURecords (used for Bundle charges)	Refer to this complex type in Section 4
ContainerBundleVersionRecords block ends				
ContainerBundleSummaryRecords block begins			Required block for each ContainerBundleMPURecord block	
SackTrayContainerRecord	SackTrayContainerRecordType complex type		Optional block; 0 to many pairings can be submitted depending upon the number of SackTrayContainerMPURecords (used for Sack or Tray charges)	Refer to this complex type in Section 4
PalletContainerRecord	PalletContainerRecordType complex type		Optional block; 0 to many pairings can be submitted depending upon the number of PalletMPURecords (used for Pallet charges)	Refer to this complex type in Section 4
BundleRecord	BundleRecordType complex type		Optional block; 0 to many pairings can be	Refer to this complex type in Section 4

Copyright © 2014 USPS®. All Rights Reserved

Mail.XML 13.0B- ContainerBundleReportQueryResponse				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
			submitted depending upon the number of BundleMPURecords (used for Bundle charges)	
ContainerBundleSummaryRecords block ends				
Choice Block ENDS				
ReturnInfo Block	basicReturnInfo complex type		Optional.	Refer to this complex type in Section 4
ContainerBundleReports block ENDS				
QueryResults block ENDS				
QueryError block begins			Required when the query data cannot be provided; provides a reason for the error	
ReturnInfo Block	basicReturnInfoType complex type		Required	Refer to this complex type in Section 4
QueryError block ends				
Choice Block ENDS				

3.17 ContainerManifestCreateRequest

Purpose

The purpose of this message is to allow small mailers to receive SPM data on eInduction mails. This message allows mailer to associate containers to postage statements so that they can get Start-The-Clock data later.

Business Rules

- The system shall validate the data in the container manifest message and shall generate a Container manifest report with Container grouping ID, Appointment ID (optional for pre induction, required for post induction), Entry Facility Name, facility Type, Locale key (shall send to all Locale keys valid for the logical Entry point, if physical Locale key is not provided). The StatementID in the message represents the Statement ID of the Postage Statement.
- The system shall get the Entry Point Zip code from the postage statement if not available in the Container Manifest Create request, and show pre induction (status), Induction (status), container count, tray count, extra container count, type (container), estimated Arrival date, Scheduled Arrival Date/time, Closeout Date/time, StartTheClock date, and Postage paid (postage statement link.
- The system shall validate entry point discount, postage finalized, barcode valid and missing validations, barcode on a single appointment before releasing the containers to SV for induction.

3.17.1 ContainerManifestCreateRequest Data Structure

Mail.XML 13.0B- ContainerManifestCreateRequest				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
ContainerManifestHeaderInfo	ContainerManifestHeaderInfo Attribute	-	Required	Refer this attribute in Section 7
SubmittingParty	ParticipantIDType complex type		Required block; Identifies the customer submitting the message	Refer to this complex type in Section 4
SubmittingSoftware	SubmittingSoftwareType complex type		Required block; Identifies the software	Refer to this complex type in Section 4

Copyright © 2014 USPS®. All Rights Reserved

Mail.XML 13.0B- ContainerManifestCreateRequest				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
			submitting the message	
SubmitterTrackingID	String 20		Required	
Sequence Block BEGINS			Required 1 to many allowed	
container	mailxml_mm:containerManifestType			
Sequence Block ENDS				

3.18 ContainerManifestCreateResponse

Purpose

This is the response message to ContainerManifestCreateRequest.

Business Rules

- ContainerManifestCreateAccept block is returned when the ContainerManifestCreateRequest message is accepted
- ContainerManigestCreateReject block is returned when ContainerManigestCreateRequest message is rejected.

3.18.1 ContainerManifestCreateResponse Data Structure

Mail.XML 13.0B- ContainerManifestCreateResponse				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
TrackingID	String 12	-	Optional	Allow mailers to re-query message using this ID in MRRR message.
SubmitterTrackingID	String 20		Required	
Choice Block BEGINS			Required. Either Accept or Reject block is returned	
ContainerManifestCreateAccept Block BEGINS				
ContainerManifestHeaderInfo	ContainerManifestHeaderInfo attribute	-	Required	Refer this attribute in Section 7
ReturnInfo	basicReturnInfo complex type	-	Optional	Refer this attribute in Section 7
ContainerManifestCreateAccept Block ENDS				
ContainerManifestCreateReject Block BEGINS				
ContainerManifestHeaderInfo	ContainerManifestHeaderInfo attribute	-	Required	Refer this attribute in Section 7
ReturnInfo	basicReturnInfo complex type	-	Required	Refer this attribute in Section 7
ContainerManifestCreateReject Block BEGINS				
Choice Block ENDS				

3.19 ContainerManifestUpdateRequest

Purpose

Copyright © 2014 USPS®. All Rights Reserved

This is the request message for updating ContainerManifestCreateRequest messages. Message to allow update of Container Manifest data.

Business Rules

3.19.1 ContainerManifestUpdateRequest Data Structure

Mail.XML 13.0B- ContainerManifestUpdateRequest				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
ContainerManifestUpdateRequest Block BEGINS		-		
Sequence Block opens			Required.	
SubmittingParty	ParticipantIDType		Identifies the customer submitting the message	Refer 'ParticipantIDType' complex type in Section 4.
SubmittingSoftware	SubmittingSoftwareType		Identifies the software submitting the message	Refer 'SubmittingSoftware' complex type in Section 4.
SubmitterTrackingID	String 20		Required	
Container	mailxml_mm:containerManifestType	-	Required, One to many	Reference 'containerType' complex type in Section 4
Sequence Block closes				
ContainerManifestHeaderInfo	ContainerManifestHeaderInfo attribute		Required	Reference 'ContainerManifestHeaderInfo' attribute group in Section 4
ContainerManifestUpdateRequest Block ENDS		-		

3.20 ContainerManifestUpdateResponse

Purpose

Response to the message requesting updating of container manifest.

Business Rules

3.20.1 ContainerManifestUpdateResponse Data Structure

Mail.XML 13.0B- ContainerManifestUpdateResponse				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
ContainerManifestUpdateResponse Block BEGINS		-		
Sequence Block opens			Required.	
TrackingID	String 12	-	Optional	Provide the Tracking ID for the user to re-query when an error occur during the transmission

Copyright © 2014 USPS®. All Rights Reserved

Mail.XML 13.0B- ContainerManifestUpdateResponse				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
SubmitterTrackingID	String 20		Required	
Choice block opens				
ContainerManifestUpdateAccept block opens		-		
Complex block opens				
Sequence block opens				
ReturnInfo	basicReturnInfo complex type		Optional	Refer to this complex type in Section 4
Sequence block closes				
ContainerManifestHeaderInfo	ContainerManifestHeaderInfo Attribute	-	Required	Refer to this attribute in Section 4
Complex block closes				
ContainerManifestUpdateAccept block closes				
ContainerManifestUpdateReject block opens				
Complex block opens				
Sequence block opens				
ReturnInfo	basicReturnInfo complex type		Optional	Refer to this complex type in Section 4
Sequence block closes				
ContainerManifestHeaderInfo	ContainerManifestHeaderInfo Attribute	-	Required	Refer to this attribute in Section 4
Complex block closes				
ContainerManifestUpdateReject block closes				
Choice block closes				
Sequence block closes				
Complex block closes				
ContainerManifestUpdateResponse Block ENDS				

3.21 ContainerStatusNotification

Notification from USPS that a container status information is ready for pickup.

3.21.1 ContainerStatusNotification Data Structure

Mail.XML 13.0B- ContainerStatusNotification				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
ContainerStatusNotification Begins				
Complex Type Block Opens				
Sequence Block Opens			Required	

Copyright © 2014 USPS®. All Rights Reserved

Mail.XML 13.0B- ContainerStatusNotification				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
SubmittingParty	ParticipantIDType		Identifies the customer submitting the message	Refer 'ParticipantIDType' complex type in Section 4.
SubmittingSoftware	SubmittingSoftwareType		Identifies the software submitting the message	Refer 'SubmittingSoftware' complex type in Section 4.
PushMessageID	String, 25 characters		Optional	
ContainerStatusID	containerStatusIDType		Required, 1 to many	Refer to 'containerStatusIDType' in Appendix A
NotificationDate	date		Required	
Sequence Block Closes				
Complex Block Closes				
ContainerStatusNotification Ends				

3.22 ContainerStatusQueryRequest

The container status message set for PS Form 8017 and PS form 8125 containers allows a mailer, mail owner, or consolidator to provide container key information and find out if the container has any eInduction-related or any other issues prior to shipping the container to the USPS.

3.22.1 ContainerStatusQueryRequest Data Structure

Mail.XML 13.0B- ContainerStatusQueryRequest				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
Sequence Block Opens			Optional	
SubmittingParty	ParticipantIDType		Identifies the customer submitting the message	Refer 'ParticipantIDType' complex type in Section 7.
SubmittingSoftware	SubmittingSoftwareType		Identifies the software submitting the message	Refer 'SubmittingSoftware' complex type in Section 7.
SubmitterTrackingID	String 20		Required	
Sequence Block Opens			Required	
Choice Block Opens				
ContainerID Block Opens				Refer to 'containerIDType' complex type in Section 4
MaildatContainer Block Opens				
UserLicenceCode	String, 4 characters		Required (attribute)	
MaildatJobID	String, 8 characters		Required (attribute)	
ContainerID	Non Negative Integer, 6 digits		Required (attribute)	
UniqueContainerBarc	String, 24 characters		Optional (attribute)	

Copyright © 2014 USPS®. All Rights Reserved

Mail.XML 13.0B- ContainerStatusQueryRequest				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
ode				
MaildatContainer Block Closes				
MailXMLContainer Block Opens				
MailingGroupID	Non Negative Integer		Required	
CustomerGroupID	String, 25 characters		Required	
ContainerBarcode	Container24CharacterBarcodeType		Optional	
ContainerID	String, 6 characters		Required	
MailXMLContainer Block Closes				
ContainerID Block Closes				
IMcb	IMcbType		Required	
ConsigneeApptID	String, 12 characters		Required. 1 to many allowed	
ConsigneeContainer ManifestID	nonNegativeInteger		Required	
ContentID Block Opens			Required. 1 to many block allowed	
ConsigneeContentID	String, 12 characters		Required (attribute)	
SchedulerContentID	String, 12 characters		Optional (attribute)	
ContentID Block Closes				
Choice Block Opens			Optional	
Sequence Block Opens			Required	
UserLicenseCode	userLicenseCodeType		Required	
MaildatJobID	jobIDType		Required	
Sequence Block Closes				
Sequence Block Opens			Required	
CustomerGroupID	String, 6 characters		Optional	
MailingGroupID	nonNegativeInteger		Required	
Sequence Block Closes				
Choice Block Closes				
eInductionIndicator	eInductionIndicatorType	Yes/No	Optional	
Sequence Block Opens				
Sequence Block Closes				
ContainerInfoIncludedInResponseFlag	containerInfoIncludedInResponseFlagType		Optional. 0 to many block allowed.	

3.23 ContainerStatusQueryResponse

The following eInduction issues can stop the creation of an electronic 8125 (e8125) are:

- invalid barcode – the barcode data format is not valid
- payment not finalized – the clerk has not yet finalized payment

Copyright © 2014 USPS®. All Rights Reserved

- payment not yet processed – the electronic data has not been updated by the mailer to make the container in a ready to pay status
- entry point payment discount error – the entry point discount filed vs. the physical facility where mail is scheduled through FAST for delivery does not support the discount type

In all of these cases, unless the issues are resolved electronically through an update of data or through the clerk finalizing the postage, the containers' e8125 or e8017 will not be generated and sent to the Surface Visibility (SV) devices for induction. When that container shows up without an e8125 at the plant, the container can be stopped and its processing can be delayed or it can be returned to the shipper.

3.23.1 ContainerStatusQueryResponse Data Structure

Mail.XML 13.0B- ContainerStatusQueryResponse				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
ContainerStatusQueryResponse message BEGINS				
sequence block opens				
TrackingID	String 20		optional	
SubmitterTrackingID	String 20		Required	
choice block opens				
QueryResults complexType opens				
sequence block opens				
LargeTransactionDividerResult			optional	
ContainerStatusInfoType			unbounded	
sequence block closes				
QueryResults complexType closes				
QueryError complexType opens				
choice block closes				
sequence block closes				
ContainerStatusQueryResponse message ENDS				

3.24 ContainerUpdateRequest

Purpose

Allows USPS customers to update a container originally submitted through Mail.dat or Mail.XML.

Business Rules

Mail.dat Business Rules:

- Must be submitted after a Mail.dat file submission has occurred
- The container must already exist in the *PostalOne!* system
- The container must not have any finalized postage
- All additional business rules that apply to Mail.dat file based container updates apply to the Mail.XML container update message set
  - All fields for Full and Mixed Service processing must be provided prior to submission
  - A matching ID in the ContainerID field in the FullContainerID block must exist.

Copyright © 2014 USPS®. All Rights Reserved

- The CRID must match the Mailing Facility ID in the .seg file
- The following elements can be submitted in the ContainerUpdateRequest to update the value originally submitted in the .csm file (indicated in parenthesis):
  - ReservationNumber (Reservation Number)
  - IMBarcode (Label: IM™ Container Or IM™ Tray Barcode)
  - ScheduledInductionDate (Scheduled Induction Date)
  - ScheduledInductionTime (Scheduled Induction Time)
  - CSATripID (CSA Trip ID)
  - USPSPickUp (USPS Pick UP)
  - ConsigneeContentID (FAST Content ID)
  - FASTScheduerID (FAST Scheduler ID)
  - EntryPointADLocaleKey (Entry Point - Actual / Delivery - Locale Key)
  - EntryPointADPostalCode (Entry Point - Actual / Delivery - Postal Code)
  - ScheduledShipDate (Scheduled Ship Date)
  - ScheduledShipTime (Scheduled Ship Time)
  - TruckDispatchNumber (Truck or Dispatch Number)
  - StopDesignator (Stop Designator)
  - A Transportation Update will not be accepted when a container is identified as having a parent container through the Parent Container Reference ID originally submitted in the in the .csm file.
  - A Transportation Update will not be accepted when a container is identified as having a sibling logical container through the Sibling Container Reference ID and Sibling Container Indicator originally submitted in the .csm file.

Mail.XML Business Rules:

- Must be submitted after the QualificationReportDetailCreateRequest message has been accepted
- The container must already exist in the *PostalOne!*
- All of the data element within the SummaryRecordUpdate block should be treated as Optional except for the ContainerStatus element.
- The system shall track every container data updated through Mail.XML by user/company that has sent the update. It will also flag the transaction that are being updated with Mail.XML instead of Mail.dat
- The following elements can be submitted in the ContainerUpdateRequest to update the value originally submitted in the QualificationReportSummaryCreateRequest/QualificationReportDetailCreateRequest (indicated in parenthesis):
  - IMBarcode (ContainerBarcode)
  - EntryPointADLocaleKey (EntryLocaleKey)
  - EntryPointADPostalCode (PhysicalPostalCodeEntryPoint)
  - ScheduledInductionDate (ScheduleInductionDateTime)
  - ScheduledInductionTime (ScheduleInductionDateTime)
  - CSADispatchNumber (CSADispatchNumber)
  - USPSPickUp (USPSPickUp)
  - ConsigneeContentID (ConsigneeContentID)
  - ScheduledShipDate (ScheduledShipDateTime)
  - ScheduledShipTime (ScheduledShipDateTime)
  - TruckDispatchNumber (TruckAndDispatchNumber)

Copyright © 2014 USPS®. All Rights Reserved

- For Transportation Updates, all fields provided in the ContainerUpdateRequest message will be validated, but only the valid Transportation Update fields will be updated in the database. Any additional fields provided will be ignored.
- A Transportation Update when ContainerStatus is T cannot be submitted more than 30 calendar days after the PostageStatementMaililngDate.
- The *PostalOne!* system will only support Transportation Updates submitted within 30 days of the Postage Statement Mailing Date. If the Submission Date for the Mail.dat file or Mail.XML ContainerUpdateRequest message is more than 30 days after the Postage Statement Mailing Date, the file and/or message will be rejected.
- A Transportation Update will not be accepted when a container is identified as having a parent container through the ParentContainerRefID originally submitted in the original QualificationReportDetailCreateRequest.
- A Transportation Update will not be accepted when a container is identified as having a sibling container through the SiblingContainerID submitted in the original QualificationReportDetailCreateRequest.

3.24.1 ContainerUpdateRequest Data Structure

Mail.XML 13.0B- ContainerUpdateRequest				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
ContainerUpdateRequest BEGINS				
SubmittingParty Block	ParticipantIDType		Required block; Identifies the customer submitting the message	Refer to this complex type in Section 4
SubmittingSoftware Block	SubmittingSoftwareType		Required block; Identifies the software submitting the message	Refer to this complex type in Section 4
SubmitterTrackingID	String 20		Required	
SummaryRecordUpdate	summaryRecordUpdateType complex type	-	Required 1 to many allowed. Containers all information to be updated.	Refer to this complex type in Section 4
ContainerUpdateRequest ENDS				

3.25 ContainerUpdateResponse

Purpose

The MailDatContainerUpdateResonse will be used by USPS to notify the customer if their request to update a container originally submitted via Mail.dat has been accepted or rejected.

Error/Return Codes

Refer Section 8 to view shared error/return codes and also a list of error/return codes tied this message.

Business Rules

Mail.dat Business Rules:

- Will accept if original container exists and valid values are passed in updated fields
- Will reject if original container does not exist or invalid values are passed in updated fields
- If accepted, container information returned will reflect updated values in *PostalOne!*
- If rejected, container information returned will reflect attempted updated values from the request
- Will reject if attempting to update the logical facility after payment has been received on a container
- Will only allow T status after an R or X

Copyright © 2014 USPS®. All Rights Reserved

- Will reject if deleted containers are attempted to be re-used
- The ReturnInfo block will have a description for rejection
- Postage statement will be cancelled if ContainerStatus is updated to C or D and PostageStatementStatus is UPD and ContainerStatus is R
- EntryPointEDPostalCode and EntryPointEDFacility fields cannot be updated when the original container has a ContainerStatus of R
- Only the Full Container Block will be returned to a mailer to confirm requested updates if the message is accepted
- Postage statement will be cancelled and the associated Reconciliation Report will be updated for the specified CRID if PosatageStatementStatus is UPD and all SummaryRecordUpdate block are updated to D
- The ContainerStatus field in the SummaryRecordUpdate block can only be populated with R if it is updating a container that has the ContainerStatus populated with C for Cancel in the prior update
- Transportation update information is not sent to the Full-Service system for Full-Service appointment or CSA compliance checking

3.25.1 ContainerUpdateResponse Data Structure

Mail.XML 13.0B- ContainerUpdateResponse				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
ContainerUpdateResponse BEGINS				
TrackingID	String 12	-	Optional	Allow mailers to re-query the message using this ID in MRRR message.
Choice Block BEGINS			Required. 1 to many allowed. Either ContainerUpdateAccept or ContainerUpdateReject is returned.	
ContainerUpdateAccept Block begins			Block received upon accepting request	
FullContainerID	fullContainerIDType complex type		Required	Refer to this complex type in Section 4
ReturnInfo	basicReturnInfo complex type		Optional	Refer to this complex type in Section 4
ContainerUpdateAccept block ends				
ContainerUpdateReject block begins				
FullContainerID	fullContainerIDType complex type		Required	Refer to this complex type in Section 4
ReturnInfo	basicReturnInfo complex type		Required	Refer to this complex type in Section 4
ContainerUpdateReject block ends				
Choice Block ENDS				
ContainerUpdateResponse ENDS				

3.26 CustomerMailReportCreateRequest

Purpose

This report is used mainly for Permit/Customer Identification. This report allows the specific customer identification and permit identification who may need to be charged for paying the shortage of postage.

Copyright © 2014 USPS®. All Rights Reserved

Business Rules

- This report is required for MLOCR mailing
- Message cannot be sent until a QualificationReportDetailCreateRequest message has been accepted and the customer receives an acceptance message through the QualificationReport CreateResponse message
- Message cannot be sent until a PostageSatementCreateRequest message has been accepted and the customer receives an acceptance message through the PostageStatementCreate Response message
- Will accept if the CustomerGroupID, MailingGroupID, and SubmittingParty information matches an existing mailing group.
- Will validate that the OnePassPlannedOrActual element within the CustomerMailReportCreateRequest matches the OnePassPlannedOrActualFlag element within the QualificationReportDetailCreateRequest message
- Will reject if invalid values are provided

3.26.1 CustomerMailReportCreateRequest Data Structure

Field Description

Mail.XML 13.0B- CustomerMailReportCreateRequest				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
CustomerMailReport CreateRequest BEGINS				
SubmittingParty	participantIDType complex type		Required Block but all attributes within this block are optional	Refer to this complex type in Section 4
SubmittingSoftware	submittingSoftwareTy pe complex type		Required	Refer to this complex type in Section 4
SubmitterTrackingID	String 20		Required	
CustomerGroupID	String 25		Required	
MailingGroupID	nonnegative Integer		Required	
OnePassPlannedOrA ctual	yesNo simple type	Yes/No	Optional	Refer to this simple type in Section 5
OnePassOrTwoPass	onePassOrTwoPassT ype simple type		Optional	Refer to this simple type in Section 5
CustomerMailReportI nfo Block BEGIN			Required 1 to many allowed	
CustomerName	String 50		Optional	
PermitInfo	permitPublicationDat aType complex Type		Optional	Refer to this complex type in Section 4
Weight	Double		Optional The value of Weight must be in Pounds.	
RateAffixed	Double		Optional	
AdditionalPermitInfo	permitPublicationDat aType complex Type		Optional	Refer to this complex type in Section 4
NumberOfPieces	nonnegative Integer		Optional	
PostageAffixed	Double		Optional	
TotalPostage	Double		Optional	
RunningTotalNumber OfPieces	nonnegative Integer		Optional	
CustomerMailReportI nfo Block END				
CustomerMailReport CreateRequest ENDS				

Copyright © 2014 USPS®. All Rights Reserved

3.27 CustomerMailReportCreateResponse

Purpose

This is a response message to CustomerMailReportCreateRequest

Business Rules

This report is required for MLOCR mailing

3.27.1 CustomerMailReportCreateResponse Data Structure

Mail.XML 13.0B- CustomerMailReportCreateResponse				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
CustomerMailReport CreateResponse BEGINS				
TrackingID	String 12	-	Optional	Allow mailers to re-query the message using this ID in MRRR Message
SubmitterTrackingID	String 20		Required	
Choice Block BEGINS			Required. Accept or Reject block is returned	
CustomerMailReport CreateAccept Block BEGIN			Either Accept or Reject Block is returned	
ReturnInfo	basicReturnInfo complex type		Optional	Refer to this complex type in Section 4
CustomerMailReport CreateAccept Block END				
CustomerMailReport CreateReject Block BEGIN				
ReturnInfo	basicReturnInfo complex type		Optional	Refer to this complex type in Section 4
CustomerMailReport CreateReject Block END				
Choice Block ENDS				
CustomerMailReport CreateResponse ENDS				

3.28 EndCombinedMailingRequest

Purpose

The endCombinedMailing method is used to mark when postage statements for a combined mailing have all been submitted.

Business Rules

- BeginCombinedMailingRequest must be accepted before submitting the EndCombinedMailingRequest message for the specified MailingGroupID and CustomerGroupID
- All postage statements to be combined must be submitted before sending the end request
- This message is used to combine statements from the PostageStatementCreateRequest.
- This message is used to combine statements from the PeriodicalStatementCreateRequest and/or the ConsolidatedPeriodicalStatementCreateRequest
- All postage statements within the combined mailing must have the same FormType

Copyright © 2014 USPS®. All Rights Reserved

- All periodical statements within a Combined Periodical mailing must have the same CombinedMailingID
- All postage statements within the combined mailing must be accepted before the submission of the EndCombinedMailingRequest message. The postage statement will not be included in the combined mailing if it is submitted after the EndCombinedMailingRequest message is submitted or if it was rejected
- First-Class Commercial Plus Parcels will be accepted when the following conditions are met:
  - FormType in the CreatePostageStatement block is FC (First-Class)
  - PresentationCategory in the CreatePostageStatement block is PF (Parcel, First-Class)
  - PriceType in the CreatePostageStatement block is commercialplus

***Note**: Important information on combined and consolidated postage statements:*

Part A – Currently, the Mail.XML specs allows the user to provide different data for the fields listed in Part C below for each postage statement request. During a Combined Mailing Request or during a Consolidated Periodical Postage Statement Request, the values of these fields (listed in Part C) have to be same from a business and processing stand-point. The current implementation of Mail.XML does not provide a feature where the user could supply this data for all of the postage statements that are consolidated or combined. A future release of Mail.XML and *PostalOne!* will cater to this requirement where the user will be required to provide with only one set of data (listed in Part C) for the whole message set of combined or consolidated postage statements. However, in the current implementation, USPS recommends all users to follow the set of instructions provided in section.

Part B – For the following set of postage statement message requests, follow the instructions documented in Part C below.

- BeginCombinedMailingRequest
- EndCombinedMailingRequest
- ConsolidatedPeriodicalStatementCreateRequest
- PeriodicalStatementCreateRequest
- PostageStatementCreateRequest

Part C – For all of the postage statement create requests (items 3, 4, and 5 from above), during a Combined Mailing request (meaning postage statements enclosed in between items 1 and 2 from above) and for ConsolidatedPeriodicalStatementCreateRequest user must provide the same values inside all of the postage statements for the following fields.

- IssueDate
- IssueNumber
- VolumeNumber
- CustomerReferenceID
- AgencyCostCode
- PermitPublicationData *(block of PermitHolderData block)*
- PostagePaymentMethod
- RateType
- ProcessingCategory

3.28.1 EndCombinedMailingRequest Data Structure

Mail.XML 13.0B- EndCombinedMailingRequest				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
EndCombinedMailing Request BEGINS				
MailXMLPostageStat ementRequestHeade rInfo	MailXMLPostageStat ementRequestHeade rInfo attribute		Required	Refer this attribute in Section 7
SubmittingParty	ParticipantIDType		Required block;	Refer to this complex

Copyright © 2014 USPS®. All Rights Reserved

Mail.XML 13.0B- EndCombinedMailingRequest				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
Block	complex type		Identifies the customer submitting the message	type in Section 4
SubmittingSoftware Block	SubmittingSoftwareType complex type		Required block; Identifies the software submitting the message	Refer to this complex type in Section 4
SubmitterTrackingID	String 20		Required	
CombinedMailingID	Non-negative Integer		Required	
EndCombinedMailing Request ENDS				

3.29 EndCombinedMailingResponse

Purpose

The EndCombinedMailingResponse will be used by USPS to notify the customer if their request to end a combined mailing has been accepted or rejected.

Error/Return Codes

Refer Section 8 to learn shared error/return codes and also list of error/return codes tied this message.

Business Rules

- Will accept if a combined mailing is open for the mailing group and more than one postage statement has been submitted
- Will reject if a combined mailing is NOT already open for the mailing group
- Will reject if a more than one postage statement has NOT been submitted for the mailing group
- Upon accepting, the *PostalOne!* system will be able to display the combined postage statements
- The ReturnInfo block will have a description for rejection
- This message is used to combine statements from the PostageStatementCreateRequest.
- This message is used to combine statements from the PeriodicalStatementCreateRequest and/or the ConsolidatedPeriodicalStatementCreateRequest
- The Periodical Verification statement will be generated immediately after receiving an EndCombinedMailingResponse accept message.

3.29.1 EndCombinedMailingResponse Data Structure

Mail.XML 13.0B- EndCombinedMailingResponse				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
EndCombinedMailing Response BEGINS				
TrackingID	String 12	-	Optional	Allow mailers to re-query the message using this ID in MRRR message
SubmitterTrackingID	String 20		Required	
Choice Block BEGINS			Required Accept or reject block is returned.	
EndCombinedMailing Accept Block begins			Block received upon accepting request	
MailXMLMsgRespons eHeaderInfo	MailXMLMsgRespons eHeaderInfo attribute		Required	Refer this attribute in Section 7

Copyright © 2014 USPS®. All Rights Reserved

Mail.XML 13.0B- EndCombinedMailingResponse				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
Sequence block BEGINS				
CombinedMailingID	Non-negative integer		Required	
ReturnInfo	basicReturnInfo complex type		Optional Provides reason for return Required Multiple pairings of ReturnCode and ReturnDescription can be provided in the block	Refer to this complex type in Section 4
Sequence block ENDS				
EndCombinedMailing Accept Block ends				
EndCombinedMailing Reject Block begins			Block received upon accepting request	
MailXMLMsgRespons eHeaderInfo	MailXMLMsgRespons eHeaderInfo attribute		Required	Refer this attribute in Section 7
ReturnInfo	basicReturnInfo complex type		Required Provides reason for return Required Multiple pairings of ReturnCode and ReturnDescription can be provided in the block	Refer to this complex type in Section 4
EndCombinedMailing Rejectt Block ends				
Choice Block ENDS				
EndCombinedMailing Response ENDS				

3.30 MailingGroupQueryRequest

The MailingGroupQueryRequest message will allow the customer to provide a Customer Group ID (Customer Job ID) to request the information on a mailing group in the *PostalOne!* system.

3.30.1 MailingGroupQueryRequest Data Structure

Mail.XML 13.0B- MailingGroupQueryRequest				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
SubmittingParty	ParticipantIDType complex type		Identifies the customer submitting the message	Refer to this complex type in Section 4
SubmittingSoftware	SubmittingSoftwareT ype complex type		Identifies the software submitting the message	Refer to this complex type in Section 4
SubmitterTrackingID	String 20		Required	
MailXMLMailGroupR equestHeaderInfo	MailXMLMailGroupR equestHeaderInfo attribute	-	Required	Refer this attribute block in Section 7

Copyright © 2014 USPS®. All Rights Reserved

3.31 MailingGroupQueryResponse

The MailingGroupQueryResponse message will allow the USPS *PostalOne!* system to sends back basic information about the mailer, including Permit or Publication Number information, mailing acceptance office ZIP Code, and the type of presort used in the mailing while assigning a MailingGroupID.

For more details on required vs. optional fields and blocks as well as the data types, please review the Mail.XML Transaction Message Protocol Messaging Specification.

3.31.1 MailingGroupQueryResponse Data Structure

Mail.XML 13.0B- MailingGroupQueryResponse				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
MailXMLMailGroupResponseHeaderInfo	MailXMLMailGroupResponseHeaderInfo attribute	-	Required	Refer this attribute in Section 7
TrackingID	String 12	-	Optional	Allow mailers to re-query the message using this ID in MRRR Message
SubmitterTrackingID	String 20		Required	
Choice Block BEGINS			Required. QueryResult or QueryError is returned.	
QueryResults Block BEGINS				
MailingGroup	mailingGroupDataType complex type	-	Required	Refer to this complex type in Section 4
ReturnInfo	basicReturnInfo complex type		Optional	Refer to this complex type in Section 4
QueryResults Block ENDS				
QueryError Block BEGINS				
ReturnInfo	basicReturnInfo complex type		Required	Refer to this complex type in Section 4
QueryError Block ENDS				
Choice Block ENDS				

3.32 MailPieceCancelRequest

Purpose

Used to cancel a previously created mailpiece or piece range

Business Rules

- Must be submitted to a currently existing mailpiece or piece range
- MailingGroupID and CustomerGroupID must exist for an open mailing
- Cannot cancel a mailpiece if the 'W' or 'S' indicators for WastedPieceIndicator have resulted in adjusting an already finalized postage statement
- Cannot cancel a mailpiece or piece range if postage has been finalized on its corresponding container

3.32.1 MailPieceCancelRequest Data Structure

Mail.XML 13.0B- MailPieceCancelRequest				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
MailPieceCancelReq				

Copyright © 2014 USPS®. All Rights Reserved

Mail.XML 13.0B- MailPieceCancelRequest				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
uest Message BEGINS				
CustomerGroupID	String 25		Optional attribute	
MailingGroupID	nonNegative Integer		Optional attribute	
MaildatJobID	jobIDType simple type		Optional attribute	Refer to this simple type in Section 5
UserLicenseCode	userLicenseCodeTyp e simple type		Optional attribute	Refer to this simple type in Section 5
SubmittingParty Block	ParticipantIDType		Required block; Identifies the customer submitting the message	Refer to this complex type in Section 4
SubmittingSoftware Block	SubmittingSoftwareT ype		Required block; Identifies the software submitting the message	Refer to this complex type in Section 4
SubmitterTrackingID	String 20		Required	
Choice Block BEGINS			Either Maildat or Mailxml blocks should be used.	
Sequence Block 1 BEGINS (Maildat submission)				
UserLicenseCode	userLicenseCodeTyp e simple type		Field not being supported	Refer to this simple type in Section 5
MaildatJobID	jobIDType simple type		Field not being supported	Refer to this simple type in Section 5
TransmittedCount	64onnegative Integer		Optional	
Choice Block BEGINS			Either PDRMailPiece or PDRRangePiece or MailPieceID block or PieceRangeID	
PDRMailPieceBlock BEGINS			Block not being supported	
PackageID	packageIDType simple type	-	Required	Refer to this simple type in Section 5
CQTDatabaseID	CQTDatabaseIDType simple type	-	Required	Refer to this simple type in Section 5
MailPieceBlock	mailPieceBlockTYpe complex type		Required	Refer to this complex type in Section 4
PDRMailPieceBlock ENDS				
PDRRangePieceBloc k block BEGINS			Block not being supported	
DatabaseContainerID	databaseContainerID Type simple type	-	Required	Refer to this simple type in Section 5
PieceRangeBlock block BEGINS			Required	
PieceRangeID	String 22	-	Required	-
IMbarcodeLowerSeri alization block begins				
MailerID6	mailerID6Type		Required	Refer to this simple

Copyright © 2014 USPS®. All Rights Reserved

Mail.XML 13.0B- MailPieceCancelRequest				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
				type in Section 5
SerialNumber9	iMBSerialNumber9Type		Required	Refer to this simple type in Section 5
OR				
MailerID9	mailerID9Type		Required	Refer to this simple type in Section 5
SerialNumber6	iMBSerialNumber6Type		Required	Refer to this simple type in Section 5
IMbarcodeLowerSerialization block ends				
IMBarcodeUpperSerialization block begins				
MailderID6	mailerID6Type		Required	Refer to this simple type in Section 5
SerialNumber9	iMBSerialNumber9Type		Required	Refer to this simple type in Section 5
OR				
MailerID9	mailerID9Type		Required	Refer to this simple type in Section 5
SerialNumber6	iMBSerialNumber6Type		Required	Refer to this simple type in Section 5
IMBarcodeUpperSerialization block ends				
MailPreparer	ParticipantIDType			See Section 7 for Details
MailOwner	ParticipantIDType			See Section 7 for Details
Choice Block BEGINS			Required. ServiceCode or MailClass	
ServiceTypeCode	ServiceTypeCodeType simple type		Required	Refer to this simple type in Section 5
MailClass	mailClassType simple type		Required	Refer to this simple type in Section 5
Choice Block ENDS				
ServiceLevelIndicator	ServiceLevelIndicatorType simple type		Required	Refer to this simple type in Section 5
Pieces	nonNegative Integer		Required 1 to many allowed	
Copies	nonNegative Integer		Required 1 to many allowed	
PieceRangeBlockType ENDS				
PDRRangePieceBlock ENDS				
MailPieceID Block begins			Required. 1 to many allowed	
IMB block begins	IntelligentMailBarcodeType			See Section 8 for Details
PlanetCode	planetCodeType simple type		Optional	Refer to this simple type in Section 5
DeliveryPointZip	RoutingZipCodeType	Refer ‘RoutingZipCodeType’ simple type	Conditionally required for Full-Service / Mixed Service	Refer to this simple type in Section 5

Copyright © 2014 USPS®. All Rights Reserved

Mail.XML 13.0B- MailPieceCancelRequest				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
			mailings.	
DeliveryContainerID	Ns22		Required	
DeliveryPointZip	RoutingZipCodeType		Conditionally required for Full-Service / Mixed Service mailings.	Refer to this simple type in Section 5
MailPieceID Block ENDS				
PieceRangeID	String 22		Required 1 to many allowed	
Choice Block END				
Sequence Block 1 ENDS (Maildat Submission)				
Sequence Block 2 BEGINS (MailXML Submission)				
CustomerGroupID	String, 25 characters		Required field; must be populated with the same value as the CustomerGroupID in the MailPieceCreateResponse message	
MailingGroupID	Non-negative Integer		Required field; must be populated with the same value as the MailingGroupID in the MailPieceCreateResponse message	
TransmittedCount	Non-negative Integer		Not required Count of records transmitted in message	
Choice Block BEGINS				
MailPieceBlockGroup	MailPieceBlockGroup Type complex type		1 to many can be submitted Either MailPieceBlock or MailXMLPieceRange Block submitted	Refer to this complex type in Section 4
MailXMLPieceRange Block	MailXMLPieceRange BlockType complex type	-	Required 1 to many allowed	Refer to this complex type in Section 4
Choice Block ENDS				
Sequence Block 2 ENDS (MailXML Submission)				
MailPieceCancelRequest Message ENDS				

3.33 MailPieceCancelResponse

Purpose

Accept or reject a request to cancel a mailpiece or piece range

Error/Return Codes

Copyright © 2014 USPS®. All Rights Reserved

Refer Section 8 to view shared error/return codes and also a list of error/return codes tied this message.

Business Rules

- Will accept if the mailpiece or piece range exists
- Will accept if Postage StatementStatus is UPD for USPS Processing Due
- Will reject if the mailpiece or piece range does not exist
- Will reject if a mailpiece 'W' or 'S' indicators for WastedPieceIndicator have resulted in adjusting an already finalized postage statement
- Will reject if Postage StatementStatus is FIN for finalized or FPP for finalized pending payment
- For mail piece and piece range cancellation QualificationReportDetailCreateRequest and BundleDetailCreateRequest messages have not been accepted
- The MailPieceBlock for the MailPieceCancelRequest and MailPieceCreateRequest must be the same for the specified MailingGroupID and CustomerGroupID
- The MailXMLPieceRangeBlock for the MailPieceCancelRequest and MailPieceCreateRequest must be the same for the specified MailingGroupID and CustomerGroupID
- The ReturnInfo block will have a description for rejection

3.33.1 MailPieceCancelResponse Data Structure

Mail.XML 13.0B- MailPieceCancelResponse				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
MailPIeceCancelResponse BEGINS				
TrackingID	String 12	-	Optional	-
SubmitterTrackingID	String 20		Required	
Choice Block BEGINS				
MailPieceCreateAccept Block begins			Block received upon accepting request 1 to many can be submitted	
MailXMLHeaderInfo	MailXMLHeaderInfo attribute	-	Required	Refer this attribute block in Section 7
ReturnInfo	basicReturnInfo complex type		Optional 1 to many allowed	Refer to this complex type in Section 4
MailPieceCreateAccept Block ENDS				
MailPieceCreateReject Block BEGINS			Block received upon rejecting request	
MailXMLHeaderInfo	MailXMLHeaderInfo attribute	-	Required	Refer this attribute block in Section 7
ReturnInfo	basicReturnInfo complex type		Required	Refer to this complex type in Section 4
MailPieceCreateReject Block ENDS				
Choice Block ENDS				
MailPIeceCancelResponse ENDS				

3.34 MailPieceCreateRequest

Purpose

Copyright © 2014 USPS®. All Rights Reserved

Used to create mailpieces or piece ranges for a mailing group. Piece Range records should represent the maximum number of pieces for a handling unit/container for a particular service level. To ensure efficient Full-Service processing, single pieces should be represented by Mail Pieces instead of the same Upper and Lower Piece Ranges.

Business Rules

- The MailPieceCreateRequest message can only be submitted when the FullServiceParticipationIndicator in the OpenMailingGroupRequest message is set to F (Full-Service) or M (Mixed Service).
- Must be submitted after all QualificationReportSummaryCreateRequest and QualificationReportDetailCreateRequest messages have been accepted
- MailingGroupID and CustomerGroupID must exist for an open mailing
- In the WastedPieceIndicator field; only 'X' and 'T' are recommended at this time. If 'W' or 'S' is provided then system will ignore those values and those will be treated as blank by the system.
- The system will support shortage and spoilage that do not trigger postage adjustment with WastedPieceIndicator field set to X and T. The system will validate that the number of MailPieceBlock blocks without WastedPieceIndicator set to X and T equals the sum of the TotalPieces fields, the TotalCopies fields, or a value in between the sum of these fields in the ContainerDetailData blocks in the QualificationReportSummaryCreateRequest/QualificationReportDetailCreateRequest message.
- For full-service and mixed service mailings, each container ID in the MailPieceCreateRequest message must exist in a previously submitted QualificationReportDetailCreateRequest message.
- For full-service and mixed service mailings, the total number of pieces per container ID in the MailPieceCreateRequest message cannot exceed the total number of pieces per container in the previously submitted QualificationReportDetailCreateRequest message (for mail piece or piece range).
- For Full-Service and Mixed Service mailings, at least one of CRID, MailOwnerMID6, MailOwnerMID9, PermitNumber, or PublicationNumber must be provided,
- For MLOCR mailings, either the BarcodeID, ServiceTypeCode, MailerID6, and SerialNumber9 fields or the BarcodeID, ServiceTypeCode, MailerID9, and SerialNumber6 fields must be populated.
- For MLOCR mailings, the IMBUpperSerialization block and IMBLowerSerialization block must be populated.
- The MailPieceCreateRequest messages will be rejected when the sum of the MailXMLPieceRangeBlock IMbarcodeUpperSerialization minus the MailXMLPieceRangeBlocks IMbarcodeLowerSerialization plus 1 (one) for all Full-Service blocks within the mailing group is either:
  - 20% or more greater than the larger of either (1) the sum of the Pieces field for all full-service PieceRangeBlocks or (2) the sum of Copies field for all full-service PieceRangeBlocks, or
  - Less than the smaller of either (1) the sum of the Pieces field for all full-service PieceRangeBlocks or (2) the sum of Copies field for all full-service PieceRangeBlocks.
- For IMpb Non-Compliance processing of the ZIP+4 verification requires that the 9 digit ZIP+4 be provided as part of the MailPieceCreateRequest. The IMpb Non-Compliance processing excludes periodical parcels.
- MailPieceCreateRequest messages can be submitted before or after the Postage/Periodical/Consolidated Statements. If they are submitted after, it must be before finalization. Full-service or mixed service mailings cannot be finalized until all pieces are submitted via the MailPieceCreateRequest messages. All piece counts must match between the MailPieceCreateRequest, Postage/Periodical/Consolidated Statements and QualificationReportSummaryCreateRequest/QualificationReportDetailCreateRequest messages.

  Note: *The MailXMLPieceRangeBlock and PDRRangePieceBlock blocks inside the mailPieceRequest block have been removed, instead utilize the PDRMailPieceBlock and MailPieceBlockGroup blocks.*

- The MailPieceCreateRquestcan be broken into multiple messages when the piece count is over 40,000 pieces. To break the message into multiple parts and link them together the Attribute block "LargeTransactionDividerGroupOptionalType" can be utilized with the following fields:
  - MessageGroupID
  - TotalMessageCount
  - MessageSerialNumber

Copyright © 2014 USPS®. All Rights Reserved

- TransmittedRecordCount
- TotalRecordCount
- TotalRecordsAcrossMessages
- LastMessage

3.34.1 MailPieceCreateRequest Data Structure

Mail.XML 13.0B- MailPieceCreateRequest				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
MailPieceCreateRequest Message BEGINS				
LargeTransactionDividerGroupOptionalType	LargeTransactionDividerGroupOptionalType attribute		Not Currently Supported	Refer this attribute in Section 7
MailXMLHeaderInfo	MailXMLHeaderInfo attribute		Required	Refer this attribute in Section 7
SubmittingParty Block	ParticipantIDType		Required block; Identifies the customer submitting the message	Refer 'ParticipantIDType' complex type in Section 7.
SubmittingSoftware Block	SubmittingSoftwareType		Required block; Identifies the software submitting the message	Refer 'SubmittingSoftware' complex type in Section 7.
Choice Block BEGINS			Required Either Sequence Block 1 or Sequence Block 2 is required.	
Sequence Block 1 BEGINS				
UserLicenseCode	Mailxml_base:userLicenseCodeType		Field not being supported	Refer Section 5
MaildatJobID	Mailxml_base:jobIDType		Field not being supported	Refer Section 5
TransmittedCount	69onnegative Integer		Optional	
Choice Block BEGINS			Either PDRMailPIeceBlock or PDRRangePieceBlock or PieceLiteRecord block	Currently this block is not supported
PDRMailPieceBlock			Block not being supported	
PDRRangePieceBlock			Block not being supported	
PieceBarcodeRecord Block	PieceBarcodeRecord BlockType complex type	-	Required if provided 1 to many allowed	Refer to this complex type in Section 4
Choice Block ENDS				
Sequence Block 1 ENDS				
Sequence Block 2 BEGINS				
CustomerGroupID	String, 25 characters		Required field; must be populated with the same value as the CustomerGroupID in the	

Copyright © 2014 USPS®. All Rights Reserved

Mail.XML 13.0B- MailPieceCreateRequest				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
			QualificationReportCreateResponse message	
MailingGroupID	Non-negative Integer		Required field; must be populated with the same value as the MailingGroupID in the QualificationReportCreateResponse message	
TransmittedCount	Non-negative Integer		Optional Count of records transmitted in message	
Choice Block BEGINS			Either MailPieceBlockGroup or MailXMLPieceRange Block or PieceLiteRecord block	
MailPieceBlockGroup	MailPieceBlockGroup Type complex type	-	Required. 1 to many	Refer to this complex type in Section 4
MailXMLPieceRange Block	MailXMLPieceRange BlockType complex type	-	Block not being supported	Refer to this complex type in Section 4
MailXMLPieceBarcodeRecord	PieceBarcodeRecord BlockForMailXMLType complex type	-	Required 1 to many allowed	Refer to this complex type in Section 4
Choice Block ENDS				
Sequence Block 2 ENDS				
MailPieceCreateRequest Message ENDS				

3.35 MailPieceCreateResponse

Purpose

Accept or reject a request to create a mailpiece or piece range

Error/Return Codes

Refer Section 8 to view shared error/return codes and also a list of error/return codes tied this message.

Business Rules

- Will accept if all required fields are populated and values are valid
- Will reject if all required fields are not populated
- Will reject if invalid values are provided
- Will reject if FullServiceParticipationIndicator is NOT F for Full-Service or M for Mixed Service
- Mail Pieces and piece ranges for a specified MailingGroupID and CustomerGroupID must have an accepted QualificationReportDetailCreateRequest and BundleDetailCreatRequest
- The ReturnInfo block will have a description for rejection

3.35.1 MailPieceCreateResponse Data Structure

Copyright © 2014 USPS®. All Rights Reserved

Mail.XML 13.0B- MailPieceCreateResponse				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
MailPieceCreateResponse BEGINS				
TrackingID	String 12	-	Optional	Allow mailers to re-query the message using this ID in MRRR message.
SubmitterTrackingID	String 20		Required	
ConsigneeTrackingID	mailxml_base:s20		Optional	
Choice Block BEGINS			Required Either accept or reject block is returned.	
MailPieceCreateAccept Block begins			Block received upon accepting request	
MailXMLHeaderInfo	MailXMLHeaderInfo attribute	-	Required	Refer this attribute in Section 7
ReturnInfo	basicReturnInfo complex type		Optional 1 to many allowed	Refer to this complex type in Section 4
MailPieceCreateAccept Block ends				
MailPieceCreateReject Block begins			Block received upon rejecting request Only one can be submitted	
MailXMLHeaderInfo	MailXMLHeaderInfo attribute	-	Required	Refer this attribute in Section 7
ReturnInfo	basicReturnInfo complex type		Required	Refer to this complex type in Section 4
MailPieceCreateReject Block ends				
Choice Block ENDS				
MailPIeceCreateResponse ENDS				

3.36 MailPieceUpdateRequest

Purpose

Used to update a previously created mailpiece or piece range

Business Rules

- Must be submitted to a currently existing mailpiece or piece range
- MailingGroupID and CustomerGroupID must exist for an open mailing
- The MailPieceBlock for the MailPieceUpdateRequest and MailPieceCreateRequest must be the same for the specified MailingGroupID and CustomerGroupID
- The MailXMLPieceRangeBlock for the MailPieceUpdateRequest and MailPieceCreateRequest must be the same for the specified MailingGroupID and CustomerGroupID
- Cannot update a mailpiece if the 'W' or 'S' indicators for WastedPieceIndicator have resulted in adjusting an already finalized postage statement
- Cannot update a mailpiece or piece range if postage has been finalized on its corresponding container
- The MailPieceUpdateRequest messages will be rejected where the sum of the MailXMLPieceRangeBlock IMbarcodeUpperSerialization minus the MailXMLPieceRangeBlocks IMbarcodeLowerSerialization plus 1 (one) for all Full-Service blocks within the mailing group is either:
    - 20% or more greater than the larger of either (1) the sum of the Pieces field for all full-service PieceRangeBlocks or (2) the sum of Copies field for all full-service PieceRangeBlocks, or

Copyright © 2014 USPS®. All Rights Reserved

- Less than the smaller of either (1) the sum of the Pieces field for all full-service PieceRangeBlocks or (2) the sum of Copies field for all full-service PieceRangeBlocks.

Note: *the MailXMLPieceRangeBlock and PDRRangePieceBlock blocks inside the mailPieceRequest block will be removed in the next major Mail.XML version. At this time it is strongly advised that milers stop using these two blocks, instead utilize the PDRMailPieceBlock and MailPieceBlockGroup blocks.*

3.36.1 MailPieceUpdateRequest Data Structure

Mail.XML 13.0B- MailPieceUpdateRequest				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
MailPieceUpdateRequest Message BEGINS				
MailXMLHeaderInfo	MailXMLHeaderInfo attribute	-	Required	Refer this attribute in Section 7
SubmittingParty	ParticipantIDType		Required block; Identifies the customer submitting the message	Refer to this complex type in Section 4
SubmittingSoftware	SubmittingSoftwareType		Required block; Identifies the software submitting the message	Refer to this complex type in Section 4
Choice Block BEGINS			Either Maildat or Mailxml blocks should be used.	
Sequence Block 1 BEGINS (Maildat submission)				
UserLicenseCode	userLicenseCodeType simple type		Field not being supported	Refer to this simple type in Section 5
MaildatJobID	jobIDType simple type		Field not being supported	Refer to this simple type in Section 5
TransmittedCount	nonnegative Integer		Optional	
Choice Block BEGINS			Either PDRMailPiece or PDRRangePiece or MailPieceID block or PieceRangeID	
PDRMailPieceBlock BEGINS			Block not being supported.	
PackageID	packageIDType simple type	-	Required	Refer to this simple type in Section 5
CQTDatabaseID	CQTDatabaseIDType simple type	-	Required	Refer to this simple type in Section 5
MailPieceBlock	mailPieceBlockTYpe complex type		Required	Refer to this complex type in Section 4
PDRMailPieceBlock ENDS				
PDRRangePieceBlock block BEGINS			Block not being supported	
DatabaseContainerID	databaseContainerID Type simple type	-	Required	Refer to this simple type in Section 5
PieceRangeBlock BEGINS			Required	

Copyright © 2014 USPS®. All Rights Reserved

Mail.XML 13.0B- MailPieceUpdateRequest				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
PieceRangeID	String 22	-	Required	-
IMbarcodeLowerSerialization block begins				
MailerID6	mailerID6Type		Required	Refer to this simple type in Section 5
SerialNumber9	iMBSerialNumber9Type		Required	Refer to this simple type in Section 5
OR				
MailerID9	mailerID9Type		Required	Refer to this simple type in Section 5
SerialNumber6	iMBSerialNumber6Type		Required	Refer to this simple type in Section 5
IMbarcodeLowerSerialization block ends				
IMBarcodeUpperSerialization block begins				
MailderID6	mailerID6Type		Required	Refer to this simple type in Section 5
SerialNumber9	iMBSerialNumber9Type		Required	Refer to this simple type in Section 5
OR				
MailerID9	mailerID9Type		Required	Refer to this simple type in Section 5
SerialNumber6	iMBSerialNumber6Type		Required	Refer to this simple type in Section 5
IMBarcodeUpperSerialization block ends				
MailPreparer	ParticipantIDType			See Section 7 for Details
MailOwner	ParticipantIDType			See Section 7 for Details
Choice Block BEGINS			Required. ServiceCode or MailClass	
ServiceTypeCode	ServiceTypeCodeType simple type		Required	Refer to this simple type in Section 5
MailClass	mailClassType simple type		Required	Refer to this simple type in Section 5
Choice Block ENDS				
ServiceLevelIndicator	ServiceLevelIndicatorType simple type		Required	Refer to this simple type in Section 5
Pieces	nonNegative Integer		Required 1 to many allowed	
Copies	nonNegative Integer		Required 1 to many allowed	
PieceRangeBlockType ENDS				
PDRRangePieceBlock ENDS				
PieceBarcodeRecordBlock	PieceBarcodeRecordBlockType complex type	-	Required 1 to many allowed	Refer to this complex type in Section 4
Choice Block END				

Copyright © 2014 USPS®. All Rights Reserved

Mail.XML 13.0B- MailPieceUpdateRequest				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
Sequence Block 1 ENDS (Maildat Submission)				
Sequence Block 2 BEGINS (MailXML Submission)				
CustomerGroupID	String, 25 characters		Required field; must be populated with the same value as the CustomerGroupID in the MailPieceCreateResponse message	
MailingGroupID	Non-negative Integer		Required field; must be populated with the same value as the MailingGroupID in the MailPieceCreateResponse message	
TransmittedCount	Non-negative Integer		Not required Count of records transmitted in message	
Choice Block BEGINS				
MailPieceBlockGroup	MailPieceBlockGroupType complex type		1 to many can be submitted Either MailPieceBlock or MailXMLPieceRange Block submitted	Refer to this complex type in Section 4
MailXMLPieceRange Block	MailXMLPieceRangeBlockType complex type	-	Block not being supported.	Refer to this complex type in Section 4
MailXMLPieceBarcodeRecord	PieceBarcodeRecordBlockForMailXMLType complex type	-	Required. 1 to many allowed	Refer to this complex type in Section 4
Choice Block ENDS				
Sequence Block 2 ENDS (MailXML Submission)				
MailPieceCancelRequest Message ENDS				

3.37 MailPieceUpdateResponse

Purpose

Accept or reject a request to update a mailpiece or piece range

Error/Return Codes

Refer Section 8 to view shared error/return codes and also a list of error/return codes tied this message.

Business Rules

- Will accept if the mailpiece or piece range exists
- Will accept if postage statement is USPS Processing Due
- Will reject if the mailpiece or piece range does not exist

Copyright © 2014 USPS®. All Rights Reserved

- Will reject if a mailpiece 'W' or 'S' indicators for WastedPieceIndicator have resulted in adjusting an already finalized postage statement
- Will reject if postage statement is finalized or finalized pending payment on the mailpiece or piece range's corresponding container
- The ReturnInfo block will have a description for rejection

3.37.1 MailPieceUpdateResponse Data Structure

Mail.XML 13.0B- MailPieceUpdateResponse				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
MailPieceUpdateResponse BEGINS				
TrackingID	String 12	-	Optional	Allow mailers to re-query the message using this ID in MRRR Message.
SubmitterTrackingID	String 20		Required	
Choice Block BEGINS			Required. Either Accept or Reject block is returned.	
MailPieceUpdateAccept Block BEGINS			Block received upon accepting request	
MailXMLHeaderInfo	MailXMLHeaderInfo attribute	-	Required	Refer this attribute in Section 7
ReturnInfo	basicReturnInfo complex type		Optional	Refer to this complex type in Section 4
MailPieceUpdateAccept Block ENDS				
MailPieceUpdateReject Block BEGINS			Block received upon rejecting request	
MailXMLHeaderInfo	MailXMLHeaderInfo attribute	-	Required	Refer this attribute in Section 7
ReturnInfo	basicReturnInfo complex type		Required	Refer to this complex type in Section 4
MailPieceUpdateReject Block ENDS				

3.38 OpenMailingGroupRequest

Purpose

Allows USPS customers to create mailing groups to submit qualification report, mailpiece, and postage statement information.

Business Rules

- Must be submitted before all other messages for eDoc with the exception of SiblingContainerCreate or ContainerUpdate message
- Multiple mailing groups can be opened for a distinct SubmitterCRID, Permit Number or Publication Number, PostOfficeOfMailingZip, MailingFacility, and MailXMLPresentationCategory
- The dashboard will not display empty mailing groups
- Letters and Flats can both be part of the same mailing group but both require separate postage statements by shape.

3.38.1 OpenMailingGroupRequest Data Structure

Mail.XML 13.0B- OpenMailingGroupRequest				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**

Copyright © 2014 USPS®. All Rights Reserved

Mail.XML 13.0B- OpenMailingGroupRequest				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
OpenMailingGroupRequest BEGINS				
MailXMLOpenMailGroupRequestHeaderInfo	MailXMLOpenMailGroupRequestHeaderInfo attribute		Required	Refer this attribute in Section 7
SubmittingParty	ParticipantIDType complex type		Required block; Identifies the customer submitting the message	Refer to this complex type in Section 4
SubmittingSoftware	SubmittingSoftwareType complex type		Required block; Identifies the software submitting the message	Refer to this complex type in Section 4
SubmitterTrackingID	String 20		Required	
MailingGroupData	MailingGroupDataType complex type		Provides the basic information for the mailing group Only one must be submitted with OpenMailingGroupRequest message	Refer to this complex type in Section 4
OpenMailingGroupRequest ENDS				

3.39 OpenMailingGroupResponse

Purpose

The OpenMailingGroupResponse will be used by USPS to notify the customer if their request to open a mailing group has been accepted or rejected.

Error/Return Codes

Refer Section 8 to view shared error/return codes, Cross message validations, and a list of error/return codes tied this message.

Business Rules

- Will reject if invalid values are provided in the request
- Will reject if MailingGroupData required data does not exist in database
- The ReturnInfo block will have a description for rejection

3.39.1 OpenMailingGroupResponse Data Structure

Mail.XML 13.0B- OpenMailingGroupResponse				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
OpenMailingGroupResponse BEGINS				
TrackingID	String 12	-	Optional	Allow mailers to re-query the message using this ID in MRRR message.
SubmitterTrackingID	String 20		Required	

Copyright © 2014 USPS®. All Rights Reserved

Mail.XML 13.0B- OpenMailingGroupResponse				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
Choice Block BEGINS			Required Either Accept or Reject block is returned.	
OpenMailingGroupAccept Block BEGINS			Block received upon accepting request	
MailXMLOpenMailGroupResponseAcceptHeaderInfo	MailXMLOpenMailGroupResponseAcceptHeaderInfo attribute		Required	Refer this attribute in Section 7
ReturnInfo	basicReturnInfo complex type	-	Optional	Refer to this complex type in Section 4
OpenMailingGroupAccept Block ENDS				
OpenMailingGroupReject Block BEGINS			Block received upon rejecting request	
MailXMLOpenMailGroupResponseRejectHeaderInfo	MailXMLOpenMailGroupResponseRejectHeaderInfo attribute	-	Required	Refer this attribute in Section 7
Sequence Block BEGINS				
PostOfficeOfMailingZip	Exact String 5	-	Required	-
ReturnInfo				
Sequence Block ENDS				
OpenMailingGroupReject block ENDS				
Choice Block ENDS				
OpenMailingGroupResponse ENDS				

3.40 PeriodicalStatementCreateRequest

Purpose

Allows the USPS customer to submit a Periodicals postage statement to a mailing group

Business Rules

- Mail owner or preparer must send the OpenMailingGroupRequest message and open a mailing group successfully (receive a MailingGroupID) in an acceptance message before sending this message
- Mail owner or preparer must send the QualificationReportDetailCreateRequest message and receive an accepted response that the mailing is qualified before sending this message
- Mail owner or preparer must send the ContainerBundleReportCreateRequest message and receive an accept response before sending this message
- Mail owner or preparer must send this message before sending the ConsolidatedPeriodicalStatementRequest message

Copyright © 2014 USPS®. All Rights Reserved

- For full-service or mixed service mailings, there are two options for how to populate the container information.
  - PeriodicalLineItemData block
    - Include one PeriodicalLineItemData block for each container represented on each line of the postage statement. ContainerID and ContainerDetailID must exist from a previously submitted qualification report.
    -
    - Do not include ContainerPostage block. If provided, it will be ignored.
  - ContainerPostage block
    - All containers are represented in the ContainerPostage blocks with the number of pieces and copies for each container. The container IDs must match an ID of a container from a previously submitted qualification report.
    - Do not provide Container IDs in the LineItemData blocks. Lines could potentially then be collapsed together as they would not need to be broken out by container. (If any Container ID is provided, the Container Postage block will be disregarded).

  Notes: *Parent and sibling containers do not need to be represented.*
  Any full-service or mixed service container that is not represented will not be sent to SASP and will not receive full-service feedback. Per January 2014 requirements version 15.0A container information is to be populated using the PeriodicalLineItemData block.

- For full-service and mixed service mailings, ContainerID and ContainerDetailID in the PeriodicalLineItemData block or ContainerID in the ContainerPostage block in the postage statement message must exist in a previously submitted QualificationReportDetailCreateRequest message.
- For full-service and mixed service mailings, ContainerID and ContainerDetailID in the PeriodicalLineItemData block or ContainerID in the ContainerPostage block in the postage statement message must exist in a MailPieceCreateRequest message submitted either before or after the Postage Statement.
- For full-service and mixed service mailings, the total number of pieces associated to a ContainerDetailID in the postage statement message must be equal to the number of pieces for that ContainerDetailID in the QualificationReportDetailCreateRequest message.
- For full-service and mixed service mailings, the total number of pieces associated to a ContainerDetailID in the QualificationReportDetailCreateRequest message must match the total number of pieces per ContainerDetailID in the MailPieceCreateRequest message.
- ContainerDetailID must be unique and can only be submitted on one postage statement across the mailing group and must account for all associated mailpieces.
- Firm Bundles and Addressed Supplements;
  - For a mailing that includes neither Addressed Supplements nor Firm Bundles, the number of copies must equal the number of pieces
  - For a mailing including Firm Bundles and no Addressed Supplements, the number of pieces cannot exceed the number of copies
  - For a mailing including Addressed Supplements and no Firm Bundles, the number of copies cannot exceed the number of pieces
  - The number of In-County Copies and Outside-County Copies must match between Piece and Pound postage lines.
  - The sum of InCountyAddressedSupplementPieces, OutsideCountyAddressedSupplementPieces, and PiecesExcludingAddressedSupplmentPieces must equal the total pieces submitted
  - The number of InCountyAddressedSupplementPieces and OutsideCountyAddressedSupplementPieces cannot exceed the number of In-County and Outside-County pieces, respectively
- The system will support government Inside-County Periodical and Pending Periodical mailings.
- Rate Categories AF, BF, DF, GF, and KF are not supported for First-Class Mail, Standard Mail, or Periodicals.
- The number of pieces must equal the number of copies when the mailing does not include Firm Bundles or Addressed Supplements and InOutCountyIndicator is N.

Copyright © 2014 USPS®. All Rights Reserved

- The number of pieces must be less than or equal to the number of copies when the mailing includes Firm Bundles but does not have any Addressed Supplements and InOutCountyIndicator is N.
- The number of pieces must be greater than or equal to the number of copies when the mailing includes Addressed Supplements but does not have Firm Bundles and InOutCountyIndicator is N.

***Note**: Important information on combined and consolidated postage statements:*

Part A – Currently, the Mail.XML specs allows the user to provide different data for the fields listed in Part C below for each postage statement request. During a Combined Mailing Request or during a Consolidated Periodical Postage Statement Request, the values of these fields (listed in Part C) have to be same from a business and processing stand-point. The current implementation of Mail.XML does not provide a feature where the user could supply this data for all of the postage statements that are consolidated or combined. A future release of Mail.XML and *PostalOne!* will cater to this requirement where the user will be required to provide with only one set of data (listed in Part C) for the whole message set of combined or consolidated postage statements. However, in the current implementation, USPS recommends all users to follow the set of instructions provided in section.

Part B – For the following set of postage statement message requests, follow the instructions documented in Part C below.

- BeginCombinedMailingRequest
- EndCombinedMailingRequest
- ConsolidatedPeriodicalStatementCreateRequest
- PeriodicalStatementCreateRequest
- PostageStatementCreateRequest

Part C – For all of the postage statement create requests (items 3, 4, and 5 from above), during a Combined Mailing request (meaning postage statements enclosed in between items 1 and 2 from above) and for ConsolidatedPeriodicalStatementCreateRequest user must provide the same values inside all of the postage statements for the following fields.

- IssueDate
- IssueNumber
- VolumeNumber
- CustomerReferenceID
- AgencyCostCode
- PermitPublicationData (block of PermitHolderData block)
- PostagePaymentMethod
- RateType
- ProcessingCategory
- Apply an outside county container charge on all physical pallets or physical trays split across associated PeriodicalLineItemData blocks in a mailing when the following conditions are met:
  - InOutCountyIndicator is set to ‘N’.
    - Option 1: The data provided for Container postage detail (containerPostageType) shall be used to validate the charges for Periodical postage.
    - Option 2: ContainerInfoData block shall be used to validate the charges for Periodical postage.
    - Option 3: when InOutCountyIndicator is provided. The InOutCountyIndicator set to N shall be combined with the Pieces and Containers to validate the charges for Periodical postage
  - Apply option 1, option 2, or option 3 to validate and calculate the charges for Consolidated Periodical postages.

3.40.1 PeriodicalStatementCreateRequest Data Structure

Mail.XML 13.0B- PeriodicalStatementCreateRequest

Copyright © 2014 USPS®. All Rights Reserved

Field	Format	Acceptable Values	Business Rules	Comments
PeriodicalStatementCreateRequest Message BEGINS				
MailXMLPostageStatementRequestHeaderInfo	MailXMLPostageStatementRequestHeaderInfo attribute	-	Required	Refer this attribute in Section 7
SubmittingParty	ParticipantIDType complex type		Required block; Identifies the customer submitting the message	Refer to this complex type in Section 4
SubmittingSoftware	SubmittingSoftwareType complex type		Required block; Identifies the software submitting the message	Refer to this complex type in Section 4
SubmitterTrackingID	String 20		Required	
CreatePeriodicalStatement	createPeriodicalStatementType complex type	-	Required block; contains data critical to postage statement calculation	Refer to this complex type in Section 4
PeriodicalStatementCreateRequest Message ENDS				

3.41 PeriodicalStatementCreateResponse

Purpose

Response to the customer's request to create a Periodical Postage Statement

Error/Return Codes

Refer Section 8 to view shared error/return codes and also a list of error/return codes tied this message.

Business Rules

Message will be sent in response to and must follow the PeriodicalStatementCreateRequest

3.41.1 PeriodicalStatementCreateResponse Data Structure

Mail.XML 13.0B- PeriodicalStatementCreateResponse				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
PeriodicalStatementCreateResponse BEGINS				
TrackingID	String 12	-	Optional	Allow mailers to retrieve the data without actually resending the message by using this ID in MRRR message.
SubmitterTrackingID	String 20		Required	
Choice Block BEGINS			Required Either Accept or Reject block is returned.	
PeriodicalStatementCreateAccept block begins			Response from USPS indicating that the PeriodicalStatementCreateRequest message was	

Copyright © 2014 USPS®. All Rights Reserved

Mail.XML 13.0B- PeriodicalStatementCreateResponse				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
			accepted and a Periodical Postage Statement was created (choice between StatementID, UserPostageStatementID, TotalPostage, TotalPostageDue, and ReturnInfo block or TrackingID and ReturnInfo block)	
MailXMLPostageStatementResponseHeaderInfo	MailXMLPostageStatementResponseHeaderInfo attribute		Required	Refer this attribute in Section 7
StatementID	Non-negative integer		Required field	
UserPostageStatementID	String, 10 characters		Optional field	
TotalPostage	Double		Required field, two decimal points provided. If not generated for Statement ID there will be a reject block.	
TotalPostageDue	Double		Required field, may be zero, two decimal points provided. If not generated for Statement ID there will be a reject block.	
VolumeNumber	String 5	-	Optional	-
IssueNumber	String 6	-	Optional	-
ReturnInfo	basicReturnInfo complex type		Optional block; paired with StatementID, UserPostageStatementID, TotalPostage, and TotalPostageDue	Refer to this complex type in Section 4
PeriodicalStatementCreateAccept block ends				
PeriodicalStatementCreateReject block BEGINS			Response from USPS indicating that the PeriodicalStatementCreateRequest message was rejected and a Periodical Postage Statement was not created and the reason why	
MailXMLPostageStatementResponseHeaderInfo	MailXMLPostageStatementResponseHeaderInfo attribute block	-	Required	Refer this attribute in Section 7
ReturnInfo	basicReturnInfo complex type	-	Required block	Refer to this complex type in Section 4
PeriodicalStatementC				

Copyright © 2014 USPS®. All Rights Reserved

Mail.XML 13.0B- PeriodicalStatementCreateResponse				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
reateReject block ends				
Choice Block ENDS				
PeriodicalStatementCreateResponse ENDS				

3.42 PeriodicalStatementQueryRequest

Purpose

Allows the USPS customer to retrieve a Periodicals postage statement

Business Rules

Must be submitted after a periodical postage statement has been created (after the PeriodicalStatementCreateRequest message has been accepted)

3.42.1 PeriodicalStatementQueryRequest Data Structure

Mail.XML 13.0B- PeriodicalStatementQueryRequest				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
PeriodicalStatementQueryRequest BEGINS				
MailXMLPostageStatementRequestHeaderInfo	MailXMLPostageStatementRequestHeaderInfo attribute	-	Required	Refer this attribute in Section 7
SubmittingParty	ParticipantIDType complex type		Required block; Identifies the customer submitting the message	Refer to this complex type in Section 4
SubmittingSoftware	SubmittingSoftwareType complex type		Required block; Identifies the software submitting the message	Refer to this complex type in Section 4
SubmitterTrackingID	String 20		Required	
Choice Block BEGINS			Either Statement ID or IncludedChildStatement is required	
StatementID	Non-negative integer		Required field	
IncludeChildStatement	yesNo	Yes/No	Required field, if No only the requested Statement ID is returned. If Yes, the statement ID requested and its child statements are returned.	
Choice Block ENDS				
PeriodicalStatementQueryRequest ENDS				

3.43 PeriodicalStatementQueryResponse

Purpose

Return either the postage statement query results data or the reason why there was a query error

Error/Return Codes

Refer Section 8 to view shared error/return codes and also a list of error/return codes tied this message.

Copyright © 2014 USPS®. All Rights Reserved

Business Rules

- Will accept if StatementID or TrackingID exists
- Will reject if StatementID or TrackingID does not exist
- The ReturnInfo block will have a description for a QueryError

3.43.1 PeriodicalStatementQueryResponse Data Structure

Mail.XML 13.0B- PeriodicalStatementQueryResponse				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
PeriodicalStatementQueryResponse BEGINS				
MailXMLPostageStatementResponseHeaderInfo	MailXMLPostageStatementResponseHeaderInfo attribute		Required	Refer this attribute in Section 7
Sequence Block BEGINS				
TrackingID	String, 12	-	Optional. Provides the Tracking ID when message fails to get delivered	Allow mailers to retrieve the data without re-query the message by using this ID in MRRR Message.
SubmitterTrackingID	String 20		Required	
Choice Block BEGINS			Required Either QueryResult or QueryError is returned.	
QueryResults block BEGINS			Required block; accepting the query request message and returning the query for a successful PeriodicalStatementQueryRequest message	
PeriodicalStatementData	PeriodicalStatementDataType complex type	-	Required	Refer to this complex type in Section 4
ReturnInfo	basicReturnInfoType complex type		Optional block	Refer to this complex type in Section 4
QueryResults block ENDS				
QueryError block BEGINS			Required block if there are any failed validations in the PeriodicalStatementQueryRequest message or when the query data cannot be provided	
ReturnInfo	basicReturnInfoType		Required block	Refer to this complex type in Section 4
QueryError block ENDS				
Choice Block ENDS				
PeriodicalStatementQueryResponse ENDS				

Copyright © 2014 USPS®. All Rights Reserved

3.44 PostageStatementCancelRequest

Purpose

Allows the USPS customer to cancel a submitted postage statement (including a Periodicals statement) that has not already been reversed or finalized

Business Rules

- Must be submitted after a postage statement has been created (PeriodicalStatementCreateResponse or PostageStatementCreateResponse indicates accepted)
- Will not be accepted after a postage statement has been finalized (PostageStatementStatus is FIN or FPP.)
- All postage statements in a mailing group is cancelled if a StatementID is not submitted
- First-Class Commercial Plus Parcels will be accepted when the following conditions are met:
  - FormType in the CreatePostageStatement block is FC (First-Class)
  - PresentationCategory in the CreatePostageStatement block is PF (Parcel, First-Class)
  - PriceType in the CreatePostageStatement block is commercialplus

3.44.1 PostageStatementCancelRequest Data Structure

Mail.XML 13.0B- PostageStatementCancelRequest				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
PostageStatementCancelRequest BEGINS				
MailXMLPostageStatementRequestHeaderInfo	MailXMLPostageStatementRequestHeaderInfo attribute	-	Required	Refer this attribute in Section 7
SubmittingParty	ParticipantIDType complex type		Required block; Identifies the customer submitting the message	Refer to this complex type in Section 4
SubmittingSoftware	SubmittingSoftwareType complex type		Required block; Identifies the software submitting the message	Refer to this complex type in Section 4
SubmitterTrackingID	String 20		Required	
StatementID	Non-negative Integer		Optional. *PostalOne!* assigned postage statement ID Optional	
PostageStatementCancelRequest ENDS				

3.45 PostageStatementCancelResponse

Purpose

Accept or reject a request to cancel postage statement (including a periodical statement)

Error/Return Codes

Refer Section 8 to view shared error/return codes and also a list of error/return codes tied this message.

Business Rules

- Will accept if postage statements exist in the mailing group and postage is not finalized
- Will reject if postage statements do not exist in the mailing group or the StatementID requested does not exist.
- Will reject if postage is finalized (PostageStatementStatus is FIN or FPP.)
- The ReturnInfo block will have a description for rejection

3.45.1 PostageStatementCancelResponse Data Structure

Copyright © 2014 USPS®. All Rights Reserved

Mail.XML 13.0B- PostageStatementCancelResponse				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
PostageStatementCancelResponse BEGINS				
TrackingID	String 12	-	Optional	Allow mailers to retrieve the data without re-query the message by using this ID in MRRR Message.
SubmitterTrackingID	String 20		Required	
Choice Block BEGINS			Required Either Accept or Reject block is returned.	
PostageStatementCancelAccept Block BEGINS			Block received upon accepting request	
MailXMLMsgResponseHeaderInfo	MailXMLMsgResponseHeaderInfo attribute		Required	Refer this attribute in Section 7
UserPostageStatementID	String, 10 characters		Optional. User created postage statement ID	
StatementID	Non-negative Integer		Required. *PostalOne!* assigned postage statement ID	
PostageStatementCancelAccept Block ENDS				
PostageStatementCancelReject Block BEGINS				
MailXMLMsgResponseHeaderInfo	MailXMLMsgResponseHeaderInfo attribute	-	Required	Refer this attribute in Section 7
ReturnInfo	basicReturnInfoType complex type	-	Required. Provides reason for return Required Multiple pairings of ReturnCode and ReturnDescription can be provided in the block	Refer to this complex type in Section 4
PostageStatementCancelReject Block ends				
Choice Block ENDS				
PostageStatementCancelResponse ENDS				

3.46 PostageStatementCreateRequest

Purpose

Allows the USPS customer to submit a 3600-series postage statement to a mailing group. This message allows the customer to submit either the basic-form or extended-form of the 3600-series postage statement, in order to accommodate either singular or multiple entries for each line item, which allows the customer to submit non-identical piece weight mailings.

Copyright © 2014 USPS®. All Rights Reserved

Business Rules

- Must be submitted after all mailpieces or piece ranges are submitted for a mailing group
- Postage adjustments will be expected for postage statements with wasted or spoiled pieces
- The 'Section' and 'Line Number' elements will be corrected if an error is made in submitting
- The only instance where ‘Section’ and ‘Line Number’ will be taken as submitted (and not corrected/changed) is for the Full-Service discount lines. Otherwise, the full-service discount lines will be generated based on a FullServiceParticipationIndicator of ‘F’ in the PostageStatementLineItemData block.
- The PermitHolderforAPData block will be required for Postage Payment Method of 'S' or 'M' and cannot be a meter. It must be either an OI or PI permit.
- The FormType field cannot be 'PE' = Periodicals Class for a PostageStatementCreateRequest. In this case use the PeriodicalStatementCreateRequest message.
- For full-service or mixed service mailings, there are two options for how to populate the container information.
  - PostageStatementlLineItemData block
    - Include one PostageStatementLineItemData block for each container represented on each line of the postage statement. Version ID, ContainerID, and ContainerDetailID must exist from a previously submitted qualification report.
    - Do not include ContainerPostage block. If provided, it will be ignored.
  - ContainerPostage block
    - All containers are represented in the ContainerPostage blocks with the number of pieces and copies for each container. The container IDs must match an ID of a container from a previously submitted qualification report.
    - Do not provide Container IDs in the LineItemData blocks. Lines could potentially then be collapsed together as they would not need to be broken out by container. (If any Container ID is provided, the Container Postage block will be disregarded).

  Notes: *Parent and sibling containers do not need to be represented.*
  Any full-service or mixed service container that is not represented will not be sent to SASP and will not receive full-service feedback. Per January 2014 requirements version 15.0A container information is to be populated using the PostageStatementLineItemData block.
- For full-service and mixed service mailings, VersionID, ContainerID and ContainerDetailID in the PostageStatementLineItemData block or ContainerID in the ContainerPostage block in the postage statement message must exist in a previously submitted QualificationReportDetailCreateRequest message.
- For full-service and mixed service mailings, ContainerID and ContainerDetailID in the PostageStatementLineItemData block must or ContainerID in the ContainerPostage block in the postage statement message exist in a MailPieceCreateRequest message submitted either before or after the Postage Statement.
- For full-service and mixed service mailings, the total number of pieces associated to a ContainerDetailID in the postage statement message must be equal to the number of pieces for that ContainerDetailID in the QualificationReportDetailCreateRequest message.
- For full-service and mixed service mailings, the total number of pieces associated to a ContainerDetailID in the QualificationReportDetailCreateRequest message must match the total number of pieces per ContainerDetailID in the MailPieceCreateRequest message.
- For IMpb Non-Compliance processing of the ZIP+4 verification requires that the 9 digit ZIP+4 be provided as part of the MailPieceCreateRequest. The IMpb Non-Compliance processing excludes periodical parcels
- ContainerDetailID must be unique and can only be submitted on one postage statement across the mailing group and must account for all associated mailpieces.
- PublicationNumber cannot be populated in a PostageStatementCreateRequest message
- For MLOCR First-Class mailings claiming Single Piece prices, the PermitType in the PermitHolderData block in the PostageStatementCreateRequest message must be set to Permit Imprint (PI), Metered (MT), or PC (Precanceled Stamps). At least one SortationLevel in

Copyright © 2014 USPS®. All Rights Reserved

QualificationReportSummaryCreateRequest/QualificationReportDetailCreateRequest message must be set to "AN."

***NOTE**: Wherever SortationLevel is used, it is defined as Type=ContainerLevelType.*

- FormType PP for Package Services Parcel Post is not supported.
- Rate Categories AF, BF, DF, GF, and KF are not supported for First-Class Mail, Standard Mail, or Periodicals.
- First-Class Commercial Plus Parcels will be accepted when the following conditions are met:
  - FormType in the CreatePostageStatement block is FC (First-Class)
  - PresentationCategory in the CreatePostageStatement block is PF (Parcel, First-Class)
  - PriceType in the CreatePostageStatement block is commercialplus
- The following ServiceCode values will be supported for First-Class Commercial Plus Parcels:
  - CM – Certified Mail
  - COD – Collect on Delivery
  - COM – Certificate of Mailing
  - DC – USPS Tracking
  - IM – Insured Mail
  - RD – Restricted Delivery
  - RR – Return Receipt
  - RRE – Return Receipt Electronic
  - SC – Signature Confirmation
  - SH – Special Handling
- *PostalOne!* Mail.XML will utilize the SimplifiedAddressIndicator to support EDDM for Standard Mail flats, Irregular Parcels, and BPM Flats.

***Note** - Important information on combined and consolidated postage statements:*

Part A – Currently, the Mail.XML specs allows the user to provide different data for the fields listed in Part C below for each postage statement request. During a Combined Mailing Request or during a Consolidated Periodical Postage Statement Request, the values of these fields (listed in Part C) have to be same from a business and processing stand-point. The current implementation of Mail.XML does not provide a feature where the user could supply this data for all of the postage statements that are consolidated or combined. A future release of Mail.XML and the *PostalOne!* system will cater to this requirement where the user will be required to provide with only one set of data (listed in Part C) for the whole message set of combined or consolidated postage statements. However, in the current implementation, USPS recommends all users to follow the set of instructions provided in section.

Part B – For the following set of postage statement message requests, follow the instructions documented in Part C below.

1. BeginCombinedMailingRequest
2. EndCombinedMailingRequest
3. ConsolidatedPeriodicalStatementCreateRequest
4. PeriodicalStatementCreateRequest
5. PostageStatementCreateRequest

Part C – For all of the postage statement create requests (items 3, 4, and 5 from above), during a Combined Mailing request (meaning postage statements enclosed in between items 1 and 2 from above) and for ConsolidatedPeriodicalStatementCreateRequest user must provide the same values inside all of the postage statements for the following fields.

IssueDate
IssueNumber
VolumeNumber
CustomerReferenceID

Copyright © 2014 USPS®. All Rights Reserved

AgencyCostCode
PermitPublicationData *(block of PermitHolderData block)*
PostagePaymentMethod
RateType
ProcessingCategory

3.46.1 PostageStatementCreateRequest Data Structure

Mail.XML 13.0B- PostageStatementCreateRequest				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
PostageStatementCreateRequest BEGINS				
MailXMLPostageStatementRequestHeaderInfo	MailXMLPostageStatementRequestHeaderInfo attribute	-	Required	Refer this attribute in Section 7
SubmittingParty	ParticipantIDType complex type	-	Required block; Identifies the customer submitting the message	Refer to this complex type in Section 4
SubmittingSoftware	SubmittingSoftwareType complex type		Required block; Identifies the software submitting the message	Refer to this complex type in Section 4
SubmitterTrackingID	String 20		Required	
CreatePostageStatment	CreatePostageStatementType complex type		Required Only one can be submitted	Refer to this complex type in Section 4
PostageStatementCreateRequest ENDS				

3.47 PostageStatementCreateResponse

Purpose

The PostageStatementCreateResponse will be used by USPS to notify the customer if their request to submit a 3600-series postage statement to a mailing group has been accepted or rejected.

Error/Return Codes

Refer Section 8 to view shared error/return codes and also a list of error/return codes tied this message.

Business Rules

- Will accept if all required fields are provided and values are valid
- Will reject if a required field is not provided
- Will reject if a value provided is invalid
- Will reject if not all pieces are accounted for from submitted mailpieces or piece ranges
- Will reject if FormType is 'PE' for Periodicals
- Will reject if PostagePaymentMethod is 'S' or 'M' and PermitHolderForAPData Block is not provided
- The ReturnInfo block will have a description for rejection

3.47.1 PostageStatementCreateResponse Data Structure

Mail.XML 13.0B- PostageStatementCreateResponse				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
PostageStatementCreateResponse BEGINS				
TrackingID	String 12	-	Optional	Allow mailers to retrieve data without re-query the message

Copyright © 2014 USPS®. All Rights Reserved

Mail.XML 13.0B- PostageStatementCreateResponse				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
				by using this ID in MRRR message.
SubmitterTrackingID	String 20		Required	
Choice Block BEGINS			Required. Either accept or Reject block is returned.	
PostageStatementCreateAccept Block BEGINS			Either StatementID, UserPostageStatementID, TotalPostage, TotalPostageDue and ReturnInfo Block group or TrackingID and ReturnInfo Block group is submitted in the PostageStatementCreateAccept Block	
MailXMLPostageStatementResponseHeaderInfo	MailXMLPostageStatementResponseHeaderInfo attribute		Required	Refer this attribute in Section 7
StatementID	Non-negative Integer		Required field; paired with UserPostageStatementID, TotalPostage, TotalPostageDue, and ReturnInfo block	
UserPostageStatementID	String, 10 characters		Optional field; paired with StatementID, TotalPostage, TotalPostageDue, and ReturnInfo block	
TotalPostage	Double		Two decimals Required field; paired with StatementID, UserPostageStatementID, TotalPostageDue, and ReturnInfo block	
TotalPostageDue	Double		Required field; paired with StatementID, UserPostageStatementID, TotalPostage and ReturnInfo block	
ReturnInfo	basicReturnInfoType		Optional block; paired with StatementID, UserPostageStatementID, TotalPostage, and TotalPostageDue	Refer to this complex type in Section 4
PostageStatementCreateAccept Block ENDS				
PostageStatementCreateReject Block BEGINS			Response from USPS indicating that the PostageStatementCreateRequest	

Copyright © 2014 USPS®. All Rights Reserved

Mail.XML 13.0B- PostageStatementCreateResponse				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
			message was rejected and a Postage Statement was not created and the reason why	
MailXMLPostageStatementResponseHeaderInfo	MailXMLPostageStatementResponseHeaderInfo attribute	-	Required	Refer this attribute in Section 7
ReturnInfo	basicReturnInfoType complex type	-	Required. Provides reason for return Required Multiple pairings of ReturnCode and ReturnDescription can be provided in the block	Refer to this complex type in Section 4
PostageStatementCreateReject Block ENDS				
Choice Block ENDS				
PostageStatementCreateResponse ENDS				

3.48 PostageStatementQueryRequest

Purpose

Used to query the status of a postage statement

Business Rules

- Must be submitted after a postage statement has been created
- First-Class Commercial Plus Parcels will be accepted when the following conditions are met:
  - FormType in the CreatePostageStatement block is FC (First-Class)
  - PresentationCategory in the CreatePostageStatement block is PF (Parcel, First-Class)
  - PriceType in the CreatePostageStatement block is commercial plus

3.48.1 PostageStatementQueryRequest Data Structure

Mail.XML 13.0B- PostageStatementQueryRequest				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
PostageStatementQueryRequest BEGINS				
MailXMLPostageStatementRequestHeaderInfo	MailXMLPostageStatementRequestHeaderInfo attribute		Required	Refer this attribute in Section 7
SubmittingParty	participantIDType complex type		Required block; Identifies the customer submitting the message	Refer to this complex type in Section 4
SubmittingSoftware	submittingSoftwareType complex type		Required block; Identifies the software submitting the message	Refer to this complex type in Section 4
SubmitterTrackingID	String 20		Required	
StatementID	Non-negative Integer		Required if the	

Copyright © 2014 USPS®. All Rights Reserved

Mail.XML 13.0B- PostageStatementQueryRequest				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
			TrackingID is not provided	
PostageStatementQueryRequest ENDS				

3.49 PostageStatementQueryResponse

Purpose

Accept or reject a request to create a combined mailing

Error/Return Codes

Refer Section 8 to view shared error/return codes and also a list of error/return codes tied this message.

Business Rules

- Will accept if PostageStatementID or TrackingID exists
- Will reject if PostageStatementID or TrackingID does not exist
- The ReturnInfo block will have a description for a Query Error

3.49.1 PostageStatementQueryResponse Data Structure

Mail.XML 13.0B- PostageStatementQueryResponse				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
PostageStateQueryResponse BEGINS				
MailXMLPostageStatementResponseHeaderInfo	MailXMLPostageStatementResponseHeaderInfo attribute		Required	Refer this attribute in Section 7
Sequence Block BEGINS				
TrackingID	String,12	-	Optional.	Allow mailers to retrieve the data without re-query the message by using this ID in MRRR Message
SubmitterTrackingID	String 20		Required	
Choice Block BEGINS			Required Either QueryResult or QueryError is returned.	
QueryResults Block BEGIN				
PostageStatementData	PostageStatementDataType complex type		Required. Only 1 occurrence	Refer to this complex type in Section 4
ReturnInfo	basicReturnInfoType complex type		Optional	Refer to this complex type in Section 4
QueryResults Block ENDS				
QueryError Block BEGINS				
ReturnInfo Block	basicReturnInfoType		Required. Provides reason for return Required Multiple pairings of ReturnCode and	Refer to this complex type in Section 4

Copyright © 2014 USPS®. All Rights Reserved

Mail.XML 13.0B- PostageStatementQueryResponse				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
			ReturnDescription can be provided in the block	
QueryError Block ENDS				
Choice Block ENDS				
Sequence Block ENDS				
PostageStatementQueryResponse ENDS				

3.50 PostageStatementStatusQueryRequest

Purpose

Used to query the status of a postage statement

Business Rules

- Must be submitted after a postage statement has been created
- First-Class Commercial Plus Parcels will be accepted when the following conditions are met:
  - FormType in the CreatePostageStatement block is FC (First-Class)
  - PresentationCategory in the CreatePostageStatement block is PF (Parcel, First-Class)
  - PriceType in the CreatePostageStatement block is commercialplus

3.50.1 PostageStatementStatusQueryRequest Data Structure

Mail.XML 13.0B- PostageStatementStatusQueryRequest				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
PostageStatementStatusQueryRequest BEGINS				
MailXMLDashboardHeaderInfo	MailXMLDashboardHeaderInfo attribute	-	Required	Refer this attribute in Section 7
SubmittingParty	participantIDType complex type		Required block; Identifies the customer submitting the message	Refer to this complex type in Section 4
SubmittingSoftware	submittingSoftwareType complex type		Required block; Identifies the software submitting the message	Refer to this complex type in Section 4
StatementID	Non-negative Integer		Required if the TrackingID is not provided	
IncludeChildStatement	yesNo	Yes, No	Optional, only used for Periodicals Consolidated postage statements. If yes, the child statements will be returned in the response, else child statements will not be returned.	
PostageStatementStatusQueryRequest ENDS				

Copyright © 2014 USPS®. All Rights Reserved

3.51 PostageStatementStatusQueryResponse

Purpose

Accept or reject a query for postage statement status

Error/Return Codes

Refer Section 8 to view shared error/return codes and also a list of error/return codes tied this message.

Business Rules

- Will accept if postage statement exists in the mailing group
- Will reject if postage statement does not exist in the mailing group
- The ReturnInfo block will have a description for a QueryError

3.51.1 PostageStatementStatusQueryResponse Data Structure

Mail.XML 13.0B- PostageStatementStatusQueryResponse				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
PostageStatementStatusQueryResponse BEGINS				
MailXMLDashboardHeaderInfo	MailXMLDashboardHeaderInfo attribute		Required	Refer this attribute in Section 7
TrackingID	String 12	-	Optional	Allow mailers to retrieve the data without re-query the message by using this ID in MRRR Message.
SubmitterTrackingID	String 20		Required	
Choice Block BEGINS			Required. Either QueryResults or QueryError block is returned.	
QueryResults Block BEGINS			1 to many allowed.	
PostageStatementSummary	PostageStatementSummaryType complex type		Required 1 to many can be submitted	Refer to this complex type in Section 4
ReturnInfo	basicReturnInfoType complex type		Provides reason for return Optional Multiple pairings of ReturnCode and ReturnDescription can be provided in the block	Refer to this complex type in Section 4
QueryResults Block ENDS				
QueryError Block BEGINS				
ReturnInfo	basicReturnInfo complex type		Provides reason for return Required Multiple pairings of ReturnCode and ReturnDescription can be provided in the block	Refer to this complex type in Section 4
QueryError Block ENDS				

Copyright © 2014 USPS®. All Rights Reserved

Mail.XML 13.0B- PostageStatementStatusQueryResponse				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
Choice Block ENDS				
PostageStatementStatusQueryResponse ENDS				

3.52 QualificationReportCreateRequest

3.52.1 QualificationReportCreateRequest Data Structure

Mail.XML 13.0B- QualificationReportDetailCreateRequest				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
QualificationReportDetailCreateRequest BEGINS				
complexType BEGINS				
sequence BEGINS				
SubmittingParty	mailxml_defs:participantIDType			
SubmittingSoftware	mailxml_defs:submittingSoftwareType			
SubmitterTrackingID	mailxml_base:s20		Optional	
OnePassPlannedOrActualFlag	mailxml_base:onePassPlannedOrActualFlagType		Optional	
QualificationReport	mailxml_mm:qualificationReportDataType			
sequence ENDS				
MailXMLQualReportRequestHeaderInfo	mailxml_mm:MailXMLQualReportRequestHeaderInfo			
complexType ENDS				
QualificationReportDetailCreateRequest ENDS				

3.53 QualificationReportCreateResponse

3.53.1 QualificationReportCreateResponse Data Structure

Mail.XML 13.0B- QualificationReportCreateResponse				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
QualificationReportCreateResponse BEGINS				
complexType BEGINS				
sequence BEGINS				
TrackingID	mailxml_base:s20		optional	
SubmitterTrackingID	mailxml_base:s20		optional	
choice BEGINS				
QualificationReportCreateAccept BEGINS				
complexType BEGINS				
sequence BEGINS				

Copyright © 2014 USPS®. All Rights Reserved

Mail.XML 13.0B- QualificationReportCreateResponse				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
CustomerQualificationReportID	mailxml_base:s66		required	
ReturnInfo	mailxml_defs:basicReturnInfoType		optional	
sequence ENDS				
MailXMLQualReportResponseHeaderInfo	mailxml_mm:MailXMLQualReportResponseHeaderInfo			
complexType ENDS				
QualificationReportCreateAccept ENDS				
QualificationReportCreateReject BEGINS				
complexType BEGINS				
sequence BEGINS				
ReturnInfo	mailxml_defs:basicReturnInfoType			
sequence ENDS				
MailXMLQualReportResponseHeaderInfo	mailxml_mm:MailXMLQualReportResponseHeaderInfo			
complexType ENDS				
QualificationReportCreateReject ENDS				
choice ENDS				
sequence ENDS				
complexType ENDS				
QualificationReportCreateResponse ENDS				

3.54 QualificationReportQueryRequest

Purpose

This message should be sent when customer would like to request the qualification Report.

Business Rules

Cannot be sent until the QualificationReportDetailCreateRequest and QualificationReportSummaryCreateRequest have been successful.

3.54.1 QualificationReportQueryRequest Data Structure

Mail.XML 13.0B- QualificationReportQueryRequest				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
QualificationReportQueryRequest BEGINS				
MailXMLMessageHeaderInfo	MailXMLMessageHeaderInfo attribute	-	Required	Refer this attribute in Section 7
Sequence Block BEGINS				
SubmittingParty	participantIDType complex type	-	Required	Refer to this complex type in Section 4
SubmittingSoftware	submittingSoftwareType complex type	-	Required	Refer to this complex type in Section 4
SubmitterTrackingID	String 20		Required	
MailingFacility	CRIDType simple		Required	Refer to this simple

Copyright © 2014 USPS®. All Rights Reserved

Mail.XML 13.0B- QualificationReportQueryRequest				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
	type			type in Section 5
PostageStatementStatus	postageStatementStatusType simple type		Optional	Refer to this simple type in Section 5
QualificationReportClass	qualificationReportClassType simple type		Optional	Refer to this simple type in Section 5
CustomerQualificationReportID	String, 66	-	Optional	
BeginDate	Date/Time	-	Optional	-
EndDate	Date/Time	-	Optional	-
Preparer	permitPublicationDataType complex type		Optional	Refer to this complex type in Section 4
PermitHolder	permitPublicationDataType complex type		Optional	Refer to this complex type in Section 4
IssueBeginDate	Date/Time	-	Optional	-
IssueEndDate	Date/Time	-	Optional	-
IssueNumber	String, 6	-	Optional	-
VolumeNumber	String, 5	-	Optional	-
DestinationFacilityZip	String, 9	Up to nine digit zip code of the destination facility	Required	
Sequence Block ENDS				
QualificationReportQueryRequest ENDS				

3.55 QualificationReportQueryResponse

Purpose

This is a response message returned from USPS to the requester who sends the QualificationReportQueryRequest message.

Business Rules

Cannot be sent until QualificationReportQueryRequest message is received

USPS collects the data based on the QueryRequest and return all data in this message.

3.55.1 QualificationReportQueryResponse Data Structure

Mail.XML 13.0B- QualificationReportQueryResponse				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
QualificationReportQueryResponse BEGINS				
MailXMLMessageHeaderInfo	MailXMLMessageHeaderInfo attribute	-	Required	Refer this attribute in Section 7
Sequence Block BEGINS				
TrackingID	String, 12	-	Optional. Returns the Tracking ID when an error is occurred or when message is too large and request cannot be completed	

Copyright © 2014 USPS®. All Rights Reserved

Mail.XML 13.0B- QualificationReportQueryResponse				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
SubmitterTrackingID	String 20		Required	
Choice Block BEGINS				
QueryResult Block BEGINS	-	-	Required Block	
Sequence Block BEGINS				
QualificationReport block	qualificationReportDataType complex type	Complex Type	Required block; contains the values necessary to populate a Qualification Report	Refer to this complex type in Section 4
ReturnInfo	basicReturnInfoType	-	Optional Block Allow 0 to many occurrence	Refer to this complex type in Section 4
Sequence Block ENDS				
QueryResults block ENDS				
QueryError Block BEGINS			Required Block	
ReturnInfo	basicReturnInfoType		Required block when error occurs	Refer to this complex type in Section 4
QueryError Block ENDS				
Choice Block ENDS				
Sequence Block ENDS				
QualificationReportQueryResponse ENDS				

3.56 QualificationReportSummaryCreateRequest

Purpose

The purpose of this message is to allow users to create summary of Qualification Report. In most cases this message will be followed by QualificationReportDetailCreateRequest message. The concept behind breaking the summary and detail is to divide the amount of data that is sent as part of one single QualificationReportDetailCreateRequest. *PostalOne!* will require breakup of qualification reports into summary and detail messages to allow breakup of large qualification report data.

3.56.1 QualificationReportSummaryCreateRequest Data Structure

Mail.XML 13.0B- QualificationReportSummaryCreateRequest				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
QualificationReportSummaryCreateRequest BEGINS				
MailXMLQualReportRequestHeaderInfo	MailXMLQualReportRequestHeaderInfo attribute	-	Required	Refer this attribute block in Section 7
SubmittingParty	participantIDType complex type	-	Required	Refer to this complex type in Section 4
SubmittingSoftware	submittingSoftwareType complex type	-	Required	Refer to this complex type in Section 4
SubmitterTrackingID	String 20		Required	
OnePassPlannedOrA	onePassPlannedOrA	-	Optional	Refer to this simple

Copyright © 2014 USPS®. All Rights Reserved

Mail.XML 13.0B- QualificationReportSummaryCreateRequest				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
ctualFlag	ctualFlagType simple type			type in Section 5
QualificationReportSummary	qualificationReportSummaryDataType complex type	-	Required	Refer to this complex type in Section 4
QualificationReportSummaryCreateRequest ENDS				

3.57 QualificationReportSummaryCreateResponse

Purpose

This is a response message for QualificationReportSummaryCreateRequest message. It results in acceptance or rejection of the request and details are provided in the response.

3.57.1 QualificationReportSummaryCreateResponse Data Structure

Mail.XML 13.0B- QualificationReportSummaryCreateResponse				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
QualificationReportSummaryCreateResponse BEGINS				
TrackingID	String 12	-	Optional.	Allow users to retrieve the previously submitted request message data without resending the actual request message by using this ID in MRRR Message
SubmitterTrackingID	String 20		Required	
Choice Block BEGINS	-	-	Either Accept or Reject block is returned	-
QualificationReportSummaryCreateAcceptBlock BEGINS				
MailXMLQualReportResponseHeaderInfo	MailXMLQualReportResponseHeaderInfo attribute	-	Required	Refer this attribute block in Section 7
CustomerQualificationReportID	String 66	-	Optional	-
ReturnInfo	basicReturnInfo complex type	-	Optional	Refer to this complex type in Section 4
QualificationReportSummaryCreateAcceptBlock ENDS				
QualificationReportSummaryCreateRejectBlock BEGINS				
MailXMLQualReportResponseHeaderInfo	MailXMLQualReportResponseHeaderInfo attribute block	-	Required	Refer this attribute block in Section 7
ReturnInfo	basicReturnInfo complex type	-	Required	Refer to this complex type in Section 4
QualificationReportSu				

Copyright © 2014 USPS®. All Rights Reserved

Mail.XML 13.0B- QualificationReportSummaryCreateResponse				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
mmaryCreateReject Block ENDS				
Choice Block ENDS				
QualificationReportSummaryCreateResponse ENDS				

3.58 QualificationReportDetailCreateRequest

Purpose

The purpose of this message is to allow users to create details of Qualification Report. The concept behind breaking the summary and detail is to divide the amount of data that is sent as part of one single QualificationReportDetailCreateRequest. *PostalOne!* will require breakup of qualification reports into summary and detail messages to allow breakup of large qualification report data.

3.58.1 QualificationReportDetailCreateRequest Data Structure

Mail.XML 13.0B- QualificationReportDetailCreateRequest				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
QualificationReportDetailCreateRequest BEGINS				
MailXMLQualReportRequestHeaderInfo	MailXMLQualReportRequestHeaderInfo attribute	-	Required	Refer this attribute block in Section 7
SubmittingParty	participantIDType complex type	-	Required	Refer to this complex type in Section 4
SubmittingSoftware	submittingSoftwareType complex type	-	Required	Refer to this complex type in Section 4
SubmitterTrackingID	String 20		Required	
OnePassPlannedOrActualFlag	onePassPlannedOrActualFlagType simple type	-	Optional	Refer to this simple type in Section 5
QualificationReport	qualificationReportDetailDataType complex type	-	Required	Refer to this complex type in Section 4
QualificationReportDetailCreateRequest ENDS				

3.59 QualificationReportDetailCreateResponse

Purpose

This is a response message for QualificationReportDetailCreateRequest message. It results in acceptance or rejection of the request and details are provided in the response.

3.59.1 QualificationReportDetailCreateResponse Data Structure

Field Description

Mail.XML 13.0B- QualificationReportDetailCreateResponse				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
QualificationReportDetailCreateResponse BEGINS				
TrackingID	String 12	-	Optional.	Allow users to retrieve the previously submitted

Copyright © 2014 USPS®. All Rights Reserved

Mail.XML 13.0B- QualificationReportDetailCreateResponse				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
				request message data without resending the actual request message by using this ID in MRRR Message
SubmitterTrackingID	String 20		Required	
Choice Block BEGINS	-	-	Either Accept or Reject block is returned	-
QualificationReportDetailCreateAccept Block BEGINS				
MailXMLQualReportResponseHeaderInfo	MailXMLQualReportResponseHeaderInfo attribute	-	Required	Refer this attribute block in Section 7
CustomerQualificationReportID	String 66	-	Optional	-
ReturnInfo	basicReturnInfo complex type	-	Optional	Refer to this complex type in Section 4
QualificationReportDetailCreateAccept Block ENDS				
QualificationReportDetailCreateReject Block BEGINS				
MailXMLQualReportResponseHeaderInfo	MailXMLQualReportResponseHeaderInfo attribute block	-	Required	Refer this attribute block in Section 7
ReturnInfo	basicReturnInfo complex type	-	Required	Refer to this complex type in Section 4
QualificationReportDetailCreateReject Block ENDS				
Choice Block ENDS				
QualificationReportDetailCreateResponse ENDS				

3.60 SummaryZipDestinationReportCreateRequest

Purpose

This report is used by the USPS to identify all pieces of the postage statements are correctly calculated and can be verified through this report against all postage statements.

Business Rules

- This report is required for MLOCR mailing
- A QualificationReportDetailCreateRequest and PostageStatementCreateRequest message must be submitted prior to submitting the SummaryZipDestinationReportCreateRequest
- The *PostalOne!* System will validate the fields in the SummaryZipDestinationReportCreate Request message
- The *PostalOne!* System will generate the SummaryZipDestinationReportCreateAccept block in the SummaryZipDestinationCreateResponse message if the SummaryZipDestinationReportCreateRequest message is accepted

Copyright © 2014 USPS®. All Rights Reserved

- The *PostalOne!* System will generate the SummaryZipDestinationReportCreateReject block in the SummaryZipDestinationCreateResponse message if the SummaryZipDestinationReportCreateRequest message is rejected
- The *PostalOne!* will continue to support NFM Processing Category (i.e. NA or NB)
- Sibling trays shall be tied to logical trays and sibling pallets to logical pallets in a Presort job with Presentation Category of P = Conventional Presort and postage statement has been submitted.
- SummaryZipDestinationReportCreateRequest message is required for Mail.XML transactions once a PostageStatementCreate Request, PeriodicalsPostageStatementCreateRequest, or ConsolidatedPostageStatementCreateRequest has been submitted and the qualification report includes logical containers.
- Postage statements with logical containers cannot be finalized until a SummaryZipDestinationReportCreateRequest message has been accepted.
-

3.60.1 SummaryZipDestinationReportCreateRequest Data Structure

Mail.XML 13.0B- SummaryZipDestinationReportCreateRequest				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
SummaryZipDestinationReportCreateRequest BEGINS				
SubmittingParty	participantIDType complex type		Required Block but all attributes within this block are optional	Refer to this complex type in Section 4
SubmittingSoftware	submittingSoftwareType complex type		Required	Refer to this complex type in Section 4
SubmitterTrackingID	String 20		Required	
CustomerGroupID	String 25		Required	
MailingGroupID	nonnegative Integer		Required	
OnePassPlannedOrActual	yesNo simple type	Yes/No	Optional	
OnePassOrTwoPass	onePassOrTwoPassType simple type		Optional	Refer to this simple type in Section 5
Sequence Block BEGIN			1 to many allowed	
EntryPointZip	zipCodeThreeOrFiveDigit simple type		Required	Refer to this simple type in Section 5
EntryFacilityType	EntryFacilityType simple type		Optional	Refer to this simple type in Section 5
SummaryZipDestinationReport Block BEGIN			Required 1 to many allowed	
DestinationZip	zipCodeThreeOrFiveDigit simple type		Required	Refer to this simple type in Section 5
ProcessingCategory	processingCategoryType simple type		Optional	Refer to this simple type in Section 5
PostagePaymentMethod	postagePaymentMethodType simple type		Required	Refer to this simple type in Section 5
MLOCRRateType	mlocrRateType simple type		Optional	Refer to this simple type in Section 5
Weight	Double		Optional The value of Weight must be in Pounds.	
RateAffixed	Double		Optional	
NumberOfPieces	nonnegative Integer		Optional	
NumberOfPiecesDifference	nonnegative Integer		Optional	

Copyright © 2014 USPS®. All Rights Reserved

Mail.XML 13.0B- SummaryZipDestinationReportCreateRequest				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
PostageAffixed	Double		Optional	
CumulativePostageAffixed	Double		Optional	
TotalPostage	Double		Optional	
NetPostageDue	Double		Optional	
CumulativePostageDue	Double		Optional	
RunningTotalPieces	nonnegative Integer		Optional	
SortationLevel	ContainerLevelType simple type		Required	Refer to this simple type in Section 5
SummaryZipDestinationReport Block END				
Sequence Block END				
SummaryZipDestinationReportCreateRequest ENDS				

3.61 SummaryZipDestinationReportCreateResponse

Purpose

This is the response message to SummaryZipDestinationReportCreateRequest message

Business Rules

- This message is required for MLOCR mailing.
- The *PostalOne!* System will generate the SummaryZipDestinationReportCreateAccept block in the SummaryZipDestinationCreateResponse message if the SummaryZipDestinationReportCreateRequest message is accepted
- The *PostalOne!* System will generate the SummaryZipDestinationReportCreateReject block in the SummaryZipDestinationCreateResponse message if the SummaryZipDestinationReportCreateRequest message is rejected

3.61.1 SummaryZipDestinationReportCreateResponse Data Structure

Mail.XML 13.0B- SummaryZipDestinationReportCreateResponse				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
SummaryZipDestinationReportCreateResponse BEGINS				
TrackingID	String 12	-	Optional	Allow mailers to retrieve the data without re-query the message by using this ID in MRRR Message.
SubmitterTrackingID	String 20		Required	
Choice Block BEGINS			Required Either Accept or Reject block is required.	
SummaryZipDestinationReportCreateAccept Block BEGIN			Either Accept or Reject Block is returned	
ReturnInfo	basicReturnInfo complex type		Optional	Refer to this complex type in Section 4

Copyright © 2014 USPS®. All Rights Reserved

Mail.XML 13.0B- SummaryZipDestinationReportCreateResponse				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
SummaryZipDestinationReportCreateAccept Block END				
SummaryZipDestinationReportCreateReject Block BEGIN			Either Accept or Reject Block is returned	
ReturnInfo	basicReturnInfo complex type		Required	Refer to this complex type in Section 4
SummaryZipDestinationReportCreateReject Block END				

3.62 ReconciliationReportQueryRequest

The customer cannot update the Qualification report once filed. After the customer goes through the process of printing and delivering the mail to the USPS, the Reconciliation report is created that shows how much mail was planned and how much was mailed. In the ReconciliationReportQueryRequest, the customer is required to provide the mailing group ID and Customer group ID besides the mandatory elements of Submitting party and Submitting software.

3.62.1 ReconciliationReportQueryRequest Data Structure

Field Description

Mail.XML 13.0B- ReconciliationReportQueryRequest				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
ReconciliationReportQueryRequest BEGINS				
MailXMLDashboardtHeaderInfo	MailXMLDashboardtHeaderInfo attribute block	-	Required	Refer this attribute in Section 7
SubmittingParty	ParticipantIDType complex type		Required. Identifies the customer submitting the message	Refer to this complex type in Section 4.
SubmittingSoftware	SubmittingSoftwareType complex type		Required. Identifies the software submitting the message	Refer to this complex type in Section 4.
SubmitterTrackingID	String 20		Required	
QualificationReportClass	qualificationReportClassType simple type		Optional	Refer to this simple type in Section 5
BeginDate	DateTime	YYYY-MM-DDTHH:MM:SS	Optional	
EndDate	DateTime	YYYY-MM-DDTHH:MM:SS	Optional	
Preparer	permitPublicationDataType complex type	-	Optional	Refer to this complex type in Section 4
PermitHolder	permitPublicationDataType complex type	-	Optional	Refer to this complex type in Section 4
IssueBeginDate	DateTime	YYYY-MM-DDTHH:MM:SS	Optional	
IssueEndDate	DateTime	YYYY-MM-DDTHH:MM:SS	Optional	
IssueNumber	String, 6		Optional	

Copyright © 2014 USPS®. All Rights Reserved

Mail.XML 13.0B- ReconciliationReportQueryRequest				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
VolumeNumber	String, 5		Optional	
ReconciliationReport QueryRequest ENDS				

3.63 ReconciliationReportQueryResponse

In the ReconciliationReportQueryResponse message the *PostalOne!* system responds back with a reconciliation report for every qualification report within the Job/mailing group. The USPS responds back with one Mailing Group Summary and one or more Reconciliation Summary reports. The message also includes an optional Return Code and description. If there are issues, the USPS responds back with the Query Error block and provides one or more Return codes and descriptions to explain the errors.

3.63.1 ReconciliationReportQueryResponse Data Structure

Mail.XML 13.0B- ReconciliationReportQueryResponse				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
ReconciliationReport QueryResponse BEGINS				
MailXMLDashboardt HeaderInfo	MailXMLDashboardt HeaderInfo attribute	-	Required	Refer this attribute in Section 7
TrackingID	String 12	-	Optional	Allow mailers to retrieve the date without re-query the message by using this ID in MRRR message.
SubmitterTrackingID	String 20		Required	
Choice Block BEGINS			Required. Either QueryResult or QueryError block is returned.	
QueryResults Block BEGINS			0 to many allowed.	
MailingGroupSummary	MailingGroupSummary complex	-	Required	Refer to this complex type in Section 4
QualificationSummaryReport	QualificationSummaryReport complex type	-	Optional 0 to many allowed	Refer to this complex type in Section 4
ReconciliationReport	QualificationReport complex type	-	Optional. 0 to many allowed	Refer to this complex type in Section 4
ReturnInfo	basicReturnInfo complex type		Optional	Refer to this complex type in Section 4
QueryResults Block ENDS				
QueryError Block BEGINS				
ReturnInfo	basicReturnInfo complex type		Required	Refer to this complex type in Section 4
QueryError Block ENDS				
Choice Block ENDS				
ReconciliationReport QueryResponse ENDS				

Copyright © 2014 USPS®. All Rights Reserved

3.64 Message Response Retrieval Request Processing

3.64.1 Fault and Fault Recovery Messages

This series of messages is primarily used to support the Asynchronous communication when the response from the USPS may not be within a 7 seconds period and the USPS gives out a Tracking ID to the customer. The customer then uses the Tracking ID to get his message response back using the Message Response Retrieval Request/Response message. Please note all of the response messages now have a TrackingID though all messages are not specifically outlined above under Mail.XML 13.0Bsection.

- Message Response Retrieval Request
- Message Response Retrieval Response

Customers have the ability to provide Tracking ID in the MessageResponseRetrievalRequest message to retrieve data for the entire Response message.

Copyright © 2014 USPS®. All Rights Reserved

4. Complex and Attribute Data Types Data Structure for Mail.XML 13.0B

4.1 complexType: abstractPostageStatementDataType

Blocks Included:abstractPostageStatementData

Mail.XML 13.0B- complexType: abstractPostageStatementDataType				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
abstractPostageStatementDatType Block BEGINS			Required Only one can be submitted	
AgencyCostCode	mailxml_mm:agencyCostCodeType		Optional	
DeliveryStatisticsFileDate	date		Optional	
AutomationAddressMatchDate	date		Optional	
CustomerReferenceID	mailxml_base:s40		Optional	
CustomerCommitmentAgreementNumber	mailxml_base:s40		Optional	
UserPostageStatementID	mailxml_base:s10		Optional	
CarrierRouteAddressMatchDate	date		Optional	
CarrierRouteSequencingDate	date		Optional	
CertificationData	mailxml_mm:certificationDataType			
ContainerCount	mailxml_mm:containerCountType			
UserPostageStatementID	mailxml_base:s10		Optional	:
ContainerCount	mailxml_mm:containerCountType			
EnclosedBy	mailxml_base:enclosedByType		Optional	
DalPieces	nonNegativeInteger		Optional	
EstimateIndicator	mailxml_base:yesNo			
ExtendedForm	mailxml_base:yesNo			
FormType	mailxml_base:formType			
mailxml_mm:PostageStatementLineItemData			Optional	
PostageStatementMailingDate	date			
PackagingMethod	mailxml_base:packagingMethodType			
PostageAffixedAmount	double		Optional	
PostagePaymentMethod	mailxml_mm:postagePaymentMethodType			
ProcessingCategory	mailxml_base:processingCategoryType			
RateType	mailxml_base:rateType			
RegisterOfMailing	mailxml_base:yesNo			
SackingBasis	mailxml_base:sackin		Optional	

Copyright © 2014 USPS®. All Rights Reserved

Mail.XML 13.0B- complexType: abstractPostageStatementDataType				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
	gBasisType			
SinglePieceWeight	double		Optional	
mailxml_defs:ExtraServiceData			Optional	
mailxml_mm:ExtraServiceSummaryData			Optional	
StatementSequenceNumber	mailxml_base:s20		Optional	
RepositionableNotesIndicator	mailxml_base:yesNo			
DocumentVersionData			Optional	
MeteredAffixedMethod	mailxml_base:meteredAffixedMethodType		Optional	
CombinedMailingID	nonNegativeInteger		Optional	
SinglePieceDimensionalWeight	double		Optional	
EnclosingVolumeNo	mailxml_base:s05		Optional	
EnclosingIssueNo Optional	mailxml_base:s06		Optional	
EnclosingIssueDate	date		Optional	
MoveUpdateMethod	mailxml_base:moveUpdateMethodTyp		Optional	
PaymentDateandTime	dateTime		Optional	
MailArrivalDateandTime	dateTime		Optional	
PostageAutoFinalization	Mailxml_mm: PostageAutoFinalizationType		Optional	
abstract PostageStatementDataType Block ENDS				

4.2 complexType: AddressType

Mail.XML 13.0B- complexType: AddressType				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
AddressType Block begins				
Address1	String 1-64 characters		Required;	
Address2	String 1-64 characters		Optional;	
Address3	String 1-40 characters		Optional;	
Address4	String 1-40 characters		Optional;	
City	String 1-45 characters		Required;	
County	String 1-45 characters		Optional;	
State	String 2 Characters	AA, AE, AL, AK, AP, AS, AZ, AR, CA, CO, CT, DE, DC, FM, FL,	Required;	

Copyright © 2014 USPS®. All Rights Reserved

Mail.XML 13.0B- complexType: AddressType				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
		GA, GU, HI, IL, IN, IA, ID, KS, KY, LA, MH, MD, MA, ME, MO, MI, MN, MS, MT, NE, NH, NV, NJ, NM, NY, NC, ND, MP, OH, OR, OK, PW, PA, PR, RI, SC, SD, TN, TX, UT, VT, VI, VA, WA, WV, WI, WY"/>		
ZipCode	Numeric String 9 characters		Required;	
GPSCoordinates	Complex			See GPSCoordinates in Section 8
CommunicationRole	Attribute, String	From, To, CC	Required;	
AddressType ends				

4.3 complexType: basicReturnInfoType

Complex Type: basicReturnInfoType				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
basiReturnInfoType BEGINS				
Sequence Block BEGINS				
ErrorWarning	mailxml_defs:errorWarningType		Optional Unbounded	Refer to this complex type in Section 4
ContainerErrorWarningBlock	mailxml_defs:containerErrorWarningBlockType		Optional Unbounded	
Sequence Block ENDS				
basiReturnInfoType ENDS				

4.4 complexType: bundleRecordType

Mail.XML 13.0B- complexType: bundleRecordType				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
BundleRecord block begins			Optional block; 0 to many pairings can be submitted depending upon the number of BundleMPURecords (used for Bundle charges)	
PublicationInfo	permitPublicationDataType complex type	-	Required	Refer to this complex type in Section 4
PublicationTitle	String, 60 characters		Required	
PostageStatementLineNumber	postageStatementLineNumber3Type		Optional field; uses the Container Level and Entry level to find the lines	Refer to this simple type in Section 5
ChargeableContainer	chargeableContainer		Required field;	Refer to this simple

Copyright © 2014 USPS®. All Rights Reserved

Mail.XML 13.0B- complexType: bundleRecordType				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
Level	LevelType		<BLANK> = NULL is not supported	type in Section 5
ChargeableBundleLevel	chargeableBundleLevelType		Required field; <BLANK> = NULL is not supported	Refer to this simple type in Section 5
Bundles	Double		Required	
IssueDate	Date	YYYY-MM-DD	Required	
IssueNumber	String, 6 characters		Optional	
VolumeNumber	String, 5 characters		Optional	
BundleRecord block ends				

4.5 complexType: bundleVersionRecordType

Mail.XML 13.0B- complexType: bundleVersionRecordType				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
BundleVersionRecord block begins			Optional block; 0 to many pairings can be submitted depending upon the number of BundleMPURecords (used for Bundle charges)	
DocumentVersionData	DocumentVersionData complex type		Required	Refer to this complex type in Section 4
PublicationInfo	permitPublicationDataType complex type	-	Required	Refer to this complex type in Section 4
PublicationTitle	String, 60 characters		Required	
PostageStatementLineNumber	postageStatementLineNumber3Type		Optional field; uses the Container Level and Entry level to find the lines	Refer to this simple type in Section 5
ChargeableContainerLevel	chargeableContainerLevelType		Required field; <BLANK> = NULL is not supported	Refer to this simple type in Section 5
ChargeableBundleLevel	chargeableBundleLevelType		Required field; <BLANK> = NULL is not supported	Refer to this simple type in Section 5
Bundles	Double		Required	
IssueDate	Date	YYYY-MM-DD	Required	
IssueNumber	String, 6 characters		Optional	
VolumeNumber	String, 5 characters		Optional	
BundleVersionRecord block ends				

4.6 complexType: CertificationDataType

Blocks Included: CertificationData

Mail.XML 13.0B- complexType: CertificationDataType				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
CertificationDataType Block BEGINS				
ContactName	String,40 characters		Required;	

Copyright © 2014 USPS®. All Rights Reserved

Mail.XML 13.0B- complexType: CertificationDataType				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
PhoneAreaCode	Exact string, 3 characters	Numbers	Required field; must be exactly 3 characters	
PhoneLast4	Exact String, 4 characters	Numbers	Required field; must be exactly 4 characters	
PhonePrefix	Exact string, 3 characters		Required field; must be exactly 3 characters	
CertificationDataType Block ENDS				

4.7 complexType: CommonContactType

Blocks Included: CommonContact

Mail.XML 13.0B- complexType: CommonContactType				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
CommonContactType Block begins				
ContactName	String,1-60 characters		Required;	
Telephone	String 1-25 characters		Optional;	
MobilePhone	String 1-25 characters		Optional;	
Email	String		Optional;	
Fax	String 1-25 characters		Optional;	
GPSCoordinates	Complex			See GPSCoordinates in Section 8
ContactID	Complex			See ContactIDType in Section 8
ContactType	Attribute	AccountManager, Carrier, CrossDock, CustomerService, HelpDesk, DropShipCoordinator, ApptCoordinator, Plant, InboundFreightCoordinator, SalesOffice, TruckDriver, Warehouse, Other,	Required;	
CommonContactType ends				

4.8 Complex Type: consigneeFacilityType

ConsigneeFacilityType is a block that provides Facility information where mailers should drop their mail.

Mail.XML 10.0 - Complex Type: consigneeFacilityType				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
consigneeFacilityType BEGINS				
CompanyName	String, 40 characters		Required	

Copyright © 2014 USPS®. All Rights Reserved

Mail.XML 10.0 - Complex Type: consigneeFacilityType				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
Choice Block BEGINS				
Sequence Block BEGINS				
FacilityNumber	String, 15 characters		Required	
FacilityAddress	addressType complex type		Optional, refer to AddressType	Refer to this complex type in Section 4
FacilityAddress	addressType complex type		Required	Refer to this complex type in Section 4
Choice Block ENDS				
FacilityName	String, 40 characters		Optional	
FacilityType	String, 15 characters		Optional	
URL	Xs:anyURL		Optional	
CommonContact	commonContactType complex type		Optional 0 to many allowed	Refer to this complex type in Section 4
consigneeFacilityTyp e ENDS				

4.9 complexType: ContactIDType

Blocks Included: ContactID

Mail.XML 13.0B- complexType: ContactIDType				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
ContactIDType Block begins				
IDValue	String,1-30 characters		Required;	
IDValueType	String;	DriversLicense, EmployeeID	Required;	
ContactIDType ends				

4.10 complexType: ContainerCountType

Blocks Included: ContainerCount

Required at least one of the fields in this block must be populated with a non-zero value

Mail.XML 13.0B- complexType: ContainerCountType				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
ContainerCountType Block begins			Required block; at least one of the fields in this block must be populated with a nonzero value	
OtherType	Non-Negative Integer		Conditionally required if no other fields are populated with a nonzero value	
Pallets	Non-Negative Integer		Conditionally required if no other fields are populated with a nonzero value	
Sacks	Non-Negative Integer		Conditionally required if no other fields are populated with a nonzero value	
Trays1mm	Non-Negative Integer		Conditionally required	

Copyright © 2014 USPS®. All Rights Reserved

Mail.XML 13.0B- complexType: ContainerCountType				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
			if no other fields are populated with a nonzero value	
Trays2emm	Non-Negative Integer		Conditionally required if no other fields are populated with a nonzero value	
Trays2mm	Non-Negative Integer		Conditionally required if no other fields are populated with a nonzero value	
TraysFlat	Non-Negative Integer		Conditionally required if no other fields are populated with a nonzero value	
ContainerCountType ends				

4.11 complexType: ContainerIDType

Blocks Included: ContainerID

Mail.XML 13.0B- complexType: ContainerIDType				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
ContainerIDType Block begins				
MaildatContainer	maildatContainerIDType		Required	See 'maildatContainerIDType' complex type in Section 4
MailXMLContainer	MailXMLContainerID Type		Required	See 'MailXMLContainerID Type' complex type in Section 4
ContainerIDType ends				

4.12 complexType: containerKeysInfoType

Blocks Included: ContainerKeysInfoType

Mail.XML 13.0B- complexType: containerKeysInfoType				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
containerKeysInfoType Block Begins				
Sequence block opens				
IMcb	IMcbType		Optional	See 'IMcbType' simple type in Section 5
IMtb	IMtbType		Optional	See 'IMtbType' simple type in Section 5
ContainerID	String, 6 characters		Optional	
ContainerType	mailXMLContainerType		Optional	See 'mailXMLContainerType' simple type in

Copyright © 2014 USPS®. All Rights Reserved

Mail.XML 13.0B- complexType: containerKeysInfoType				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
				Section 5
FSNonFSAvailability Date	Date		Optional	
FullServiceIndicator	yesNo		Optional	
Sequence block closes				
containerKeysInfoTyp e Block Ends				

4.13 complexType: containerPostInductionInfoType

Blocks Included: ContainerPostInductionInfoType

Mail.XML 13.0B- complexType: containerPostInductionInfoType				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
containerPostInductio nInfoType Block BEGINS				
Sequence block opens				
EPDValidation	yesNo		Optional;	
PaymentValidation	yesNo		Optional	
LabelListValidation	yesNo		Optional	
PostInductionStatus	containerStatusType		Optional	Reference ‘containerStatusType’ simple type in Section 5
ReturnInfo	returnInfoType		Optional, Zero to many	See ‘returnInfoType’ complex type in Section 4
Sequence block closes				
containerPostInductio nInfoType Block ENDS				

4.14 complexType: ContainerStatusIDType

Blocks Included:ContainerStatusNotification

Mail.XML 13.0B- complexType: ContainerStatusIDType				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
containerStatusIDTyp e BEGINS				
Sequence Block Opens			Required	
Choice Block Opens			Required	
ContainerID	containerIDType		Required	Refer to ‘containerIDType’ complex type in Section 4
ConsigneeApptID	String, 12 characters		Required. 1 to many allowed	
ConsigneeContainer ManifestID	nonNegativeInteger		Required	
ContentID Block Opens			Required. 1 to many block allowed	

Copyright © 2014 USPS®. All Rights Reserved

Mail.XML 13.0B- complexType: ContainerStatusIDType				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
ConsigneeContentID	String, 12 characters		Required (attribute)	
SchedulerContentID	String, 12 characters		Optional (attribute)	
ContentID Block Closes				
Sequence Block Opens			Required	
UserLicenseCode	userLicenseCodeTyp e		Optional	
MaildatJobID	jobIDType		Optional	
CustomerGroupID	String, 25 characters		Optional	
MailingGroupID	nonNegativeInteger		Optional	
Sequence Block Closes				
Choice Block Closes			Required	
Sequence Block Closes				
containerStatusIDTyp e ENDS				

4.15 complexType: containerStatusInfoType

Mail.XML 13.0B- complexType: containerStatusInfoType				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
containerStatusInfoTy pe BEGINS				
Sequence Block Opens			Required	
Sequence Block Opens			Required	
Choice Block Opens			Required	
ContainerID	containerIDType		Required	Refer to 'containerIDType' complex type in Section 4
IMcb	IMcbType		Required	Refer to 'IMcbType' simple type in Section 5
ConsigneeApptID	String, 12 characters		Required. 1 to many allowed	
ConsigneeContainer ManifestID	nonNegativeInteger		Required	
ContentID Block Opens			Required. 1 to many block allowed	
ConsigneeContentID	String, 12 characters		Required (attribute)	
SchedulerContentID	String, 12 characters		Optional (attribute)	
ContentID Block Closes				
Sequence Block Opens			Required	
UserLicenseCode	userLicenseCodeTyp e		Optional	
MaildatJobID	jobIDType		Optional	
CustomerGroupID	String, 25 characters		Optional	
MailingGroupID	nonNegativeInteger		Optional	
Sequence Block				

Copyright © 2014 USPS®. All Rights Reserved

Mail.XML 13.0B- complexType: containerStatusInfoType				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
Closes				
Choice Block Closes			Required	
Sequence Block Closes				
eInductionIndicator	eInductionIndicatorype	Yes/No	Optional	
ContainerKeysInfo	containerKeysInfoType complex type		Required	Reference 'containerKeysInfoType' complex type in Section 4
ContainerDetail	containerInfoDataType complex type		Optional, Zero to many	Reference 'containerInfoDataType' complex type in Appendix A
PalletHandoffInfo	palletHandoffInfoType complex type		Optional, Zero to many	Reference 'palletHandoffInfoType' complex type in Appendix A
ConsolidatorCommunicationInfo	ConsolidatorCommunicationInfoType complex type		Optional, Zero to many	Reference 'ConsolidatorCommunicationInfoType' complex type in Appendix A
PaymentInfo	postageStatementSummaryType complex type		Optional, Zero to many	Reference 'postageStatementSummaryType' complex type in Section 4
ApptInfo	pickupApptBlockResponseType complex type		Optional, Zero to many	Reference 'pickupApptBlockResponseType' complex type in Section 4
eDocFacility	consigneeFacilityType complex type		Optional	Reference 'consigneeFacilityType' complex type in Section 4
PlannedAppointmentFacility	consigneeFacilityType complex type		Optional	Reference 'consigneeFacilityType' complex type in Section 4
InductionFacility	consigneeFacilityType complex type		Optional	Reference 'consigneeFacilityType' complex type in Section 4
PreInductionInfo	containerPreInductionInfoType complex type		Optional	Reference 'containerPreInductionInfoType' complex type in Section 4
ContainerReleaseInfo	containerReleaseInfoType complex type		Optional, Zero to many	Reference 'containerReleaseInfoType' complex type in Section 4
InductionCloseoutInfo	inductionCloseoutInfoType complex type		Optional, Zero to many	Reference 'inductionCloseoutInfoType' complex type in Section 4
InductionIssues	inductionIssuesType		Optional, Zero to	Reference

Copyright © 2014 USPS®. All Rights Reserved

Mail.XML 13.0B- complexType: containerStatusInfoType				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
	complex type		many	'inductionIssuesType' complex type in Section 4
PostInductionInfo	containerPostInductionInfoType complex type		Optional	Reference 'containerPostInductionInfoType' complex type in Section 4
Sequence Block Closes				
containerStatusInfoType ENDS				

4.16 complexType: ContainerType

Blocks Included: ContainerManifestUpdateRequest

Mail.XML 13.0B- complexType: ContainerType				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
containerType BEGINS				
Sequence Block Opens			Required	
ContainerID	String, 6 characters		Required	
StatementID	nonNegativeInteger		Required. 1 to many allowed	
EntryPointZip	zipCodeThreeOrFive Digit simple type		Required	Reference 'zipCodeThreeOrFive Digit' simple type in Section 5
EntryLocaleKey	localeKeyType		Optional	Reference 'localeKeyType' simple type in Section 5
Choice block opens				
IMcb	IMcbType		Required	
IMtb	IMtbType		Required	
IMpb	IMpbType		Required	
Choice block closes				
Sequence block closes				
containerType ENDS				

4.17 complexType: contentUspsSummaryType

Blocks Included: contentUspsSummaryType

Mail.XML 13.0B- complexType: contentUspsSummaryType				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
contentUspsSummaryType BEGINS				
DestinationDiscountIndicator	mailxml_base:yesNo	Yes No	Optional	
ZoneSkippingIndicator	mailxml_base:yesNo	Yes No	Optional	
FullServiceIndicator	mailxml_base:yesNo	Yes No	Optional	

Copyright © 2014 USPS®. All Rights Reserved

Mail.XML 13.0B- complexType: contentUspsSummaryType				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
eInductionIndicator	mailxml_base:yesNo	Yes No	Optional	
Pallets	mailxml_tm:palletUnitType		Optional	
Bedload	mailxml_tm:bedloadUnitType		Optional	
Perishable	mailxml_base:yesNo	Yes No	Optional	
MailClass	mailxml_base:mailClassType		Optional	
RateType	mailxml_base:rateType		Optional	
InHomeStart	dateTime		Optional	
InHomeEnd	dateTime		Optional	
processingCategory	mailxml_base:processingCategoryType		Optional	
PriorityMailIndicator	mailxml_base:yesNo	Yes No	Optional	
VerificationLocation	mailxml_base:verificationLocationType		Optional	
NewsIndicator	mailxml_base:yesNo	Yes No	Optional	
EvsIndicator	mailxml_base:yesNo	Yes No	Optional	
MailContentName	mailxml_base:s30		Optional	
MailPreparerID	mailxml_base:s12		Optional	
MailPreparerCRID	mailxml_base:CRIDType		Optional	
AdvanceMailingID	mailxml_base:s09		Optional	
EFileNumber	mailxml_base:s12		Optional	
ContainsAutoMail	mailxml_base:yesNo	Yes No	Optional	
SchedulerContentID	mailxml_base:s12		Optional	
ConsigneeContentID	mailxml_base:s12		Optional	
contentUspsSummaryType ENDS				

4.18 complexType: ContainerPostageType

Mail.XML 13.0B- complexType: ContainerPostageType				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
ContainerPostageType Block begins			Required by *PostalOne!*	
ContainerID	String 6	-	Required	
Pieces	Non Negative Integer	-	Required	
Copies	Non Negative Integer	-	Required	

4.19 complexType: createPostageStatementType

Blocks Included: CreatePostageStatement

Mail.XML 13.0B- complexType: createPostageStatementType				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**

Copyright © 2014 USPS®. All Rights Reserved

Mail.XML 13.0B- complexType: createPostageStatementType				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
CreatePostageStatementType Block BEGINS			Require Only one can be submitted	
AgencyCostCode	Mailxml_base:agencyCostCodeType		Optional field Required when Permit Type is OI or OM.	Refer 'agencyCostCode' simple type in Section 5
DeliveryStatisticsFileDate	Date	-	Optional. It allows USPS to validate that correct file is used when the pieces contains simplified addresses.	
AutomationAddressMatchDate	Date	YYYY-MM-DD	Conditionally required for Automation rate pieces. The system will validate that this field cannot be more than 90 calendar days before the PostageStatementMailingDate for Carrier Route mail (RateCategory A, B, D, AF, BF, or DF). The field cannot be more than 180 calendar days before the PostageStatementMailingDate for non-Carrier Route Mail (RateCategory is E, H, L, L1, L2, L3, or L4).	
CustomerReferenceID	String, 40 characters		Optional field. Mailers may submit up to 999 unique CustomerReferenceIDs.	CustomerReferenceID is CAPS Account Number
UserPostageStatementID	String, 10 characters		Optional field	
CarrierRouteAddressMatchDate	Date	YYYY-MM-DD	Conditionally required for Carrier Route rate pieces	
CarrierRouteSequencingDate	Date	YYYY-MM-DD	Conditionally required for Carrier Route rate pieces when Rate Category is A, AF, B, BF, D, or DF.	
CertificationData Block	certificationDataType		Required	See Section 6 for Details
ContainerCount Block	containerCountType		Required block; at least one of the fields in this block must be populated with a	Refer "containerCountType" in Section 6

Copyright © 2014 USPS®. All Rights Reserved

Mail.XML 13.0B- complexType: createPostageStatementType				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
			nonzero value	
EnclosedBy	Mailxml_base:enclosedByType	Refer 'enclosedByType' simple type	Optional field, Required for enclosure, must be set to PE	Refer Section 5
DalPieces	Non-negative Integer		Optional field, required for Detached Addressed Labels. Must equal the number of pieces on Part I and J of the postage statement.	
EstimateIndicator	Mailxml_base:yesNo		Required. When yes, the system will create preliminary postage statements for MLOCR jobs. This field is ignored for presort jobs.	-
ExtendedForm	Mailxml_base:yesNo	True requires PostageStatementLineItemData; False requires LineItemSummaryData	Required field. A single postage statement may contain either PostageStatementLineItemData or LineItemSummaryData	
FormType	Mailxml_base:formType	Refer 'formType' simple type	Required Must be SM or FC when EnclosedBy is populated.	Refer Section 5
LineItemSummaryData Block	LineItemSummaryData complex		Optional field 0 to many can be submitted when ExtendedForm is False	Refer "LineItemSummaryData" complex in Section 6 below.
PostageStatementLineItemData Block			Optional field must submit one to many if ExtendedForm is True.	Refer "PostageStatementLineITemData" complex in Section 6 below.
PostageStatementMailingDate	Date	YYYY-MM-DD	Required. Must equal the date specified in the Qualification Report. It may be up to one year in future or back dated to most recent price change	
PackagingMethod	Mailxml_base:packagingMethodType	Refer 'packagingMethodType' simple type	Optional field If FormType is BP this field must be 0, 1 or 2. If FormType is FC this field must be 0 or	Refer Section 5

Copyright © 2014 USPS®. All Rights Reserved

Mail.XML 13.0B- complexType: createPostageStatementType				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
			1 If FormType is ML this field must be 0, 1 or 2. If FormType is SM this field must be 0, 1 or 2.	
PostageAffixedAmount	Double		Optional (Conditionally required if the Postage Payment Method is 'M' or 'S') up to three decimal places	
PostagePaymentMethod	Mailxml_base:postagePaymentMethodType	Refer 'postagePaymentMethodType' simple type	Required If FormType is BP this field must be S, M or P. If FormType is FC this field must be S, M or P. If FormType is ML this field must be M or P. If FormType is PM this field must be P. If FormType is PP this field must be S, M or P. If FormType is SM this field must be S, M or P.	Refer Section 5
ProcessingCategory	Mailxml_base:processingCategoryType	Refer 'processingCategoryType' simple type	Required field If FormType = BP, then the following values are valid: FL, NP, MP, IR If FormType = FC, then the following values are valid: LT, FL, CD, PF If FormType = ML, then the following values are valid: FL, NP, MP, IR If FormType = PM, then the following values are valid: LT, FL, PF If FormType = PP, then the following values are valid: MP, IR, NP If FormType = SM, then the following values are valid: LT, FL, MP, IR, NP, CM, NA, NB	Refer Section 5

Copyright © 2014 USPS®. All Rights Reserved

Mail.XML 13.0B- complexType: createPostageStatementType				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
RateType	Mailxml_base:rateType	Refer 'rateType' simple type	Required field	Refer Section 5
RegisterOfMailing	Mailxml_base:yesNo	Yes or No	Required, Causes *PostalOne!* to generate a register. If true, must provide container ID, container display name, container type, entry facility type, and entry ZIP (at the line item level)	
SackingBasis	Mailxml_base:sackingBasisType	Refer 'sackingBasisType' simple type	Optional field Required for CR, 3/5 or basic sacking. If FormType is SM this field must be 0, 2, 3, or 4 If FormType is PP this field must be either 0, 1 or 4.	Refer Section 5
SinglePieceWeight	Double		Optional up to four decimal places The value of SinglePieceWeight must be in Pounds.	
ExtraServiceData Block BEGINS			Optional field 0 to many can be submitted. For postage statements claiming extra services Use either the ExtraServiceData block or the ExtraServiceSummary block.	
ServiceCode	Mailxml_base:serviceCodeType	Refer 'serviceCodeType' simple type	Required	Refer Section 5
ServiceRate	Double		Optional field up to four decimals	
ServiceSubCode	Mailxml_base:serviceSubCodeType	Refer 'serviceSubCodeType' simple type	Required	Refer Section 5
ServiceValue	Double		Required, up to two decimals	
TotalAmount	Double		Optional field, up to four decimals	
TotalPieces	Non-negative Integer		Required	
ExtraServiceData Block ENDS				
ExtraServiceSummaryData			Optional field 0 to many can be	

Copyright © 2014 USPS®. All Rights Reserved

Mail.XML 13.0B- complexType: createPostageStatementType				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
Block BEGINS			submitted For postage statements claiming extra services Use either the ExtraServiceData block or the ExtraServiceSummary block.	
LineLabel	String, 80 characters		Optional field	
LineNumber	String, 3 characters		Optional field This field will be ignored if populated; LineNumber will only be taken into account for Full-Service discount lines	
Section	String, 1 character		Optional field	
ServiceCode	Mailxml_base:serviceCodeType	Refer 'serviceCodeType' simple type	Required	Refer Section 5
TotalAmount	Decimal		Required, up to three decimals	
TotalPieces	Non-negative Integer		Required	
USPSPackageUniqueCharacteristic	Mailxml_base:uspsPackageUniqueCharacteristicType	Simple type	Optional	Refer Section 5
USPSPriceIncentiveType	Mailxml_base:USPSPriceIncentiveType	Simple Type	Optional The *PostalOne!* system does not perform any validation on PermitNumber when this field data is provided. The Mailer can use "PostageAffixedReplyRidesFree" only for First Class Mail Letters and must be Full-Service IMb mail pieces weighing between 1 to 1.2 oz but will be processed at 2Oz price rate.	Refer Section 5
USPSPriceIncentiveID	Mailxml_base:USPSPriceIncentiveIDType	Simple Type	Optional This field is ignored.	Refer Section 5
ExtraServiceSummaryData Block ENDS				
StatementSequenceNumber	String, 20 characters		Optional field	
RepositionableNotesIndicator	Mailxml_base:yesNo	True if there are repositionable notes, else False.	Required	
DocumentVersionDat	Complex		Optional field	

Copyright © 2014 USPS®. All Rights Reserved

Mail.XML 13.0B- complexType: createPostageStatementType				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
a Block BEGIN			0 to many can be submitted	
VersionID	String, 10 characters		Required;	
VersionName	String, 12 characters		Required;	
VersionDescription	String, 30 characters		Optional	
PieceWeight	Decimal		Required field up to four decimals. The value of PieceWeight must be in Pounds.	
AdPercent	Mailxml_base:percentageType		Optional	Refer 'percentageType' simple type in Section 5
RateAffixed	Decimal	-	Optional field, up to three decimals. Required when Postage Payment Method is S or M.	-
ContentOfMail	Mailxml_base:contentofMail	Refer Simple type definitions	Optional	Refer Section 5
StandardFlatType	Mailxml_base:standardFltTypeType	Refer simple type definitions	Optional	Refer Section 5
USPSPriceIncentiveType	Mailxml_base:USPSPriceIncentiveType	Simple Type	Optional The *PostalOne!* system does not perform any validation on PermitNumber when this field data is provided. The Mailer can use "PostageAffixedReplyRidesFree" only for First Class Mail Letters and must be Full-Service IMb mail pieces weighing between 1 to 1.2 oz but will be processed at 2Oz price rate.	Refer Section 5
USPSPriceIncentiveID	Mailxml_base:USPSPriceIncentiveIDType	Simple Type	Optional This field is ignored.	Refer Section 5
DocumentVersionData Block END				
MeteredAffixedMethod	Mailxml_base:meteredAffixedMethodType	–Refer 'meteredAffixedMethodType' simple type	Optional field Required for metered postage affixed	Refer Section 5
CombinedMailingID	Non-negative Integer		Optional field; Required for Combined Mailings	
SinglePieceDimensionalWeight	Double		Optional, up to four decimals. Required for balloon or oversize prices up to four decimals.	

Copyright © 2014 USPS®. All Rights Reserved

Mail.XML 13.0B- complexType: createPostageStatementType				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
			The value of SinglePieceDimensionWeight must be in Pounds.	
EnclosingVolumeNo	String, 5 characters		Optional field, used for Periodicals enclosures otherwise ignored	
EnclosingIssueNo	String, 6 characters		Optional field, used for Periodicals enclosures otherwise ignored	
EnclosingIssueDate	Date	YYYY-MM-DD	Optional field, used for Periodicals enclosures otherwise ignored. Required when EnclosedBy is populated.	
PriceType	priceType	commercial, commercialplus	Optional field. Required when the mail is First Class. Should always assume it is commercial unless otherwise identified.	
MoveUpdateMethod	Mailxml_base:moveUpdateMethodType	Refer 'moveUpdateMethodType' simple type	Optional field. Required when FormType is SM.	Refer Section 5
PermitHolderDataBlock	mailerDataRequestType		Required	See Section 6 for Details
MailingOwnerDataBlock	mailerDataRequestType		Optional	See Section 6 for Details
MailingAgentDataBlock	mailerDataRequestType		Optional	See Section 6 for Details
PermitHolderForAPData Block	mailerDataRequestType		Conditionally required for Postage Payment Method of 'S' or 'M'	See Section 6 for Details
ContainerPostage	Mailxml:containerPostageType		Conditionally Required by *PostalOne!* for Full-Service or Mixed mailings (Full-Service plus another type)	See Section 6

4.20 Complex Type: errorWarningType

Mail.XML 13.0B - Complex Type: errorWarningType				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
errorWarningType BEGINS				
Sequence Block BEGINS				
Code	mailxml_base:s08		Optional	Refer to this simple type in Section 5
Severity	mailxml_base:severityType		Optional	Refer to this simple type in Section 5
KeyIDvalues	mailxml_base:s500		Optional	Refer to this simple

Copyright © 2014 USPS®. All Rights Reserved

Mail.XML 13.0B - Complex Type: errorWarningType				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
				type in Section 5
SubmissionDate	SubmissionDate		Optional	Refer to this simple type in Section 5
ErrorDescription	mailxml_base:s1000		Optional	Refer to this simple type in Section 5
Action	mailxml_base:s1000		Optional	Refer to this simple type in Section 5
TrackingID	mailxml_base:s20		Optional	Refer to this simple type in Section 5
SubmitterTrackingID	mailxml_base:s20		Required	Refer to this simple type in Section 5
MailxmlDetail	mailxml_defs:mailxml DetailType		Optional	Refer to this complex type in Section 4
Sequence Block ENDS				
errorWarningType ENDS				

4.21 complexType: FullContainerIDType

Blocks Included:

- OriginalContainer
- CancelledSiblingContainer
- SiblingToDelete
- AcceptedSiblingContainer
- NewSiblingContainer
- RejectedSiblingContainer

Mail.XML 13.0B- complexType: FullContainerIDType				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
FullContainerIDType Block begins			Attributes block	
UserLicenseCode	String, 4 characters		Required; references existing Mail.dat container	
MaildatJobID	String, 8 characters		Required for Mail.dat submitted containers; references existing Mail.dat container	
ContainerGroupID	String 25		Required	
MailingGroupID	Non Negative Integer		Required for Mail.XML submitted containers.	
ContainerID	ContainerType	Optional	Optional Cannot use existing ContainerID to identify a new container.	
UniqueContainerBarcode	String, 24 characters		Optional field; references existing Mail.dat container	
FullContainerIDType Block ends			End of block	

Copyright © 2014 USPS®. All Rights Reserved

4.22 complexType: GPSCoordinates

Mail.XML 13.0B- complexType: GPSCoordinates				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
GPSCoordinates Block begins				
Latitude	Numeric; maximum 18 digits; 8 decimals;		Required;	
Longitude	Numeric; maximum 18 digits; 8 decimals;		Required	
Height	Numeric; maximum 18 digits; 8 decimals;		Optional;	
GPSSystem	String	ECEF, HAE, MSL	Required	
GPSCoordinates ends				

4.23 complexType: IntelligentMailBarcodeType

Mail.XML 13.0B- complexType: IntelligentMailBarcodeType				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
IntelligentMailBarcodeType Block begins			Required Only one block submitted	
BarcodeID	Number, 2 characters		Not required	
ServiceTypeCode	Number, 3 characters		Conditionally required if Mail Class is not provided	
MailClass	Number, 1 character		Conditionally required if Service Type Code is not provided	
MailerID6	Number, 6 characters		Required Only one pairing of MailerID and SerialNumber is required	
SerialNumber9	Number, 9 characters		Required Only one pairing of MailerID and SerialNumber is required	
MailerID9	Number, 9 characters		Required Only one pairing of MailerID and SerialNumber is required	
SerialNumber6	Number, 6 characters		Required Only one pairing of MailerID and SerialNumber is required	
DeliveryPointZIP	Number, 11 characters		Not required	
IntelligentMailBarcodeType Block ends				

Copyright © 2014 USPS®. All Rights Reserved

4.24 complexType: LargeTransactionDividerGroupType

Blocks Included:LargeTransactionDividerGroupType; LargeTransactionDividerGroupOptionalType

Mail.XML 13.0B- complexType: LargeTransactionDividerGroupType				
Field	Format	Acceptable Values	Business Rules	Comments
Message Group ID	String, Length 20	-	Not currently supported	-
Total Message Count	Positive Integer	-	Not currently supported	-
Message Serial Number	Positive Integer	-	Not currently supported	-
Transmitted Record Count	Positive Integer	-	Not currently supported	-
Total Records Across Message	Positive Integer	-	Not currently supported	-
Last Message	Boolean	Yes/No	Not currently supported	-

4.25 complexType: LinkageType

Blocks Included: CreateLinkage; LinkageCreated; CancelLinkage; LinkageRejected

Mail.XML 13.0B- complexType: LinkageType				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
OriginalContainer block begins			Required block; block of data the has been stored in the *PostalOne!* system	
MailDatContainer Block	Complex			See Section 7 for Details
MailXMLContainer block	Complex			See Section 7 for Details
ContainerBarcode	String, 24 characters		Optional if filled in MaildatContainer block or MailXMLContainer block	
OriginalContainer block ends				

4.26 complexType: LinkingContainerIDType

Blocks Included: OriginalContainer; LinkedContainer

Mail.XML 13.0B- complexType: LinkingContainerIDType				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
OriginalContainer block begins			Required block; block of data the has been stored in the *PostalOne!* system	
MailDatContainer Block	Complex			See Section 7 for Details
MailXMLContainer block	Complex			See Section 7 for Details
ContainerBarcode	String, 24 characters		Optional if filled in MaildatContainer block or MailXMLContainer block	

Copyright © 2014 USPS®. All Rights Reserved

Mail.XML 13.0B- complexType: LinkingContainerIDType				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
OriginalContainer block ends				

4.27 complexType: MaildatContainerIDType

Blocks Included: MaildatContainer

Mail.XML 13.0B- complexType: MaildatContainerIDType				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
MailDatContainer Block begins			Contains original container identifiers Required Only one block can be submitted	
UserLicenseCode	String, 4 characters		Required field; must match the User License Code from the .hdr file in Mail.dat	
MaildatJobID	String, 8 characters		Required field; must match the Job ID from the .csm file in Mail.dat	
ContainerID	String, 6 characters		Required field; must match the Container ID from the .csm file in Mail.dat	
UniqueContainerBarcode	String, 24 characters		Not required (attribute)	
MailDatContainer Block ends				

4.28 complexType: MailerDataRequestType

Mail.XML 13.0B- complexType: MailerDataRequestType				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
MailerDataRequestType Block begins				
MID Block	Complex		Optional Block	See MIDType in Section 4 for Details
ContactName	String, 60 characters		Required	
PermitPublicationData Block	Complex		Required Block	See PermitPublicationDataType in Section 4 for Details

4.29 complexType: MailerDataType

Blocks Included: PermitHolderData; MailingOwnerData; MailingAgentData; PermitHolderForAPData; PublisherData

Mail.XML 13.0B- complexType: MailerDataType				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
MailerDataType Block begins				
Address1	String 64		(1-1) Required	
Address2	String 64		(0-1) Optional	
City	String 45		(0-1) Optional	

Copyright © 2014 USPS®. All Rights Reserved

Mail.XML 13.0B- complexType: MailerDataType				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
Country	String 45		(0-1) Optional	
DunsNumber	String 20		(0-1) Optional	
Email	Email		(0-1) Optional	
MID Block	Complex			See MIDType in Section 4 for Details
CRID	CRID		(0-1) Optional	
ContactName	String, 60 characters		Required	USPS ignores this contact name and picks up the contact info tied to the permit in the permit system.
PermitPublicationData Block	Complex			See PermitPublicationDataType in Section 4 for Details
PhoneAreaCode	String Exactly 3		Required	
PhoneExtension	String 5		Optional	
PhoneLast4	String Exactly 4		Required	
PhonePrefix	String Exactly 3		Required	
State	StateCode		Optional	
ZipCode	ZipCode		Required	
ZipCode4	String Exactly 4		Optional	
MIDType Block ends				

4.30 complexType: MailXMLContainerIDType

Blocks Included: MailXMLContainer

Mail.XML 13.0B- complexType: MailXMLContainerIDType				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
MailXMLContainer block begins			Required block; MaildatContainer or MailXMLContainer block must be submitted	
MailingGroupID	Non-Negative integer		Required field; MailingGroupID and CustomerGroupID must be populated	
CustomerGroupID	String, 25 characters		Required field; MailingGroupID and CustomerGroupID must be populated	
ContainerID	String, 6 characters		Field not supported; using the CustomerContainerID	
ContainerBarcode	String, 24 characters		Required field	
MailXMLContainer block ends				

4.31 Complex Type: mailxmlDetailType

Complex Type: returnInfoType				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
mailxmlDetailType				

Copyright © 2014 USPS®. All Rights Reserved

Complex Type: returnInfoType				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
BEGINS				
Sequence Block BEGINS				
MailXMLVersion	mailxml_base:s08		Optional	Refer to this simple type in Section 5
MailXMLMsgSize	mailxml_base:s20		Optional	Refer to this simple type in Section 5
MailXMLMsgName	mailxml_base:s80		Optional	Refer to this simple type in Section 5
MailXMLBlockName	mailxml_base:s500		Optional	Refer to this simple type in Section 5
Sequence Block ENDS				
mailxmlDetailType ENDS				

4.32 attributeGroup: MailXMLMsgResponseHeaderInfo

Mail.XML 13.0B- attributeGroup: MailXMLMsgResponseHeaderInfo				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
MailXMLMsgRespons eHeaderInfo Block begins			Attributes block	
CustomerGroupID	String, 25 characters		Required (attribute)	
MailingGroupID	Non-negative Integer		Required (attribute)	
TrackingID	String, 12 characters		For asynchronous transactions Not required (attribute)	
Status		Accepted, Amended, Cancelled, Counterproposal, New, NoAction, Original, PartiallyAccepted, Pending, Rejected, Replaced	Not required (attribute)	
MailXMLMsgRespons eHeaderInfo Block ends				

4.33 attributeGroup: MailXMLPostageStatementRequestHeaderInfo

Mail.XML 13.0B- attributeGroup: MailXMLPostageStatementRequestHeaderInfo				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
MailXMLPostageStat ementResponseHead erInfo Block BEGINS			Attributes block; Required	
CustomerGroupID	String, 25 characters		Required (attribute)	
MailingGroupID	Non-negative Integer		Required (attribute)	
Status	Mailxml_base:statusT ype	Refer simple type definition in Section 5	Optional	Refer Section 5
MailXMLPostageStat ementResponseHead erInfo				

Copyright © 2014 USPS®. All Rights Reserved

Mail.XML 13.0B- attributeGroup: MailXMLPostageStatementRequestHeaderInfo				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
Block ENDS				

4.34 complexType: MIDType

Blocks Included: MID

Mail.XML 13.0B- complexType: MIDType				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
MIDType Block begins			Contains six or nine digit MIDs	
MID6	String, 6 characters		Conditionally required if MID9 is not submitted	
MID9	String, 9 characters		Conditionally required if MID6 is not submitted	
MIDType Block ends				

4.35 complexType: ParticipantIDType

Blocks Included: SubmittingParty

Mail.XML 13.0B- complexType: ParticipantIDType				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
ParticipantIDType Block BEGINS				
MailerID6	String, 6 characters		Not required (attribute) Either MailerID6 or MailerID9 can be provided, not both	
MailerID9	String, 9 characters		Not required (attribute) Either MailerID6 or MailerID9 can be provided, not both	
CRID	String, 10 characters		Not required (attribute), Either CRID or MID can be provided for authorization	
SchedulerID	String, 12 characters		Not supported for eDoc messages	
MaildatUserLicense	mailxml_base:userLicenseCodeTye		Not supported for eDoc messages	
ShippingAgentID	mailxml_base:s12		Required	
ReceivingAgentID	mailxml_base:s12		Required	
ConsigneeTrackingID	mailxml_base:s20		Required	
ParticipantIDType Block ENDS				

4.36 complexType: PermitPublicationDataType

Blocks Included: PermitPublicationData; PublicationInfo

Copyright © 2014 USPS®. All Rights Reserved

Mail.XML 13.0B- complexType: PermitPublicationDataType				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
Choice Block BEGINS				
Sequence Block BEGINS				
PermitNumber	Numeric String – Length 8		Required When PublicationNumber is not provided	
PaymentAccountNumber	mailxml_base:s20		A new field to identify the Postage Account is proposed. This field is applicable to all classes of mail. This field is added to support the enhanced payment process The Payment Account Number is different from the Permit Number and will be initially used in addition to the Permit Number. In the future, this field may replace the Permit information. This field will be the authorization of payment for mail without affixing full postage or participation in workshare discounts.	
PermitType	mailxml_base:permitTypeType	Simple type	Required When PublicationNumber is not provided.	Refer 'permitTypeType' simple type in Section 5
PermitZip4	Numeric String 9		Required When PublicationNumber is not provided.	
Sequence Block ENDS				
Sequence Block BEGINS				
PublicationNumber	String, 8		Required when PermitNumber, PermitType, and PermitZip4 are not provided.	
PaymentAccountNumber	mailxml_base:s20		A new field to identify the Postage Account is proposed. This field is applicable to all classes of mail. This field is added to support the enhanced payment process The	

Copyright © 2014 USPS®. All Rights Reserved

Mail.XML 13.0B- complexType: PermitPublicationDataType				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
			Payment Account Number is different from the Permit Number and will be initially used in addition to the Permit Number. In the future, this field may replace the Permit information. This field will be the authorization of payment for mail without affixing full postage or participation in workshare discounts.	
Sequence Block ENDS				
Choice Block ENDS				

4.37 Complex Type: pickupApptBlockResponseType

Mail.XML 10.0 - Complex Type: pickupApptBlockResponseType				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
pickupApptBlockResponseType BEGINS				
TrackingID	String 12	-	Optional	-
ConsigneeApptID	String, 12 Characters		Optional	
ConsigneeFacility	consigneeFacilityType complex type	-	Optional	Refer to this complex type in Section 4
PickupLocation	consigneeFacilityType complex type	-	Required	Refer to this complex type in Section 4
ScheduledAppt	dateTime	-	Required	-
Comment	String 256	-	Optional	-
TransportationResponsibility	responsibleTransportationPartyType simple type	-	Required	Refer to this simple type in Section 8
pickupApptBlockResponseType ENDS				

4.38 complexType: ReturnInfo

Blocks Included: ReturnInfo

Mail.XML 13.0B- complexType: ReturnInfo/basicReturnInfoType				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
ReturnInfo Block BEGINS				
Sequence Block BEGINS				
ReturnCode	Numeric String – Length 4	-	Optional	

Copyright © 2014 USPS®. All Rights Reserved

Mail.XML 13.0B- complexType: ReturnInfo/basicReturnInfoType				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
ReturnDescription	String, Length 260	-	Required	
Sequence Block ENDS				
ReturnInfo Block ENDS				

4.39 complexType: SubmittingSoftwareType

Blocks Included: submittingSoftware

Mail.XML 13.0B- complexType: SubmittingSoftwareType				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
SoftwareName	String		Required Customer must provide the name of their software	
Vendor	String		Required This is vendor name	
Version	String		Required This is version number of the software	
ApprovalDate	Date	YYYY-MM-DD	Optional This is the date when USPS approved the vendor's software	
ApprovalKey	String		Optional This is the approval key provided by USPS to the vendor upon approval of their software	

4.40 complexType: CertificationDataType

Blocks Included: CertificationData

Mail.XML 13.0B- complexType: CertificationDataType				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
CertificationDataType Block BEGINS				
ContactName	String,40 characters		Required;	
PhoneAreaCode	Exact string, 3 characters	Numbers	Required field; must be exactly 3 characters	
PhoneLast4	Exact String, 4 characters	Numbers	Required field; must be exactly 4 characters	
PhonePrefix	Exact string, 3 characters		Required field; must be exactly 3 characters	
CertificationDataType Block ENDS				

Copyright © 2014 USPS®. All Rights Reserved

4.41 complexType: ContainerCountType

Blocks Included: ContainerCount

Note: *Required - at least one of the fields in this block must be populated with a non-zero value*

Mail.XML 13.0B- complexType: ContainerCountType				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
ContainerCountType Block BEGINS			Required block; at least one of the fields in this block must be populated with a nonzero value	
OtherType	Non-Negative Integer		Conditionally required if no other fields are populated with a nonzero value	
Pallets	Non-Negative Integer		Conditionally required if no other fields are populated with a nonzero value	
Sacks	Non-Negative Integer		Conditionally required if no other fields are populated with a nonzero value	
Trays1mm	Non-Negative Integer		Conditionally required if no other fields are populated with a nonzero value	
Trays2emm	Non-Negative Integer		Conditionally required if no other fields are populated with a nonzero value	
Trays2mm	Non-Negative Integer		Conditionally required if no other fields are populated with a nonzero value	
TraysFlat	Non-Negative Integer		Conditionally required if no other fields are populated with a nonzero value	
ContainerCountType Block ENDS				

4.42 complexType: MailOwnerBlockType

Blocks Included: MailOwner

Mail.XML 13.0B- complexType: MailOwnerBlockType				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
MailOwnerBlockType BEGINS			Optional Block	
CRID	Mailxml_base:CRIDType	Refer simple type definition	Optional	Refer Section 5
SchedulerID	String 12	-	Optional	-
MaildatUserLicense	Mailxml_base:userLicenseCodeType	Refer simple type definition	Optional	Refer Section 5
PermitPublicationData Block	permitPublicationDataType	-	Optional	Refer Section 6
Choice Block BEGINS			Optional	

Copyright © 2014 USPS®. All Rights Reserved

Mail.XML 13.0B- complexType: MailOwnerBlockType				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
MailOwnerMID6	Numeric String 6	-	Either MailOwnerMID6 or MailOwnerMID9 is required when this choice block is used.	-
MailOwnerMID9	Numeric String 9	-	Either MailOwnerMID6 or MailOwnerMID9 is required when this choice block is used.	
Choice Block ENDS				
MailOwnerBlockType ENDS				

4.43 complexType: MailerDataType

Blocks Included: PermitHolderData; MailingOwnerData; MailingAgentData; PermitHolderForAPData; PublisherData

Mail.XML 13.0B- complexType: MailerDataType				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
MailerDataType Block begins				
Address1	String 64		(1-1) Required	
Address2	String 64		(0-1) Optional	
City	String 45		(0-1) Optional	
Country	String 45		(0-1) Optional	
DunsNumber	String 20		(0-1) Optional	
Email	Email		(0-1) Optional	
MID Block	Complex			See MIDType in Section 6 for Details
CRID	CRIDType		Optional	Refer to this simple type in Section 5
ContactName	String, 60 characters		Required	USPS ignores this contact name and picks up the contact info tied to the permit in the permit system.
PermitPublicationData Block	Complex		Optional	See PermitPublicationDataType in Section 6 for Details
PhoneAreaCode	String Exactly 3		Required	
PhoneExtension	String 5		Optional	
PhoneLast4	String Exactly 4		Required	
PhonePrefix	String Exactly 3		Required	
State	Mailxml_base:StateCode	Refer Section 5 for this simple type definition	Optional	Refer Section 5
ZipCode	Numeric String, 9		Required	
ZipCode4	String Exactly 4		Optional	
MailerDataType Block ends				

4.44 complexType: MailerDataRequestType

Mail.XML 13.0B- complexType: MailerDataRequestType

Copyright © 2014 USPS®. All Rights Reserved

Field	Format	Acceptable Values	Business Rules	Comments
MailerDataRequestType Block begins				
MID Block	Complex		Optional Block	See MIDType in Section 6 for Details
ContactName	String, 60 characters		Required	
PermitPublicationData Block	Complex		Required Block	See PermitPublicationDataType in Section 6 for details
MailerDataRequestType Block ENDS				

4.45 complexType: MailCharacteristicsType

NOTE: *The PostalOne! system will support MailCharacteristicsType inside DocumentVersionDataWithPermit for qualificationReport and PostageStatment blocks only. MailCharacteristicsType provided in any other block will not be processed.*

Mail.XML 13.0B- complexType: MailCharacteristicsType				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
Content	mailxml_base:characteristicContentType	Refer simple type definition in Section 5	Optional	
Incentive	characteristicIncentiveType	Refer simple type definition in Section 5	Optional	
Fee	mailxml_base:characteristicFeeType	Refer simple type definition in Section 5	Optional	

4.46 attributeGroup: MailXMLPostageStatementResponseHeaderInfo

Mail.XML 13.0B- attributeGroup: MailXMLPostageStatementResponseHeaderInfo				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
MailXMLPostageStatementRequestHeaderInfo Block BEGINS			Attributes block; Required	
CustomerGroupID	String, 25 characters		Required (attribute)	
MailingGroupID	Non-negative Integer		Required (attribute)	
MailXMLPostageStatementRequestHeaderInfo Block ENDS				

4.47 complexType: QualificationReportDataType

Blocks Included: QualificationReport

Mail.XML 13.0B- complexType: QualificationReportDataType				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
qualificationReportDataType Block BEGINS				
DMMSection	String, 12 characters		Optional field	-
BatchManifestIndicator	Mailxml_base:yesNo		Required field	Refer Section 5
ContainerInfoData BLOCK	ContainerInfo Data	-	Optional block; must provide one for each container (may have multiple	Refer “ContainerInfoData” block below in Section 6

Copyright © 2014 USPS®. All Rights Reserved

Mail.XML 13.0B- complexType: QualificationReportDataType				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
			ContainerDetailData blocks within ContainerInfoData block)	
CustomerQualificationReportID	String, 66 characters		Optional field	
FormType	mailxml_base:formType	Refer 'formType' simple type	Required field. For Full-Service / Mixed Service mailings, the FormType can only be 'FC', 'SM', 'PE', and 'BP'.	Refer Section 5
PreparedDate	Date/Time	YYYY-MM-DDTHH:MM:SS	Required field	
QualificationReportPreparer BLOCK	Complex type		Required block; contains permit information of the mail preparer	Refer "qualificationReporPreparerDataType" block below in Section 6
PresortSWCompany	String, 50 characters		Optional field, displayed in Qualification Report	
PresortSWProduct	String, 50 characters		Optional field, displayed in Qualification Report	
PresortSWVersion	String, 20 characters		Optional field, displayed in Qualification Report	
DocumentVersionDataWithPermit block	Complex		Required Block. Allow to 1 to many occurrence	See "DocumentVersionDataWithPermit" block in Section 6 for Details
LogicalPhysicalBundleIndicator	Mailxml_base:logicalPhysicalBundleIndicatrType	Simple Type	Optional	Refer Section 5
SoftwareVendorZAPOption	String 1		Optional	
ZoneMatrixDate	Date	YYYY-MM-DD	Optional	
qualificationReportDataType Block ENDS				

4.48 complexType: QualificationReportPreparerDataType

Blocks Included: QualificationReportPreparer

Mail.XML 13.0B- complexType: QualificationReportPreparerDataType				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
qualificationReportPreparerDataType Block BEGINS			Required block; contains permit information of the mail preparer	
Choice Block BEGINS				
Sequence BEGINS				
PermitNumber	String, 8 characters		Required field when	

Copyright © 2014 USPS®. All Rights Reserved

Mail.XML 13.0B- complexType: QualificationReportPreparerDataType				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
			PermitType and PermitZIP4 are populated	
PermitType	mailxml_base:permiTYpeType	Refer 'permitTypeType' simple type	Required field when PermitNumber and PermitZIP4 are populated	Refer Section 5
PermitZip4	Numeric String, 9 characters		Required field when PermitNumber and PermitType are populated	
Sequence ENDS				
PublicationNumber	String, 9 characters		Required field when PermitNumber, PermitType, PermitZIP4 are not populated	
Choice Block ENDS				
Choice Block BEGINS				
MailerID6	Mailxml_base:MailerID6 type		Optional Conditionally required for Full-Service / Mixed Service mailings that at least one field is populated between the CRID, MailerID6, and MailerID9 fields	Refer "mailerID6type" simple type in Section 5
MailerID9	Mailxml_base:MailerID9 type		Optional Conditionally required for Full-Service / Mixed Service mailings that at least one field is populated between the CRID, MailerID6, and MailerID9 fields	Refer "mailerID9type" simple type in Section 5
Choice Block ENDS				
CRID	Mailxml_base:CRID type		Optional Conditionally required for Full-Service / Mixed Service mailings that at least one field is populated between the CRID, MailerID6, and MailerID9 fields	Refer "CRIDType" simple type in Section 5
qualificationReportPreparerDataType Block ENDS				

4.49 complexType: ContainerPostageType

Mail.XML 13.0B- complexType: ContainerPostageType				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
ContainerPostageTyp			Optional in XSD but	

Copyright © 2014 USPS®. All Rights Reserved

Mail.XML 13.0B- complexType: ContainerPostageType				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
e Block begins			required by *PostalOne!* during implementation	
ContainerID	String 6	-	Required	
Pieces	Non Negative Integer	-	Required	
ContainerDetailID	String, 9	-	Optional	-
Copies	Non Negative Integer	-	Required	
ContainerPostageTyp e Block ENDS				

4.50 complexType: bundleDetailType

Blocks Included: BundleDetail

Mail.XML 13.0B- complexType: bundleDetailType				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
BundleDetailType Block BEGINS			Required block; 1 to many pairings (Required block for any mailing that includes bundled mail)	
ContainerID	String, 6 characters		Required	
BundleID	String, 6 characters		Required field	
TotalPieces	Non-Negative Integer		Required field	
TotalCopies	Non-Negative Integer		Required field	
BundleZIP	Mailxml_base:zipCod eThreeOrFiveDigit	Simple Type	Required field	Refer to this simple type in Section 5
BundleCarrierRoute	Exact String, 4 characters	A = Saturation-ECR B = High Density-ECR D = Carrier Route O = Carrier Route Barcode	Optional field; Required field if the SortationLevel is Carrier Route	
DestinationEntry	mailxml_base:entryDi scountType	Refer ‘entryDiscountType’ simple type	Optional field Determines the Entry Discount If FormType is BP this field must be N, B, S, or D. If FormType is FC this field must be N. If FormType is ML this field must be N. If FormType is PE this field must be A. If FormType is PM this field must be N. If Form Type is PP this field must be B, S, D, P, Q or A. If FormType is SM this field must be N, B, S or D.	Refer to this simple type in Section 5
Zone	mailxml_base:zoneIC Type	Refer ‘zoneICType’ simple type	Optional field If FormType is BP, this field must be N,	Refer to this simple type in Section 5

Copyright © 2014 USPS®. All Rights Reserved

Mail.XML 13.0B- complexType: bundleDetailType				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
			1, 3, 4, 5, 6, 7, or 8 If FormType is FC, this field must be N If FormType is ML, this field must be N If FormType is PE, this field must be N, 1, 3, 4, 5, 6, 7, or 8 If FormType is PM, this field must be N, 1, 3, 4, 5, 6, 7, or 8 If FormType is SM, this field must be N	
DestinationZIP	Mailxml_base:zipCodeThreeOrFiveDigit	Simple Type	Optional field	Refer to this simple type in Section 5
OutsideCountyBundleIndicator	mailxml_base:inCountyOutCountyIndicatorType	Refer 'inCountyOutCountyIndicatorType' simple type	Optional field Required for Periodicals If FormType is PE this field must be I or N.	Refer to this simple type in Section 5
ChargableBundleIndicator	Mailxml_base:yesNo	Simple Type	Optional	Refer to this simple type in Section 5
SortationLevel	mailxml_base:ContainerLevelType		Required field	Refer to this simple type in Section 5
BundleLevel	mailxml_base:bundleDetailLevelType	Refer 'bundleDetailLevelType' simple type	Required field	Refer to this simple type in Section 5
ParentBundleID	String, 6 characters		Optional field	
BundleBarcode	String, 20 characters		Optional field	
BundleStatus	mailxml_base:bundleStatusType		Optional field; Not supporting <BLANK> as a value	Refer to this simple type in Section 5
BundleRecordStatus	mailxml_base:bundleRecordStatusTye		Optional field	Refer to this simple type in Section 5
Incentive	mailxml_base:characteristicIncentiveType		Optional	
Fee	mailxml_base:characteristicFeeType		Optional	
USPSPackageUniqueCharacteristic	Mailxml_base:uspsPackageUniqueCharacteristicType	Refer Simple Type	Optional	Refer to this simple type in Section 5
BundleVersion block begins			Optional block; displayed on Qualification Report Bundle Detail	
VersionID	String, 10 characters		Required field; displayed on Qualification Report Bundle Detail	
VersionName	String, 12 characters		Required field; displayed on Qualification Report Bundle Detail	
BundleVersion block ends				

Copyright © 2014 USPS®. All Rights Reserved

Mail.XML 13.0B- complexType: bundleDetailType				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
BundleDetailType Block ENDS				

4.51 complexType: IntelligentMailBarcodeType

Mail.XML 13.0B- complexType: IntelligentMailBarcodeType				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
IntelligentMailBarcodeType Block begins			Required Only one block submitted	
BarcodeID	Number, 2 characters		Optional	
Choice Block BEGINS		-	Optional ServiceCode or MailClass	-
ServiceTypeCode	Mailxml_base:service Type CodeTYpe		Conditionally required if Mail Class is not provided	Refer Section 5
MailClass	Mailxml_base:mailClassType		Conditionally required if Service Type Code is not provided	Refer Section 5
Choice Block ENDS				
Choice Block BEGINS			Required	
Sequence Block BEGINS				
MailerID6	Mailxml_base:mailerID6Type		Required Only one pairing of MailerID and SerialNumber is required	Refer Section 5
SerialNumber9	iMBSerialNUmber9Type		Required Only one pairing of MailerID and SerialNumber is required	Refer Section 5
Sequence Block ENDS				
Sequence Block BEGINS				
MailerID9	mailerID9Type		Required Only one pairing of MailerID and SerialNumber is required	Refer Section 5
SerialNumber6	iMBSerialNumber6Type		Required Only one pairing of MailerID and SerialNumber is required	Refer Section 5
Sequence Block END				
Choice Block ENDS				
DeliveryPointZIP	RoutingZipCodeType		Not required	Refer Section 5
IntelligentMailBarcodeType Block ends				

Copyright © 2014 USPS®. All Rights Reserved

4.52 complexType: ContainerCountType

Blocks Included: ContainerCount

Note: Required at least one of the fields in this block must be populated with a non-zero value

Mail.XML 13.0B- complexType: ContainerCountType				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
ContainerCountType Block BEGINS			Required block; at least one of the fields in this block must be populated with a nonzero value	
OtherType	Non-Negative Integer		Conditionally required if no other fields are populated with a nonzero value	
Pallets	Non-Negative Integer		Conditionally required if no other fields are populated with a nonzero value	
Sacks	Non-Negative Integer		Conditionally required if no other fields are populated with a nonzero value	
Trays1mm	Non-Negative Integer		Conditionally required if no other fields are populated with a nonzero value	
Trays2emm	Non-Negative Integer		Conditionally required if no other fields are populated with a nonzero value	
Trays2mm	Non-Negative Integer		Conditionally required if no other fields are populated with a nonzero value	
TraysFlat	Non-Negative Integer		Conditionally required if no other fields are populated with a nonzero value	
ContainerCountType Block ENDS				

4.53 complexType:ContainerErrorWarningBlockType

Blocks Included: ReturnnfoType and basicReturnInfoType

Mail.XML 13.0B- complexType:ContainerErrorWarningBlockType				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
ContainerErrorWarningBlockType BEGINS				
ConsigneeContainerGroupingID	String 16	-	-	-
ConsigneeContentID	String 12	-	-	-
ShipperContainerGroupingID	String 16	-	-	-
IMcb	IMcbType	-	-	Refer to this simple type in Section 5
IMtb	IMtbType	-	-	Refer to this simple type in Section 5

Copyright © 2014 USPS®. All Rights Reserved

Mail.XML 13.0B- complexType:ContainerErrorWarningBlockType				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
IMpb	IMpbType	-	-	Refer to this simple type in Section 5
MailContentName	String 30	-	-	-
SchedulerContentID	String 12	-	-	-
ContainerErrorWarningBlockType ENDS				

4.54 complexType: ContainerInfoData

Blocks Included: ContainerInfoData

PostalOne! for all supported Mail.XML versions will process the ContainerInfoData "includedInOtherDocType" field value of "I = Internal co-palletization indicator from the Origin Job - Original Container."

- Value of "I" indicates to the system that the postage statements does not need to be finalized prior to submission of the consolidator file set.
- A Mail.XML update submission cannot contain both values "O" and "I." If an original ContainerInfoData in XML contains value of "O" then "I" is not an acceptable value; if an original ContainerInfoData in XML contains "I" then "O" is not an acceptable value.
- "IncludedInOtherDocType" field will be added as a postage statement variable to generate unique postage statements for origin submissions of tray based co-palletization, or consolidator submission of bundle based co-palletization.
- A master statement may identify both "I" and "O," however each child statement shall only have either "I" or "O."
- First Class and Standard Mail, the MLOCR logical Trays for sibling tubs/bundles use Supplemental PhysicalContainerID in the ContainerInfoData block.
  - ContainerDetailData is not required when logical trays are referred to in SupplementalPhysicalContainerID
- Total weight, container gross weight, number of pieces, or numbers of copies are not required for a ContainerInfoData block without a ContainerDetailData record.
- ContainerInfoData block without a ContainerDetailData record.

Air Boxes

- ContainerType of AB = Air Box is supported for Periodicals and Pending Periodicals.
- Only Full-Service and Mixed Full-Service submissions are eligible to use ContainerType AB = Air Box.
- Air Box container type is treated as a pallet
- Sibling Air Box containers require TotalWeight to be populated.
- Sibling Container weight will be considered for calculating postage on ContainerType of Air Box.
  - Air Boxes will be charged Sack or Pallet rates depending on the TotalWeight.
    - Air Boxes will be charged as Sacks if they weigh less than or equal to 70 lbs.
    - Air Boxes will be considered Pallets if they weigh more than 70 lbs. and less than or equal to 200 lbs.
- *PostalOne!* shall validate sortation for an Air Box as a pallet according to the following:

  Note: Sack preparation is not allowed.
  - Carrier route, required at 70 lbs.
  - Carrier route, optional at 20 lbs. or above.
  - 5-digit scheme carrier routes, required at 70 lbs.
  - 5-digit scheme carrier routes, optional at 20 lbs. or above
  - 5-digit carrier routes, required at 70 lbs.

Copyright © 2014 USPS®. All Rights Reserved

- 5-digit carrier routes, optional at 20 lbs. or above
- 3-digit carrier routes, required at 70 lbs.
- 3-digit carrier routes, optional at 20 lbs. or above
- 5-digit scheme, required at 70 lbs.
- 5-digit scheme, optional at 20 lbs. or above
- 5-digit, required at 70 lbs.
- 5-digit, optional at 20 lbs. or above
- 3-digit, required at 70 lbs.
- 3-digit, optional at 20 lbs. or above
- SCF, required at 70 lbs.
- SCF, optional at 20 lbs. or above
- ADC, required at 70 lbs.
- ADC, optional at 20 lbs. or above.
- Origin mixed ADC, required, no minimum
- Mixed ADC, required, no minimum

Mail.XML 13.0B- complexType: ContainerInfoData				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
ContainerInfoData BEGINS				
PhysicalPostalCodeEntryPoint	String, 6 characters		Required field; 5-digit zip code (6 digits for international zip codes)	
ActualContainerShipDateTime	dateTime	YYYY-MM-DDTHH:MM:SS	Optional field. Required when USPSPickup is Y.	
CSADispatchNumber	String, 10 characters		Optional field. Conditionally required for Full-Service / Mixed Service mailings if the USPSPickup is ‘Y’ (Yes).	
CSAID	String, 10 characters		Optional field. Conditionally required for Full-Service / Mixed Service mailings if the USPSPickup is ‘Y’ (Yes), or the EntryPointFacilityType is ‘O’ (Origin).	
CSADispatchTime	Time	HH:MM:SS	Optional field; required only if DMU verified and USPS transported origin	
CarrierRouteNumber	Exact String, 4 characters		Optional field; required for Carrier Route rate pieces	
CinCode	String, 3 characters		Optional field	
ContainerBarcode	IMCBType simple		Optional field.	Refer to this simple

Copyright © 2014 USPS®. All Rights Reserved

Mail.XML 13.0B- complexType: ContainerInfoData				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
	type		Conditionally required to be populated with a 21-character IMcb for Full-Service / Mixed Service mailings when the container type is one of the following: B = Bedload U = Unit Load Device P = Pallet H = EIRS 61 – Hamper, Large Canvas A = EIRS 61P – Hamper, Large Plastic G = EIRS 66 – General Purpose Mail Container w/Gate D = EIRS 68 – Eastern Region Mail Container w/Web Door R = EIRS 84 – Wire Container Rigid C = EIRS 84C – Collapsible Wire Container. Conditionally required to be populated with a 24-character IMtb for Full-Service / Mixed Service mailings when the container type is one of the following: S = Sack (general) 1 = #1 Sack 2 = #2 Sack 3 = #3 Sack 4 = 01V Sack 5 = 03V Sack E = EMM Tray F = Flat Tub O = 1' Tray T = 2' Tray	type in Section 5
ContainerDetailData	ContainerDetailData complex		Optional block. Required for all ContainerInfoData blocks except for Parent or Sibling containers. Not required when logical trays are referred to in SupplementalPhysicalContainerID	Refer to this complex type in Section 4

Copyright © 2014 USPS®. All Rights Reserved

Mail.XML 13.0B- complexType: ContainerInfoData				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
ContainerDisplayName	String, 50 characters		Optional in XSD but REQUIRED by *PostalOne!* to generate qualification report	
ContainerType	mailXMLContainerType simple type		Required field; displayed on Qualification Report. At least one ContainerType must be 'L' (Logical Tray) when the LogicalPhysicalContainerIndicator field within OpenMailingGroupRequest message is 'L' (Logical).	Refer to this simple type in Section 5
IMpb	IMpbType simple type	-	Optional	Refer to this simple type in Section 5
IncludedInOtherDoc	includedInOtherDocType simple type		Optional field. Must be O if the container will be co-palletized.	Refer to this simple type in Section 5
ContainerID	String, 6 characters		Required field; displayed on Qualification Report	
ParentContainerID	String, 6 characters		Optional field. Cannot be populated if SiblingContainerID is populated. Required when IncludedinOtherDoc field is L and SiblingContainerID is not populated.	
DestinationZip	zipCodeThreeOrFiveDigit	3 or 5 digits	Required field; displayed on Qualification Report	Refer to this simple type in Section 5
EntryPointFacilityType	entryFacilityType'		Required field; displayed on Qualification Report	Refer to this simple type in Section 5
EntryPointZip	zipCodeThreeOrFiveDigit	3 or 5 digits	Required field; displayed on Qualification Report	Refer to this simple type in Section 5
EntryLocaleKey	localeKeyType		Optional field. Required when EntryFacilityType is O and no appointment is provided. Must be populated with the actual Locale key from the USPS Drop Shipment Product. However, when the Facility Type is 'O' or 'H', the EntryLocaleKey field must be filed with	Refer to this simple type in Section 5

Copyright © 2014 USPS®. All Rights Reserved

Mail.XML 13.0B- complexType: ContainerInfoData				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
			either actual Locale Key or the word 'ORIGIN'. For Full-Service or Mixed-Service mailings, it is recommended that the Locale Key be provided whenever possible	
SiblingContainerID	String, 6 characters		Conditionally required if a sibling container exists to accept the overflow of piece-weight or to allow Logical Trays/Container with Physical Trays/Containers for Full-Service / Mixed Service mailings. Cannot be populated if ParentContainerID is populated.	
ProcessingCategory	processingCategoryType		Required field; displayed on Qualification Report If FormType = BP, then the following values are valid: FL, NP, MP, IR If FormType = FC, then the following values are valid: LT, FL, CD, PF If FormType = ML, then the following values are valid: FL, NP, MP, IR If FormType = PM, then the following values are valid: LT, FL, PF If FormType = PE, then the following values are valid: LT, FL, MP, IR, NP If FormType = PP, then the following values are valid: MP, IR, NP If FormType = SM, then the following values are valid: LT, FL, MP, IR, NP, CM, NA, NB For Full-Service / Mixed Service mailings,	Refer to this simple type in Section 5

Copyright © 2014 USPS®. All Rights Reserved

Mail.XML 13.0B- complexType: ContainerInfoData				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
			if FormType = BP, then the following values are valid: FL If FormType = FC, then the following values are valid: LT, FL, CD If FormType = PE, then the following values are valid: LT, FL If FormType = SM, then the following values are valid: LT, FL	
SortationLevel	ContainerLevelType simple type		Required field; displayed on Qualification Report. For MLOCR First-Class mailings, the SortationLevel must be “AN” when the RateLevel is Single-Piece (“SP”).	Refer to this simple type in Section 5
OverflowIndicator	yesNo simple type	Yes No	Optional field; displayed on Qualification Report if Yes	Refer to this simple type in Section 5
ScheduledInductionDateTime	dateTime	YYYY-MM-DDTHH:MM:SS	Optional field. Must be within 30 days, past or future, of the PostageStatement MailingDate. Conditionally required for Full-Service / Mixed Service mailings when the ConsigneeApptID is populated, or the CSAID is populated and the USPSPickup is ‘N’ (No). Must be within 30 days, past or future, of the PostageStatement MailingDate.	
ScheduledShipDateTime	dateTime	YYYY-MM-DDTHH:MM:SS	Optional Conditionally required for Full-Service / Mixed Service mailings when the EntryPointFacilityType is ‘O’ (Origin) and USPSPickup is ‘Y’ (Yes).	
USPSPickup	yesNo simple type	Yes No	Required field	Refer to this simple type in Section 5

Copyright © 2014 USPS®. All Rights Reserved

Mail.XML 13.0B- complexType: ContainerInfoData				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
MailOwnerCRID	CRIDType simple type		Optional field	Refer to this simple type in Section 5
ConsigneeContentID	String, 9 characters		Optional field	
ConsigneeApptID	String, 10 characters		Optional field	
PostageStatementMailingDate	Date	YYYY-MM-DD	Optional field It may be up to one year in future or back dated to most recent price change	
ContainerAcceptanceDate	Date	YYYY-MM-DD	Optional field	
ContainerAcceptanceTime	Time	HH:MM:SS	Optional field	
CarrierID	String, 15 characters		Optional field	
TruckAndDispatchNumber	String, 10 characters		Optional field	
TotalWeightOfContainer	Double		Optional field The value of TotalWeightOfContainer must be in Pounds.	
AdditionalTrayPostageAmount	Double		Optional field. Accepts up to 4 decimals.	
eInductionIndicator	yesNo simple type	-	Optional	Refer to this simple type in Section 5
Incentive	mailxml_base:characteristicIncentiveType		Optional	
Fee	mailxml_base:characteristicFeeType		Optional	
ReadyForSASP	yesNo simple type	-	Optional	Refer to this simple type in Section 5
ContainerInfoData ENDS				

4.55 attributeGroup: ContainerManifestHeaderInfo

Mail.XML 13.0B- attributeGroup: ContainerManifestHeaderInfo				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
ContainerManifestHeaderInfo BEGINS				
CustomerGroupID	String 25	-	Optional	-
MailingGroupID	nonNegativeInteger	-	Optional	-
ContainerManifestGroupID	nonNegativeInteger	-	Optional	-
MaildatJobID	jobIDType simple type	-	Optional	Refer to this simple type in Section 5
UserLicenseCode	userLicenseCodeType simple type	-	Optional	Refer to this simple type in Section 5
ConsigneeContentID	String 12	-	Optional	-
ConsigneeApptID	String 12	-	Optional	-
SchedulerDateTime	Date	-	Optional	-
ContainerManifestHeaderInfo ENDS				

Copyright © 2014 USPS®. All Rights Reserved

4.56 complexType:ContainerPostageType

Mail.XML 13.0B- complexType:ContainerPostageType				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
ContainerPostageType Block begins			Optional in XSD but required by *PostalOne!* during implementation	
ContainerID	String 6	-	Required	
Pieces	Non Negative Integer	-	Required	
ContainerDetailID	String, 9	-	Optional	-
Copies	Non Negative Integer	-	Required	
Choice Block BEGINS			Optional 0 to many allowed When provided one of following must be included: 1. IMcb 2. IMtb 3. IMpb	
IMtb	IMtbType simple type	-	Required	Refer to this simple type in Section 5
IMcb	IMcbType simple type	-	Required	Refer to this simple type in Section 5
IMpb	IMpbType simple type	-	Required	Refer to this simple type in Section 5
Choice Block ENDS				
ContainerPostageType Block ENDS				

4.57 complexType: ContainerDetailData

Blocks Included: ContainerDetailData

Mail.XML 13.0B- complexType: ContainerDetailData				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
ContainerDetailData BEGINS			Optional block. Required for all ContainerInfoData blocks except for Parent or Sibling containers. Allow 0 to many occurrence	
MailOwner block	permitPublicationDataType complex type	Complex Type	Optional	Refer to this complex type in Section 4
ContainerDetailID	String, 9	ContainerID	Optional This field allow linkage between postage statement and qualification report	
CarrierRouteNumber	String exactly 4		Optional	
CumulativePostage	Double		Optional	
EntryDiscountType	entryDiscountType simple type		Required	Refer to this simple type in Section 5
MailEndSeqNo	String 50		Optional	
MailStartSeqNo	String 50		Optional	

Copyright © 2014 USPS®. All Rights Reserved

Mail.XML 13.0B- complexType: ContainerDetailData				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
Postage	Double		Required	
RateLevel	rateLevelType simple type		Required	Refer to this simple type in Section 5
TotalCopies	nonNegative Integer		Required	
TotalPieces	nonNegative Integer		Required Must be '0' when the SiblingContainerID is populated.	
Zone	zoneICType simple type		Optional	Refer to this simple type in Section 5
VersionID	String 10		Optional	
ZipThreeFive	zipCodeThreeOrFive Digit	3 or 5 digit zipcode	Optional field. Required if different from DestinationZip	Refer to this simple type in Section 5
InOutCountyIndicator	InOutCountyIndicator Type simple type		Optional field. Required when FormType is PE.	Refer to this simple type in Section 5
RateLevelIndicator	rateLevelIndicatorTyp e simple type		Optional	Refer to this simple type in Section 5
ContainerChargeCont ainerLevel	cccLevelType simple type		Optional	Refer to this simple type in Section 5
ActualPieces	nonNegative Integer		Optional	
ServiceLevelIndicator	serviceLevelIndicator Type simple type		Required. Conditionally required for Full-Service/Mixed Service mailings. Validated against the FullServiceParticipati onIndicator field within the OpenMailingGroupRe quest message: (1) When the FullServiceParticipati onIndicator is F – all ServiceLevelIndicator s must be F, and (2) When the FullServiceParticipati onIndicator is M – at least one ServiceLevelIndicator s must be F	Refer to this simple type in Section 5
MailCharacteristicsTy pe	mailxml_defs:MailCh aracteristicsType	Complex Type		
ContainerDetailData ENDS				

4.58 complexType: ComponentPeriodicalAdPercentType

Mail.XML 13.0B- complexType: ComponentPeriodicalAdPercentType				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
ComponentPeriodical AdPercentType BEGINS				

Copyright © 2014 USPS®. All Rights Reserved

Mail.XML 13.0B- complexType: ComponentPeriodicalAdPercentType				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
Component	FullComponentType complex type	-	Required	Refer to this simple type in Section 5
ComponentPeriodicalAdPercent	Double	-	Required	-
ComponentPeriodicalAdPercentStatus	componentPeriodicalAdPercentStatysType simple type	-	Required	Refer to this simple type in Section 5
ComponentPeriodicalAdPercentBasis	Double	-	Required	-

4.59 complexType: ComponentWeightUpdateType

Mail.XML 13.0B- complexType: ComponentWeightUpdateType				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
ComponentWeightUpdateType BEGINS				
Component	FullComponentType complex type	-	Required	Refer to this simple type in Section 5
ComponentWeight	Double	-	Required	-
ComponentWeightSource	componentWeightSourceType simple type	-	Required	Refer to this simple type in Section 5
ComponentWeightStatus	componentWeightStatusType simple type	-	Required	Refer to this simple type in Section 5

4.60 complexType: CreatePeriodicalStatementType

Mail.XML 13.0B- complexType: CreatePeriodicalStatementType				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
createPeriodicalStatementType BEGINS				
AdvertisingPercentage	percentageType simple type	-	Required	Refer to this simple type in Section 5
DeliveryStatisticsFileDate	Date	-	Optional	-
AutomationAddressMatchDate	Date	-	Optional	-
CustomerReferenceID	String 40	-	Optional	-
UserPostageStatementID	String 10	-	Optional	-
CarrierRouteAddressMatchDate	Date	-	Optional	-
CarrierRouteSequencingDate	Date	-	Optional	-
CertificationData	certificationDataType complex type	-	Required	Refer to this complex type in Section 4
ContainerCount	containerCountType complex type	-	Required	Refer to this complex type in Section 4
CopyWeight	Double	-	Required	-
EditionCode	String 20	-	Optional	-
FirstIssueDate	Date	-	Optional	-
FormType	formType simple type	-	Required	Refer to this simple type in Section 5
IssueDate	Date	-	Required	-

Copyright © 2014 USPS®. All Rights Reserved

Mail.XML 13.0B- complexType: CreatePeriodicalStatementType				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
IssueFrequency	String 20	-	Optional	-
LastIssueDate	Date	-	Optional	-
PostageStatementMailingDate	Date	-	Required	-
Over10	yesNo	Yes or No	Required	-
LimitedCirculationDiscountClaimed	yesNo	Yes or No	Required	-
PeriodicalLineItemData	PeriodicalLineItemData ELEMENT	-	Optional 0 to many allowed	Refer the definition of this element in Section 7
PostagePaymentMethod	postagePaymentMethodType simple type	-	Required	Refer to this simple type in Section 5
ProcessingCategory	processingCategoryType simple type	-	Required	Refer to this simple type in Section 5
PublicationTitle	String 60	-	Optional	-
CombinedMailingID	nonNegativeInteger	-	Optional	-
RateType	RateType simple type	-	Required	Refer to this simple type in Section 5
SingleRideAlongWeight	Double	-	Optional	-
StatementSequenceNumber	String 20	-	Optional	-
EntryFacilityType	entryFacilityType simple type	-	Optional	Refer to this simple type in Section 5
EntryZip	Exact String 5	-	Optional	-
AgencyCostCode	agencyCostCodeType simple type	-	Optional	Refer to this simple type in Section 5
RepositionableNotesIndicator	yesNo	Yes or No	Required	-
DocumentVersionData	DocumentVersionData block	-	Optional	Refer this block in Section 7
MoveUpdateMethod	moveUpdateMethodType simple type	-	Optional	Refer to this simple type in Section 5
VolumeNumber	String 5	-	Optional	-
IssueNumber	String 6	-	Optional	-
InCountyAddressedSupplementPieces	nonNegativeInteger	-	Optional	-
OutsideCountyAddressedSupplementPieces	nonNegativeInteger	-	Optional	-
PiecesExcludingAddressedSupplementPieces	nonNegativeInteger	-	Required	-
ContainerPostage	containerPostageType complex type	-	Optional 0 to many allowed	-
MailingAgentData	mailerDataRequestType complex type	-	Optional	Refer to this complex type in Section 4
PublisherData	mailerDataRequestType complex type	-	Optional	Refer to this complex type in Section 4
PendingPostageAmount	Double	-	Optional	-

Copyright © 2014 USPS®. All Rights Reserved

4.61 complexType: containerInfoDataType

Blocks Included: ContainerInfoDataType

Mail.XML 13.0B - complexType: containerInfoDataType				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
containerInfoDataType BEGINS				
Sequence Block BEGINS				
PhysicalPostalCodeEntryPoint	mailxml_base:s06		Required	
ActualContainerShipDateTime	xs:dateTime		Optional	
CSADispatchNumber	mailxml_base:s10		Optional	
CSAID	mailxml_base:s10		Optional	
CSADispatchTime	xs:time		Optional	
CarrierRouteNumber	mailxml_base:es4		Optional	
CinCode	mailxml_base:s03		Optional	
ContainerBarcode	mailxml_base:IMcbType		Optional	
ContainerDetailData	mailxml_defs:ContainerDetailData		Optional Unbounded	
ContainerDisplayName	mailxml_base:s50		Optional	
ContainerType	mailxml_base:mailXMLContainerType		Required	
IMpb	mailxml_base:IMpbType		Optional	
IncludedInOtherDoc	mailxml_base:includedInOtherDocType		Optional	
ContainerID	mailxml_base:s06		Required	
ParentContainerID	mailxml_base:s06		Optional	
DestinationZip	mailxml_base:zipCodeThreeOrFiveDigit		Required	
EntryPointFacilityType	mailxml_base:entryFacilityType		Required	
EntryPointZip	mailxml_base:zipCodeThreeOrFiveDigit		Required	
EntryLocaleKey	mailxml_base:localeKeyType		Optional	
SiblingContainerID	mailxml_base:s06		Optional	
ProcessingCategory	mailxml_base:processingCategoryType		Required	
SortationLevel	mailxml_base:containerLevelType		Required	
OverflowIndicator	mailxml_base:yesNo		Optional	
ScheduledInductionDateTime	xs:dateTime		Optional	
ScheduledShipDateTime	xs:dateTime		Optional	
USPSPickup	mailxml_base:yesNo		Required	
MailOwnerCRID	mailxml_base:CRIDType		Optional	
ConsigneeContentID	mailxml_base:s09		Optional	
ConsigneeApptID	mailxml_base:s10		Optional	

Copyright © 2014 USPS®. All Rights Reserved

Mail.XML 13.0B - complexType: containerInfoDataType				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
PostageStatementMailingDate	xs:date		Optional	
ContainerAcceptanceDate	xs:date		Optional	
ContainerAcceptanceTime	xs:time		Optional	
CarrierID	mailxml_base:s15		Optional	
TruckAndDispatchNumber	mailxml_base:s10		Optional	
TotalWeightOfContainer	xs:double		Optional	
AdditionalTrayPostageAmount	xs:double		Optional	
eInductionIndicator	mailxml_base:yesNo		Optional	
Sequence Block BEGINS				
Incentive	mailxml_base:characteristicIncentiveType		Optional	
Fee	mailxml_base:characteristicFeeType		Optional	
Sequence Block ENDS				
ReadyForSASP	mailxml_base:yesNo		Optional	
AcceptMisshipped	mailxml_base:yesNo		Optional	
Sequence Block ENDS				
containerInfoDataType ENDS				

4.62 complexType: palletHandoffInfoType

Blocks Included: palletHandoffInfoType

Mail.XML 13.0B - complexType: palletHandoffInfoType				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
PalletHandoffInfoType BEGINS				
PalletInfoMsgHeaderInfo Attribute Group Block			Required	
palletHandoffInfoType ENDS				

4.63 attributeGroup: PalletInfoMsgHeaderInfo

Mail.XML 13.0B- attributeGroup: PalletInfoMsgHeaderInfo				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
PalletInfoMsgHeaderInfo Block BEGINS			Attributes block	
ShipperApptRequestID	mailxml_base:s12		Required	
ConsigneeApptID	mailxml_base:s12		Required	
SchedulerCorpID	mailxml_base:s12		Required	
SchedulerID	mailxml_base:s12		Required	
SchedulerCRID	mailxml_base:CRIDT		Required	

Copyright © 2014 USPS®. All Rights Reserved

Mail.XML 13.0B- attributeGroup: PalletInfoMsgHeaderInfo				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
	ype			
CreatorSchedulerCorpID	mailxml_base:s12		Required	
CreatorSchedulerID	mailxml_base:s12		Optional	
ShipperMultiStopID	mailxml_base:s12			
ConsigneeMultiStopID	mailxml_base:s12			
ShipperStopNumber	mailxml_base:n06		Required	
ApptType	mailxml_base:apptTypeType		Required	
PickupOrDelivery	mailxml_base:pickupOrDeliveryType		Required	
PalletPositionCount	mailxml_base:n02		Required	
TransferAllContent	mailxml_base:yesNo	Yes or No	Required	
Start	xs:dateTime		optional	
End	xs:dateTime		optional	
PalletInfoMsgHeaderInfo Block ends				

4.64 complexType: containerPreInductionInfoType

Blocks Included: containerPreInductionInfoType

Mail.XML 13.0B - complexType: containerPreInductionInfoType				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
containerPreInductionInfoType BEGINS				
Sequence Block BEGINS				
BarcodeFormatValidation	mailxml_base:yesNo		Optional	
UniqueBarcodeValidation	mailxml_base:yesNo		Optional	
EPDValidation	mailxml_base:yesNo		Optional	
SingleAppointmentValidation	mailxml_base:yesNo		Optional	
IMcbToAppointmentLinage	mailxml_base:yesNo		Optional	
PaymentValidation	mailxml_base:yesNo		Optional	
LabelingListValidation	mailxml_base:yesNo		Optional	
PreInductionStatus	mailxml_tm:containerStatusType		Optional	
ReturnInfo	mailxml_defs:returnInfoType			
Sequence Block ENDS				
containerPreInductionInfoType ENDS				

Copyright © 2014 USPS®. All Rights Reserved

4.65 complexType: containerReleaseInfoType

Blocks Included: containerReleaseInfoType

Mail.XML 13.0B - complexType: containerPreInductionInfoType				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
containerReleaseInfoType BEGINS				
Sequence Block BEGINS				
TransactionID	mailxml_base:s50		Optional	
MessageGeneratedDate	xs:dateTime		Optional	
MessageSentTarget	mailxml_base:s10		Optional	
MessageType	mailxml_base:s50		Optional	
Sequence Block ENDS				
containerReleaseInfoType ENDS				

4.66 complexType: inductionCloseoutInfoType

Blocks Included: inductionCloseoutInfoType

Mail.XML 13.0B - complexType: containerPreInductionInfoType				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
inductionCloseoutInfoType BEGINS				
Sequence Block BEGINS				
TransactionID	mailxml_base:s12		Optional	
MessageGeneratedDate	xs:dateTime		Optional	
Appointment Information Fields				
ConsigneeApptID	mailxml_base:s12		Optional	
ApptStatus	mailxml_base:apptStatusType		Optional	
CloseoutEmployeeUserID	mailxml_base:s12		Optional	
ApptCloseOutDateTime	xs:dateTime		Optional	
ApptCloseOutEmployeeContactInfo	mailxml_defs:commonContactType		Optional	
Add DropShip Or Origin entered Fields				
DropShipOrOrigin	mailxml_base:s12		Optional	
Verification Information Fields				
ApptAuthorizationAction	mailxml_base:s12		Optional	
VerificationEmployeeUserID	mailxml_base:s12		Optional	
Shipyard Information Fields				
ActualConsigneeFacilityID	mailxml_base:s15		Optional	
ActualFacilityType	mailxml_base:s15		Optional	

Copyright © 2014 USPS®. All Rights Reserved

Mail.XML 13.0B - complexType: containerPreInductionInfoType				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
ActualSiteNassCode	mailxml_base:s05		Optional	
ActualSiteName	mailxml_base:s50		Optional	
FacilityArrival	xs:dateTime		Optional	
FacilityDeparture	xs:dateTime		Optional	
Dock Door Information Fields				
ActualDockDoorArrival	xs:dateTime		Optional	
ActualStartUnload	xs:dateTime		Optional	
ActualEndUnload	xs:dateTime		Optional	
DockDoorNo	mailxml_base:s15		Optional	
ConsigneeMailLoadAcceptanceAction	mailxml_base:s15		Optional	
ContainersInducted	mailxml_tm:ContainerInductedType		Optional Unbounded	
ContainerDiscrepancies	mailxml_tm:ContainerDiscrepancyType		Optional Unbounded	
Sequence Block ENDS				
inductionCloseoutInfoType ENDS				

4.67 complexType: inductionIssuesType

Blocks Included: inductionIssuesType

Mail.XML 13.0B - complexType: containerPreInductionInfoType				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
inductionIssuesType BEGINS				
Sequence block Opens				
ContainerProblem	mailxml_tm:InductionProblemType		Optional, One to many	
AppointmentProblem	mailxml_tm:InductionProblemType		Optional, One to many	
TruckLoadProblem	mailxml_tm:InductionProblemType		Optional, One to many	
Sequence block Closes				
inductionIssuesType ENDS				

4.68 complexType: ConsolidatorCommunicationInfoType

Blocks Included: ConsolidatorCommunicationInfoType

Mail.XML 13.0B - complexType: containerPreInductionInfoType				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
ConsolidatorCommunicationInfoType BEGINS				
Sequence block BEGINS				
PalletID	mailxml_base:s09		Optional	Refer to this simple type in Section 5

Copyright © 2014 USPS®. All Rights Reserved

Mail.XML 13.0B - complexType: containerPreInductionInfoType				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
ContainerBarcode	mailxml_base:IMcbType			
InternalID	mailxml_base:s10		Optional	Refer to this simple type in Section 5
BillingNumber	xs:nonNegativeInteger		Optional	Refer to this simple type in Section 5
OriginFacilityInfo	mailxml_defs:consigneeFacilityType		Optional	Reference 'consigneeFacilityType' complex type in Section 4
ConsolidatorFacilityInfo	mailxml_defs:consigneeFacilityType		Optional	Reference 'consigneeFacilityType' complex type in Section 4
PalletCount	xs:nonNegativeInteger		Optional	Refer to this simple type in Section 5
FacilityType	mailxml_base:s15		Optional	Refer to this simple type in Section 5
DestinationCity	mailxml_base:s45		Optional	Refer to this simple type in Section 5
DestinationState	mailxml_base:stateCode		Optional	Refer to this simple type in Section 5
DestinationZipCod	mailxml_defs:zipCode		Optional	Refer to this complex type in Section 4
LocaleKey	mailxml_base:localeKeyType		Optional	Reference 'localeKeyType' simple type in Section 5
FirstpickupDate	xs:dateTime		Optional	Refer to this simple type in Section 5
ActualWarehouseDate	xs:dateTime		Optional	Refer to this simple type in Section 5
DueAtConsolidatorDate	xs:dateTime		Optional	Refer to this simple type in Section 5
RecdAtConsolidatorDate	xs:dateTime		Optional	Refer to this simple type in Section 5
ConsolidatedInventoryStatus	mailxml_base:s15		Optional	Refer to this simple type in Section 5
ShippedQuantity	xs:nonNegativeInteger		Optional	Refer to this simple type in Section 5
ShipmentComplete	mailxml_base:yesNo		Optional	Refer to this simple type in Section 5
ConsolidatorShipDate	xs:dateTime		Optional	Refer to this simple type in Section 5
BeginDeliveryWindowDate	xs:dateTime		Optional	Refer to this simple type in Section 5
EndDeliveryWindowDate	xs:dateTime		Optional	Refer to this simple type in Section 5
ApptDate	xs:dateTime		Optional	Refer to this simple type in Section 5
ActualDeliveryDate	xs:dateTime		Optional	Refer to this simple type in Section 5
CoPalPoolDate	xs:dateTime		Optional	Refer to this simple type in Section 5
DeliveryType	mailxml_base:pickupOrDeliveryType		Optional	Reference 'pickupOrDeliveryType' simple type in

Copyright © 2014 USPS®. All Rights Reserved

Mail.XML 13.0B - complexType: containerPreInductionInfoType				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
				Section 5
PurchaseOrderNumber	xs:nonNegativeInteger		Optional	Refer to this simple type in Section 5
SackTrayCount	xs:nonNegativeInteger		Optional	Refer to this simple type in Section 5
PieceCount	xs:nonNegativeInteger		Optional	Refer to this simple type in Section 5
Weight	xs:double		Optional	Refer to this simple type in Section 5
ContainerStatus	mailxml_tm:containerStatusType		Optional	Reference ‘containerStatusType’ simple type in Section 5
LastPickupdate	xs:dateTime		Optional	Refer to this simple type in Section 5
LastPickupType	mailxml_base:uspsPickupType		Optional	Reference ‘uspsPickupType‘ simple type in Section 5
CurrentZone	mailxml_base:zoneICType		Optional	Reference ‘zoneICType‘ simple type in Section 5
CurrentLocation	mailxml_defs:consigneeFacilityType		Optional	Reference ‘consigneeFacilityType‘ complex type in Section 4
AppointmentDate	xs:dateTime		Optional	Refer to this simple type in Section 5
AppointmentNumber	mailxml_base:s12		Optional	Refer to this simple type in Section 5
CustomerName	mailxml_base:s50		Optional	Refer to this simple type in Section 5
InvoiceNumber	mailxml_base:s10		Optional	Refer to this simple type in Section 5
BillTo	mailxml_base:s10		Optional	Refer to this simple type in Section 5
MailPreparerJobID	mailxml_base:s08		Optional	Refer to this simple type in Section 5
StatComment	mailxml_base:s500		Optional	Refer to this simple type in Section 5
ServiceRequestID	mailxml_base:s20		Optional	Refer to this simple type in Section 5
ServiceItem	mailxml_base:s20		Optional	Refer to this simple type in Section 5
ReferenceNumber	mailxml_base:s06		Optional	Refer to this simple type in Section 5
VersionNumber	mailxml_base:s04		Optional	Refer to this simple type in Section 5
Method	mailxml_base:s10		Optional	Refer to this simple type in Section 5
OutboundShippingDate	xs:dateTime		Optional	Refer to this simple type in Section 5
MiddleDayOfTransit	mailxml_base:ns03		Optional	Refer to this simple type in Section 5
ActualTransit	mailxml_base:ns03		Optional	Refer to this simple type in Section 5
HoldDays	mailxml_base:ns03		Optional	Refer to this simple

Copyright © 2014 USPS®. All Rights Reserved

Mail.XML 13.0B - complexType: containerPreInductionInfoType				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
				type in Section 5
DeliveryConfirmation	mailxml_base:apptStatusType		Optional	Refer to this simple type in Section 5
ScheduledPickupDateStart	xs:dateTime		Optional	Refer to this simple type in Section 5
ScheduledPickupDateEnd	xs:dateTime		Optional	Refer to this simple type in Section 5
PS8125ReceivedDate	xs:dateTime		Optional	Refer to this simple type in Section 5
SegmentTapeCode	mailxml_base:s10		Optional	Refer to this simple type in Section 5
BillingVersionNumber	mailxml_base:s96		Optional	Refer to this simple type in Section 5
MailPreparerJobName	mailxml_base:s30		Optional	Refer to this simple type in Section 5
StartInFacilityDate	xs:dateTime		Optional	Refer to this simple type in Section 5
EndInFacilityDate	xs:dateTime		Optional	Refer to this simple type in Section 5
DSMSStatus	mailxml_base:s12		Optional	Refer to this simple type in Section 5
ReleasedBy	mailxml_base:s50		Optional	Refer to this simple type in Section 5
ReleasedDate	xs:dateTime		Optional	Refer to this simple type in Section 5
Sequence block ENDS				
ConsolidatorCommunicationInfoType ENDS				

4.69 complexType: CreatePostageStatementType

Blocks Included: CreatePostageStatement

Mail.XML 13.0B- complexType: CreatePostageStatementType				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
CreatePostageStatementType BEGINS			Required Only one can be submitted	
AgencyCostCode	agencyCostCodeType		Optional field Required when Permit Type is OI or OM.	Refer ‘agencyCostCode’ simple type in Section 5
DeliveryStatisticsFileDate	Date	-	Optional. It allows USPS to validate that correct file is used when the pieces contains simplified addresses.	
AutomationAddressMatchDate	Date	YYYY-MM-DD	Conditionally required for Automation rate pieces. The system will validate that this field cannot be more than 90 calendar days	

Copyright © 2014 USPS®. All Rights Reserved

Mail.XML 13.0B- complexType: CreatePostageStatementType				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
			before the PostageStatementMailingDate for Carrier Route mail (RateCategory A, B, D, AF, BF, or DF). The field cannot be more than 180 calendar days before the PostageStatementMailingDate for non-Carrier Route Mail (RateCategory is E, H, L, L1, L2, L3, or L4). The mailer must specify the date when the address list was generated.	
CustomerReferenceID	String, 40 characters		Optional field. Mailers may submit up to 999 unique CustomerReferenceIDs.	CustomerReferenceID represents CAPS Account Number
CustomerCommitmentAgreementNumber	String 40	-	Optional	-
UserPostageStatementID	String, 10 characters		Optional field	
CarrierRouteAddressMatchDate	Date	YYYY-MM-DD	Conditionally required for Carrier Route rate pieces	
CarrierRouteSequencingDate	Date	YYYY-MM-DD	Conditionally required for Carrier Route rate pieces when Rate Category is A, AF, B, BF, D, or DF.	
CertificationData	certificationDataType		Required	See Section 7 for Details
ContainerCount	containerCountType		Required block; at least one of the fields in this block must be populated with a nonzero value	Refer “containerCountType” in Section 7
EnclosedBy	Mailxml_base:enclosedByType	Refer ‘enclosedByType’ simple type	Optional field, Required for enclosure, must be set to PE	Refer Section 5
DalPieces	Non-negative Integer		Optional field, required for Detached Addressed Labels. Must equal the number of pieces on Part I and J of the postage statement.	
EstimateIndicator	Mailxml_base:yesNo		Required. When yes, the system will create	-

Copyright © 2014 USPS®. All Rights Reserved

Mail.XML 13.0B- complexType: CreatePostageStatementType				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
			preliminary postage statements for MLOCR jobs. This field is ignored for presort jobs.	
ExtendedForm	Mailxml_base:yesNo	True requires PostageStatementLineItemData; False requires LineItemSummaryData	Required field. A single postage statement may contain either PostageStatementLineItemData or LineItemSummaryData	
FormType	Mailxml_base:formType	Refer 'formType' simple type	Required Must be SM or FC when EnclosedBy is populated.	Refer Section 5
LineItemSummaryData	LineItemSummaryData complex type		Optional field 0 to many can be submitted when ExtendedForm is False	Refer "LineItemSummaryData" complex in Section 7
PostageStatementLineItemData	PostageStatementLineItemData complex type		Optional field must submit one to many if ExtendedForm is True else it is optional field.	Refer "PostageStatementLineITemData" complex in Section 7 below.
PostageStatementMailingDate	Date	YYYY-MM-DD	Required. Must equal the date specified in the Qualification Report. It may be up to one year in future or back dated to most recent price change	
PackagingMethod	Mailxml_base:packagingMethodType	Refer 'packagingMethodType' simple type	Optional field If FormType is BP this field must be 0, 1 or 2. If FormType is FC this field must be 0 or 1. If FormType is ML this field must be 0, 1 or 2. If FormType is SM this field must be 0, 1 or 2.	Refer Section 5
PostageAffixedAmount	Double		Optional (Conditionally required if the Postage Payment Method is 'M' or 'S') up to three decimal places	
PostagePaymentMethod	Mailxml_base:postagePaymentMethodTyp		Required If FormType is BP	Refer Section 5

Copyright © 2014 USPS®. All Rights Reserved

Mail.XML 13.0B- complexType: CreatePostageStatementType				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
	e		this field must be S, M or P. If FormType is FC this field must be S, M or P. If FormType is ML this field must be M or P. If FormType is PM this field must be P. If FormType is PP this field must be S, M or P. If FormType is SM this field must be S, M or P.	
ProcessingCategory	Mailxml_base:processingCategoryType	Refer 'processingCategoryType' simple type	Required field If FormType = BP, then the following values are valid: FL, NP, MP, IR If FormType = FC, then the following values are valid: LT, FL, CD, PF If FormType = ML, then the following values are valid: FL, NP, MP, IR If FormType = PM, then the following values are valid: LT, FL, PF If FormType = PP, then the following values are valid: MP, IR, NP If FormType = SM, then the following values are valid: LT, FL, MP, IR, NP, CM, NA, NB	Refer Section 5
RateType	Mailxml_base:RateType		Required field	Refer Section 5
RegisterOfMailing	Mailxml_base:yesNo	Yes or No	Required, Causes *PostalOne!* to generate a register. If true, must provide container ID, container display name, container type, entry facility type, and entry ZIP (at the line item level)	
SackingBasis	Mailxml_base:sackingBasisType	Refer 'sackingBasisType' simple type	Optional field Required for CR, 3/5 or basic sacking.	Refer Section 5

Copyright © 2014 USPS®. All Rights Reserved

Mail.XML 13.0B- complexType: CreatePostageStatementType				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
			If FormType is SM this field must be 0, 2, 3, or 4 If FormType is PP this field must be either 0, 1 or 4.	
SinglePieceWeight	Double		Optional up to four decimal places The value of SinglePieceWeight must be in Pounds.	
ExtraServiceData	ExtraServicesData complex type	-	Optional field 0 to many can be submitted. For postage statements claiming extra services Use either the ExtraServiceData block or the ExtraServiceSummary block.	Refer to this complex type in Section 4
ExtraServiceSummaryData	ExtraServiceSummaryData complex type		Optional field 0 to many can be submitted For postage statements claiming extra services Use either the ExtraServiceData block or the ExtraServiceSummary block.	Refer to this complex type in Section 4
StatementSequenceNumber	String, 20 characters		Optional field	
RepositionableNotesIndicator	Mailxml_base:yesNo	True if there are repositionable notes, else False.	Required	
DocumentVersionData	DocumentVersionData complex type	-	Optional field 0 to many can be submitted	Refer to this complex type in Section 4
MeteredAffixedMethod	Mailxml_base:meteredAffixedMethodType	–Refer 'meteredAffixedMethodType' simple type	Optional field Required for metered postage affixed	Refer Section 5
CombinedMailingID	Non-negative Integer		Optional field; Required for Combined Mailings	
SinglePieceDimensionalWeight	Double		Optional, up to four decimals. Required for balloon or oversize prices up to four decimals. The value of SinglePieceDimensionWeight must be in Pounds.	
EnclosingVolumeNo	String, 5 characters		Optional field, used for Periodicals	

Copyright © 2014 USPS®. All Rights Reserved

Mail.XML 13.0B- complexType: CreatePostageStatementType				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
			enclosures otherwise ignored	
EnclosingIssueNo	String, 6 characters		Optional field, used for Periodicals enclosures otherwise ignored	
EnclosingIssueDate	Date	YYYY-MM-DD	Optional field, used for Periodicals enclosures otherwise ignored. Required when EnclosedBy is populated.	
PriceType	priceType simple type	commercial, commercialplus	Optional field. Required when the mail is First Class. Should always assume it is commercial unless otherwise identified.	Refer to this simple type in Section 5
MoveUpdateMethod	Mailxml_base:moveUpdateMethodType		Optional field. Required when FormType is SM.	Refer to this simple type in Section 5
PaymentDateandTime	dateTime	-	Optional	-
MailArrivalDateandTime	dateTime	-	Optional	-
ContainerPostage	containerPostageType complex type	-	Optional. 0 to many allowed.	Refer to this complex type in Section 4
PermitHolderData	mailerDataRequestType complex type		Required. Note the Contact Name inside this block is ignored by *PostalOne!*	Refer to this complex type in Section 4
MailingOwnerData	mailerDataRequestType complex type		Optional	Refer to this complex type in Section 4
MailingAgentData	mailerDataRequestType complex type		Optional	Refer to this complex type in Section 4
PermitHolderForAPData	mailerDataRequestType complex type		Conditionally required for Postage Payment Method of 'S' or 'M'. Note the Contact Name inside this block is ignored by *PostalOne!*	Refer to this complex type in Section 4
CreatePostageStatementType ENDS				

Copyright © 2014 USPS®. All Rights Reserved

4.70 complexType: DataRecipient

Mail.XML 13.0B- complexType: DataRecipient				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
DataRecipient BEGINS				
CRID	CRIDType simple type	-	Required;	Refer to this simple type in Section 5
Role	roleType simple type	-	Required	Refer to this simple type in Section 5
DataRecipient ENDS				

4.71 complexType: DocumentVersionData

Mail.XML 13.0B- complexType: DocumentVersionData				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
DocumentVersionData block BEGINS			Optional block; contains Version Summary Report information (0 to many pairings)	
VersionID	String, 10 characters		Required;	
VersionName	String, 12 characters		Required;	
VersionDescription	String, 30 characters		Optional	
PieceWeight	Double		Required The value of PieceWeight must be in Pounds.	
AdPercent	percentageType simple type		Optional; Percentage - max value 100.00.	Refer to this simple type in Section 5
RateAffixed	Double		Optional;	
StandardFlatType	standardFlatTypeType simple type	-	Optional	Refer to this simple type in Section 5
PMODIndicator	YesNo	Yes or No	Optional	-
MailCharacteristicsType	mailxml_defs:MailCharacteristicsType	Complex Type	Optional	
DocumentVersionData Block ENDS				

4.72 complexType: DocumentVersionDataWithPermit

Blocks Included: DocumentVersionDataWithPermit

Mail.XML 13.0B- complexType: DocumentVersionDataWithPermit				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
DocumentVersionData BEGINS			Required block; contains Version Summary Report information (1 to many pairings)	
VersionID	String, 10 characters		Required;	
VersionName	String, 12 characters		Required;	
VersionDescription	String, 30 characters		Optional	
PieceWeight	Double		Optional The value of PieceWeight must be in Pounds.	
AdPercent	PercentageType simple type		Optional; Percentage - max value 100.00.	Refer to this simple type in Section 5

Copyright © 2014 USPS®. All Rights Reserved

Mail.XML 13.0B- complexType: DocumentVersionDataWithPermit				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
StandardFlatType	standardFlatTypeType		Optional	Refer to this simple type in Section 5
RateAffixed	Double		Optional;	
PermitPublicationData	permitPublicationDataType complex type		Optional;	Refer to this complex type in Section 4
TotalCopies	Non-negative numeric		Required;	
TotalPieces	Non-negative numeric		Required;	
MailCharacteristicsType	mailxml_defs:MailCharacteristicsType	Complex Type	Optional	
DocumentVersionData Block ENDS				

4.73 complexType: ExtraServiceData

Mail.XML 13.0B- complexType: ExtraServiceData				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
extraServiceData BEGINS				
ServiceCode	serviceCodeType simple type	-	Required	Refer to this simple type in Section 5
ServiceRate	Double		Optional field up to four decimals	
ServiceSubCode	serviceSubCodeType simple type	-	Required	Refer to this simple type in Section 5
ServiceValue	Double		Required, up to two decimals	
TotalAmount	Double		Optional field, up to four decimals	
Collect Amount	Double		Required	
TotalPieces	Non-negative Integer		Required	
extraServiceData ENDS				

4.74 complexType: ExtraServiceSummaryData

Mail.XML 13.0B- complexType: ExtraServiceSummaryData				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
extraServiceSummaryData BEGINS				
LineLabel	String, 80 characters		Optional field	
LineNumber	String, 3 characters		Optional field This field will be ignored if populated; LineNumber will only be taken into account for Full-Service discount lines	
Section	String, 1 character		Optional field	
ServiceCode	serviceCodeType simple type	-	Optional	Refer to this simple type in Section 5

Copyright © 2014 USPS®. All Rights Reserved

Mail.XML 13.0B- complexType: ExtraServiceSummaryData				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
TotalAmount	Decimal		Required, up to three decimals	
CollectAmount	Double		Required	
TotalPieces	Non-negative Integer		Required	
USPSPackageUniqueCharacteristic	uspsPackageUniqueCharacteristicType simple type	-	Optional	Refer to this simple type in Section 5
Incentive	mailxml_base:characteristicIncentiveType		Optional	
Fee	mailxml_base:characteristicFeeType		Optional	
extraServiceSummaryData ENDS				

4.75 Complex Type: Fault

Complex Type: Fault				
Field	**Format**	**Acceptable Value**	**Business Rules**	**Comments**
Fault Block BEGINS				
Sequence Block BEGINS				
ErrorWarning	mailxml_defs:errorWarningType		Required	Refer to this complex type in Section 4
Sequence Block ENDS				
Attribute Group BEGINS				
TrackingID	mailxml_base:s20		Required	Refer to this simple type in Section 5
Attribute Group ENDS				
Fault Block ENDS				

4.76 complexType: FullContainerIDType

Mail.XML 13.0B- complexType: FullContainerIDType				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
FullContainerIDType Block begins				
Choice Block BEGINS			Required Either ULC/MaildatJObID OR CustomerGroupID/MailingGroupID is required	
UserLicenseCode	userLicenseCodeType simple type	-	Required; references existing Mail.dat container	Refer to this simple type in Section 5
MaildatJobID	jobIDType simple type		Required for Mail.dat submitted containers; references existing Mail.dat container	Refer to this simple type in Section 5
ContainerGroupID	String 25		Required;	
MailingGroupID	Non Negative Integer		Required for	

Copyright © 2014 USPS®. All Rights Reserved

Mail.XML 13.0B- complexType: FullContainerIDType				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
			Mail.XML submitted containers.	
Choice Block ENDS				
ContainerID	String 6		Optional. Cannot use existing ContainerID to identify a new container. 1 to many allowed.	
UniqueContainerBarcode	IMcbType simple type		Optional field; references existing Mail.dat container	Refer to this simple type in Section 5
FullContainerIDType Block ends			End of block	

4.77 complexType: FullComponentType

Mail.XML 13.0B- complexType: FullComponentType				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
FullComponentType BEGINS				
UserLicenseCode	userLicenseCodeType simple type	-	Required	Refer to this simple type in Section 5
MaildatJobID	jobIDType simple type	-	Required	Refer to this simple type in Section 5
ComponentID	String 8	-	Required	-
FullComponentType ENDS				

4.78 complexType: IntelligentMailBarcodeType

Mail.XML 13.0B- complexType: IntelligentMailBarcodeType				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
IntelligentMailBarcodeType Block begins			Required Only one block submitted	
BarcodeID	Number, 2 characters		Optional	
Choice Block BEGINS		-	Optional ServiceCode or MailClass	-
ServiceTypeCode	Mailxml_base:serviceTypeCodeTYpe		Conditionally required if Mail Class is not provided	Refer Section 5
MailClass	Mailxml_base:mailClassType		Conditionally required if Service Type Code is not provided	Refer Section 5
Choice Block ENDS				
Choice Block BEGINS			Required	
Sequence Block BEGINS				
MailerID6	Mailxml_base:mailerID6Type		Required Only one pairing of MailerID and SerialNumber is required	Refer Section 5

Copyright © 2014 USPS®. All Rights Reserved

Mail.XML 13.0B- complexType: IntelligentMailBarcodeType				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
SerialNumber9	iMBSerialNUmber9Type		Required Only one pairing of MailerID and SerialNumber is required	Refer Section 5
Sequence Block ENDS				
Sequence Block BEGINS				
MailerID9	mailerID9Type		Required Only one pairing of MailerID and SerialNumber is required	Refer Section 5
SerialNumber6	iMBSerialNumber6Type		Required Only one pairing of MailerID and SerialNumber is required	Refer Section 5
Sequence Block END				
Choice Block ENDS				
DeliveryPointZIP	RoutingZipCodeType		Not required	Refer Section 5
IntelligentMailBarcodeType Block ends				

4.79 complexType: IntelligentMailPackageBarcodeType

Mail.XML 13.0B- complexType: IntelligentMailPackageBarcodeType				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
IntelligentMailPackageBarcodeType Block BEGINS				
PostalRoutingCodeAppID	String 3	-	Required	-
DestinationZipCode	zipCodeFiveOrNineDigit Simple type	-	Required	Refer to this simple type in Section 5
ChannelApplicationIdentifier	String 2	-	Required	-
ServiceTypeCode	serviceTypeCodeType simple type	-	Required	Refer to this simple type in Section 5
Choice Block BEGINS			Required Either Sequence Block 1 or 2 is required	
Sequence Block 1 BEGINS				
MailerID6	Mailer6Type simple type		Required	Refer to this simple type in Section 5
SerialNumber10or14	serialNumberTenOrFourteen simple type			Refer to this simple type in Section 5
Sequence Block 1 ENDS				
Sequence Block 1 BEGINS				
MailerID9	Mailer9Type simple type			Refer to this simple type in Section 5

Copyright © 2014 USPS®. All Rights Reserved

Mail.XML 13.0B- complexType: IntelligentMailPackageBarcodeType				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
SerialNumber7or11	serialNumberSevenOrEleven simple type			Refer to this simple type in Section 5
Sequence Block 1 ENDS				
Mod10CheckDigit	String 1	-	Required	-
IntelligentMailPackageBarcodeType Block ENDS				

4.80 complexType:LargeTransactionDividerGroupOptionalType

Mail.XML 13.0B- complexType:LargeTransactionDividerGroupOptionalType				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
MessageGroupID	String 20	-	Optional	-
TotalMessageCount	Positive Integer	-	Optional	-
MessageSerialNumber	Positive Integer	-	Optional	-
TransmittedRecordCount	Positive Integer	-	Optional	-
TotalRecordsAcrossMessage	Positive Integer	-	Optional	-
LastMessage	yesNo simple type	Yes or No	Optional	-

4.81 complexType: LargeQualReportTransDividerType

Mail.XML 13.0B- complexType: LargeQualReportTransDividerType				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
LargeQualReportTransDividerType BEGINS				
CustomerQualificationReportID	String 66	-	Required	-
MessageGroupID	String 20	-	Required	-
MessageSequenceNumber	String 20	-	Required	-
TotalContainerInfoBlocksCount	PositiveInteger	-	Required	-
TotalDocVersionWithPermitBlocksCount	positiveInteger	-	Required	-
TransmittedContainerInfoCount	positiveInteger	-	Required	-
TransmittedDocVersionCount	positiveInteger	-	Required	-
TotalMessages	positiveInteger	-	Required	-
LastMessage	yesNo simple type	-	Optional	Refer to this simple type in Section 5
LargeQualReportTransDividerType ENDS	-	-	-	

Copyright © 2014 USPS®. All Rights Reserved

4.82 complexType: LineItemSummaryData

Blocks Included: LineItemSummaryData

Mail.XML 13.0B- complexType: LineItemSummaryData				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
LineItemSummaryData BEGINS			Optional field 0 to many can be submitted when ExtendedForm is False	
ProcessingCategory	Mailxml_base:processingCategoryType	Refer 'processingCategoryType' simple type	Optional, required for more than one processing category in a postage statement. Required field If FormType = BP, then the following values are valid: FL, NP, MP, IR If FormType = FC, then the following values are valid: LT, FL, CD, PF If FormType = ML, then the following values are valid: FL, NP, MP, IR If FormType = PM, then the following values are valid: LT, FL, PF If FormType = PP, then the following values are valid: MP, IR, NP If FormType = SM, then the following values are valid: LT, FL, MP, IR, NP, CM, NA, NB *if there are multiple weights and Letters and Post Cards as the processing categories then you must provide separate lineitems for cards and letters in this block.	Refer Section 5
BarcodeRate	Mailxml_base:barcodeRateType		Required	Refer Section 5
EntryDiscount	Mailxml_base:entryDiscountType		Required field If FormType = BP, then this field must be N, B, S, or D If FormType = FC, then this field must be N If FormType = ML,	Refer Section 5

Copyright © 2014 USPS®. All Rights Reserved

Mail.XML 13.0B- complexType: LineItemSummaryData				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
			then this field must be N If FormType = PM, then this field must be N If FormType = PP, then this field must be B, S, D, or N If FormType = SM, then this field must be N, B, S, or D	
LineLabel	String, 80 characters		Optional field	
LineNumber	String, 3 characters		Optional field This field will be ignored if populated; LineNumber will only be taken into account for Full-Service discount lines	
PiecePostage	Double		Optional field up to four decimal places	
PieceRate	Double		Optional field up to three decimal places	
MarketingOrFulfillmentType	Mailxml_base:marketingOrFulfillmentType		Optional	Refer Section 5
StandardFlatType	standardFlatTypeType simple type	-	Optional	Refer to this simple type in Section 5
SubtotalPostageAmount	Double		Required field up to four decimal places	
DiscountTotalAmount	Double		Required field up to four decimal places	
FeeTotalAmount	Double		Required field up to four decimal places	
StandardFlatType	Mailxml_base:standardFlatTypeType		Optional	Refer Section 5
TotalPostageAmount	Double		Required field up to four decimal places	
PoundPostage	Double		Optional field up to four decimal places	
PoundRate	Double		Optional field up to three decimal places	
PreparedAsSM	Mailxml_base:yesNo	Yes or No	Required The “True” indicates that mail is actually prepared as Standard when the RateCategory=S The “False” indicates that mail is actually prepared as First Class when the RateCategory=S	
RateCategory	Mailxml_base:rateCategoryType		Required field If FormType = BP, then this field must be D, N, or S If FormType = FC,	Refer Section 5

Copyright © 2014 USPS®. All Rights Reserved

Mail.XML 13.0B- complexType: LineItemSummaryData				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
			then this field must be E, H, L1, L2, L3, L4, N, or S If FormType = ML, then this field must be G, N, S If FormType = PM, then this field must be S If FormType = PP, then this field must be G, K, S, Z1, or Z2 If FormType = SM, then this field must be A, B, E, H, N, AF, BF, DF, L1, L2, L5, L6, L7, L8, NG, NK, N5, N6, PI, PM, P7, P8, PE, PQ, PR, PG, PK, P5, or P6	
Section	String, 1 character		Optional field	
SurchargeType	Mailxml_base:surchargeType		Required If FormType = BP, this field must be N If FormType = FC, this field must be A, E, N, or R If FormType = ML, this field must be N If FormType = PM, this field must be D, E, N, or P If FormType = PP, this field must be 2 or N If FormType = SM, this field must be L or N	Refer Section 5
TotalPieces	Non-negative Integer		Required	
SimplifiedAddressIndicator	mailxml_base: simplifiedAddressType	Y = Yes, M = Mixed, R = Residential only	Optional	
TotalWeight	Double		Optional field, up to four decimal places. The value of TotalWeight must be in Pounds.	
WeightBreakType	Mailxml_base:weightBreakType		Optional field. Required when piece weights are non-identical. If FormType is BP this field must be N. If FormType is FC this field must be A, B or N. If FormType is ML	Refer Section 5

Copyright © 2014 USPS®. All Rights Reserved

Mail.XML 13.0B- complexType: LineItemSummaryData				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
			this field must be N. If FormType is PM this field must be N. If FormType is PP this field must be N. If FormType is SM this field must be A, B or H.	
Zone	Mailxml_base:zoneICType		Optional field If FormType is BP, this field must be N, 1, 3, 4, 5, 6, 7, or 8, DDU, SCF If FormType is FC, this field must be N If FormType is ML, this field must be N If FormType is PM, this field must be N, 1, 3, 4, 5, 6, 7, or 8 If FormType is SM, this field must be N	Refer Section 5
FlatRateIndicator	mailxml_base:flatRateIndicatorType		Optional field If Form Type is PM this field must be B, E, L or M or S.	Refer Section 5
USPSPackageUniqueCharacteristic	Mailxml_base:uspsPackageUniqueCharacteristicType		Optional	Refer Section 5
MailCharacteristicsType	mailxml_defs:MailCharacteristicsType	Complex Type		
LineItemSummaryData Block END				

4.83 complexType: MailOwnerBlockType

Blocks Included: MailOwner

Mail.XML 13.0B- complexType: MailOwnerBlockType				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
MailOwnerBlockType BEGINS			Optional Block	
CRID	Mailxml_base:CRIDType	Refer simple type definition	Optional	Refer Section 5
SchedulerID	String 12	-	Optional	-
MaildatUserLicense	Mailxml_base:userLicenseCodeType	Refer simple type definition	Optional	Refer Section 5
PermitPublicationData Block	permitPublicationDataType	Refer complex type definition in Section 7	Optional	Refer Section 7
Choice Block BEGINS			Optional	
MailOwnerMID6	Numeric String 6	-	Either MailOwnerMID6 or MailOwnerMID9 is required when this	-

Copyright © 2014 USPS®. All Rights Reserved

Mail.XML 13.0B- complexType: MailOwnerBlockType				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
			choice block is used.	
MailOwnerMID9	Numeric String 9	-	Either MailOwnerMID6 or MailOwnerMID9 is required when this choice block is used.	
Choice Block ENDS				
MailOwnerBlockType ENDS				

4.84 complexType:MailPieceBlockGroupType

Mail.XML 13.0B- complexType:MailPieceBlockGroupType				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
MailPieceBlockGroup Type BEGINS				
ContainerID	String 6		Required	
ContainerDetailID	String 9		Optional. Links Qual, Postage, and Mailpiece data	-
BundleID	String 12		Optional	
MailPieceBlock	mailPieceBlockType complex type		Required 1 to many can be submitted	Refer to this complex type in Section 4
MailPieceBlockGroup Type ENDS				

4.85 complexType:MailPieceBlockType

Mail.XML 13.0B- complexType:MailPieceBlockType				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
MailPieceBlockType BEGINS				
ServiceLevelIndicator	serviceLevelIndicator Type		Required For Full-Service / Mixed Service mailings, the ServiceLevelIndicator field must be populated with 'F' when its associated ContainerID has the ServiceLevelIndicator field in the QualificationReportDetailCreateRequest message populated with 'F'.	Refer to this simple type in Section 5
Choice Block BEGINS			OPTIONAL. If provided then either LOTSequence Data or WalkSequence data should be provided.	-

Copyright © 2014 USPS®. All Rights Reserved

Mail.XML 13.0B- complexType:MailPieceBlockType				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
Sequence Block BEGINS				
LOTSequenceDirectionCode	String, 1 character		Either WalkSequenceNumber or combination of LOTSequenceDirectionCode and LOTSequenceNumber should be provided.	
LOTSequenceNumber	Number, 4 characters		Either WalkSequenceNumber or combination of LOTSequenceDirectionCode and LOTSequenceNumber should be provided	
Sequence Block ENDS				
WalkSequenceNumber	Number, 5 characters		Either WalkSequenceNumber or combination of LOTSequenceDirectionCode and LOTSequenceNumber	
Choice Block ENDS				
Choice Block BEGINS			Optional Either IMB or PlantCode with DeliveryPointZip OR DeliveryCOntainerID with DeliveryPointZip is required, if this choice block is used.	
IMB Block	IntelligentMailBarcodeType		Required Block. Only one occurrence is allowed	Refer to this complex type in Section 4
Sequence Block BEGINS				
PlanetCode	planetCodeType simple type		Not required	Refer to this simple type in Section 5
DeliveryPointZIP	:routingZipCodeType		Conditionally required if PlanetCode is submitted	Refer to this simple type in Section 5
Sequence Block ENDS				
Sequence Block BEGINS				
DeliveryContainerID	Numeric string, 22 characters		Field not being supported	
DeliveryPointZIP	routingZipCodeType	Refer 'routingZipCodeType' simple type	Field not being supported in conjunction with DeliveryContainerID	Refer to this simple type in Section 5
Sequence Block ENDS				

Copyright © 2014 USPS®. All Rights Reserved

Mail.XML 13.0B- complexType:MailPieceBlockType				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
Choice Block ENDS				
PieceID	String, 22 characters		Required	
WastedPieceIndicator	wastedPieceIndicator Type		Not required	Refer to this simple type in Section 5
MLOCRrateANDpostageMarking	String, 7 characters		Not required	
MoveComplianceUpdateMethod	moveUpdateMethodType		Not required	Refer to this simple type in Section 5
MailOwner	mailOwnerBlockType complex type		Optional Block	See this complex type in Section 7
BarCodeApplicator Block	ParticipantIDType complex type	-	Optional	See this complex type in Section 7
MachineID	String, 4 characters		Optional	
ACSKeyline	String, 16 characters		Optional	
HoldForPickup	yesNo simple type	-	Optional	Refer to this simple type in Section 5
NumberOfPiecesToHold	positiveInteger	-	Optional	-
MailPieceBlockType ENDS				

4.86 complexType: MailerDataType

Blocks Included:

- PermitHolderData
- MailingOwnerData
- MailingAgentData
- PermitHolderForAPData
- PublisherData

Mail.XML 13.0B- complexType: MailerDataType				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
MailerDataType Block begins				
Address1	String 64		(1-1) Required	
Address2	String 64		(0-1) Optional	
City	String 45		(0-1) Optional	
Country	String 45		(0-1) Optional	
DunsNumber	String 20		(0-1) Optional	
Email	Email		(0-1) Optional	
MID Block	Complex			See MIDType in Section 7 for Details
CRID	CRIDType		Optional	Refer to this simple type in Section 5
ContactName	String, 60 characters		Required	USPS ignores this contact name and picks up the contact info tied to the permit in the permit system.
PermitPublicationData Block	Complex		Optional	See PermitPublicationDataType in Section 7 for Details

Copyright © 2014 USPS®. All Rights Reserved

Mail.XML 13.0B- complexType: MailerDataType				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
PhoneAreaCode	String Exactly 3		Required	
PhoneExtension	String 5		Optional	
PhoneLast4	String Exactly 4		Required	
PhonePrefix	String Exactly 3		Required	
State	Mailxml_base:StateCode	Refer Section 5 for this simple type definition	Optional	Refer Section 5
ZipCode	Numeric String, 9		Required	
ZipCode4	String Exactly 4		Optional	
MailerDataType Block ends				

4.87 complexType: MailerDataRequestType

Mail.XML 13.0B- complexType: MailerDataRequestType				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
MailerDataRequestType Block begins				
MID	MIDType complex type		Optional Block	Refer to this complex type in Section 4
CRID	CRIDType simple type	-	Optional	Refer to this simple type in Section 5
ContactName	String, 60 characters		Required	
PermitPublicationData	permitPublicationDataType complex type		Required	Refer to this complex type in Section 4
MailerDataRequestType Block ENDS				

4.88 complexType: MailerSerialNumberBlockType

Mail.XML 13.0B- complexType: MailerDataRequestType				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
MailerSerialNumberBlockType BEGINS				
Choice Block BEGINS			Required Either MailerID6/SerialNumber9 OR MailerID9/SerialNumber6 is allowed	
MailerID6	MailerID6Type simple type	-	Required	Refer to this simple type in Section 5
SerialNumber9	iMBSerialNumber9Type simple type	-	Required	Refer to this simple type in Section 5
MailerID9	MailerID9Type simple type	-	Required	Refer to this simple type in Section 5
SerialNumber6	iMBSerialNumber6Type simple type	-	Required	Refer to this simple type in Section 5
Choice Block ENDS				
DeliveryPointZip	RoutingZipCodeType simple type	-	Optional	Refer this simple type Section 5
MailerSerialNumberBlockType ENDS				

Copyright © 2014 USPS®. All Rights Reserved

4.89 complexType:MailingGroupDataType

Mail.XML 13.0B- complexType:MailingGroupDataType				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
MailingGroupDataType BEGINS				
CustomerDescription	String 50	-	Optional	-
SubmitterCRID	CRIDType simple type	-	Required	Refer to this simple type in Section 5
PermitPublicationData	permitPublicationDataType complex type	-	Required	Refer to this complex type in Section 4
PostOfficeOfMailingZip	Exact String 5	-	Required	-
MailingFacility	CRIDType simple type	-	Optional	Refer to this simple type in Section 5
MailXMLPresentationCategory	mailXMLPresentationCategoryType simple type	-	Required	Refer to this simple type in Section 5
MailerID	String	-	Optional	-
FullServiceParticipationIndicator	fspiType simple type	-	Optional	Refer to this simple type in Section 5
MailAgreementType	mailAgreementTypeType simple type	-	Optional	Refer to this simple type in Section 5
ContractNumber	String 20	-	Optional	-
OnePassIndicator	yesNo simple type	-	Optional	Refer to this simple type in Section 5
LogicalPhysicalContainerIndicator	LogicalPhysicalContainerIndicatorType simple type	-	Optional	Refer to this simple type in Section 5
MailingGroupDataType ENDS				

4.90 complexType: MailingGroupSummary

Mail.XML 13.0B- complexType: MailingGroupSummary				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
MailingGroupSummary BEGINS				
MailerJOBID	String	-	Required	-
BeginDate	DateTime	-	Required	
EndDate	DateTime	-	Required	-
OpenDate	DateTime	-	Required	-
CloseDate	DateTime	-	Required	-
PreparerName	String	-	Required	-
PreparerCRID	CRIDType simple type	-	Required	Refer to this simple type in Section 5
Origin	String	-	Required	-
Description	String	-	Required	-
MailingGroupSummary ENDS				

4.91 complexType: MIDType

Blocks Included: MID

Mail.XML 13.0B- complexType: MIDType				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**

Copyright © 2014 USPS®. All Rights Reserved

Mail.XML 13.0B- complexType: MIDType				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
MIDType Block begins			Contains six or nine digit MIDs	
MID6	String, 6 characters		Conditionally required if MID9 is not submitted	
MID9	String, 9 characters		Conditionally required if MID6 is not submitted	
MIDType Block ends				

4.92 attributeGroup: MailXMLOpenMailGroupRequestHeaderInfo

Mail.XML 13.0B- attributeGroup: MailXMLOpenMailGroupRequestHeaderInfo				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
CustomerGroupID	String 25		Required	-

4.93 attributeGroup: MailXMLMailOpenGroupResponseAcceptHeaderInfo

Mail.XML 13.0B- attributeGroup: MailXMLMailOpenGroupResponseAcceptHeaderInfo				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
CustomerGroupID	String 25		Required	-
MailingGroupID	nonNegativeInteger	-	Required	-
Status	statusType simple type	-	Optional	Refer to this simple type in Section 5

4.94 attributeGroup: MailXMLMailOpenGroupResponseRejectHeaderInfo

Mail.XML 13.0B- attributeGroup: MailXMLMailOpenGroupResponseRejectHeaderInfo				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
CustomerGroupID	String 25		Required	-
MailingGroupID	nonNegativeInteger	-	Required	-
Status	statusType simple type	-	Optional	Refer to this simple type in Section 5

4.95 attributeGroup: MailXMLDashboardHeaderInfo

Mail.XML 13.0B- attributeGroup: MailXMLDashboardHeaderInfo				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
CustomerGroupID	String 25		Required	-
MailingGroupID	nonNegativeInteger	-	Required	-

4.96 attributeGroup: MailXMLMailGroupRequestHeaderInfo

Mail.XML 13.0B- attributeGroup: MailXMLMailGroupRequestHeaderInfo

Copyright © 2014 USPS®. All Rights Reserved

Field	Format	Acceptable Values	Business Rules	Comments
CustomerGroupID	String 25		Required	-
MailingGroupID	nonNegativeInteger	-	Required	-

4.97 attributeGroup: MailXMLMailGroupResponseHeaderInfo

Mail.XML 13.0B- attributeGroup: MailXMLMailGroupResponseHeaderInfo				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
CustomerGroupID	String 25		Required	-
MailingGroupID	nonNegativeInteger	-	Required	-
Status	statusType simple type	-	Optional	Refer to this simple type in Section 5

4.98 attributeGroup: MailXMLHeaderInfo

Mail.XML 13.0B- attributeGroup: MailXMLHeaderInfo				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
User License Code	UserLicenseCode simple type		Optional	Refer to this simple type in Section 5
Maildat Job ID	jobIDType simple type	-	Optional	Refer to this simple type in Section 5
Customer Group ID	String, 25 character	-	Optional	-
Mailing Group ID	Non Negative Integer	-	Optional	-

4.99 attributegroup: MailXMLMsgResponseHeaderInfo

Mail.XML 13.0B- attributegroup: MailXMLMsgResponseHeaderInfo				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
MailXMLMsgResponseHeaderInfo Block begins			Attributes block	
CustomerGroupID	String, 25 characters		Required (attribute)	
MailingGroupID	Non-negative Integer		Required (attribute)	
Status	StatusType simple type	-	Optional	Refer to this simple type in Section 5
MailXMLMsgResponseHeaderInfo Block ends				

4.100 attributeGroup: MailXMLPieceRangeBlockType

Mail.XML 13.0B- attributeGroup: MailXMLPieceRangeBlockType				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
MailXMLPieceRangeBlockType BEGINS				
ContainerID	String 6		Required 1 to many allowed	
PieceRangeBlock Block BEGINS			Required 1 to many can be submitted	

Copyright © 2014 USPS®. All Rights Reserved

Mail.XML 13.0B- attributeGroup: MailXMLPieceRangeBlockType				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
PieceRangeID	String 22		Required	
IMBarcodeLowerSerialization Block begins			Required Only one can be submitted	
Choice Block BEGINS				
Sequence Block # 1 BEGINS				
MailerID6	mailerID6Type		Required Only one pairing of MailerID and SerialNumber is required If provided, MailerID6 fields must be the same in the IMbarcodeUpperSerialization and IMbarcodeLowerSerialization blocks	Refer Section 5
SerialNumber9	iMBSerialNumber9Type		Required Only one pairing of MailerID and SerialNumber is required	Refer Section 5
Sequence Block # 1 ENDS				
Sequence Block # 2 BEGINS				
MailerID9	mailerID9Type		Required Only one pairing of MailerID and SerialNumber is required If provided, MailerID9 fields must be the same in the IMbarcodeUpperSerialization and IMbarcodeLowerSerialization blocks	Refer Section 5
SerialNumber6	iMBSerialNumber6Type		Required Only one pairing of MailerID and SerialNumber is required	Refer Section 5
Sequence Block # 2 ENDS				
Choice Block ENDS				
IMBarcodeLowerSerialization Block ends				
IMBarcodeUpperSerialization Block begins			Required Only one can be submitted	
Choice Block BEGINS				
Sequence Block				

Copyright © 2014 USPS®. All Rights Reserved

Mail.XML 13.0B- attributeGroup: MailXMLPieceRangeBlockType				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
BEGINS				
MailerID6	mailerID6Type		Required Only one pairing of MailerID and SerialNumber is required If provided, MailerID6 fields must be the same in the IMbarcodeUpperSerialization and IMbarcodeLowerSerialization blocks	Refer Section 5
SerialNumber9	iMBSerialNumber9Type		Required Only one pairing of MailerID and SerialNumber is required	
Sequence Block ENDS				
Sequence Block BEGINS				
MailerID9	mailerID9Type		Required Only one pairing of MailerID and SerialNumber is required If provided, MailerID9 fields must be the same in the IMbarcodeUpperSerialization and IMbarcodeLowerSerialization blocks	Refer Section 5
SerialNumber6	iMBSerialNumber6Type		Required Only one pairing of MailerID and SerialNumber is required	
Sequence Block ENDS				
Choice Block ENDS				
IMBarcodeUpperSerialization Block ends				
MailPreparer Block	ParticipantIDType		Conditionally required for Full-Service mailings. If not provided then user will get Full-Service compliance error and no Full-Service data feedback will be available to the mailer.	See Section 7 for Details
MailOwner Block	ParticipantIDType		Conditionally required for Full-Service mailings. If not	See Section 7 for Details

Copyright © 2014 USPS®. All Rights Reserved

Mail.XML 13.0B- attributeGroup: MailXMLPieceRangeBlockType				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
			provided then user will get Full-Service compliance error and no Full-Service data feedback will be available to the mailer.	
Choice Block BEGINS			Required ServiceCode or MailClass	
ServiceTypeCode	serviceTypeCodeType		Conditionally required for Full-Service / Mixed Service mailings if Mail Class is not provided.	Refer Section 5
MailClass	mailClassType		Conditionally required for Full-Service / Mixed Service mailings if Service Type Code is not provided.	Refer Section 5
Choice Block ENDS				
ServiceLevelIndicator	serviceLevelIndicatorType		Required For Full-Service / Mixed Service mailings, the ServiceLevelIndicator field must be populated with 'F' when its associated ContainerID has the ServiceLevelIndicator field in the QualificationReportDetailCreateRequest message populated with 'F'.	Refer Section 5
Pieces	Non-Negative Integer		Required 1 to many allowed If the FullServiceParticipationIndicator field is populated with a 'F', then the IMbarcodeUpperSerialization block minus the IMbarcodeLowerSerialization block is equal to the piece count and the copy count.	
Copies	Non-Negative Integer		Required 1 to many allowed If the FullServiceParticipationIndicator field is populated with a 'F',	

Copyright © 2014 USPS®. All Rights Reserved

Mail.XML 13.0B- attributeGroup: MailXMLPieceRangeBlockType				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
			then the IMbarcodeUpperSerialization block minus the IMbarcodeLowerSerialization block is equal to the piece count and the copy count.	
PieceRangeBlock Block ENDS				
MailXMLPieceRangeBlockType ENDS				

4.101 complexType: MPSRResponseBlockType

Blocks Included: MPSRResponseBlockType

Mail.XML 13.0B- complexType: MPSRResponseBlockType				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
MPSRResponseBlockType BEGINS				
ContainerID	mailxml_base:s06			
FullServiceIndicator	mailxml_base:yesNo	Yes No	Optional	
PSRResponseBlock	mailxml_defs:PSRResponseBlockType			
MPSRResponseBlockType ENDS				

4.102 attributeGroup: MailXMLPostageStatementResponseHeaderInfo

Mail.XML 13.0B- attributeGroup: MailXMLPostageStatementResponseHeaderInfo				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
MailXMLPostageStatementResponseHeaderInfo Block BEGINS			Attributes block; Required	
CustomerGroupID	String, 25 characters		Required (attribute)	
MailingGroupID	Non-negative Integer		Required (attribute)	
Status	Mailxml_base:statusType	Refer simple type definition in Section 5	Optional	Refer Section 5
MailXMLPostageStatementResponseHeaderInfo Block ENDS				

4.103 attributeGroup: MailXMLPostageStatementRequestHeaderInfo

Mail.XML 13.0B- attributeGroup: MailXMLPostageStatementRequestHeaderInfo				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
MailXMLPostageStatementRequestHeaderInfo Block BEGINS			Attributes block; Required	

Copyright © 2014 USPS®. All Rights Reserved

Mail.XML 13.0B- attributeGroup: MailXMLPostageStatementRequestHeaderInfo				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
CustomerGroupID	String, 25 characters		Required (attribute)	
MailingGroupID	Non-negative Integer		Required (attribute)	
IssueDate	Date	-	Optional	-
IssueNumber	String 6	-	Optional	-
VolumeNumber	String 5	-	Optional	-
CustomerReferenceID	String 40	-	Optional	CustomerReferenceID represents CAPS Account Number
AgencyCostCode	agencyCostCodeType simple type	-	Optional	Refer this simple type Section 5
PermitNumber	String 8	-	Optional	-
PermitType	permitTypeType simple type	-	Optional	Refer to this simple type in Section 5
PermitZip4	Numeric String 9	-	Optional	-
PublicationNumber	String 8	-	Optional	
PostageStatementMethod	postagePaymentMethodType simple type	-	Optional	Refer to this simple type in Section 5
RateType	RateType simple type	-	Optional	Refer to this simple type in Section 5
ProcessingCategory	processingCategoryType simple type	-	Optional	Refer to this simple type in Section 5
MailXMLPostageStatementRequestHeaderInfo Block ENDS				

4.104 attributeGroup: MailXMLQualReportRequestHeaderInfo

Mail.XML 13.0B- attributeGroup: MailXMLQualReportRequestHeaderInfo				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
MailXMLQualReportRequestHeaderInfo block begins				
CustomerGroupID	String, 25 characters		Required field; must be populated with the same value as the CustomerGroupID in the OpenMailingGroupRequest message	
MailingGroupID	Non-Negative Integer		Required field; must be populated with the same value as the MailingGroupID in the OpenMailingGroupRequest message	
Replace	yesNo	Yes No	Optional field	
MixedMailFlag	yesNo	Yes or No	Required. To identify the mixed mailing.	-
TotalMessageCount	positiveInteger	-	Optional	-
TotalDocVersionsWithPermitBlocksCount	nonNegativeInteger	-	Required	
LastMessage	yesNo	Yes No	Optional	

Copyright © 2014 USPS®. All Rights Reserved

Mail.XML 13.0B- attributeGroup: MailXMLQualReportRequestHeaderInfo				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
MailXMLQualReportRequestHeaderInfo ENDS				

4.105 attributeGroup: MailXMLQualReportResponseHeaderInfo

Mail.XML 13.0B- attributeGroup: MailXMLQualReportResponseHeaderInfo				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
MailXMLQualReportResponseHeaderInfo block begins				
CustomerGroupID	String, 25 characters		Required field; must be populated with the same value as the CustomerGroupID in the OpenMailingGroupRequest message	
MailingGroupID	Non-Negative Integer		Required field; must be populated with the same value as the MailingGroupID in the OpenMailingGroupRequest message	
MessageSequenceNumber	String 20	-	Optional field	
MailXMLQualReportResponseHeaderInfo ENDS				

4.106 complexType: ManifestErrorWarningDetailType

Mail.XML 13.0B- complexType: ManifestErrorWarningDetailType				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
ManifestErrorWarningDetailType complexType BEGINS				
sequence block BEGINS				
ErrorWarningCode	mailxml_mm:ErrorWarningCodeType		optional	
ElectronicFileLineNumber	mailxml_base:ns09		optional	
IMpb	mailxml_base:IMpbType		optional	
DescriptionElectronicFileErrorWarning	mailxml_base:s34		optional	
ErrorWarningMessage	mailxml_base:s60		optional	
sequence block ENDS				
ManifestErrorWarningDetailType complexType ENDS				

Copyright © 2014 USPS®. All Rights Reserved

4.107 complexType: ManifestErrorWarningSummaryType

Mail.XML 13.0B- complexType: ManifestErrorWarningSummaryType				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
ManifestErrorWarningSummaryType complextype BEGINS				
sequence block BEGINS				
MID	mailxml_defs:MIDType		optional	
ElectronicFileSequenceNumber	mailxml_base:ns14		optional	
ElectronicFileReceiptDate	xs:date		optional	
ElectronicFileReceiptTime	xs:time		optional	
EntryFacilityZipCode	mailxml_base:ns05		optional	
MailingDate	xs:date		optional	
NumberOfRecordsRead	mailxml_base:ns09		optional	
NumberOfRecordsRejected	mailxml_base:ns09		optional	
NumberOfRecordsAccepted	mailxml_base:ns09		optional	
NumberOfElectronicFileD1RecordRecordsAccepted	mailxml_base:ns09		optional	
NumberOfElectronicFileD2RecordRecordsAccepted	mailxml_base:ns09		optional	
SummaryMessage	mailxml_base:s60		optional	
ManifestErrorWarningDetail	mailxml_mm:ManifestErrorWarningDetailType		optional, unbounded	
sequence block ENDS				
ManifestErrorWarningSummaryType complextype ENDS				

4.108 complexType: manifestMailType

Mail.XML 13.0B- complexType: manifestMailType				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
manifestMailType complexType block BEGINS				
Sequence Block BEGINS				
HeaderRecordID	mailxml_base:s02			
ManifestIDNumber	mailxml_base:ns22			
ElectronicFileType	mailxml_base:electronicFileType			
USPSElectronicFileVersionNumber	mailxml_base:ns03			
ElectronicFileNumber	mailxml_base:ns34			
DateOfMailing	xs:date			

Copyright © 2014 USPS®. All Rights Reserved

Mail.XML 13.0B- complexType: manifestMailType				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
TimeOfMailing	xs:time			
EntryFacilityType	mailxml_base:entryFacilityType			
EntryFacilityZipCode	mailxml_base:ns05			
EntryFacilityZipPlusFour	mailxml_base:s09		Optional	
DirectEntryOriginCountryCode	mailxml_base:s02		Optional	
ShipmentFeeCode	mailxml_base:s03		Optional	
ExtraFeeForShipment	mailxml_base:ns06		Optional	
FileRecordCount	xs:nonNegativeInteger			
SoftwareVendorProductVersion	mailxml_base:s08			
SoftwareVendorCode	mailxml_base:s04			
TransactionID	mailxml_base:s12		Optional	
Sequence Block BEGINS				
TrackingInformation	mailxml_mm:ManifestTrackingInformationType		Optional, Unbounded	
PaymentInformation	mailxml_mm:paymentInformationType		Optional, Unbounded	
SpecialProductInformation	mailxml_mm:specialProductInformationType		Optional, Unbounded	
Sequence Block ENDS				
Sequence Block ENDS				
manifestMailType complexType block ENDS				

4.109 complexType: ManifestTrackingInformationType

Mail.XML 13.0B- complexType: ManifestTrackingInformationType				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
ManifestTrackingInformationType block BEGINS				
Sequence block BEGINS				
DetailRecordID	mailxml_base:s02			
IMpb	mailxml_base:IMpbType			
MailClass	mailxml_base:mailClassType			
ServiceTypeCode	mailxml_base:ServiceTypeCodeType			
BarCodeConstructCode	mailxml_base:s04			
DestinationZipCode	mailxml_defs:zipCode			
DestinationZipPlusFo	mailxml_base:s09		Optional	

Copyright © 2014 USPS®. All Rights Reserved

Mail.XML 13.0B- complexType: ManifestTrackingInformationType				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
ur				
DestinationFacilityType	mailxml_base:s01		Optional	
DestinationCountryCode	mailxml_base:s02			
PostalCode	mailxml_base:s11			
CarrierRoute	mailxml_base:s05			
LogisticsManagerMID	mailxml_defs:MIDType			
MailOwnerMID	mailxml_defs:MIDType			
ContainerID1	mailxml_base:iMBType			
ContainerType1	mailxml_base:s02			
ContainerType2	mailxml_base:s02			
ContainerID2	mailxml_base:iMBType			
ContainerType3	mailxml_base:s02			
ContainerID3	mailxml_base:iMBType			
MailOwnerCRID	mailxml_base:CRIDType			
CustomerReferenceID	mailxml_base:s30			
FASTReservationNumber	mailxml_base:s15			
FASTScheduledInductionDate	mailxml_base:scheduledInductionDateType			
FASTScheduledInductionTime	xs:time			
Sequence block ENDS				
ManifestTrackingInformationType block ENDS				

4.110 complexType: palletContainerVersionRecordType

Mail.XML 13.0B- complexType: palletContainerVersionRecordType				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
PalletContainerVersionRecords block begins			Optional block; 0 to many pairings can be submitted depending upon the number of PalletMPURecords (used for Pallet charges)	
DocumentVersionData	DocumentVersionData complex type		Required	Refer to this complex type in Section 4
PublicationInfo	permitPublicationDataType complex type		Required	Refer to this complex type in Section 4
PublicationTitle	String, 60 characters		Required	
PostageStatementLineNumber	postageStatementLineNumber1Type		Optional field; uses the Container Level and Entry level to find the lines	Refer to this simple type in Section 5

Copyright © 2014 USPS®. All Rights Reserved

Mail.XML 13.0B- complexType: palletContainerVersionRecordType				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
ChargeableContainer Level	chargeableContainer LevelType		Required field; <BLANK> = NULL is not supported	Refer to this simple type in Section 5
ChargeableEntryLeve l	chargeableEntryLevel Type		Required field; <BLANK> = NULL is not supported	Refer to this simple type in Section 5
Containers	Double		Required	
IssueDate	Date	YYYY-MM-DD	Required	
IssueNumber	String, 6 characters		Optional	
VolumeNumber	String, 5 characters		Optional	
PalletContainerVersio nRecords block ends				

4.111 complexType: palletContainerRecordType

Mail.XML 13.0B- complexType: palletContainerRecordType				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
PalletContainerRecor ds block begins			Optional block; 0 to many pairings can be submitted depending upon the number of PalletMPURecords (used for Pallet charges)	
PublicationInfo	permitPublicationDat aType complex type		Required	Refer to this complex type in Section 4
PublicationTitle	String, 60 characters		Required	
PostageStatementLin eNumber	postageStatementLin eNumber1Type		Optional field; uses the Container Level and Entry level to find the lines	Refer to this simple type in Section 5
ChargeableContainer Level	chargeableContainer LevelType		Required field; <BLANK> = NULL is not supported	Refer to this simple type in Section 5
ChargeableEntryLeve l	chargeableEntryLevel Type		Required field; <BLANK> = NULL is not supported	Refer to this simple type in Section 5
Containers	Double		Required	
IssueDate	Date	YYYY-MM-DD	Required	
IssueNumber	String, 6 characters		Optional	
VolumeNumber	String, 5 characters		Optional	
PalletContainerRecor ds block ends				

4.112 complexType: paymentInformationType

Mail.XML 13.0B- complexType: paymentInformationType				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
paymentInformationT ype complexType block BEGINS				
sequence block BEGINS				

Copyright © 2014 USPS®. All Rights Reserved

Mail.XML 13.0B- complexType: paymentInformationType				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
PaymentAccountNumber	mailxml_base:ns10		optional	
PaymentMethod	mailxml_mm:postagePaymentMethodType		optional	
CSSCProductID	mailxml_base:s14		optional	
CSSCNumber	mailxml_base:s22		optional	
ProcessingCategory	mailxml_base:processingCategoryType		optional	
RateIndicaror	mailxml_base:s02		optional	
Height	xs:double		optional	
Width	xs:double		optional	
Length	xs:double		optional	
ExtraServiceFeeFifthService	xs:double"			
ExtraServiceFeeFourthService	xs:double"			
ExtraServiceFeeThirdService	xs:double"			
ExtraServiceFeeSecondService	xs:double"			
ExtraServiceFeeFirstService	xs:double"			
ExtraServiceCodeFifthService	mailxml_base:s03"			
ExtraServiceCodeFourthService	mailxml_base:s03"			
ExtraServiceCodeThirdService	mailxml_base:s03"			
ExtraServiceCodeSecondService	mailxml_base:s03"			
ExtraServiceCodeFirstService	mailxml_base:s03"			
ValueOfArticle	xs:double"			
CODAmountDueSender	xs:double"			
HandlingCharge	xs:decimal"			
SurchargeType	mailxml_base:surchargeType"			
SurchargeAmount	xs:double		optional	
NonIncidentalEnclosureRateIndicator	mailxml_mm:manifestRateLevelIndicatorType		optional	
NonIncidentalEnclosureClass	mailxml_mm:manifestMailClassType		optional	
NonIncidentalEnclosurePostage	xs:double		optional	
NonIncidentalEnclosureWeight	xs:double		optional	
NonIncidentalEnclosureProcessingCategory	mailxml_base:processingCategoryType		optional	
POBoxIndicator	mailxml_base:yesNo"			
SignatureWaiver	mailxml_base:yesNo		Optional	
PostalRoutingBarcode	mailxml_base:s01		Optional	

Copyright © 2014 USPS®. All Rights Reserved

Mail.XML 13.0B- complexType: paymentInformationType				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
OpenDistributeContentsIndicator	mailxml_base:s02		Optional	
DeliveryOptionIndicator	mailxml_base:s01		Optional	
DestinationDeliveryPoint	mailxml_base:ns02"			
DiscountAmount	xs:double		Optional	
DiscountType	mailxml_base:s02		Optional	
DimensionalWeight	mailxml_base:weightUnitType		Optional	
Zone	mailxml_base:zoneICType		Optional	
DestinationRateInd	mailxml_mm:manifestRateLevelIndicatorType		Optional	
PieceWeight	xs:double		Optional	
WeightUnit	mailxml_base:weightUnitType		Optional	
PostageType	mailxml_base:s01		Optional	
Postage	xs:double		Optional	
ChargebackCode	mailxml_base:s06		Optional	
MeterSerialNumber	mailxml_base:s20		Optional	
PostOfficeOfAccountZipCode	mailxml_base:ns05		Optional	
sequence block ENDS				
paymentInformationType complexType block ENDS				

4.113 complexType: PieceBarcodeRecordBlockType

Mail.XML 13.0B- complexType: PieceBarcodeRecordBlockType				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
PieceBarcodeRecordBlockType BEGINS				
PieceBarcodeRecordUniqueID	Integer	-	Required	-
ContainerID	String 6	-	Required	-
ContainerDetailID	String 9	-	Required	-
BundleID	String 6	-	Optional	-
MailerSerialNumberBlock	mailerSerialNumberBlockType complex type	-	Required	Refer to this complex type in Section 4
WastedPieceIndicator	WastedPieceIndicatorType simple type	-	Optional	Refer to this simple type in Section 5
PackageID	packageIDType simple type	-	Required	Refer to this simple type in Section 5
CQTDatabaseID	CQTDatabaseIDType simple type	-	Required	Refer to this simple type in Section 5
Choice Block BEGINS			Required Either IMB or IMPackageBarcode	
IMB	intelligentMailBarcodeType complex type	-	Required	Refer to this complex type in Section 4

Copyright © 2014 USPS®. All Rights Reserved

Mail.XML 13.0B- complexType: PieceBarcodeRecordBlockType				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
IMPackageBarcode	intelligentMailPackageBarcodeType complex type	-	Required	Refer to this complex type in Section 4
Choice Block ENDS				
PieceBarcodeRecordBlockType ENDS				

4.114 complexType: PieceBarcodeRecordBlockForMailXMLType

Mail.XML 13.0B- complexType: PieceBarcodeRecordBlockForMailXMLType				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
PieceBarcodeRecordBlockForMailXMLType BEGINS				
PieceBarcodeRecordUniqueID	Integer	-	Required	-
ContainerID	String 6	-	Required	-
ContainerDetailID	String 9	-	Required	-
BundleID	String 6	-	Optional	-
MailerSerialNumberBlock	mailerSerialNumberBlockType complex type	-	Required	Refer to this complex type in Section 4
WastedPieceIndicator	WastedPieceIndicatorType simple type	-	Optional	Refer to this simple type in Section 5
Choice Block BEGINS			Required Either IMB or IMPackageBarcode	
IMB	intelligentMailBarcodeType complex type	-	Required	Refer to this complex type in Section 4
IMPackageBarcode	intelligentMailPackageBarcodeType complex type	-	Required	Refer to this complex type in Section 4
Choice Block ENDS				
PieceBarcodeRecordBlockForMailXMLType ENDS				

4.115 complexType: pieceLiteRecordBlockType

Mail.XML 13.0B- complexType: pieceLiteRecordBlockType				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
pieceLiteRecordBlockType BEGINS				
CustomerQualificationReportID	String 66	-	Optional	-
ContainerID	String 6	-	Optional	-
ContainerDetailID	String 9	-	Optional	-
PieceLite	pieceLiteBlockType complex type	-	Required	Refer to this complex type in Section 4
WastedPieceIndicator	wastedPieceIndicatorType simple type	-	Optional	Refer to this simple type in Section 5
PackageID	packageIDType simple type	-	Required	Refer to this simple type in Section 5
CQTDatabaseID	CQTdatabaseIDType simple type	-	Optional	Refer to this simple type in Section 5

Copyright © 2014 USPS®. All Rights Reserved

Mail.XML 13.0B- complexType: pieceLiteRecordBlockType				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
pieceLiteRecordBlock Type ENDS				

4.116 complexType: pieceLiteBlockType

Mail.XML 13.0B- complexType: pieceLiteBlockType				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
pieceLiteBlockType BEGINS				
Choice Block BEGINS			Either mailerID6 and SerialNumber 9 or mailerID9 and SerialNumber 6 is required	
Sequence Block # 1 BEGINS				
MailerID6	mailID6Type simple type	-	Required	Refer to this simple type in Section 5
SerialNumber9	iMBSerialNumber9Type simple type	-	Required	Refer to this simple type in Section 5
Sequence Block # 1 ENDS				
Sequence Block # 2 BEGINS				
MailerID9	mailerID9Type simple type	-	Required	Refer to this simple type in Section 5
SerialNumber6	iMBSerialNumber6Type simple type	-	Required	Refer to this simple type in Section 5
Sequence Block # 2 ENDS				
Choice Block ENDS				
DeliveryPointZip	RoutingZipCodeType simple type	-	Optional	Refer to this simple type in Section 5
pieceLiteBlockType ENDS				

4.117 complexType: PeriodicalLineItemData

Mail.XML 13.0B- complexType: PeriodicalLineItemData				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
PeriodicalLineItemData BEGINS				
Copies	nonNegativeInteger	-	Optional	-
ContainerDetailID	String 9	-	Optional field; Required for Full-Service mailings (mixed allowed), and Non Full-Service with containers marked for eInduction	-
DiscountQty	Double	-	Optional	-
PeriodicalPrice	periodicalPriceType simple type	-	Optional	Refer to this simple type in Section 5
InOutCountyIndicator	inCountyOutCountyIndicatorType	-	Required	-
LineLabel	String 80	-	Optional	-

Copyright © 2014 USPS®. All Rights Reserved

Mail.XML 13.0B- complexType: PeriodicalLineItemData				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
LineNumber	String 3	-	Optional This field will be ignored if populated; LineNumber will only be taken into account for Full-Service discount lines	-
NonCopies	nonNegativeInteger	-	Optional	-
PieceRate	Double	-	Optional	-
Pieces	nonNegativeInteger	-	Optional	-
PostageAmount	Double	-	Optional	-
PoundRate	Double	-	Optional	-
RateCategory	rateCategoryType simple type	-	Optional	Refer to this simple type in Section 5
Section	String 1	-	Optional	-
SubreqCopies	nonNegativeInteger	-	Optional	-
Zone	zoneICType simple type	-	Optional	Refer to this simple type in Section 5
ChargeableContainer Type	chargeableContainer Type simple type	-	Optional	Refer to this simple type in Section 5
ChargeableContainer Level	chargeableContainer LevelType simple type	-	Optional	Refer to this simple type in Section 5
ContainerID	String 6	-	Optional field; Required for Full-Service mailings (mixed allowed), and Non Full-Service with containers marked for eInduction	-
ChargeableBundleLe vel	chargeableBundleLev elType simple type	-	Optional	Refer to this simple type in Section 5
Bundles	Double	-	Optional	-
ChargeableEntryLeve l	chargeableEntryLevel Type simple type	-	Optional	Refer to this simple type in Section 5
Containers	Double	-	Optional	-
MachinableFlag	yesNo	Yes or No	Optional	-
FullServiceParticipati onIndicator	fspiType simple type	-	Optional	Refer to this simple type in Section 5
USPSPackageUniqu eCharacteristic	uspsPackageCharact eristicType simple type	-	Optional	Refer to this simple type in Section 5
Incentive	mailxml_base:charact eristicIncentiveType		Optional	
Fee	mailxml_base:charact eristicFeeType		Optional	
HoldForPickup	yesNo	Yes or No	Optional	-
NumberofPiecesToH old	positiveInteger	-	Optional	-

4.118 complexType: PeriodicalStatementDataType

Mail.XML 13.0B- complexType: PeriodicalStatementDataType				
Field	**Format**	**Acceptable Values**	**Busines s Rules**	**Comments**
PeriodicalStatementD ataType				

Copyright © 2014 USPS®. All Rights Reserved

Mail.XML 13.0B- complexType: PeriodicalStatementDataType				
Field	**Format**	**Acceptable Values**	**Busines s Rules**	**Comments**
Block BEGINS				
AdvertisingPercentage	PercentageType simple type		Required field; 5 total digits with a max value of 100.00	Refer to this simple type in Section 5
DeliveryStatisticsFileDate	Date	-	Optional. Allows USPS to validate the correct file date for simplified addresses.	-
AutomationAddressMatchDate	Date	YYYY-MM-DD	Optional field; Required for Automation mailings The system will validate that this field cannot be more than 90 calendar days before the PostageStatementMailingDate for Carrier Route mail (RateCategory A, B, D, AF, BF, or DF). The field cannot be more than 180 calendar days before the PostageStatementMailingDate for non-Carrier Route Mail (RateCategory is E, H, L, L1, L2, L3, or L4). The mailer must specify the date when the address list was generated.	
CustomerReferenceID	String, 40 characters		Optional field; Used to populate Customer Reference ID	CustomerReferenceID represents CAPS Account Number
UserPostageStatementID	String, 10 characters		Optional field; Used to populate User Postage Statement ID to uniquely identify postage statement	
CarrierRouteAddressMatchDate	Date	YYYY-MM-DD	Optional field; Required for Carrier Route Automation pieces	
CarrierRouteSequencingDate	Date	YYYY-MM-DD	Optional field; Required for Carrier Route Sequencing pieces	
CertificationData	CertificationDataType		Required block; data used in the certification statement section of the postage statement	See Section 7 for Details
ContainerCount	ContainerCountType		Required block; at	See Section 7 for

Copyright © 2014 USPS®. All Rights Reserved

Mail.XML 13.0B- complexType: PeriodicalStatementDataType				
Field	**Format**	**Acceptable Values**	**Busines s Rules**	**Comments**
			least one of the fields in this block must be populated with a nonzero value	Details
CopyWeight	Double		Required field; used for *PostalOne!* postage calculation, *PostalOne!* accepts up to four decimals. The value of CopyWeight must be in Pounds.	
EditionCode	String, 20 characters		Optional field; printed on postage statement if provided	
FirstIssueDate	Date	YYYY-MM-DD	Optional field; not used by *PostalOne!*	
FormType	Mailxml_base:formType	Refer 'formType' simple type	Required field	Refer Section 5
IssueDate	Date	YYYY-MM-DD	Required field	
IssueFrequency	String, 20 characters		Optional field; populated with the frequency the postage statement comes from Publication data	
LastIssueDate	Date	YYYY-MM-DD	Optional field; not used by *PostalOne!*	
PostageStatementMailingDate	Date	YYYY-MM-DD	Required field; Used to determine prices and display on postage statement It may be up to one year in future or back dated to most recent price change	
Over10	Mailxml_base:yesNo	Yes = Subscribers or Requesters over the 10% rule No = No subscribers or requesters over the 10% rule	Required field	
LimitedCirculationDiscountClaimed	Mailxml_base:yesNo	Yes No	Required field	
PeriodicalLineItemData	PeriodicalLineItemData ELEMENT		Required block; data used to generate specific line items of postage statement (one to many pairings) One to many allowed	Refer this in Section 7
PostagePaymentMethod	postagePaymentMethodType simple type		Required field	Refer to this simple type in Section 5
ProcessingCategory	processingCategoryType simple type		Required field	Refer to this simple type in Section 5
PublicationTitle	String, 60 characters		Optional field, *PostalOne!* uses this	

Copyright © 2014 USPS®. All Rights Reserved

Mail.XML 13.0B- complexType: PeriodicalStatementDataType				
Field	**Format**	**Acceptable Values**	**Busines s Rules**	**Comments**
			to get the Title	
CombinedMailingID	Non-negative Integer		Optional field, required if a combined mailing	
RateType	rateType		Required field	Refer to this simple type in Section 5
SingleRideAlongWeight	double		Optional The value of SingleRideAlongWeight must be in Pounds.	
StatementSequenceNumber	String, 20 characters		Optional field; displayed on postage statement if provided	
EntryFacilityType	entryFacilityType		Optional field; Required for discounts on dropping to entry facility type	Refer to this simple type in Section 5
EntryZip	Numeric, exactly 5 characters		Optional field; displayed on the postage statement register info if provided	
AgencyCostCode	agencyCostCodeType simple type		Optional field; Required if a government publication (can start with leading zeroes)	Refer to this simple type in Section 5
RepositionableNotesIndicator	Mailxml_ase:yesNo	NO = no repositionable notes Yes = repositionable notes	Required field	
DocumentVersionData	DocumentVersionData Type		Optional block; Required for Version Summary Report	Refer to this complex type in Section 4
MoveUpdateMethod	moveUpdateMethodType simple type		Optional field; does not apply for Periodicals	Refer to this simple type in Section 5
VolumeNumber	String, 5	-	Optional	-
IssueNumber	String, 6	-	Optional	-
InCountyAddressedSupplementPieces	Non-negative Integer		Optional	
OutsideCountyAddressedSupplementPieces	Non-negative Integer		Optional	
PiecesExcludingAddressedSupplementPIeces	Non-negative Integer		Required	
ContainerPostage	containerPostageType complex type	-	Optional. Allow 0 to many	Refer to this complex type in Section 4
StatementID	Non-negative integer		Optional field	
MailClass	mailClassType simple type		Optional field	Refer to this simple type in Section 5
Origin	String, 6 characters		Optional field	
PostageStatementStatus	postageStatementStatusType simple type		Optional field	Refer to this simple type in Section 5
TotalCopies	Non-negative Integer		Required field	

Copyright © 2014 USPS®. All Rights Reserved

Mail.XML 13.0B- complexType: PeriodicalStatementDataType				
Field	**Format**	**Acceptable Values**	**Busines s Rules**	**Comments**
TotalPieces	Non-negative Integer		Required field	
TotalPostageAmount	Double		Required field, two decimal places	
TotalWeight	Double		Required field, no decimal places. The value of TotalWeight must be in Pounds.	
MailingAgentData	mailerDataType complex type		Optional field; Required if there is a mailing agent for the mail owner	Refer to this complex type in Section 4
PublisherData	mailerDataType complex type		Required block; *PostalOne!* uses this data to bill the postage statement	Refer to this complex type in Section 4
PendingPostageAmount	Double	-	Optional, required for pending Periodicals, two decimal places provided.	
MailArrivalDateandTime	dateTime	-	Optional	-
PaymentDateandTime	dateTime	-	Optional	-
StartTheClockDate	Date	-	Optional	-
PeriodicalStatementData block ENDS				

4.119 complexType: ParticipantIDType/ SubmittingParty

Blocks Included:SubmittingParty

Mail.XML 13.0B- complexType: ParticipantIDType/ SubmittingParty				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
MailerID6	mailerID6Type simple type		Optional. Either MailerID6 or MailerID9 can be provided.	Refer to this simple type in Section 5
MailerID9	mailerID9Type simple type		Optional. Either MailerID6 or MailerID9 can be provided.	Refer to this simple type in Section 5
CRID	CRIDType simple type		Optional. Either CRID or MailerID can be provided	Refer to this simple type in Section 5
SchedulerID	String, 12 characters		Optional	
MaildatUserLicense	userLicenseCodeTye simple type		Optional	Refer to this simple type in Section 5
ShippingAgentID	String 12	-	Optional	-
ReceivingAgentID	String 12	-	Optional	-

4.120 complexType: PermitPublicationDataType

Blocks Included: PermitPublicationData; PublicationInfo

Mail.XML 13.0B- complexType: PermitPublicationDataType

Copyright © 2014 USPS®. All Rights Reserved

Field	Format	Acceptable Values	Business Rules	Comments
PermitPublicationDataType BEGINS				
Choice Block BEGINS				
Sequence Block BEGINS				
PermitNumber	Numeric String – Length 8		Required When PublicationNumber is not provided	
PermitType	permitTypeType simple type		Required When PublicationNumber is not provided.	Refer to this simple type in Section 5
PermitZip4	Numeric String 9		Required When PublicationNumber is not provided.	
Sequence Block ENDS				
PublicationNumber	String, 8		Required when PermitNumber, PermitType, and PermitZip4 are not provided.	
Choice Block ENDS				
PermitPublicationDataType ENDS				

4.121 attributeGroup: PostageMessageHeaderInfo

Mail.XML 13.0B- attributeGroup: PostageMessageHeaderInfo				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
CustomerGroupID	String 25		Required	-
MailingGroupID	nonNegativeInteger	-	Required	-

4.122 complexType: PostageStatementSummaryType

Mail.XML 13.0B- complexType: PostageStatementSummaryType				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
PostageStatementSummary BEGINS				
StatementID	Non-negative Integer		Optional	
UserPostageStatementID	String, 10 characters		Optional	
UserPostageStatementSequenceID	Numeric String 10		Optional	
USPSPostageStatementSequenceID	Numeric String, 10 characters		Optional	
PostageStatementStatus	postageStatementStatusType simple type		Required	Refer to this simple type in Section 5
PostageStatementSummary ENDS				

4.123 complexType: PostageStatementDataType

Blocks Included: PostageStatementData

Mail.XML 13.0B- complexType: PostageStatementDataType

Copyright © 2014 USPS®. All Rights Reserved

Field	Format	Acceptable Values	Business Rules	Comments
PostageStatementDataType Block BEGINS			Required Only one can be submitted	
abstract PostageStatementDataType Block BEGINS				
abstract PostageStatementDataType Block ENDS				
AgencyCostCode	Mailxml_base:agencyCostCodeType		Optional field Required when Permit Type is OI or OM.	Refer 'agencyCostCode' simple type in Section 5
DeliveryStatisticsFileDate	Date	-	Optional. It allows USPS to validate that correct file is used when the pieces contains simplified addresses.	
AutomationAddressMatchDate	Date	YYYY-MM-DD	Conditionally required for Automation rate pieces. The system will validate that this field cannot be more than 90 calendar days before the PostageStatementMailingDate for Carrier Route mail (RateCategory A, B, D, AF, BF, or DF). The field cannot be more than 180 calendar days before the PostageStatementMailingDate for non-Carrier Route Mail (RateCategory is E, H, L, L1, L2, L3, or L4). The mailer must specify the date when the address list was generated.	
CustomerReferenceID	String, 40 characters		Optional field. Mailers may submit up to 999 unique CustomerReferenceIDs.	CustomerReferenceID represents CAPS Account Number
UserPostageStatementID	String, 10 characters		Optional field	
CarrierRouteAddressMatchDate	Date	YYYY-MM-DD	Conditionally required for Carrier Route rate pieces	

Copyright © 2014 USPS®. All Rights Reserved

Mail.XML 13.0B- complexType: PostageStatementDataType				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
CarrierRouteSequencingDate	Date	YYYY-MM-DD	Conditionally required for Carrier Route rate pieces when Rate Category is A, AF, B, BF, D, or DF.	
CertificationData Block	certificationDataType		Required	See Section 7 for Details
ContainerCount Block	containerCountType		Required block; at least one of the fields in this block must be populated with a nonzero value	Refer “containerCountType” in Section 7
EnclosedBy	Mailxml_base:enclosedByType	Refer ‘enclosedByType’ simple type	Optional field, Required for enclosure, must be set to PE	Refer Section 5
DMLType	mailxml_base:DLTypeType		Add a new field DMLTypeType with three enumerations A, B and C. The Postage Statement Create Request will be enhanced with this update, and DMLType of type DMLTypeType will be added to the message.	
EstimateIndicator	Mailxml_base:yesNo		Required. When yes, the system will create preliminary postage statements for MLOCR jobs. This field is ignored for presort jobs.	-
ExtendedForm	Mailxml_base:yesNo	True requires PostageStatementLineItemData; False requires LineItemSummaryData	Required field. A single postage statement may contain either PostageStatementLineItemData or LineItemSummaryData	
FormType	Mailxml_base:formType	Refer ‘formType’ simple type	Required Must be SM or FC when EnclosedBy is populated.	Refer Section 5
LineItemSummaryData Block	LineItemSummaryData complex		Optional field 0 to many can be submitted when ExtendedForm is False	Refer “LineItemSummaryData” complex in Section 7 below.
NumberOfPiecesEDDM	nonNegativeInteger		Optional	

Copyright © 2014 USPS®. All Rights Reserved

Mail.XML 13.0B- complexType: PostageStatementDataType				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
PostageStatementLineItemData Block			Optional field must submit one to many if ExtendedForm is True.	Refer "PostageStatementLineITemData" complex in Section 7 below.
PostageStatementMailingDate	Date	YYYY-MM-DD	Required. Must equal the date specified in the Qualification Report. It may be up to one year in future or back dated to most recent price change	
PackagingMethod	Mailxml_base:packagingMethodType	Refer 'packagingMethodType' simple type	Optional field If FormType is BP this field must be 0, 1 or 2. If FormType is FC this field must be 0 or 1. If FormType is ML this field must be 0, 1 or 2. If FormType is SM this field must be 0, 1 or 2.	Refer Section 5
PostageAffixedAmount	Double		Optional (Conditionally required if the Postage Payment Method is 'M' or 'S') up to three decimal places	
PostagePaymentMethod	Mailxml_base:postagePaymentMethodType	Refer 'postagePaymentMethodType' simple type	Required If FormType is BP this field must be S, M or P. If FormType is FC this field must be S, M or P. If FormType is ML this field must be M or P. If FormType is PM this field must be P. If FormType is PP this field must be S, M or P. If FormType is SM this field must be S, M or P.	Refer Section 5
ProcessingCategory	Mailxml_base:processingCategoryType	Refer 'processingCategoryType' simple type	Required field If FormType = BP, then the following values are valid: FL, NP, MP, IR If FormType = FC, then the following	Refer Section 5

Copyright © 2014 USPS®. All Rights Reserved

Mail.XML 13.0B- complexType: PostageStatementDataType				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
			values are valid: LT, FL, CD, PF If FormType = ML, then the following values are valid: FL, NP, MP, IR If FormType = PM, then the following values are valid: LT, FL, PF If FormType = PP, then the following values are valid: MP, IR, NP If FormType = SM, then the following values are valid: LT, FL, MP, IR, NP, CM, NA, NB	
RateType	Mailxml_base:rateType	Refer 'rateType' simple type	Required field	Refer Section 5
RegisterOfMailing	Mailxml_base:yesNo	Yes or No	Required, Causes *PostalOne!* to generate a register. If true, must provide container ID, container display name, container type, entry facility type, and entry ZIP (at the line item level)	
SackingBasis	Mailxml_base:sackingBasisType	Refer 'sackingBasisType' simple type	Optional field Required for CR, 3/5 or basic sacking. If FormType is SM this field must be 0, 2, 3, or 4 If FormType is PP this field must be either 0, 1 or 4.	Refer Section 5
SinglePieceWeight	Double		Optional up to four decimal places The value of SinglePieceWeight must be in Pounds.	
ExtraServiceData Block BEGINS			Optional field 0 to many can be submitted. For postage statements claiming extra services Use either the ExtraServiceData block or the ExtraServiceSummary block.	
ServiceCode	Mailxml_base:serviceCodeType	Refer 'serviceCodeType'	Required	Refer Section 5

Copyright © 2014 USPS®. All Rights Reserved

Mail.XML 13.0B- complexType: PostageStatementDataType				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
		simple type		
ServiceRate	Double		Optional field up to four decimals	
ServiceSubCode	Mailxml_base:service SubCodeType	Refer 'serviceSubCodeTyp e' simple type	Required	Refer Section 5
ServiceValue	Double		Required, up to two decimals	
TotalAmount	Double		Optional field, up to four decimals	
TotalPieces	Non-negative Integer		Required	
ExtraServiceData Block ENDS				
ExtraServiceSummar yData Block BEGINS			Optional field 0 to many can be submitted For postage statements claiming extra services Use either the ExtraServiceData block or the ExtraServiceSummar y block.	
LineLabel	String, 80 characters		Optional field	
LineNumber	String, 3 characters		Optional field This field will be ignored if populated; LineNumber will only be taken into account for Full-Service discount lines	
Section	String, 1 character		Optional field	
ServiceCode	Mailxml_base:service CodeType	Refer 'serviceCodeType' simple type	Required	Refer Section 5
TotalAmount	Decimal		Required, up to three decimals	
TotalPieces	Non-negative Integer		Required	
USPSPackageUniqu eCharacteristic	Mailxml_base:uspsPa ckageUniqueCharact eristicType	Simple type	Optional	Refer Section 5
ExtraServiceSummar yData Block ENDS				
StatementSequence Number	String, 20 characters		Optional field	
RepositionableNotesI ndicator	Mailxml_base:yesNo	True if there are repositionable notes, else False.	Required	
DocumentVersionDat a Block BEGIN	Complex		Optional field 0 to many can be submitted	
VersionID	String, 10 characters		Required;	
VersionName	String, 12 characters		Required;	
VersionDescription	String, 30 characters		Optional	
PieceWeight	Decimal		Required field up to	

Copyright © 2014 USPS®. All Rights Reserved

Mail.XML 13.0B- complexType: PostageStatementDataType				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
			four decimals. The value of PieceWeight must be in Pounds.	
AdPercent	Mailxml_base:percentageType		Optional	Refer 'percentageType' simple type in Section 5
RateAffixed	Decimal	-	Optional field, up to three decimals. Required when Postage Payment Method is S or M.	-
StandardFlatType	Mailxml_base:standardFltTypeType	Refer simple type definitions	Optional	Refer Section 5
DocumentVersionData Block END				
MeteredAffixedMethod	Mailxml_base:meteredAffixedMethodType	–Refer 'meteredAffixedMethodType' simple type	Optional field Required for metered postage affixed	Refer Section 5
CombinedMailingID	Non-negative Integer		Optional field; Required for Combined Mailings	
SinglePieceDimensionalWeight	Double		Optional, up to four decimals. Required for balloon or oversize prices up to four decimals. The value of SinglePieceDimensionWeight must be in Pounds.	
EnclosingVolumeNo	String, 5 characters		Optional field, used for Periodicals enclosures otherwise ignored	
EnclosingIssueNo	String, 6 characters		Optional field, used for Periodicals enclosures otherwise ignored	
EnclosingIssueDate	Date	YYYY-MM-DD	Optional field, used for Periodicals enclosures otherwise ignored. Required when EnclosedBy is populated.	
PriceType	priceType	commercial, commercialplus	Optional field. Required when the mail is First Class. Should always assume it is commercial unless otherwise identified.	
MoveUpdateMethod	Mailxml_base:moveUpdateMethodType	Refer 'moveUpdateMethodType' simple type	Optional field. Required when FormType is SM.	Refer Section 5

Copyright © 2014 USPS®. All Rights Reserved

Mail.XML 13.0B- complexType: PostageStatementDataType				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
StatementID	NonNegative integer	-	Optional	-
ConfirmationNumber	NonNegative integer	-	Required	-
MailClass	Mailxml_base:mailClassType	Refer simple type definition	Optional	Refer to this simple type in Section 5
Origin	String	-	Optional	-
SpecialFeesAmount	Decimal	-	Optional	-
PostageStatementStatus	Mailxml_base:postageStatementStatusType	Refer simple type definition	Optional	Refer to this simple type in Section 5
Total Pieces	NonNegative Integert	-	Required	-
TotalPostageAmount	Decimal	-	Required	-
TotalPostageAmount Due	Decimal	-	Required	-
TotalWeight	Decimal	-	Required	-
PermitHolderData Block	mailerDataType		Optional	See Section 7 for Details
MailCharacteristicsType	mailxml_defs:MailCharacteristicsType	Complex Type		
MailingOwnerData Block	mailerDataType		Optional	See Section 7 for Details
MailingAgentData Block	mailerDataType		Optional	See Section 7 for Details
PermitHolderForAPData Block	mailerDataType		Conditionally required for Postage Payment Method of 'S' or 'M'	See Section 7 for Details
MailCharacteristicsType	mailxml_defs:MailCharacteristicsType	Complex Type		
STCInfo	STCForContainerOrTrayType complex type	-	Optional 0 to many allowed	Refer to this complex type in Section 4
PostageStatementDataType Block ENDS				

4.124 complexType: PostageStatementLineItemData

Blocks Included: PostageStatementLineItemData

Mail.XML 13.0B- complexType: PostageStatementLineItemData				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
PostageStatementLineItemData Block BEGINS			Optional field must submit one to many if ExtendedForm is True.	For full-service or mixed service mailings, all containers must be included in either the PostageStatementLineItem Data Block or the ContainerPostage Block
ProcessingCategory	Mailxml_base:processingCategoryType		Optional field If FormType = BP, then the following values are valid: FL, NP, MP, IR If FormType = FC, then the following values are valid: LT,	Refer Section 5

Copyright © 2014 USPS®. All Rights Reserved

Mail.XML 13.0B- complexType: PostageStatementLineItemData				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
			FL, CD, PF If FormType = ML, then the following values are valid: FL, NP, MP, IR If FormType = PM, then the following values are valid: LT, FL, PF If FormType = PP, then the following values are valid: MP, IR, NP If FormType = SM, then the following values are valid: LT, FL, MP, IR, NP, CM, NA, NB	
StandardFlatType	Mailxml_base:standardFlatTypeType		Optional	Refer Section 5
ContainerDetailID	String, 9		Optional field; Required for Full-Service mailings (mixed allowed), and Non Full-Service with containers marked for eInduction	
BarcodeRate	Mailxml_base:barcodeRateType		Required If FormType = BP, this field must be Y or N If FormType = FC, this field must be N or O If FormType = ML, this field must be Y or N If FormType = PM, this field must be N or O If FormType = PP, this field must be Y or N If FormType = SM, this field must be Y, N, or O	Refer Section 5
ContainerDisplayName	String, 50 characters		Optional field. Required when RegisterOfMailing is True.	
ContainerID	String, 6 characters		Optional field; Required when RegisterOfMailing is True, for Full-Service mailings (mixed allowed), and Non Full-Service with containers marked for	

Copyright © 2014 USPS®. All Rights Reserved

Mail.XML 13.0B- complexType: PostageStatementLineItemData				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
			eInduction. If referenced a logical sibling container, must be associated to an existing physical container.	
EntryDiscount	Mailxml_base:entryDiscountType		Required field If FormType = BP, then this field must be N, B, S, or D If FormType = FC, then this field must be N If FormType = ML, then this field must be N If FormType = PM, then this field must be N If FormType = PP, then this field must be B, S, D, or N If FormType = SM, then this field must be N, B, S, or D	Refer Section 5
EntryFacilityType	Mailxml_base:entryFacilityType		Optional field. Required when RegisterOfMailing is True.	Refer Section 5
EntryZip	Mailxml_base:zipCodeThreeOrFiveDigit		Optional field. Required when RegisterOfMailing is True.	Refer Section 5
Heavy Letter	Mailxml_base:yesNo	Yes or not	Required	
MarketingOrFulfillmentType	Mailxml_base:marketingOrFulfillmentType		Optional	Refer Section 5
LineLabel	String, 80 characters		Optional field	
LineNumber	String, 3 characters		Optional field This field will be ignored if populated; LineNumber will only be taken into account for Full-Service discount lines	
PieceRate	Double		Optional field, up to three decimals	
SubtotalPostageAmount	Double		Required field up to four decimal places	
DiscountTotalAmount	Double		Required field up to four decimal places	
FeeTotalAmount	Double		Required field up to four decimal places	
TotalPostageAmount	Double		Required field up to four decimal places	
PoundRate	Double		Optional field, up to three decimals	
PreparedAsSM	Mailxml_base:yesNo	Yes or No	Required	

Copyright © 2014 USPS®. All Rights Reserved

Mail.XML 13.0B- complexType: PostageStatementLineItemData				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
			The “True” indicates that mail is actually prepared as Standard when the RateCategory=S The “False” indicates that mail is actually prepared as First Class when the RateCategory=S	
RateCategory	Mailxml_base:rateCategoryType		Optional Field If FormType = BP, then this field must be D, N, or S If FormType = FC, then this field must be E, H, L1, L2, L3, L4, N, or S If FormType = ML, then this field must be G, N, S If FormType = PM, then this field must be S If FormType = PP, then this field must be G, K, S, Z1, or Z2 If FormType = SM, then this field must be A, B, E, H, N, AF, BF, DF, L1, L2, L5, L6, L7, L8, NG, NK, N5, N6, PI, PM, P7, P8, PE, PQ, PR, PG, PK, P5, or P6	Refer Section 5
Section	String, 1 character		Optional field	
SinglePieceWeight	Double		Optional, up to four decimal places The value of SinglePieceWeight must be in Pounds.	
SurchargeType	Mailxml_base:surchargeType		Required If FormType = BP, this field must be N If FormType = FC, this field must be A, E, N, or R If FormType = ML, this field must be N If FormType = PM, this field must be D, E, N, or P If FormType = PP, this field must be 2 or N If FormType = SM,	Refer Section 5

Copyright © 2014 USPS®. All Rights Reserved

Mail.XML 13.0B- complexType: PostageStatementLineItemData				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
			this field must be L or N	
TotalPieces	Non-negative Integer		Required	
SimplifiedAddressIndicator	mailxml_base: SimplifiedAddressIndicator	Y = Yes, M = Mixed, R = Residential only	Optional	
TotalWeight	Double		Optional field The value of TotalWeight must be in Pounds.	
Zone	Mailxml_base:zoneICType		Optional field If FormType is BP, this field must be N, 1, 3, 4, 5, 6, 7, or 8, DDU, SCF If FormType is FC, this field must be N If FormType is ML, this field must be N If FormType is PM, this field must be N, 1, 3, 4, 5, 6, 7, or 8 If FormType is SM, this field must be N	Refer Section 5
ExtendedDeliveryFee Applies	yes/No		New form for ExtendedDeliveryFee Applies is proposed to be added to Postage Statement and Line Item Data	Refer Section 5
VersionID	String, 10 characters		Optional field. Required when PostageAffixedAmount is not provided, for Full-Service mailings (mixed allowed), and Non Full-Service with containers marked for eInduction	
ContainerType	Mailxml_base:mailXMLContainerType		Optional field. Required when RegisterOfMailing is True.	Refer Section 5
FlatRateIndicator	Mailxml_base:flatRateIndicatorType		Optional field	Refer Section 5
FullServiceParticipationIndicator	Mailxml_base:fspiType		Optional field, for mixed Full-Service and not Full-Service each postage statement line must be expressed as either Full-Service or not Full-Service (omit the FullServiceParticipationIndicator). The same line number may be expressed	Refer Section 5

Copyright © 2014 USPS®. All Rights Reserved

Mail.XML 13.0B- complexType: PostageStatementLineItemData				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
			twice.	
SinglePieceDimensionalWeight	Double		Optional, required for balloon or oversize prices up to four decimals. The value of SinglePieceDimensionWeight must be in Pounds.	
SinglePieceDimensionPrice	Double	-	Optional	-
SinglePieceSimensionalBalloonPrice	Double	-	Optional	-
USPSPackageUniqueCharacteristic	Mailxml_base:uspsPackageUniqueCharacteristicType		Optional	Refer Section 5
HoldForPickup	yesNo	Yes or No	Optional	-
NumberofPiecesToHold	positiveInteger	-	Optional	-
MailCharacteristicsType	mailxml_defs:MailCharacteristicsType	Complex Type		
PostageStatementLineItemData Block ENDS				

4.125 complexType: PTPubDiscountsandFeesType

Mail.XML 13.0B- complexType: PTPubDiscountsandFeesType				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
PTPubDiscountsandFeesType Block BEGINS				
Sequence block BEGINS			;	
FileID	mailxml_mm:PTFileIDType		Required	Refer to this simple type in Section 5
PubDate	xs:date		Required	
EffectiveStartDate	xs:date			
EffectiveEndDate	xs:date		Required	
PriceType	mailxml_mm:PTPriceType		Required	
MailClass	mailxml_mm:PTClassType		Required	
MailShapePackaging	mailxml_mm:PTMailShapePackagingType		Optional	
MachinabilityPreparation	mailxml_mm:PTMachinabilityPreparationType		Optional	
ContSortBundleSort	mailxml_mm:PTContSortBundleSortType			
MailEntry	mailxml_mm:PTMailEntryType		Optional	
DiscountType	mailxml_mm:PTDicsountType		Optional	

Copyright © 2014 USPS®. All Rights Reserved

Mail.XML 13.0B- complexType: PTPubDiscountsandFeesType				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
PTNonMachSurcharge	xs:decimal		Optional	
PTNonBarcodedSurcharge	xs:decimal		Optional	
PTDetachedLabelSurcharge	xs:decimal		Optional	
PTSundayDeliverySurcharge	xs:decimal		Optional	
PTIMbDiscount	xs:decimal		Optional	
PTMachOrBarcodeDiscount	xs:decimal		Optional	
Sequence block ENDS				
PTPubDiscountsandFeesType Block ENDS				

4.126 complexType: PTincentivesFeesKeysType

Mail.XML 13.0B- complexType: PTincentivesFeesKeysType				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
PTincentivesFeesKeysType Block BEGINS				
Sequence block BEGINS			;	
IncentiveKey	xs:nonNegativeInteger		Required	Refer to this simple type in Section 5
FileID	mailxml_mm:PTFileIDType		Required	Refer to this simple type in Section 5
PubDate	xs:date		Required	
EffectiveStartDate	xs:date			
EffectiveEndDate	xs:date		Required	
PriceType	mailxml_mm:PTPriceType		Required	
MailClass	mailxml_mm:PTClassType		Required	
MailShapePackaging	mailxml_mm:PTMailShapePackagingType		Optional	
MachinabilityPreparation	mailxml_mm:PTMachinabilityPreparationType		Optional	
PTIncAggregateInd	mailxml_base:yesNo		Optional	
PTIncIMbInd	mailxml_base:yesNo		Optional	
PTIncBaselineVol	xs:integer		Optional	
PTIncBaselineRev	xs:integer		Optional	
PTIncVolumeChange	xs:integer		Optional	
PTIncVolumePercentChange	mailxml_base:percentageType		Optional	
PTIncRevenueChange	xs:integer		Optional	
PTIncRevenuePercentChange	mailxml_base:percentageType		Optional	
PTIncWeightThrGreaterThan	mailxml_base:ns06		Optional	

Copyright © 2014 USPS®. All Rights Reserved

Mail.XML 13.0B- complexType: PTincentivesFeesKeysType				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
PTIncWeightThrLessThan	mailxml_base:ns06		Optional	
TimePeriodStartPeriodForChangeDate	xs:date		Optional	
TimePeriodEndPeriodForChangeDate	xs:date		Optional	
PTincentivesFeesRulesBlock mailxml_mm:PTincentivesFeesRulesBlockType	mailxml_mm:PTincentivesFeesRulesBlockType			
Sequence block ENDS				
PTincentivesFeesKeysType Block ENDS				

4.127 complexType: PTWithIncentivesFeesDeliveryType

Mail.XML 13.0B- complexType: PTWithIncentivesFeesDeliveryType				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
PTWithIncentivesFeesDeliveryType Block BEGINS				
Sequence block BEGINS				
PTpostageKeys	mailxml_mm:PTpostageKeysType			
PTincentivesFeesKeys	mailxml_mm:PTincentivesFeesKeysType			
PTPubDiscountsandFees	mailxml_mm:PTPubDiscountsandFeesType			
PTExtraServicesKeys	mailxml_mm:PTExtraServicesKeysType			
Sequence block ENDS				
PTWithIncentivesFeesDeliveryType Block ENDS				

4.128 complexType: PTpostageKeysType

Mail.XML 13.0B- complexType: PTpostageKeysType				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
PTpostageKeysType Block BEGINS				
Sequence block BEGINS			;	
PriceKey	xs:nonNegativeInteger		Required	
PriceStructure	mailxml_mm:PTPriceStructureType		Required	
FileID	mailxml_mm:PTFileIDType		Required	Refer to this simple type in Section 5
PubDate	xs:date		Required	

Copyright © 2014 USPS®. All Rights Reserved

Mail.XML 13.0B- complexType: PTpostageKeysType				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
EffectiveStartDate	xs:date			
EffectiveEndDate	xs:date		Required	
PriceType	mailxml_mm:PTPrice Type		Required	
MailClass	mailxml_mm:PTClass Type		Required	
MailShapePackaging	mailxml_mm:PTMailS hapePackagingType		Optional	
MachinabilityPreparat ion	mailxml_mm:PTMach inabilityPreparationTy pe		Optional	
ContSortBundleSort	mailxml_mm:PTCont SortBundleSortType		Optional	
MailEntry	mailxml_mm:PTMailE ntryType		Optional	
Content	mailxml_base:charact eristicContentType		Optional	
PeriodicalsPrice	mailxml_mm:PTPerPr iceType		Optional	
PeriodicalsAdvertisin g	mailxml_mm:PTPerA dvType		Optional	
PeriodicalsBarcoded	mailxml_mm:PTPerC ontSortType		Optional	
PeriodicalsContainer Sort	mailxml_mm:PTPerC ontSortType			
PTpostagePrices	mailxml_mm:PTposta gePricesType			
Sequence block ENDS				
PTpostageKeysType Block ENDS				

4.129 complexType: PTpostagePricesType

Mail.XML 13.0B- complexType: PTpostagePricesType				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
PTpostagePricesTyp e Block BEGINS				
Sequence block BEGINS			;	
PriceKey	xs:nonNegativeInteg er		Required	
PiecePounDZonedIn d	mailxml_mm:PTPLBZ NIndType		Required	
LineItemNumber	mailxml_base:s03		Required	
Price	mailxml_mm:PTPrice AmountType		Required	
MinBreak	mailxml_mm:PTMinB reakType		Optional	
MaxBreak	mailxml_mm:PTMaxB reakType		Optional	
AccountPaymentMet hod	mailxml_base:postag ePaymentMethodTyp e		Optional	
SimplifiedAddress	mailxml_base:		Optional	

Copyright © 2014 USPS®. All Rights Reserved

Mail.XML 13.0B- complexType: PTpostagePricesType				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
	simplifiedAddressType			
Printorder	xs:nonNegativeInteger		Optional	
Sequence block ENDS				
PTpostagePricesType Block ENDS				

4.130 complexType: PTincentivesFeesRulesBlockType

Mail.XML 13.0B- complexType: PTincentivesFeesRulesBlockType				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
PTincentivesFeesRulesBlockType Block BEGINS				
Sequence block BEGINS			;	
IncentiveKey	xs:nonNegativeInteger		Required	
IncFeeRulesKey	xs:nonNegativeInteger		Required	
ContSortBundleSort	mailxml_mm:PTContSortBundleSortType		Optional	
MailEntry	mailxml_mm:PTMailEntryType		Optional	
PaymentMethod	mailxml_base:postagePaymentMethodType		Optional	
IncentiveFeeType	mailxml_mm:PTIncentiveFeeTypeType		Optional	
IncentiveFeeRule	mailxml_mm:PTIncentiveFeeRuleType		Optional	
Content	mailxml_base:characteristicContentType		Optional	
ContSortBundleSort	mailxml_mm:PTContSortBundleSortType		Optional	
RulesPercentPriceValue	mailxml_base:percentageType		Optional	
PriceValueChange	xs:decimal		Optional	
Sequence block ENDS				
PTincentivesFeesRulesBlockType Block ENDS				

4.131 complexType: PTExtraServicesKeysType

Mail.XML 13.0B- complexType: PTExtraServicesKeysType				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
PTExtraServicesKeysType Block BEGINS				
Sequence block BEGINS			;	

Copyright © 2014 USPS®. All Rights Reserved

Mail.XML 13.0B- complexType: PTExtraServicesKeysType				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
PriceKey	xs:nonNegativeInteger			
FileID	mailxml_mm:PTFileIDType		Required	Refer to this simple type in Section 5
PubDate	xs:date		Required	
EffectiveStartDate	xs:date			
EffectiveEndDate	xs:date		Required	
ExtraServices	mailxml_mm:PTExtraServicesType		Optional	
MailClass	mailxml_mm:PTClassType		Optional	
MailEntry	mailxml_mm:PTMailEntryType		Optional	
PriceStructure	mailxml_mm:PTExtraServicePriceStructureType"		Optional	
PTExtraServicesPricesBlock	mailxml_mm:PTExtraServicesPricesBlockType		Required	
Sequence block ENDS				
PTExtraServicesKeysType Block ENDS				

4.132 complexType: PTExtraServicesPricesBlockType

Mail.XML 13.0B- complexType: PTWithIncentivesFeesType				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
PTWithIncentivesFeesType Block BEGINS				
Sequence block BEGINS			;	
SubmittingParty	mailxml_defs:participantIDType		Optional	
SubmittingSoftware	mailxml_defs:submittingSoftwareType		Optional	
DataRecipient	mailxml_defs:DataRecipient		Optional	
PTpostageKeys	mailxml_mm:PTpostageKeysType		Required	
PTincentivesFeesKeys	mailxml_mm:PTincentivesFeesKeysType		Required	
PTPubDiscountsandFees	mailxml_mm:PTPubDiscountsandFeesType		Required	
PTExtraServicesKeys	mailxml_mm:PTExtraServicesKeysType		Required	
Sequence block ENDS				
LargeTransactionDividerGroupOptionalType	mailxml_defs:LargeTransactionDividerGroupOptionalType		Required	
PTWithIncentivesFeesType Block ENDS				

Copyright © 2014 USPS®. All Rights Reserved

4.133 complexType: QualificationReport

Mail.XML 13.0B- complexType: QualificationReport				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
QualificationReports BEGINS				
OriginalPieces	Non Negative Integer		Required	
ActualPieces	Non Negative Integer		Required	
Postage	Double		Required	
ClosedContainer block BEGINS				
OriginalPieces	Non Negative Integer		Required	
ActualPieces	Non Negative Integer		Required	
Postage	Double		Required	
ClosedContainer block ENDS				
PostageStatementCanceled block BEGINS				
OriginalPieces	Non Negative Integer		Required	
ActualPieces	Non Negative Integer		Required	
Postage	Double		Required	
PostageStatementCanceled ENDS				
PostageStatementUSPSProcessingDue block BEGINS				
OriginalPieces	Non Negative Integer		Required	
ActualPieces	Non Negative Integer		Required	
Postage	Double		Required	
PostageStatementUSPSProcessingDue block ENDS				
PostageStatementReworked block BEGINS				
OriginalPieces	Non Negative Integer		Required	
ActualPieces	Non Negative Integer		Required	
Postage	Double		Required	
PostageStatementReworked block ENDS				
PostageStatementFinalized block BEGINS				
OriginalPieces	Non Negative Integer		Required	
ActualPieces	Non Negative Integer		Required	
Postage	Double		Required	
PostageStatementFinalized block ENDS				
PostageStatementReversed block BEGINS				
OriginalPieces	Non Negative Integer		Required	
ActualPieces	Non Negative Integer		Required	
Postage	Double		Required	
PostageStatementReversed block ENDS				
PostageStatementNotAvailable block BEGINS				

Copyright © 2014 USPS®. All Rights Reserved

Mail.XML 13.0B- complexType: QualificationReport				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
OriginalPieces	Non Negative Integer		Required	
ActualPieces	Non Negative Integer		Required	
Postage	Double		Required	
PostageStatementNotAvailable block ENDS				
TotalPieces	Non Negative Integer		Required	
TotalActualPieces	Non Negative Integer		Required	
TotalPostage	Double		Required	
ReconciliationReport block ENDS				

4.134 complexType: QualificationSummaryReport

Mail.XML 13.0B- complexType: QualificationSummaryReport				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
QualificationSummaryReport BEGINS				
RateCategory	rateCategoryType simple type		Required	Refer to this simple type in Section 5
Pieces	Non Negative Integer		Required	
ClosedPieces	Non Negative Integer		Required	
FormType	formType simple type		Required	Refer to this simple type in Section 5
TotalPieces	Non Negative Integer		Required	-
TotalClosedPieces	Non Negative Integer		Required	
PostageStatements block BEGINS			Required Block	
Sequence Block BEGINS				
Line	String, 2 characters		Required	
USPSProcessingDue block BEGINS				
Pieces	Non Negative Integer		Required	
Postage	Double		Required	
TotalPieces	Non Negative Integer		Required	
TotalPostage	Double		Required	
USPSProcessingDue block ENDS				
Finalize block BEGINS				
Pieces	Non Negative Integer		Required	
Postage	Double		Required	
TotalPieces	Non Negative Integer		Required	
TotalPostage	Double		Required	
Finalize block ENDS				
Sequence Block ENDS				
PostageStatements block ENDS				
QualificationSummaryReport block ENDS				

Copyright © 2014 USPS®. All Rights Reserved

4.135 complexType: QualificationReportDataType

Blocks Included: QualificationReport

Mail.XML 13.0B- complexType: QualificationReportDataType				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
qualificationReportDataType BEGINS				
DMMSection	String, 12 characters		Optional field	-
BatchManifestIndicator	yesNo		Required field	Refer Section 5
ContainerInfoData	ContainerInfo Data complex type	-	0 to many allowed. Optional block; must provide one for each container (may have multiple ContainerDetailData blocks within ContainerInfoData block)	Refer to this complex type in Section 4
CustomerQualificationReportID	String, 66 characters		Optional field	
CustomerCommitmentAgreementNumber	String 40	-	Optional	-
FormType	formType		Required field. For Full-Service / Mixed Service mailings, the FormType can only be ‘FC’, ‘SM’, ‘PE’, and ‘BP’.	Refer Section 5
PreparedDate	Date/Time	YYYY-MM-DDTHH:MM:SS	Required field	
QualificationReportPreparer	qualificationPreparerDataType complex type		Required block; contains permit information of the mail preparer	Refer to this complex type in Section 4
PresortSWCompany	String, 50 characters		Optional field, displayed in Qualification Report	
PresortSWProduct	String, 50 characters		Optional field, displayed in Qualification Report	
PresortSWVersion	String, 20 characters		Optional field, displayed in Qualification Report	
LogicalPhysicalBundleIndicator	logicalPhysicalBundleIndicatrType simple type		Optional	Refer Section 5
SoftwareVendorZAPOption	String 1		Optional	
ZoneMatrixDate	Date	YYYY-MM-DD	Optional	
qualificationReportDataType ENDS				

4.136 complexType: QualificationReportDetailDataType

Mail.XML 13.0B- complexType: QualificationReportDetailDataType				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
qualificationReportDe				

Copyright © 2014 USPS®. All Rights Reserved

Mail.XML 13.0B- complexType: QualificationReportDetailDataType				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
tailDataType BEGINS				
CustomerQualificationReportID	String 66	-	Required	The CustomerQualificationReportID field in the QualificationReportDetailCreateRequest message must match an existing CustomerQualificationReportID from an accepted QualificationReportSummaryCreateRequest message within a MailingGroupID
ContainerInfoData	ContainerInfoData complex	-	Optional 0 to many allowed	-
DocumentVersionDataWithPermit	DocumentVersionDataWithPermit complex type	-	Required 1 to many allowed	-

4.137 complexType: QualificationReportSummaryDataType

Mail.XML 13.0B- complexType: QualificationReportSummaryDataType				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
qualificationReportSummaryDataType BEGINS				
DMMSection	String, 12 characters		Optional field	-
BatchManifestIndicator	yesNo		Required field	Refer Section 5
CustomerQualificationReportID	String, 66 characters		Required field	The CustomerQualificationReportID field in the QualificationReportDetailCreateRequest message must match an existing CustomerQualificationReportID from an accepted QualificationReportSummaryCreateRequest message within a MailingGroupID
FormType	formType simple type		Required field. For Full-Service / Mixed Service mailings, the FormType can only be ‘FC’, ‘SM’, ‘PE’, and ‘BP’.	Refer Section 5
PreparedDate	Date/Time	YYYY-MM-DDTHH:MM:SS	Required field	
QualificationReportPreparer	qualificationPreparerDataType complex		Required block; contains permit	Refer to this complex type in Section 4

Copyright © 2014 USPS®. All Rights Reserved

Mail.XML 13.0B- complexType: QualificationReportSummaryDataType				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
	type		information of the mail preparer	
PresortSWCompany	String, 50 characters		Optional field, displayed in Qualification Report	
PresortSWProduct	String, 50 characters		Optional field, displayed in Qualification Report	
PresortSWVersion	String, 20 characters		Optional field, displayed in Qualification Report	
LogicalPhysicalBundleIndicator	logicalPhysicalBundleIndicatrType simple type		Optional	Refer Section 5
SoftwareVendorZAPOption	String 1		Optional	
ZoneMatrixDate	Date	YYYY-MM-DD	Optional	
SeamlessAcceptance	mailxml_base:yesNo	Yes or No	Default : YES	
qualificationReportSummaryDataType ENDS				

4.138 complexType: QualificationPreparerDataType

Blocks Included: QualificationReportPreparer

Mail.XML 13.0B- complexType: QualificationPreparerDataType				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
qualificationPreparerDataType BEGINS			Required block; contains permit information of the mail preparer	
Choice Block BEGINS			Either publicationNumber or PermitNumber, PermitType, and PermitZip4 is required.	
Sequence BEGINS				
PermitNumber	String, 8 characters		Required field when PermitType and PermitZIP4 are populated	
PermitType	permitTypeType simple type		Required field when PermitNumber and PermitZIP4 are populated	Refer Section 5
PermitZip4	Numeric String, 9 characters		Required field when PermitNumber and PermitType are populated	
Sequence ENDS				
PublicationNumber	String, 9 characters		Required field when PermitNumber, PermitType, PermitZIP4 are not populated	

Copyright © 2014 USPS®. All Rights Reserved

Mail.XML 13.0B- complexType: QualificationPreparerDataType				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
Choice Block ENDS				
Choice Block BEGINS			Either MailerID6 or MailerID9 is required	
MailerID6	MailerID6 type simple type		Optional Conditionally required for Full-Service / Mixed Service mailings that at least one field is populated between the CRID, MailerID6, and MailerID9 fields	Refer to this simple type in Section 5
MailerID9	MailerID9 type simple type		Optional Conditionally required for Full-Service / Mixed Service mailings that at least one field is populated between the CRID, MailerID6, and MailerID9 fields	Refer to this simple type in Section 5
Choice Block ENDS				
CRID	CRID type		Optional Conditionally required for Full-Service / Mixed Service mailings that at least one field is populated between the CRID, MailerID6, and MailerID9 fields	Refer to this simple type in Section 5
qualificationReportPreparerDataType ENDS				

4.139 complexType: QualificationReportPreparerDataType

Blocks Included: QualificationReportPreparer

Mail.XML 13.0B- complexType: QualificationReportPreparerDataType				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
qualificationReportPreparerDataType Block BEGINS			Required block; contains permit information of the mail preparer	
Choice Block BEGINS				
Sequence BEGINS				
PermitNumber	String, 8 characters		Required field when PermitType and PermitZIP4 are populated	
PermitType	mailxml_base:permiTYpeType	Refer 'permitTypeType' simple type	Required field when PermitNumber and PermitZIP4 are populated	Refer Section 5
PermitZip4	Numeric String, 9		Required field when	

Copyright © 2014 USPS®. All Rights Reserved

Mail.XML 13.0B- complexType: QualificationReportPreparerDataType				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
	characters		PermitNumber and PermitType are populated	
Sequence ENDS				
PublicationNumber	String, 9 characters		Required field when PermitNumber, PermitType, PermitZIP4 are not populated	
Choice Block ENDS				
Choice Block BEGINS				
MailerID6	Mailxml_base:MailerID6 type		Optional Conditionally required for Full-Service / Mixed Service mailings that at least one field is populated between the CRID, MailerID6, and MailerID9 fields	Refer “mailerID6type” simple type in Section 5
MailerID9	Mailxml_base:MailerID9 type		Optional Conditionally required for Full-Service / Mixed Service mailings that at least one field is populated between the CRID, MailerID6, and MailerID9 fields	Refer “mailerID9type” simple type in Section 5
Choice Block ENDS				
CRID	Mailxml_base:CRID type		Optional Conditionally required for Full-Service / Mixed Service mailings that at least one field is populated between the CRID, MailerID6, and MailerID9 fields	Refer “CRIDType” simple type in Section 5
qualificationReportPreparerDataType Block ENDS				

4.140 complexType: ReturnInfoType

Blocks Included: ReturnInfo

Complex Type: returnInfoType				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
returnInfoType BEGINS				
Sequence Block BEGINS				
ConsigneeFacility	mailxml_defs:consigneeFacilityType		Optional	Refer to this complex type in Section 4
ErrorWarning	mailxml_defs:errorWa		Optional	Refer to this complex

Copyright © 2014 USPS®. All Rights Reserved

Complex Type: returnInfoType				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
	rningType		Unbounded	type in Section 4
ContainerErrorWarningBlock	mailxml_defs:containerErrorWarningBlockType		Optional Unbounded	
Sequence Block ENDS				
returnInfoType ENDS				

4.141 complexType: SackTrayContainerVersionRecordType

Mail.XML 13.0B- complexType: SackTrayContainerVersionRecordType				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
SackTrayContainerVersionRecords block begins			Optional block; 0 to many pairings can be submitted depending upon the number of SackTrayContainerMPURecords (used for Sack or Tray charges)	
DocumentVersionData	DocumentVersionData complex type		Required	Refer to this complex type in Section 4
PublicationInfo	permitPublicationDataType complex type	-	Required	Refer to this complex type in Section 4
PublicationTitle	String, 60 characters		Required	
PostageStatementLineNumber	postageStatementLineNumber2Type		Optional field; uses the Container Level and Entry level to find the lines	Refer to this simple type in Section 5
ChargeableContainerLevel	chargeableContainerLevelType		Required field; <BLANK> = NULL is not supported	Refer to this simple type in Section 5
ChargeableEntryLevel	chargeableEntryLevelType		Required field; <BLANK> = NULL is not supported	Refer to this simple type in Section 5
Containers	Double		Required	
IssueDate	Date	YYYY-MM-DD	Required	
IssueNumber	String, 6 characters		Optional	
VolumeNumber	String, 5 characters		Optional	
SackTrayContainerVersionRecords block ends				

4.142 complexType: SackTrayContainerRecordType

Mail.XML 13.0B- complexType: SackTrayContainerRecordType				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
SackTrayContainerRecords block begins			Optional block; 0 to many pairings can be submitted depending upon the number of SackTrayContainerMPURecords (used for Sack or Tray charges)	

Copyright © 2014 USPS®. All Rights Reserved

Mail.XML 13.0B- complexType: SackTrayContainerRecordType				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
PublicationInfo	permitPublicationDataType complex type	-	Required	Refer to this complex type in Section 4
PublicationTitle	String, 60 characters		Required	
PostageStatementLineNumber	postageStatementLineNumber2Type		Optional field; uses the Container Level and Entry level to find the lines	Refer to this simple type in Section 5
ChargeableContainerLevel	chargeableContainerLevelType		Required field; <BLANK> = NULL is not supported	Refer to this simple type in Section 5
ChargeableEntryLevel	chargeableEntryLevelType		Required field; <BLANK> = NULL is not supported	Refer to this simple type in Section 5
Containers	Double		Required	
IssueDate	Date	YYYY-MM-DD	Required	
IssueNumber	String, 6 characters		Optional	
VolumeNumber	String, 5 characters		Optional	
SackTrayContainerRecords block ends				

4.143 complexType: STCForContainerOrTrayType

Mail.XML 13.0B- complexType: STCForContainerOrTrayType				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
STCForContainerOrTrayType BEGINS				
StartTheClockDate	Date	-	Required	-
Choice Block BEGINS				
IMtb	IMtbType simple type	-	Optional	Refer to this simple type in Section 5
IMcb	IMcbType simple type	-	Optional	Refer to this simple type in Section 5
IMpb	IMpbType simple type	-	Optional	Refer to this simple type in Section 5
Choice Block ENDS				
STCForContainerOrTrayType ENDS				

4.144 complexType: MPSRequestType

Blocks Included: MPSRequestType

Mail.XML 13.0B- complexType: MPSRequestType				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
MPSRequestType BEGINS				
ScanState	mailxml_base:MPSStateType			
MPSQuery	mailxml_base:MPSQueryType			
MPSRequestType ENDS				

Copyright © 2014 USPS®. All Rights Reserved

4.145 complexType: MPSRBlockType

Blocks Included: MPSRBlockType

Mail.XML 13.0B- complexType: MPSRBlockType				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
MPSRBlockType BEGINS				
ContainerID	mailxml_base:s06			
PSRBlock	mailxml_defs:PSRBlockType			
MPSRBlockType ENDS				

4.146 complexType: ReturnInfo

Mail.XML 13.0B- complexType: ReturnInfo				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
ReturnInfo Block begins			Provides reason for return Not required can be provided Multiple pairings of ReturnCode and ReturnDescription in the block	
Sequence Block Begins			The is sequence is optional and the maximum number is unbounded	
ReturnCode			Not required	
ReturnDescription	String, 260 characters		Required	
Sequence Block Ends				
ReturnInfo Block ends				

4.147 complexType: SubmittingSoftwareType

Blocks Included: submittingSoftware

Mail.XML 13.0B- complexType: SubmittingSoftwareType				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
SoftwareName	String		Required	
Vendor	String		Required	
Version	String		Required	
ApprovalDate	Date	YYYY-MM-DD	Not required	
ApprovalKey	String		Not required	

4.148 complexType: UspsSummaryType

Blocks Included: UspsSummaryType

Mail.XML 13.0B- complexType: SubmittingSoftwareType				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
UspsSummaryType BEGINS				

Copyright © 2014 USPS®. All Rights Reserved

Mail.XML 13.0B- complexType: SubmittingSoftwareType				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
DestinationDiscountIndicator	mailxml_base:yesNo	Yes No	Optional	
ZoneSkippingIndicator	mailxml_base:yesNo	Yes No	Optional	
FullServiceIndicator	mailxml_base:yesNo	Yes No	Optional	
eInductionIndicator	mailxml_base:yesNo	Yes No	Optional	
Pallets	mailxml_tm:palletUnitType		Optional	
Bedload	mailxml_tm:bedloadUnitType		Optional	
Perishable	mailxml_base:yesNo	Yes No	Optional	
MailClass	mailxml_base:mailClassType		Optional	
RateType	mailxml_base:rateType		Optional	
InHomeStart	dateTime		Optional	
InHomeEnd	dateTime		Optional	
processingCategory	mailxml_base:processingCategoryType		Optional	
PriorityMailIndicator	mailxml_base:yesNo	Yes No	Optional	
VerificationLocation	mailxml_base:verificationLocationType		Optional	
NewsIndicator	mailxml_base:yesNo	Yes No	Optional	
EvsIndicator	mailxml_base:yesNo	Yes No	Optional	
MailContentName	mailxml_base:s30		Optional	
MailPreparerID	mailxml_base:s12		Optional	
MailPreparerCRID	mailxml_base:CRIDType		Optional	
AdvanceMailingID	mailxml_base:s09		Optional	
EFileNumber	mailxml_base:s12		Optional	
ContainsAutoMail	mailxml_base:yesNo	Yes No	Optional	
SchedulerContentID	mailxml_base:s12		Optional	
ConsigneeContentID	mailxml_base:s12		Optional	
UspsSummaryType ENDS				

4.149 complexType: SubmittingSoftwareType

Blocks Included: SubmittingSoftware

Mail.XML 13.0B- complexType: SubmittingSoftwareType				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
SoftwareName	String		Required Customer must provide the name of their software	

Copyright © 2014 USPS®. All Rights Reserved

Mail.XML 13.0B- complexType: SubmittingSoftwareType				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
Vendor	String		Required This is vendor name	
Version	String		Required This is version number of the software	
ApprovalDate	Date	YYYY-MM-DD	Optional This is the date when USPS approved the vendor's software	
ApprovalKey	String		Optional This is the approval key provided by USPS to the vendor upon approval of their software	

4.150 complexType: SummaryRecordUpdateType

Mail.XML 13.0B- complexType: SummaryRecordUpdateType				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
SummaryRecordUpdateType BEGINS				
Sequence Block BEGINS				
FullContainerID	fullContainerIDType complex type	-	Required	Refer to this complex type in Section 4
Choice Block BEGINS			Optional Block 0 to 2 allowed. Either provide EntryPointEDPostalCode and EntryPointEDFacilityType OR EntryPointADLocaleKey and EntryPointADPostalCode	
PhysicalPostalCodeEntryPoint	mailxml_base:s06			Refer to this simple type in Section 5
EntryPointEDPostalCode	entryPointEDPostalCodeType simple type		Conditionally required if EntryPointEDFacilityType is populated Ignored for Mail.XML transportation updates	Refer to this simple type in Section 5
EntryPointEDFacilityType	entryPointEDFacilityTypeType		Conditionally required if EntryPointEDPostalCode is populated Ignored for Mail.XML transportation updates	Refer to this simple type in Section 5
DestinationZip	mailxml_base:zipCodeThreeOrFiveDigit			
EntryPointFacilityTyp	mailxml_base:entryF			

Copyright © 2014 USPS®. All Rights Reserved

Mail.XML 13.0B- complexType: SummaryRecordUpdateType				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
e	acilityType			
EntryPointZip	mailxml_base:zipCodeThreeOrFiveDigit			
EntryLocaleKey	mailxml_base:localeKeyType			
EntryPointADLocaleKey	entryPointADLocaleKeyType		Conditionally required if EntryPointADPostalCode is populated Original data will be updated for Mail.XML transportation updates (this updates the PhysicalPostalCodeEntryPoint from the Qualification Report message)	Refer to this simple type in Section 5
EntryPointADPostalCode	entryPointADPostalCodeType simple type		Conditionally required if EntryPointADLocaleKey is populated Original data will be updated for Mail.XML transportation updates	Refer to this simple type in Section 5
Choice Block ENDS				
ContainerGroupingDescription	String, 9 characters		Not required Ignored for Mail.XML transportation updates	Refer to this simple type in Section 5
MailOwnerCRID	mailxml_base:CRIDType		Optional	
ParentContainerRefID	parentContainerRefIDType simple type		Not required Ignored for Mail.XML transportation updates	Refer to this simple type in Section 5
TruckDispatchNumber	truckDispatchNumberType simple type		Not required Ignored for Mail.XML transportation updates	Refer to this simple type in Section 5
StopDesignator	stopDesignatorType simple type	-	Not required Ignored for Mail.XML transportation updates	Refer to this simple type in Section 5
ReservationNumber	ReservationNumberType simple type		Not required Original data will be updated for Mail.XML transportation updates	Refer to this simple type in Section 5
CarrierID	mailxml_base:s15		Optional	Refer to this simple type in Section 5
Sequence Block # 1 BEGINS			Optional	
ContainerShipDate	Date	YYYY-MM-DD	Conditionally required if ContainerShipTime is populated	Refer to this simple type in Section 5

Copyright © 2014 USPS®. All Rights Reserved

Mail.XML 13.0B- complexType: SummaryRecordUpdateType				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
			Ignored for Mail.XML transportation updates	
ContainerShipTime	Time	HH:MM:SS	Conditionally required if ContainerShipDate is populated Ignored for Mail.XML transportation updates	Refer to this simple type in Section 5
ScheduledShipDateTime	xs:dateTime		Optional	
Sequence Block # 1 ENDS				
Sequence Block # 2 BEGINS			Optional	
ScheduledShipDate	Date	YYYY-MM-DD	Conditionally required if ScheduledShipTime is populated Original data will be updated for Mail.XML transportation updates	Refer to this simple type in Section 5
ScheduledShipTime	Time	HH:MM:SS	Conditionally required if ScheduledShipDate is populated Original data will be updated for Mail.XML transportation updates	Refer to this simple type in Section 5
ScheduledShipDateTime	xs:dateTime		Optional	
Sequence Block # 2 ENDS				
Sequence Block # 3 BEGINS			Optional	
ActualContainerShipDate	Date	YYYY-MM-DD	Conditionally required if ActualContainerShipTime is populated Ignored for Mail.XML transportation updates	Refer to this simple type in Section 5
ActualContainerShipTime	Time	HH:MM:SS	Conditionally required if ActualContainerShipDate is populated Ignored for Mail.XML transportation updates	Refer to this simple type in Section 5
Sequence Block # 4 ENDS				
Sequence Block # 5 BEGINS			Optional	
ScheduledContainerPickupDate	Date	YYYY-MM-DD	Conditionally required if ScheduledContainerPickupTime is	Refer to this simple type in Section 5

Copyright © 2014 USPS®. All Rights Reserved

Mail.XML 13.0B- complexType: SummaryRecordUpdateType				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
			populated Ignored for Mail.XML transportation updates	
ScheduledContainerPickupTime	Time	HH:MM:SS	Conditionally required if ScheduledContainerPickupDate is populated Ignored for Mail.XML transportation updates	Refer to this simple type in Section 5
ScheduledInductionDateTime	xs:dateTime		Optional	
Sequence Block # 5 ENDS				
Sequence Block # 6 BEGINS			Optional	
ActualContainerPickupDate	Date	YYYY-MM-DD	Conditionally required if ActualContainerPickupTime is populated Ignored for Mail.XML transportation updates	Refer to this simple type in Section 5
ActualContainerPickupTime	Time	HH:MM:SS	Conditionally required if ActualContainerPickupDate is populated Ignored for Mail.XML transportation updates	Refer to this simple type in Section 5
Sequence Block # 6 ENDS				
ContainerAcceptanceDate	Date	YYYY-MM-DD	Not required Ignored for Mail.XML transportation updates	Refer to this simple type in Section 5
ContainerAcceptanceTime	xs:time		Optional	
ScheduledInHomeDate	Date	YYYY-MM-DD	Not required Ignored for Mail.XML transportation updates	Refer to this simple type in Section 5
AdditionalInHomeRange	additionalInHomeRangeType simple type		Not required Ignored for Mail.XML transportation updates	Refer to this simple type in Section 5
Sequence Block # 7 BEGINS			Optional	
ScheduledInductionDate	Date	YYYY-MM-DD	Conditionally required if ScheduledInductionTime is populated Original data will be updated for Mail.XML transportation	Refer to this simple type in Section 5

Copyright © 2014 USPS®. All Rights Reserved

Mail.XML 13.0B- complexType: SummaryRecordUpdateType				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
			updates	
ScheduledInductionTime	Time	HH:MM:SS	Conditionally required if ScheduledInductionDate is populated Original data will be updated for Mail.XML transportation updates	Refer to this simple type in Section 5
Sequence Block # 7 ENDS				
Sequence Block # 8 BEGINS			Optional	
ActualInductionDate	Date	YYYY-MM-DD	Conditionally required if ActualInductionTime is populated Ignored for Mail.XML transportation updates	Refer to this simple type in Section 5
ActualInuctionTime	Time	HH:MM:SS	Conditionally required if ActualInductionDate is populated Ignored for Mail.XML transportation updates	Refer to this simple type in Section 5
Sequence Block # 8 ENDS				
Sequence Block # 9 BEGINS			Optional	
PostageStatementMailingDate	xs:date		Optional	
PostageStatementMailingDate	Date	YYYY-MM-DD	Conditionally required if PostageStatementMailingTime is populated Ignored for Mail.XML transportation updates	Refer to this simple type in Section 5
PostageStatementMailingTime	Time	HH:MM:SS	Conditionally required if PostageStatementMailingDate is populated Ignored for Mail.XML transportation updates	Refer to this simple type in Section 5
TruckAndDispatchNumber	mailxml_base:s10		Optional	Refer to this simple type in Section 5
Sequence Block # 9 ENDS				
ContainerReadyToPayTransactionID	Number, 6 characters		Not required Ignored for Mail.XML transportation updates	Refer to this simple type in Section 5
TransportationCarrierID	String, 15 characters		Not required Ignored for Mail.XML transportation	Refer to this simple type in Section 5

Copyright © 2014 USPS®. All Rights Reserved

Mail.XML 13.0B- complexType: SummaryRecordUpdateType				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
			updates	
CSATripID	String, 10 characters		Not required Original data will be updated for Mail.XML transportation updates	Refer to this simple type in Section 5
CSADispatchNumber	mailxml_base:s10		Optional	
CSAID	mailxml_base:s10		Optional	Refer to this simple type in Section 5
CSADispatchTime	xs:time		Optional	
InternalDate	Date	YYYY-MM-DD	Not required Ignored for Mail.XML transportation updates	Refer to this simple type in Section 5
TotalWeight	totalWeightType simple type		Not required Ignored for Mail.XML transportation updates. The value of TotalWeight must be in Pounds.	Refer to this simple type in Section 5
UniqueContainerID	uniqueContainerIDType simple type		Not required	Refer to this simple type in Section 5
ContainerStatus	maildatContainerStatusType	Refer 'maildatContainerStatusTYpe' simple type	Required Must be 'T' for Mail.XML updates	Refer to this simple type in Section 5
TransShipBoLNumber	transShipBoLNumberType simple type		Not required Ignored for Mail.XML transportation updates	Refer to this simple type in Section 5
PostageGroupingID	postageGroupingIDType simple type		Not required Ignored for Mail.XML transportation updates	Refer to this simple type in Section 5
ContainerGrossWeight	containerGrossWeightType simple type		Not required Ignored for Mail.XML transportation updates. The value of ContainerGrossWeight must be in Pounds.	Refer to this simple type in Section 5
ContainerHeight	containerHeightType simple type		Not required Ignored for Mail.XML transportation updates	Refer to this simple type in Section 5
ContainerHeightSource	containerHeightSourceType	Refer 'containerHeightSourceType' simple type	Not required Ignored for Mail.XML transportation updates	Refer to this simple type in Section 5
TransportDUNSNumber	String, 15 characters		Not required Ignored for Mail.XML transportation updates	Refer to this simple type in Section 5
IMBarcode	IMcbType simple type		Not required Original data will be updated for Mail.XML transportation	Refer to this simple type in Section 5

Copyright © 2014 USPS®. All Rights Reserved

Mail.XML 13.0B- complexType: SummaryRecordUpdateType				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
			updates	
IMpb	mailxml_base:IMpbType		Optional	Refer to this simple type in Section 5
ContainerBarcode	mailxml_base:IMcbType			Refer to this simple type in Section 5
UserInformationLine1	UserInformationLine1 Type simple type		Not required Ignored for Mail.XML transportation updates	Refer to this simple type in Section 5
UserInformationLine2	UserInformationLine2 Type simple type		Not required Ignored for Mail.XML transportation updates	Refer to this simple type in Section 5
ConsigneeContentID	ConsigneeContentID Type simple type		Not required Original data will be updated for Mail.XML transportation updates	Refer to this simple type in Section 5
FASTSchedulerID	FastSchedulerIDType simple type		Not required Original data will be updated for Mail.XML transportation updates.	Refer to this simple type in Section 5
USPSPickUp	uspsPickupType simple type		Not required Original data will be updated for Mail.XML transportation updates	Refer to this simple type in Section 5
CarrierRouteNumber	String exactly 4		Optional Ignored for Mail.XML transportation updates	Refer to this simple type in Section 5
CinCode	String 3		Optional Ignored for Mail.XML transportation updates	Refer to this simple type in Section 5
ParentContainerID	mailxml_base:s06			Refer to this simple type in Section 5
ContainerDetailData	mailxml_defs:ContainerDetailData			Refer to this complex type in Section 4
ContainerDisplayName	String 50		Optional Ignored for Mail.XML transportation updates	Refer to this simple type in Section 5
ContainerType	mailXMLContainerType simple type		Optional Ignored for Mail.XML transportation updates	Refer to this simple type in Section 5
ProcessingCategory	mailxml_base:processingCategoryType		Optional	Refer to this simple type in Section 5
IncludedInOtherDoc	includedInOtherDocType simple type		Optional Ignored for Mail.XML transportation updates	Refer to this simple type in Section 5
SiblingContainerID	mailxml_base:s06		Optional	Refer to this simple type in Section 5
SiblingContainerID	String 6		Optional	Refer to this simple

Copyright © 2014 USPS®. All Rights Reserved

Mail.XML 13.0B- complexType: SummaryRecordUpdateType				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
			Ignored for Mail.XML transportation updates	type in Section 5
SortationLevel	containerLevelType simple type		Optional Ignored for Mail.XML transportation updates	Refer to this simple type in Section 5
OverflowIndicator	yesNo simple type	Yes No	Optional Ignored for Mail.XML transportation updates	Refer to this simple type in Section 5
USPSPickup	mailxml_base:yesNo		Required	Refer to this simple type in Section 5
TotalWeightOfContainer	xs:double		Optional	Refer to this simple type in Section 5
AdditionalTrayPostageAmount	xs:double		Optional	Refer to this simple type in Section 5
eInductionIndicator	mailxml_base:yesNo		Optional	Refer to this simple type in Section 5
ReadyForSASP	mailxml_base:yesNo		Optional	Refer to this simple type in Section 5
AcceptMisshipped	mailxml_base:yesNo		Optional	Refer to this simple type in Section 5
LabelDestLine1	mailxml_base:s30		Optional	Refer to this simple type in Section 5
LabelDestLine2	mailxml_base:s30		Optional	Refer to this simple type in Section 5
LabelEntryOriginPointLine	mailxml_base:s30		Optional	Refer to this simple type in Section 5
LabelUserInfoLine1	mailxml_base:s40		Optional	Refer to this simple type in Section 5
LabelUserInfoLine2	mailxml_base:s40		Optional	Refer to this simple type in Section 5
LabelContLabelCINCode	mailxml_base:s30		Optional	Refer to this simple type in Section 5
LabelContLabelType	mailxml_base:s01		Optional	Refer to this simple type in Section 5
PresortLabelingListEffectiveDateTime	xs:dateTime		Optional	Refer to this simple type in Section 5
LastUsedLabelingListEffectiveDateTime	xs:dateTime		Optional	Refer to this simple type in Section 5
PresortCityStatePublicationDateTime	mailxml_base:s40		Optional	Refer to this simple type in Section 5
LastUsedCityStatePublicationDateTime	mailxml_base:s40		Optional	Refer to this simple type in Section 5
PresortZoneChartMatrixPublicationDateTime	mailxml_base:s30		Optional	Refer to this simple type in Section 5
LastUsedZoneChartMatrixPublicationTime	mailxml_base:s01		Optional	Refer to this simple type in Section 5
LastUsedMailDirectionPublicationDateTime	xs:dateTime		Optional	Refer to this simple type in Section 5
Sequence Block ENDS				
SummaryRecordUpd				

Copyright © 2014 USPS®. All Rights Reserved

Mail.XML 13.0B- complexType: SummaryRecordUpdateType				
Field	**Format**	**Acceptable Values**	**Business Rules**	**Comments**
ateType ENDS				

Copyright © 2014 USPS®. All Rights Reserved

5. Mail.XML 13.0B Simple Types Data Structure

The simple types below list variation of validation in Mail.XML for each version of the Mail.XML 13.0B..

5.1 simpleType: actionCodeType

Tag	actionCodeType
Base	xs:string
enumeration	F = Forwarded
enumeration	W = Wasted
enumeration	R = Returned
enumeration	U = Unable to determine action

5.2 simpleType: addressCorrectionMoveType

Tag	addressCorrectionMoveType
Base	xs:string
enumeration	F = Family Move
enumeration	I = Individual Move
enumeration	B = Business Move

5.3 simpleType: additionalInHomeRangeType

Tag	additionalInHomeRangeType
Base	mailxml_base:n01

5.4 simpleType: adjustmentStatusType

Tag	adjustmentStatusType
Base	xs:string
enumeration	R = Ready to Pay
enumeration	X = Paid
enumeration	C = Cancel
enumeration	P = Preliminary Postage Statement
enumeration	T = Transportation

5.5 simpleType: adjustmentType

Tag	adjustmentType
Base	xs:string
enumeration	1 = Re-order in excess of tolerance
enumeration	2 = “Average Remail” Add-on
enumeration	3 = Spoilage
enumeration	4 = Shortage

5.6 simpleType: agencyCostCodeType

Tag	agencyCostCodeType
Base	xs:string
pattern	[0-9]{5}|[0-9]{6}

5.7 simpleType: apptMethodType

Tag	apptMethodType
Base	xs:string
enumeration	Online
enumeration	Phone
enumeration	Webservices - Detail
enumeration	Webservices - No Detail

Copyright © 2014 USPS®. All Rights Reserved

5.8 simpleType: apptStateType

Tag	apptStateType
Base	xs:string
enumeration	Scheduled
enumeration	Arrived
enumeration	ApptValidated
enumeration	WaitingToBeUnloaded
enumeration	Unloading
enumeration	FinishedUnloading
enumeration	ResolvingProblems
enumeration	Rejected
enumeration	Closed

5.9 simpleType: apptStatusType

Tag	apptStatusType
Base	xs:string
enumeration	Open
enumeration	Closed
enumeration	No Show
enumeration	Unscheduled
enumeration	Rejected

5.10 simpleType: apptTypeType

Tag	apptTypeType
Base	xs:string
enumeration	Pallet
enumeration	DropAndPick
enumeration	Speedline
enumeration	Bedload

5.11 simpleType: barcodeRateType

Tag	barcodeRateType
Base	xs:string
enumeration	Y = Yes
enumeration	N = No
enumeration	O = Other

5.12 simpleType: billReasonCodeType

Tag	billReasonCodeType
Base	xs:string
enumeration	E
enumeration	F
enumeration	M
enumeration	N

5.13 simpleType: bundleDetailLevelType

Tag	bundleDetailLevelType
Base	xs:string
enumeration	A = Firm
enumeration	B = Carrier Route
enumeration	C = 5-Digit
enumeration	D = Unique 3-Digit
enumeration	E = (Reserve for future)
enumeration	F = 3-Digit

Copyright © 2014 USPS®. All Rights Reserved

Tag	bundleDetailLevelType
enumeration	G = (Reserve for future)
enumeration	H = ADC
enumeration	I = AADC
enumeration	J = (Reserve for future)
enumeration	K = Origin MxADC
enumeration	L = MxADC
enumeration	M = MxAADC
enumeration	N = (Reserve for future)
enumeration	O = Working
enumeration	P = (Reserve for future)
enumeration	Q = (Reserve for future)
enumeration	R = Parcel
enumeration	S = Multi-Piece Parcel
enumeration	T = 3D Scheme
enumeration	U = 5D Scheme + L007
enumeration	V = NDC (previously as BMC)
enumeration	W = 5-Digit Super Scheme
enumeration	X = FSS Sort Plan

5.14 simpleType: bundleLevelType

Tag	bundleLevelType
Base	Removed
enumeration	
enumeration	

5.15 simpleType: bundleRecordStatusType

Tag	bundleRecordStatusType
Base	xs:string
enumeration	O = Original
enumeration	D = Delete
enumeration	I = Insert
enumeration	U = Update

5.16 simpleType: bundleStatusType

Tag	bundleStatusType
Base	xs:string
enumeration	Blank
enumeration	C = Cancel

5.17 simpleType: canadaAdMailOnlyType

Tag	canadaAdMailOnlyType
Base	xs:string
enumeration	ST = Standard
enumeration	LG = Large

5.18 simpleType: chargeableBundleLevelType

Tag	chargeableBundleLevelType
Base	xs:string
enumeration	3 = 3-Digit/SCF
enumeration	5 = 5-Digit/Carrier Route
enumeration	A = ADC/AADC
enumeration	C = Carrier Route
enumeration	F = Firm
enumeration	M = Mixed ADC and Mixed AADC

Copyright © 2014 USPS®. All Rights Reserved

5.19 simpleType: chargeableContainerType

Tag	chargeableContainerType
Base	xs:string
enumeration	Sacks-Trays
enumeration	Pallets
enumeration	Airbox

5.20 simpleType: chargeableContainerLevelType

Tag	chargeableContainerLevelType
Base	xs:string
enumeration	3 = 3-Digit/SCF
enumeration	5 = 5-Digit/Carrier Route
enumeration	A = ADC/AADC
enumeration	M = Mixed ADC & Mixed AADC

5.21 simpleType: chargeableEntryLevelType

Tag	chargeableEntryLevelType
Base	xs:string
enumeration	B = Destination NDC (Previously BMC)
enumeration	C = Origin SCF
enumeration	D = DDU
enumeration	J = Origin ADC
enumeration	K = Origin NDC (previously BMC)
enumeration	O = Origin Post Office/ DMU
enumeration	R = Destination ADC
enumeration	S = Destination SCF

5.22 simpleType: characteristicContentType

Tag	characteristicContentType
Base	xs:string
enumeration	CT = Catalog
enumeration	RR = Reply Envelope or Reply Card
enumeration	NF = Contents NOT required to be mailed FCM
enumeration	DC = DVD/CD or other disk
enumeration	PS = Product Sample
enumeration	RT = Round Trip ONLY: One DVD/CD or other disk (can be LT or FL)
enumeration	MI = Mobile Interactive Technology
enumeration	NP = PACT act

5.23 simpleType: characteristicFeeType

Tag	characteristicFeeType
Base	xs:string
enumeration	OS = Operational Surcharge
enumeration	GS = Geographic Surcharge
enumeration	PP = Picture Permit Indicia

5.24 simpleType: characteristicIncentiveType

Tag	characteristicIncentiveType
Base	xs:string
enumeration	SS = Seasonal Sale
enumeration	MT = Mailer Type (For 13.0A/B only MT = Color Branded Mobile Technology)
enumeration	VV = Volume w/% off
enumeration	VP = Volume w/price off

Copyright © 2014 USPS®. All Rights Reserved

Tag	characteristicIncentiveType
enumeration	RE = Revenue
enumeration	PI = Piece Count
enumeration	PP = Picture Permit Indicia
enumeration	PS = Product Sample
enumeration	SB = Small Bus w/% off
enumeration	CT = Container
enumeration	RR = Return Receipt
enumeration	DC = DVD/CD or other disk
enumeration	RT = Round Trip Only
enumeration	MI = Mobile Interactive
enumeration	ME = Mobile Energy Technology
enumeration	IV = Invoice (For 13.0A/B only IV = Premium Advertising)

5.25 simpleType: classNotificationType

Tag	classNotificationType
Base	xs:string
enumeration	A = (Reserved for future use)
enumeration	B = First-Class Mail
enumeration	C = Periodicals, Initial Notification
enumeration	D = Standard Mail
enumeration	E = Package Services
enumeration	F = Periodicals, Follow-up Notifications

5.26 simpleType: closeoutIrregularitiesType

Tag	closeoutIrregularitiesType
Base	xs:string
enumeration	B = Broken Pallet
enumeration	C = Count don't Match 8125
enumeration	D = Damaged Mail
enumeration	DR = Driver Refused to Assist
enumeration	G = Good
enumeration	IA = Improper Appointment Type
enumeration	IM = Improper Mail Class
enumeration	I = Improper Mail Makeup
enumeration	IF = Incorrect Mail Facility
enumeration	L = Load Unsafe
enumeration	M = Mailing not separated by 8125
enumeration	MI = Miscellaneous
enumeration	NP = No Paperwork (Missing Paperwork)
enumeration	O = Others
enumeration	OW = Overweight Pallets
enumeration	NM = Package on NDC non-machinable
enumeration	P = Pallet Too Tall
enumeration	VS = Vehicle Size
enumeration	CP = Courtesy Pallets
enumeration	CM = Container do not match 8017
enumeration	SM = Separation do not match 8107
enumeration	AR = Altered Required Field on Form
enumeration	IO = Incorrect Entry Office
enumeration	MN = Missing Appointment Number
enumeration	MS = Missing Origin Signature and/or Round Stamp
enumeration	MF = Missing Required Mailer Field on Form
enumeration	MA = Multiple Appts Associated to Load
enumeration	NF = No Form with Shipment
enumeration	IP = Incorrect Processing Category

Copyright © 2014 USPS®. All Rights Reserved

Tag	closeoutIrregularitiesType
enumeration	PD = Past in Home Date

5.27 simpleType: closeoutResolutionType

Tag	closeoutResolutionType
Base	xs:string
enumeration	DCD = Driver Contracted Dispatch Office
enumeration	DCO = Destination Contacted Origin
enumeration	DRL = Driver Reconciled Load
enumeration	INR = Irregularities Count Not be Resolved on Dock

5.28 simpleType: communicationRoleType

Tag	communicationRoleType
Base	xs:string
enumeration	From
enumeration	To
enumeration	CC

5.29 simpleType: componentWeightSourceType

Tag	componentWeightSourceType
Base	String
enumeration	A
enumeration	C
enumeration	P
enumeration	L

5.30 simpleType: componentWeightStatusType

Tag	componentWeightStatusType
Base	String
enumeration	N
enumeration	P
enumeration	F
enumeration	M

5.31 simpleType: consigneeContentIDType

Tag	consigneeContentIDType
Base	mailxml_base:s09

5.32 simpleType: containerBundleStatusType

Tag	containerBundleStatusType
Base	xs:string
enumeration	-1 = Failed
enumeration	0 = Pending
enumeration	1 = Success

5.33 simpleType: containerAcceptanceDateType

Tag	containerAcceptanceDateType
Base	xs:date

5.34 simpleType: cccLevelType

Tag	cccLevelType
Base	xs:string

Copyright © 2014 USPS®. All Rights Reserved

Tag	cccLevelType
enumeration	3 = 3-Digit/SCF
enumeration	5 = 5-Digit/Carrier Route
enumeration	A = ADC/AADC
enumeration	M = Mixed ADC & Mixed AADC

5.35 simpleType: containerGroupingDescriptionType

Tag	containerGroupingDescriptionType
Base	Removed

5.36 simpleType: containerGrossWeightType

Tag	containerGrossWeightType
Base	mailxml_base:s05

5.37 simpleType: containerHeightType

Tag	containerHeightType
Base	mailxml_base:n03

5.38 simpleType: containerLevelType

Tag	containerLevelType
Base	xs:string
enumeration	A = CR-Direct Eligibility Type = S, T, P
enumeration	B = Mixed CR in 5 Digit Eligibility Type = S, T, P
enumeration	C = Mixed CR in 3 Digit Eligibility Type = S, T
enumeration	D = CR – 5D Scheme Eligibility Type = S, T, P
enumeration	E = FSS Scheme
enumeration	F = FSS Facility
enumeration	G = 5 Digit (Auto/Presort) Eligibility Type = S, T, P
enumeration	H = 5 Digit (Merged) Eligibility Type = S, T, P
enumeration	I = 5 Digit (Presort Only) Eligibility Type = S, T, P
enumeration	J = 5 Digit (Barcode Only) Eligibility Type = S, T, P
enumeration	K = Metro Scheme Eligibility Type = P
enumeration	M = 5D Scheme (Presort) Eligibility Type = S, T, P
enumeration	N = 5D Scheme (Auto/Presort) Eligibility Type = S, T, P
enumeration	P = 5D Scheme (Barcode) Eligibility Type = S, T, P
enumeration	Q = 5D Scheme (Merged) Eligibility Type = S, T, P
enumeration	R = 3 Digit (Auto, Presort) Eligibility Type = S, T
enumeration	S = 3 Digit (Barcode) Eligibility Type = S, T
enumeration	T = 3 Digit (Presort) Eligibility Type = S, T
enumeration	U = 3 Digit (CR, Auto, Presort)

Copyright © 2014 USPS®. All Rights Reserved

Tag	containerLevelType
	Eligibility Type = S, T, P
enumeration	V = 3 Digit Scheme Eligibility Type = T
enumeration	W = Deleted Place Holder
enumeration	X = SCF Eligibility Type = S, P
enumeration	Y = Protected SCF Eligibility Type = P
enumeration	Z = ADC Eligibility Type = S, T, P
enumeration	AA = AADC Eligibility Type = T
enumeration	AB = Mixed ADC Eligibility Type = S, T, P
enumeration	AC = Mixed AADC Eligibility Type = T
enumeration	AD = ASF Eligibility Type = S, P
enumeration	AE = NDC (previously known as BMC) Eligibility Type = S, P
enumeration	AF = Protected NDC Eligibility Type = P
enumeration	AG = Mixed NDC Eligibility Type = S, P
enumeration	AH = Origin MxADC
enumeration	AI = Protected ADC
enumeration	AJ = Single Piece Container Eligibility Type = S, T
enumeration	AK = MXDS – Mixed Surface Eligibility Type = P
enumeration	AL = MXDA – Mixed Air CSA FCM Only
enumeration	AM = Working Eligibility Type = P
enumeration	AN = Single Piece – First Class Eligibility Type = P
enumeration	AO = Surface Eligibility Type = P
enumeration	AP = Air Eligibility Type = P
enumeration	AQ = Local Eligibility Type = P
enumeration	AR = Origin SCF
enumeration	AS = Origin Mixed ADC Surface
enumeration	AT = Mixed ADC Air
enumeration	BA = Urban Direct Eligibility Type = S, T
enumeration	BB = Rural Direct Eligibility Type = S, T
enumeration	BC = Station Eligibility Type = S, T, P
enumeration	BD = City Eligibility Type = S, T, P
enumeration	BE = FSA Eligibility Type = P
enumeration	BF = DCF Eligibility Type = S, T, P
enumeration	BG = FCP Eligibility Type = S, T, P

Copyright © 2014 USPS®. All Rights Reserved

Tag	containerLevelType
enumeration	BH = Province Eligibility Type = P
enumeration	BI = Residual Eligibility Type = S, T, P
enumeration	BJ = Foreign Eligibility Type = S, T, P
enumeration	BK = Country Eligibility Type = S, T, P
enumeration	BL = Mixed Country Eligibility Type = S, T, P
enumeration	BM = M Bags Eligibility Type = S

5.39 simpleType: containerPickupDateType

Tag	containerPickupDateType
Base	xs:date

5.40 simpleType: containerPickupTimeType

Tag	containerPickupTimeType
Base	xs:time

5.41 simpleType: containerShipDateType

Tag	containerShipDateType
Base	xs:date

5.42 simpleType: containerShipTimeType

Tag	containerShipTimeType
Base	xs:time

5.43 simpleType: contactType

Tag	contactType
Base	xs:string
enumeration	AccountManager
enumeration	Carrier
enumeration	CrossDock
enumeration	CustomerService
enumeration	HelpDesk
enumeration	DropShipCoordinator
enumeration	ApptCoordinator
enumeration	Plant
enumeration	InboundFreightCoordinator
enumeration	SalesOffice
enumeration	TruckDriver
enumeration	Warehouse
enumeration	Other

5.44 simpleType: containerStatusType

Tag	containerStatusType
Base	xs:string
enumeration	Accepted
enumeration	OnHold
enumeration	Rejected

Copyright © 2014 USPS®. All Rights Reserved

5.45 simpleType: containerHeightSourceType

Tag	containerHeightSourceType
Base	xs:string
enumeration	A = Actual
enumeration	E = Estimated

5.46 simpleType: CQTdatabaseIDType

Tag	CQTdatabaseIDType
Base	xs:nonNegativeInteger
totalDigits	8
whiteSpace	collapse

5.47 simpleType: creditDebitIndicator

Tag	creditDebitIndicator
Base	xs:string
enumeration	C = Credit
enumeration	D = Debit

5.48 simpleType: CRIDType

Tag	CRIDType
Base	xs:string
maxLength	15
minLength	1
pattern	([0-9])*

5.49 simpleType: cRIDStatusType

Tag	cRIDStatusType
Base	xs:string
enumeration	New
enumeration	Existing

5.50 simpleType: csaTemplateType

Tag	csaTemplateType
Base	xs:string
enumeration	PVDS-PER
enumeration	DMU-C
enumeration	DMU-P
enumeration	BMEU
enumeration	UPVDS-PER
enumeration	UDMU-C
enumeration	UDMU-P
enumeration	UBMEU
enumeration	U

5.51 simpleType: csaStatusType

Tag	csaStatusType
Base	xs:string
enumeration	ACT
enumeration	PEN
enumeration	INACT
enumeration	INCOMP
enumeration	PREAPP

Copyright © 2014 USPS®. All Rights Reserved

5.52 simpleType: databaseContainerIDType

Tag	databaseContainerIDType
Base	xs:nonNegativeInteger
totalDigits	6

5.53 simpleType: dayFrequencyType

Tag	dayFrequencyType
Base	xs:string
enumeration	Daily
enumeration	Monday
enumeration	Tuesday
enumeration	Wednesday
enumeration	Thursday
enumeration	Friday
enumeration	Saturday
enumeration	Sunday

5.54 simpleType: daysOfWeekType

Tag	daysOfWeekType
Base	xs:string
enumeration	MON
enumeration	TUE
enumeration	WED
enumeration	THU
enumeration	FRI
enumeration	SAT
enumeration	SUN
enumeration	MF
enumeration	MS
enumeration	ALL
enumeration	H

5.55 simpleType: DirectOrMixedCategoryType

Tag	DirectOrMixedCategoryType
Base	String
enumeration	Direct
enumeration	Mixed

5.56 simpleType: dec18-8

Tag	dec18
Base	xs:decimal
totalDigits	18
fractionDigits	8

5.57 simpleType: deliverabilityCodeType

Tag	dec18
Base	xs:string
enumeration	K = COA Match, No Forwarding Address
enumeration	G = COA Match, PO Box Closed, No Forwarding Address
enumeration	W = COA Match with a temporary COA

5.58 simpleType: DMLType

Tag	DMLTypeType
Base	xs:string

Copyright © 2014 USPS®. All Rights Reserved

Tag	DMLTypeType
enumeration	A
enumeration	B
enumeration	C

5.59 simpleType: electronicFileType

Tag	electronicFileType
Base	String 1
enumeration	1=Postage & Tracking File
enumeration	2=Tracking File
enumeration	3=Return Service
enumeration	4=Corrections
enumeration	5=Electronic Verification
enumeration	C=Parcel Return Service

5.60 simpleType: emailType

Tag	emailType
Base	xs:string

5.61 simpleType: enclosedByType

Tag	enclosedByType
Base	xs:string
enumeration	SM = Standard Mail
enumeration	BP = Bound Printed Matter
enumeration	PE = Periodicals
enumeration	PP = Parcel Post
enumeration	ML = Media/Library Mail

5.62 simpleType: entryDiscountType

Tag	entryDiscountType
Base	xs:string
enumeration	N = None
enumeration	B = DNDC (previous DBMC)
enumeration	S = DSCF
enumeration	D = DDU
enumeration	A = DADC
enumeration	C = Origin SCF
enumeration	K = Origin NDC

5.63 simpleType: entryFacilityType

Tag	entryFacilityType
Base	xs:string
enumeration	O = Origin
enumeration	B = NDC (Previous BMC)
enumeration	S = SCF
enumeration	D = DDU
enumeration	A = ADC

5.64 simpleType: entryPointEDPostalCodeType

Tag	entryPointEDPostalCodeType
Base	mailxml_base:s06

Copyright © 2014 USPS®. All Rights Reserved

5.65 simpleType: entryPointEDFacilityTypeType

Tag	entryPointEDFacilityTypeType
Base	mailxml_base:s01

5.66 simpleType: entryPointADLocaleKeyType

Tag	entryPointADLocaleKeyType
Base	mailxml_base:s09

5.67 simpleType: entryPointADPostalCodeType

Tag	entryPointADPostalCodeType
Base	mailxml_base:s09

5.68 simpleType: ErrorWarningCodeType

Tag	ErrorWarningCodeType
Base	xs:string
enumeration	E = Error
enumeration	W = Warning

5.69 simpleType: es3

Tag	es3
Base	xs:string
maxLength	3
minLength	3
whiteSpace	preserve

5.70 simpleType: es4

Tag	es4
Base	xs:string
maxLength	4
minLength	4
whiteSpace	preserve

5.71 simpleType: es5

Tag	es5
Base	xs:string
maxLength	5
minLength	5
whiteSpace	preserve

5.72 simpleType: exemptionCodeType

Tag	exemptionCodeType
Base	xs:string
enumeration	APO
enumeration	APS
enumeration	CAPC
enumeration	DUE
enumeration	HC

5.73 simpleType: fASTSchedulerIDType

Tag	fASTSchedulerIDType
Base	mailxml_base:s12

Copyright © 2014 USPS®. All Rights Reserved

5.74 simpleType: feeNotificationType

Tag	feeNotificationType
Base	String
enumeration	E = Electronic Fee Charged
enumeration	1 = Automated Fee 1st Notice
enumeration	2 = Automated Fee 2nd Notice
enumeration	3 = Automated Fee Charged for 3 or more notices

5.75 simpleType: flatRateIndicatorType

Tag	flatRateIndicatorType
Base	xs:string
enumeration	B = Box – Priority Mail Flat Rate Only
enumeration	C = Priority Mail Critical Mail – Letter
enumeration	D = Priority Mail Critical Mail – Letter with Signature
enumeration	E = Envelope – Priority Mail Flat Rate Only
enumeration	F = Priority Mail Critical Mail – Flat
enumeration	G = Priority Mail Critical Mail – Flat with Signature
enumeration	L = Box – Large Priority Mail Flat Rate Only
enumeration	M = Box – Large Military Destination Priority Mail Flat Rate Only
enumeration	O = Priority Mail Padded Flat Rate Envelope
enumeration	P = Priority Mail Legal Flat Rate Envelope
enumeration	S = Small – Priority Mail Flat Rate Only

5.76 simpleType: formType

Tag	formType
Base	xs:string
enumeration	PM = Priority Mail
enumeration	FC = First-Class
enumeration	SM = Standard Mail
enumeration	BP = Bound Printed Matters
enumeration	PE = Periodicals
enumeration	PP = Parcel Post
enumeration	ML = Media/Library Mail
enumeration	IM = International Mailing

5.77 simpleType: fullServiceComplianceIndicatorType

Tag	fullServiceComplianceIndicatorType
Base	mailxml_base:yesNo

5.78 simpleType: fspiType

Tag	fspiType
Base	xs:string
enumeration	M = Mixed
enumeration	F = Full-Service

5.79 simpleType: gPSSystemType

Tag	gPSSystemType
Base	xs:string
enumeration	ECEF
enumeration	HAE
enumeration	MSL

Copyright © 2014 USPS®. All Rights Reserved

5.80 simpleType: IDType

Tag	IDType
Base	xs:string
enumeration	DriversLicense
enumeration	EmployeeID

5.81 simpleType: iMBType

Tag	iMBType
Base	xs:string
maxLength	34
minLength	20
pattern	([0-9])+

5.82 simpleType: IMcbType

Tag	IMcbType
Base	xs:string
maxLength	24
minLength	21

5.83 simpleType: IMpbType

Tag	IMpbType
Base	String
maxLength	34
minLength	34

5.84 simpleType: iMBarcodeIDType

Tag	iMBarcodeIDType
Base	mailxml_base:ns02

5.85 simpleType: iMBSerialNumber6Type

Tag	iMBSerialNumber6Type
Base	mailxml_base:ns06

5.86 simpleType: iMBSerialNumber9Type

Tag	iMBSerialNumber9Type
Base	mailxml_base:ns09

5.87 simpleType: iMBUpperSerializationType

Tag	iMBUpperSerializationType
Base	mailxml_base:s18

5.88 simpleType: iMBLowerSerializationType

Tag	iMBLowerSerializationType
Base	mailxml_base:s18

5.89 simpleType: IMtbType

Tag	IMtbType
Base	String
maxLength	24
minLength	24

Copyright © 2014 USPS®. All Rights Reserved

5.90 simpleType: includedInOtherDocType

Tag	includedInOtherDocType
Base	xs:string
enumeration	L = Linked
enumeration	O = Original

5.91 simpleType: internalDateType

Tag	internalDateType
Base	xs:date

5.92 simpleType: internationalPSPartType

Tag	internationalPSPartType
Base	String
enumeration	A = First Class ail International Permit Imprint
enumeration	B = International Surface Airlift – ISAL
enumeration	C = International Priority Airmail – IPA
enumeration	D = Priority Mail International Permit Imprint
enumeration	E = Global Shipping Software (GSS) Permit Imprint – Priority Mail International
enumeration	F = Global Shipping Software Permit Imprint – Express Mail International
enumeration	G = Global Shipping Software Permit Imprint – Global Express Guaranteed
enumeration	H = Global Bulk Economy Mail Permit Imprint
enumeration	I = Global Direct Canada Admail Permit Imprint
enumeration	J = Global Direct Canada Publication Mail – Permit Imprint
enumeration	K = Global Direct Canada Letter Mail – Permit Imprint
enumeration	Q = Global Direct Permit Imprint
enumeration	R = Reserved
enumeration	S = Extra Services

5.93 simpleType: internationalZoneType

Tag	internationalZoneType
Base	String
enumeration	1 through 15

5.94 simpleType: internationalPSPartSectionType

Tag	internationalPSPartSectionType
enumeration	ICLM = Canada Incentive Letter Mail Standard (S/L) – Machinable
enumeration	ICLO = Canada Letter Mail Other (Non-Standard and Oversize)
enumeration	ICLP = Canada Incentive Letter Mail Standard (S/L) – Presort
enumeration	ICLPL = Canada Incentive Letter Mail Standard (S/L) – Presort Local
enumeration	ICLS = Canada Letter Mail Standard (S/L)
enumeration	ICOM = Canada Incentive Letter Mail Oversize (O/S) – Machinable
enumeration	ICOP = Canada Incentive Letter Mail Oversize (O/S) – Presort
enumeration	IEM = Express Mail International
enumeration	IEMF = Express Mail International Flat Rate Envelop
enumeration	IFCP = LCP Residual/Forward Consolidation Point (FCP)
enumeration	IFE = Flat Rate Envelop (Individual Weight Limit: 4 lbs)
enumeration	IFLB = Large Flat Rate Box (Individual Weight Limit: 20 lbs)
enumeration	IFMB = Medium Flat Rate Box (Individual Weight Limit: 20 lbs)
enumeration	IFSB = Small Flat Rate Box (Individual Weight Limit: 4 lbs)
enumeration	IGBB = Global Bulk Economy Mail-Base Price-New Jersey Entry
enumeration	IGBM = Global Bulk Economy Mail M-Bag New Jersey Entry
enumeration	IGD = Global Direct
enumeration	IGXG = Global Express Guaranteed (GXG)
enumeration	ILDC = LCP Distribution Center Facility
enumeration	ILDD = LCP Delivery Mode Direct

Copyright © 2014 USPS®. All Rights Reserved

Tag	internationalPSPartSectionType
enumeration	ILDF = LCP Delivery Facility
enumeration	IMBG = M-Bag Airmail Sacks
enumeration	INDG = NDG Presort
enumeration	IPM = Priority Mail International
enumeration	IPMI = International Priority Mail IPA
enumeration	IPMM = International Priority Mail M-Bag IPA
enumeration	IRV = Reserved
enumeration	ISAL = International Surface Airlift – ISAL
enumeration	ISAM = International Surface Airlift M-Bag – ISAL

5.95 simpleType: internationalPriceGroupType

Tag	internationalPriceGroupType
Base	String
enumeration	1 = Canada
enumeration	2 = Mexico
enumeration	3 through 5 = China, Eastern Europe, Hong Kong, Japan, South Korea, Turkey, Western Europe
enumeration	6 through 9 = Africa, Asia (exception include price group 3 through 5), central America, Middle East, South America
enumeration	10 through 15 = Unknown – for future use

5.96 simpleType: inCountyOutCountyIndicatorType

Tag	inCountyOutCountyIndicatorType
Base	xs:string
enumeration	I – In County
enumeration	N = Outside County

5.97 simpleType: jobIDType

Tag	jobIDType
Base	xs:string
maxLength	8
minLength	1
whiteSpace	Preserve

5.98 simpleType: localeKeyType

Tag	localeKeyType
Base	mailxml_base:s09

5.99 simpleType: inductionStatusType

Tag	inductionStatusType
Base	xs:string
enumeration	A = Accepted
enumeration	N = Rejected

5.100 simpleType: logicalPhysicalBundleIndicatorType

Tag	logicalPhysicalBundleIndicatorType
Base	xs:string
enumeration	P = Physical
enumeration	L = Logical

5.101 simpleType: logicalPhysicalContainerIndicatorType

Tag	logicalPhysicalContainerIndicatorType

Copyright © 2014 USPS®. All Rights Reserved

Tag	logicalPhysicalContainerIndicatorType
Base	xs:string
enumeration	P = Physical
enumeration	L = Logical

5.102 simpleType: LowerDateRange

Tag	LowerDateRange
Base	xs:date

5.103 simpleType: mailAgreementTypeType

Tag	mailAgreementTypeType
Base	xs:string
enumeration	A = Alternate Mailing System
enumeration	B = Optional Procedure
enumeration	C = Manifest Mailing
enumeration	D = Value Added
enumeration	E = Combined Mail
enumeration	F = Combined and Value Added

5.104 simpleType: mailClassType

Tag	mailClassType
Base	xs:string
enumeration	1 = First-Class Mail
enumeration	2 = Periodicals
enumeration	3 = Standard Mail
enumeration	4 = Package Services
enumeration	6 = (Future Placeholder)

5.105 simpleType: MailPieceScanAvailabilityDate

Tag	MailPieceScanAvailabilityDate
Base	xs:date

5.106 simpleType: MailPieceScanRecordCount

Tag	MailPieceScanRecordCount
Base	xs:nonNegativeInteger

5.107 simpleType: maildatContainerStatusType

Tag	maildatContainerStatusType
Base	xs:string
enumeration	R = Ready to Pay
enumeration	X = Paid
enumeration	C = Cancel
enumeration	D = Delete
enumeration	P = Preliminary Postage Statement
enumeration	T = Transportation Information Update

5.108 simpleType: mailerID6Type

Tag	mailerID6Type
Base	mailxml_base:ns06

5.109 simpleType: MID6

Tag	MID6
Base	xs:mailerID6Type

Copyright © 2014 USPS®. All Rights Reserved

5.110 simpleType: mailerID9Type

Tag	mailerID9Type
Base	mailxml_base:ns09

5.111 simpleType: MID9

Tag	MID9
Base	xs:mailerID6Type

5.112 simpleType: mailXMLContainerType

Tag	mailXMLContainerType
Base	xs:string
enumeration	1 = #1 Sack
enumeration	2 = #2 Sack
enumeration	3 = #3 Sack
enumeration	4 = 01V Sack
enumeration	5 = 03V Sack
enumeration	6 = OD Sack
enumeration	7 = OD Parcel
enumeration	8 = OD Full Tray Box
enumeration	9 = OD Half Tray Box
enumeration	10 = Flat Trays
enumeration	11 = FRE/FRB
enumeration	12 = OD Surface Transported Pallets
enumeration	13 = OD Full Pallet Box (Surface Only)
enumeration	14 = OD Half Pallet Box (Surface Only)
enumeration	E = EMM Tray
enumeration	F = Flat Tub
enumeration	L = Logical Tray
enumeration	O = 1’ Tray
enumeration	P = Pallet
enumeration	S = Sack (General)
enumeration	T = 2’ Tray
enumeration	V = Sack (Virtual)
enumeration	B = Bedload
enumeration	U – Unit Load Device
enumeration	Z = User Pallet
enumeration	X = (Future Placeholder)
enumeration	H = EIRS 61 – Hamper, Large Canvas
enumeration	A = EIRS 61P – Hamper, Large Plastic
enumeration	G = EIRS 66 – General Purpose Mail Container w/Gate
enumeration	D = EIRS 68 – Eastern Region Mail Container w/Web Door
enumeration	R = EIRS 84 – Wire Container Rigid
enumeration	C = EIRS 84C – Collapsible Wire Container
enumeration	CT = Carton
enumeration	M = Logical Pallet (MLOCR)
enumeration	AB = Air Box
enumeration	Y = PMOD Sack

5.113 simpleType: mailXMLPresentationCategoryType

Tag	mailXMLPresentationCategoryType
Base	xs:string
enumeration	M = MLOCR
enumeration	P = Conventional Presort
enumeration	I = Manifest Individual
enumeration	N = Single Piece
enumeration	S = Manifest Summary

Copyright © 2014 USPS®. All Rights Reserved

5.114 simpleType: manifestType

Tag	manifestType
enumeration	DM = Domestic Mail
enumeration	IM = International Mail

5.115 simpleType: manifestMailClassType

Tag	manifestMailClassType
enumeration	BB = BoundPrinted Material
enumeration	BL = Library Rate
enumeration	BP = Parcel Post
enumeration	BS = Media Mail
enumeration	CP = Priority Mail International Parcels
enumeration	DM = Domestic Matter for the Blind
enumeration	EX = Express Mail®
enumeration	FC = First Class Mail®
enumeration	IE = Express Mail International
enumeration	IL = Priority Mail International Letters
enumeration	LC = First Class Mail International
enumeration	PG = Global Express Guaranteed
enumeration	PM = Priority Mail
enumeration	S2 = Standard Mail Non-Profit
enumeration	S3 = Standard Mail Enhanced Carrier Route
enumeration	S4 = Standard Mail Nonprofit Enhance Carrier Route
enumeration	SA = Standard Mail

5.116 simpleType: manifestRateLevelType

Tag	manifestRateLevelType
enumeration	AD = "ADC Rate”
enumeration	BA = "Basic Rate"
enumeration	BM = "Balloon Rate"
enumeration	BP = "Basic Bound Printed Matter Pre-bar coded"
enumeration	BS = "NDC Special Standard"
enumeration	B3 = "3-Digit Balloon Rate"
enumeration	CB = "Carrier Route Basic Rate"
enumeration	CD = "Express Mail Custom Design"
enumeration	CH = "Carrier Route High Density Rate"
enumeration	CR = "Carrier Route Rate"
enumeration	CS = "Carrier Route Saturation Rate"
enumeration	C1 = "Cubic Pricing Tier 1"
enumeration	C2 = "Cubic Pricing Tier 2"
enumeration	C3 = "Cubic Pricing Tier 3"
enumeration	C4 = "Cubic Pricing Tier 4"
enumeration	C5 = "Cubic Pricing Tier 5"
enumeration	DN = "Dimensional Nonrectangular Rate"
enumeration	DR = "Dimensional Rectangular Rate"
enumeration	E1 = "Express Mail Same Day Airport Flat Rate"
enumeration	E3 = "Express Mail Flat Rate Hold For Pickup"
enumeration	E4 = "Express Mail Flat Rate Post Office To Addressee"
enumeration	FB = "Priority Mail Medium Flat Rate Box"
enumeration	FE = "Flat Rate Envelope"
enumeration	IG = "P/PS<15Lbs, combined length/girth >84" & <= 108" subject to balloon rate"
enumeration	IM = "P/ PS between 108" and 130" subject to oversize rate"
enumeration	MA = "Mixed ADC Rate"
enumeration	MB = "Mixed NDC Rate"
enumeration	NP = "Non-presorted Rate"
enumeration	OS = "Oversize"
enumeration	PG = "PM<15lbs combined length/girth >84" & <=108" subject to balloon rate"

Copyright © 2014 USPS®. All Rights Reserved

Tag	manifestRateLevelType
enumeration	PL = "Priority Mail Large Flat Rate Box"
enumeration	PM = "Priority Mail Large Flat Rate Box APO/FPO"
enumeration	PP = "Express Mail Hold For Pickup"
enumeration	PR = "Presorted Rate"
enumeration	RB = "Bulk Basic"
enumeration	SB = "Media Mail NDC"
enumeration	SP = "Single Piece Rate"
enumeration	S1 = "Single Piece – Flat"
enumeration	S2 = "Single Piece – Parcel"
enumeration	S5 = "Media Mail 5 Digit"
enumeration	1A = "Intra-NDC Single Piece Rate"
enumeration	1E = "Inter-NDC Single Piece Rate"
enumeration	2A = "Intra-NDC Balloon Rate"
enumeration	2E = "Inter-NDC Balloon Rate"
enumeration	3A = "Intra-NDC Oversized Rate"
enumeration	3D = "3-Digit Rate"
enumeration	3E = "Inter-NDC Oversized Rate"
enumeration	5D = "5 Digit Rate"
enumeration	5S = "5 Digit Special Standard"

5.117 simpleType: manifestExtraServiceCode

Tag	manifestExtraServiceCode
enumeration	420 = Parcel Return Service
enumeration	430 = Open & Distribute
enumeration	440 – Re Shipment
enumeration	910 = Certified Mail
enumeration	915 = COD
enumeration	920 = USPS Tracking
enumeration	921 = Signature Confirmation
enumeration	925 = Express Mail Merchandise Insurance
enumeration	930 = Insurance <=$200
enumeration	931 = Insurance >$200
enumeration	935 = Parcel Airlift (PAL)
enumeration	940 = Registered Mail
enumeration	950 = Restricted Delivery
enumeration	955 = Return Receipt
enumeration	957 = Return Receipt Electronic
enumeration	960 = Return Receipt for Merchandise
enumeration	970 = Special Handling
enumeration	980 = Merchandise Return Service (MRS)
enumeration	985 = Hold for Pickup

5.118 simpleType: MarketingOrFulfillmentType

Tag	MarketingOrFulfillmentType
Base	xs:string
enumeration	Marketing
enumeration	Fulfillment

5.119 simpleType: mIDStatusType

Tag	mIDStatusType
Base	xs:string
enumeration	New
enumeration	Existing

Copyright © 2014 USPS®. All Rights Reserved

5.120 simpleType: meteredAffixedMethodType

Tag	meteredAffixedMethodType
Base	xs:string
enumeration	C = Metered - Correct
enumeration	L = Metered – Lowest
enumeration	M = Metered - Neither

5.121 simpleType: MLOCRRateType

Tag	MLOCRRateType
Base	xs:string
enumeration	R
enumeration	N

5.122 simpleType: monthType

Tag	monthType
Base	xs:nonNegativeInteger
maxInclusive	12
minInclusive	1

5.123 simpleType: moveUpdateMethodType

Tag	moveUpdateMethodType
Base	xs:integer
enumeration	0 = None
enumeration	1 = ACS
enumeration	2 = NCOA
enumeration	4 = Mailer Move Update Process
enumeration	5 = Ancillary Service Endorsement
enumeration	6 = Multiple
enumeration	7 = N/A
enumeration	8 = OneCode ACS

5.124 simpleType: MPUIDType

Tag	MPUIDType
Base	xs:nonNegativeInteger
totalDigits	5

5.125 simpleType: MPSQueryType

Tag	MPSQueryType
Base	xs:string
enumeration	A = All Detail
enumeration	S = Sample Detail
enumeration	SC = Scan Count

5.126 simpleType: MPSStateType

Tag	MPSStateType
Base	xs:string
enumeration	1 = Induction
enumeration	2 = In Process
enumeration	3 = Both Induction and In Process
enumeration	4 = Cross Dock
enumeration	5 = USPS Transportation
enumeration	6 = USPS Pick Up

Copyright © 2014 USPS®. All Rights Reserved

5.127 simpleType: ns01

Tag	ns01
Base	xs:string
pattern	[0-9]{1}

5.128 simpleType: ns02

Tag	ns02
Base	xs:string
pattern	[0-9]{2}

5.129 simpleType: ns03

Tag	ns03
Base	xs:string
pattern	[0-9]{3}

5.130 simpleType: ns04

Tag	ns04
Base	xs:string
pattern	[0-9]{4}

5.131 simpleType: ns05

Tag	ns05
Base	xs:string
pattern	[0-9]{5}

5.132 simpleType: ns06

Tag	ns06
Base	xs:string
pattern	[0-9]{6}

5.133 simpleType: ns09

Tag	ns09
Base	xs:string
pattern	[0-9]{9}

5.134 simpleType: ns10

Tag	ns10
Base	xs:string
pattern	[0-9]{10}

5.135 simpleType: ns11

Tag	ns11
Base	xs:string
pattern	[0-9]{11}

5.136 simpleType: ns14

Tag	ns14
Base	xs:string
pattern	[0-9]{14}

Copyright © 2014 USPS®. All Rights Reserved

5.137 simpleType: ns22

Tag	ns22
Base	xs:string
pattern	[0-9]{22}

5.138 simpleType: n01

Tag	n01
Base	xs:positiveInteger
totalDigits	1

5.139 simpleType: n02

Tag	n02
Base	xs:positiveInteger
totalDigits	2

5.140 simpleType: n03

Tag	n03
Base	xs:nonNegativeInteger
totalDigits	3

5.141 simpleType: n05

Tag	n05
Base	xs:nonNegativeInteger
totalDigits	5

5.142 simpleType: n06

Tag	n06
Base	xs:nonNegativeInteger
totalDigits	6

5.143 simpleType: addressType

Tag	addressType
Base	xs:string
enumeration	F = Foreign
enumeration	G = General Delivery
enumeration	H = Highway Route Contract
enumeration	P = Post Office Box
enumeration	R = Rural Route
enumeration	S = Street Address
enumeration	U = Urbanization Name
enumeration	V = Highway Contract Route with box number
enumeration	X = Rural Route with box number

5.144 simpleType: operatingModeType

Tag	operatingModeType
Base	xs:string
enumeration	N = Normal
enumeration	B = ByPass

5.145 simpleType: onePassPlannedOrActualFlagType

Tag	onePassPlannedOrActualFlagType
Base	xs:string

Copyright © 2014 USPS®. All Rights Reserved

Tag	onePassPlannedOrActualFlagType
enumeration	A = Actual
enumeration	P = Planned

5.146 simpleType: onePassOrTwoPassType

Tag	onePassOrTwoPassType
Base	xs:string
enumeration	One
enumeration	Two

5.147 simpleType: packageIDType

Tag	packageIDType
Base	mailxml_base:s06

5.148 simpleType: PackageServicesType

Tag	PackageServicesType
Base	xs:string
enumeration	PS
enumeration	BPM
enumeration	LIB
enumeration	MEDIA
enumeration	PP

5.149 simpleType: packageCountRangeType

Tag	packageCountRangeType
Base	xs:Integer
Pattern	[1-9]|[1-9][0]

5.150 simpleType: packagingMethodType

Tag	packagingMethodType
Base	xs:string
enumeration	0 = Piece Count
enumeration	1 = Weight
enumeration	2 = Both

5.151 simpleType: palletHandlingUnitType

Tag	palletHandlingUnitType
Base	xs:string
enumeration	Sacks
enumeration	Bundles
enumeration	MixedLengthTrays
enumeration	1ft Tray
enumeration	2ft Tray
enumeration	EMM Tray
enumeration	Flat Tub
enumeration	Parcels

5.152 simpleType: palletType

Tag	palletType
Base	xs:string
enumeration	Pallet
enumeration	EIRS 61 - Hamper, Large Canvas
enumeration	EIRS 61P - Hamper, Large Plastic

Copyright © 2014 USPS®. All Rights Reserved

Tag	palletType
enumeration	EIRS 66 - General Purpose Mail Container w/Gate
enumeration	EIRS 68 - Eastern Region Mail Container w/Web Door
enumeration	EIRS 84 - Wire Container Rigid
enumeration	EIRS 84C - Collapsible Wire Container

5.153 simpleType: parentContainerRefIDType

Tag	parentContainerRefIDType
Base	mailxml_base:s06

5.154 simpleType: percentageType

Tag	percentageType
Base	xs:decimal
totalDigits	5
fractionDigits	2
minInclusive	0.00
maxInclusive	100.00

5.155 simpleType: periodicalPriceType

Tag	periodicalPriceType
Base	xs:string
enumeration	D = Non-Advertising Pound Rate – DSCF (B13)
enumeration	C = Non-advertising Pound Rate – DDU (B12)
enumeration	E = Non-Advertising Pound Rate – DADC (B14)
enumeration	R = Repositionable notes (surcharge) (A21, F2)
enumeration	Z = Non-Advertising Pound Rate – All Others (B15)
enumeration	5 = Non-Advertising Piece Rate (C30)
enumeration	9 = Ride-along Surcharge (A20, F1)
enumeration	1 = DDU (A17)

5.156 simpleType: permitTypeType

Tag	permitTypeType
Base	xs:string
enumeration	PI = Permit Imprint
enumeration	MT = Metered Tape
enumeration	PC = Pre-cancelled Stamps
enumeration	BR = Business Reply
enumeration	PE = Periodicals
enumeration	GH = Ghost
enumeration	OI = Official Imprint
enumeration	OM = Official Imprint
enumeration	PP = Pending Periodicals
enumeration	PA = Partial Permit Imprint

5.157 simpleType: phoneNumberType

Tag	phoneNumberType
Base	xs:string
maxLength	25
minLength	1
whiteSpace	preserve

5.158 simpleType: pickupOrDeliveryType

Tag	pickupOrDeliveryType
Base	xs:string

Copyright © 2014 USPS®. All Rights Reserved

Tag	pickupOrDeliveryType
enumeration	Pickup
enumeration	Delivery

5.159 simpleType: planetCodeType

Tag	planetCodeType
Base	xs:string
maxLength	13
minLength	11
pattern	[0-9]{2}

5.160 SimpleType: postageAutoFinalizationType

Tag	postageAutoFinalizationType
Base	xs:string
enumeration	Passed
enumeration	Failed
enumeration	Pending
Enumeration	Not Applicable

5.161 simpleType: postageGroupingIDType

Tag	postageGroupingIDType
Base	mailxml_base:s08

5.162 simpleType: postagePaymentMethodType

Tag	postagePaymentMethodType
Base	xs:string
enumeration	S
enumeration	M
enumeration	P

5.163 simpleType: postageStatementLineNumber1Type

Tag	postageStatementLineNumber1Type
Base	xs:string
enumeration	E26
enumeration	E27
enumeration	E28
enumeration	E29
enumeration	E30
enumeration	E31
enumeration	E32
enumeration	E33
enumeration	E34
enumeration	E35
enumeration	E36
enumeration	E37
enumeration	E38
enumeration	E39
enumeration	E40
enumeration	E41
enumeration	E42
enumeration	E43
enumeration	E44
enumeration	E45

Copyright © 2014 USPS®. All Rights Reserved

Tag	postageStatementLineNumber1Type
enumeration	E46

5.164 simpleType: postageStatementLineNumber2Type

Tag	postageStatementLineNumber2Type
Base	xs:string
enumeration	E1
enumeration	E2
enumeration	E3
enumeration	E4
enumeration	E5
enumeration	E6
enumeration	E7
enumeration	E8
enumeration	E9
enumeration	E10
enumeration	E11
enumeration	E12
enumeration	E13
enumeration	E14
enumeration	E15
enumeration	E16
enumeration	E17
enumeration	E18
enumeration	E19
enumeration	E20
enumeration	E21
enumeration	E22
enumeration	E23
enumeration	E24

5.165 simpleType: postageStatementLineNumber3Type

Tag	postageStatementLineNumber3Type
Base	xs:string
enumeration	D1
enumeration	D2
enumeration	D3
enumeration	D4
enumeration	D5
enumeration	D6
enumeration	D7
enumeration	D8
enumeration	D9
enumeration	D10
enumeration	D11
enumeration	D12
enumeration	D13
enumeration	D14
enumeration	D15
enumeration	D16
enumeration	D17

5.166 simpleType: postageStatementStatusType

Tag	postageStatementStatusType
Base	xs:string

Copyright © 2014 USPS®. All Rights Reserved

Tag	postageStatementStatusType
enumeration	UPD = Updated
enumeration	FIN = Finalized
enumeration	REW = Rework
enumeration	REV = Reversed
enumeration	CAN = Cancelled
enumeration	FAI = Failed Verification
enumeration	PEN = Pending
enumeration	PAS = Passed
enumeration	INC = Incomplete
enumeration	NAP = Not Available for Processing
enumeration	EST = Estimate Postage
enumeration	CON = Consolidated Postage Statement
enumeration	ERR = Error
enumeration	COM = Complete
enumeration	AVW = Address Verification Warning
enumeration	PAV = Pending Address Verification
enumeration	FPP = Finalized Pending Payment

5.167 simpleType: priceType

Tag	priceType
Base	xs:string
enumeration	commercial
enumeration	commercialplus
enumeration	retail
enumeration	NSA

5.168 simpleType: primarySecondaryIndicatorType

Tag	primarySecondaryIndicatorType
Base	xs:string
enumeration	P = Primary
enumeration	S = Secondary

5.169 simpleType: processingCategoryType

Tag	processingCategoryType
Base	xs:string
enumeration	LT = Letter
enumeration	FL = Flat
enumeration	CD = Card
enumeration	OS = Outside Parcel
enumeration	MP = Machinable Parcel
enumeration	IR = Irregular Parcel
enumeration	PF = Parcel, First Class
enumeration	CM = Custom Mail
enumeration	NP = Non-Machinable Parcel
enumeration	Removed
enumeration	Removed
enumeration	SP = Small Packets
enumeration	MB = M-Bags

5.170 simpleType: processingCodeType

Tag	processingCodeType
Base	xs:string
enumeration	S = Surface
enumeration	MXDS = Mixed Surface

Copyright © 2014 USPS®. All Rights Reserved

Tag	processingCodeType
enumeration	L = Locale
enumeration	WKG = Working Mail
enumeration	A = Air Separation
enumeration	MXDA = Mixed Air
enumeration	SP = Single Piece

5.171 simpleType: PTFileIDType

Tag	PTFileIDType
Base	xs:string
enumeration	PUB
enumeration	NSA
enumeration	SEASALE
enumeration	INC
enumeration	FEE
enumeration	SURC
enumeration	DISC
enumeration	1
enumeration	2
enumeration	3
enumeration	4
enumeration	NONE

5.172 simpleType: PTExtraServMinBrkGreaterThanoeEqlType

Tag	PTExtraServMinBrkGreaterThanoeEqlType
Base	mailxml_base:ns09

5.173 simpleType: PTExtraServMaxBrkLessThanorEqlType

Tag	PTExtraServMaxBrkLessThanorEqlType
Base	mailxml_base:ns09

5.174 simpleType: PTExtraServFlatFeeretailType

Tag	PTExtraServFlatFeeretailType
Base	mailxml_base:ns06

5.175 simpleType: PTExtraServIncrementFeeType

Tag	PTExtraServIncrementFeeType
Base	mailxml_base:ns06

5.176 simpleType: PTMachinabilityPreparationType

Tag	PTMachinabilityPreparationType
Base	xs:string
enumeration	AUTO
enumeration	NONAUTO
enumeration	MACH
enumeration	NONMACH
enumeration	IRR
enumeration	NONE

5.177 simpleType: PTExtraServIncrementBreakType

Tag	PTExtraServIncrementBreakType
Base	mailxml_base:ns09

Copyright © 2014 USPS®. All Rights Reserved

5.178 simpleType: PTExtraServicesType

Tag	PTExtraServicesType
Base	xs:string
enumeration	CERTIFICATEOFMAILING
enumeration	CERTIFIEDMAIL
enumeration	COD
enumeration	RESTRICTEDDELIVERY
enumeration	NOTICEOFNONDELIVERY
enumeration	ALTERATIONOFCODCHARGES
enumeration	REGISTRATIONCOD
enumeration	DESIGNATIONOFNEWADDRESS
enumeration	INSURANCE
enumeration	RETURNRECEIPTMAIL
enumeration	RETURNRECEIPTELECTRONIC
enumeration	RETURNRECEIPTAFTERMAILING
enumeration	RETURNRECEIPTFORMERCHANDISE
enumeration	REGISTEREDMAIL
enumeration	SPECIALHANDLING
enumeration	SUNDAYDELIVERY
enumeration	DELIVERYCONFIRMATION
enumeration	SIGNATURECONFIRMATION
enumeration	1
enumeration	2
enumeration	3
enumeration	4
enumeration	5
enumeration	6
enumeration	7
enumeration	8
enumeration	9
enumeration	10

5.179 simpleType: PTContSortBundleSortType

Tag	PTContSortBundleSortType
Base	xs:string
enumeration	SAT
enumeration	HD
enumeration	BASIC
enumeration	5D
enumeration	3D
enumeration	AADC
enumeration	MAADC
enumeration	ADC
enumeration	MADC
enumeration	NDC
enumeration	MNDC
enumeration	SCF
enumeration	SP
enumeration	PRES
enumeration	3DSCF
enumeration	BASIC
enumeration	CR
enumeration	CRBASIC
enumeration	CRHD
enumeration	FIRM
enumeration	CRSAT
enumeration	NONE

Copyright © 2014 USPS®. All Rights Reserved

5.180 simpleType: PTMailEntryType

Tag	PTMailEntryType
Base	xs:string
enumeration	NDC
enumeration	SCF
enumeration	ADC
enumeration	DDU
enumeration	NONE

5.181 simpleType: postagePaymentMethodType

Tag	postagePaymentMethodType
Base	xs:string
enumeration	S
enumeration	M
enumeration	P

5.182 simpleType: PTIncentiveFeeTypeType

Tag	PTIncentiveFeeTypeType
Base	xs:string
enumeration	SS
enumeration	MT
enumeration	VV
enumeration	VP
Enumeration	RE
enumeration	PI
enumeration	SB
enumeration	IV
enumeration	CN
Enumeration	OS
enumeration	GS

5.183 simpleType: PTIncentiveFeeRuleType

Tag	PTIncentiveFeeRuleType
Base	xs:string
enumeration	NM
enumeration	C1
enumeration	D1
Enumeration	D2
enumeration	D3
enumeration	D4
enumeration	D5
enumeration	D6
enumeration	D7
Enumeration	D8
enumeration	D9
enumeration	D10
enumeration	D11
enumeration	D12
Enumeration	D13
enumeration	D14
enumeration	D15
enumeration	D16
enumeration	D17
enumeration	D18
Enumeration	D19
enumeration	D20

Copyright © 2014 USPS®. All Rights Reserved

Tag	PTIncentiveFeeRuleType
enumeration	NONE

5.184 simpleType: PTPriceType

Tag	PTPriceType
Base	xs:string
enumeration	RET
enumeration	CB
enumeration	CP
Enumeration	INC
enumeration	NSA
enumeration	GEPS
enumeration	CPP
enumeration	1
enumeration	2
Enumeration	3
enumeration	4
enumeration	NONE

5.185 simpleType: PTClassType

Tag	PTClassType
Base	xs:string
enumeration	FC
enumeration	PM
enumeration	PC
enumeration	EX
enumeration	PP
enumeration	SM
enumeration	SN
enumeration	MM
enumeration	PP
enumeration	PS
Enumeration	PB
enumeration	PO
enumeration	PN
enumeration	LM
enumeration	PE
enumeration	BB
Enumeration	PR
enumeration	CM
enumeration	NONE

5.186 simpleType: PTMailShapePackagingType

Tag	PTMailShapePackagingType
Base	xs:string
enumeration	LTRS
enumeration	FLTS
enumeration	CDS
enumeration	LRGE
enumeration	FLRE
enumeration	FLE
enumeration	FRPE
enumeration	FRLE
enumeration	SFRB
enumeration	MFRB
enumeration	LFRB

Copyright © 2014 USPS®. All Rights Reserved

Tag	PTMailShapePackagingType
enumeration	LFRBA
enumeration	RBA
enumeration	RBB

5.187 simpleType: PTDicsountType

Tag	PTDicsountType
Base	xs:string
enumeration	FIXED
enumeration	VARIABLE
enumeration	PERCENT
enumeration	NONE

5.188 simpleType: PTPLBZNIndType

Tag	PTPLBZNIndType
Base	xs:string
enumeration	BP
enumeration	LB
enumeration	1
enumeration	2
enumeration	3
enumeration	4
enumeration	5
enumeration	6
enumeration	7
enumeration	8
enumeration	1-8
enumeration	ZADC
enumeration	ZSCF
enumeration	ZDDU
enumeration	NONE

5.189 simpleType: PTPriceAmountType

Tag	PTPriceAmountType
Base	mailxml_base:ns06

5.190 simpleType: PTMinBreakType

Tag	PTMinBreakType
Base	mailxml_base:ns06

5.191 simpleType: PTMaxBreakType

Tag	PTMaxBreakType
Base	mailxml_base:ns06

5.192 simpleType: PTPriceStructureType

Tag	PTPriceStructureType
Base	xs:string
enumeration	OZNZ
enumeration	LBNZ
enumeration	LBZ
enumeration	CU
enumeration	FR
enumeration	PLB
enumeration	PLBZ

Copyright © 2014 USPS®. All Rights Reserved

Tag	PTPriceStructureType
enumeration	ZONE
enumeration	PERPNZ
enumeration	PERLBNZ
enumeration	PERLB
enumeration	NONE

5.193 simpleType: PTPerPriceType

Tag	PTPerPriceType
Base	xs:string
enumeration	BUND
enumeration	POC
enumeration	LBIC
enumeration	LBOC
enumeration	CONT
enumeration	RIDEALONG
enumeration	REPIC
enumeration	REPOC
enumeration	RIDEALONG
enumeration	RIDEALONG
enumeration	NONE

5.194 simpleType: PTPerAdvType

Tag	PTPerAdvType
Base	xs:string
enumeration	ADV
enumeration	SCAGADV
enumeration	NADV
enumeration	SCAGNADV
enumeration	NONE

5.195 simpleType: PTPerBarcodedType

Tag	PTPerBarcodedType
Base	xs:string
enumeration	PALLET
enumeration	TRAYSACK
enumeration	MADC
enumeration	ADCTRAYSACK
enumeration	3DSCF
enumeration	5DCR
enumeration	ADCPALLET
enumeration	3DSCFPALLET
enumeration	5DCRPALLET
enumeration	NONE

5.196 simpleType: PTExtraServicePriceStructureType

Tag	PTExtraServicePriceStructureType
Base	xs:string
enumeration	FIXED
enumeration	VARIABLE
enumeration	VARIABLEINCREMENTAL
enumeration	RETAIL
enumeration	NONE

Copyright © 2014 USPS®. All Rights Reserved

5.197 simpleType: qualificationReportClassType

Tag	qualificationReportClassType
Base	xs:string
enumeration	FC = First Class
enumeration	S = Standard
enumeration	P = Periodicals
enumeration	PM = Priority Mail
enumeration	PP = Parcel Post
enumeration	A = Air Mail

5.198 simpleType: rateCategoryType

Tag	rateCategoryType
Base	xs:string
enumeration	A = Saturation ECR
Enumeration	A1 = Non-Automation Saturation – ECR
enumeration	AF = Saturation ECT Letter
enumeration	B = High Density ECR
Enumeration	B1 = Non-Automation High Density - ECR
Enumeration	B4 = Standard Mail - High Density Lite
Enumeration	B5 = Non Automation - Standard Mail - High Density Lite
enumeration	BF = High Density SCR Letter
enumeration	C = High Density Plus – ECR Catalog
enumeration	C1 = Non Automation High Density Plus
enumeration	D = Carrier Route
enumeration	D1 = Non Automation Carrier Route
enumeration	DF = Carrier Letter
enumeration	E = 5 Digit Barcode
enumeration	FB = Firm Bundle (Not In-County)
enumeration	G = 5D Non-Barcode
enumeration	GF = 5D Letter
enumeration	H = 3 Digit Barcode
enumeration	K = 3D Non-Barcode
enumeration	KF = 3D Letter
enumeration	L = Basic Barcode
enumeration	L1 = AADC Barcode
enumeration	L2 = Mixed AADC Barcode
enumeration	L3 = ADC Barcode
enumeration	L4 = Mixed ADC Barcode
enumeration	L5 = ADC Non-Barcode
enumeration	L6 = Mixed ADC Non-Barcode
enumeration	L7 = AADC Non-Barcode
enumeration	L8 = Mixed AADC Non-Barcode
enumeration	TE = 5-Digit
enumeration	TK = SCF
enumeration	TQ = NDC
enumeration	TR = Mixed NDC
enumeration	M = placeholder
enumeration	N = Basic Non-Automation (Basic Presorted)
enumeration	O = Carrier Route – Barcode
enumeration	O1 = Non Automation Carrier Route – Barcode *CURRENTLY NOT ALLOWED TO BE USED.*
enumeration	PI = 5 Digit Parcel 0.2063 Pounds or less
enumeration	PM = 3 Digit Parcel 0.2063 Pounds or less
enumeration	P7 = NDC Parcel 0.2063 pounds or less
enumeration	P8 = Mixed NDC Parcel 0.2063 Pounds or less
enumeration	PE = 5 Digit Machinable Parcel over 0.2063 Pounds

Copyright © 2014 USPS®. All Rights Reserved

Tag	rateCategoryType
enumeration	PQ = NDC Machinable Parcel over 0.2063 Pounds
enumeration	PR = Mixed NDC Machinable Parcel over 0.2063 Pounds
enumeration	PG = 5 Digit Irregular Parcel over 0.2063 Pounds
enumeration	PK = 3 Digit Irregular Parcel over 0.2063 Pounds
enumeration	P5 = NDC Irregular Parcel over 0.2063 Pounds
enumeration	P6 = Mixed NDC Irregular Parcel over 0.2063 Pounds
enumeration	S = Single Piece
enumeration	Z1 = Parcel Post (NDC Sort)
enumeration	Z2 = Parcel Post (ONDC Sort)
enumeration	P10 = Priority Mail Regional Rate Box A (max weight 15 lbs)
enumeration	P11 = Priority Mail Regional Rate Box B (max weight 20 lbs)
enumeration	P12 = Priority Mail – Cubic Tier 1 (up to .10 lbs)
enumeration	P13 = Priority Mail – Cubic Tier 2 (up to .20 lbs)
enumeration	P14 = Priority Mail – Cubic Tier 3 (up to .30 lbs)
enumeration	P15 = Priority Mail – Cubic Tier 4 (up to .40 lbs)
enumeration	P16 = Priority Mail – Cubic Tier 5 (up to .50 lbs)
enumeration	IA10 = International Postcards
enumeration	IA11 = Letters (up to 3.5 ounces), Flats and Packages/Small Packets (up to 4 pounds)
enumeration	IA12 = Nonmachinable Surcharge (letters only, up to 3.5 ounces)
enumeration	IA13 = M-Bag Airmail
enumeration	IB14 = Worldwide Nonpresort
enumeration	IB15 = International Surface Air Lift-M-Bag-ISAL
enumeration	IC15 = International Priority Mail-IPA
enumeration	IC17 = Worldwide Nonpresort
enumeration	IC18 = International Priority Mail-M-Bag-IPA
enumeration	ID19 = Priority Mail International
enumeration	ID20 = Flat Rate Envelopes (Individual Weight Limit: 4 lbs.) (15" x 9 1/2" or Smaller)
enumeration	ID21 = Padded Flat Rate Envelope (Individual Weight Limit: 4 lbs.)
enumeration	ID22 = Small Flat Rate Boxes (Individual Weight Limit: 4 lbs.) (Including items O-Small FRBX, ODVDS, and O-1096-L)
enumeration	ID23 = Medium Flat Rate Boxes (Individual Weight Limit: 20 lbs.)
enumeration	ID24 = Large Flat Rate Box (Individual Weight Limit: 20 lbs.)
enumeration	IE25 = Flat Rate Envelopes (Individual Weight Limit: 4 lbs.) (15" x 9 1/2" or Smaller)
enumeration	IE26 = Padded Flat Rate Envelope (Individual Weight Limit 4 lbs.)
enumeration	IE27 = Small Flat Rate Boxes (Individual Weight Limit: 4 lbs.) (Including items O-Small FRBX, ODVDS, and O-1096-L)
enumeration	IE28 = Medium Flat Rate Boxes (Individual Weight Limit: 20 lbs.)
enumeration	IE29 = Large Flat Rate Box (Individual Weight Limit: 20 lbs.)
enumeration	IF30 = Express Mail International
enumeration	IF31 = Express Mail International Flat Rate Envelopes (15" x 9 1/2" or Smaller)
enumeration	IG32 = Global Express Guaranteed (GXG)
enumeration	IH33 = Global Bulk Economy Mail-Base Prices-New Jersey Entry
enumeration	IH34 = Global Bulk Economy Mail-M-Bag - New Jersey Entry
enumeration	II35 = NDG Presort
enumeration	II36 = LCP Delivery Mode Direct
enumeration	II37 = LCP Delivery Facility
enumeration	II38 = LCP Distribution Center Facility (DCF)
enumeration	II39 = LCP Forward Consolidation Point (FCP)
enumeration	II40 = LCP Residual
enumeration	II41 = Excess Weight Postage-if applicable (for items over 0.1100 lbs. up to 1.100 lbs. [over 1.76 oz. up to 17.6 oz.])
enumeration	IJ42 = NDG Presort
enumeration	IJ43 = LCP Delivery Mode Direct
enumeration	IJ44 = LCP Delivery Facility
enumeration	IJ45 = LCP Distribution Center Facility (DCF)
enumeration	IJ46 = LCP Forward Consolidation Point (FCP)
enumeration	IJ47 = LCP Residual

Copyright © 2014 USPS®. All Rights Reserved

Tag	rateCategoryType
enumeration	IK48 = Canada Lettermail - Standard (S/L) - up to 1.0576 oz.
enumeration	IK49 = Canada Lettermail - Standard (S/L) -over 1.0576 oz. and up to 1.7632 oz.
enumeration	IK50 = Canada Lettermail - Other Lettermail (Non-standard and Oversize) - up to 3.5264 oz.
enumeration	IK51 = Canada Lettermail - Other Lettermail (Non-standard and Oversize) - over 3.5264 oz. and up to 7.0544 oz.
enumeration	IK52 = Canada Lettermail - Other Lettermail (Non-standard and Oversize) - over 7.0544 oz. and up to 10.5808 oz.
enumeration	IK53 = Canada Lettermail - Other Lettermail (Non-standard and Oversize) - over 10.5808 oz. and up to 14.1088 oz.
enumeration	IK54 = Canada Lettermail - Other Lettermail (Non-standard and Oversize) - over 14.1088 oz. and up to 17.6368 oz.
enumeration	IK55 = Canada Incentive Lettermail - Standard (S/L) Machinable - up to 1.0576 oz.
enumeration	IK56 = Canada Incentive Lettermail - Standard (S/L) Machinable - over 1.0576 oz. and up to 1.7632 oz.
enumeration	IK57 = Canada Incentive Lettermail - Standard (S/L) Machinable - over 1.7632 oz. and up to 3.5264 oz.
enumeration	IK58 = Canada Incentive Lettermail - Standard (S/L) - Presort - up to 1.0576 oz.
enumeration	IK59 = Canada Incentive Lettermail - Standard (S/L) - Presort - over 1.0576 oz. and up to 1.7632 oz.
enumeration	IK60 = Canada Incentive Lettermail - Standard (S/L) - Presort - over 1.7632 oz. and up to 3.5264 oz.
enumeration	IK61 = Canada Incentive Lettermail - Standard (S/L) - Presort Local - up to 1.0576 oz.
enumeration	IK62 = Canada Incentive Lettermail - Standard (S/L) - Presort Local - over 1.0576 oz. and up to 1.7632 oz.
enumeration	IK63 = Canada Incentive Lettermail - Standard (S/L) - Presort Local - over 1.7632 oz. and up to 3.5264 oz.
enumeration	IK64 = Canada Incentive Lettermail - Oversize (O/S) - Machinable - up to 3.5264 oz.
enumeration	IK65 = Canada Incentive Lettermail - Oversize (O/S) - Machinable - over 3.5264 oz. and up to 17.6368 oz.
enumeration	IK66 = Canada Incentive Lettermail - Oversize (O/S) - Presort - up to 3.5264 oz.
enumeration	IK67 = Canada Incentive Lettermail - Oversize (O/S) - Presort - over 3.5264 oz. and up to 17.6368 oz.
enumeration	IQ68 = Global Direct
enumeration	IR69 = Reserved
enumeration	PS1 = Reserved
enumeration	PS2 = Reserved
enumeration	PS3 = Reserved
enumeration	PS4 = Reserved
enumeration	PS5 = Reserved
enumeration	PS6 = Reserved
enumeration	PS7 = Reserved
enumeration	PS8 = Reserved
enumeration	PS9 = Reserved
enumeration	PS11 = Reserved

5.199 simpleType: rateLevelType

Tag	rateLevelType
Base	xs:string
enumeration	SP = Single Piece
enumeration	5B = Auto 5 Digit
enumeration	3B = Auto 3 Digit
enumeration	AB = Auto ADC/AADC
enumeration	PSRT = Presort
enumeration	5D = Presort 5 Digit
enumeration	3D = Presort 3 Digit
enumeration	NDC = NDC Presort
enumeration	ONDC = ONDC Presort
enumeration	BP = Standard Mail NDC
enumeration	MP = Mixed NDC Standard
enumeration	AD = ADC Presort
enumeration	MD = Mixed ADC Presort
enumeration	WS = Carrier Route Saturation

Copyright © 2014 USPS®. All Rights Reserved

Tag	rateLevelType
enumeration	HD = Carrier Route High Density
enumeration	CR = Carrier Route Basic
enumeration	MB = Auto Mixed ADC/AADC
enumeration	FB = Firm Bundle
enumeration	BB = Barcode Basic
enumeration	SCF = Sectional Center Facility

5.200 simpleType: rateLevelIndicatorType

Tag	rateLevelIndicatorType
Base	xs:string
enumeration	A = Auto (use with Rate Level 5B, 3B, AB, MB)
enumeration	B = Non-Auto (use with Rate Level 5D, 3D, AD, MD)
enumeration	C = ECR (use with Rate Level WS, HD, CR)
enumeration	M = Machinable (use with Rate Level AB, MB)
enumeration	N = Non-Machinable (use with Rate Level 5D, 3D, AD, MD)

5.201 simpleType: rateType

Tag	rateType
Base	xs:string
enumeration	R = Regular
enumeration	L = Library Mail
enumeration	B = Bound Printed Matter
enumeration	C = Classroom
enumeration	S = Science of Agriculture
enumeration	F = Media Mail
enumeration	A = Alt Delivery
enumeration	N = Non-Profit
enumeration	P = Parcel Post
enumeration	D = Parcel Select
enumeration	T = Priority Mail
enumeration	X = Other
enumeration	H = (Placeholders)
enumeration	M = (Placeholders)
enumeration	Z = (Placeholders)
enumeration	E = Priority Mail Flat Fixed (Rate Envelope)
enumeration	G = Priority Mail Flat Fixed (rate Box)
enumeration	1 = UA (International)
enumeration	2 = UL (International)
enumeration	3 = UM (International)
enumeration	4 = UR (International)
enumeration	J = Priority Mail Flat – Large Box
enumeration	K = Priority Mail Flat – Large Box APO/FPO
enumeration	V=FCM Election Mail
enumeration	W = Science and Agriculture Limited
enumeration	Y = Regular Limited Circulation

5.202 simpleType: reasonCodeType

Tag	reasonCodeType
Base	xs:string
enumeration	A = Attempted – Not Known
enumeration	B = Returned for Better Address
enumeration	D = Outside Delivery Limits
enumeration	E = In Dispute
enumeration	I = Insufficient Address

Copyright © 2014 USPS®. All Rights Reserved

Tag	reasonCodeType
enumeration	L = Illegible
enumeration	M = No Mail Receptacle
enumeration	N = No such number
enumeration	P = Deceased
enumeration	Q = Not Deliverable as Addressed/ Unable to Forward
enumeration	R = Refused
enumeration	S = No Such Street
enumeration	U = Unclaimed
enumeration	V = Vacant
enumeration	X = No Such Office

5.203 simpleType: recurringStatusType

Tag	recurringStatusType
Base	xs:string
enumeration	Active
enumeration	Pending
enumeration	All

5.204 simpleType: reservationNumberType

Tag	reservationNumberType
Base	mailxml_base:s15

5.205 simpleType: retrieveDataBy

Tag	retrieveDataBy
Base	xs:string
enumeration	FS = Full Service
enumeration	NFS = Non-Full Service
enumeration	Both

5.206 simpleType: roleType

Tag	roleType
Base	xs:string
enumeration	Data Update Agent
enumeration	Owner
enumeration	Confirm Subscriber
enumeration	Confirm Data Receiver
enumeration	ACS Data Receiver
enumeration	ACS Subscriber
enumeration	List Owner
enumeration	Mail Creator
enumeration	Addressor
enumeration	Comail
enumeration	CoMingler
enumeration	MLOCR
enumeration	Mail Owner
enumeration	Mail Agent
enumeration	Entry Point Planner
enumeration	Shipment Planner
enumeration	Consolidator
enumeration	Secondary Consolidator
enumeration	Appointment Management Receiver
enumeration	Consignee/Product Receiver
enumeration	Dispatcher
enumeration	Tracker CONFIRM-scan

Copyright © 2014 USPS®. All Rights Reserved

Tag	roleType
enumeration	Tracker CONFIRM-payer
enumeration	Tracker Seed Source
enumeration	Tracker Piece-level-scan
enumeration	Tracker ASN-scan
enumeration	Tracker Induction-scan
enumeration	Tracker Planet-code
enumeration	ACS receiver
enumeration	ACS payer
enumeration	Seamless Acceptance
enumeration	Seamless Verification
enumeration	Security
enumeration	Logistics Provider
enumeration	Carrier
enumeration	Data Brokering Agent
enumeration	Nixie
enumeration	StartTheClock
enumeration	ContainerVisibility
enumeration	DeliveryPointValidation

5.207 simpleType: responsibleTransportationPartyType

Tag	responsibleTransportationPartyType
Base	xs:string
enumeration	Shipper
enumeration	Consignee

5.208 simpleType: RoutingZipCodeType

Tag	RoutingZipCodeType
Base	xs:string
maxLength	11
minLength	0

5.209 simpleType: s01

Tag	s01
Base	xs:string
maxLength	1
minLength	1
whiteSpace	preserve

5.210 simpleType: s02

Tag	s02
Base	xs:string
maxLength	2
minLength	1
whiteSpace	preserve

5.211 simpleType: s03

Tag	s03
Base	xs:string
maxLength	3
minLength	1
whiteSpace	preserve

Copyright © 2014 USPS®. All Rights Reserved

5.212 simpleType: s04

Tag	s04
Base	xs:string
maxLength	4
minLength	1
whiteSpace	preserve

5.213 simpleType: s05

Tag	s05
Base	xs:string
maxLength	5
minLength	1
whiteSpace	preserve

5.214 simpleType: s06

Tag	s06
Base	xs:string
maxLength	6
minLength	1
whiteSpace	preserve

5.215 simpleType: s07

Tag	s07
Base	xs:string
maxLength	7
minLength	1
whiteSpace	preserve

5.216 simpleType: s08

Tag	s08
Base	xs:string
maxLength	8
minLength	1
whiteSpace	preserve

5.217 simpleType: s09

Tag	s09
Base	xs:string
maxLength	9
minLength	1
whiteSpace	preserve

5.218 simpleType: s10

Tag	s10
Base	xs:string
maxLength	10
minLength	1
whiteSpace	preserve

5.219 simpleType: s11

Tag	s11
Base	xs:string

Copyright © 2014 USPS®. All Rights Reserved

Tag	s11
maxLength	11
minLength	1
whiteSpace	preserve

5.220 simpleType: s12

Tag	s12
Base	xs:string
maxLength	12
minLength	1
whiteSpace	preserve

5.221 simpleType: s15

Tag	s15
Base	xs:string
maxLength	15
minLength	1
whiteSpace	preserve

5.222 simpleType: s16

Tag	s16
Base	xs:string
maxLength	16
minLength	1
whiteSpace	preserve

5.223 simpleType: s18

Tag	s18
Base	xs:string
maxLength	18
minLength	1
whiteSpace	preserve

5.224 simpleType: s20

Tag	s20
Base	xs:string
maxLength	20
minLength	1
whiteSpace	preserve

5.225 simpleType: s22

Tag	s22
Base	xs:string
maxLength	22
minLength	1
whiteSpace	preserve

5.226 simpleType: s25

Tag	s25
Base	xs:string
maxLength	25
minLength	1
whiteSpace	preserve

Copyright © 2014 USPS®. All Rights Reserved

5.227 simpleType: s28

Tag	s28
Base	xs:string
maxLength	28
minLength	1
whiteSpace	preserve

5.228 simpleType: s30

Tag	s30
Base	xs:string
maxLength	30
minLength	1
whiteSpace	preserve

5.229 simpleType: s31

Tag	s31
Base	xs:string
maxLength	31
minLength	1
whiteSpace	preserve

5.230 simpleType: s34

Tag	s34
Base	xs:string
maxLength	34
minLength	1
whiteSpace	preserve

5.231 simpleType: s37

Tag	s37
Base	xs:string
maxLength	37
minLength	1
whiteSpace	preserve

5.232 simpleType: s40

Tag	s40
Base	xs:string
maxLength	40
minLength	1
whiteSpace	preserve

5.233 simpleType: s45

Tag	s45
Base	xs:string
maxLength	45
minLength	1
whiteSpace	preserve

5.234 simpleType: s50

Tag	s50
Base	xs:string
maxLength	50

Copyright © 2014 USPS®. All Rights Reserved

Tag	s50
minLength	1
whiteSpace	preserve

5.235 simpleType: s60

Tag	s60
Base	xs:string
maxLength	60
minLength	1
whiteSpace	preserve

5.236 simpleType: s64

Tag	s64
Base	xs:string
maxLength	64
minLength	1
whiteSpace	preserve

5.237 simpleType: s66

Tag	s66
Base	xs:string
maxLength	66
minLength	1
whiteSpace	preserve

5.238 simpleType: s80

Tag	s80
Base	xs:string
maxLength	80
minLength	1
whiteSpace	preserve

5.239 simpleType: s256

Tag	s256
Base	xs:string
maxLength	256
minLength	1
whiteSpace	preserve

5.240 simpleType: s260

Tag	s260
Base	xs:string
maxLength	260
minLength	1
whiteSpace	preserve

5.241 simpleType: s1000

Tag	s1000
Base	xs:string
maxLength	1000
minLength	1
whiteSpace	preserve

Copyright © 2014 USPS®. All Rights Reserved

5.242 simpleType: sackingBasisType

Tag	sackingBasisType
Base	xs:string
enumeration	0 = Piece Count
enumeration	1 = 20 lbs.
enumeration	2 = 125 Pieces
enumeration	3 = 15 lbs.
enumeration	4 = Both

5.243 simpleType: ScanState

Tag	ScanState
Base	xs: MPSStateType

5.244 simpleType: scheduledInductionDateType

Tag	scheduledInductionDateType
Base	xs:date

5.245 simpleType: scheduledInductionTimeType

Tag	scheduledInductionTimeType
Base	xs:time

5.246 simpleType: scheduledInHomeDateType

Tag	scheduledInHomeDateType
Base	xs:date

5.247 simpleType: serialNumberSevenOrEleven

Tag	serialNumberSevenOrEleven
Base	String
Pattern	"[0-9]{7}|[0-9]{11}"

5.248 simpleType: serialNumberTenOrFourteen

Tag	serialNumberTenOrFourteen
Base	String
Pattern	"[0-9]{10}|[0-9]{14}"

5.249 simpleType: serviceLevelIndicatorType

Tag	serviceLevelIndicatorType
Base	xs:string
enumeration	F = Full-Service
enumeration	B = Basic
enumeration	O = Other

5.250 simpleType: serviceCodeType

Tag	serviceCodeType
Base	xs:string
enumeration	CM = Certified Mail
enumeration	COD = Collect on Delivery
enumeration	CODE = Electronic Collect on Delivery
enumeration	COM = Certificate of Mailing
enumeration	DC = USPS Tracking
enumeration	IM = Insured Mail

Copyright © 2014 USPS®. All Rights Reserved

Tag	serviceCodeType
enumeration	PAL = Parcel Airlift
enumeration	RD = Restricted Delivery
enumeration	RM = Registered Mail
enumeration	RR = Return Receipt
enumeration	RRE = Return Receipt Electronic
enumeration	RRM = Return Receipt for Merchandise
enumeration	SC = Signature Confirmation
enumeration	SH = Special Handling
enumeration	AS = Adult Signature
enumeration	RAS = Restricted Adult Signature
enumeration	DCD=Day Certain Delivery
enumeration	CBM = Certificate of Bulk Mailing

5.251 simpleType: ServiceTypeCodeType

Tag	ServiceTypeCodeType
Base	mailxml_base:ns03

5.252 simpleType: sortationLevelType

Tag	sortationLevelType
Base	xs:string
enumeration	CRD
enumeration	5DG
enumeration	CR5
enumeration	5DGS
enumeration	CR5S
enumeration	M5D
enumeration	M5DS
enumeration	MET
enumeration	3DG
enumeration	CR3
enumeration	3DGS
enumeration	ADC
enumeration	AADC
enumeration	MADC
enumeration	MAAD
enumeration	SCF
enumeration	PSCF
enumeration	NDC
enumeration	PNDC
enumeration	MNDC
enumeration	ASF
enumeration	OMX
enumeration	PADC
enumeration	MRDC
enumeration	SP
enumeration	MXDS
enumeration	MXDA
enumeration	WORKING
enumeration	SINGLEPIECE
enumeration	SURFACE
enumeration	AIR
enumeration	LOCAL

Copyright © 2014 USPS®. All Rights Reserved

5.253 simpleType: serviceSubCodeType

Tag	serviceSubCodeType
Base	xs:string
enumeration	N = None or Not Bulk
enumeration	E = Electronic
enumeration	R = Retail or Registered
enumeration	T = Requested at Time of Mailing
enumeration	B = Bulk

5.254 simpleType: severityType

Tag	severityType
Base	xs:string
enumeration	Error
enumeration	Warning
enumeration	Information

5.255 simpleType: simplifiedAddressType

Tag	simplifiedAddressType
Base	xs:string
enumeration	M = Mixed
enumeration	R = Residential
enumeration	B = Business

5.256 simpleType: standardFlatType

Tag	standardFlatTypeType
Base	xs:string
enumeration	Catalog
enumeration	NotCatalog

5.257 simpleType: stateCode

Tag	stateCode
Base	xs:string
enumeration	AA
enumeration	AE
enumeration	AP
enumeration	AL
enumeration	AK
enumeration	AS
enumeration	AZ
enumeration	AR
enumeration	CA
enumeration	CO
enumeration	CT
enumeration	DE
enumeration	DC
enumeration	FM
enumeration	FL
enumeration	GA
enumeration	GU
enumeration	HI
enumeration	IL
enumeration	IN
enumeration	IA
enumeration	ID

Copyright © 2014 USPS®. All Rights Reserved

Tag	stateCode
enumeration	KS
enumeration	KY
enumeration	LA
enumeration	MH
enumeration	MD
enumeration	MA
enumeration	MO
enumeration	MI
enumeration	MN
enumeration	MS
enumeration	MT
enumeration	NE
enumeration	NH
enumeration	NV
enumeration	NJ
enumeration	NM
enumeration	NY
enumeration	NC
enumeration	ND
enumeration	MP
enumeration	OH
enumeration	OR
enumeration	OK
enumeration	PW
enumeration	PA
enumeration	PR
enumeration	RI
enumeration	SC
enumeration	SD
enumeration	TN
enumeration	TX
enumeration	UT
enumeration	VT
enumeration	VI
enumeration	VA
enumeration	WA
enumeration	WV
enumeration	WI
enumeration	WY

5.258 simpleType: statusType

Tag	statusType
Base	xs:string
enumeration	Accepted
enumeration	Amended
enumeration	Cancelled
enumeration	Counterproposal
enumeration	New
enumeration	NoAction
enumeration	Original
enumeration	PartiallyAccepted
enumeration	Pending
enumeration	Rejected
enumeration	Replaced

Copyright © 2014 USPS®. All Rights Reserved

5.259 simpleType: stopDesignatorType

Tag	stopDesignatorType
Base	mailxml_base:s02

5.260 simpleType: surchargeType

Tag	surchargeType
Base	xs:string
enumeration	2 = Oversized Surcharge
enumeration	A = First-Class Mail Parcel Surcharge
enumeration	D = Dimensional Rate
enumeration	N = Not Oversized
enumeration	P = Balloon Surcharge
enumeration	E = Permit Reply Mail
enumeration	R = First-Class Mail Non-machinable Letters (0.0625 lbs or less)
enumeration	L = Detached Address Labels Used

5.261 simpleType: totalWeightType

Tag	totalWeightType
Base	mailxml_base:s05

5.262 simpleType: trailerLengthType

Tag	trailerLengthType
Base	xs:string
enumeration	20ft
enumeration	40ft
enumeration	45ft
enumeration	48ft
enumeration	53ft

5.263 simpleType: transportationMethodType

Tag	transportationMethodType
Base	xs:string
enumeration	USPS
enumeration	Mailer

5.264 simpleType: transportationModeType

Tag	transportationModeType
Base	xs:string
enumeration	0 = Reject Due to Error
enumeration	1 = Local and Working
enumeration	2 = Bypassed or Unassigned Surface or Air Mail
enumeration	3 = Assigned Surface (S-AMS Surface)
enumeration	4 = Assigned Air
enumeration	9 = Reject Due to Purge

5.265 simpleType: transShipBoLNumberType

Tag	transShipBoLNumberType
Base	mailxml_base:s05

5.266 simpleType: trayType

Tag	trayType
Base	xs:string
enumeration	MixedLengthTrays

Copyright © 2014 USPS®. All Rights Reserved

Tag	trayType
enumeration	1ft Tray
enumeration	2ft Tray
enumeration	EMM Tray
enumeration	Flat Tub

5.267 simpleType: trayTypeIndicatorType

Tag	trayTypeIndicatorType
Base	xs:string
enumeration	T = 2 Foot Tray
enumeration	M = MLOCR
enumeration	N = MM Tray
enumeration	E = EMM Tray
enumeration	O = 1 Foot Tray
enumeration	U = Unit Load Device
Refer to Mail.dat guide for a complete list of container types from the Container summary Record – .csms	

5.268 simpleType: truckDispatchNumberType

Tag	truckDispatchNumberType
Base	mailxml_base:s10

5.269 simpleType: unitLoadType

Tag	unitLoadType
Base	xs:string
enumeration	CrossDockPallets
enumeration	WorkingPallets
enumeration	Trailers

5.270 simpleType: uOMType

Tag	uOMType
Base	xs:string
enumeration	AirDryMetricTonne
enumeration	AirDryPercent
enumeration	AirDryShortTon
enumeration	Bale
enumeration	BoardFoot
enumeration	BookUnit
enumeration	Box
enumeration	Bundle
enumeration	C-Size
enumeration	Centimeter
enumeration	Cord
enumeration	CubicFoot
enumeration	CubicMeter
enumeration	Cubit
enumeration	Day
enumeration	DotsPerInch
enumeration	Foot
enumeration	Gallon
enumeration	Gram
enumeration	GramsPerSquareMeter
enumeration	Hour
enumeration	HundredBoardFeet
enumeration	HundredLinealFeet
enumeration	HundredPound

Copyright © 2014 USPS®. All Rights Reserved

Tag	uOMType
enumeration	HundredSquareFeet
enumeration	Inch
enumeration	Kilogram
enumeration	KilogramsPerDay
enumeration	KilogramsPerWeek
enumeration	KnownBreaks
enumeration	Layer
enumeration	Leaves
enumeration	LinearFoot
enumeration	LinesPerInch
enumeration	Load
enumeration	MagazineUnit
enumeration	Megabyte
enumeration	Meter
enumeration	MetricTon
enumeration	MetricTonsPerDay
enumeration	MetricTonsPerWeek
enumeration	Micron
enumeration	Millimeter
enumeration	Minute
enumeration	Month
enumeration	None
enumeration	Package
enumeration	Page
enumeration	PagesPerInch
enumeration	PalletUnit
enumeration	Percentage
enumeration	PerThousand
enumeration	Picas
enumeration	Piece
enumeration	PixelsPerInch
enumeration	Pound
enumeration	PoundsPerDay
enumeration	PoundsPerHour
enumeration	PoundsPerWeek
enumeration	PulpUnit
enumeration	Ream
enumeration	Reel
enumeration	Set
enumeration	Sheet
enumeration	ShortTon
enumeration	ShortTonsPerDay
enumeration	ShortTonsPerHour
enumeration	ShortTonsPerWeek
enumeration	Signature
enumeration	Skid
enumeration	SquareInch
enumeration	SquareFeet
enumeration	SquareMeter
enumeration	ThousandBoardFeet
enumeration	ThousandLinealFeet
enumeration	ThousandPieces
enumeration	ThousandSquareCentimeters
enumeration	ThousandSquareFeet
enumeration	ThousandSquareInch
enumeration	Ton
enumeration	TonsPerHour

Copyright © 2014 USPS®. All Rights Reserved

Tag	uOMType
enumeration	Unit
enumeration	UnknownBreaks
enumeration	Week
enumeration	Yard

5.271 simpleType: UpperDateRange

Tag	UpperDateRange
Base	xs:date

5.272 simpleType: uniqueContainerIDType

Tag	uniqueContainerIDType
Base	xs:string
maxLength	12
minLength	1
whiteSpace	preserve

5.273 simpleType: userInformationLine1Type

Tag	userInformationLine1Type
Base	mailxml_base:s40

5.274 simpleType: userInformationLine2Type

Tag	userInformationLine2Type
Base	mailxml_base:s40

5.275 simpleType: userLicenseCodeType

Tag	userLicenseCodeType
Base	xs:string
maxLength	4
minLength	1
whiteSpace	preserve

5.276 simpleType: uspsPackageUniqueCharacteristicType

Tag	uspsPackageUniqueCharacteristicType
Base	Xs:string

5.277 simpleType: uspsPickupType

Tag	uspsPickupType
Base	xs:string
enumeration	Y = Yes
enumeration	N = No

5.278 simpleType: verificationLocationType

Tag	verificationLocationType
Base	xs:string
enumeration	BMEU
enumeration	DMU

5.279 simpleType: verificationReportType

Tag	verificationReportType
Base	xs:string
enumeration	CSAVerification

Copyright © 2014 USPS®. All Rights Reserved

Tag	verificationReportType
enumeration	ContainerBarcodeVerification
enumeration	HandlingUnitBarcodeVerification
enumeration	PieceBarcodeVerification
enumeration	ByForConflictVerification
enumeration	ServiceTypeVerification
enumeration	AppointmentVerification
enumeration	MailerIDVerification
Enumeration	ServicePerformanceVerification
enumeration	DeliveryPointVerification
enumeration	EntryFacilityVerification
enumeration	DefaultTrayBarcodeVerification
enumeration	IMDVerification
enumeration	All
enumeration	NoErrors

5.280 simpleType: wastedPieceIndicatorType

Tag	wastedPieceIndicatorType
Base	xs:string
enumeration	W = Wasted
enumeration	S = Shortage
enumeration	X = Wasted piece and postage adjustment should NOT be triggered
enumeration	T = Shortage pieces not produced and postage adjustment should NOT be triggered

5.281 simpleType: weekFrequencyType

Tag	weekFrequencyType
Base	xs:string
enumeration	Weekly
enumeration	Bi-Weekly
enumeration	First
enumeration	Second
enumeration	Third
enumeration	Fourth
enumeration	Fifth
enumeration	Sixth

5.282 simpleType: weightBreakType

Tag	weightBreakType
Base	xs:string
enumeration	A = For standard Mail Non-Letters, Piece Weight is over 0.2063 lbs. For First-Class Mail Permit Reply, piece weight is over 0.0625 lbs.
enumeration	B = For standard mail, piece weight is 0.2063 lbs or less For First-Class Mail Permit Reply, piece weight is 0.0625 lbs or less.
enumeration	H = For standard Mail Letters, piece weight is over 0.2063 lbs
enumeration	N = None

5.283 simpleType: yesNo

Tag	yesNo
Base	xs:string
enumeration	Yes
enumeration	No

5.284 simpleType: zipCodeThreeOrFiveDigit

Tag	zipCodeThreeOrFiveDigit
Base	xs:string

Copyright © 2014 USPS®. All Rights Reserved

Tag	zipCodeThreeOrFiveDigit
pattern	"[0-9]{3}|[0-9]{5}" - Space removed

5.285 simpleType: zoneICType

Tag	zoneICType
Base	xs:string
enumeration	N = None
enumeration	M = [Future Placeholder]
enumeration	LC = Local
enumeration	1 = Zone 1 & 2
enumeration	3 = Zone 3
enumeration	4 = Zone 4
enumeration	5 = Zone 5
enumeration	6 = Zone 6
enumeration	7 = Zone 7
enumeration	8 = Zone 8
enumeration	ICD
enumeration	IC
enumeration	DDU
enumeration	SCF
enumeration	ADC

Copyright © 2014 USPS®. All Rights Reserved

6. eDocumentation Form Values

The appendix lists the values associated with the following Mail.XML messages: MailingGroupQueryRequest, MailingGroupQueryResponse, ReconciliationReportQueryRequest, ReconciliationReportQueryResponse, ContainerStatusQueryRequest, and ContainerStatusQueryResponse.

eDoc Form Values

6.1 Container Status Type

Value	Description
Accepted	Accepted for Induction, passed validation
OnHold	Waiting for Induction validation to complete
Rejected	Didn't satisfy the induction validation rules

6.2 Entry Facility Type Values

Value	Description
Accepted	Accepted for Induction, passed validation
OnHold	Waiting for Induction validation to complete
Rejected	Didn't satisfy the induction validation rules

6.3 Entry Facility Type

Value	Description
O	Origin
B	BMC
S	SCF
D	DDU

6.4 Form Type

Value	Description	Postage Statement
PM	Priority Mail	3600
FC	First-Class Mail	3600
SM	Standard Mail	3602
BP	Bound Printed Matter	3605
PP	Package Services	3605
PE	Periodicals	3541
ML	Media/Library Mail	3605

6.5 Full-Service Indicator

Value	Description
Blank/Null/Nil	Null
F	Full-Service
B	Basic
P	PostNet
O	Other

6.6 Postage Statement Status Definitions

Status	Definition
AVW	Address verification resulted in warnings.
CAN	A mailer canceled the postage statement.
COM	Awaiting completion of combined mailing.
CON	This statement is part of a consolidated postage statement and cannot be individually updated.
ERR	A USPS clerk was unable to finalize a statement due to a system error.
EST	The postage is an estimate based on preliminary postage data, not an actual postage statement.

Copyright © 2014 USPS®. All Rights Reserved

Status	Definition
	This is only available for postage statements submitted by mailers using Mail.dat files.
FAI	The postage statement failed verification.
FIN	The postage statement has been finalized.
FPP	Finalized pending payment – only Centralized Postage Payment for Periodicals
INC	Postage statement entry is incomplete - initial entry was interrupted.
NAP	The statement is not available for processing by the system. This usually indicates a type of postage statement not currently supported.
PAS	The postage statement passed MERLIN verification, but was not finalized at the machine.
PAV	The postage statement is pending address verification.
PEN	The postage statement is pending finalization.
QMR	A postal employee has performed a Quality Mail Review. The QMR stage only appears on a verification receipts entered by postal employees and does not affect postage statements submitted electronically.
REV	A postal employee has reversed the postage statement transaction.
REW	A verification issue has been identified and the mailing has been returned to the mailer for correction or rework.
UPD	A file has been received and a postage statement is available for processing (USPS Processing is Due).

6.7 Rate Category

Value	Description
Blank/Null/Nil	Null
A	Saturation ECR
AF	Standard Mail Saturation ECR Letter Paid As Flat
B	High Density ECR
BF	Standard Mail High Density ECR Letter Paid As Flat
D	Basic ECR (Carrier Route)
DF	Standard Mail Basic ECR Letter Paid As Flat
E	5-Digit Automation (5-Digit Barcode)
FB	Firm Bundle Outside County
G	5-Digit Non Barcode(Auto)
GF	5-Digit Non Barcode (Auto) Letter Paid As Flat
H	3-Digit Automation (3-Digit Barcode)
K	3-Digit Non Barcode(Auto)
KF	3-Digit Non Barcode (Auto) Letter Paid As Flat
L	Basic Automation (Basic Barcode)
L1	AADC Barcode
L2	Mixed AADC Barcode
L3	ADC Barcode
L4	Mixed ADC Barcode
L5	ADC Non-Barcode
L6	Mixed ADC Non-Barcode
L7	AADC Non-Barcode
L8	Mixed AADC Non-Barcode
TE	5-Digit
TK	SCF
TQ	NDC
TR	Mixed NDC
N	Basic Nonautomation (Basic Presorted)
NG	5-Digit Not Flat Machinable
NK	3-Digit Not Flat Machinable
N5	ADC/BMC Not Flat Machinable
N6	Mixed ADC/BMC Not Flat Machinable

Copyright © 2014 USPS®. All Rights Reserved

Value	Description
PI	5-Digit Parcel 0.2063 pounds or less
PM	3-Digit Parcel 0.2063 pounds or less
P7	ADC Parcel 0.2063 pounds or less
P8	Mixed ADC Parcel 0.2063 pounds or less
PE	5-Digit Machinable Parcel over 0.2063 pounds
PQ	BMC Machinable Parcel over 0.2063 pounds
PR	Mixed BMC Machinable Parcel over 0.2063 pounds
PG	5-Digit Irregular Parcel over 0.2063 pounds
PK	3-Digit Irregular Parcel over 0.2063 pounds
P5	ADC Irregular Parcel over 0.2063 pounds
P6	Mixed ADC Irregular Parcel over 0.2063 pounds
S	Single Piece
Z1	BMC Presort
Z2	OBMC Presort

6.8 First Class Mail – Rate Category and Corresponding Rate Level

Rate Category	Rate Category Description	Processing Category	Rate Level	Rate Level Description
E	5-Digit Barcode	FL	5B	Auto 5-Digit
H	3-Digit Barcode	FL	3B	Auto 3-Digit
L3	ADC Barcode	FL	AB	Auto ADC/AADC
L4	Mixed ADC Barcode	FL	MB	Auto Mixed ADC/AADC
N	Basic (1C/4C Presort)	FL	PSRT	Presorted
S	Single Piece	FL	SP	Single-Piece
E	5-Digit Barcode	LT	5B	Auto 5-Digit
H	3-Digit Barcode	LT	3B	Auto 3-Digit
L1	AADC Barcode	LT	AB	Auto ADC/AADC
L2	Mixed AADC Barcode	LT	MB	Auto Mixed ADC/AADC
N	Basic (1C/4C Presort)	LT	PSRT	Presorted
S	Single Piece	LT	SP	Single-Piece
G	5-Digit Barcode	PF	5D	Presort 5-Digit
K	3-Digit Non-Barcode	PF	3D	Presort 3-Digit
S	Single Piece	PF	SP	Single-Piece
L5	ADC	PF	AD	ADC Presort

6.9 Periodicals In-County – Rate Category and Corresponding Rate Level

For Periodicals Mail, the RateLevel in the ContainerDetailData in the ContainerInfo in the QualificationReportDetailCreateRequest must correspond to the RateCategory for the piece postage lines in the PeriodicalStatementCreateRequest. The following tables for Periodicals In-County – Rate Category and Corresponding Rate Level and Periodicals Outside-County – Rate Category and Corresponding Rate Level show the correspondence for each processing category FL = Flats, IR = Parcels and LT = Letters.

Rate Category	Rate Category Description	Processing Category	Rate Level	Rate Level Description
A	Saturation ECR	FL	WS	Carrier Route Saturation
B	High Density ECR	FL	HD	Carrier Route High Density
D	Carrier Route	FL	CR	Carrier Route Basic
E	5-Digit Barcode	FL	5B	Auto 5-Digit

Copyright © 2014 USPS®. All Rights Reserved

Rate Category	Rate Category Description	Processing Category	Rate Level	Rate Level Description
H	3-Digit Barcode	FL	3B	Auto 3-Digit
L	Basic Barcode	FL	BB	Barcode Basic
G	5-Digit Non-Barcode	FL	5D	Presort 5-Digit
K	3-Digit Non-Barcode	FL	3D	Presort 3-Digit
N	Basic Nonautomation	FL	PSRT	Presorted
A	Saturation ECR	IR	WS	Carrier Route Saturation
B	High Density ECR	IR	HD	Carrier Route High Density
D	Carrier Route	IR	CR	Carrier Route Basic
E	5-Digit Barcode	IR	5B	Auto 5-Digit
H	3-Digit Barcode	IR	3B	Auto 3-Digit
L	Basic Automation	IR	BB	Barcode Basic
G	5-Digit Non-Barcode	IR	5D	Presort 5-Digit
K	3-Digit Non-Barcode	IR	3D	Presort 3-Digit
N	Basic Nonautomation	IR	PSRT	Presorted
A	Saturation ECR	LT	WS	Carrier Route Saturation
AF	Saturation Letter - ECR (Pd Flt)	LT	WS	Carrier Route Saturation
B	High Density ECR	LT	HD	Carrier Route High Density
BF	High Density Letter - ECR (Pd Flt)	LT	HD	Carrier Route High Density
D	Carrier Route	LT	CR	Carrier Route Basic
DF	Carrier Route Letter (Pd Flt)	LT	CR	Carrier Route Basic
E	5-Digit Barcode	LT	5B	Auto 5-Digit
H	3-Digit Barcode	LT	3B	Auto 3-Digit
L	Basic Automation	LT	BB	Barcode Basic
G	5-Digit Non-Barcode	LT	5D	Presort 5-Digit
GF	5-Digit Letter (Pd Flt)	LT	5D	Presort 5-Digit
K	3-Digit Non-Barcode	LT	3D	Presort 3-Digit
KF	3-Digit Letter (Pd Flt)	LT	3D	Presort 3-Digit
N	Basic Nonautomation	LT	PSRT	Presorted
NF	Basic Letter (Pd Flt)	LT	PSRT	Presorted

6.10 Periodicals Outside-County – Rate Category and Corresponding Rate Level

Rate Category	Rate Category Description	Processing Category	Rate Level	Rate Level Description
A	Saturation ECR	FL	WS	Carrier Route Saturation
B	High Density ECR	FL	HD	Carrier Route High Density
D	Carrier Route	FL	CR	Carrier Route Basic
E	5-Digit Barcode	FL	5B	Auto 5-Digit
H	3-Digit Barcode	FL	3B	Auto 3-Digit
L3	ADC Barcode	FL	AB	Auto ADC/AADC
L4	Mixed ADC Barcode	FL	MB	Auto Mixed ADC/AADC
G	5-Digit Non-Barcode	FL	5D	Presort 5-Digit
K	3-Digit Non-Barcode	FL	3D	Presort 3-Digit
L5	ADC Non-Barcode	FL	AD	ADC Presort
L6	Mixed ADC Non-Barcode	FL	MD	Mixed ADC Presort
FB	Outside County Firm Bundle	FL	FB	Firm Bundle
A	Saturation ECR	IR	WS	Carrier Route Saturation

Copyright © 2014 USPS®. All Rights Reserved

Rate Category	Rate Category Description	Processing Category	Rate Level	Rate Level Description
B	High Density ECR	IR	HD	Carrier Route High Density
D	Carrier Route	IR	CR	Carrier Route Basic
E	5-Digit Barcode	IR	5B	Auto 5-Digit
H	3-Digit Barcode	IR	3B	Auto 3-Digit
L3	ADC Barcode	IR	AB	Auto ADC/AADC
L4	Mixed ADC Barcode	IR	MB	Auto Mixed ADC/AADC
G	5-Digit Non-Barcode	IR	5D	Presort 5-Digit
K	3-Digit Non-Barcode	IR	3D	Presort 3-Digit
L5	ADC Non-Barcode	IR	AD	ADC Presort
L6	Mixed ADC Non-Barcode	IR	MD	Mixed ADC Presort
FB	Outside County Firm Bundle	IR	FB	Firm Bundle
A	Saturation ECR	LT	WS	Carrier Route Saturation
AF	Saturation Letter - ECR (Pd Flt)	LT	WS	Carrier Route Saturation
B	High Density ECR	LT	HD	Carrier Route High Density
BF	High Density Letter - ECR (Pd Flt)	LT	HD	Carrier Route High Density
D	Carrier Route	LT	CR	Carrier Route Basic
DF	Carrier Route Letter (Pd Flt)	LT	CR	Carrier Route Basic
E	5-Digit Barcode	LT	5B	Auto 5-Digit
H	3-Digit Barcode	LT	3B	Auto 3-Digit
L1	AADC Barcode	LT	AB	Auto ADC/AADC
L2	Mixed AADC Barcode	LT	MB	Auto Mixed ADC/AADC
G	5-Digit Non-Barcode	LT	5D	Presort 5-Digit
GF	5-Digit Letter (Pd Flt)	LT	5D	Presort 5-Digit
K	3-Digit Non-Barcode	LT	3D	Presort 3-Digit
KF	3-Digit Letter (Pd Flt)	LT	3D	Presort 3-Digit
L7	AADC Non-Barcode	LT	AD	ADC Presort
L8	Mixed AADC Non-Barcode	LT	MD	Mixed ADC Presort
NF	Basic Letter (Pd Flt)	LT	PSRT	Presorted
FB	Outside County Firm Bundle	LT	FB	Firm Bundle

6.11 Standard Mail – Rate Category and Corresponding Rate Level

For Standard Mail, the RateLevel in the ContainerDetailData in the ContainerInfo in the QualificationReportDetailCreateRequest must correspond to the RateCategory for the piece postage lines in the PostageStatementCreateRequest. The following table for Standard Mail – Rate Category and Corresponding Rate Level show the correspondence for each processing category FL = Flats, IR = Parcels, LT = Letters, MP = Machinable Parcel, NF = Not Flat Machinable.

Rate Category	Rate Category Description	Processing Category	Rate Level	Rate Level Description
N	Basic (1C/4C Presort)	CM	PSRT	Presorted
A	Saturation ECR	FL	WS	Carrier Route Saturation
B	High Density ECR	FL	HD	Carrier Route High Density
D	Carrier Route	FL	CR	Carrier Route Basic

Copyright © 2014 USPS®. All Rights Reserved

Rate Category	Rate Category Description	Processing Category	Rate Level	Rate Level Description
E	5-Digit Barcode	FL	5B	Auto 5-Digit
H	3-Digit Barcode	FL	3B	Auto 3-Digit
L3	ADC Barcode	FL	AB	Auto ADC/AADC
L4	Mixed ADC Barcode	FL	MB	Auto Mixed ADC/AADC
G	5-Digit Non-Barcode	FL	5D	Presort 5-Digit
K	3-Digit Non-Barcode	FL	3D	Presort 3-Digit
L5	ADC Non-Barcode	FL	AD	ADC Presort
L6	Mixed ADC Non-Barcode	FL	MD	Mixed ADC Presort
PG	5-Digit Non-Machinable	IR	5D	Presort 5-Digit
PI	5-Digit (Std Prcl Piece Rate)	IR	5D	Presort 5-Digit
PK	3-Digit Non-Machinable	IR	3D	Presort 3-Digit
PM	3-Digit	IR	3D	Presort 3-Digit
P5	ADC Non-Machinable	IR	AD	ADC Presort
P6	Mixed ADC Non-Machinable	IR	MD	Mixed ADC Presort
P7	ADC	IR	AD	ADC Presort
P8	Mixed ADC	IR	MD	Mixed ADC Presort
A	Saturation ECR	LT	WS	Carrier Route Saturation
B	High Density ECR	LT	HD	Carrier Route High Density
D	Carrier Route	LT	CR	Carrier Route Basic
AF	Saturation Letter - ECR (Pd Flt)	LT	WS	Carrier Route Saturation
BF	High Density Letter - ECR (Pd Flt)	LT	HD	Carrier Route High Density
DF	Carrier Route Letter (Pd Flt)	LT	CR	Carrier Route Basic
E	5-Digit Barcode	LT	5B	Auto 5-Digit
H	3-Digit Barcode	LT	3B	Auto 3-Digit
L1	AADC Barcode	LT	AB	Auto ADC/AADC
L2	Mixed AADC Barcode	LT	MB	Auto Mixed ADC/AADC
L7	AADC Non-Barcode	LT	AD	ADC Presort
L8	Mixed AADC Non-Barcode	LT	MD	Mixed ADC Presort
N5	BMC	LT	BP	Standard Mail BMC
N6	Mixed BMC	LT	MP	Mixed BMC Standard
G	5-Digit Non-Barcode	LT	5D	Presort 5-Digit
K	3-Digit Non-Barcode	LT	3D	Presort 3-Digit
L5	ADC Non-Barcode	LT	AD	ADC Presort
L6	Mixed ADC Non-Barcode	LT	MD	Mixed ADC Presort
GF	5-Digit Letter (Pd Flt)	LT	5D	Presort 5-Digit
KF	3-Digit Letter (Pd Flt)	LT	3D	Presort 3-Digit
N	Basic (1C/4C Presort)	LT	PSRT	Presorted
NF	Basic Letter (Pd Flt)	LT	PSRT	Presorted
PE	5-Digit Machinable	MP	5D	Presort 5-Digit
PQ	BMC Machinable	MP	BP	Standard Mail BMC
PR	Mixed BMC Machinable	MP	MP	Mixed BMC Standard

Copyright © 2014 USPS®. All Rights Reserved

Rate Category	Rate Category Description	Processing Category	Rate Level	Rate Level Description
NG	5-Digit	NF	5D	Presort 5-Digit
NK	3-Digit	NF	3D	Presort 3-Digit
N5	ADC	NF	AD	ADC Presort
N6	Mixed ADC	NF	MD	Mixed ADC Presort

6.12 FSS Preparation - Add pricing for Outside County Periodicals prepared as FSS

The *PostalOne!* system shall support bundle and container prices for Outside County Periodicals flats (MailClass = 2, ProcessingCategory = FL, and formType = PM) prepared as FSS and mapped to Periodical Statement lines as follows for all applicable sack, tray and pallet types per the current mapping:

PeriodicalLineItemData >> Section	PeriodicalLineItemData >> InOutCountyIndicator	PostageStatementLineNumber (2)	EntryDiscount (3)	Sortation Level (ContainerLevelType)	Bundle Level (BundleDetailLevelType)
D (Part D - Outside County Bundle Prices)	N = Outside-County	D15 (for 5-digit, 5-digit container)	N (None)	E-FSS Sort Plan	X = FSS or B = Carrier Route or C = 5 Digit
D (Part D - Outside County Bundle Prices)	N = Outside-County	D12 (for 5-digit, SCF container)	N (None)	F – FSS Facility	X = FSS or B = Carrier Route or C = 5 Digit
E (Part E - Outside County Container Prices)	N = Outside-County	E15 (for SCF DADC)	A (DADC) (1)	F – FSS Facility	X = FSS or B = Carrier Route or C = 5 Digit
E (Part E - Outside County Container Prices)	N = Outside-County	E16 (for SCF DSCF)	S (DSCF)	F – FSS Facility	X = FSS or B = Carrier Route or C = 5 Digit
E (Part E - Outside County Container Prices)	N = Outside-County	E22 (for 5-digit DADC)	A (DADC) (1)	E-FSS Sort Plan	X = FSS or B = Carrier Route or C = 5 Digit
E (Part E - Outside County Container Prices)	N = Outside-County	E23 (for 5-digit SCF)	S (DSCF)	E-FSS Sort Plan	X = FSS or B = Carrier Route or C = 5 Digit

Table 6-1 - Added Pricing for Outside-County FSS Bundles and Containers

The meaning of A is Destination ADC (DADC) and it is defined as DADC in the IDEAlliance Mail.XML specification.

The PostageStatementLineNumber could be a value in one of the following blocks:

- ContainerBundleReportCreateRequest >> ContainerBundleVersionRecord >> SackTrayContainerVersionRecord >> PostageStatementLineNumber
- ContainerBundleReportCreateRequest >> ContainerBundleVersionRecord >> BundleVersionRecord >> PostageStatementLineNumber
- ContainerBundleReportCreateRequest >> ContainerBundleSummaryRecord >> BundleRecord >> PostageStatementLineNumber

Copyright © 2014 USPS®. All Rights Reserved

- ContainerBundleReportCreateRequest >> ContainerBundleSummaryRecord >> SackTrayContainerRecord >> PostageStatementLineNumber

The EntryDiscount field could be a value in one of the following blocks:

- QualificationReportSummaryCreateRequest/QualificationReportDetailCreateRequest >> ContainerInfoData >> ContainerDetailData >> EntryDiscountType
- PostageStatementCreateRequest >> LineItemSummaryData >> EntryDiscount
- PostageStatementCreateRequest >> PostageStatementLineItemData >> EntryDiscount
- BundleDetailCreateRequest >> BundleDetailType >> DestinationEntry

Value	Definition	FSS Level
A	CR-Direct Eligibility Type = S, T, P	FSS Scheme
B	Mixed CR in 5 Digit Eligibility Type = S, T, P	FSS Scheme
C	Mixed CR in 3 Digit Eligibility Type = S, T	FSS Scheme
E	FSS Scheme	FSS Scheme
J	5 Digit (Barcode Only) Eligibility Type = S, T, P	FSS Scheme
P	5D Scheme (Barcode) Eligibility Type = S, T, P	FSS Scheme
F	FSS Facility	FSS Facility
X	SCF Eligibility Type = S, P	FSS Facility
Y	Protected SCF Eligibility Type = P	FSS Facility

Table 6-2 - containerLevelType valid for FSS

Value	Definition	FSS Level
B	Carrier Route	FSS Scheme
C	5 Digit	FSS Scheme
X	FSS Scheme	FSS Scheme

Table 6-3 - BundleDetailLevelType Valid for FSS

6.13 Fault Codes

Faults, such as a message timeout or invalid XML are to be communicated using the fault element and returned within the detail section of the SOAP fault. The fault is made up of a Tracking ID and one or more error warning blocks which contain more details.

Below is a list of supported element/attributes of the fault element.

Element/Attribute	Value (example)
Code	See error code list below for details.
Severity	Error, Warning, Information
SubmissionDate	Current date
ErrorDescription	See Description in the code list table below
TrackingID	Populate if available
SubmitterTrackingID	Populate if available
MailXMLVersion	Populate if available
MailXMLMsgSize	Populate if available
MailXMLMsgName	Populate if available

Copyright © 2014 USPS®. All Rights Reserved

The fault codes that are applicable to all Mail.XML messages are sent whenever a fault occurs in the transmission of a message.

Code	Description	Action*	Messages	Severity
401	Incomplete/Cannot Parse	Please submit the request again with well-formed XML according to XSD.	Fault (All Mail.XML Messages)	Error
402	Not Well Formed XML	Please submit the request again with well-formed XML according to XSD	Fault (All Mail.XML Messages)	Error
403	Request XML is invalid against the XSDs	Please submit the request again with well-formed XML according to XSD.	Fault (All Mail.XML Messages)	Error
412	Invalid user	Please submit the request again with a valid user.	Fault (All Mail.XML Messages)	Error
440	Sorry - MailXML version is not supported	Please submit the request again with MailXML version supported by PostalOne Data Distribution System.	Fault (All Mail.XML Messages)	Error
500	Mail.XML generic internal error	Please contact PostalOne! Help Desk.	Fault (All Mail.XML Messages)	Error
501	MailXML request is missing 'SubmitterTrackingID' which is required for processing the Message	Please submit the request again with SubmitterTrackingID.	Fault (All Mail.XML Messages)	Error
502 [1]	Duplicate submitter ID. This Mail.XML request for Message #messageName# with SubmitterTrackingID #submitterTrackingID# was not processed by Mail.XML application because an identical request was received on #submitDate# and was assigned TrackingID of #trackingID#.	Please use the MRRR message with Tracking ID #trackingID# to retrieve.	Fault (All Mail.XML Messages)	Error
503	Not Implemented - MailXML message received is not supported	Please submit the request again with MailXML message supported by PostalOne Data Distribution System.	Fault (All Mail.XML Messages)	Error
505 [1]	Submitter tracking ID is too long	Please submit the request again with SubmitterTrackingID length not exceeding the length specified in the Tech Spec.	Fault (All Mail.XML Messages)	Error
1500	Invalid tracking ID	Please submit the request again with a valid Tracking ID.	Fault (All Mail.XML Messages)	Error
1502 [2]	Come Back Later	The response is not available at this time, Please try again later.	Fault (All Mail.XML Messages)	Warning
1502	Come Back Later	The response is not available at this time, Please try again later.	MessageResponseRetrievalResponse	Warning
1510	The TrackingID provided in the MessageResponseRetrievalResponse request was processed by Mail.XML application on #processedDate#. No response was received by Mail.XML from the target application.	Please submit the request again or contact PostalOne! Help Desk.	Fault (All Mail.XML Messages)	Information
1600	MRRR version not matching original request version.	Please submit the MRRR request again using the same MailXML version that was used to submit the original request.	Fault (All Mail.XML Messages)	Error

Copyright © 2014 USPS®. All Rights Reserved

Code	Description	Action*	Messages	Severity
5008	FULLSERVICE-EDOC: Empty Message.	Please contact PostalOne! Help Desk	Fault (All eDoc Messages)	Error
5009	FULLSERVICE-EDOC: Request is not XML Message.	Please contact PostalOne! Help Desk	Fault (All eDoc Messages)	Error
5101 [3]	Unauthorized - Required SubmittingParty information is empty or missing.	Please submit the request again with valid SubmittingParty block.	Fault (All Mail.XML Messages)	Error
5102 [3]	Unauthorized - User does not have access to specified SubmittingParty.	Please submit the request again with valid SubmittingParty block or contact PostalOne! Help Desk.	Fault (All Mail.XML Messages)	Error
5103 [3]	Unauthorized - User does not have access to 'Manage Mailing Activity' service.	Please contact PostalOne! Help Desk.	Fault (All Mail.XML Messages)	Error

[1] Error code 501 was used for any Submitter Tracking ID error. In Release 37, Error Codes 502 and 505 are used to enable distinction between Submitter tracking ID errors.

[2] Error Code 500 was used for any generic error and Come Back Later faults. In Release 37, Error Code 1502 is used for any Come Back Later message for consistency.

[3] Error Code 412 was used for any User Error. In Release 37, Error Codes 5101, 5102 and 5103 are used to enable distinction between user errors.

* Action tags are only available for Mail.XML specs 15.0A and above.

6.14 Support Mailer SubmitterTrackingID on MailXML 13.0B Messages

6.14.1 Business Requirements:

MailXML13.0B messages support ‘SubmitterTrackingID’ on MailXML request message. If the value is set by the mailer, *PostalOne!* system will make use of this to identify the duplicate requests, avoid processing the duplicate messages submitted. The sections given below discuss more details on MailXML Service Layer and Target Apps processing ‘SubmitterTrackingID’.

6.14.2 Business Rules/ Assumptions:

1. Mailers provide a SubmitterTrackingID as part of their request messages.
2. SubmitterTrackingID is required in Mail.XML specifications.
3. *The PostalOne!* system will use the SubmitterTrackingID (if provided) to ensure that Mailer’s requests were processed one time only by Mail.XML and target applications.
4. Mailer must provide a unique combination of SubmitterTrackingID/MessageName for 45 days in order to support these requirements.
5. *The PostalOne!* will use the combination of UserID/SubmitterTrackingID/ MessageName to identify duplicate requests from the Mailers. Please note that the business requirements call 45 days to be consistent with other Full Service uniqueness requirements.
6. *The PostalOne!* applications will include the SubmitterTrackingID (if provided by mailers) in Mail.XML responses and error messages.
7. *The PostalOne!* applications generate responses or error messages for all Mail.XML requests.
8. *The PostalOne!* applications will use the following elements to identify and handle duplicate requests:
   a. UserID
   b. MessageName
   c. TrackingID (MailXML app assigns this)
   d. SubmitterTrackignID (assigned by the Mailer)
   e. RequesetReceived DateTime(MailXML app assigns this)

Copyright © 2014 USPS®. All Rights Reserved

9. Duplicate messages will only be identified for mailers who are providing SubmitterTrackignIDs in their requests.
10. If no response is received from the target application for a given request during 48 hours window, the request will be considered obsolete and no response will be provided using MessageResponseRetrievalResponse (MRRR). An error message will be provided back to the Mailer in the MRRR (refer to example below).

Mail.XML 13.0B Example

```
<?xml version="1.0" encoding="UTF-8"?>
<mailxml:MessageResponseRetrievalResponse
xmlns:mailxml="http://idealliance.org/Specs/mailxml13.0B/mailxml"
xmlns:mailxml_base="http://idealliance.org/Specs/mailxml13.0B/base"
xmlns:mailxml_defs="http://idealliance.org/Specs/mailxml13.0B/mailxml_defs"
xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
xsi:schemaLocation="http://idealliance.org/Specs/mailxml13.0B/mailxml mailxml_13.0b.xsd ">
  <mailxml:MessageResponseRetrievalReject mailxml:TrackingID="59201401200001494823">
    <mailxml:ReturnInfo>
      <mailxml_defs:ErrorWarning>
        <mailxml_defs:Code>1510</mailxml_defs:Code>
        <mailxml_defs:Severity>Information</mailxml_defs:Severity>
        <mailxml_defs:ErrorDescription>The TrackingID provided in the MRRR request was processed by Mail.XML
application on Fri Dec 13 15:30:02 CST 2013. No response was received by Mail.XML from the target
application.</mailxml_defs:ErrorDescription>
        <mailxml_defs:Action> Please submit the request again or contact PostalOne! Help
Desk.</mailxml_defs:Action>
      </mailxml_defs:ErrorWarning>
    </mailxml:ReturnInfo>
  </mailxml:MessageResponseRetrievalReject>
</mailxml:MessageResponseRetrievalResponse>
```

6.14.3 Duplicate Request Scenarios

Scenario 1

Mailer sends original request followed by another identical request. While Mail.XML is processing the duplicate request, the response is available for the original request.

1. Mailer sends the first request with a unique SubmitterTrackingID.
2. MailXML application receives the request, captures the information below and routes the request to the target application for processing
   a. UserID
   b. MessageName
   c. TrackingID (MailXML app assigns this)
   d. SubmitterTrackignID (assigned by the Mailer)
   e. RequsetReceived DateTime (MailXML app assigns this)
3. Mailer sends the second request with the same SubmitterTrackingID.
4. MailXML application checks the request, assigns TrackingID and performs validation for the duplicate message.

Copyright © 2014 USPS®. All Rights Reserved

5. If it is a duplicate message MailXML will not forward request to the target application. An error message will be generated by the Mail.XML application and returned back to the mailer as follows:

"Duplicate submitter ID. This Mail.XML request for *MessageName* with SubmitterTrackingID *Number* was not processed by Mail.XML application because an identical request was received on *Day Date Time* and was assigned TrackingID of *Number*"

Mail.XML 13.0B Example


```
<?xml version="1.0" encoding="UTF-8"?>
<mailxml:Fault xmlns:mailxml="http://idealliance.org/Specs/mailxml13.0B/mailxml"
xmlns:mailxml_base="http://idealliance.org/Specs/mailxml13.0B/base"
xmlns:mailxml_defs="http://idealliance.org/Specs/mailxml13.0B/mailxml_defs"
xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
xsi:schemaLocation="http://idealliance.org/Specs/mailxml13.0B/mailxml mailxml_13.0b.xsd ">
  <mailxml:ErrorWarning>
    <mailxml_defs:Code>502</mailxml_defs:Code>
    <mailxml_defs:Severity>Error</mailxml_defs:Severity>
    <mailxml_defs:SubmissionDate>2014-01-13T07:54:01</mailxml_defs:SubmissionDate>
    <mailxml_defs:ErrorDescription>Duplicate submitter ID. This Mail.XML request for Message
QualificationReportSummaryCreateRequest with SubmitterTrackingID 011314085128125 was not processed by
Mail.XML application because an identical request was received on Mon Jan 13 07:53:21 CST 2014 and was
assigned TrackingID of 59201401130001460039.</mailxml_defs:ErrorDescription>
    <mailxml_defs:Action>Please use the MRRR message with Tracking ID 59201401130001460039 to
retrieve.</mailxml_defs:Action>
    <mailxml_defs:TrackingID>59000000000001460043</mailxml_defs:TrackingID>
    <mailxml_defs:SubmitterTrackingID>011314085128125</mailxml_defs:SubmitterTrackingID>
    <mailxml_defs:MailxmlDetail>
      <mailxml_defs:MailXMLVersion>13.0B</mailxml_defs:MailXMLVersion>
      <mailxml_defs:MailXMLMsgSize>2122</mailxml_defs:MailXMLMsgSize>

<mailxml_defs:MailXMLMsgName>QualificationReportSummaryCreateRequest</mailxml_defs:MailXMLMsgNam
e>
    </mailxml_defs:MailxmlDetail>
  </mailxml:ErrorWarning>
</mailxml:Fault>
```


6. Mailer to use MRRR message with TrackingID mmmmmm to retrieve the responses.

Scenario 2

Mailer sends original request followed by another identical request. No response is made available by the target application for the original request.

1. Mailer sends the first request with a unique SubmitterTrackingID.
2. MailXML application receives the request, captures the information below and routes the request to the target application for processing
   a. UserID

Copyright © 2014 USPS®. All Rights Reserved

b. MessageName
c. TrackingID (MailXML app assigns this)
d. SubmitterTrackignID (assigned by the Mailer)
e. RequsetReceived DateTime (MailXML app assigns this)

3. Mailer sends the second request with the same SubmitterTrackingID.
4. MailXML application checks the request, assigns TrackingID and performs validation for the duplicate message.
5. If it is a duplicate message MailXML will not forward request to the target application. An error message will be generated by the Mail.XML application and returned back to the mailer as follows:

   "Duplicate submitter ID. This Mail.XML request for *MessageName* with SubmitterTrackingID *Number* was not processed by Mail.XML application because an identical request was received on *Day Date Time* and was assigned TrackingID of *Number*"

Mail.XML 13.0B Example


```
<?xml version="1.0" encoding="UTF-8"?>
<mailxml:Fault xmlns:mailxml="http://idealliance.org/Specs/mailxml13.0B/mailxml"
xmlns:mailxml_base="http://idealliance.org/Specs/mailxml13.0B/base"
xmlns:mailxml_defs="http://idealliance.org/Specs/mailxml13.0B/mailxml_defs"
xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
xsi:schemaLocation="http://idealliance.org/Specs/mailxml13.0B/mailxml mailxml_13.0b.xsd ">
  <mailxml:ErrorWarning>
    <mailxml_defs:Code>502</mailxml_defs:Code>
    <mailxml_defs:Severity>Error</mailxml_defs:Severity>
    <mailxml_defs:SubmissionDate>2014-01-13T07:54:01</mailxml_defs:SubmissionDate>
    <mailxml_defs:ErrorDescription>Duplicate submitter ID. This Mail.XML request for Message
QualificationReportSummaryCreateRequest with SubmitterTrackingID 011314085128125 was not processed by
Mail.XML application because an identical request was received on Mon Jan 13 07:53:21 CST 2014 and was
assigned TrackingID of 59201401130001460039.</mailxml_defs:ErrorDescription>
    <mailxml_defs:Action>Please use the MRRR message with Tracking ID 59201401130001460039 to
retrieve.</mailxml_defs:Action>
    <mailxml_defs:TrackingID>59000000000001460043</mailxml_defs:TrackingID>
    <mailxml_defs:SubmitterTrackingID>011314085128125</mailxml_defs:SubmitterTrackingID>
    <mailxml_defs:MailxmlDetail>
      <mailxml_defs:MailXMLVersion>13.0B</mailxml_defs:MailXMLVersion>
      <mailxml_defs:MailXMLMsgSize>2122</mailxml_defs:MailXMLMsgSize>

<mailxml_defs:MailXMLMsgName>QualificationReportSummaryCreateRequest</mailxml_defs:MailXMLMsgNam
e>
    </mailxml_defs:MailxmlDetail>
  </mailxml:ErrorWarning>
</mailxml:Fault>
```


6.14.4 MessageResponseRetrievalResponse Scenarios:

Scenario 1

Copyright © 2014 USPS®. All Rights Reserved

1. Mailer submits the initial request and the response is not available from Target Application in specified time.
2. MailXML Application generates a Come Back Later response and sends it back to Mailer.

Mail.XML 13.0B Example


```
<?xml version="1.0" encoding="UTF-8"?>
        <mailxml:Fault xmlns:mailxml="http://idealliance.org/Specs/mailxml13.0B/mailxml"
xmlns:mailxml_base="http://idealliance.org/Specs/mailxml13.0B/base"
xmlns:mailxml_defs="http://idealliance.org/Specs/mailxml13.0B/mailxml_defs"
xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
xsi:schemaLocation="http://idealliance.org/Specs/mailxml13.0B/mailxml mailxml_13.0b.xsd ">
  <mailxml:ErrorWarning>
    <mailxml_defs:Code>1502</mailxml_defs:Code>
    <mailxml_defs:Severity>Warning</mailxml_defs:Severity>
    <mailxml_defs:SubmissionDate>2014-01-20T06:47:32</mailxml_defs:SubmissionDate>
    <mailxml_defs:ErrorDescription>Come Back Later</mailxml_defs:ErrorDescription>
            <mailxml_defs:Action>The response is not available at this time, Please try again
        later.</mailxml_defs:Action>
    <mailxml_defs:TrackingID>59201401200001494656</mailxml_defs:TrackingID>
    <mailxml_defs:SubmitterTrackingID>48D0E3F4E44E013F-93</mailxml_defs:SubmitterTrackingID>
    <mailxml_defs:MailxmlDetail>
      <mailxml_defs:MailXMLVersion>13.0B</mailxml_defs:MailXMLVersion>
      <mailxml_defs:MailXMLMsgSize>476</mailxml_defs:MailXMLMsgSize>
<mailxml_defs:MailXMLMsgName>OpenMailingGroupRequest</mailxml_defs:MailXMLMsgName>
    </mailxml_defs:MailxmlDetail>
  </mailxml:ErrorWarning>
</mailxml:Fault>
```


Scenario 2

1. Mailer uses MRRR message with TrackingID *Number* to retrieve the responses after some wait time.
2. Target Application has already generated the response for the initial/first Request and the response is persisted in the database.
3. MailXML Application retrieves the response from database and provides the response back to Mailer.

Mail.XML 13.0B Example


```
<mailxml:MessageResponseRetrievalResponse xsi:schemaLocation="http://idealliance.org/Specs/mailxml13.0B/mailxml
mailxml_13.0b.xsd " xmlns:mailxml="http://idealliance.org/Specs/mailxml13.0B/mailxml"
xmlns:mailxml_base="http://idealliance.org/Specs/mailxml13.0B/base"
xmlns:mailxml_defs="http://idealliance.org/Specs/mailxml13.0B/mailxml_defs">
    <mailxml:MessageResponseRetrievalAccept mailxml:TrackingID="59201401230001510908"
xmlns:mailxml_mm="http://idealliance.org/Specs/mailxml13.0B/mailxml_mm">
```


Copyright © 2014 USPS®. All Rights Reserved

```
      <mailxml:QueryResults>
        <mailxml:CloseMailingGroupResponse
xmlns:maildefs="http://idealliance.org/Specs/mailxml13.0B/mailxml_defs"
xmlns:mailxml="http://idealliance.org/Specs/mailxml13.0B/mailxml_mm">
          <mailxml:SubmitterTrackingID>48D0E61B91CAEF0F-2E</mailxml:SubmitterTrackingID>
          <mailxml:CloseMailingGroupAccept mailxml:CustomerGroupID="AMZU9Q4"
mailxml:MailingGroupID="130006723">
            <mailxml:ReturnInfo/>
          </mailxml:CloseMailingGroupAccept>
        </mailxml:CloseMailingGroupResponse>
      </mailxml:QueryResults>
    </mailxml:MessageResponseRetrievalAccept>
  </mailxml:MessageResponseRetrievalResponse>
```


Scenario 3

1. Mailer uses MRRR message with TrackingID *Number* to retrieve the responses after some wait time.
2. Target Application has not generated the response for the initial/first Request yet.
3. MailXML Application provides a Come Back Later response to Mailer.

Mail.XML 13.0B Example


```
    <?xml version="1.0" encoding="UTF-8"?>
    <mailxml:MessageResponseRetrievalResponse
    xmlns:mailxml="http://idealliance.org/Specs/mailxml13.0B/mailxml"
    xmlns:mailxml_base="http://idealliance.org/Specs/mailxml13.0B/base"
    xmlns:mailxml_defs="http://idealliance.org/Specs/mailxml13.0B/mailxml_defs"
    xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
    xsi:schemaLocation="http://idealliance.org/Specs/mailxml13.0B/mailxml mailxml_13.0b.xsd ">
      <mailxml:MessageResponseRetrievalReject mailxml:TrackingID="59201401200001494823">
        <mailxml:ReturnInfo>
          <mailxml_defs:ErrorWarning>
            <mailxml_defs:Code>1502</mailxml_defs:Code>
            <mailxml_defs:Severity>Warning</mailxml_defs:Severity>
            <mailxml_defs:ErrorDescription>Come Back Later</mailxml_defs:ErrorDescription>
            <mailxml_defs:Action>The response is not available at this time, Please try again
    later.</mailxml_defs:Action>
          </mailxml_defs:ErrorWarning>
        </mailxml:ReturnInfo>
      </mailxml:MessageResponseRetrievalReject>
</mailxml:MessageResponseRetrievalResponse>
```


Copyright © 2014 USPS®. All Rights Reserved

7. Postage Statement Mappings

7.1 Mailing Information – Non Periodicals

7.1.1 Mailing Group Summary Information

The *PostalOne!* system will populate the Mailing Group Summary Information section of the Postage Statement based on the information that is provided in the Mail.XML messages.

The fields listed in the table below will determine the values that will be populated in the Mailing Group Summary Information section.

Mailing Group Summary Information Fields	Message/Field	Notes
Mailing Group ID	MailingGroupID	Mailing Group Unique Sequence Number
Preparer	PostageStatementCreateRequest	Looks up the Permit_No and Permit_Type in the P_Finance, P_Company, and P_Permit using the PermitNumber and PermitZip4 fields within the PermitPublicationData block within the MailingAgentData block within the CreatePostageStatement block and the CustomerReferenceID field within the CreatePostageStatement block. If the MailingAgentData block is not provided, the *PostalOne!* system looks up the Permit_No and Permit_Type in the P_Sec_User, P_Sec_User_Corp_Loc_Link, P_Company, and P_Permit tables using the PermitNumber field within the PermitPublicationData block within the MailingGroupData block within the OpenMailingGroupRequest message, the CustomerReferenceID field within the CreatePostageStatement block in the PostageStatementCreateRequest message, and the determined Finance Number.
Description	OpenMailingGroupRequest - CustomerDescription	
Mailer's Job #	OpenMailingGroupRequest - CustomerGroupID	
Finance No:	OpenMailingGroupRequest	The *PostalOne!* system looks up the Finance_No in the P_Finance table using two fields in the OpenMailingGroupRequest message: the PermitNumber field within the PermitPublicationData block within the MailingGroupData block and the PostOfficeOfMailingZip field within the MailingGroupData block.
Open Date	N/A	Date the mailing group was opened
Close Date	N/A	Date the PS was Finalized

7.1.2 Mailer Information

The *PostalOne!* system will populate the Mailer Information section of the Postage Statement based on information that is provided in the Mail.XML messages.

The fields listed in the table below will determine the values that will be populated in the Mailer Information section.

Mailer Information Fields	Field	Notes
Permit Holder		The *PostalOne!* system looks up the Company_Name, Address_Line1, Address_Line2, City, State, Zip_Code, Zip_Code4, Contact_Phone, and Contact_Email in the P_Finance, P_Permit, and P_Company table using the PermitNumber and PermitZip4 fields within the PermitPublicationData block within the PermitHolderData block within the CreatePostageStatement block in the

Copyright © 2014 USPS®. All Rights Reserved

Mailer Information Fields	Field	Notes
		PostageStatementCreateRequest message. The State is determined from the Zip_Code.
Mailing Agent		The *PostalOne!* system looks up the Company_Name, Address_Line1, Address_Line2, City, State, Zip_Code, Zip_Code4, Contact_Phone, and Contact_Email in the P_Finance, P_Permit, and P_Company tables using the PermitNumber and PermitZip4 fields within the MailingAgentData within the CreatePostageStatement block in the PostageStatementCreateRequest message. The State is determined from the Zip_Code. -or- If the MailingAgentData block is not provided, the *PostalOne!* system looks up the Company_Name, Address_Line1, Address_Line2, City, State, Zip_Code, Zip_Code4, Contact_Phone, and Contact_Email in the P_Sec_User, P_Sec_User_Corp_Loc_Link, P_Company, and P_Permit tables using the PermitNumber field within the PermitPublicationData block within the MailingGroupData block within the OpenMailingGroupRequest message, the CustomerReferenceID field within the CreatePostageStatement block in the PostageStatementCreateRequest message, and the determined Finance Number. The State is determined from the Zip_Code.
Org. For Mailing is Prepared	PostageStatementCreateRequest	The *PostalOne!* system looks up the Company_Name, Address_Line1, Address_Line2, City, State, Zip_Code, Zip_Code4, Contact_Phone, and Contact_Email in the P_Finance, P_Permit, and P_Company tables using the PermitNumber and PermitZip4 fields within the PermitPublicationData block within the MailingOwnerData block within the CreatePostageStatement block in the PostageStatementCreateRequest message. The State is determined from the Zip_Code. -or- If the MailingOwnerData block is not provided, the *PostalOne!* system populates the Organization for Mailing is Prepared information with Permit Holder information.
Permit Holder's Permit	PostageStatementCreateRequest - PermitNumber	
Mailing Agent's Permit	PostageStatementCreateRequest - PermitType, PermitNumber	If the PermitType field is not provided within PermitPublicationData block within the MailingAgent block, the *PostalOne!* system looks up the Permit_Type in the P_Permit table using the PermitNumber field within the PermitPublicationData block within the MailingAgentData block within the CreatePostageStatement block. -or- If the MailingAgentData block is not provided, the *PostalOne!* system looks up the Permit_No and Permit_Type in the P_Sec_User, P_Sec_User_Corp_Loc_Link, P_Company, and P_Permit tables using the PermitNumber field within the PermitPublicationData block within the MailingGroupData block within the OpenMailingGroupRequest message, the CustomerReferenceID field within the CreatePostageStatement block in the PostageStatementCreateRequest message, and the determined Finance Number.

7.1.3 Postage Summary Information

Copyright © 2014 USPS®. All Rights Reserved

The *PostalOne!* system will populate that Postage Summary information section of the Postage Statement based on the information that is provided in the Mail.XML messages.

The fields listed in the table below will determine the values that will be populated in the Postage Summary section.

Postage Summary Information Fields	Message/Field	Notes
Post Office of Mailing	OpenMailingGroupRequest	The *PostalOne!* system looks up the City, State, and Zip_Code in the P_Company table using the PostOfficeOfMailingZip field within the MailingGroupData block in the OpenMailingGroupRequest message. The State is determined from the Zip_Code.
Processing Category	PostageStatementCreateRequest – ProcessingCategory	
Mailer's Mailing Date	PostageStatementCreateRequest – PostageStatementMailingDate	
Federal Agency Cost Code	PostageStatementCreateRequest – AgencyCostCode	
Statement Seq. No	N/A	System generated sequence number
No. & type of Containers	PostageStatementCreateRequest – ContainerCount	Sum of containers grouped by Container Type
Type of Postage	PostageStatementCreateRequest – PostagePaymentMethod	
Weight of a Single Piece	PostageStatementCreateRequest – SinglePieceWeight or SinglePieceDimensionalWeight	
Hold For Pickup	PostageStatementCreateRequest - HoldForPickUp	First-Class Mail, Priority Mail, and Package Services only
Combined Mailing	PostageStatementCreateRequest – PermitNumber	Combined Mailing checkbox will be checked when a Mail.dat job is submitted with multiple values populated in the Permit Holder field.
Total Pieces	PostageStatementCreateRequest - TotalPieces	First-Class Mail, Standard Mail, and Package Services only
Of Total Pieces, # With Simplified Addresses	PostageStatementCreateRequest - NumberOfPiecesSimplifiedAddress	Standard Mail Only
Total Weight	PostageStatementCreateRequest – TotalWeight	
For Mail Enclose Within Another Class	PostageStatementCreateRequest - FormType	First-Class Mail, Priority Mail, and Standard Mail only
If Sacked, Based On	PostageStatementCreateRequest - SackingBasis	Standard Mail and Priority Mail only
Packaging Based on	PostageStatementCreateRequest - PackagingMethod	Package Services only
For Automation Price Pieces, Enter Date of Address Matching and Coding	PostageStatementCreateRequest - AutomationAddressMatchDate	
For Carrier Route Price Piece, Enter Date for Address Matching and Coding	PostageStatementCreateRequest - CarrierRouteAddressMatchDate	Standard Mail only
For Carrier Route Price Pieces, Enter Date of Carrier Route Sequencing	PostageStatementCreateRequest - CarrierRouteSequencingDate	Standard Mail only
For pieces bearing a simplified address enter data of delivery statistics file or	PostageStatementCreateRequest - DeliveryStatisticsFileDate	Standard Mail only

Copyright © 2014 USPS®. All Rights Reserved

Postage Summary Information Fields	Message/Field	Notes
alternative method		
For Barcoded Pieces, Enter Date of Address Matching and Coding	PostageStatementCreateRequest - AutomationAddressMatchDate	Priority Mail only
Move Update Method	PostageStatementCreateRequest - MoveUpdateMethod	First-Class Mail and Standard Mail only
Priority Mail Open and Distribute (PMOD)	PostageStatementCreateRequest - PMODIndicator	Priority Mail only
Total Postage	N/A	Sum of all parts of a postage statement
Address Matching Date – Automation	PostageStatementCreateRequest – AutomationAddressMatchDate	
Address Matching Date – Carrier Route	PostageStatementCreateRequest - CarrierRouteAddressMatchDate	
Customer Reference ID	PostageStatementCreateRequest - CustomerReferenceID	
Incentive Claimed	PostageStatementCreateRequest - USPSPriceIncentiveType	

7.2 Mailing Information – Periodicals

7.2.1 Mailing Group Summary Information

The *PostalOne!* system will populate the Mailing Group Summary Information section of the Periodicals Postage Statement based on the information that is provided in the Mail.XML messages.

The fields listed in the table below will determine the values that will be populated in the Mailing Group Summary Information section.

Mailing Group Summary Information Fields	Message/Field	Notes
Mailing Group ID	MailingGroupID	Mailing Group Unique Sequence Number
Preparer	PeriodicalStatementCreateRequest	Looks up the Permit_No and Permit_Type in the P_Finance, P_Company, and P_Permit using the PermitNumber and PermitZip4 fields within the PermitPublicationData block within the MailingAgentData block within the CreatePostageStatement block and the CustomerReferenceID field within the CreatePostageStatement block. If the MailingAgentData block is not provided, the *PostalOne!* system looks up the Permit_No and Permit_Type in the P_Sec_User, P_Sec_User_Corp_Loc_Link, P_Company, and P_Permit tables using the PermitNumber field within the PermitPublicationData block within the MailingGroupData block within the OpenMailingGroupRequest message, the CustomerReferenceID field within the CreatePostageStatement block in the PostageStatementCreateRequest message, and the determined Finance Number.
Description	OpenMailingGroupRequest - CustomerDescription	
Mailer's Job #	OpenMailingGroupRequest - CustomerGroupID	
Finance No:	OpenMailingGroupRequest	The *PostalOne!* system looks up the Finance_No in the P_Finance table using two fields in the OpenMailingGroupRequest message: the PermitNumber field

Copyright © 2014 USPS®. All Rights Reserved

Mailing Group Summary Information Fields	Message/Field	Notes
		within the PermitPublicationData block within the MailingGroupData block and the PostOfficeOfMailingZip field within the MailingGroupData block.
Open Date	N/A	Date the mailing group was opened
Close Date	N/A	Date the PS was Finalized

7.2.2 Mailer Information

The *PostalOne!* system will populate the Mailer Information section of the Periodicals Postage Statement based on the information that is provided in the Mail.XML messages.

The fields listed in the table below will determine the values that will be populated in the Mailer Information section.

Mailer Information Fields	Message/Field	Notes
Publication Title and Owner or News Agent's Name	PeriodicalStatementCreateRequest	The *PostalOne!* system looks up the Company_Name, Address_Line1, Address_Line2, City, State, Zip_Code, Zip_Code4, Contact_Phone, and Contact_Email in the P_Finance, P_Permit, and P_Company tables using the PublicationNumber or PermitNumber field within the PermitPublicationData block within PublisherData block within the CreatePeriodicalStatement block.
Mailer's Name, Address, Telephone Number, and Email	PeriodicalStatementCreateRequest	The *PostalOne!* system looks up Company_Name, Address_Line1, Address_Line2, City, State, Zip_Code, Zip_Code4, Contact_Phone, and Contact_Email in the P_Finance, P_Permit, and P_Company tables using the PermitNumber or PublicationNumber field within the PermitPublicationData block within the MailingAgentData block within the CreatePeriodicalStatement block in the PeriodicalStatementCreateRequest message, the CustomerReferenceID field within the CreatePeriodicalStatement block in the PeriodicalStatementCreateRequest message, and the determined Finance Number.-or-If the MailingAgentData block is not provided, the *PostalOne!* system looks up Company_Name, Address_Line1, Address_Line2, City, State, Zip_Code, Zip_Code4, Contact_Phone, and Contact_Email in the P_Sec_User, P_Sec_User_Corp_Loc_Link, P_Company, and P_Permit tables using the PermitNumber or PublicationNumber field within the PermitPublicationData block within the MailingGroupData block within the OpenMailingGroupRequest message, the CustomerReferenceID field within the CreatePostageStatement block in the PeriodicalStatementCreateRequest message, and the determined Finance Number.
Entry Post Office Name, State, and ZIP+4	OpenMailingGroupRequest	The *PostalOne!* system looks up the City, State, Zip_Code, and Zip_Code4 in the P_Company table using the PostOfficeOfMailingZip field within the MailingGroupData block. The State is determined from the Zip_Code.

7.2.3 Mailing Information

The *PostalOne!* system will populate the Mailing Information section of the Periodicals Postage Statement based on the information that is provided in the Mail.XML messages.

The fields listed in the table below will determine the values that will be populated in the Mailing Information section.

Copyright © 2014 USPS®. All Rights Reserved

Mailing Information Fields	Message/Field	Notes
Applicable Part Completed	N/A	Sections of the postage statement that were completed
Statement for bundles/containers only	N/A	
Price Category	PeriodicalStatementCreateRequest - RateType	
Combined Mailing	PeriodicalStatementCreateRequest – PublicationNumber	Combined Mailing checkbox will be checked when a Mail.XML mailings is submitted with multiple values populated in the Permit Holder field.
Consolidated Postage Statement	ConsolidatedPeriodicalStatementCreateRequest	Consolidated Mailing checkbox will be checked when a ConsolidatedPeriodicalStatementCreateRequest message is submitted
Publication No.	PeriodicalStatementCreateRequest - PublicationNumber	
Edition/Code	PeriodicalStatementCreateRequest - EditionCode	
Mailer's Mailing Date:	PeriodicalStatementCreateRequest – PostageStatementMailingDate	
Processing Category	PeriodicalStatementCreateRequest - ProcessingCategory	
No. of Addressed Pieces Excluding Address Supplements	N/A	Sum of the number of pieces for each line item for each completed part of the postage statement (excluding Addressed Supplements)
In-County Addressed Supplements	PeriodicalStatementCreateRequest – InCountryAddressedSupplementPieces	Sum of the number of In-County Addressed Supplements
Out-County Addressed Supplements	PeriodicalStatementCreateRequest – OutCountyAddressedSupplementPieces	Sum of the number of Out-County Addressed Supplements
Issue Date	PeriodicalStatementCreateRequest – IssueDate	
Volume Number	PeriodicalStatementCreateRequest – VolumeNumber	
Issue Number	PeriodicalStatementCreateRequest – IssueNumber	
Issue Frequency	PeriodicalStatementCreateRequest - IssueFrequency	
Statement Sequence No.	N/A	System generated sequence number
Weight of Single Ride-Along Piece	PeriodicalStatementCreateRequest - SingleRideAloneWeight	Calculated when Rate Type 'H' (Ride Along Weight)
Weight per Copy for Issue	PeriodicalStatementCreateRequest – CopyWeight	
Advertising Percentage in This Issue	PeriodicalStatementCreateRequest – AdvertisingPercentage	
Number and Type of Containers	PeriodicalStatementCreateRequest - ContainerCount	Sum of containers grouped by Container Type
Total Postage	N/A	Calculated by summing the total postage for all parts of the postage statement
For Automation Price Pieces, Enter Date for Address Matching and Coding	PeriodicalStatementCreateRequest - AutomationAddressMatchDate	

Copyright © 2014 USPS®. All Rights Reserved

Mailing Information Fields	Message/Field	Notes
For Carrier Route Price Piece, Enter Date for Address Matching and Coding	PeriodicalStatementCreateRequest - CarrierRouteAddressMatchDate	
For Carrier Route Price Pieces, Enter Date of Carrier Route Sequencing	PeriodicalStatementCreateRequest - CarrierRouteSequencingDate	
For pieces bearing a simplified address enter data of delivery statistics file or alternative method	PeriodicalStatementCreateRequest - DeliveryStatisticsFileDate	

Copyright © 2014 USPS®. All Rights Reserved

8. Error Messages

Faults, such as a message timeout or invalid XML are to be communicated using the <fault element and returned within the detail section of the SOAP fault. The fault consists of a Tracking ID and one or more fault codes and optional fault descriptions.

8.1 Error Codes and Messages

Faults, such as a message timeout or invalid XML are to be communicated using the <fault element and returned within the detail section of the SOAP fault. The fault consists of a Tracking ID and one or more fault codes and optional fault descriptions.

Below is the list of the error codes that will be used by USPS when deploying the eDocumentation Messages.

Error Code	Error Message
8000	CustomerGroupID in the HeaderInfo block must be the same for all messages in a mailing group.
8002	CRID field within the SubmittingParty block must be the same for all request messages in a mailing group.
8003	All fields within the DocumentVersionData block must match the corresponding fields in DocumentVersionData blocks and DocumentVersionDataWithPermit blocks with the same VersionID, except Periodicals with Non-Incidental Enclosures.
8004	More than %%1 failures for Warning code: %%2
8006	MailingGroupData block must be populated with a combination of values that exist in the *PostalOne!* Mail.dat database within the OpenMailingGroupRequest message.
8007	PermitNumber field within the PermitPublicationData block must map to the SubmitterCRID within the MailingGroupData block for preparing electronic documentation.
8008	PermitNumber field within the PermitPublicationData block must map to the SubmitterCRID within the MailingGroupData block must be unique when combined with the PermitType and PostOfficeOfMailingZip fields of the OpenMailingGroupRequest message.
8009	The first 5 characters of the PermitZIP4 field within the PermitPublicationData block must match the PostOfficeOfMailingZip field within the MailingGroupData block.
8010	MailingFacility field within the MailingGroupData block must be populated with a value that is the same as the CRID of the SubmittingParty block.
8011	OnePassIndicator field must be populated if the MailXMLPresentationCategory field in the MailingGroupData block is populated with M.
8012	OpenMailingGroupRequest message must be accepted before submitting the CloseMailingGroupRequst message for the specified MailingGroupID.
8013	The fields within the SubmittingParty block in the CloseMailingGroupRequest message must be populated with the same values as the fields within the SubmittingParty block of an open mailing group.
8014	CustomerGroupID field in the CloseMailingGroupRequest must be populated with the same value as the CustomerGroupID in the OpenMailingGroupRequest.
8015	MailingGroupID field in the CloseMailingGroupRequest must be populated with the same value as the MailingGroupID in the OpenMailingGroupResponse.
8016	MailingGroupID and CustomerGroupID in the CloseMailingGroupRequest must be populated with the same value as the MailingGroupID and CustomerGroupID of an accepted OpenMailingGroupRequest.
8017	OpenMailingGroupRequest message must be accepted before submitting the QualificationReportSummaryCreateRequest/QualificationReportDetailCreateRequest message for the specified MailingGroupID and CustomerGroupID.
8018	ContainerInfoData block(s) is required for each container/handling unit for a qualification report.
8020	Each ContainerInfoData block needs the ContainerDetailData block populated except when it is a Parent Container, it is a Sibling Container, or it is referenced in the SupplementalPhysicalContainerID field of a Container which contains a ContainerDetailData block.(Container ID: {1}).
8022	ActualContainerShipDate is required when USPSPickup field in the ContainerInfoData block in the QualificationReport block is Y. (Container ID: %%1)
8023	ContainerBarcode field in the ContainerInfoData block in the QualificationReport block cannot be populated when the ContainerType field value is L, M, or V. (Container ID: %%1)
8026	ParentContainerID field in the ContainerInfoData block in the QualificationReport block cannot be populated if the SiblingContainerID field is populated. (Container ID: %%1)
8027	ParentContainerID in the ContainerInfoData block in the QualificationReport block must point to another existing ParentContainerID within the QualificationReportSummaryCreateRequest/QualificationReportDetailCreateRequest messages.

Copyright © 2014 USPS®. All Rights Reserved

Error Code	Error Message
	(Container ID: %%1)
8028	SiblingContainerID field in the ContainerInfoData block in the QualificationReport block must point to a different container also in the QualificationReportSummaryCreateRequest/QualificationReportDetailCreateRequest message. (Container ID: %%1)
8030	EntryLocaleKey must contain 6 characters. (Container ID: %%1)
8032	AdditionalTrayPostageAmount must contain less than or equal to 4 decimal characters. (Container ID: %%1)
8033	PermitNumber within the PermitPublicationData block in the MailingGroupData block must be populated with a value combined with the PostOfficeOfMailingZIP in the MailingGroupData block that maps to a single active Finance Number.
8035	InOutCountyIndicator field in the ContainerDetailData block in the ContainerInfoData block in the QualificationReport block is required when FormType is PE. (Container ID: %%1)
8037	Only one ContainerID field in the MailXMLPieceRange block can be populated.
8039	BundleDetailCreateRequest message must be accepted before submitting the MailPieceCreateRequest message when BundleID in the MailPieceBlockGroup is populated for the specified MailingGroupID and CustomerGroupID.. (BundleID: %%1, ContainerID: %%2)
8040	PublicationNumber field in the QualificationReportPreparer block in the QualificationReport block cannot be populated when the FormType is not populated with PE for Periodicals.
8041	PermitNumber field in the QualificationReportPreparer block in the QualificationReport block is required when the FormType is not PE for Periodicals or Pending Periodicals.
8042	PermitType field within the QualificationReportPreparer in the QualificationReport block is required when the FormType is not PE for Periodicals or Pending Periodicals.
8043	PermitZIP4 field within the QualificationReportPreparer block in the QualificationReport block is required when the FormType is not PE for Periodicals or Pending Periodicals.
8045	VersionID field value within the DocumentVersionDataWithPermit block in the QualificationReport block must be referenced in at least one VersionID in the ContainerDetailData block. (Version ID: %%1)
8046	PieceWeight field within the DocumentVersionDataWithPermit block in the QualificationReport block must contain less than or equal to 4 decimal characters. (Version ID: %%1)
8047	AdPercent field value within the DocumentVersionDataWithPermit block in the QualificationReport block cannot be more than 4 decimals. (Version ID: %%1)
8048	AdPercent field value within the DocumentVersionDataWithPermit block of the QualificationReportDetailCreateRequest or DocumentVersionData block of the ConsolidatedPeriodicalStatementCreateRequest or PeriodicalStatementCreateRequest cannot be equal to or more than 100.00. (Version ID: {1})
8049	RateAffixed field within the DocumentVersionDataWithPermit block in the QualificationReport block cannot be more than 3 decimal characters. (Version ID: %%1)
8050	RateAffixed field within the DocumentVersionDataWithPermit block in the QualificationReport block is required when the PermitType field is set to MT, PC, or OM. (Version ID: %%1)
8051	PermitNumber field in the DocumentVersionDataWithPermit block in the QualificationReport block is required when the FormType is FC, SM, BP, ML, PM, or PP. The PermitNumber field cannot be populated when FormType is PE for Periodicals. Form type is: %%2
8053	PermitType field within PermitPublicationData block in the DocumentVersionDataWithPermit block in the QualificationReport block cannot be populated when the PublicaitonNumber is populated. (Version ID: %%1)
8055	PermitZIP4 field within PermitPublicationData block in the DocumentVersionDataWithPermit block in the QualificationReport block is required when the FormType is: PM, FC, SM, BP, PP, or ML.
8058	PublicationNumber field in the PermitPublicationData block in the DocumentVersionDataWithPermit block in the QualificationReport data block should not be populated when the FormType is not populated with PE for Periodicals or Pending Periodicals.
8061	QualificationReportSummaryCreateRequest/QualificationReportDetailCreateRequest message must be accepted before submitting the BundleDetailCreateRequest message for the specified CustomerGroupID and MailingGroupID.
8062	CustomerBundleID is a required field.
8063	BundleZIP must be populated with either 3 or 5 characters.
8064	BundleCarrierRoute is required when the SortationLevel in the BundleDetail block of the BundleDetailCreateRequest message is populated with A, B, C, D, or U.
8065	MailingGroupID and Customer GroupID in the BundleCreateRequestHeaderInfo block must be populated

Copyright © 2014 USPS®. All Rights Reserved

Error Code	Error Message
	with the same values as the MailingGroupID and CustomerGroupID of an accepted OpenMailingGroupRequest message.
8066	ContainerID must be populated with the same value as the ContainerID in the ContainerInfoData block of the QualificationReportSummaryCreateRequest/QualificationReportDetailCreateRequest message for the specified MailingGroupID and CustomerGroupID. Found Missing ContainerID: %%1
8067	VersionID must be populated with the same value as the VersionID in the ContainerDetailData block of the QualificationReportSummaryCreateRequest/QualificationReportDetailCreateRequest message for the specified MailingGroupID and CustomerGroupID. Found Missing VersionID: %%1
8068	BundleDetailCreateRequest message with the updated number of pieces for the specified combination of MailingGroupID, CustomerGroupID, and BundleID must be accepted before submitting the BundleDetailCancelRequest message. (BundleID '%%1')
8069	MailPieceCancelRequest message with the updated number of cancelled pieces for the specified combination of MailingGroupID, CustomerGroupID, and BundleID must be accepted before submitting the BundleDetailCancelRequest message.
8070	BundleDetailCreateRequest message must be accepted before submitting the BundleDetailCancelRequest message.
8071	BundleID is a required field.
8073	ContainerID must match the ContainerID in the BundleDetail block of the BundleDetailCreateRequest message for the specified MailingGroupID and CustomerGroupID. ContainerID %%1 was not found.
8074	BundleID must match the BundleID in the BundleDetail block of the BundleDetailCreateRequest message for the specified MailingGroupID and CustomerGroupID.
8075	OriginalContainer block must contain fields that are populated with the values that exist for the specified CRID.
8076	NewSiblingContainer block must be populated with values that tie to the values populated in the OriginalContainer block.
8077	CRID in the SubmittingParty block must be populated with the same value as the Mailing Facility ID in the .seg file for the specified information in the OriginalContainer block.
8078	UserLicenseCode field in the OriginalContainer block must be populated with the same value as the value populated in the User License Code field from the .hdr file of the existing container.
8079	MaildatJobID field in the OriginalContainer block must be populated with the same value as the value populated in the Job ID field from the .csm file of the existing container.
8080	ContainerID field in the OriginalContainer block must be populated with the same value as the value populated in the Container ID field in the .csm file of the existing container.
8081	UniqueContainerBarcode field in the OriginalContainer block, if populated, is populated with the same value as the Label: IM Container or IM Tray Barcode field in the .csm file of the existing container.(UniqueContainerBarcode %%1)
8082	UserLicenseCode field in the NewSiblingContainer block must be populated with the same value as the value populated in the UserLicenseCode field in the OriginalContainer block.
8083	MaildatJobID field in the NewSiblingContainer block must be populated with the same value as the value populated in the MaildatJobID field in the OriginalContainer block.
8084	MaildatJobID field in the NewSiblingContainer block must be populated with the same value as the value populated in the MaildatJobID field in the OriginalContainer block.
8087	ContainerID in the NewSiblingContainer block must be unique within the MaildatJobID. (ContainerID: %%1)
8088	The SiblingContainerCreateRequest message for this combination of CRID, MaildatJobID, ContainerId and SiblingContainerID does not exist.(Original ContainerID: %%1, Sibling ContainerID: %%2, CRID: %%3)
8089	SiblingToDelete block must be tied to an existing sibling container in the *PostalOne!* Mail.dat database for the specified CRID. (Sibling ContainerID: %%1)
8090	UserLicenseCode field in the OriginalContainer block must be populated with the same value as the value populated in the UserLicenseCode field in the OriginalContainer block of the SiblingContainerCreateRequest message.
8091	MaildatJobID field in the OriginalContainer block must be populated with the same value as the value populated in the MaildatJobID field in the OriginalContainer block of the SiblingContainerCreateRequest message.
8092	ContainerID field in the OriginalContainer block must be populated with the same value as the value populated in the ContainerID field in the OriginalContainer block of the SiblingContainerCreateRequest message.

Copyright © 2014 USPS®. All Rights Reserved

Error Code	Error Message
8093	UniqueContainerBarcode field in the OriginalContainer block, if populated, is populated with the same value as the value populated in the UniqueContainerBarcode field in the OriginalContainer block of the SiblingContainerCreateRequest message.
8094	UserLicenseCode field in the SiblingToDelete block must be populated with the same value as the value populated in the UserLicenseCode field in the NewSiblingContainer block of the SiblingContainerCreateRequest message for the specified CRID.
8095	MaildatJobID field in the SiblingToDelete block must be populated with the same value as the value populated in the MaildatJobID field in the NewSiblingContainer block of the SiblingContainerCreateRequest message for the specified CRID.
8096	ContainerID field in the SiblingToDelete block must be populated with the same value as the value populated in the ContainerID field in the NewSiblingContainer block of the SiblingContainerCreateRequest message for the specified CRID.
8097	UniqueContainerBarcode field in the SiblingToDelete block must be populated with the same value as the value populated in the UniqueContainerBarcode field in the NewSiblingContainer block of the SiblingContainerCreateRequest message for a specified CRID.
8098	The ContainerID field in the SibilingToDelete block cannot have ContainerType set to L, V, or M. (Sibling ContainerID: %%1)
8100	OpenMailingGroupRequest message must be accepted before submitting the PostageStatementCreateRequest message for the specified CustomerGroupID and MailingGroupID.
8101	BeginCombinedMailingRequest message must be accepted before submitting the PostageStatementCreateRequest message for the specified CustomerGroupID and MailingGroupID for a combined mailing.
8102	LineItemSummaryData block is required when the ExtendedForm in the CreatePostageStatement block is populated with False.
8103	PostageStatementLineItemData is required when the ExtendedForm in the CreatePostageStatement block is populated with True.
8104	PermitHolderForAPData is required when the PostagePaymentMethod in the CreatePostageStatement block is populated with M or S.
8105	MailingGroupID and Customer GroupID in the MailXMLPostageStatementRequestHeaderInfo block must be populated with the same values as the MailingGroupID and CustomerGroupID of an accepted OpenMailingGroupRequest message.
8106	AgencyCostCode in the CreatePostageStatement block must contain less than or equal to 5 characters.
8107	AgencyCostCode in the CreatePostageStatement block is required when the PermitType in the PermitPublicationData block in the MailingGroupData block is populated with OI or OM.
8113	CarrierRouteSequencingDate is required when the RateCategory in the PostageStatementLineItemData block is populated with A, B, D, O, A1, B1, or D1.
8114	PiecePostage in the LineItemSummaryData block must contain less than or equal to 4 decimal characters.
8115	PieceRate in the LineItemSummaryData block must contain less than or equal to 3 decimal characters.
8116	PostageAmount in the LineItemSummaryData block must contain less than or equal to 4 decimal characters.
8117	PoundPostage in the LineItemSummaryData block must contain less than or equal to 4 decimal characters.
8118	PoundRate in the LineItemSummaryData block must contain less than or equal to 3 decimal characters.
8119	PreparedAsSM must be populated with Yes when the FormType in the CreatePostageStatement block is populated with SM.
8121	TotalWeight in the LineItemSummaryData block must contain less than or equal to 4 decimal characters.
8123	ContainerDisplayName is required when the RegisterOfMailing in the CreatePostageStatement block is populated with True.
8124	ContainerID is required when the RegisterOfMailing in the CreatePostageStatement block is populated with True.
8125	EntryFacilityType is required when the RegisterOfMailing in the CreatePostageStatement block is populated with True.
8126	EntryZIP is required when the RegisterOfMailing in the CreatePostageStatement block is populated with True.
8128	PieceRate in the PostageStatementLineItemData block must contain less than or equal to 3 decimal characters.
8129	PostageAmount in the PostageStatementLineItemData block must contain less than or equal to 4 decimal

Copyright © 2014 USPS®. All Rights Reserved

Error Code	Error Message
	characters.
8130	PoundRate in the PostageStatementLineItemData block must contain less than or equal to 3 decimal characters.
8131	When PreparedAsSM is True and Form Type is FC, then ProcessingCategory must be FL, LT, or PF, and RateCategory must be S.
8133	SinglePieceWeight in the PostageStatementLineItemData block must contain less than or equal to 4 decimal characters.
8134	TotalWeight in the PostageStatementLineItemData block must contain less than or equal to 4 decimals characters.
8135	Zone can only be populated with N, 1, 3, 4, 5, 6, 7, 8, DDU, or SCF in the PostageStatementCreateRequest message.
8136	VersionID is required when the PostageAffixedAmount in the CreatePostageStatement block is not provided.
8137	ContainerType is required when the RegisterOfMailing in the CreatePostageStatement block is populated with True.
8138	SinglePieceDimensionalWeight in the PostageStatementLineItemData block must contain less than or equal to 4 decimal characters.
8139	SinglePieceDimensionalWeight in the PostageStatementLineItemData block must be populated with a value greater than zero when the SurchargeType in the *PostageStatementLineItemData* block is populated with D.
8140	PostageAffixedAmount is required when the PostagePaymentMethod in the CreatePostageStatement block is populated with M or S.
8141	When SinglePieceWeight in the CreatePostageStatement block is provided, it must match all SinglePieceWeight fields in the PostageStatementLineItemData block.
8142	ServiceRate in the ExtraServiceData block must contain less than or equal to 3 decimal characters.
8143	ServiceValue in the ExtraServiceDatamust block must contain less than or equal to 4 decimal characters.
8144	TotalAmount in the ExtraServiceData block must contain less than or equal to 4 decimal characters.
8145	TotalAmount in the ExtraServiceSummaryData block must contain less than or equal to 4 decimal characters.
8146	PieceWeight in the DocumentVersionData block must contain less than or equal to 4 decimal characters.
8147	RateAffixed is required when the PostagePaymentMethod in the CreatePostageStatement block is populated with M or S.
8148	RateAffixed in the DocumentVersionData block must contain less than or equal to 3 decimal characters.
8149	SinglePieceDimensionalWeight CreatePostageStatement must contain less than or equal to 4 decimal characters.
8153	MoveUpdateMethod is required when the FormType in the CreatePostageStatement block is populated with SM.
8155	The PermitNumber and PermitZIP4 or PublicationNumber in the PermitHolderData or PublisherData blocks and the MailingAgentData block must map to the same Finance Number and must be active.
8156	PermitType must be populated with MT or OM when the MeteredAffixedMethod in the CreatePostageStatement block is populated with M.
8157	PermitType must be populated with PC when the PostagePaymentMethod in the CreatePostageStatement block is populated with S.
8158	PublicationNumber cannot be populated in the PermitPublicationData block in the PermitHolderData block of the PostageStatementCreateRequest.
8159	PublicationNumber cannot be populated in the PermitPublicationData block in the MailingOwnerData block of the PostageStatementCreateRequest.
8160	PublicationNumber cannot be populated in the PermitPublicationData block in the MailingAgentData block of the PostageStatementCreateRequest.
8161	PermitType field in the PermitPublicationData block in the PermitHolderForAPData block must be populated with PI, OI, MT, or PC.
8162	PublicationNumber cannot be populated in the PermitPublicationData block in the PermitHolderForAPData block of the PostageStatementCreateRequest.
8163	PostageStatementMailingDate in the CreatePostageStatement block must match the PostageStatementMailingDate in the QualificationReportSummaryCreateRequest/QualificationReportDetailCreateRequest message when it is populated for the same ContainerID for the specified MailingGroupID and CustomerGroupID.
8164	CombinedMailingID in the CreatePostageStatement block must match the CombinedMailingID in the

Copyright © 2014 USPS®. All Rights Reserved

Error Code	Error Message
	BeginCombinedMailingAccept block of the BeginCombinedMailingResponse message for the specified MailingGroupID and CustomerGroupID.
8165	ServiceSubCode must be populated with N when ServiceCode in the ExtraServiceData block is populated with CM. Extra Service Data block number %%1 contains an invalid Sub Service Code %%2 for Service Code %%3.
8166	ServiceSubCode must be populated with N or R when ServiceCode in the ExtraServiceData block is populated with COD. Extra Service Data block number %%1 contains an invalid Sub Service Code %%2 for Service Code %%3.
8167	ServiceSubCode must be populated with N when ServiceCode in the ExtraServiceData block is populated with COM. Extra Service Data block number %%1 contains an invalid Sub Service Code %%2 for Service Code %%3.
8168	ServiceSubCode must be populated with E or R when ServiceCode in the ExtraServiceData block is populated with DC. Extra Service Data block number %%1 contains an invalid Sub Service Code %%2 for Service Code %%3.
8169	ServiceSubCode must be populated with N when ServiceCode in the ExtraServiceData block is populated with IM. Extra Service Data block number %%1 contains an invalid Sub Service Code %%2 for Service Code %%3.
8170	ServiceSubCode must be populated with N when ServiceCode in the ExtraServiceData block is populated with PAL. Extra Service Data block number %%1 contains an invalid Sub Service Code %%2 for Service Code %%3.
8171	ServiceSubCode must be populated with N when ServiceCode in the ExtraServiceData block is populated with RD. Extra Service Data block number %%1 contains an invalid Sub Service Code %%2 for Service Code %%3.
8172	ServiceSubCode must be populated with N when ServiceCode in the ExtraServiceData block is populated with RM. Extra Service Data block number %%1 contains an invalid Sub Service Code %%2 for Service Code %%3.
8173	ServiceSubCode must be populated with T when ServiceCode in the ExtraServiceData block is populated with RR. Extra Service Data block number %%1 contains an invalid Sub Service Code %%2 for Service Code %%3.
8174	ServiceSubCode must be populated with E when ServiceCode in the ExtraServiceData block is populated with RRE. Extra Service Data block number %%1 contains an invalid Sub Service Code %%2 for Service Code %%3.
8175	ServiceSubCode must be populated with N when ServiceCode in the ExtraServiceData block is populated with RRM. Extra Service Data block number %%1 contains an invalid Sub Service Code %%2 for Service Code %%3.
8176	ServiceSubCode must be populated with E or R when ServiceCode in the ExtraServiceData block is populated with SC. Extra Service Data block number %%1 contains an invalid Sub Service Code %%2 for Service Code %%3.
8177	ServiceSubCode must be populated with N when ServiceCode in the ExtraServiceData block is populated with SH. Extra Service Data block number %%1 contains an invalid Sub Service Code %%2 for Service Code %%3.
8178	SinglePieceWeight in the CreatePostageStatement block must be populated with the same value as the SinglePieceWeight in the PostageStatementLineItemData block for the specified MailingGroupID and CustomerGroupID.
8179	SinglePieceWeight in the CreatePostageStatement block must be populated with the same value as the PieceWeight in the DocumentVersionData block of the CreatePostageStatement block when the DocumentVersionData block is populated.
8181	DalPieces must be populated with a value that is equal to the total number of pieces with ProcessingCategory FL, MP, IR, or NP and RateCategory A, B, D, or O for the specified MailingGroupID and CustomerGroupID when provided.
8182	Pieces greater than 3.3 ounces and less than 16 ounces and pieces less than or equal to 3.3 ounces cannot be submitted together within a mailing when DalPieces is populated.
8184	StatementID in the PostageStatementQueryRequest message must exist for the specified MailingGroupID and CustomerGroupID.
8185	PeriodicalStatementID can only be submitted in the PeriodicalStatementQueryRequest.
8186	PostageStatementCreateRequest message or PeriodicalStatementCreateRequest message must be accepted before submitting the PostageStatementStatusQueryRequest message for the specified MailingGroupID, CustomerGroupID and StatementID.
8191	StatementID in the PostageStatementCancelRequest message must exist for the specified

Copyright © 2014 USPS®. All Rights Reserved

Error Code	Error Message
	MailingGroupID and CustomerGroupID.
8193	OpenMailingGroupRequest message must be accepted before submitting the BeginCombinedMailingRequest for the specified MailingGroupID and CustomerGroupID.
8194	MailingGroupID and CustomerGroupID of the BeginCombinedMailingRequest must be populated with the same values as the value populated in MailingGroupID and CustomerGroupID for an accepted OpenMailingGroupRequest message.
8195	All PostageStatementCreateRequest messages must be submitted for the specified MailingGroupID, CustomerGroupID,and CombinedMailingID before submitting the EndCombinedMailingRequest message.
8196	BeginCombinedMailingRequest message must be accepted for the specified MailingGroupID, CustomerGroupID, and CombinedMailingID before submitting the EndCombinedMailingRequest message.
8197	MailingGroupID and CustomerGroupID in the of the EndCombinedMailingRequest must be populated with the same values as the value populated in MailingGroupID and CustomerGroupID for an accepted OpenMailingGroupRequest message.
8198	OpenMailingGroupRequest message must be accepted before submitting the PeriodicalStatementCreateRequest message for the specified CustomerGroupID and MailingGroupID. (User Postage Statement ID: %%1).
8199	DocumentVersionData block in the CreatePeriodicalStatementData block is required. (User Postage Statement ID: %%1).
8200	AdvertisingPercentage in the CreatePeriodicalStatementData block must contain less than or equal to 2 decimal characters. (User Postage Statement ID: %%1).
8204	CopyWeight in the CreatePeriodicalStatementData block must contain less than or equal to 4 decimal characters. (User Postage Statement ID: %%1).
8205	DiscountQty in the PeriodicalLineItemData block is required when the PeriodicalPrice in the PeriodicalLineItemData block is populated with 1. (User Postage Statement ID: %%1).
8206	DiscountQty in the PeriodicalLineItemData block cannot contain decimal characters. (User Postage Statement ID: %%1).
8207	PeriodicalPrice in the PeriodicalLineItemData block can only be populated with Blank, 1, 5, 9, C, D, E, R, or Z. (User Postage Statement ID: %%1).
8210	Pieces in the PeriodicalLineItemData block is required when RateCategory in the PeriodicalLineItemData block is populated. (User Postage Statement ID: %%1).
8213	RateCategory in the PeriodicalLineItemData block can only be populated with A, B, D, O, FB, E, G, H, K, L1, L2, L3, L4, L5, L6, L, N in the PeriodicalLineItemData block. (User Postage Statement ID: {1}).
8214	At least one of the SubReqCopies or the NonCopies field is required and must be populated with a non-zero integer when both bundles and containers are not populated (User Postage Statement ID: %%1).
8217	ChargeableContainerLevel is required when InOutCountyIndicator is populated with N and ChargeableEntryLevel and ChargeableContainerType and Containers in the PeriodicalLineItemData block are populated. (User Postage Statement ID: %%1).
8218	ChargeableBundleLevel in the PeriodicalLineItemData block is required when InOutCountyIndicator is populated with N and ChargeableContainerLevel and Bundles in the PeriodicalLineItemData block are populated. (User Postage Statement ID: %%1).
8219	Bundles in the PeriodicalLineItemData block must contain less than or equal to 4 decimal characters. (User Postage Statement ID: %%1).
8220	Bundles in the PeriodicalLineItemData block is required when InOutCountyIndicator is populated with N and ChargeableContainerLevel and ChargeableBundleLevel in the PeriodicalLineItemData block are populated. (User Postage Statement ID: %%1).
8221	ChargeableEntryLevel is required when InOutCountyIndicator is populated with N and ChargeableContainerLevel and ChargeableContainerType and Containers in the PeriodicalLineItemData block are populated. (User Postage Statement ID: %%1).
8222	Containers in the PeriodicalLineItemData block must contain less than or equal to 4 decimal characters. (User Postage Statement ID: %%1).
8223	Containers in the PeriodicalLineItemData block is required when is populated with N and ChargeableContainerLevel, ChargeableEntryLevel and ChargeableContainerType in the PeriodicalLineItemData block are populated. (User Postage Statement ID: %%1).
8224	MachinableFlag in the PeriodicalLineItemData block is required when the RateCategory in the PeriodicalLineItemData block is populated and the processing category is flats. (User Postage Statement ID: %%1).
8225	PostagePaymentMethod in the CreatePeriodicalStatementData block can only be populated with P. (User

Copyright © 2014 USPS®. All Rights Reserved

Error Code	Error Message
	Postage Statement ID: %%1).
8226	ProcessingCategory in the CreatePeriodicalStatementData block can only be populated with LT, FL, IR, MP, or NP. (User Postage Statement ID: %%1).
8227	RateType in the CreatePeriodicalStatementData block can only be populated with R, N, S, C, W, or Y. (User Postage Statement ID: %%1).
8228	SingleRideAlongWeight is required when the PeriodicalPrice in the PeriodicalLineItemData block is populated with 9. (User Postage Statement ID: %%1).
8229	SingleRideAlongWeight must contain less than or equal to 4 decimal characters. (User Postage Statement ID: %%1).
8234	CombinedMailingID in the CreatePeriodicalStatementData block must be populated with the same value as the CombinedMailingID of the BeginCombinedMailingRequest message for a specified MailingGroupID and CustomerGroupID. (User Postage Statement ID: %%1).
8235	AdPercent in the DocumentVersionData block must contain less than or equal to 2 decimal characters. (User Postage Statement ID: %%1).
8236	AdPercent in the DocumentVersionData block must be populated with the same value as the AdvertisingPercentage in the CreatePeriodicalStatementData block. (User Postage Statement ID: %%1).
8237	RateAffixed in the DocumentVersionData block must contain less than or equal to 3 decimal characters. (User Postage Statement ID: %%1).
8238	RateAffixed in the DocumentVersionData block is not required when the PermitType in the PermitPublicationData block within the CreatePeriodicalStatementData block is populated with PI. (User Postage Statement ID: %%1).
8239	PermitType in the PermitPublicationData block in the PublisherData block in the CreatePeriodicalStatementData block must be populated with PP. (User Postage Statement ID: %%1).
8240	PendingPostageAmount in the CreatePeriodicalStatementData block is required when the PermitType in the PermitPublicationData block within the CreatePeriodicalStatementData block is populated with PP. (User Postage Statement ID: %%1).
8241	PendingPostageAmount in the CreatePeriodicalStatementData block must contain exactly 2 decimal characters. (User Postage Statement ID: %%1).
8242	MailingGroupID and CustomerGroupID in the PeriodicalStatementCreateRequest message must be the same values as the MailingGroupID and CustomerGroupID of an accepted OpenMailingGroupRequest message. (User Postage Statement ID: %%1).
8243	RateCategory in the PeriodicalLineItemData block and ChargeableContainerLevel in the PeriodicalLineItemData block cannot be populated in the same line. (User Postage Statement ID: %%1).
8244	RateCategory in the PeriodicalLineItemData block and Zone in the PeriodicalLineItemData block cannot be populated in the same line. (User Postage Statement ID: %%1).
8245	Containers in the PeriodicalLineItemData block and Bundles in the PeriodicalLineItemData block cannot be populated in the same line. (User Postage Statement ID: %%1).
8246	RateCategory in the PeriodicalLineItemData block and PeriodicalPrice in the PeriodicalLineItemData block cannot be populated in the same line. (User Postage Statement ID: %%1).
8247	ChargeableContainerLevel in the PeriodicalLineItemData block and PeriodicalPrice in the PeriodicalLineItemData block cannot be populated in the same line. (User Postage Statement ID: %%1).
8248	The Pending Periodical PermitZIP+4 or Periodical Publication number must map to the same finance number as the OpenMailingGroupRequest for a specified MailingGroupID and CustomerGroupID and must be active. (User Postage Statement ID: %%1).
8250	PeriodicalStatementCreateRequest must be accepted prior to submitting the PeriodicalStatementQueryRequest message for the specified MailingGroupID, CustomerGroupID, and StatementID.
8252	Postage StatementID in the PeriodicalStatementQueryRequest message must match the StatementID provided in the PeriodicalStatementCreateResponse message for the specified MailingGroupID and CustomerGroupID.
8255	AdvertisingPercentage in the PeriodicalStatement block must contain less than or equal to 2 decimal characters. (User Postage Statement ID: %%1).
8258	CarrierRouteAddressMatchingDate in the PeriodicalStatement block is required when the RateCategory in the LineItemSummaryData block is populated with A, B, or D. (User Postage Statement ID: %%1).
8259	CarrierRouteAddressMatchingDate in the PeriodicalStatement block is required when the RateCategory in the PeriodicalLineItemData block is populated with A, B, or D. (User Postage Statement ID: %%1).
8260	CarrierRouteSequencingDate in the PeriodicalStatement block is required when the RateCategory in the LineItemSummaryData block is populated with A, AF, B, BF, D, or DF. (User Postage Statement ID:

Copyright © 2014 USPS®. All Rights Reserved

Error Code	Error Message
	%%1).
8261	CarrierRouteSequencingDate in the PeriodicalStatement block is required when the RateCategory in the PeriodicalLineItemData block is populated with A, B, or D. (User Postage Statement ID: %%1).
8262	CopyWeight in the PeriodicalStatement block must contain less than or equal to 4 decimal characters. (User Postage Statement ID: %%1).
8263	FormType in the PeriodicalStatement block must be populated with PE. (User Postage Statement ID: %%1).
8264	PostagePaymentMethod in the PeriodicalStatement block must be populated with P. (User Postage Statement ID: %%1).
8265	ProcessingCategory in the PeriodicalStatement block must be populated with LT, FL, IR, MP, or NP. (User Postage Statement ID: %%1).
8267	SingleRideAlongWeight in the PeriodicalStatement block is required when the PeriodicalPrice in the PeriodicalLineItemData block is populated with 9. (User Postage Statement ID: %%1).
8268	SingleRideAlongWeight in the PeriodicalStatement block must contains less than or equal to 4 decimal characters. (User Postage Statement ID: %%1).
8272	AgencyCostCode in the PeriodicalStatement block must contain 6 characters when mapped to USPS. (User Postage Statement ID: %%1).
8273	AdPercent in the DocumentVersionData block must be populated with the same value as the AdvertisingPercentage in the PeriodicalStatement block. (User Postage Statement ID: %%1).
8274	RateAffixed in the DocumentVersionData block is not required when the PermitType in the PermitPublicationData block within the PeriodicalStatement block is populated with PI. (User Postage Statement ID: %%1).
8275	PermitType in the PermitPublicationData block within the ConsolidatedPeriodicalStatementCreateRequest message must be populated with PP.
8276	PendingPostageAmount in the PeriodicalStatement block is required when the PermitType in the PermitPublicationData block within the PeriodicalStatement block is populated with PP. (User Postage Statement ID: %%1).
8277	PendingPostageAmount in the PeriodicalStatement block must contain exactly 2 decimal characters. (User Postage Statement ID: %%1).
8279	Bundles in the PeriodicalLineItemData block of the CreateConsolidatedPeriodicalStatementData block must contain less than or equal to 4 decimal characters. (User Postage Statement ID: %%1).
8281	MailingGroupID and CustomerGroupID in the ConsolidatedPeriodicalStatementCreateRequest message must be the same values as the MailingGroupID and CustomerGroupID of an accepted OpenMailingGroupRequest message. (User Postage Statement ID: %%1).
8282	QualificationReportSummaryCreateRequest/QualificationReportDetailCreateRequest message must be accepted before submitting the ContainerBundleReportCreateRequest message for the specified MailingGroupID and CustomerGroupID.
8283	Either the SackTrayContainerVersionRecord block, the PalletContainerVersionRecord block, or the BundleVersionRecord block is required when the ContainerBundleVersionRecords block is sent.
8286	Either the SackTrayContainerRecord block, the PalletContainerRecord block, or the BundleRecord block is required when the ContainerBundleSummaryRecords block is sent.
8288	ContainerBundleReportCreateRequest message can only be provided when the FormType in the QualificationReportSummaryCreateRequest/QualificationReportDetailCreateRequest message is PE.
8289	Containers field in the SackTrayContainerVersionRecord block in the ContainerBundleVersionRecords block must contain less than or equal to 4 decimal characters.
8290	Containers field in the PalletContainerVersionRecord block in the ContainerBundleVersionRecords block must contain less than or equal to 4 decimal characters.
8291	Bundles field in the BundleVersionRecord block in the ContainerBundleVersionRecords block must contain less than or equal to 4 decimal characters.
8292	Containers field in the SackTrayContainerRecord block in the ContainerBundleSummaryRecords block must contain less than or equal to 4 decimal characters.
8293	Containers field in the PalletContainerRecord block in the ContainerBundleSummaryRecords block must contain less than or equal to 4 decimal characters.
8294	Bundles field in the BundleRecord block in the ContainerBundleSummaryRecords block must contain less than or equal to 4 decimal characters.
8295	The specified combination of MailingGroupID and CustomerGroupID in the ContainerBundleReportHeaderInfo block must match the values as that of the open mailing group.
8296	ContainerBundleReportCreateRequest message must be accepted before submitting the

Copyright © 2014 USPS®. All Rights Reserved

Error Code	Error Message
	ContainerBundleReportQueryRequest message for the specified MailingGroupID and CustomerGroupID.
8297	CustomerGroupID and MailingGroupID must exist for an accepted ContainerBundleReportCreateRequest message.
8298	ContainerBundleReportCreateRequest message must be accepted before submitting the ContainerBundleCancelRequest message for the specified MailingGroupID and CustomerGroupID.
8299	The specified combination of CustomerGroupID and MailingGroupID must be populated with the same combination of CustomerGroupID and MailingGroupID as an accepted ContainerBundleReportCreateRequest message.
8300	QualificationReportSummaryCreateRequest/QualificationReportDetailCreateRequest message must be accepted before submitting the MailPieceCreateRequest message to create a mail piece for the specified MailingGroupID and CustomerGroupID. (PieceID not found: %%1)
8301	QualificationReportSummaryCreateRequest/QualificationReportDetailCreateRequest message must be accepted before submitting the MailPieceCreateRequest message to create a piece range for the specified MailingGroupID and CustomerGroupID. (PieceRangeID not found: %%1)
8302	LOTSequenceDirectionCode in the MailPieceBlock must be populated when combined with the LOTSequenceNumber is populated and when Carrier Route LOT is used. (Piece ID: %%1).
8304	LOTSequenceNumber in the MailPieceBlock must be populated when the LOTSequenceDirection is populated.
8306	WalkSequenceNumber in the MailPieceBlock must be populated when Carrier Route LOT is used and the LOTSequenceDirection is not populated.
8307	DeliveryPointZIP in the MailPieceBlock block must contain 0, 5, 9, or 11 characters.
8309	DeliveryPointZIP in the MailPieceBlock block must be populated when the IMB block is not used and combined with the PlanetCode field. (Piece ID: %%1)
8310	MailerID6 in the IMbarcodeUpperSerialization block in the MailXMLPieceRangeBlock must match the MailerID6 in the IMbarcodeLowerSerialization block in the MailXMLPieceRangeBlock.(Piece Range ID is %%1)
8311	MailerID9 in the IMbarcodeUpperSerialization block in the MailXMLPieceRangeBlock must match the MailerID9 in the IMbarcodeLowerSerialization block in the MailXMLPieceRangeBlock.(Piece Range ID is %%1)
8312	SerialNumber6 in the IMbarcodeUpperSerialization block must be populated with a value greater than or equal to the SerialNumber6 in the IMbarcodeLowerSerialization block. (Piece Range ID is %%1)
8313	SerialNumber9 in the IMbarcodeUpperSerialization block must be populated with a value greater than or equal to the SerialNumber9 in the IMbarcodeLowerSerialization block. (Piece Range ID is %%1)
8314	MailerID6 fields must be blank when the ServiceLevelIndicator is populated with P. (piece_range_id: %%1)
8315	MailerID9 must be blank when the ServiceLevelIndicator is populated with P. (Found: %%1)
8316	SerialNumber6 must be blank when the ServiceLevelIndicator is populated with P. (Found: %%1)
8317	SerialNumber9 must be blank when the ServiceLevelIndicator is populated with P. (Found: %%1)
8318	The specified combination of MailingGroupID and CustomerGroupID in the MailPieceCreateRequest message must match the values of the accepted OpenMailingGroupRequest message.
8319	MailPieceCreateRequest must be accepted to create a mail piece before submitting a MailPieceUpdateRequest message for the specified MailingGroupID and CustomerGroupID.
8320	MailPieceCreateRequest must be accepted to create a piece range before submitting a MailPieceUpdateRequest message for the specified MailingGroupID and CustomerGroupID.
8325	MailPieceCreateRequest must be accepted to create a mail piece before submitting a MailPieceCancelRequest message for the specified MailingGroupID and CustomerGroupID.
8326	MailPieceCreateRequest must be accepted to create a piece range before submitting a MailPieceCancelRequest message for the specified MailingGroupID and CustomerGroupID.
8329	MailPieceBlock in the MailPieceCancelRequest message must be populated with the same values as the fields within the MailPieceBlock of the MailPieceCreateRequest message for the specified combination of MailingGroupID and CustomerGroupID.
8330	MailXMLPieceRangeBlock in the MailPieceCancelRequest message must be populated with the same values as the fields within the MailXMLPieceRangeBlock of the MailPieceCreateRequest message for the specified combination of MailingGroupID and CustomerGroupID.
8332	PostageStatementCreateRequest or PeriodicalStatementCreateRequest message must be accepted before submitting the PostageAdjustmentCreateRequest for the specified MailingGroupID and CustomerGroupID.
8333	StatementID in the PostageAdjustment block must be populated with the same value as the StatementID

Copyright © 2014 USPS®. All Rights Reserved

Error Code	Error Message
	in the PostageStatementCreateResponse or PeriodicalStatementCreateResponse for a specified MailingGroupID and CustomerGroupID. (Statement ID: %%1)
8334	AdjustmentAmount in the PostageAdjustment block must contain less than or equal to 2 decimal characters. (Statement ID: %%1)
8335	AdjustmentAmount field in the PostageAdjustment block must be less than the PostageAmount field in the PostageStatementCreateRequest message or PeriodicalStatementCreateRequest message. (Statement ID: %%1)
8336	TotalPiecesAffected field within the PostageAdjustment block must be less than the TotalPieces field in the PostageStatementCreateRequest message or PeriodicalStatementCreateRequest message. (Statement ID: %%1)
8337	UserPostageStatementID in the PostageAdjustment block must be populated with the same value as the UserPostageStatementID in the PostageStatementCreateResponse message or the PeriodicalStatementCreateResponse message. (Statement ID: %%1)
8338	AdjustmentDate in the PostageAdjustment block must be populated with a date later than the latest mailing date for the specified StatementID, MailingGroupID and CustomerGroupID. (Statement ID: %%1)
8339	PostageAdjustment block AdjustmentAmount must be less than the TotalPostage generated by the system on the PostageStatementCreateRequest or PeriodicalStatementCreateRequest for a specified MailingGroupID and CustomerGroupID. (Statement ID: %%1)
8342	Mail.dat Job ID: %%1 and User License Code: %%2 not found. Values must be populated with the same value in the .hdr file from the original Mail.dat submission.
8343	ContainerID %%1 must be populated with the same value as the Container ID in the .csm file from the original Mail.dat job submission for the specified CRID.
8344	UniqueContainerBarcode %%1 must be populated with same value as the Label: IM Container Or IM Tray Barcode field in the .csm file from the original Mail.dat job submission for the specified CRID.
8345	EntryPointEDPostalCode must contain exactly 5 characters (Container ID: %%1).
8346	EntryPointEDPostalCode is required when the EntryPointEDFacilityType is populated. (Container ID: %%1)
8347	EntryPointEDFacilityType is required when the EntryPointEDPostalCode is populated. (Container ID: %%1)
8348	EntryPointADLocaleKey must contain exactly 6 characters. (Container ID: %%1)
8349	EntryPointADLocaleKey is required when the EntryPointADPostalCode is populated. (Container ID: %%1)
8350	EntryPointADPostalCode is required when the EntryPointADLocaleKey is populated. (Container ID: %%1)
8351	ParentContainerReferenceID is required when a Parent Container exists. (Container ID: %%1)
8352	ContainerStatus previously populated with C can only be updated to R or D for the specified CRID. (Container ID: %%1)
8353	ContainerStatus previously populated with D cannot be updated for the specified CRID. (Container ID: %%1)
8354	ContainerStatus previously populated with R can only be updated to D, X, T, or C for the specified CRID. (Container ID: %%1)
8355	ContainerStatus previously populated with T can only be updated to D, X, or C for the specified CRID. (Container ID: %%1)
8356	ContainerStatus previously populated with X can only be updated to T for the specified CRID. (Container ID: %%1)
8358	IMBarcode field must be populated with either 21 or 24 characters. (Container ID: %%1)
8360	ContainerStatus cannot be updated to R when the Container Status of the original Mail.dat submission is populated with R. (Container ID: %%1)
8361	StopDesignator field cannot be updated when updating an original Mail.XML job. (Container ID: %%1)
8362	The StopDesignator field can only be updated when the ContainerStatus in the SummaryRecordUpdate block of the ContainerUpdateRequest message is populated with T. (Container ID: %%1, ContainerStatus: %%2)
8363	The TruckDispatchNumber field can only be updated when the ContainerStatus in the SummaryRecordUpdate block of the ContainerUpdateRequest message is populated with T. (Container ID: %%1, ContainerStatus: %%2)
8378	ServiceLevelIndicator in at least one ContainerDetailData block must be populated with F when the FullServiceParticipationIndicator in the MailingGroupData block of the OpenMailingGroupRequest message is populated with M.
8379	ServiceLevelIndicator in the ContainerDetailData block must be populated with F when the FullServiceParticipationIndicator in the MailingGroupData block of the OpenMailingGroupRequest

Copyright © 2014 USPS®. All Rights Reserved

Error Code	Error Message
	message is populated with F.
8380	At least one QualificationReportSummaryCreateRequest/QualificationReportDetailCreateRequest ContainerInfoData block must have a ContainerType of L or M if the LogicalPhysicalIndicator in the OpenMailingGroupRequest is L, MailXMLPresentationCategory is P, FullServiceParticipationIndicator is F or M.
8381	ContainerType must be populated with S = Sack (General), 1 = #1 Sack, 2 = #2 Sack, 3 = #3 Sack, 4 = 01V Sack, 5 = 03V Sack, V = Sack (Virtual), E = EMM Tray, F = Flat Tub, O = 1 ft Tray, T = 2 ft Tray, B = Bedload, U = Unit Load Device, Z = User Pallet, P = Pallet, H = EIRS 61 - Hamper, Large Canvas, A = EIRS 61P - Hamper, Large Plastic, G = EIRS 66 - General Purpose Mail Container w/Gate, D = EIRS 68 - Eastern Region Mail Container w/Web Door, R = EIRS 84 - Wire Container Rigid, C = EIRS 84C - Collapsible Wire Container, CT = Carton or AB = Air Box if the LogicalPhysicalContainerIndicator in the OpenMailingGroupRequest message is populated with P and FullServiceParticipationIndicator is F or M.
8382	FormType in the QualifcationReport block must be populated with FC, SM, BP, or PE when the FullServiceParticipationIndicator in the MailingGroupData block of the OpenMailingGroupRequest message is populated with F or M.
8383	ContainerInfoData block ProcessingCategory must be LT, FL, or CD when the QualificationReport block FormType is FC and FullServiceParticipationIndicator in the MailingGroupData block is F or M for the specified MailingGroupID and CustomerGroupID.
8384	ContainerInfoData block ProcessingCategory must be populated with LT or FL when the QualificationReport block FormType is SM and FullServiceParticipationIndicator in the MailingGroupData block is F or M for a specified MailingGroupID and CustomerGroupID.
8385	ContainerInfoData block ProcessingCategory must be populated with LT or FL when the QualificationReport block FormType is PE and FullServiceParticipationIndicator in the MailingGroupData block is F or M for a specified MailingGroupID and CustomerGroupID.
8386	ContainerInfoData block ProcessingCategory must be populated with FL when the QualificationReport block FormType is BP and FullServiceParticipationIndicator in the MailingGroupData block is F or M for the specified MailingGroupID and CustomerGroupID.
8387	CSAID is required when mail is DMU verified, mail is origin-entered, and FullServiceParticipationIndicator in the MailingGroupData block is F or M.
8388	CSAID is required when the mailer is a large volume mailer, mail is entered at a BMEU at an agreed upon time prior to CET, and FullServiceParticipationIndicator in the MailingGroupData block is F or M. (Container ID %%1)
8390	CSAID is required when the EntryPointFacilityType in the ContainerInfoData block is populated with O and the ConsigneeApptID in the ContainerInfoData block is populated and FullServiceParticipationIndicator in the MailingGroupData block is F or M.
8396	ScheduledShipDateTime is required when the EntryPointFacilityType is O, USPSPickup is populated with Y, and FullServiceParticipationIndicator in the MailingGroupData block is F or M.
8399	ContainerDetailData block TotalPieces must be 0 when the ContainerDetailData block is provided, ContainerInfoData block SiblingContainerID is populated, and MailingGroupData block FullServiceParticipationIndicator is F or M. (Container ID: %%1)
8400	ContainerBarcode must be populated with 21 characters when the ContainerType in the ContainerInfoData block is populated with B, U, W, P, H, A, G, D, R, C, Z, or AB and FullServiceParticipationIndicator in the MailingGroupData block is F or M.
8401	ContainerBarcode must be populated with 24 characters when the ContainerType in the ContainerInfoData block is populated with S, 1, 2, 3, 4, 5, E, F, O, T, or CT and FullServiceParticipationIndicator in the MailingGroupData block is F or M.
8402	IMtb or IMcb is required when the SiblingContainerCreateRequest ContainerType is B, U, P, H, A, G, D, R, C, S, 1, 2, 3, 4, 5, E, F, O, T, or CT and the Full-Service Participation Indicator in the MailingGroupData block is F or M. (ContainerID: {1})
8405	BarcodeID in the IMB block is required when the MailPieceBlock is provided.
8412	DeliveryPointZIP in the IMB block is required when the ServiceLevelIndicator is F. (Piece_id: {1})
8416	At least one of CRID, MailerID6, or MailerID9 in the MailOwner block of the MailPieceCreateRequest message must be populated when the MailXMLRangeBlock is populated
8417	MailerID9 must be populated with the same value as the MailerID9 in the IMbarcodeLowerSerialization block when submitted instead of the MailerID6. (ContainerID: %%1)
8418	MailerID6 must be populated with the same value as the MailerID6 in the IMbarcodeLowerSerialization block when submitted instead of the MailerID9. (ContainerID: %%1)

Copyright © 2014 USPS®. All Rights Reserved

Error Code	Error Message
8419	For all Full-Service MailXMLPieceRangeBlocks, the sum of the IMbarcodeUpperSerialization minus the IMbarcodeLowerSerialization plus one must be between the smaller of the sum of Pieces or Copies and 2% more than the larger of the sum of Pieces or Copies. .
8420	IMbarcodeUpperSerialization subtracted by the IMbarcodeLowerSerialization must equal the piece count and copy count when the PieceRange block is provided.
8421	The number of MailPieceBlocks associated to a ContainerID must equal the sum or between TotalPieces and TotalCopies in the ContainerDetailData block in the Qual Report for the ContainerID, MailingGroupID, and CustomerGroupID. (Container ID: %%1)
8422	The number of pieces in PieceRangeBlocks associated to a ContainerID cannot exceed the value in the ContainerDetailData block TotalPieces when the PieceRange Block is populated for a specified MailingGroupID and CustomerGroupID. (Container ID: %%1)
8423	PostageStatementLineItemData block is required when the FullServiceParticipationIndicator in the MailingGroupData block is populated with F or M.
8427	The pieces associated to a ContainerID in the Postage-, Periodical-, or ConsolidatedPeriodicalStatementCreateRequest message cannot exceed the sum of TotalPieces for that ContainerID in the Qualification Report (ContainerID %%1).
8428	MailXMLPieceBlock ServiceLevelIndicator must be F when the ContainerDetailData block ServiceLevelIndicator fields are all populated with F for the specified ContainerID within a specified MailingGroupID and CustomerGroupID. (ContainerID: %%1)
8429	MailXMLPieceRangeBlock ServiceLevelIndicator must be F when the ContainerDetailData block ServiceLevelIndicator fields are all populated with F for the specified ContainerID within a specified MailingGroupID and CustomerGroupID. (ContainerID: %%1)
8432	QualificationReportSummaryCreateRequest/QualificationReportDetailCreateRequest message must be accepted before submitting the PostageStatementCreateRequest message as for the specified MailingGroupID and CustomerGroupID when the FullServiceParticipationIndicator is F.
8434	ServiceLevelIndicator in the PieceRangeBlock must be populated with F, B, P, or O when the FullServiceParticipationIndicator field within the MailingGroupData block is M.
8435	At least one PieceRangeBlock must have the ServiceLevelIndicator field populated with F when the FullServiceParticipationIndicator field within the MailingGroupData block is populated with M.
8436	ServiceLevelIndicator in the ContainerDetailData block must be populated with F, B, P, or O when the FullServiceParticipationIndicator field within the MailingGroupData block is M.
8438	ContainerType must be populated with L when the PresentationCategory is populated with M and LogicalPhysicalContainerIndicator is populated with L in the MailingGroupData block.
8439	ContainerType must be populated with E, F, O, M, P, T, H, A, G, D, R or C in the ContainerInfoData block when another ContainerType field in the ContainerInfoData block is populated with L for the specified MailingGroupID and CustomerGroupID.
8440	At least one ContainerDetailData block must exist for each ContainerInfoData block in the Qual Report when the ContainerType is L and the OpenMailingGroupRequest MailXMLPresentationCategory is M for the specified MailingGroupID and CustomerGroupID.
8441	CustomerQualificationReportID field in the QualificationReport block is required when the MailXMLPresentationCategory field within the MailingGroupData block of the OpenMailingGroupRequest message is M.
8443	CustomerQualificationReportID field in the QualificationReport block is required for a MLOCR One-Pass mailing.
8444	The OnePassPlannedOrActualFlag in the QualificationReportSummaryCreateRequest/QualificationReportDetailCreateRequest message is required when the OnePassIndicator field in the OpenMailingGroupRequest message is Yes for the specified MailingGroupID and CustomerGroupID.
8445	PostageStatementLineItemData Containers for an MLOCR mailing must be in the QualificationReportSummaryCreateRequest/QualificationReportDetailCreateRequest message when the OnePassPlannedOrActualFlag is A for the specified MailingGroupID and CustomerGroupID. (ContainerID %%1 was not found)
8446	Mailing must be a One Pass MLOCR when OnePassPlannedOrActualFlag in the QualificationReportSummaryCreateRequest/QualificationReportDetailCreateRequest message is populated with A in the second submission for the specified MailingGroupID and CustomerGroupID.
8449	FormType in the QualificationReport bock must be FC for First-Class or SM for Standard Mail.
8451	No more than one LineItemSummaryData block in the CreatePostageStatement block can have the RateCategory populated with S for the specified MailingGroupID and CustomerGroupID.
8452	PostageAdjustmentCreateRequest message cannot be submitted for MLOCR mailings.

Copyright © 2014 USPS®. All Rights Reserved

Error Code	Error Message
8453	ProcessingCategory must be LT, FL, or CD when the FormType in the QualificationReport block is FC and MailXMLPresentationCategory in the MailingGroupData block is M for the specified MailingGroupID and CustomerGroupID.
8454	DocumentVersionData or -DataWithPermit PieceWeight cannot exceed 13oz when the QualificationReportSummaryCreateRequest/QualificationReportDetailCreateRequest FormType is FC and the ProcessingCategory is FL.
8456	PostagePaymentMethod in the PostageStatementCreateRequest must be P or M when the FormType is FC and ProcessingCategory is FL for the specified MailingGroupID and CustomerGroupID.
8460	ProcessingCategory in the ContainerInfoData block must be populated with LT when the FormType QualificationReport block is populated with SM for an MLOCR mailing.
8461	PieceWeight in the DocumentVersionData block or the DocumentVersionDataWithPermit block must be less than or equal to 3.3 ounces when the ProcessingCategory is LT and FormType is SM in the QualificationReportSummaryCreateRequest/QualificationReportDetailCreateRequest message.
8467	PostageAffixedAmount must be populated with a value greater than 0 when the PostagePaymentMethod in the CreatePostageStatement block is populated with M or S.
8469	MeteredAffixedMethod is required when the PostagePaymentMethod in the CreatePostageStatement block is populated with M.
8470	PermitHolderData block in the CreatePostageStatement block is required when the PostagePaymentMethod in the CreatePostageStatement block is populated with M or S.
8475	StatementID in the PostageAdjustment block must be populated with a value that references a postage statement where the Stage is not populated with FIN. (Statement ID: %%1)
8480	StatementID in the PostageAdjustment block must be populated with a value that references a postage statement that has not already been adjusted. (Statement ID: %%1)
8481	A PeriodicalStatementCreateRequest must be accepted before submitting a PostageStatementCreateRequest message with the EnclosedBy field set to PE for the same MailingGroupID and CustomerGroupID.
8482	OpenMailingGroupRequest message must be accepted before submitting the PeriodicalStatementCreateRequest for the specified MailingGroupID and CustomerGroupID.
8485	ProcessingCategory must be populated with FL, NP, MP, or IR when the FormType is BP.
8486	Zone must be populated with N, 1, 3, 4, 5, 6, 7, 8, DDU or SCF when FormType is BP and Processing Category is FL, MP, IR, or NP.
8490	EntryDiscount must be populated with N, B, S or D when FormType is BP.
8491	RateCategory must be populated with D, N, or S when the FormType is BP.
8492	SurchargeType must be populated with N when the FormType is BP.
8493	WeightBreakType must be populated with N when the FormType is BP.
8494	BarcodeRate must be populated with Y or N when the FormType is BP.
8497	PostagePaymentMethod must be populated with P when the FormType is BP.
8498	RateType must be populated with B when FormType is BP.
8500	SinglePieceWeight must be populated with a value less than or equal to 15 pounds when the FormType is BP.
8501	TotalPieces and TotalCopies must be populated with the same values when FormType is BP.
8502	ServiceCode must be populated with COD, COM, DC, IM, PAL, RD, RR, RRE, RRM, SC, or SH when FormType is BP.
8503	ProcessingCategory must be populated with LT, FL, CD, or PF when FormType is FC.
8504	Zone must be populated with N when FormType is FC and ProcessingCategory is LT, FL, CD, or PF.
8505	RateType must be populated with R or M when FormType is FC and ProcessingCategory is LT.
8506	RateCategory must be populated with E, H, L1, L2, N, PR, or S when FormType is FC and ProcessingCategory is LT.
8507	RateType must be populated with R or M when FormType is FC and ProcessingCategory is FL.
8508	RateCategory must be populated with E, H, L3, L4, N, PR, or S when FormType is FC and ProcessingCategory is FL.
8509	RateType must be populated with R or M when FormType is FC and ProcessingCategory is CD.
8510	RateCategory must be populated with E, H, L1, L2, N, or S when FormType is FC and ProcessingCategory is CD.
8511	RateType must be populated with R when FormType is FC and ProcessingCategory is PF.
8512	RateCategory must be populated with E, G, H, K, L3, L4, L5, L6, S, or N when FormType is FC and ProcessingCategory is PF.
8513	EntryDiscount must be populated with N when FormType is FC.

Copyright © 2014 USPS®. All Rights Reserved

Error Code	Error Message
8515	SurchargeType must be populated with A, E, N, R or L when FormType is FC.
8516	WeightBreakType must be populated with A, B, or N when provided and when the FormType is FC.
8517	SinglePieceWeight must be populated with a value greater than 0.0625 pounds when FormType is FC and SurchargeType is E and WeightBreakType is A.
8518	SinglePieceWeight must be populated with a value less than or equal to 0.0625 pounds when FormType is FC and SurchargeType is E and WeightBreakType is B.
8519	BarcodeRate must be populated with N or O when FormType is FC.
8520	EntryFacilityType must be populated with O, B, S, or D when FormType is FC.
8521	PackagingMethod must be populated with 0, 1, or Blank when FormType is FC.
8522	PostagePaymentMethod must be populated with S, M, or P when FormType is FC.
8524	MoveUpdateMethod must be populated with ASE, ACS, ALT, FAST, MULT, or NCOA when FormType is SM.
8525	EnclosedBy must be populated with SM, BP, PE, or ML when FormType is FC.
8526	ServiceCode must be populated with SH, COM, COD, RR, RM, SC, DC, RRE, CM, IM, or RD when FormType is FC.
8527	ProcessingCategory must be populated with PF when FormType is FC and ServiceCode is SC.
8528	ProcessingCategory must be populated with FL, MP, NP, or IR when FormType is ML.
8529	Zone must be populated with N when FormType is ML and ProcessingCategory is MP or IR.
8530	ProcessingCategory must be populated with FL, MP, or IR when FormType is ML and RateType is F.
8531	Zone must be populated with N when FormType is ML and RateType is F.
8533	ProcessingCategory must be populated with FL, MP, or IR when FormType is ML and RateType is L.
8536	EntryDiscount must be populated with N when FormType is ML.
8537	RateCategory must be populated with G, N, S, or E when FormType is ML.
8538	SurchargeType must be populated with N when FormType is ML.
8539	WeightBreakType must be populated with N when FormType is ML.
8540	BarcodeRate must be populated with Y or N when FormType is ML.
8541	EntryFacilityType must be populated with A, O, B, S, or D when FormType is ML.
8542	PackagingMethod must be populated with 0, 1, 2, or Blank when FormType is ML.
8543	PostagePaymentMethod must be populated with M or P when FormType is ML.
8544	RateType must be populated with L or F when FormType is ML.
8545	SackingBasis must be populated with 0 or 1 when FormType is ML.
8546	SinglePieceWeight must be less than or equal to 35 pounds when FormType is ML and BarcodeRate is Yes.
8547	SinglePieceWeight must be less than or equal to 70 pounds when FormType is ML and BarcodeRate is No.
8548	TotalPieces and TotalCopies must be populated with the same values when the FormType is ML.
8549	ServiceCode must be populated with COD, COM, DC, IM, PAL, RD, RR, RRE, RRM, SC, or SH when FormType is ML.
8550	ProcessingCategory must be populated with LT, FL, MP, IR, or NP when FormType is PE.
8551	The Zone field in the PeriodicalLineItemData block of the PeriodicalStatementCreateRequest message is provided, it must be populated with N, 1, 3, 4, 5, 6, 7, 8, ADC, DDU, SCF, or LC, when the FormType = PE in the CreatePeriodicalStatement block. ICD is no longer supported by USPS for In-county mailing. Please use DDU.
8554	EntryFacilityType must be populated with O, B, D, A, or S when FormType is PE. (User Postage Statement ID: %%1).
8557	LimitedCirculationDiscountClaimed must be populated with Yes when the FormType is PE and RateType is W or Y. (User Postage Statement ID: %%1).
8558	ContainerChargeContainerLevel must be populated with 3, 5, A, or M when FormType is PE.
8559	InOutCountyIndicator must be populated with N or I when FormType is PE.
8560	AdPercent is required when FormType is PE. (User Postage Statement ID: %%1).
8562	EntryFacilityType must be populated with O, B, S, D, or A when FormType is PE or Pending Periodicals. (User Postage Statement ID: %%1).
8563	RateCategory must be populated with A, B, D, E, G, H, K, L, L1, L2, L3, L4, L5, L6, L7, L8, FB, N, or O when mailing is identified as Periodicals. (User Postage Statement ID: {1}).
8564	When populated, Zone must be populated with DDU, 1, 3, 4, 5, 6, 7, 8, SCF, ADC, or N when FormType is PE and InOutCountyIndicator is I. (User Postage Statement ID: %%1).
8567	ProcessingCategory can only be populated with FL, MP, or LT when FormType is PE and

Copyright © 2014 USPS®. All Rights Reserved

Error Code	Error Message
	InOutCountyIndicator is I and RateCategory is L, H, or E. (User Postage Statement ID: %%1).
8571	RateCategory must be populated with A, B, D, FB, E, G, H, K, L3, L4, L5, or L6 when FormType is PE, and InOutCountyIndicator is N, and MachinableFlag is N, and ProcessingCategory is FL. (User Postage Statement ID: {1}).
8572	RateCategory must be populated with A, B, D, FB, E, G, H, K, L3, L4, L5, or L6 when FormType is PE and InOutCountyIndicator is N and MachinableFlag is Blank and ProcessingCategory is IR, MP, or NP. (User Postage Statement ID: %%1).
8573	RateCategory must be populated with A, B, D, FB, E, G, H, K, L1, L2, L3, L4, L5, or L6 when FormType is PE and InOutCountyIndicator is N and MachinableFlag is Blank and ProcessingCategory is LT. (User Postage Statement ID: %%1).
8574	ChargeableContainerLevel must be populated with M when FormType is PE and InOutCountyIndicator is N and ChargeableBundleLevel is M. (User Postage Statement ID: %%1).
8575	ChargeableContainerLevel must be populated with M or A when FormType is PE and InOutCountyIndicator is N and ChargeableBundleLevel is A. (User Postage Statement ID: %%1).
8576	ChargeableContainerLevel must be populated with M, A, or 3 when FormType is PE and InOutCountyIndicator is N and ChargeableBundleLevel is 3. (User Postage Statement ID: %%1).
8577	ChargeableContainerLevel must be populated with M, A, 3, or 5 when FormType is PE and InOutCountyIndicator is N and ChargeableBundleLevel is 5. (User Postage Statement ID: %%1).
8578	ContainerType must be populated with Pallets-Sacks-Trays when FormType is PE and Containers is populated. (User Postage Statement ID: %%1).
8579	ChargeableEntryLevel must be populated with C, J, or O when FormType is PE and ChargeableContainerLevel is M. (User Postage Statement ID: %%1).
8581	ChargeableEntryLevel must be populated with B, C, J, K, O, or R when FormType is PE and ChargeableContainerLevel is A. (User Postage Statement ID: %%1).
8583	ChargeableEntryLevel must be populated with B, C, J, K, O, R, or S when FormType is PE and ChargeableContainerLevel is 3. (User Postage Statement ID: %%1).
8585	ChargeableEntryLevel must be populated with B, C, D, J, K, O, R, or S when FormType is PE and ChargeableContainerLevel is 5. (User Postage Statement ID: %%1).
8586	ProcessingCategory must be populated with LT, FL or PF when FormType is PM.
8587	Zone must be populated with N, 1, 3, 4, 5, 6, 7, or 8 when FormType is PM and ProcessingCategory is LT, FL, or PF.
8588	RateType must be C, E, L, or T when FormType is PM and ProcessingCategory is FL
8589	RateCategory must be S, PR, P10, P11, P12, P13, P14, P15, or P16 when FormType is PM and ProcessingCategory is FL..
8590	RateType must be C or T when FormType is PM and ProcessingCategory is LT
8591	RateCategory must be S when FormType is PM and ProcessingCategory is LT.
8592	RateType must be E, G, J, K, L, X, or T when FormType is PM and ProcessingCategory is PF.
8593	RateCategory must be S, P10, P11, P12, P13, P14, P15, or P16 when FormType is PM and ProcessingCategory is PF.
8594	EntryDiscount must be populated with N when FormType is PM.
8595	RateCategory must be populated with S, PR, P10, P11, P12, P13, P14, P15, or P16 when FormType is PM.
8596	SurchargeType must be populated with D, E, N, or P when FormType is PM.
8597	WeightBreakType must be populated with N when FormType is PM.
8599	BarcodeRate must be populated with N or O when FormType is PM.
8600	EntryFacilityType must be populated with O, B, S, or D when FormType is PM.
8601	PostagePaymentMethod must be populated with P when FormType is PM.
8602	RateType must be populated with C, L, T, E, G, J, K, or X when FormType is PM.
8603	PriceType must be populated with Commercial, Commercial Plus, or Retail when FormType is PM.
8605	ServiceCode must be populated with AS, RAS, CM, COD, COM, DC, IM, RD, RM, RR, RRE, RRM, SC, or SH when FormType is PM.
8606	ProcessingCategory must be populated with MP, IR, or NP when FormType is PP.
8607	Zone must be populated with N, 1, 3, 4, 5, 6, 7, 8, DDU or SCF when FormType is PP.
8611	ProcessingCategory must be populated with MP, NP or IR when FormType is PP and RateType is P.
8612	Zone must be populated with 1, 3, 4, 5, 6, 7, or 8 when FormType is PP and RateType is P.
8613	RateCategory must be populated with S when FormType is PP and RateType is P.
8616	SurchargeType must be populated with 2 or N when FormType is PP.

Copyright © 2014 USPS®. All Rights Reserved

Error Code	Error Message
8617	WeightBreakType must be populated with N when FormType is PP.
8618	BarcodeRate must be populated with N when FormType is PP and RateType is P.
8620	PostagePaymentMethod must be populated with M or P when FormType is PP.
8621	RateType must be populated with P when FormType is PP.
8626	SinglePieceWeight must be populated with a value less than or equal to 70 pounds when FormType is PP, RateType is P, SurchargeType is N, RateCategory is S, and BarcodeRate is Y.
8627	SinglePieceWeight must be populated with a value less than or equal to 70 pounds when FormType is PP, RateType is P, SurchargeType is N, RateCategory is S, and BarcodeRate is N.
8628	SinglePieceWeight must be populated with a value less than or equal to 70 pounds when FormType is PP, RateType is P, SurchargeType is P, and RateCategory is S.
8629	SinglePieceWeight must be populated with a value less than or equal to 70 pounds when FormType is PP RateType is P, SurchargeType is 2, and RateCategory is S.
8630	SinglePieceWeight must be populated with a value less than or equal to 70 pounds when FormType is PP, RateType is P, SurchargeType is N or 2, and RateCategory is Z1 or Z2.
8631	SinglePieceWeight must be populated with a value less than or equal to 70 pounds when FormType is PP and RateType is P and SurchargeType is P or 2 and RateCategory is Z1 or Z2.
8632	TotalPieces and TotalCopies must be populated with the same values when FormType is PP.
8633	If populated, ServiceCode must be populated with COD, COM, DC, IM, PAL, RD, RR, RRE, RRM, SC, or SH when FormType is PP.
8634	ProcessingCategory must be populated with LT, FL, MP, IR, NP, CM, NA, or NB when FormType is SM. (User Postage Statement ID: %%1).
8635	Zone must be populated with N when FormType is SM and ProcessingCategory is LT, FL, MP, IR, or CM. (User Postage Statement ID: %%1).
8637	RateCategory must be populated with N when FormType is SM and ProcessingCategory is CM. (User Postage Statement ID: {1}).
8638	EntryDiscount must be populated with N when FormType is SM and ProcessingCategory is CM. (User Postage Statement ID: %%1).
8640	RateCategory must be populated with A, B, C, C1, D, O, E, G, H, K, L3, L4, L5, or L6 when FormType is SM and ProcessingCategory is FL. (User Postage Statement ID: {1}).
8642	RateCategory must be populated with A, B, D, O, P5, P6, P7, P8, PG, PI, PK, or PM when FormType is SM and ProcessingCategory is IR. (User Postage Statement ID: %%1).
8644	RateCategory must be populated with A, A1, B, B1, C, C1, D, D1, O, E, G, H, K, L1, L2, L5, L6, L7, or L8 when FormType is SM and ProcessingCategory is LT. (User Postage Statement ID: {1}).
8646	RateCategory must be populated with A, B, D, PE, PQ, or PR when FormType is SM and ProcessingCategory is MP. (User Postage Statement ID: %%1).
8648	RateCategory must be populated with N5, N6, NG, or NK when FormType is SM and ProcessingCategory is NA or NB. (User Postage Statement ID: %%1).
8649	EntryDiscount must be populated with N, B, S, or D when FormType is SM. (User Postage Statement ID: %%1).
8650	RateCategory must be populated with A, A1, B, B1, C, C1, D, D1, O, E, G, H, K, N, L1, L2, L3, L4, L5, L6, L7, L8, PE, PG, PI, PK, PM, PQ, PR, P5, P6, P7, or P8 when FormType is SM. (User Postage Statement ID: {1}).
8651	SurchargeType must be populated with L or N when FormType is SM. (User Postage Statement ID: %%1).
8652	WeightBreakType must be populated with A, B, or H when FormType is SM. (User Postage Statement ID: %%1).
8653	PieceWeight must be populated with a value greater than 0.2063 pounds when FormType is SM and WeightBreakType is A. (User Postage Statement ID: %%1).
8654	PieceWeight must be populated with a value less than or equal to 0.2063 pounds when FormType is SM and WeightBreakType is B. (User Postage Statement ID: %%1).
8655	PieceWeight must be populated with a value greater than 0.2063 pounds when FormType is SM and WeightBreakType is H and ProcessingCategory is LT. (User Postage Statement ID: %%1).
8656	BarcodeRate must be populated with Y, N, or O when FormType is SM. (User Postage Statement ID: %%1).
8657	EntryFacilityType must be populated with O, B, S, or D when FormType is SM. (User Postage Statement ID: %%1).
8658	PackagingMethod must be populated with 0, 1, 2, or Blank when FormType is SM. (User Postage Statement ID: %%1).

Copyright © 2014 USPS®. All Rights Reserved

Error Code	Error Message
8659	PostagePaymentMethod must be populated with S, M, or P when FormType is SM. (User Postage Statement ID: %%1).
8660	RateType must be populated with R or N when FormType is SM. (User Postage Statement ID: %%1).
8661	SackingBasis must be populated with 0, 1, 2, 3, 4, or Blank when FormType is SM. (User Postage Statement ID: %%1).
8662	EnclosedBy must be populated with SM, BP, PE, PP, or ML when FormType is SM. (User Postage Statement ID: %%1).
8663	ServiceCode must be populated with CBM, CODE, DC, DCE, IM, RRM, RD, or SCE when FormType is SM. (User Postage Statement ID: {1})
8665	The MailingGroupID in the OriginalContainerLinkageCancelRequest must be populated with the Consolidator MailingGroupID.
8666	OpenMailingGroupRequest message must be accepted before submitting the OriginalContainerLinkageCreateRequest message for the specified CRID when a Mail.dat container is being linked.
8667	QualificationReportSummaryCreateRequest/QualificationReportDetailCreateRequest must be accepted before submitting the OriginalContainerLinkageCreateRequest for the specified CRID when a Mail.XML container is being linked. (Linked Mailing Group: %%1, Linked Container ID: %%2).
8668	Values populated in the MailDatContainer block must exist when the original container was submitted through Mail.dat. (Original Mail.dat Job ID: %%1, Original Mail.dat Container ID: %%2).
8669	Values populated in the MailXMLContainer block must exist when the original container was submitted through Mail.XML. (Original Mailing Group: %%1, Original Container ID: %%2).
8670	Either the MailDatContainer block or the MailXMLContainer block of the OriginalContainer block is required.
8672	Populated fields in the MailXMLContainer block in the LinkedContainer block must link to fields in a MailXMLContainer block in the OriginalContainer block. (Linked Mailing Group: %%1, Linked Container ID: %%2).
8673	CustomerGroupID in the OriginalContainerLinkageCreateHeaderInfo block is required.
8674	MailingGroupID in the OriginalContainerLinkageCreateHeaderInfo block is required.
8675	OriginalContainerLinkageCreateRequest message must be accepted before the OriginalContainerLinkageCancelRequest message for the specified CRID when the linked container is created through Mail.XML. (Reason: %%1)
8676	OpenMailingGroupRequest message must be accepted before submitting the OriginalContainerCancelLinkageRequest message for the specified CRID when the linked container is created through Mail.dat.
8677	OpenMailingGroupRequest message must be accepted before submitting the OriginalContainerCreateLinkageRequest message for the specified CRID when the linked container is created through Mail.dat.
8678	PublicationNumber within the PermitPublicationData block in the MailingGroupData block must be populated with a value combined with the PostOfficeOfMailingZIP in the MailingGroupData block that maps to a single active Finance Number.
8679	PermitNumber field within the PermitPublicationData block in the DocumentVersionDataWithPermit block must exist and map back to a Finance Number. (Version ID: %%1)
8680	MailPieceBlock or MailXMLPieceRangeBlock is required when the FullServiceParticipationIndicator is populated with M.
8689	BundleID must be a unique value within a ContainerID in the BundleDetail block across the mailing group. (ContainerID: %%1, BundleID: %%2).
8692	OriginalContainer block must contain fields that are populated with the values that exist in the *PostalOne!* Mail.dat database for the specified CRID.
8693	ContainerID value that has been deleted within the SiblingContainerCancelRequest message cannot be reused within a mailing group. (Sibling Container ID: %%1 was previously cancelled.)
8694	UserPostageStatementID must be unique within the MailingGroupID. (User Postage Statement ID: %%1).
8695	ServiceCode must be populated with CM, COD, DC, IM, RD, RM, RR, RRE, RRM, SC, or SH when FormType is PM.
8696	CustomerQualificationReportID in the QualificationReport must be a unique value within the MailingGroupID.
8697	ContainerID in the QualificationReport must be a unique value within the MailingGroupID. (Container ID: %%1)
8698	VersionID in the ContainerDetailData must be populated and referenced with a VersionID in at least one

Copyright © 2014 USPS®. All Rights Reserved

Error Code	Error Message
	DocumentVersionDataWithPermit block associated to a Qualification Report. (Container ID: %%1)
8702	ContainerPostage is required when the FullServiceParticipationIndicator is F or M except when the ContainerID is populated for all PeriodicalStatementLineItemData blocks for the specified StatementSequenceNumber. (User Postage Statement ID: %%1).
8715	SiblingContainerCancelRequest message cannot be submitted when the original container and sibling container have the ContainerStatus of Ready to Pay. (Orig ContainerID: %%1, Sibling ContainerID: %%2)
8717	When the USPSPriceIncentiveType in the DocumentVersionData, LineItemSummaryData, or PostageStatementLineItemData block is provided, it must be set to Saturation-HDSCF, Saturation-HDTotal, PostageAffixedReplyRidesFree, MobileBarcode, or SummerSale.
8718	The maximum weight for First-Class Mail Automation Letters and Cards is 3.5 ounces.
8719	The maximum weight for First-Class Mail Non-Automation Letters is 13 ounces.
8720	The maximum weight for First-Class Mail Automation Flats is 13 ounces.
8721	The maximum weight for First-Class Mail Non-Automation Flats is 13 ounces.
8724	The StandardFlatType field in the LineItemSummary or PostageStatementLineItemData blocks must be populated when FormType is SM and ProcessingCategory is FL.
8725	The StandardFlatType field in the DocumentVersionDataWithPermit block must be populated when FormType is SM and ProcessingCategory is FL.
8726	The RateCategory must be E, H, L3, L4, A, B, D, or O for Standard Mail Flat Catalogs.
8728	The Maximum weight for Standard Mail Letters is 16 ounces.
8729	The Maximum weight for Standard Mail Flats is 16 ounces.
8731	The maximum weight for Package Services Bound Printed Matter is 20 ounces.
8732	The version weight for Periodical and Pending Periodical Letters cannot be greater than 16 ounces (Postg Stmt. %%1).
8733	The version weight for Periodical and Pending Periodical machinable Flats cannot be greater than 22 ounces (Postg Stmt. %%1).
8734	Rate Categories AF, BF, DF, GF, and KF are not supported for First-Class Mail, Standard Mail, or Periodicals.
8735	A ContainerDetailID field submitted in the MailPieceCreateRequest message must match a ContainerDetailID field submitted in the associated QualificationReportDetailCreateRequestMessage. (ContainerDetailID %%1 missing for ContainerID %%2)
8736	A ContainerDetailID field submitted in the PostageStatementCreateRequest message must match a ContainerDetailID field submitted in the associated QualificationReportDetailCreateRequestMessage. (ContainerDetailID %%1 missing for ContainerID %%2)
8737	A ContainerDetailID field submitted in the Periodical- or ConsolidatedPeriodicalStatementCreateRequest must match a ContainerDetailID field submitted in the associated QualificationReportDetailCreateRequest. (ContainerDetailID %%1 missing for ContainerID %%2)
8738	The number of pieces for a ContainerDetailID submitted in the MailPieceCreateRequest cannot exceed the number of pieces associated to that ContainerDetailID field in the QualificationReportDetailCreateRequest. (ContainerDetailID %%1 within ContainerID %%2)
8739	The number of pieces for the ContainerDetailID field submitted in the PostageStatementCreateRequest cannot exceed the pieces for that ContainerDetailID in the MailPieceCreateRequest. (ContainerDetailID %%1 missing for ContainerID %%2)
8740	The ContainerDetailID number of pieces in the Periodical- or ConsolidatedPeriodicalStatementCreateRequest cannot exceed the number of pieces associated to the MailPieceCreateRequest ContainerDetailID. (ContainerDetailID %%1 missing for ContainerID %%2)
8765	ParentContainerID field in the QualificationReportSummaryCreateRequest/QualificationReportDetailCreateRequest message is required when the IncludedinOtherDoc field is L and the SiblingContainerID is null. (ContainerDetailID %%1 missing for ContainerID %%2)
8767	SiblingContainerID is an optional field and cannot be populated if the ParentContainerID field is populated. When populated its length should be between 1 and 6 characters. (Found SiblingContainerID %% for ContainerID %%2)
8768	The system only supports Transportation Update with Container Status T in the ContainerUpdateRequest message.
8769	The system supports Transportation Update with Container Status T and Submission Date is within 30 days of the Postage Statement Mailing Date.
8809	A postage statement line did not map to a valid rate.
8810	The Permit Number, Type and Zip4 Option of the Permit Holder block must be populated in a

Copyright © 2014 USPS®. All Rights Reserved

Error Code	Error Message
	PostageStatementCreateRequest message.
8811	Verify that at least one Permit block was submitted.
8812	FullServiceParticipationIndicator in the MailingGroupData block of the OpenMailingGroupRequest message must be populated with F or M for mail piece or piece range creation.
8813	OriginalContainerCancelRequest message cannot cancel linked containers when the PostageStatementStatus in the PostageStatementSummary block is UPD and the ContainerType is V. (Linked Mailing Group: %%1, Linked Container ID: %%2).
8814	OriginalContainerCancelRequest message cannot cancel linked containers when the ContainerType of the original and linked container is O, T, E, or L. (Linked Mailing Group: %%1, Linked Container ID: %%2).
8815	At least one Extra Service Summary Data Block does not match the expected Rates.
8817	EnclosedBy in the CreatePostageStatement block must be populated with PE for Enclosures.
8818	EnclosingIssueDate is required when EnclosedBy in CreatePostageStatement block is populated with PE for Enclosures.
8819	FormType in the CreatePostageStatement block must be populated with FC or SM when EnclosedBy in CreatePostageStatement block is populated with PE.
8820	EntryLocaleKey field in the ContainerInfoData block must be populated for drop shipped mail. (Container ID: %%1)
8821	PostageStatementLineData does not match the Extended form setting in the header.
8822	More than %%1 failures for error code: %%2
8823	Version ID must be unique within the submitted message. (Version ID: %%1).
8824	An error occurred when parsing the message.
8826	SiblingContainerCreateRequest message must be sent before the original container has ContainerStatus populated with R.
8827	The MaildatJobID and UserLicenseCode provided did not map to a valid job.
8828	The new linked ctr id is already assigned to a different original ctr. (Linked ctr: %%1)
8831	When provided, RateCategory must be A, B, D, E, H, O, L1, L2, L3, or L4 when the FormType is PE, the InOutCountyIndicator is I, and the ServiceLevelIndicator for the associated ContainerID is F.
8832	When provided, RateCategory must be A, B, D, E, H, O, L1, L2, L3, L4, or FB when the FormType is PE, the InOutCountyIndicator is N, and the ServiceLevelIndicator for the associated ContainerID is F.
8833	RateCategory can only be E, H, L1, or L2 when FormType is FC, ProcessingCategory is CD, and the ServiceLevelIndicator for the associated ContainerID is F.
8834	RateCategory can only be E, H, L1, or L2 when FormType is FC, ProcessingCategory is LT, and the ServiceLevelIndicator for the associated ContainerID is F.
8835	RateCategory can only be E, H, L3, or L4 when FormType is FC, ProcessingCategory is FL, and the ServiceLevelIndicator for the associated ContainerID is F.
8836	RateCategory can only be A, A1, B, B1, C, C1, D,D1, O, E, H, L1 or L2 when FormType is SM, ProcessingCategory is LT, and the ServiceLevelIndicator for the associated ContainerID is F.
8837	The RateCategory field can only be populated with A, B, C, C1, D, O, E, H, L3 or L4 when the FormType is SM, ProcessingCategory is FL, and the ServiceLevelIndicator for the associated ContainerID is F.
8838	RateCategory can only be A, B, D, O, E, H, L3 or L4 when FormType is BP, ProcessingCategory is FL, and the ServiceLevelIndicator for the associated ContainerID is F.
8839	A Header record for Periodical Statement %%1 failed to generate.
8840	Only one Pieces field in the MailXMLPieceRange block can be populated.
8841	Only one Copies field in the MailXMLPieceRange block can be populated.
8842	The Origin Container Barcode specified in the Original Container Linkage message does not match the submitted Origin Container Barcode: %%1
8843	The Linked Container Barcode specified in the Original Container Linkage message does not match the submitted Linked Container Barcode: %%1
8844	The ProcessingCategory of child containers must match the ProcessingCategory of their respective parent container.
8845	The CinCode field in in the ContainerInfoData can only contain numeric characters.
8846	The FormType must be PE for a Periodical Statement or SM (if MixedMailFlag is set to Yes)
8847	The mail class must be the same across a co-palletized mailing.
8849	The Permit with Number %%1, and Type %%2 does not map to the same Finance Number as the permit for the Mailing Group.
8850	An OriginalContainerID and OriginalMailingGroup or a OriginalJobID in the OriginalContainerLinkageCreateRequest can not have been previously linked to a consolidator

Copyright © 2014 USPS®. All Rights Reserved

Error Code	Error Message
	MailingGroup. Container Id %%1
8851	The ContainerID field in the OriginalContainer block does not have a finalized postage statement associated to it, which is needed for Tray-Based Co-Palletization. Container Id: %%1
8856	The Total Postage for line block %%1 must be between the Postage calculated at the minimum and maximum rates for Section %%2, Line Number %%3
8857	The number of pieces in the InCountyAddressedSupplementPieces field cannot exceed the sum of all pieces in PeriodicalLineItemData blocks where InOutCountyIndicator is set to I. (User Postage Statement ID: %%1)
8858	The service level of the Linked Container may not be higher than that of the Original Container. Original Container Service Level: %%1, Linked Container Service Level: %%2
8859	When populated, the ContainerType field in SiblingContainerCreateRequest message must be populated with 1, 2, 3, 4, 5, E, F, O, P, S, T, B, U, Z, H, A, G, D, R, C, or CT.
8860	The number of pieces in the OutsideCountyAddressedSupplementPieces field cannot exceed the sum of all pieces in PeriodicalLineItemData blocks where InOutCountyIndicator is set to N. (User Postage Statement ID: %%1)
8861	For Copalletization, the linked container must have an Included In Other Documentation value of L. Container ID: %%1
8862	For Copalletization, the original container must have an Included In Other Documentation value of O or I. Container ID: {1}
8864	Each Periodical Statement submitted in a PeriodicalStatementCreateRequest or a ConsolidatedStatementCreateRequest must contain at least one PeriodicalLineItemData block.
8865	Each Postage Statement submitted in a PostageStatementCreateRequest must contain at least one PostageStatementLineItemData block or one LineItemSummaryData block.
8866	Invalid permit information was entered to claim the Science and Agriculture rate.
8867	Invalid Permit and Mail Owner information was entered to claim the Non-Profit rate.
8868	Invalid permit information was entered to claim the Classroom rate.
8869	An Internal Error occurred during the %%1 step while processing your message.
8870	A QualificationReportSummaryCreateRequest/QualificationReportDetailCreateRequest with the OnePassPlannedOrActualFlag with A must be preceded by a QualificationReportSummaryCreateRequest/QualificationReportDetailCreateRequest with the OnePassPlannedOrActualFlag set to P .
8871	All Postage Statements in a Combined Mailing must have the same Form Type. The Form Type for this Combined Mailing is %%1.
8873	Invalid permit information was entered to claim the Science of Agriculture Limited Circulation rate.
8874	Invalid permit information was entered to claim the Regular Limited Circulation rate.
8875	All Periodical Statements in a ConsolidatedPeriodicalStatementCreateRequest must have the same Combined Mailing ID.
8876	The QualificationReportSummaryCreateRequest/QualificationReportDetailCreateRequest message cannot have the records with the IncludedInOtherDoc field values set to O and L.
8877	The LineItemSummaryData block must have the PiecePostage field populated when the single piece weight is not provided.
8878	The PostageAmount in the LineItemSummaryData block must equal the PiecePostage plus the PoundPostage when the single piece weight is not provided.
8879	The PostageAmount in the LineItemSummaryData block cannot be greater than the PiecePostage amount when the single piece weight is not provided.
8880	The Piece Postage for line block %%1 must be between the Postage calculated at the minimum and maximum rates for Section %%2, Line Number %%3
8881	The Pound Postage for line block %%1 must be between the Postage calculated at the minimum and maximum rates for Section %%2, Line Number %%3
8882	Tray based copal container linkages cannot be cancelled. (ContainerID: %%1)
8883	Bundle based copal container linkages cannot be cancelled after the associated postage statements have been finalized. (ContainerID: %%1
8884	The Original Container and Linked Container must have the same Container Barcodes required for Full-service and Mixed Service containers. %%1
8885	When populated, the FullServiceParticipationIndicator field must be set to F.
8886	The Permit Holder Permit Type cannot equal PE or PP in a PostageStatementCreateRequest message.
8887	Neither the PermitNumber {1} associated to finance number {2} and PermitType {3} nor the identified Mail Owner has a non-profit status.

Copyright © 2014 USPS®. All Rights Reserved

Error Code	Error Message
8888	Container updates to origin containers in a co-pal tray job are not allowed after the consolidator job has been submitted. (Container ID: %%1)
8889	The number of pieces must equal the number of copies when the mailing does not include Firm Bundles or Addressed Supplements and InOutCountyIndicator is N.
8890	The number of pieces must be less than or equal to the number of copies when the mailing includes Firm Bundles but does not have any Addressed Supplements and InOutCountyIndicator is N.
8891	The number of pieces must be greater than or equal to the number of copies when the mailing includes Addressed Supplements but does not have Firm Bundles and InOutCountyIndicator is N.
8900	The CRID in the SubmittingParty block of the SiblingContainerCreateRequest message must match the CRID of the mailer that created the MailingGroup. (CRID: %%1)
8901	The CustomerGroupID field within the OriginalContainer block of the SiblingContainerCreateRequest message must be a string between 1 and 25 characters and match the CustomerGroupID of the existing container. (Container GroupID: %%1)
8902	The MailingGroupID field within the OriginalContainer block of the SiblingContainerCreateRequest message must be a non-negative integer and match the MailingGroupID of the existing container. (Mailing Group ID: %%1)
8903	The ContainerID fields in the OriginalContainer block of the SiblingContainerCreateRequest message must match the ContainerID fields in the QualificationReportSummaryCreateRequest/QualificationReportDetailCreateRequest message for the existing container. (Container ID: %%1)
8906	The ProcessingCategory field in the SummaryZipDestinationReport block of the SummaryZipDestinationReportCreateRequest message must be populated with LT, FL, CD, MP, IR, PF, CM, NP, NA, or NB.
8907	The PostagePaymentMethod field in the SummaryZipDestinationReport block of the SummaryZipDestinationReportCreateRequest message must be populated with S, M or P.
8908	The combination of MailingGroupID and CustomerGroupID in the SummaryZipDestinationReportCreateRequest message must be populated with the same values as that of the open mailing group.
8909	The QualificationReportSummaryCreateRequest/QualificationReportDetailCreateRequest message must be accepted before submitting the SummaryZipDestinationReportCreateRequest message for that specified MailingGroupID.
8910	The PostageStatementCreateRequest, PeriodicalStatementCreateRequest, or ConsolidatedPeriodicalStatementCreateRequest message must be accepted before submitting the SummaryZipDestinationReportCreateRequest message for that specified MailingGroupID..
8911	The CustomerGroupID field within the NewSiblingContainer block of the SiblingContainerCreateRequest message is the same value as the CustomerGroupID in the OriginalContainer block. (Container ID: %%1 , Customer Group ID: %%2)
8912	The MailingGroupID field within the NewSiblingContainer block of the SiblingContainerCreateRequest message is the same value as the MailingGroupID in the OriginalContainer block. (Container ID: %%1 , Mailing Group ID: %%2)
8915	The UniqueContainerBarcode field in the NewSiblingContainer block of the SiblingContainerCreateRequest message is a required field when the FullServiceParticipationIndicator in the OpenMailingGroupRequest message was F. (Container ID: %%1)
8916	The UniqueContainerBarcode field in the NewSiblingContainer block of the SiblingContainerCreateRequest message is a required field when the FullServiceParticipationIndicator in the OpenMailingGroupRequest message was M. (Container ID: %%1)
8930	The combination of MailingGroupID and CustomerGroupID in the CustomerMailReportCreateRequest message must be populated with the same values as that of the OpenMailing Group.
8931	The QualificationReportSummaryCreateRequest/QualificationReportDetailCreateRequest message must be accepted before submitting the CustomerMailReportCreateRequest message for that specified MailingGroupID.
8932	The PostageStatementCreateRequest message must be accepted before submitting the CustomerMailReportCreateRequest message for that specified MailingGroupID.
8935	The PermitType field in the PermitInfo block in the CustomerMailReportInfo block of the CustomerMailReportCreateRequest message must be PI, MT, PC, BR, GH, OI or OM when the PermitNumber field is populated.
8936	The PermitType field in the AdditionalPermitInfo block in the CustomerMailReportInfo block of the CustomerMailReportCreateRequest message must be PI, MT, PC, BR, GH, OI or OM when the PermitNumber field is populated.

Copyright © 2014 USPS®. All Rights Reserved

Error Code	Error Message
8937	The SiblingContainerCreateRequest message cannot be processed after the PostageStatementCreateRequest has been submitted for this Mailing Group. (Orig Container ID: %%1)
8938	The CRID in the SubmittingParty block of the SiblingContainerCancelRequest message must match the CRID of the mailer that created the MailingGroup. (CRID: %%1)
8939	The CustomerGroupID field within the OriginalContainer block of the SiblingContainerCancelRequest message is a string between 1 and 25 characters and must match the CustomerGroupID of the existing container. (Container GroupID: %%1)
8940	The MailingGroupID field within the OriginalContainer block of the SiblingContainerCancelRequest message is a non-negative integer and must match the MailingGroupID of the existing container. (Mailing Group ID: %%1)
8941	The ContainerID fields in the OriginalContainer block of the SiblingContainerCancelRequest message must match the ContainerID fields in the QualificationReportSummaryCreateRequest/QualificationReportDetailCreateRequest message for the existing container. (Container ID: %%1)
8942	The CustomerGroupID field within the SiblingToDelete block of the SiblingContainerCancelRequest message must match the CustomerGroupID in the OriginalContainer block. (Container ID: %%1 , Customer Group ID: %%2)
8943	The MailingGroupID field within the SiblingToDelete block of the SiblingContainerCancelRequest message must be populated with the same value as the MailingGroupID in the OriginalContainer block. (Container ID: %%1 , Mailing Group ID: %%2)
8944	The SiblingContainerCancel message must be submitted and processed before finalization of the postage statement associated to the oldest sibling for Full-Service and Mixed mailings. (Orig Container ID: %%1)
8945	The CustomerGroupID in the FullContainerID Block of the ContainerUpdateRequest message must match the CustomerGroupID of the existing container. (Container ID: {1} , Customer Group ID: {2})
8946	The MailingGroupID in the FullContainerID Block of the ContainerUpdateRequest message must match the MailingGroupID of the existing container. (MailingGroup ID: {1})
8947	The ContainerID in the FullContainerID Block of the ContainerUpdateRequest message must match the ContainerID in the QualificationReportDetailCreateRequestMessage for the specified MailingGroupID. (Container ID: {1})
8948	The UniqueContainerBarcode in the ContainerUpdateRequest FullContainerID block must match the existing container in the Qual Report message for the MailingGroupID and ContainerID. (Container ID: %%1, UniqueContainerBarcode: %%2)
8949	The Reservation field can only be updated when the ContainerStatus in the SummaryRecordUpdate block of the ContainerUpdateRequest message is populated with T. (Container ID: %%1)
8950	The IMBarcode field can only be updated when the ContainerStatus in the SummaryRecordUpdate block of the ContainerUpdateRequest message is populated with T. (Container ID: %%1)
8952	The CSATripID field can only be updated when the ContainerStatus in the SummaryRecordUpdate block of the ContainerUpdateRequest message is populated with T. (Container ID: %%1)
8953	The USPSPickUp field can only be updated when the ContainerStatus in the SummaryRecordUpdate block of the ContainerUpdateRequest message is populated with T. (Container ID: %%1)
8954	The ConsigneeContentID field can only be updated when the ContainerStatus in the SummaryRecordUpdate block of the ContainerUpdateRequest message is populated with T. (Container ID: %%1)
8955	The EntryPointADLocaleKey field can only be updated when the ContainerStatus in the SummaryRecordUpdate block of the ContainerUpdateRequest message is populated with T. (Container ID: %%1)
8956	The EntryPointADPostalCode field can only be updated when the ContainerStatus in the SummaryRecordUpdate block of the ContainerUpdateRequest message is populated with T. (Container ID: %%1)
8957	The ScheduledShipDateTIme field can only be updated when the ContainerStatus in the SummaryRecordUpdate block of the ContainerUpdateRequest message is populated with T. (Container ID: %%1)
8958	The ContainerStatus field in the SummaryRecordUpdate block of the ContainerUpdateRequest message must be populated with T when updating a Mail.XML job. (Container ID: %%1, ContainerStatus: %%2)
8959	The PostageStatementMailingDate in the ContainerInfoData block cannot be more than %%1 days in the future of the submission date and cannot be backdated prior to %%2.
8961	The ScheduledShipDateTime field in the ContainerInfoData block must be within 30 days of the past or present of the PostageStatementMailingDate.
8962	The EntryLocaleKey field in the ContainerInfoData block is required unless the EntryFacilityType field in

Copyright © 2014 USPS®. All Rights Reserved

Error Code	Error Message
	the ContainerInfoData block is populated with O and no appointment is provided.
8964	The ScheduledShipDate field in the SummaryRecordUpdate block of the ContainerUpdateRequest message must be within 30 days of the PostageStatementMailingDate field in the QualificationReportSummaryCreateRequest/QualificationReportDetailCreateRequest message for a Full-Service mailing.
8965	The PublicationNumber in the PermitInfo block or the AdditionalPermitInfo block in the CustomerMailReportInfo block of the CustomerMailReportCreateRequest message cannot be populated.
8967	The ContainerID field of the NewSiblingContainer must be unique within the mailing group. (Container ID: %%1).
8968	The ContainerID field in the PostageStatementLineItemData block in the PostageStatementCreateRequest message referenced as a sibling container with a ContainerType of M must be linked to an existing physical container. (Container ID: %%1).
8969	The ContainerID field in the PostageStatementLineItemData block in the PostageStatementCreateRequest message referenced as a sibling container with a ContainerType of L must be linked to an existing physical handling unit. (Container ID: %%1).
8970	The MailXMLPresentationCategory in the OpenMailingGroupRequest must be populated with M, P, C, or E for the SummaryZIPDestinationReportCreateRequest message to be processed.
8971	The MailXMLPresentationCategory in the OpenMailingGroupRequest must be populated with M for the CustomerMailReportCreateRequest message to be processed.
8972	If the OriginalContainer block UniqueContainerBarcode field is populated in the SiblingContainerCreateRequest or -CancelRequest, it must match the Qual Report ContainerBarcode field. (Container ID: %%1, UniqueContainerBarcode: %%2).
8973	Transportation updates cannot be performed on linked containers created at the Consolidator level for all Mail.XML Tray-Based Co-Palletized Full or Mixed-Service mailings. (Container ID: %%1).
8974	A linked container cannot be updated after the associated Postage Statement has been finalized for all Mail. XML Bundle-Based Co-Palletized Full or Mixed-Service mailings. (Container ID: %%1).
8975	Each container in the PostageStatementCreateRequest message must have been submitted in a QualificationReportSummaryCreateRequest/QualificationReportDetailCreateRequest message.
8984	Average piece range count error
8985	Duplicate Tray Barcode error - The ContainerBarcode in the ContainerInfoData block must be unique below the configurable threshold ({1}) when the ContainerType field is populated with S = Sack (general), 1 = #1 Sack, 2 = #2 Sack, 3 = #3 Sack, 4 = 01V Sack, 5 = 03V Sack, F = Flat Tub, O = 1 Tray, T = 2 Tray, E = EMM Tray, or F = Flat Tub. The current Percentage is ({2}).
8986	The PermitHolderData block PermitType in the PostageStatementCreateRequest message must be PI, PC, or MT when the PostageStatementCreateRequest RateCategory is S and the OpenMailingGroupRequest MailXMLPresentationCategory is M.
8987	The SortationLevel must be AJ when the RateLevel is SP in the QualificationReportSummaryCreateRequest/QualificationReportDetailCreateRequest message and FormType is FC in the QualificationReportSummaryCreateRequest/QualificationReportDetailCreateRequest message and the MailXMLPresentationCategory is M in the OpenMailingGroupRequest.
8988	At least one SortationLevel in the QualificationReportSummaryCreateRequest/QualificationReportDetailCreateRequest message must be set to AJ when the RateCategory is S and the FormType is FC in the PostageStatementCreateRequest and the PresentationCategory is M in the OpenMailingGroupRequest.
8989	The BarcodeID, ServiceTypeCode, MailerID6 or -9, and SerialNumber9 or -6 fields in the MailPieceCreateRequest IMB block must be populated when the OpenMailingGroupRequest MailXMLPresentationCategory is M and FullServiceParticipationIndicator is F or M.
8990	The MailPieceCreateRequest message IMbarcodeLowerSerialization and IMbarcodeUpperSerialization block fields must be populated when the OpenMailingGroupRequest message MailXMLPresentationCategory is M and the FullServiceParticipationIndicator is F or M.
8991	The AutomationAddressMatchDate cannot be more than 90 calendar days before the PostageStatementMailingDate when RateCategory is A, B, D, or O for carrier route mail.
8992	The AutomationAddressMatchDate cannot be more than 180 calendar days before the PostageStatementMailingDate when RateCategory is E, H, L, L1, L2, L3, or L4 for non-carrier route automation mail.
8993	When the PeriodicalPrice field within the PeriodicalLineItemData block is set to 1, the sum of DiscountQty must be greater than 0 and less than or equal to the sum of Pieces for In-County Piece Prices.
8994	The InOutCountyIndicator field must be set to I when the PeriodicalPrice field is set to 1 within the

Copyright © 2014 USPS®. All Rights Reserved

Error Code	Error Message
	PeriodicalLineItemData block of the PeriodicalStatementCreateRequest message.
8995	The Zone field must be set to DDU when the PeriodicalPrice field is set to 1 within the PeriodicalLineItemData block of the PeriodicalStatementCreateRequest message.
8996	The InOutCountyIndicator field must be set to I when the PeriodicalPrice field is set to 1 within the PeriodicalLineItemData block within the PeriodicalStatement block of the ConsolidatedPeriodicalStatementCreateRequest message.
8997	The Zone field must be set to DDU when the PeriodicalPrice field is set to 1 within the PeriodicalLineItemData block within the PeriodicalStatement block of the ConsolidatedPeriodicalStatementCreateRequest message.
8998	When the PeriodicalPrice field is set to 1 and the mailing does not contain In-County Addressed Supplements, the sum of DiscountQty must be greater than 0 and less than or equal to the number of Copies for In-County Pound Prices.
8999	The postage statement with statement ID: %%1, has been frozen and cannot be cancelled.
9000	PendingPostageAmount cannot be provided when the PublicationNumber is provided in the PermitPublicationData block within the CreatePeriodicalStatementData block of the PeriodicalStatementCreateRequest message. (User Postage Statement ID: %%1)
9001	PendingPostageAmount cannot be provided when the PublicationNumber is provided in the PermitPublicationData block within the PeriodicalStatement block of the ConsolidatedPeriodicalStatementCreateRequest message. (User Postage Statement ID: %%1)
9002	There can be no more than 999 unique CustomerReferenceIDs submitted in the PostageStatementCreateRequest, PeriodicalStatementCreateRequest, or ConsolidatedPeriodicalStatementCreateRequest messages submitted to a single Mail.XML MailingGroupID.
9003	The PostageStatementMailingDate field in the ContainerInfoData block in the QualificationReportSummaryCreateRequest/QualificationReportDetailCreateRequest message cannot span the price change date; within a job these dates must either be all before or all after %%1.
9004	The PostageStatementMailingDate field cannot be more than %%1 days in the future of the submission date and cannot be backdated prior to %%2.
9005	The PostageStatementMailingDate fields within a Mailing Group cannot span a price change date; they must be populated with all dates either before or after %%1.
9006	The Zone field in the ContainerDetailData block must be populated when the FormType is PE for Periodicals.
9008	A Transportation Update when ContainerStatus is T cannot be submitted more than 30 calendar days after the PostageStatementMailingDate.
9012	StandardFlatType must be the same for all DocumentVersionData, PostageStatementLineItemData, and LineItemSummaryData blocks within a PostageStatementCreateRequest message.
9013	The ContainerType field in the ContainerInfoData block contains an invalid value; ContainerType AB is only supported, when the FormType in the QualificationReportSummaryCreateRequest message is populated with PE = Periodicals.
9014	The maximum weight for Standard Mail Automation Carrier Route Letters is 3.5 ounces.
9015	The ProcessingCategory in the PeriodicalStatement or CreatePeriodicalStatement blocks must be set to FL when the SortationLevel in the QualificationReportSummaryCreateRequest/QualificationReportDetailCreateRequest or BundleDetailCreateRequest is set to E or F.
9016	The ProcessingCategory in the PeriodicalStatement or CreatePeriodicalStatement blocks must be set to FL when the BundleLevel in the BundleDetail block in the BundleDetailCreateRequest is set to X.
9017	The BundleLevel in the BundleDetailCreateRequest must be set to X when the associated SortationLevel in the QualificationReportSummaryCreateRequest/QualificationReportDetailCreateRequest or BundleDetailCreateRequest is set to E or F for Periodicals.
9018	The ContainerType in the QualificationReportSummaryCreateRequest/QualificationReportDetailCreateRequest must be set to P, Z, H, A, G, D, R, or C when the associated SortationLevel in the QualificationReportSummaryCreateRequest/QualificationReportDetailCreateRequest is set to E or F for Periodicals.
9019	The FormType field must be set to First-Class Mail or Standard Mail for a co-palletized mailing with the Container Type field set to F, O or T
9020	When a mailing is not a Simple Mailing, the combination of Mail Class derived from the ServiceTypeCode, MailerID and SerialNumber in the IMB block must be unique below the configurable threshold ({1}) when the mailing is Full or Mixed Service. (MailerID: {2}; SerialNumbers: {3}).

Copyright © 2014 USPS®. All Rights Reserved

Error Code	Error Message
9021	The MailerID and SerialNumber in the PieceRangeBlock must be unique within a mailing group below the configurable threshold (0%) when the mailing is Full-Service or Mixed Service. (PieceRange ID: ################)
9023	The EntryPointFacilityType in the ContainerInfoData block cannot be populated with N when the FullServiceParticipationIndicator in the OpenMailingGroupRequest message is F or M.
9024	The CSAID in the ContainerInfoData block must be populated with a 10 digit numeric between 1000000000 and 9999999999 when the FullServiceParticipationIndicator in the OpenMailingGroupRequest message is F or M.
9026	When the mailing is Full-Service or Mixed Service, the ConsigneeApptID in the ContainerInfoData block must be populated with one of the formats specified in the Mail.XML Tech Spec.
9027	The EntryPointADLocaleKey in the SummaryRecordUpdate block must be populated with 6 alphanumeric characters and cannot be populated with ORIGIN when the EntryPointFacilityType is O, the ContainerStatus is T and the mailing is Mixed or Full -Service.
9029	When the mailing is Full-Service or Mixed Service and the ContainerStatus in the SummaryRecordUpdate block is T, the ReservationNumber in the SummaryRecordUpdate block must be populated with one of the formats specified in the Mail.XML Tech Spec.
9031	The piece weight for First-Class Commercial Plus Parcels must be greater than or equal to 3.5oz and less than 16oz.
9032	The SurchargeType in the PostageStatementLineItemData or LineItemSummaryData block must be populated with N for First-Class Commercial Plus Parcels.
9034	The maximum weight for Package Services Bound Printed Matter non-barcoded Flats is 15 pounds.
9035	The maximum weight for Package Services Media/ Library Mail non-barcoded Flats is 70 pounds.
9036	The version weight for Periodical and Pending Periodical non-machinable Flats cannot be greater than 4.4 pounds (Postg Stmt. %%1).
9037	When submitting multiple MailPieceCreateRequest messages, the messages may only contain MailPieceBlockGroups or MailXMLPieceRangeBlockGroups, but not both within the same Mailing Group.
9038	The ContainerBarcode in the ContainerInfoData block must be unique below the configurable threshold (0%) when the mailing is Full-Service or Mixed Service. (Container Barcode: %%2).
9040	The FormType field contains an invalid value; it must contain FC or SM when the USPSPriceIncentiveType field is populated with MobileBarcode.
9041	The PermitType field contains an invalid value; it must contain PI when the USPSPriceIncentiveType field is populated with MobileBarcode.
9042	The ProcessingCategory field contains an invalid value; it must contain FL,LT, or CD when the USPSPriceIncentiveType field is populated with MobileBarcode.
9043	The PostageStatementMailingDateTime field must be populated with a date between %%1 and %%2.
9045	The PostageStatementMailingDateTime field must be populated with a date between %%1 and %%2 for an update submission when the USPSPriceIncentiveType field is populated with MobileBarcode.
9046	The PostageStatementMailingDateTime field must be populated between %%1 and %%2 for an update submission when the .cpt Postal Price Incentive Type of the Mail.dat original submission is populated with MB.
9062	The EntryPointFacilityType field in the ContainerInfoData block cannot be populated with B, D, or S when the FormType field in the QualificationReport block of the QualificationReportSummaryCreateRequest/QualificationReportDetailCreateRequest message is populated with FC.
9063	The EntryPointFacilityType field in the ContainerInfoData block cannot be populated with B, D, or S when the FormType field in the QualificationReport block of the QualificationReportSummaryCreateRequest message is populated with FC.
9064	The CSAID field in the ContainerInfoData block is required when the FormType field in the QualificationReport block is FC and the SortationLevel in the ContainerInfoData block is AK, AL, AM, AN, AO, AP, or AQ.
9065	The CSAID field in the ContainerInfoData block is required when the FormType in the QualificationReport block of the QualificationReportSummaryCreateRequest message is FC and SortationLevel in the ContainerInfoData block is AK, AL, AM, AN, AO, AP or AQ.
9067	OpenMailingGroupRequest message must be accepted before submitting the QualificationReportSummaryCreateRequest message for the specified MailingGroupID and CustomerGroupID.
9068	The CustomerQualificationReportID field in the QualificationReportSummary block of the QualificationReportSummaryCreateRequest message must be populated with a unique value within a

Copyright © 2014 USPS®. All Rights Reserved

Error Code	Error Message
	MailingGroupID.
9070	The FormType field in the QualificationReportSummary block contains an invalid value; it must contain FC, PE, PP, SM, BP, ML, or PM.
9072	OpenMailingGroupRequest message must be accepted before submitting the QualificationReportDetailCreateRequest message for the specified MailingGroupID and CustomerGroupID.
9073	The CustomerQualificationReportID field in the QualificationReportDetailCreateRequest message must match an existing CustomerQualificationReportID from an accepted QualificationReportSummaryCreateRequest message within a MailingGroupID.
9074	InOutCountyIndicator field in the ContainerDetailData block in the ContainerInfoData block in the QualificationReport block is required when FormType in the QualificationReportSummaryRequest message is PE. (Container ID: %%1)
9075	PermitNumber field in the DocumentVersionDataWithPermit block in the QualificationReport block is required when the FormType in the QualificationReportSummaryCreateRequest message is PM, FC, SM, BP, PP, or ML. Form type is: %%2
9076	PermitZIP4 field within PermitPublicationData block in the DocumentVersionDataWithPermit block in the QualificationReport block is required when the FormType in the QualificationReportSummaryCreateRequest message is PM, FC, SM, BP, PP, or ML.
9077	PublicationNumber field in the PermitPublicationData block in the DocumentVersionDataWithPermit block should not be populated when the FormType in the QualificationReportSummaryRequest message is not populated with PE for Periodicals or Pending Periodicals.
9078	All QualificationReportDetailCreateRequest messages must be accepted before submitting the associated BundleDetailCreateRequest message for the specified MailingGroupID and CustomerGroupID.
9079	All QualificationReportDetailCreateRequest messages must be accepted before submitting the associated ContainerBundleReportCreateRequest message for the specified MailingGroupID and CustomerGroupID.
9080	ContainerBundleReportCreateRequest message can only be provided when the FormType in the QualificationReportSummaryCreateRequest message is PE.
9081	All QualificationReportDetailCreateRequest messages must be accepted before submitting the associated MailPieceCreateRequest message to create a piece range for the specified MailingGroupID and CustomerGroupID.
9082	All QualificationReportDetailCreateRequest messages must be accepted before submitting the associated MailPieceCreateRequest message to create a mail piece for the specified MailingGroupID and CustomerGroupID.
9083	At least one QualificationReportDetailCreateRequest ContainerInfoData block must have a ContainerType of L or M if the LogicalPhysicalIndicator in the OpenMailingGroupRequest is L, MailXMLPresentationCategory is P, FullServiceParticipationIndicator is F or M.
9084	All QualificationReportDetailCreateRequest messages must be accepted before submitting the associated PostageStatementCreateRequest message for the specified MailingGroupID and CustomerGroupID.
9085	PieceWeight field in the DocumentVersionDataWithPermit block must be less than or equal to 13 oz when the ProcessingCategory field is populated with FL and the FormType field in the QualificationReportSummaryCreateRequest message is populated with FC.
9088	ProcessingCategory field in the ContainerInfoData block must be populated with LT or FL when the FormType field in the QualificationReportSummaryCreateRequest message is populated with SM for MLOCR mailings.
9089	PieceWeight field in the DocumentVersionDataWithPermit block cannot exceed 3.3 ounces when the ProcessingCategory field in the ContainerInfoData block is LT and the FormType field in the QualificationReportSummaryCreateRequest message is SM.
9090	All QualificationReportDetailCreateRequest messages must be accepted before submitting the associated OriginalContainerLinkageCreateRequest message for the specified MailingGroupID and CustomerGroupID.
9091	A ContainerDetailID field submitted in the MailPieceCreateRequest message must match a ContainerDetailID field submitted in the associated QualificationReportDetailCreateRequest message. (ContainerDetailID %%1 missing for ContainerID %%2)
9092	A ContainerDetailID field submitted in the PostageStatementCreateRequest message must match a ContainerDetailID field submitted in the associated QualificationReportDetailCreateRequest message. (ContainerDetailID %%1 missing for ContainerID %%2)
9093	A ContainerDetailID field submitted in the PeriodicalStatementCreateRequest message must match a ContainerDetailID field submitted in the associated QualificationReportDetailCreateRequest message. (ContainerDetailID %%1 missing for ContainerID %%2)

Copyright © 2014 USPS®. All Rights Reserved

Error Code	Error Message
9094	A ContainerDetailID field submitted in the ConsolidatedPeriodicalStatementCreateRequest message must match a ContainerDetailID field in the associated QualificationReportDetailCreateRequest message. (ContainerDetailID %%1 missing for ContainerID %%2)
9095	The number of pieces for a ContainerDetailID submitted in the MailPieceCreateRequest cannot exceed number of copies associated to that ContainerDetailID field in the QualificationReportDetailCreateRequest. (ContainerDetailID {1} within ContainerID {2}).
9096	ParentContainerID field in the QualificationReportDetailCreateRequest message is required when the IncludedInOtherDoc field is L and the SiblingContainerID is null. (ContainerDetailID %%1 missing for ContainerID %%2)
9098	The ContainerID fields in the OriginalContainer block of the SiblingContainerCreateRequest message must match the ContainerID fields in the QualificationReportDetailCreateRequest message for the existing container. (Container ID: %%1)
9099	All QualificationReportDetailCreateRequest messages must be accepted before submitting the associated SummaryZipDestinationReportCreateRequest message for the specified MailingGroupID and CustomerGroupID.
9100	All QualificationReportDetailCreateRequest messages must be accepted before submitting the associated CustomerMailReportCreateRequest message for the specified MailingGroupID and CustomerGroupID.
9101	The ContainerID fields in the FullContainer block of the ContainerUpdateRequest message must match the ContainerID fields in the QualificationReport message for the existing container. (Container ID: {1})
9102	The ScheduledInductionDate field in the SummaryRecordUpdate block of the ContainerUpdateRequest message must be within 30 days of PostageStatementMailingDate field in the QualificationReportDetailCreateRequest message for a Full-Service mailing.
9103	The ScheduledShipDate field in the SummaryRecordUpdate block of the ContainerUpdateRequest message must be within 30 days of PostageStatementMailingDate field in the QualificationReportDetailCreateRequest message for a Full-Service mailing.
9105	The SortationLevel must be AJ when the RateLevel is SP in the QualificationReportDetailCreateRequest message and FormType is FC in the QualificationReportSummaryCreateRequest message and the MailXMLPresentationCategory is M in the OpenMailingGroupRequest.
9106	At least one SortationLevel in the Qualification Report message must be AJ when the RateCategory is S and the FormType is FC in the PostageStatementCreateRequest and the MailXMLPresentationCategory is M in the OpenMailingGroupRequest.
9107	The ProcessingCategory in the PeriodicalStatement or CreatePeriodicalStatement blocks must be set to FL when the SortationLevel in the Qualification Report or BundleDetailCreateRequest is set to E or F.
9109	The ContainerType in the QualificationReportDetailCreateRequest must be set to P, Z, H, A, G, D, R, or C when the associated SortationLevel in the QualificationReportDetailCreateRequest is set to E or F for Periodicals.
9111	PostageStatementMailingDate in the CreatePostageStatement block must match the PostageStatementMailingDate in QualificationReportDetailCreateRequest message when it's populated for the same ContainerID for the specified MailingGroupID and CustomerGroupID.
9112	The ContainerID fields in the OriginalContainer block of the SiblingContainerCancelRequest message must match the ContainerID fields in the QualificationReportDetailCreateRequest message for the existing container. (Container ID: %%1)
9113	ContainerID must be populated with the same value as the ContainerID in the ContainerInfoData block of the QualificationReportDetailCreateRequest message for the specified MailingGroupID and CustomerGroupID. Found Missing ContainerID: %%1
9114	VersionID must be populated with the same value as the VersionID in the ContainerDetailData block of the QualificationReportDetailCreateRequest message for the specified MailingGroupID and CustomerGroupID. Found Missing VersionID: %%1
9115	The count of the Copies field in the PeriodicalLineItemData block must be equal to the sum of NonCopies and SubreqCopies in the PeriodicalStatementCreateRequest message.
9116	The count of the Copies field in the PeriodicalLineItemData block must be equal to the sum of NonCopies and SubreqCopies in the ConsolidatedPeriodicalStatementCreateRequest message.
9130	The FormType field in the CreatePostageStatement block must be populated with PM when the ContainerType field in the PostageStatementLineItemData block is 6, 7, 8, 9, 10, or 11.
9132	The FormType field in the QualificationReport block of the QualificationReportSummaryCreateRequest message must be populated with PM when the ContainerType field in the ContainerInfoData block is 6, 7, 8, 9, 10, or 11.
9133	The FormType field in the CreatePostageStatement block must be populated with PM when the

Copyright © 2014 USPS®. All Rights Reserved

Error Code	Error Message
	RateCategory field in the associated postage statement is P10, P11, P12, P13, P14, P15, or P16.
9136	The maximum weight for a Priority Mail cubic mail piece is 20lbs.
9137	The CRID field within the QualificationReportPreparer block in the QualificationReport block is required.
9138	The FormType in the qualification report must be set to FC when the SortationLevel in the is set to AK, AL, AM, AN, AO, AP, or AQ.
9139	The PMODIndicator field in the DocumentVersionData block must be populated with Yes when the ContainerType is populated with 6, 7, 8, 9, 10, or 11.
9140	The PMODIndicator field in the DocumentVersionData block must be populated with Yes when the RateCategory is populated with P12, P13, P14, P15, or P16.
9141	The FormType field in the CreatePostageStatement block must be populated with PM when the FlatRateIndicator is populated with O, C, P, or F.
9142	The IssueDate field in the MailXMLPostageStatementRequestHeaderInfo block of the ConsolidatedPeriodicalStatementCreateRequest message must match IssueDate field in the MailXMLPostageStatementRequestHeaderInfo block of BeginCombinedMailingRequest message.
9143	IssueNumber field in the MailXMLPostageStatementRequestHeaderInfo block of the ConsolidatedPeriodicalStatementCreateRequest message must match IssueNumber field in the MailXMLPostageStatementRequestHeaderInfo block of BeginCombinedMailingRequest message.
9144	VolumeNumber field in MailXMLPostageStatementRequestHeaderInfo block of the ConsolidatedPeriodicalStatementCreateRequest message must match VolumeNumber field in the MailXMLPostageStatementRequestHeaderInfo block of BeginCombinedMailingRequest message.
9145	CustomerReferenceID field in MailXMLPostageStatementRequestHeaderInfo block of ConsolidatedPeriodicalStatementCreateRequest message must match CustomerReferenceID in MailXMLPostageStatementRequestHeaderInfo block of BeginCombinedMailingRequest message.
9146	AgencyCostCode field in MailXMLPostageStatementRequestHeaderInfo block of the ConsolidatedPeriodicalStatementCreateRequest message must match AgencyCostCode field in MailXMLPostageStatementRequestHeaderInfo block of BeginCombinedMailingRequest message.
9147	PermitNumber field in MailXMLPostageStatementRequestHeaderInfo block of the ConsolidatedPeriodicalStatementCreateRequest message must match PermitNumber field in MailXMLPostageStatementRequestHeaderInfo block of BeginCombinedMailingRequest message.
9148	PermitType field in the MailXMLPostageStatementRequestHeaderInfo block of the ConsolidatedPeriodicalStatementCreateRequest message must match PermitType field in the MailXMLPostageStatementRequestHeaderInfo block of BeginCombinedMailingRequest message.
9149	PermitZip4 field in MailXMLPostageStatementRequestHeaderInfo block of the ConsolidatedPeriodicalStatementCreateRequest message must match PermitZip4 field in MailXMLPostageStatementRequestHeaderInfo block of BeginCombinedMailingRequest message.
9150	PublicationNumber field in MailXMLPostageStatementRequestHeaderInfo block of the ConsolidatedPeriodicalStatementCreateRequest message must match PublicationNumber in MailXMLPostageStatementRequestHeaderInfo block of BeginCombinedMailingRequest message.
9151	PostageStatementMethod in MailXMLPostageStatementRequestHeaderInfo block of ConsolidatedPeriodicalStatementCreateRequest message must match PostageStatementMethod in MailXMLPostageStatementRequestHeaderInfo block of BeginCombinedMailingRequest message.
9152	RateType field in the MailXMLPostageStatementRequestHeaderInfo block of the ConsolidatedPeriodicalStatementCreateRequest message must match RateType field in the MailXMLPostageStatementRequestHeaderInfo block of BeginCombinedMailingRequest message.
9153	ProcessingCategory field in MailXMLPostageStatementRequestHeaderInfo block of the ConsolidatedPeriodicalStatementCreateRequest message must match ProcessingCategory MailXMLPostageStatementRequestHeaderInfo block of BeginCombinedMailingRequest message.
9154	IssueDate field in the MailXMLPostageStatementRequestHeaderInfo block of the ConsolidatedPeriodicalStatementCreateRequest message must match IssueDate field in the MailXMLPostageStatementRequestHeaderInfo block of EndCombinedMailingRequest message.
9155	IssueNumber field in the MailXMLPostageStatementRequestHeaderInfo block of the ConsolidatedPeriodicalStatementCreateRequest message must match IssueNumber field in the MailXMLPostageStatementRequestHeaderInfo block of EndCombinedMailingRequest message.
9156	VolumeNumber field in MailXMLPostageStatementRequestHeaderInfo block of the ConsolidatedPeriodicalStatementCreateRequest message must match VolumeNumber field in the MailXMLPostageStatementRequestHeaderInfo block of EndCombinedMailingRequest message.
9157	CustomerReferenceID field in MailXMLPostageStatementRequestHeaderInfo block of ConsolidatedPeriodicalStatementCreateRequest message must match CustomerReferenceID in MailXMLPostageStatementRequestHeaderInfo block of EndCombinedMailingRequest message.

Copyright © 2014 USPS®. All Rights Reserved

Error Code	Error Message
9158	AgencyCostCode field in MailXMLPostageStatementRequestHeaderInfo block of the ConsolidatedPeriodicalStatementCreateRequest message must match AgencyCostCode field in MailXMLPostageStatementRequestHeaderInfo block of EndCombinedMailingRequest message
9159	PermitNumber field in MailXMLPostageStatementRequestHeaderInfo block of the ConsolidatedPeriodicalStatementCreateRequest message must match PermitNumber field in MailXMLPostageStatementRequestHeaderInfo block of EndCombinedMailingRequest message.
9160	PermitType field in the MailXMLPostageStatementRequestHeaderInfo block of the ConsolidatedPeriodicalStatementCreateRequest message must match PermitType field in the MailXMLPostageStatementRequestHeaderInfo block of EndCombinedMailingRequest message.
9161	The PermitZip4field in MailXMLPostageStatementRequestHeaderInfo block of the ConsolidatedPeriodicalStatementCreateRequest message must match PermitZip4field in MailXMLPostageStatementRequestHeaderInfo block of EndCombinedMailingRequest message.
9162	PublicationNumber field in MailXMLPostageStatementRequestHeaderInfo block of the ConsolidatedPeriodicalStatementCreateRequest message must match PublicationNumber in MailXMLPostageStatementRequestHeaderInfo block of EndCombinedMailingRequest message.
9163	PostageStatementMethod in MailXMLPostageStatementRequestHeaderInfo block of ConsolidatedPeriodicalStatementCreateRequest message must match PostageStatementMethod in MailXMLPostageStatementRequestHeaderInfo block of EndCombinedMailingRequest message.
9164	RateType field in the MailXMLPostageStatementRequestHeaderInfo block of the ConsolidatedPeriodicalStatementCreateRequest message must match RateType field in the MailXMLPostageStatementRequestHeaderInfo block of EndCombinedMailingRequest message.
9165	ProcessingCategory field in MailXMLPostageStatementRequestHeaderInfo block of the ConsolidatedPeriodicalStatementCreateRequest message must match ProcessingCategory MailXMLPostageStatementRequestHeaderInfo block of EndCombinedMailingRequest message.
9167	The FormType field in the QualificationReport block of the QualificationReportSummaryCreateRequest message must be populated with FC when the ContentOfMail field in the DocumentVersionWithPermit block is populated with F.
9168	The FormType field in the CreatePostageStatement block must be populated with FC when the ContentOfMailType field in the DocumentVersionData block is populated with F.
9170	The ProcessingCategory field in the ContainerInfoData block must be populated with LT or FL when the ContentOfMail field in the DocumentVersionDataWithPermit block is populated with F.
9171	The ProcessingCategory field must be populated with LT or FL when the ContentOfMailType field in the DocumentVersionData block is populated with F.
9173	When ContentOfMail in the DocumentVersionDataWithPermit block or ContentOfMailType in the DocumentVersionData block is set to F, then all instances of those fields in the Mailing Group must also be set to F.
9175	A postage statement may not be resubmitted with the EstimateIndicator field in the CreatePostageStatement block populated with Yes after the postage statement was previously submitted with an EstimateIndicator value of No.
9179	For eInduction processing, the ContainerBarcode field in the ContainerInfoData block must be populated when the corresponding ContainerType in the ContainerInfoData block is P, H, A, G, D, R, C, Z, or AB.
9180	For eInduction processing, the EntryLocaleKey field in the ContainerInfoData block must be populated when the corresponding ContainerType is P, H, A, G, D, R, C, Z, AB, M, T, O, E, F, S, 1, 2, 3, or L and the container is not a sibling.
9181	For eInduction processing, the ContainerBarcode field in the ContainerInfoData block must be populated when the corresponding ContainerType in the ContainerInfoData block is P, H, A, G, D, R, C, Z, or AB.
9182	For eInduction processing, the ContainerBarcode field in the ContainerInfoData block must begin with 99M when the corresponding ContainerType in the ContainerInfoData block is P, H, A, G, D, R, C, Z, or AB.
9183	For eInduction processing, the ContainerBarcode field in the ContainerInfoData block for IMcb(s)/pallets must be unique within the mailing group and amongst all containers associated to the SubmittingParty CRID that were finalized within the last 45 days. Container Barcode: {1}, Container ID: {2}.
9185	The CustomerReferenceID field in the PeriodicalStatement block must contain one value in the ConsolidatedPeriodicalStatementCreateRequest message.
9188	The MixedMailFlag field in the MailXMLQualReportRequestHeaderInfo block of the QualificationReportDetailCreateRequest must match the MixedMailFlag field in MailXMLQualReportRequestHeaderInfo block of QualificationReportSummaryCreateRequest message.
9191	The MailerID6 field in the SubmittingParty block of the QualificationReportDetailCreateRequest message must match the MailerID6 field in the SubmittingParty block of the

Copyright © 2014 USPS®. All Rights Reserved

Error Code	Error Message
	QualificationReportSummaryCreateRequest message.
9192	The MailerID9 field in the SubmittingParty block of the QualificationReportDetailCreateRequest message must match the MailerID9 field in the SubmittingParty block of the QualificationReportSummaryCreateRequest message.
9194	The ShippingAgent field in the SubmittingParty block of the QualificationReportDetailCreateRequest message must match the ShippingAgent field in the SubmittingParty block of the QualificationReportSummaryCreateRequest message.
9195	The ReceivingAgent field in the SubmittingParty block of the QualificationReportDetailCreateRequest message must match the ReceivingAgent field in the SubmittingParty block of the QualificationReportSummaryCreateRequest message.
9196	The SoftwareName field in the SubmittingSoftware block of the QualificationReportDetailCreateRequest message must match the SoftwareName field in the SubmittingSoftware block of the QualificationReportSummaryCreateRequest message.
9197	The Vendor field in the SubmittingSoftware block of the QualificationReportDetailCreateRequest message must match the Vendor field in the SubmittingSoftware block of the QualificationReportSummaryCreateRequest message.
9198	The Version field in the SubmittingSoftware block of the QualificationReportDetailCreateRequest message must match the Version field in the SubmittingSoftware block of the QualificationReportSummaryCreateRequest message.
9199	The ApprovalDate field in the SubmittingSoftware block of the QualificationReportDetailCreateRequest message must match the ApprovalDate field in the SubmittingSoftware block of the QualificationReportSummaryCreateRequest message.
9200	The ApprovalKey field in the SubmittingSoftware block of the QualificationReportDetailCreateRequest message must match the ApprovalKey field in the SubmittingSoftware block of the QualificationReportSummaryCreateRequest message.
9204	A PMOD package cannot be placed inside a PMOD container for Priority Mail.
9205	ParentContainerID in the ContainerInfoData block in the QualificationReport block must point to another existing ParentContainerID within the Qualification Report. (Container ID: %%1)
9206	SiblingContainerID field in the ContainerInfoData block in the QualificationReport block must point to a different container within the Qualification Report. (Container ID: %%1)
9208	The PMODIndicator must be populated with the same value for all postage statements in a mailing group.
9209	The submitted StatementID does not exist.
9210	At least one ContainerID submitted in the ContainerManifestCreateRequest must be associated to an IM Container Barcode provided in the IMcb field.
9211	The combination of ContainerID and StatementID or IMcb and StatementID must be unique within the submitted ContainerManifestCreateRequest and ContainerManifestUpdateRequest.
9213	The TotalDocVersionWithPermitBlocksCount must match number of DocumentVersionDataWithPermit blocks submitted in the QualificationReportDetailCreateRequest message.
9215	ProcessingCategory must be populated with FL, NP, MP, or IR when the FormType in the QualificationReportSummaryCreateRequest message is BP.
9216	Zone must be populated with N, 1, 3, 4, 5, 6, 7, 8, DDU or SCF when FormType field in the QualificationReportSummaryCreateRequest message is BP and Processing Category is FL, MP, IR, or NP.
9217	EntryDiscount must be populated with N, B, S or D when FormType field in the QualificationReportSummaryCreateRequest message is BP.
9218	TotalPieces and TotalCopies must be populated with the same values when FormType field in the QualificationReportSummaryCreateRequest message is BP.
9219	ProcessingCategory must be populated with LT, FL, CD, or PF when FormType field in the QualificationReportSummaryCreateRequest message is FC.
9220	Zone must be populated with N when FormType field in the QualificationReportSummaryCreateRequest message is FC and ProcessingCategory is LT, FL, CD, or PF.
9221	EntryDiscount must be populated with N when FormType field in the QualificationReportSummaryCreateRequest message is FC.
9222	ProcessingCategory must be populated with FL, MP, NP, or IR when FormType field in the QualificationReportSummaryCreateRequest message is ML.
9223	Zone must be populated with N when FormType field in the QualificationReportSummaryCreateRequest message is ML and ProcessingCategory is MP or IR.
9224	EntryDiscount must be populated with N when FormType field in the

Copyright © 2014 USPS®. All Rights Reserved

Error Code	Error Message
	QualificationReportSummaryCreateRequest message is ML.
9225	TotalPieces and TotalCopies must be populated with the same values when the FormType field in the QualificationReportSummaryCreateRequest message is ML.
9226	ProcessingCategory must be populated with LT, FL, MP, IR, or NP when FormType field in the QualificationReportSummaryCreateRequest message is PE.
9227	Zone must be populated with N, 1, 3, 4, 5, 6, 7, 8, ICD, ADC, DDU, or SCF when FormType field in the QualificationReportSummaryCreateRequest message is PE and Zone is provided.
9228	ContainerChargeContainerLevel must be populated with 3, 5, A, or M when FormType field in the QualificationReportSummaryCreateRequest message is PE.
9229	InOutCountyIndicator must be populated with N or I when FormType field in the QualificationReportSummaryCreateRequest message is PE.
9230	ProcessingCategory must be populated with LT, FL, MP, IR, NP, CM, NA, or NB when FormType field in the QualificationReportSummaryCreateRequest message is SM. (User Postage Statement ID: %%1).
9231	Zone must be populated with N when FormType FormType field in the QualificationReportSummaryCreateRequest message is SM and ProcessingCategory is LT, FL, MP, IR, or CM. (User Postage Statement ID: %%1).
9232	EntryDiscount must be populated with N, B, S, or D when FormType FormType field in the QualificationReportSummaryCreateRequest message is SM. (User Postage Statement ID: %%1).
9233	The Zone field in the ContainerDetailData block must be populated when the FormType field in the QualificationReportSummaryCreateRequest message is PE for Periodicals.
9235	The StandardFlatType field in the DocumentVersionDataWithPermit block must be populated when FormType field in the QualificationReportSummaryCreateRequest message is SM and ProcessingCategory is FL.
9236	A Qualification Report cannot have records with the IncludedInOtherDoc field values set to both O and L.
9237	QualificationReportDetailCreateRequest for a co-palletized mailing with the ContainerType set to F, O, or T can only be submitted when the FormType in the associated QualificationReportSummaryCreateRequest is FC or SM.
9238	PostageStatementMailingDate in the CreatePeriodicalStatement block must match the PostageStatementMailingDate in QualificationReportDetailCreateRequest message when it's populated for the same ContainerID for the specified MailingGroupID and CustomerGroupID.
9239	PostageStatementMailingDate in the PeriodicalStatement block must match the PostageStatementMailingDate in QualificationReportDetailCreateRequest message when it's populated for the same ContainerID for the specified MailingGroupID and CustomerGroupID.
9241	ProcessingCategory field in the ContainerInfoData block must be LT, FL, or CD when the FormType field in the QualificationReportSummaryCreateRequest message is FC and the MailXMLPresentationCategory field in the OpenMailingGroupRequest message is 'M'.
9242	The fields within the DocumentVersionDataWithPermit block for each unique VersionID must match for all QualificationReportDetailCreateRequest messages associated to the same Qualification Report. VersionID (%%1)
9243	The QualificationReportSummaryCreateRequest/QualificationReportDetailCreateRequest message is not supported in Mail.XML 10.0C.
9244	The maximum weight for a Priority Mail Regional Rate Box A mail piece is 15 lbs.
9245	The maximum weight for a Priority Mail Regional Rate Box B mail piece is 20 lbs.
9246	The PostageStatementMailingDate field in the ContainerInfoData block in the QualificationReportDetailCreateRequest message cannot span the price change date; within a job these dates must either be all before or all after %%1.
9247	The pieces associated to a ContainerDetailID in the Postage-, Periodical-, or ConsolidatedPeriodicalStatementCreateRequest cannot exceed the sum of TotalPieces for that ContainerDetailID in the Qualification Report (ContainerID %%1 ContainerDetailID %%2).
9248	A ContainerID in the MailPieceCreateRequest must exist in an accepted Qualification Report (Container ID %%1).
9249	A ContainerID in the Postage-, Periodical-, or ConsolidatedPeriodicalStatementCreateRequest must exist in an accepted Qualification Report (Container ID %%1).
9250	FormType field in the QualificationReportSummaryCreateRequest message must be FC or SM when the MailXMLPresentationCategory field in the OpenMailingGroupRequest message is populated with M.
9251	The number of QualificationReportDetailCreateRequest messages associated to a QualificationReportSummaryCreateRequest message cannot exceed the value populated in the TotalMessageCount field in the QualificationReportSummaryCreateRequest.

Copyright © 2014 USPS®. All Rights Reserved

Error Code	Error Message
9252	The PostageStatementMailingDate cannot be set to a date on or after the upcoming price change date - %%1
9254	When PreparedAsSM is True and FormType is PM, then ProcessingCategory must be FL, LT, or PF, and RateCategory must be S.
9255	For MLOCR mailings, the rate category must be one of E, H, L3, L4, N, or S for Flats or one of E, H, L1, L2, L3, L4, N, or S for Letters.
9256	The container status cannot be updated to C or D when the container is paid for on a Finalized Postage Statement (CTR ID %%1).
9257	The IMB block must be populated in the MailPieceBlock of the MailPieceCreateRequest message.
9258	The OriginalContainerLinkageCreateRequest message cannot be included in a mailing when the IncludedInOtherDoc field in the ContainerInfoData block of the QualificationReportDetailCreateRequest message is populated with O or I.
9259	The Zone field must be populated with LC, ADC, SCF, DDU, or N when the AcceptMisshipped field is set to Y and the eInductionIndicator is set to Y.
9269	AccountNumber must be an active account in the *PostalOne!* and CAPS systems when it is provided in the PermitPublicationData block of the PeriodicalStatementCreateRequest or ConsolidatedPeriodicalStatementCreateRequest.
9272	AccountNumber must be an active account in the *PostalOne!* and CAPS systems when it is provided in the PermitHolderData block of the PostageStatementCreateRequest message.
9276	The ProcessingCategory field must be populated with LT or FL when the Content field in the MailCharacteristic block is populated with RT.
9277	The FormType must be populated with FC, when the RateType is set to V .
9278	The SinglePieceWeight field must be {1} ounces or less when the ProcessingCategory is set to LT and RateType is set to V.
9278	The SinglePieceWeight field must be {1} ounces or less when the ProcessingCategory is set to LT and RateType is set to V.
9279	The PermitType in the PermitHolderData block must be set to PI, OI, MT, OM, or PC when the RateType is set to V.
9280	The PermitType in the PermitHolderForAPData block must be set to PI or OI when the RateType is set to V.
9282	PermitType in the PermitHolderData block must be populated with PI, OI, or PC when the FormType is set to FC, ProcessingCategory is set to PF, and PriceType is set to CommercialPlus.
9283	PermitType in the PermitHolderData block must be populated with PC, PI, OI, or MT when the FormType is set to FC, ProcessingCategory is set to PF, and PriceType is set to Commercial.
9289	AccountNumber <{1}> within the PermitHolderData block must be active.
9291	AccountNumber <{1}> within the PermitHolderData block must be active.
9298	A ContainerDetailID field submitted in the MailPieceUpdateRequest message must match a ContainerDetailID field submitted in the associated QualificationReportDetailCreateRequestMessage.
9299	For Seamless processing, the ContainerBarcode field in the ContainerInfoData block must contain exactly 21 characters when the corresponding ContainerType in the ContainerInfoData block is P, H, A, G, D, R, C, Z, B, U, W, or AB.
9300	For Seamless processing, the ContainerBarcode field in the ContainerInfoData block must begin with 99M when the corresponding ContainerType in the ContainerInfoData block is P, H, A, G, D, R, C, Z, B, U, W, or AB.
9301	For Seamless processing, ContainerBarcode must be populated with 24 characters when the ContainerType in the ContainerInfoData block is populated with S, 1, 2, 3, 4, 5, E, F, O, or T.
9302	For Seamless processing, the ContainerBarcode field in the ContainerInfoData block must be unique within the mailing group and amongst all containers with container types associated to physical handling units finalized within the last 45 days of the PostageStatementMailingDate.
9303	For Seamless processing, the EntryLocaleKey must be populated with a 6-digit alphanumeric value that does not contain ORIGIN.
9305	For Seamless processing, the ContainerBarcode field in the ContainerInfoData block must be unique within the mailing group and amongst all containers with container types associated to physical pallets finalized within the last 45 days of the PostageStatementMailingDate.
9308	The OpenMailingGroupCreateRequest message is no longer accepted for Mail.XML version 7.0C or 8.0B after %SubmitDateCutoff%.
9309	The ProcessingCategory must be populated with LT, FL, MP, or IR when the FormType is SM, RateCategory is A or A1, and the SimplifiedAddressIndicatorType is set to M = Mixed, R = Residential-

Copyright © 2014 USPS®. All Rights Reserved

Error Code	Error Message
	only, or B = Business-only.
9311	Mail.XML version {1} may not be submitted before {2}.
9314	Mail.XML version {1} may not be submitted with PostageStatementMailingDate before {2}.
9315	The PermitType field in the PermitHolderData block must be populated with PI or OI when FormType is set to PM, FC, SM, BP, PP, or ML and the Fee is set to PP.
9316	The FormType is set to an invalid value, when the Fee field in the DocumentVersionData block is populated with PP, the FormType must be set to PM, FC, SM, BP, PP, or ML.
9317	The FormType is set to an invalid value, when the Fee field in the DocumentVersionData block is populated with PP, the FormType must be set to PM, FC, SM, BP, PP, or ML.
9318	The FormType is set to an invalid value, when the Content field in the MailCharacteristic block is set to MI the FormType in the PostageStatementCreateRequest message must be set to FC or SM.
9319	The FormType field is set to an invalid value, when the ServiceCode field in the ExtraServiceSummaryData block is set to DCD the FormType must be set to FC or PM.
9320	The ProcessingCategory is set to an invalid value, when the FormType is set to FC, the PriceType is set to Commercial or CommercialPlus, and the ServiceCode is set to DCD, the ProcessingCategory must be set to PF.
9321	The PriceType is set to an invalid value, when the FormType is set to FC, the ProcessingCategory is set to PF, and the ServiceCode is set to DCD, the PriceType must be set to Commercial or CommercialPlus.
9322	The ProcessingCategory is set to an invalid value, when the FormType is set to PM, the PriceType is set to Commercial or CommercialPlus, and the ServiceCode is set to DCD, the ProcessingCategory must be set to PF.
9323	The PriceType is set to an invalid value, when the FormType is set to PM, the ProcessingCategory is set to PF, and the ServiceCode is set to DCD, the PriceType must be set to Commercial or CommercialPlus.
9324	PermitType is set to an invalid value, when the ServiceCode is set to DCD the PermitType must be set to PI or OI.
9325	The IMpb field must be populated in the QualificationReportDetailCreateRequest message when the ServiceCode field is populated with DCD in the PostageStatementCreateRequest message.
9326	PriceType must be populated with commercial, commercialplus, or retail.
9327	The PostageStatementCreateRequest message may only be submitted with either ExtraServiceData blocks or ExtraServiceSummaryData blocks, but not both.
9328	The SinglePieceWeight must be less than or equal to 25lbs when the FormType is set to PM and the RateType is set to E4.
9333	For eInduction processing, the IMBarcode must contain exactly 21 characters when the corresponding container type is P, H, A, G, D, R, C, Z, or AB.
9334	For eInduction processing, the IMBarcode field in the ContainerInfoData block must begin with 99M when the corresponding container type is P, H, A, G, D, R, C, Z, or AB.
9335	For eInduction processing, the IMBarcode for IMcb(s)/pallets must be unique within the mailing group and amongst all containers associated to the SubmittingParty CRID that were finalized within the last 45 days.
9338	PermitType in the PermitHolderForAPData block must be populated with PI or OI when the FormType is set to FC, ProcessingCategory is set to PF, and PriceType is set to Commercial.
9339	When the CRID is eligible for Seamless and the ContainerType is M or L, the logical container must be referenced by a physical sibling with the SiblingContainerID populated.
9342	The Process Category must be populated with LT or CD, when the RateType is set to V .
9343	The MID6, MID9, or CRID field in the MailOwnerData block and MID6, MID9, or CRID field in the MailingAgentData block are required when the AccountNumber field is populated.
9344	The MID6, MID9, or CRID field in the PublisherData block and MID6, MID9, or CRID field in the MailingAgentData block are required when the AccountNumber field is populated.
9346	For Seamless Acceptance processing, all piece data must be submitted before submission of the PostageStatementCreateRequest, PeriodicalStatementCreateRequest, or ConsolidatedPeriodicalStatementCreateRequest.
9347	The ProcessingCategory must be populated with LT, FL, MP, or IR when the FormType is SM, RateCategory is A or A1, and the NumberOfPiecesSimplifiedAddress is greater than zero.
9367	The AccountNumber field in the PermitPublicationData block of the PermitHolderData block must be populated when the AccountNumber field is populated in MailingGroupData block of the OpenMailingGroupRequest message.
9368	The AccountNumber field in the PermitPublicationData block of the PublisherData block must be populated when the AccountNumber field is populated in MailingGroupData block of the

Copyright © 2014 USPS®. All Rights Reserved

Error Code	Error Message
	OpenMailingGroupRequest message.
9371	The IncludedInOtherDoc field, on an original file set, cannot include both I and O within the same message.
9372	The QualificationReportDetailCreateRequest message cannot include containers with both I and L provided in the same MailingGroupID.
9373	The QualificationReportDetailCreateRequest message cannot include containers with both I and O provided in the same MailingGroupID.
9376	The PermitNumber field in the PermitHolderData block must be approved for NSA with Sample Showcase contracts when the RateType field is set to S1, S2, S3, S4, S5, S6, or S7.
9379	The SinglePieceWeight must be 70 lbs. or less when the FormType is set to PS, RateType is set to P, and the RateCategory is set to S.
9380	The ServiceCode field can not be populated with both SC and SCE in the same PostageStatementCreateRequest message.
9381	The ServiceCode field can not be populated with both DC and DCE in the same PostageStatementCreateRequest message.
9384	The StatementID is a required field in the Container block.
9385	The ContainerID is a required field in the Container block.
9386	The StatementID is a required field in the Container block.
9387	The IncludedInOtherDoc field can not be set to O and NULL for containers on the same Postage Statement.
9388	The IncludedInOtherDoc field can not be set to I and NULL for containers on the same Postage Statement.
9389	The IncludedInOtherDoc field can not be set to L and NULL for containers on the same Postage Statement.
9393	The number of pallets in the ContainerManifestCreateRequest message, and all messages previously manifested, may not exceed the number of pallets on the Postage Statement.
9401	The submitter must be a Mail Service Provider when the MSPIndicator field is populated with Yes.
9402	The CRID of the Mail Service Provider must exist when the MSPIndicator is populated with Yes.
9407	The BypassSeamlessAcceptance field is a required field for the QualificationReportSummary block.
9408	The submitted StatementID does not exist.
9409	The ConsigneeContainerManifestID is a required field in the ContainerManifestUpdateRequest message.
9410	The ConsigneeContainerManifestID is a required field in the ContainerManifestCancelRequest message.
9411	The submitted ConsigneeContainerManifestID in the Container block does not exist.
9412	PermitType field in the PermitPublicationData block of the PermitHolderData contains an invalid value. PermitType of PC is only allowed for Parcel Select LightWeight.
9423	Mail.XML version {1} may not be submitted on or after {2}.
9424	RateType must be populated with D, M, S1, S2, S3, S4, S5, S6, or S7 when the FormType is PS.
9425	ProcessingCategory must be populated with MP, IR, or FL when the FormType is PS.
9426	ProcessingCategory must be populated with MP or IR when the FormType is PS and the RateType is D.
9427	ProcessingCategory must be populated with MP when the FormType is PS and the RateType is M.
9428	ProcessingCategory must be populated with FL when the FormType is PS and the RateType is populated with S1, S2, S3, S4, S5, S6, or S7 for Sample Showcase.
9429	RateCategory must be populated with G, K, N, P7, PI, S, TE, TK, TQ, TR, Z1, OR Z2 when the FormType is PS.
9430	SurchargeType must be populated with 2, N, or P when the FormType is PS.
9431	The PermitType field within the PermitHolderData block contains an invalid value; it must contain PC, MT, PI, OI or OM when Mobile Interactive Technology is claimed.
9433	ProcessingCategory must be populated with CD, LT or FL when the FormType is FC and Mobile Interactive Technology is claimed.
9434	ProcessingCategory must be populated with LT or FL when the FormType is SM and Mobile Interactive Technology is claimed.
9435	RateType must be populated with R or N when the FormType is SM and Mobile Interactive Technology is claimed.
9438	The AccountNumber in the OpenMailingGroupRequest cannot be populated when FormType in the QualificationReportSummaryCreateRequest is populated with PE and the ProcessingCategory in the QualificationReportDetailCreateRequest is not populated with FL or LT.
9439	The AccountNumber in the OpenMailingGroupRequest message cannot be populated when the FormType in the PeriodicalStatementCreateRequest or ConsolidatedPeriodicalStatementCreateRequest

Copyright © 2014 USPS®. All Rights Reserved

Error Code	Error Message
	message is populated with PE and the ProcessingCategory is not FL or LT.
9440	Mail.XML version {1} is not supported for PostageStatementMailingDate of {2} or later.
9442	The number of pallets in the ContainerManifestUpdateRequest message may not exceed the number of pallets on the Postage Statement.
9446	When the MixedMailFlag field is populated with Yes within the QualificationReportSummaryCreateRequest, the following fields must be populated accordingly within the OpenMailingGroupCreateRequest: PresentationCategory must be populated with P, MailAgreementType must be populated with E, and the LogicalPhysicalContainerIndicator must be populated with P.
9447	When the MixedMailFlag field is populated with Yes, then the ProcessingCategory field value in ConsolidatedPeriodicalStatementCreateRequest should be set to FL.
9448	For Mixed Mail, the RateType in the CreatePeriodicalStatementData block can only be populated with C, H, M, N, R, S, W, Y, or Z. (User Postage Statement ID: {1}).
9449	If the value of the MixedMailFlag is Yes then the value of the ProcessingCategory in the PeriodicalStatementCreateRequest should be set to FL .
9450	SurchargeType must be populated with N when FormType is SM and MixedMailFlag is Yes. (User Postage Statement ID: {1}).
9451	AdPercent and AdvertisingPercentage must not be blank for Mixed Mail. (User Postage Statement ID: {1}).
9453	Zone cannot be N when the InOutCountyIndicator is I for Periodical mail pieces within Mixed Mail. (User Postage Statement ID: {1}).
9454	Zone cannot be 1, 3, 4, 5, 6, 7, 8, or S when the InOutCountyIndicator is N. (User Postage Statement ID: {1}).
9455	The eInductionIndicator field within the ContainerInfoData block of the QualificationReportDetailCreateRequest message contains an invalid value; in a single job, all eInductionIndicator fields must be populated with the same value for all eInductionIndicator fields. The value provided was {}.
9456	If the MixedMailFlag in the QualificationReportSummaryCreateRequest is set to Yes, then the FormType must be SM.
9457	If the MixedMailFlag in the QualificationReportDetailCreateRequest is set to Yes, ContainerDetailID field must be populated and be unique within the mailing group.
9458	If the MixedMailFlag in the QualificationReportDetailCreateRequest is set to Yes, then the VersionID in the ContainerDetailData block must match the corresponding VersionID in the DocumentVersionDataWithPermit block.
9459	If the MixedMailFlag in the QualificationReportDetailCreateRequest is set to Yes then the value of the ProcessingCategory in the PostageStatementCreateRequest must be FL.
9460	If the InOutCountyIndicator is N then Zone must be populated with 1, 3, 4, 5, 6, 7, 8, or S for Mixed Mail.
9461	For Mixed Mail, Periodical mail pieces cannot contain the following Rate Categories: G, K, L5, L6, L7, or L8.
9462	For Mixed Mail, Periodical mail pieces cannot have an EntryDiscountType of A when the InOutCountyIndicator is N or an EntryDiscountType of D when the InOutCountyIndicator is I.
9463	For Mixed Mail, Standard mail pieces must contain one of the following Rate Categories: A, B, C, D, E, G, H, L3, or L4.
9464	For Mixed Mail, the InOutCountyIndicator must be N or I.
9465	For Mixed Mail, Periodical mail pieces must have ChargeableBundleLevel values of A, B, C, D, F, H, K, L, T, or U.
9466	Mixed Mail with a ChargeableBundleLevel value of A must only contain Periodical Flat mail pieces.
9468	If the MixedMailFlag is set to Yes and FormType value to SM, then the ContainerDetailID field must be populated.
9469	If the MixedMailFlag is set to Yes then the ContainerDetailID must correspond to the ContainerDetailID from the QualificationReportDetailCreateRequest.
9470	If the MixedMailFlag is set to Yes then the MachinableFlag must be Yes.
9471	If the MixedMailFlag is set to Yes then the BarcodeRate must be O.
9472	If the MixedMailFlag is set to Yes then the RateType must be N or R for the Standard Mail pieces.
9473	If the MixedMailFlag is set to Yes then the SortationLevel for the Periodical mail pieces must be one of the following: A, B, C, D, E, F, G, H, I, J, M, Q, R, S, T, U, V, W, X, Y, AB, AD, AE, AF, AG, or AH.
9474	If the MixedMailFlag is set to Yes then the SortationLevel must not be Z, AA, AC, or AJ.
9475	If the MixedMailFlag is set to Yes then the EnclosedBy and EnclosingIssueDate fields must be populated.
9476	If the MixedMailFlag is set to Yes then the acceptable values for ProcessingCategory for enclosures are

Copyright © 2014 USPS®. All Rights Reserved

Error Code	Error Message
	LT, CD, or FL.
9482	For Mixed Mail, Periodical mail pieces must have RateCategory values of A, B, D, E, H, L, L3, L4, or FB.
9483	If the MixedMailFlag is set to Yes then FormType the ContainerBundleReportCreateRequest and the BundleDetailCreateRequest must be SM
9484	The value provided for the MarketingOrFulfillment field was {1}; it must contain SampleLarge or SampleSmall when the Content field within the MailCharacteristic block is populated with PS = Product Sample, the ProcessingCategory is populated with MP = Machinable Parcels or IR = Irregular Parcels, and the RateCategory is populated with A = Saturation - ECR or D = Carrier Route.
9486	The MoveUpdateMethod is populated with an invalid value; it must contain 0, 1, 2, 4, 5, 6, 7, or 8 when populated.
9487	When the ServiceCode field within the ExtraServiceData block is populated with CBM the FormType field must be populated with FC, PM, SM, BP, ML, or PP, the PermitType must be populated with PI or OI, and the Piece PieceWeight must be identical for all pieces within the mailing.
9488	When the ServiceCode field within the ExtraServiceSummaryData block is populated with CBM the FormType field must be populated with FC, PM, SM, BP, ML, or PP, the PermitType must be populated with PI or OI, and the Piece PieceWeight must be identical for all pieces within the mailing.
9489	Certificate of Bulk Mailing is not supported for Critical Mail. When the ServiceCode field within the ExtraServiceData or ExtraServiceSummaryData block is populated with CBM and the FormType is populated with PM, the FlatRateIndicator field cannot be populated with C = Priority Mail Critical Mail - Letter, D = Priority Mail Critical Mail - Letter with Signature, or G = Priority Mail Critical Mail - Flat with Signature.
9490	TotalPieces field in the ExtraServiceData or ExtraServiceSummaryData block of the PostageStatementCreateRequest cannot be greater than the total pieces in the PostageStatementCreateRequest.
9491	When the ServiceCode field within the ExtraServiceData or ExtraServiceSummaryData is populated with COD, the FormType field must be populated with a FC or PM.
9492	The ProcessingCategory provided was {1}. The ProcessingCategory must be PF when the FormType is FC and the ServiceCode of COD is claimed.
9493	The PermitNumber provided must be tied to a CAPS account when the ServiceCode field within the ExtraServiceData or ExtraServiceSummaryData field is populated with COD.
9494	CollectAmount must be populated when the ServiceCode is {1}.
9495	POSTNET barcode is not eligible for Automation pricing.
9496	POSTNET barcode is not eligible for Automation pricing.
9498	When the Picture Permit Indicia is claimed as an incentive, there must be a corresponding Fee of Picture Permit Indicia for the same MailCharacteristic block.
9503	For Consolidated Periodicals claiming an incentive, the VersionID field in the DocumentVersionData block must be a unique value within the ConsolidatedPeriodicalCreateRequest message.
9504	For Mixed Mail, Periodical Mail cannot have piece weight greater than 22 ounces.
9505	Periodical statements within Mixed Mail cannot contain lines E1 thru E25.
9506	Periodical statements within Mixed Mail cannot contain lines E28, E30, E32, E34, E38, E40, E45, and E47.
9507	Periodical statements within Mixed Mail cannot contain lines E36, E42, and E49.
9508	Periodical statements within Mixed Mail cannot contain line E51.
9517	The Regional Ground product is no longer supported. The RateType provided was {1}; it cannot contain M = Parcel Select Regional Ground when the FormType is PS = Parcel Select.
9518	The Parcel Post product is no longer supported. The RateType provided was {1}; it cannot contain P = Parcel Post when the FormType is PP = Parcel Post.
9519	Content of PS = Product Sample may not be submitted when the ProcessingCategory is populated with MP = Machinable Parcels or IR = Irregular Parcels, the RateCategory is populated with A = Saturation - ECR or D = Carrier Route, and the ContainerID in the PostageStatementLineItemData block is not populated.
9520	Update the PostOfficeOfMailingZip in the OpenMailingGroupRequest or thePermitZip4 in the PostageStatementCreateRequest, PeriodicalStatementCreateRequest, or ConsolidatedPeriodicalStatementCreateRequest to use either all test finance numbers or all non-test finance numbers across the mailing.
9522	The DMLType value provided was {1}; it cannot contain A or B when the Content field within the MailCharacteristic block is populated with PS = Product Sample and the RateCategory is populated with D = Carrier Route.

Copyright © 2014 USPS®. All Rights Reserved

Error Code	Error Message
9523	For postage statement processing, only one line between lines H1 - H4 of PS Form 3602-R/N may be submitted on a single postage statement when the SinglePieceWeight in the PostageStatementCreateRequest is not identical. Combinations of lines H1 and H3 or H2 and H4 may be submitted on a single postage statement if the SinglePieceWeight in the PostageStatementCreateRequest is identical.
9524	For Postage Statement processing, Form 3602R/N - Section H for Product Samples must be submitted on a separate Postage Statement.
9525	The BarcodeRate, EntryDiscount, HeavyLetter, PreparedAsSM, SurchargeType, and TotalPieces fields within the PostageStatementLineItemData block must be populated when the ChargeableContainerLevel field is not populated in the PostageStatementLineItemData block of the PostageStatementCreateRequest message.
9526	When a mailing is not a Simple Mailing, the MID6 and SerialNumber9 or MID9 and SerialNumber6 element of the IMB block of the MailPieceCreateRequest message may not be duplicated {1} or more times. The barcode that exceeded the configurable threshold is {2}.
9532	For Seamless processing, the DeliveryPointZip within the MailPieceBlock block of the MailPieceCreateRequest must be populated with an 11 digit value.
9536	For Seamless processing, the IMb block of the MailPieceBlock of the MailPieceBlockGroup within the MailPieceCreateRequest must be provided.
9540	For Seamless processing, the TotalPieces field must be populated when the LogicalPhysicalIndicator within the OpenMailingGroupCreateRequest is populated with P = Physical Container.
9546	For Seamless processing, all QualificationReport messages must be successfully submitted and accepted prior to the PostageStatementCreateRequest message being submitted.
9548	For Seamless or Seamless Parallel processing, all QualificationReport messages must be successfully submitted and accepted prior to the PeriodicalStatementCreateRequest or ConsolidatedPeriodicalStatementCreateRequest message being submitted.
9550	When multiple are provided, the IMBarcode, IMpb, and ContainerBarcode field values must be the same value, within the SummaryRecordUpdate block, of the ContainerUpdateRequest message.
9553	For Seamless processing, the CSAID field within the ContainerInfoData block must be populated with a 10 digit numeric value between 1000000000 and 9999999999.
9555	For Seamless processing, at least one QualificationReportDetailCreateRequest ContainerInfoData block must have a ContainerType of L or M when the LogicalPhysicalIndicator in the OpenMailingGroupRequest is L - Logical and the MailXMLPresentationCategory within the OpenMailingGroupRequest is populated with P - Conventional Presort.
9567	A CloseMailingGroupRequest may not be submitted when the MailingGroupID field in the CloseMailingGroupRequest has an associated Postage Statement with a status of FIN = Finalized, UPD = USPS Processing Due, or FPP = Finalized Pending Payment.
9577	When multiple are provided, the IMBarcode, IMpb, and ContainerBarcode field values must be the same value, within the SummaryRecordUpdate block, of the ContainerUpdateRequest message.
9580	The IMcb is a required field and must be populated for each Container block.
9581	The IMcb field must be populated with 21 characters.
9582	The IMcb field must begin with 99M when populated.
9583	The IMcb field for ContainerID {1} has been previously submitted in another ContainerManifestCreateRequest for the same MailingGroup and Submitting Party within the last 45 days.
9584	The IMcb field for ContainerID {1} has been previously submitted in another ContainerManifestCreateRequest message within the last 45 days.
9585	The EntryLocaleKey field is a required field and must be 6 digits in length for each Container block.
9586	The combination of IMcb {1} and StatementID {2} has been previously submitted in another ContainerManifestCreateRequest message.
9587	The IMcb for StatementID {1} has already been marked for eInduction.
9589	The user is not associated to the location CRID provided in the original eDoc. Only the eInductionIndicator and ContainerStatus for ContainerID {%1} can be updated using the ContainerUpdateRequest.
9590	The SiblingContainerID field is required when the SupplementalPhysicalContainerID field is populated, when the ContainerType in the ContainerInfoData block is populated with P, H, A, G, D, R, C, or Z.
9592	The SupplementalPhysicalContainerID field must be populated with a ContainerID that references a container with a ContainerType of M = Logical Pallet(MLOCR), P = Pallet, Z = User Pallet, H = EIRS 61 - Hamper, Large Canvas, A = EIRS 61P - Hamper, Large Plastic, G = EIRS 66 - General Purpose Mail Container w/Gate, D = EIRS 68 - Eastern Region Mail Container w/Web Door, R = EIRS 84 - Wire Container Rigid, C = EIRS 84C - Collapsible Wire Container, L = Logical Tray (MLOCR) or F = Flat Tub.

Copyright © 2014 USPS®. All Rights Reserved

Error Code	Error Message
9595	The MailCharacteristic provided was {1}. There are no qualifying pieces for the incentive claimed in the postage statement. The discount will not be applied.
9597	The eInducitonIndicator cannot be updated from Yes to No for a finalized StatementID {1}.
9598	ProcessingCategory in the PostageStatementLineItemData block of PostageStatementCreateRequest message, must be the same throughout the entire mailing, when FormType is not FC = First Class, ProcessingCategory is not a combination of CD = Cards and LT = Letters, and PriceType is non-identical.
9599	The ProcessingCategory in the CreatePeriodicalStatement block, within the PeriodicalStatementCreateRequest message, must be consistent for a single MailingGroupID.
9600	ProcessingCategory in the PeriodicalLineItemData block must be the same throughout the ConsolidatedPeriodicalStatementCreateRequest message.
9601	The Containers field, within the PeriodicalLineItemData block of the PeriodicalStatementCreateRequest message cannot exceed the total number of Sibling Containers, when the associated ContainerID is a Logical container.
9602	For mailings with logical pallets or trays, sibling container information is required, when the FullServiceParticipationIndicator is populated with F = Full-Service Option or M = Mixed (Basic and Full Mixed) and the MailXMLPresentationCategory is populated with P = Conventional Presort.
9607	TotalWeightOfContainer field in the ContainerInfoData block of the QualificationReportDetailCreateRequest message must be populated with a numeric value, less than or equal to 200 lbs., when the ContainerType is AB = Air Box.
9608	TotalWeightOfContainer field in the SummaryRecordUpdate block of the ContainerUpdateRequest message must be populated with a numeric value, less than or equal to 200 lbs., when the ContainerType is AB = Air Box.
9612	A ContainerID with a logical ContainerType of M Logical Pallet (MLOCR) or L = Logical Tray (MLOCR) in the ContainerInfoData block must be referenced by a SiblingContainerID with a physical ContainerType when the FormType is PE = Periodical in the QualificationReportSummary block of the QualificationReportSummaryCreateRequest message.
9613	A ContainerID with a logical ContainerType of V = Virtual Sack in the ContainerInfoData block must be referenced by a SiblingContainerID with a physical ContainerType when the FormType is PE = Periodical in the QualificationReportSummary block of the QualificationReportSummaryCreateRequest message.
9614	The Containers field, within the PeriodicalLineItemData block of the ConsolidatedPeriodicalStatementCreateRequest message cannot exceed the total number of Sibling Containers, when the associated ContainerID is a Logical container.
9615	The sum of all Containers in the PeriodicalLineItemData block, within the PeriodicalStatementCreateRequest message, cannot be greater than the number of Containers in the ContainerInfoData block, of the QualificationReportDetailCreateRequest message.
9617	The sum of all Containers in the PeriodicalLineItemData block, within the ConsolidatedPeriodicalStatementCreateRequest message, cannot be greater than the number of Containers in the ContainerInfoData block, of the QualificationReportDetailCreateRequest message
9618	The ContainerID in the BundleDetail block and VersionID in the BundleVersion block of the BundleCreateRequest message must match a ContainerID in the ContainerInfoData block and VersionID in the ContainerDetailData block of the QualificationReportDetailCreateRequest message when the SupplementalPhysicalContainerID is populated in the ContainerInfoData block of the QualificationReportDetailCreateRequest message, the FormType is FC = First Class or SM = Standard Mail in the QualificationReportSummary block, the ProcessingCategory is FL = Flats in the QualificationReport > ContainerInfoData and the ContainerType is F = Flat Tub or L = Logical Tray (MLOCR) in the ContainerInfoData block of the QualificationReportDetailCreateRequest.
9619	When the SupplementalPhysicalContainerID field is populated for a ContainerType of L = Logical Tray (MLOCR) in the ContainerInfoData block the ContainerType being referenced must also be L = Logical Tray (MLOCR) when the FormType is FC = First Class or SM = Standard Mail and the ProcessingCategory is FL = Flats.
9620	When the SupplementalPhysicalContainerID field is populated for a ContainerType of F = Flat Tub in the ContainerInfoData block the ContainerType being referenced must also be F = Flat Tub when the FormType is FC = First Class or SM = Standard Mail and the ProcessingCategory is FL = Flats.
9621	For simple Full-Service mailings the MailPieceCreateRequest > MailPieceBlockGroup > MailPieceBlock > ServiceLevelIndicator must be populated with F=Full-Service.
9624	ContainerID and ContainerDetailID are required fields in the PostageStatementLineItemData or PeriodicalLineItemData, blocks when the FullServiceParticiaptionIndicator is populated with F = Full-Service or M = Mixed-Service.
9625	ContainerID and ContainerDetailID are required fields in the PostageStatementLineItemData or

Copyright © 2014 USPS®. All Rights Reserved

Error Code	Error Message
	PeriodicalLineItemData, blocks when the ServiceLevelIndicator is B = Basic Service and the eInductionIndicator is Yes.
9628	VersionID is a required field in the PostageStatementLineItemData block when the FullServiceParticiaptionIndicator is populated with F = Full-Service or M = Mixed-Service.
9629	VersionID is a required field in the PostageStatementLineItemData block when the ServiceLevelIndicator is B = Basic Service and the eInductionIndicator is Yes.
9630	When the ServiceCode field within the ExtraServiceData or ExtraServiceSummaryData is populated with CM, the FormType field must be populated with a FC, PM, BP, or ML.
9631	The IncludedInOtherDoc field cannot be populated when the SiblingContainerID field is populated within the same ContainerInfoData block of the QualificationReportDetailCreateRequest message. (Container ID: {1})
9632	A unique ContainerDetailID can only be submitted on one postage statement across the mailing group and must account for all associated mailpieces. (ContainerDetailID: {1}).
9633	A unique ContainerDetailID can only be submitted on one postage statement across the mailing group and must account for all associated mailpieces. (ContainerDetailID: {1}).
9634	A unique ContainerDetailID can only be submitted on one postage statement across the mailing group and must account for all associated mailpieces. (ContainerDetailID: {1}).
9635	The VersionID, ContainerID, ContainerDetailID submitted in the PostageStatementCreateRequest must exist in the QualificationReportDetailCreateRequest when the FullServiceParticipationIndicator is populated with F = Full-Service or M = Mixed-Service.
9636	The RateCategory provided was {1}. When claiming a RateCategory of S = Single Piece for First Class Residual pieces, you must include Automation or Presort pieces.
9637	ContainerID and ContainerDetailID submitted in the PeriodicalStatementCreateRequest must exist in the QualificationReportDetailCreateRequest when the FullServiceParticipationIndicator is populated with F = Full-Service or M = Mixed-Service.
9639	ContainerID and ContainerDetailID submitted in the ConsolidatedPeriodicalStatementCreateRequest must exist in the QualificationReportDetailCreateRequest when the FullServiceParticipationIndicator is populated with F = Full-Service or M = Mixed-Service.
9642	The MailCharacteristic provided was {1}. When claiming an incentive the piece level data must be submitted prior to postage statement generation. All MailPieceCreateRequests must be submitted before PostageStatementCreateRequests when an incentive is claimed.
9643	A ContainerDetailID can only identify one Mail Owner. ContainerDetailID {1} has been identified as having more than one Mail Owner.
9647	ContainerID {1} contains Residual Letters of both less than or equal to and greater than 1 ounce.
9648	VersionID, ContainerID, ContainerDetailID submitted in the PostageStatementCreateRequest must exist in the QualificationReportDetailCreateRequest when the ServiceLevelIndicator is populated with B = Basic and the eInductionIndicator is populated with Yes.
9649	ContainerID and ContainerDetailID submitted in the PeriodicalStatementCreateRequest must exist in the QualificationReportDetailCreateRequest when the ServiceLevelIndicator is populated with B = Basic and the eInductionIndicator is populated with Yes.
9650	ContainerID and ContainerDetailID submitted in the ConsolidatedPeriodicalStatementCreateRequest must exist in the QualificationReportDetailCreateRequest when the ServiceLevelIndicator is populated with B = Basic and the eInductionIndicator is populated with Yes.
9653	ContainerDetailID field in the MailPieceCreateRequest is required when the ServiceLevelIndicator is populated with B = Basic Service and eInductionIndicator populated with Yes.
9654	The number of pieces associated to a ContainerDetailID in the PostageStatementCreateRequest must match the number of pieces associated to the ContainerDetailID in the QualificationReportDetailCreateRequest
9655	The number of pieces associated to a ContainerDetailID in the PeriodicalStatementCreateRequest must match the number of pieces associated to the ContainerDetailID in the QualificationReportDetailCreateRequest.
9656	The number of pieces associated to a ContainerDetailID in the ConsolidatedPeriodicalStatementCreateRequest must match the number of pieces associated to the ContainerDetailID in the QualificationReportDetailCreateRequest.
9657	For Full Service processing, pieces with a RateCategory of E = 5 Digit Barcode, H = 3 Digit Barcode, L = Basic Barcode, L1 = AADC BC, L2 = MxAAD BC, L3 = ADC BC L4 = MxADC BC, or N = Presort must reside in a QualificationReportDetailCreateRequest > ContainerInfoData > ContainerType of 1' Tray, T = 2' Tray, E = EMM Tray, L = Logical Tray, or F = Flat Tub where all pieces include a 31 digit IMb.

Copyright © 2014 USPS®. All Rights Reserved

Error Code	Error Message
9661	The MaildatJobID or IMcb submitted in the ContainerUpdateRequest must be unique to a single Mail.dat job submission when updating the ContainerUpdateRequest > SummaryRecordUpdate > ContainerStatus to R = Ready to Pay.
9667	The Containers field, within the PeriodicalLineItemData block of the PeriodicalStatementCreateRequest message cannot exceed the total number of Sibling Containers plus the Original Container, when the associated ContainerID is a Physical container.
9668	The Containers field, within the PeriodicalLineItemData block of the ConsolidatedPeriodicalStatementCreateRequest message cannot exceed the total number of Sibling Containers plus the Original Container, when the associated ContainerID is a Physical container.

8.2 Warning Codes and Messages

Code	Warning Message
8005	More than {1} failures for Info code: {2}
8357	When ContainerStatus is T, the ContainerUpdate message can only update the Transportation Update fields listed in the Mail.XML Technical Specification. (Container ID: {1})
8359	Postage cancellation will occur when the ContainerStatus is C or D and the Container Status from the original Mail.dat job is R and the postage statement status from the original Mail.dat job is UPD. (Container ID: {1})
8392	ScheduledInductionDateTime is required when the ConsigneeApptID in the ContainerInfoData block is populated and FullServiceParticipationIndicator in the MailingGroupData block is F or M. (Container ID: {1}).
8406	ServiceTypeCode field is required when the MailPieceBlock is provided and the MailClass in the IMB block is not populated.
8407	MailClass field is required when the MailPieceBlock is provided and the ServiceTypeCode in the IMB block is not populated.
8413	At least one of CRID, MailerID6, MailerID9, PermitNumber or PublicationNumber in the QualificationReportPreparer block must be populated when the FullServiceParticipationIndicator in the OpenMailingCreateRequest is F or M
8414	At least one of CRID, MailOwnerMID6, MailOwnerMID9, PermitNumber, or PublicationNumber in the MailOwner block of the MailPieceCreateRequest message must be populated when the MailPieceBlock is populated and the MailPieceBlock ServiceLevelIndicator is F.
8800	An unknown error occurred during response generation.
8801	The XML Version must be the same for all messages in a mailing group.
8852	The number of In County Copies does not match between the Piece and Pound charge lines for User Postage Stmt {1}. Piece: {2}, Pound: {3}.
8853	The number of Out County Copies does not match between the Piece and Pound charge lines for User Postage Stmt {1}. Piece: {2}, Pound: {3}
8855	The sum of InCounty- , OutsideCounty-, and PiecesExcludingAddressedSupplementPieces must equal the pieces in the Periodical message or the associated statement of the Consolidated Periodical message. (User Postage Statement ID: {1}, Sums: {2} , {3})
8872	The PDRMailPieceBlock block and the PDRRangePieceBlock block are not supported.
8951	The ScheduledInductionDateTime field can only be updated when the ContainerStatus in the SummaryRecordUpdate block of the ContainerUpdateRequest message is populated with T. (Container ID: {1})
8960	The ScheduledInductionDateTime field in the ContainerInfoData block must be within 30 days of the past or present of the PostageStatementMailingDate.
8962	The EntryLocaleKey field in the ContainerInfoData block is required unless the EntryFacilityType field in the ContainerInfoData block is populated with O and no appointment is provided.
8963	The ScheduledInductionDateTime field in the SummaryRecordUpdate block of the ContainerUpdateRequest message must be within 30 days of PostageStatementMailingDate field in the QualificationReportDetailCreateRequest message for a Full-Service mailing.
9102	The ScheduledInductionDateTime field in the SummaryRecordUpdate block of the ContainerUpdateRequest

Copyright © 2014 USPS®. All Rights Reserved

Code	Warning Message
	message must be within 30 days of PostageStatementMailingDate field in the QualificationReportDetailCreateRequest message for a Full-Service mailing.
9022	The EntryLocaleKey in the ContainerInfoData block must be populated with alphanumeric characters and cannot be populated with ORIGIN when the EntryPointFacilityType in the ContainerInfoData block is O and the mailing is Full-Service or Mixed Service.
9049	The AdPercent field in the DocumentVersionData block does not match the previously stored advertising percentage for VersionID ({1}).
9057	The PieceWeight field in the DocumentVersionData block does not match the previously stored edition weight for VersionID ({1})
9061	ScheduledInductionDateTime field in the ContainerInfoData block is required when USPSPickUp field in the ContainerInfoData block is No and the FullServiceParticipationIndicator in the OpenMailingGroupRequest message is F or M.
9184	For eInduction processing, the ContainerBarcode field in the ContainerInfoData block for IMcb(s)/pallets must be unique within the mailing group and amongst all containers finalized within the last 45 days. Container Barcode: {1}, Container ID: {2}.
9260	According to the Seamless Acceptance Site, the statement submitted is not eligible for Auto-Finalization. Your statement will not be Auto-Finalized.
9264	The CAPS Credit Account balance associated to PermitNumber <{1}> and PermitZIP+4 <{2}> provided in the PermitHolderData block will be negative after Postage Statement processing.
9273	The eInductionIndicator must be set to N when the ParentContainerID is not populated and ContainerType is set to S, V, 1, 2, 3, 4, 5, O, T, E, F, or L.
9284	According to the Seamless Acceptance Site, the processing category provided is not eligible for Auto-Finalization. Your statement will not be Auto-Finalized.
9287	According to the Seamless Acceptance Site, the Full Service Participation value provided is not eligible for Auto-Finalization. Your statement will not be Auto-Finalized.
9288	The balance associated to the PermitNumber <{1}> and PermitZIP+4 <{2}> provided in the PermitHolderData block will be negative after Postage Statement processing.
9290	The balance associated to AccountNumber <{1}> provided within the PermitHolderData block will be negative after Postage Statement processing.
9292	The balance associated to AccountNumber <{1}> provided within the PermitPublicationData block will be negative after Postage Statement processing.
9293	AccountNumber <{1}> within the PermitPublicationData block must be active.
9294	The balance associated to AccountNumber <{1}> provided within the PermitPublicationData block will be negative after Postage Statement processing.
9295	The balance associated to the PublicationNumber <{1}> provided within the PermitPublicationData block will be negative after Postage Statement processing.
9296	The balance associated to PublicationNumber <{1}> provided within the PermitPublicationData block will be negative after Postage Statement processing.
9304	For Seamless processing and Postage Statement auto-finalization, the eInductionIndicator must be set to Yes when the ContainerType is set to P, S, 1, 2, 3, 4, 5, F, O, T, E, B, U, W, H, A, G, D, R, C, Z, or AB.
9336	For eInduction processing, the IMBarcode for IMcb(s)/pallets must be unique within the mailing group and amongst all containers finalized within the last 45 days.
9341	For Standard Mail MLOCR mailings, the rate category must be one of E, H, L1, L2, L7, L8 or S for Letters.
9348	A ContainerDetailID field submitted in the MailPieceUpdateRequest message must match a ContainerDetailID field submitted in the associated QualificationReportDetailCreateRequestMessage.

Copyright © 2014 USPS®. All Rights Reserved

Code	Warning Message
9349	For Seamless Parallel Run processing, the ContainerBarcode field in the ContainerInfoData block must contain exactly 21 characters when the corresponding ContainerType in the ContainerInfoData block is P, H, A, G, D, R, C, Z, B, U, W, or AB.
9350	For Seamless Parallel Run processing, the ContainerBarcode field in the ContainerInfoData block must begin with 99M when the corresponding ContainerType in the ContainerInfoData block is P, H, A, G, D, R, C, Z, B, U, W, or AB.
9351	For Seamless Parallel Run processing, the ContainerBarcode field in the ContainerInfoData block must be unique within the mailing group and amongst all containers with container types associated to physical pallets finalized within the last 45 days of the PostageStatementMailingDate.
9352	For Seamless Parallel Run processing, ContainerBarcode must be populated with 24 characters when the ContainerType in the ContainerInfoData block is populated with S, 1, 2, 3, 4, 5, E, F, O, or T.
9353	For Seamless Parallel Run processing, the ContainerBarcode field in the ContainerInfoData block must be unique within the mailing group and amongst all containers with container types associated to physical handling units finalized within the last 45 days of the PostageStatementMailingDate.
9354	When the CRID is eligible for Seamless Parallel Run and the ContainerType is M or L, the logical container must be referenced by a physical sibling with the SiblingContainerID populated.
9355	For Seamless Parallel Run, the EntryLocaleKey must be populated with a 6-digit alphanumeric value that does not contain ORIGIN.
9356	A ContainerDetailID field submitted in the MailPieceCreateRequest message must match a ContainerDetailID field submitted in the associated QualificationReportDetailCreateRequest message. (ContainerDetailID {1} missing for ContainerID {2}).
9413	The CRID field within the MailingAgentData block must be populated when an Incentive is claimed.
9415	The MailOwnerCRID field within the ContainerInfoData block of the QualificationReportDetailCreateRequest must be populated when an incentive is claimed.
9442	The number of pallets in the ContainerManifestUpdateRequest message may not exceed the number of pallets on the Postage Statement.
9445	For Seamless Parallel Run processing, the eInductionIndicator for ContainerType P, S, 1, 2, 3, 4, 5, F, O, T, E, B, U, W, H, A, G, D, R, C, Z, or AB must be set to Yes.
9477	The balance associated to the PermitNumber {1} and PermitZIP+4 {2} provided in the PermitHolderData block will be negative after Postage Statement processing.
9497	The MailCharacteristic provided was {1}. The Incentive claimed is not active. The discount will not be applied.
9499	The MailCharacteristic provided was {1}. The identified mailing roles provided are not enrolled for the incentive claimed. The discount will not be applied.
9500	The MailCharacteristic provided was {1}. The incentive claimed does not yield the greatest discount. The discount will not be applied.
9501	A postage statement contains mail piece units both with mobile barcode and without mobile barcode. The postage statement must contain mail piece units all that claim mobile barcode. The {1} incentive will not be applied.
9527	The STID portion of the Intelligent Mail Barcode populated in the ServiceTypeCode field of the IMB block in the MailPieceCreateRequest must match the FormType provided in the QualificationReportSummaryCreateRequest message.
9528	The balance associated to the PermitNumber {1} and PermitZIP+4 {2} provided will cause a negative balance unless funds are added to PermitNumber {1} by the PostageStatementMailingDate. The Postage Statement falls within the allowable negative balance threshold after postage statement processing and will be Auto-Finalized.
9529	The balance associated to the PublicationNumber {1} and PermitZIP+4 {2} provided will cause a negative balance unless funds are added to PublicationNumber {1} by the PostageStatementMailingDate. The Postage Statement falls within the allowable negative balance threshold after postage statement processing and will be Auto-Finalized.
9530	The balance associated to the PermitNumber {1} and PermitZIP+4 {2} provided will cause a negative balance unless funds are added to PermitNumber {1} by the PostageStatementMailingDate. The Postage Statement does not fall within the allowable negative balance threshold after postage statement processing and will not be Auto-Finalized unless funds are added.
9531	The balance associated to the PublicationNumber {1} provided will cause a negative balance unless funds are

Copyright © 2014 USPS®. All Rights Reserved

Code	Warning Message
	added to PublicationNumber {1} by the PostageStatementMailingDate. The Postage Statement does not fall within the allowable negative balance threshold after postage statement processing and will not be Auto-Finalized unless funds are added.
9533	For Seamless Parallel Run processing, the DeliveryPointZip within the MailPieceBlock block of the MailPieceCreateRequest must be populated with an 11 digit value for pieces claiming Full Service.
9537	For Seamless Parallel Run processing, the IMb block of the MailPieceBlock of the MailPieceBlockGroup within the MailPieceCreateRequest must be provided.
9541	For Seamless Parallel Run processing, the TotalPieces field must be populated when the LogicalPhysicalIndicator within the OpenMailingGroupCreateRequest is populated with P = Physical Container.
9542	For Seamless processing, the ScheduledShipDateTime is required in the ContainerInfoData block of the QualificationReportDetailCreateRequest message when the EntryPointFacilityType field is populated with O = Origin and the USPSPickUp field is populated with Y = Yes in the ContainerInfoData block.
9543	For Seamless Parallel Run processing, the ScheduledShipDateTime is required in the ContainerInfoData block of the QualificationReportDetailCreateRequest message when the EntryPointFacilityType field is populated with O = Origin and the USPSPickUp field is populated with Y = Yes in the ContainerInfoData block.
9547	For Seamless Parallel Run processing, all QualificationReport messages must be successfully submitted and accepted prior to the PostageStatementCreateRequest message being submitted.
9554	For Seamless Parallel Run processing, the CSAID field within the ContainerInfoData block must be populated with a 10 digit numeric value between 1000000000 and 9999999999.
9556	For Seamless Parallel Run processing, at least one QualificationReportDetailCreateRequest ContainerInfoData block must have a ContainerType of L or M when the LogicalPhysicalIndicator in the OpenMailingGroupRequest is L - Logical and the MailXMLPresentationCategory within the OpenMailingGroupRequest is populated with P - Conventional Presort.
9557	There are no remaining Credits for the Earned Value incentive, incentive was not applied.
9558	For Seamless processing, the MailPieceCreateRequest message, IMb block field values must sum to a total of 31 digits.
9559	For Seamless Parallel processing, the MailPieceCreateRequest message, IMb block field values must sum to a total of 31 digits for pieces claiming Full Service.
9561	The MailCharacteristic field provided was {1}. The MailerID6, MailerID9, or the CRID field within the QualificationReportPreparer block of the QualificationSummaryReportCreateRequest must be populated with a valid value when an incentive is claimed. The discount will not be applied.
9565	The MailCharacteristic provided was {1}. The incentive claimed is not the exclusive incentive. The discount will not be applied.
9566	A postage statement contains mail piece units without Intelligent Mail Barcode (IMb). The postage statement must contain mail piece units that all contain the IMb. The {1} incentive will not be applied.
9568	For FormType {1}, the IMB block or IMPackageBarcode block within the MailPieceCreateRequest or MailPieceUpdateRequest must be populated.
9579	For FormType {1}, the 11-digit ZIP must be provided through the IMB block within the MailPieceCreateRequest or MailPieceUpdateRequest.
9570	The STID portion of the IMB populated in the ServiceTypeCode field of the IMB block in the MailPieceCreateRequest or MailPieceUpdateRequest must match the FormType provided in the QualificationReportSummaryCreateRequest message.
9571	The STC portion of the IMPackageBarcode populated in the ServiceTypeCode field of the IMPackageBarcode block in the MailPieceCreateRequest or MailPieceUpdateRequest must match the FormType provided in the QualificationReportSummaryCreateRequest message.
9572	The MID6 and SerialNumber9 or MID9 and SerialNumber6 provided in the IMB block must be unique within a Mailing Group.
9573	The mailing is not a defined Package Type. The IMPackageBarcode block may not be submitted.
9576	The combination of MID9 and SerialNumber7or11 and or MID6 and SerialNumber10or14 provided in the IMPackageBarcode block must be unique within a Mailing Group.
9569	For FormType {1}, the 11-digit ZIP must be provided through the IMB block within the MailPieceCreateRequest or MailPieceUpdateRequest.
9593	For Seamless Parallel Run processing, the QualificationReportDetailCreateRequest, ContainerInfoData, eInductionIndicator must be populated with Yes.
9603	A SummaryZipDestinationReportCreateRequest message is required for Postage Statement Finalization, when logical containers are submitted, within a mailing.
9604	A SummaryZipDestinationReportCreateRequest message is required for Periodical Statement Finalization, when logical containers are submitted, within a mailing.

Copyright © 2014 USPS®. All Rights Reserved

Code	Warning Message
9605	A SummaryZipDestinationReportCreateRequest message is required for Consolidated Periodical Statement Finalization, when logical containers are submitted, within a mailing.

Copyright © 2014 USPS®. All Rights Reserved

9. Change History Archive

eDoc-13.0B-R16 Edition 1 Change 2 January 2014

Date	Section	Title	Description
9/26/2013	2.4, 2.5	Error Codes and Messages Warning Codes and Messages	Added/modified error codes for Release 37
10/23/2013	2.8.1	Postage Statement By/For Information	Added section on by/for processing
11/6/2013	2.5	WSDLS and XSDs	Moved from Section 8 to 2.5
11/6/2013	9	Error Codes	Moved to bottom of document
11/7/2013	3.9, 3.40, 3.46,	Consolidated, Periodical, Postage Statement Create Request	Removed Container Postage as a method for required container information as ContainerID, and ContainerDetailID are validated in LineItemData blocks.

eDoc-13.0B-R15 Edition 3 Change 1

Date	Section	Title	Description
8/28/2013	1.17	Incentives	Added Hyperlink to Promotions and Incentives page
8/28/2013	5	SimpleTypes	Alphabetized SimpleTypes onePassorTwoPassType uspsPackageUniqueCharacterisitcType StandardFlatType MarketingorFulfillmentType MLOCRRateType DMLType retrieveDataBy MID6 MID9 MPSQueryType MailPieceScanAvaliabilityDate MailPieceScanRecordCount ScanState LowerDateRange UpperDateRange MPSStateType
8/28/2013	2.4, 2.5	Error Codes and Messages/ Warning Codes and Messages	Added 13.0B error codes and warnings 9309, 9593
8/29/2013	3.34.1	MailPieceCreateRequest	Updated LargeTransactionDividerGroupType from Required to Not Currently Supported

eDoc-13.0B-R16 Edition 1 Change 1

Date	Section	Title	Description
8/6/2013	N/A	Release Version Support	Added Release 35 and 37
8/6/2013	1.6	Roadmap of Mail.XML	Deleted Release 33 and 34
8/6/2013	1.1	Program Overview	Updated hyperlink to 2014
8/7/2013	5	Mail.XML 13.0B Simple Type Data Structure	Deleted Highlighted column explanation
8/6/2013	All	Entire Document	Derived from eDoc-13.0B-R16 ed1 chg 0

Copyright © 2014 USPS®. All Rights Reserved

8/19/2013	4.117	complexType: PeriodicalLineItemData	Added ContainerDetailID, Container ID rows
8/19/2013	4.124	complexType: PostageStatementLineItemData	Added ContainerDetailID, ContainerID, and VersionID rows
8/19/2013	3.9	ConsolidatedPeriodicalStatementCreateRequest	Updated bullets to reflect detail surrounding ContainerDetailID
8/19/2013	3.40	PeriodicalStatementCreateRequest	Updated bullets to reflect detail surrounding ContainerDetailID
8/19/2013	3.46	PostageStatementCreateRequest	Updated bullets to reflect detail surrounding ContainerDetailID

eDoc-13.0B-R16 Edition 1 Change 0

Date	Section	Title	Description
07/18/2013	1.9	About This Document	Updated Internal references and hyperlinks
07/15/2013	All	Entire Document	Derived from eDoc-13.0B-R15 ed.3 Chg 0

eDoc-13.0B-R15 Edition 2 Change 1

Date	Section	Title	Description
06/20/2013	4.136	qualificationReportSummaryDataType	Changed CustomerQualificationReportID to a Required field and added requirement description to Comments
06/20/2013	3.9, 3.40 and 3.46	ConsolidatedPeriodicalStatementCreateRequest PeriodicalStatementCreateRequest PostageStatementCreateRequest	Removed reference to Mobile Barcode promotions
06/20/2013	5.24	characteristicIncentiveType	Removed duplicates and added PP
06/13/2013	3.34.1 & 3.36.1	MailPieceCreateRequest & MailpieceUpdateRequest	Added “Block not supported” to PDRRangePieceBlock & MailXMLPieceRangeBlock
06/13/2013	2.4	Error Codes and Messages	Added Error Code 09550
06/11/2013	All	EntireDocument	Corrected IT Comment and Action Items
06/10/2013	3.46,5.111 & 5.237	Delivery Confirmation Name Change	Changed DeliveryConfirmation to USPS Tracking
06/04/2013	All	Entire Document	Changed file name to the format: eDoc-12.0A-R15 Ed** Chg**

eDocMail.XML 13.0B for R15 (October 2013) Edition 2 Change 0: published for review 06/04/2013

Date	Section	Title	Description
05/24/2013	2.4	Error Codes/Return Values	Removed error codes 8739 and 8740

eDocMail.XML 13.0B for R15 (October 2013) Edition 1 Change 1: published for review 05/20/2013

Date	Section	Title	Description
05/17/2013	All	Internal Review	Changed listed format and style corrections.
05/17/2013	6.15.2 & 6.15.3	Support Mailer SubmitterTrackingID on MailXML 13.0B Messages	Added new sample WDSLs
05/17/2013	All	Error codes	Corrected references from section 2.6 to section 2.4

Copyright © 2014 USPS®. All Rights Reserved

eDocMail.XML 13.0B for R15 (October 2013) Edition 1 Change 0: published for review 05/16/2013

Date	Section	Title	Description
05/13/2013	All	Entire Document	This document was derived from Mail.XML 13.0B eDoc Version 2.0

These are the changes from Mail.XML 13.0B eDoc Version 1.0 to Mail.XML 13.0B eDoc Version 2.0

Date	Section	Title	Description
3/4/2013			Updated document frontpage
3/4/2013	4.47	LineItemData table	Moved StandardAddressType to correct location in LineItemData table
3/4/2013		Table of Contents	Modified 1.1.2
3/4/2013	4.21, 4.78	fullContainerIDType Table	Updated to Optional
3/7/2013	5.19	chargeableContainerType	Added Airbox enumeration
3/20/2013	All	All sections	Incorporated changes from IT review feedback, July 2013 2nd version

These are the changes from Mail.XML 13.0A eDoc Version 4.0 to Mail.XML 13.0B eDoc Version 1.0

Date	Section	Title	Description
2/14/2013	Sec 1.6	Roadmap Table	Revised roadmap table to reflect correct dates and their corresponding release numbers
1/5/13	5.242	Fault element in Mail XML xsd definition	Add simplifiedAddressType with types M = Mixed; R = Residential-only; B = Business-only
1/5/13	4.131	SimpleType: SimplifiedAddressType table	Update PTpostagePricesType change the SimplifiedAddress from Yes/No to simplifiedAddressType
1/5/13	4.84	ComplexType: LineItemSummaryData table	Update LineItemSummaryData change the SimplifiedAddress from Yes/No to simplifiedAddressType
1/5/13	4.84	ComplexType: PostageStatementLineItemData	Update PostageStatementLineItemData change the SimplifiedAddress from Yes/No to simplifiedAddressType
1/5/13	5.19	ChargeableContainerType in Mail.XML xsd	Update ChargeableContainerType to add Airbox
1/5/13	3.22.1	ContainerStatusQueryRequest Table	Add Y/N eInduction Indicator to ContainerStatusQueryRequest/Response
1/5/13	5.149	PostageAutoFinalization Addition	Add postageAutoFinalization
1/5/13	4.1	ComplexType : AbstractStatement DataType table	Update abstractPostageStatementDataType
1/5/13			Will Update abstractPeriodicalsStatementDataType

Copyright © 2014 USPS®. All Rights Reserved

INDEX

A

ACS 5, 258, 276, 277
asynchronous 1, 15, 125

B

BeginCombinedMailingRequest 5, 6, 7, 9, 11, 12, 13, 24, 25, 89, 90
BeginCombinedMailingResponse 11, 12, 13, 24
bundle reports 1
BundleBarcode 136
BundleCarrierRoute 135
BundleDetail 27, 28
BundleDetailCancelRequest 6, 7, 8, 9, 26, 27
BundleDetailCancelResponse 27, 28
BundleDetailCreateRequest 5, 6, 7, 8, 9, 26, 28, 29, 63
BundleDetailCreateResponse 26, 29, 30
BundleID 26, 27, 28, 135, 173
BundleLevel 136
bundles 13, 38
BundleStatus 136
BundleZIP 135

C

cancelled 26, 37, 52, 53, 80, 262
Cast of Characters 1
CloseMailingGroupRequest 5, 6, 8, 9, 30
CloseMailingGroupResponse 30
combined mailing 23
CombinedMailingID 11, 12, 13, 25, 57, 118, 161, 197, 205
ConsolidatedPeriodicalStatementCreateRequest 23, 25, 31, 56, 57
ConsolidatedPeriodicalStatementCreateResponse 35
container.... 1, 13, 15, 32, 34, 36, 37, 38, 42, 48, 49, 50, 51, 52, 53, 59, 63, 64, 68, 71, 74, 82, 116, 120, 123, 132, 140, 143, 160, 165, 166, 203, 219
ContainerBundleReportCancelRequest 7, 9, 36
ContainerBundleReportCancelResponse 37
ContainerBundleReportCreateRequest . 6, 7, 10, 11, 13, 31, 36, 38, 40, 41, 42, 73
ContainerBundleReportCreateRequest, , ... 6
ContainerBundleReportCreateResponse 10, 11, 13, 37, 40, 41, 42
ContainerBundleReportQueryRequest 6, 9, 41, 44, 45, 46
ContainerID 26, 27, 28, 48, 49, 50, 108, 109, 111, 112, 120, 123, 124, 135, 142, 146, 166, 173, 179, 182, 207
ContainerPostage 32, 74, 82, 119, 206
ContainerStatusQueryRequest 48, 292
ContainerStatusQueryResponse 49, 292
ContainerUpdateRequest 5, 6, 8, 9, 50
copalletization 1, 13
Copalletized 12
Customer Group ID 179
CustomerGroupID . 9, 10, 11, 12, 26, 28, 30, 36, 38, 40, 41, 42, 48, 54, 59, 62, 63, 64, 65, 66, 67, 70, 97, 124, 125, 132, 179, 183, 184, 185
customers 1, 4, 15, 50, 71

D

DestinationEntry 135
DestinationZIP 136
DMM 13
duplicate 13

E

eDoc 2, 4, 7, 8, 15, 23, 30, 71, 126, 292
eDropShip 1, 15, 48, 49
EndCombinedMailingRequest 5, 6, 7, 9, 11, 12, 13, 55

F

flats 13
Full-Service . 2, 4, 5, 7, 8, 9, 10, 12, 13, 53, 61, 63, 66, 82, 119, 133, 134, 140, 142, 143, 144, 147, 173, 181, 182, 210, 219, 221, 222, 223, 250, 282, 292
Full-Service mailing 7

I

IDEAlliance 1, 4
irregular 13

M

machinable 13, 241, 286
Mail.dat 1, 4, 12, 15, 50, 51, 52, 120, 123, 165, 166, 292
Mail.XML 1, 2, 3, 4, 5, 12, 13, 15, 16, 23, 30, 41, 50, 51, 58, 101, 228, 229, 230, 231, 232, 233, 234, 235, 237, 251, 292, 300
Maildat Job ID 179
MaildatJobID 26, 48, 59, 60, 65, 68, 120, 123, 165
mailing... 1, 4, 7, 8, 9, 12, 13, 23, 24, 28, 30, 31, 34, 35, 36, 37, 38, 41, 53, 54, 55, 57, 58, 59, 63, 64, 67, 71, 72, 73, 80, 81, 84, 86, 88, 96, 98, 99, 135, 197, 198, 209, 292, 293
Mailing Group ID 179
MailingGroupID 9, 10, 11, 12, 26, 28, 30, 36, 38, 40, 41, 42, 48, 54, 58, 59, 62, 63, 64, 65, 66, 67, 70, 73, 97, 120, 124, 125, 132, 165, 179, 183, 184, 185
MailingGroupQueryRequest 5, 6, 8, 9, 58, 292
MailingGroupQueryResponse 58, 292
mailpiece 59, 62, 63, 66, 67, 70, 71
MailPieceCancelRequest 6, 7, 8, 9, 59, 63
MailPieceCreateRequest .. 5, 6, 7, 9, 10, 11, 32, 63, 64, 67, 74, 82
MailXMLMailGroupRequestHeaderInfo Block Opens 58
manifest 1
mixed service 5, 6, 8, 32, 64, 73, 74, 82, 206
Mixed Service.. 5, 13, 50, 61, 66, 133, 134, 140, 143, 144, 147, 173, 182, 219, 221, 222, 223
MLOCR 1, 13, 53, 55, 96, 98, 255, 256, 276
MLOCRrateANDpostageMarking 175
mother containers 13

O

OpenMailingGroupRequest. 5, 6, 7, 8, 9, 10, 11, 12, 31, 71, 72, 73, 142, 147, 184, 185
OriginalContainerLinkageCancelRequest 6, 7, 8, 9
OriginalContainerLinkageCreate 5, 6, 7, 8, 9

P

Package Services 5, 7, 241, 254, 292
Pallets 12, 106, 130, 138, 240, 241
parcels 13

Copyright © 2014 USPS®. All Rights Reserved

ParentBundleID 136
Periodicals6, 8, 9, 10, 11, 12, 13, 31, 34, 41, 73, 77, 79, 82, 84, 88, 119, 136, 161, 162, 197, 198, 205, 241, 248, 250, 254, 262, 272, 292, 293, 294, 295
PeriodicalStatementCreateRequest 6, 7, 8, 9, 10, 11, 12, 13, 23, 25, 31, 55, 57, 73, 76, 77, 78, 82, 294
PeriodicalStatementQueryRequest 7, 9, 77, 79
piece detail 1
piece ranging 1
PieceID 175
pieces .. 1, 7, 8, 9, 12, 13, 26, 27, 32, 63, 64, 74, 81, 82, 84, 96, 113, 140, 157, 158, 195, 200, 201, 290
PlanetCode 61, 174
postage.. 1, 5, 11, 12, 13, 23, 31, 32, 34, 35, 50, 53, 55, 57, 59, 63, 67, 70, 71, 73, 74, 76, 77, 78, 79, 80, 81, 82, 84, 86, 87, 88, 96, 114, 116, 118, 159, 161, 169, 195, 196, 197, 198, 201, 203, 204, 205, 210, 290, 292, 293, 294, 296
Postage . 2, 13, 37, 52, 53, 62, 63, 76, 77, 81, 82, 85, 115, 119, 147, 159, 162, 195, 202, 206, 217, 218, 237, 254, 265, 292, 293
postage adjustments 1
postage statements . 1, 5, 11, 12, 13, 31, 34, 55, 57, 71, 80, 81, 88, 96, 116, 161, 203, 204, 292, 293
Postage Statements 13
postage status 1
PostageAdjustmentCreateRequest 5, 6, 8, 9
PostageStatementCancelRequest 6, 7, 8, 9, 79
PostageStatementCreateRequest ... 5, 6, 7, 8, 9, 10, 11, 12, 23, 25, 55, 57, 81, 82, 85, 296
PostageStatementQueryRequest 5, 8
PostageStatementStatusQueryRequest 5, 7, 8, 9, 86, 87
PostalOne!... 1, 4, 15, 16, 26, 27, 28, 29, 30, 38, 50, 51, 52, 57, 58, 80, 81, 96, 98, 99, 112, 116, 119, 122, 134, 146, 160, 196, 197, 198, 203
protocol 1

Q

qualification 1, 15, 26, 28, 32, 71, 74, 82, 99, 142
Qualification. 13, 30, 92, 98, 133, 136, 142, 143, 144, 219, 221, 229
qualification reports 1, 15
QualificationReportDetailCreateRequest 5, 6, 7, 8, 9, 10, 11, 12, 28, 31, 32, 38, 40, 51, 53, 54, 63, 64, 66, 73, 74, 82, 173, 182, 294, 296

R

ReconciliationReportQueryRequest 6, 7, 8, 9, 98, 292
ReturnInfo 25, 27, 28, 29, 30, 31, 35, 36, 37, 38, 41, 44, 47, 52, 53, 55, 57, 58, 59, 63, 66, 67, 71, 72, 73, 76, 77, 78, 79, 80, 81, 84, 85, 87, 88, 89, 98, 100, 128, 226

S

SASP 32, 74, 82
Services Oriented Architecture ....*See* SOA
Sibling Container ID 13
SiblingContainerCancelRequest 6, 7, 8, 9
SiblingContainerCreateRequest 5, 6, 7, 8, 9
SOA 1
SOAP 311
SortationLevel 97, 136, 144, 235
spoilage 1
Standard Mail .. 5, 7, 12, 13, 241, 248, 250, 254, 274, 292, 293, 296, 297
SubmittingParty4, 24, 26, 28, 30, 33, 37, 38, 41, 44, 46, 47, 48, 52, 54, 56, 58, 60, 65, 68, 72, 75, 78, 80, 83, 86, 88, 97, 99, 126, 198, 300
SubmittingSoftware ... 24, 26, 28, 30, 33, 37, 38, 41, 44, 46, 47, 48, 52, 54, 56, 58, 60, 65, 68, 72, 75, 78, 80, 84, 86, 88, 97, 99
supplement 4, 15
supply chain 1
synchronous 1

T

technology 1, 15
Test Environment for Mailers Checklist and Troubleshooting Guide 4
threshold 7
TotalCopies 135, 147, 164, 198
TotalPieces . 116, 117, 135, 147, 164, 165, 171, 198, 204, 210, 218
Tracking ID 15, 40, 41, 100, 300
Tray Barcodes 13
Trays 12, 143, 240

U

United States Postal Service 1
UPD 31, 37, 52, 53, 62, 265, 293
User License Code 179
UserLicenseCode 26, 59, 60, 65, 68, 120, 123, 165
USPS 1, 4, 5, 8, 9, 12, 13, 15, 16, 24, 27, 29, 30, 31, 37, 47, 48, 50, 52, 57, 58, 62, 70, 71, 72, 73, 76, 77, 79, 81, 84, 85, 96, 98, 99, 100, 124, 131, 140, 142, 175, 286, 292, 293, 300, 311

V

VersionID 28, 118, 136, 147, 163, 205, 210
VersionName 118, 136, 163, 205
volumes 2

W

web services 1, 15, 16
Web services ....See web services
Wizard Web Services ....*See* WWS
WSDL 16
WWS 15

Z

Zone 135, 147, 172, 210, 291

Copyright © 2014 USPS®. All Rights Reserved